

Namespace GoogleMapsWrapper.Api

Classes

[GeocodeApi](#)

Provides methods for retrieving data from Google's Geocoding API.

[GoogleMapsApi](#)

The entry point of the wrapper. Exposes API objects to interact with the endpoint:

[GeocodeApi](#)

[StaticMapsApi](#)

[StaticMapCustomIcon](#)

An object that represents a custom icon for a marker. The source must be a Uri of an image.

[StaticMapsApi](#)

Provides methods for retrieving a static image of a map from Google's Static API. This object leverages an [IApiEngine](#) to send [IRequests](#) and return data in form of [IResponse<TResponse>](#)s.

Class GeocodeApi

Namespace: [GoogleMapsWrapper.Api](#)

Assembly: GoogleMapsWrapper.dll

Provides methods for retrieving data from Google's Geocoding API.

```
public class GeocodeApi
```

Inheritance

[object](#) ← GeocodeApi

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

GeocodeApi(IApiEngine)

Initializes a new instance of the [GeocodeApi](#) class.

```
public GeocodeApi(IApiEngine engine)
```

Parameters

engine [IApiEngine](#)

An instance of the API engine.

Properties

ApiType

```
public ApiTypes ApiType { get; }
```

Property Value

[ApiTypes](#)

Methods

GeocodeAsync(GpsCoordinate, string?)

Makes a request to the API endpoint for geocoding a lat/lng coordinate./>

```
public Task<IResponse<JsonDocument>> GeocodeAsync(GpsCoordinate coordinate, string?  
identifier = null)
```

Parameters

coordinate [GpsCoordinate](#)

GpsCoordinate to target the request.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[IResponse](#)<[JsonDocument](#)>>

An [IResponse<TResponse>](#) containing the raw JSON response from the Google API.

GeocodeAsync(string, string, string?)

Makes a request to the API endpoint for geocoding a lat/lng coordinate./>

```
public Task<IResponse<JsonDocument>> GeocodeAsync(string latitude, string longitude, string?  
identifier = null)
```

Parameters

latitude [string](#)

Decimal degrees gps latitude.

longitude [string](#)

Decimal degrees gps longitude.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[IResponse](#)<[JsonDocument](#)>>

An [IResponse<TResponse>](#) containing the raw JSON response from the Google API.

GeocodeParseAsync(GpsCoordinate, string?)

Makes a request to the API endpoint for geocoding a lat/lng coordinate./>

```
public Task<GeocodeContainer> GeocodeParseAsync(GpsCoordinate coordinate, string? identifier = null)
```

Parameters

coordinate [GpsCoordinate](#)

GpsCoordinate to target the request.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[GeocodeContainer](#)>

A [GeocodeContainer](#) holding data parsed from [GeocodeParser](#).

GeocodeParseAsync(string, string, string?)

Makes a request to the API endpoint for geocoding a lat/lng coordinate./>

```
public Task<GeocodeContainer> GeocodeParseAsync(string latitude, string longitude, string?  
identifier = null)
```

Parameters

latitude [string](#)

Decimal degrees gps latitude.

longitude [string](#)

Decimal degrees gps longitude.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[GeocodeContainer](#)>

A [GeocodeContainer](#) holding data parsed from [GeocodeParser](#).

GetElevationAsync(GpsCoordinate, string?)

Makes a request to the API endpoint for acquiring elevation data about a lat/lng coordinate./>

```
public Task<IResponse<JsonDocument>> GetElevationAsync(GpsCoordinate coordinate, string?  
identifier = null)
```

Parameters

coordinate [GpsCoordinate](#)

GpsCoordinate to target the request about.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[IResponse](#)<[JsonDocument](#)>>

An [IResponse<TResponse>](#) containing the raw JSON response from the Google API.

GetElevationAsync(string, string, string?)

Makes a request to the API endpoint for acquiring elevation data about a lat/lng coordinate./>

```
public Task<IResponse<JsonDocument>> GetElevationAsync(string latitude, string longitude,  
string? identifier = null)
```

Parameters

latitude [string](#)

Decimal degrees gps latitude.

longitude [string](#)

Decimal degrees gps longitude.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[IResponse](#)<[JsonDocument](#)>>

An [IResponse<TResponse>](#) containing the raw JSON response from the Google API.

GetElevationParsedAsync(GpsCoordinate, string?)

Makes a request to the API endpoint for acquiring elevation data about a lat/lng coordinate./>

```
public Task<ElevationContainer> GetElevationParsedAsync(GpsCoordinate coordinate, string?  
identifier = null)
```

Parameters

coordinate [GpsCoordinate](#)

GpsCoordinate to target the request about.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#) <[ElevationContainer](#)>

An [ElevationContainer](#) holding data parsed from [ElevationParser](#).

GetElevationParsedAsync(string, string, string?)

Makes a request to the API endpoint for acquiring elevation data about a lat/lng coordinate./>

```
public Task<ElevationContainer> GetElevationParsedAsync(string latitude, string longitude,  
string? identifier = null)
```

Parameters

latitude [string](#)

Decimal degrees gps latitude.

longitude [string](#)

Decimal degrees gps longitude.

identifier [string](#)

A string appended to the request for tracking or identification.

Returns

[Task](#) <[ElevationContainer](#)>

An [ElevationContainer](#) holding data parsed from [ElevationParser](#).

Class GoogleMapsApi

Namespace: [GoogleMapsWrapper.Api](#)

Assembly: GoogleMapsWrapper.dll

The entry point of the wrapper. Exposes API objects to interact with the endpoint:

[GeocodeApi](#)

[StaticMapsApi](#)

```
public class GoogleMapsApi
```

Inheritance

[object](#) ← GoogleMapsApi

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

GoogleMapsApi(HttpClient, IConfiguration)

Initializes a new instance of the class, using the provided [HttpClient](#) and configuration settings.

```
public GoogleMapsApi(HttpClient httpClient, IConfiguration config)
```

Parameters

httpClient [HttpClient](#)

An [HttpClient](#) to be used to process web requests.

config [IConfiguration](#)

An [IConfiguration](#) which contains the API key.

Properties

GeocodeApi

An instance of the GeocodeApi.//

```
public GeocodeApi GeocodeApi { get; }
```

Property Value

[GeocodeApi](#)

StaticMapsApi

An instance of the StaticMapsApi.///

```
public StaticMapsApi StaticMapsApi { get; }
```

Property Value

[StaticMapsApi](#)

Class StaticMapCustomIcon

Namespace: [GoogleMapsWrapper.Api](#)

Assembly: GoogleMapsWrapper.dll

An object that represents a custom icon for a marker. The source must be a Uri of an image.

```
public record StaticMapCustomIcon : IEquatable<StaticMapCustomIcon>
```

Inheritance

[object](#) ← StaticMapCustomIcon

Implements

[IEquatable](#) <[StaticMapCustomIcon](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

StaticMapCustomIcon(string, MarkerIconAnchorTypes)

```
public StaticMapCustomIcon(string uri, MarkerIconAnchorTypes anchorType  
= MarkerIconAnchorTypes.Center)
```

Parameters

uri [string](#)

anchorType [MarkerIconAnchorTypes](#)

StaticMapCustomIcon(Uri, MarkerIconAnchorTypes)

An object that represents a custom icon for a marker. The source must be a Uri of an image.

```
public StaticMapCustomIcon(Uri Uri, MarkerIconAnchorTypes AnchorType  
= MarkerIconAnchorTypes.Center)
```

Parameters

Uri [Uri↗](#)

AnchorType [MarkerIconAnchorTypes](#)

Properties

AnchorType

```
public MarkerIconAnchorTypes AnchorType { get; init; }
```

Property Value

[MarkerIconAnchorTypes](#)

Uri

```
public Uri Uri { get; init; }
```

Property Value

[Uri↗](#)

Class StaticMapsApi

Namespace: [GoogleMapsWrapper.Api](#)

Assembly: GoogleMapsWrapper.dll

Provides methods for retrieving a static image of a map from Google's Static API. This object leverages an [IApiEngine](#) to send [IRequests](#) and return data in form of [IResponse<TResponse>](#)s.

```
public class StaticMapsApi
```

Inheritance

[object](#) ← StaticMapsApi

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

StaticMapsApi(IApiEngine)

Initializes a new instance of the StaticMapsAPI.

```
public StaticMapsApi(IApiEngine engine)
```

Parameters

engine [IApiEngine](#)

An [IApiEngine](#) to process API requests and responses./>

Methods

GetMapAsync(Map, IEnumerable<Marker>?, IEnumerable<Polyline>?, string?)

Makes a request to the API endpoint for a static map image.

```
public Task<IResponse<byte[]>> GetMapAsync(Map mapSettings, IEnumerable<Marker>? markers = null, IEnumerable<Polyline>? paths = null, string? identifier = null)
```

Parameters

mapSettings [Map](#)

A [Map](#) element that defines key features about the map.>

markers [IEnumerable](#)<[Marker](#)>

Optional. [Markers](#) to be included in the map.

paths [IEnumerable](#)<[Polyline](#)>

Optional. [Polylines](#) to be included in the map.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task](#)<[IResponse](#)<[byte](#)[]>>

An [IResponse](#) containing the raw byte[] response from the Google API.

GetMapBytesAsync(Map, IEnumerable<Marker>?, IEnumerable<Polyline>?, string?)

Makes a request to the API endpoint for a static map image.

```
public Task<byte[]?> GetMapBytesAsync(Map mapSettings, IEnumerable<Marker>? markers = null, IEnumerable<Polyline>? paths = null, string? identifier = null)
```

Parameters

mapSettings [Map](#)

A [Map](#) element that defines key features about the map.>

markers [IEnumerable<Marker>](#)

Optional. [Markers](#) to be included in the map.

paths [IEnumerable<Polyline>](#)

Optional. [Polylines](#) to be included in the map.

identifier [string](#)

A string appended to the request object for tracking or identification.

Returns

[Task<byte\[\]>](#)

A [byte](#) array containing the raw byte[] data of the image.

Namespace GoogleMapsWrapper.Containers

Classes

[ElevationContainer](#)

A object to hold parsed JSON data from Elevation API responses.

[GeocodeContainer](#)

A container to hold parsed JSON information from a GoecodeAPI response.

Interfaces

[IContainer](#)

Describes a container object used to hold parsed data from an API response.

Class ElevationContainer

Namespace: [GoogleMapsWrapper.Containers](#)

Assembly: GoogleMapsWrapper.dll

A object to hold parsed JSON data from Elevation API responses.

```
public record ElevationContainer :.IContainer, IEquatable<ElevationContainer>
```

Inheritance

[object](#) ← ElevationContainer

Implements

[.IContainer](#), [IEquatable](#)<[ElevationContainer](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ElevationContainer(double, double, double, GpsCoordinate?, object?)

A object to hold parsed JSON data from Elevation API responses.

```
public ElevationContainer(double ElevationMeters, double Resolution, double ElevationFeet,  
GpsCoordinate? Coordinates, object? AssociatedData)
```

Parameters

ElevationMeters [double](#)

The elevation in meters.

Resolution [double](#)

Indicates the maximum distance between data points from which the elevation was interpolated, in meters. This property is acquired from the JSON response's 'administrative_area_level_1' property.

ElevationFeet [double](#)

The elevation in feet. This property is mathematically converted and not intrinsic to the API.

Coordinates [GpsCoordinate?](#)

The GPS coordinate for the request.

AssociatedData [object](#)

Associated information about the data or it's source. This contains the IResponse.

Properties

AssociatedData

Associated information about the data or it's source. This contains the IResponse.

```
public object? AssociatedData { get; init; }
```

Property Value

[object](#)

Coordinates

The GPS coordinate for the request.

```
public GpsCoordinate? Coordinates { get; init; }
```

Property Value

[GpsCoordinate?](#)

ElevationFeet

The elevation in feet. This property is mathematically converted and not intrinsic to the API.

```
public double ElevationFeet { get; init; }
```

Property Value

[double](#) ↗

ElevationMeters

The elevation in meters.

```
public double ElevationMeters { get; init; }
```

Property Value

[double](#) ↗

Resolution

Indicates the maximum distance between data points from which the elevation was interpolated, in meters. This property is acquired from the JSON response's 'administrative_area_level_1' property.

```
public double Resolution { get; init; }
```

Property Value

[double](#) ↗

Class GeocodeContainer

Namespace: [GoogleMapsWrapper.Containers](#)

Assembly: GoogleMapsWrapper.dll

A container to hold parsed JSON information from a GoecodeAPI response.

```
public record GeocodeContainer :.IContainer, IEquatable<GeocodeContainer>
```

Inheritance

[object](#) ← GeocodeContainer

Implements

[.IContainer](#), [IEquatable](#)<[GeocodeContainer](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

GeocodeContainer(string, string, string, string, string, int, string, GpsCoordinate?, object?)

A container to hold parsed JSON information from a GoecodeAPI response.

```
public GeocodeContainer(string Country, string State, string County, string City,  
string Municipality, int ZipCode, string Address, GpsCoordinate? Coordinates,  
object? AssociatedData)
```

Parameters

Country [string](#)

This property is acquired from the JSON response's 'country' property.

State [string](#)

This property is acquired from the JSON response's 'administrative_area_level_1' property.

County [string](#)

This property is acquired from the JSON response's 'administrative_area_level_2' property.

City [string](#)

This property is acquired from the JSON response's 'locality' property.

Municipality [string](#)

This property is acquired from the JSON response's 'administrative_area_level_3' property.

ZipCode [int](#)

This property is acquired from the JSON response's 'postal_code' property.

Address [string](#)

This property is acquired from the JSON response's 'formatted_address' property.

Coordinates [GpsCoordinate](#)?

The GPS coordinate for the request.

AssociatedData [object](#)

Associated information about the data or it's source. This contains the IResponse.

Properties

Address

This property is acquired from the JSON response's 'formatted_address' property.

```
public string Address { get; init; }
```

Property Value

[string](#)

AssociatedData

Associated information about the data or it's source. This contains the IResponse.

```
public object? AssociatedData { get; init; }
```

Property Value

[object](#)

City

This property is acquired from the JSON response's 'locality' property.

```
public string City { get; init; }
```

Property Value

[string](#)

Coordinates

The GPS coordinate for the request.

```
public GpsCoordinate? Coordinates { get; init; }
```

Property Value

[GpsCoordinate?](#)

Country

This property is acquired from the JSON response's 'country' property.

```
public string Country { get; init; }
```

Property Value

[string](#)

County

This property is acquired from the JSON response's 'administrative_area_level_2' property.

```
public string County { get; init; }
```

Property Value

[string](#)

Municipality

This property is acquired from the JSON response's 'administrative_area_level_3' property.

```
public string Municipality { get; init; }
```

Property Value

[string](#)

State

This property is acquired from the JSON response's 'administrative_area_level_1' property.

```
public string State { get; init; }
```

Property Value

[string](#)

ZipCode

This property is acquired from the JSON response's 'postal_code' property.

```
public int ZipCode { get; init; }
```

Property Value

[int](#)

Methods

ToString()

Converts to string.

```
public override string ToString()
```

Returns

[string](#)

A [string](#) that represents this instance.

Interface IContainer

Namespace: [GoogleMapsWrapper.Containers](#)

Assembly: GoogleMapsWrapper.dll

Describes a container object used to hold parsed data from an API response.

```
public interface IContainer
```

Properties

AssociatedData

A property to append data to the container.

```
object? AssociatedData { get; }
```

Property Value

[object](#)

Namespace GoogleMapsWrapper.Elements

Classes

[GoogleMapElement](#)

An abstract base class that contains properties from which map elements derive. A GoogleMapElement can be defined as a geolocational data type, such as a Map, Marker, or Polyline that is leveraged by the wrapper.

[Map](#)

Defines a 'map' object and it's characteristics. It is primarily used as a parameter for methods within the StaticMapsApi.

[Marker](#)

Defines a 'marker' (placemark) object and it's characteristics.

[Polyline](#)

Class GoogleMapElement

Namespace: [GoogleMapsWrapper.Elements](#)

Assembly: GoogleMapsWrapper.dll

An abstract base class that contains properties from which map elements derive. A GoogleMapElement can be defined as a geolocation data type, such as a Map, Marker, or Polyline that is leveraged by the wrapper.

```
public abstract class GoogleMapElement
```

Inheritance

[object](#) ← GoogleMapElement

Derived

[Map](#), [Marker](#), [Polyline](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Properties

AssociatedData

```
public object? AssociatedData { get; set; }
```

Property Value

[object](#)

Color

```
public Color Color { get; set; }
```

Property Value

[Color](#)

Height

```
public int Height { get; set; }
```

Property Value

[int](#)

Id

```
public string? Id { get; set; }
```

Property Value

[string](#)

Name

```
public string? Name { get; set; }
```

Property Value

[string](#)

SecondaryColor

```
public Color SecondaryColor { get; set; }
```

Property Value

[Color](#)

Visible

```
public bool Visible { get; set; }
```

Property Value

[bool ↗](#)

Width

```
public int Width { get; set; }
```

Property Value

[int ↗](#)

Class Map

Namespace: [GoogleMapsWrapper.Elements](#)

Assembly: GoogleMapsWrapper.dll

Defines a 'map' object and it's characteristics. It is primarily used as a parameter for methods within the StaticMapsApi.

```
public class Map : GoogleMapElement
```

Inheritance

[object](#) ← [GoogleMapElement](#) ← Map

Inherited Members

[GoogleMapElement.Name](#) , [GoogleMapElement.Id](#) , [GoogleMapElement.AssociatedData](#) ,
[GoogleMapElement.Color](#) , [GoogleMapElement.SecondaryColor](#) , [GoogleMapElement.Visible](#) ,
[GoogleMapElement.Height](#) , [GoogleMapElement.Width](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Map(MapTypes, MapScaleTypes, GpsCoordinate?, string?, string?)

```
public Map(MapTypes MapType, MapScaleTypes Scale = MapScaleTypes.HighRes, GpsCoordinate?  
Center = null, string? Id = null, string? Name = null)
```

Parameters

MapType [MapTypes](#)

Scale [MapScaleTypes](#)

Center [GpsCoordinate?](#)

Id [string](#)

Name [string](#)

Properties

Center

The type or style of map to be rendered by the API.///

```
public GpsCoordinate? Center { get; set; }
```

Property Value

[GpsCoordinate?](#)

Dimensions

A string describing the size dimensions of the map. Format is: {Height}x{Width}

```
public string Dimensions { get; set; }
```

Property Value

[string](#)

ImageFormat

Desired file format for an image of the map.///

```
public MapImageFormats ImageFormat { get; set; }
```

Property Value

[MapImageFormats](#)

MapType

The type or style of map to be rendered by the API.///

```
public MapTypes MapType { get; set; }
```

Property Value

[MapTypes](#)

Scale

Scale type of the map.///

```
public MapScaleTypes Scale { get; set; }
```

Property Value

[MapScaleTypes](#)

Zoom

A zoom value for which the map should be displayed. Accepts values: 0 to 21, where zero (default) is considered 'ommitted'. If omitted from a StaticMapsApi request, the Google API determines a zoom that best fits the map.

```
public int Zoom { get; set; }
```

Property Value

[int↗](#)

Class Marker

Namespace: [GoogleMapsWrapper.Elements](#)

Assembly: GoogleMapsWrapper.dll

Defines a 'marker' (placemark) object and it's characteristics.

```
public class Marker : GoogleMapElement
```

Inheritance

[object](#) ← [GoogleMapElement](#) ← Marker

Inherited Members

[GoogleMapElement.Name](#) , [GoogleMapElement.Id](#) , [GoogleMapElement.AssociatedData](#) ,
[GoogleMapElement.Color](#) , [GoogleMapElement.SecondaryColor](#) , [GoogleMapElement.Visible](#) ,
[GoogleMapElement.Height](#) , [GoogleMapElement.Width](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

Marker(GpsCoordinate, string?, string?)

Constructs a new marker instance.

```
public Marker(GpsCoordinate Coordinate, string? Id = null, string? Name = null)
```

Parameters

Coordinate [GpsCoordinate](#)

Id [string](#)

Name [string](#)

Fields

Scale

Affects the scale of the marker graphic rendered on a static map.

```
public MarkerScaleTypes Scale
```

Field Value

[MarkerScaleTypes](#)

Size

Affects the scale of the marker graphic rendered on a static map.

```
public MarkerSizes Size
```

Field Value

[MarkerSizes](#)

Properties

Coordinate

The location of the marker.

```
public GpsCoordinate Coordinate { get; }
```

Property Value

[GpsCoordinate](#)

CustomIcon

A custom icon to represent the marker.

```
public StaticMapCustomIcon? CustomIcon { get; set; }
```

Property Value

[StaticMapCustomIcon](#)

Label

A label applied to the marker.

```
public char Label { get; set; }
```

Property Value

[char](#)

Remarks

Accepts values that are alpha-numerical, uppercase only. Single character.

Class Polyline

Namespace: [GoogleMapsWrapper.Elements](#)

Assembly: GoogleMapsWrapper.dll

```
public class Polyline : GoogleMapElement
```

Inheritance

[object](#) ← [GoogleMapElement](#) ← Polyline

Inherited Members

[GoogleMapElement.Name](#) , [GoogleMapElement.Id](#) , [GoogleMapElement.AssociatedData](#) ,
[GoogleMapElement.Color](#) , [GoogleMapElement.SecondaryColor](#) , [GoogleMapElement.Visible](#) ,
[GoogleMapElement.Height](#) , [GoogleMapElement.Width](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

Polyline(IList<GpsCoordinate>, string?, string?)

```
public Polyline(IList<GpsCoordinate> Coordinates, string? Id = null, string? Name = null)
```

Parameters

Coordinates [IList](#) <[GpsCoordinate](#)>

Id [string](#)

Name [string](#)

Properties

Coordinates

```
public IReadOnlyList<GpsCoordinate> Coordinates { get; }
```

Property Value

[IReadOnlyList](#)<[GpsCoordinate](#)>

Geodesic

`public bool Geodesic { get; set; }`

Property Value

[bool](#)

Label

`public char? Label { get; set; }`

Property Value

[char](#)?

Weight

`public int Weight { get; set; }`

Property Value

[int](#)

Methods

AddCoordinate(GpsCoordinate)

`public void AddCoordinate(GpsCoordinate coordinate)`

Parameters

coordinate [GpsCoordinate](#)

AddCoordinate(string)

```
public void AddCoordinate(string coordinate)
```

Parameters

coordinate [string](#)

InsertCoordinate(GpsCoordinate, int)

```
public void InsertCoordinate(GpsCoordinate coordinate, int index)
```

Parameters

coordinate [GpsCoordinate](#)

index [int](#)

IsEmpty()

Returns true if the object contains 2 or more coordinates.

```
public bool IsEmpty()
```

Returns

[bool](#)

Parse(string, string)

```
public static Polyline Parse(string input, string separator)
```

Parameters

input [string](#)

separator [string](#)

Returns

[Polyline](#)

RemoveCoordinate(GpsCoordinate)

```
public void RemoveCoordinate(GpsCoordinate coordinate)
```

Parameters

coordinate [GpsCoordinate](#)

RemoveCoordinate(int)

```
public void RemoveCoordinate(int index)
```

Parameters

index [int](#)

ToString()

Returns a string that represents the current object.

```
public override string ToString()
```

Returns

string ↴

A string that represents the current object.

Namespace GoogleMapsWrapper.Engine

Classes

[ApiEngine](#)

An implementation of [IApiEngine](#) to send [IRequest](#)s and return data in form of [IResponse<TResponse>](#)s.

[FlurlExtensions](#)

Interfaces

[IApiEngine](#)

Class ApiEngine

Namespace: [GoogleMapsWrapper.Engine](#)

Assembly: GoogleMapsWrapper.dll

An implementation of [IApiEngine](#) to send [IRequests](#) and return data in form of [IResponse<TResponse>](#)s.

```
public class ApiEngine : IApiEngine
```

Inheritance

[object](#) ← ApiEngine

Implements

[IApiEngine](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Remarks

This layer of the application operates closest to the endpoint by using [HttpClient](#) to send HTTPGet requests.

Constructors

ApiEngine(HttpClient, IConfiguration)

```
public ApiEngine(HttpClient httpClient, IConfiguration config)
```

Parameters

httpClient [HttpClient](#)

config [IConfiguration](#)

Properties

BaseUrl

```
public string BaseUrl { get; }
```

Property Value

[string](#)

Methods

GetBytesAsync(IRequest)

Make a GET request to the API endpoint and return a byte array response.

```
public Task<IResponse<byte[]>> GetBytesAsync(IRequest request)
```

Parameters

request [IRequest](#)

Returns

[Task](#)<[IResponse](#)<[byte](#)[]>>

GetJsonAsync(IRequest)

Make a GET request to the API endpoint and return a JSON response.

```
public Task<IResponse<JsonDocument>> GetJsonAsync(IRequest request)
```

Parameters

request [IRequest](#)

Returns

[Task](#)<[IResponse](#)<[JsonDocument](#)>>

See Also

[IApiEngine](#)

Class FlurlExtensions

Namespace: [GoogleMapsWrapper.Engine](#)

Assembly: GoogleMapsWrapper.dll

```
public static class FlurlExtensions
```

Inheritance

[object](#) ← FlurlExtensions

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

SetQueryParamWithDefault(Url, string, object?, object?, bool)

An extension method to flur url to SetQueryParam with a default value. If the value passed is null or an empty string, the default value is used. If the default value is null, Flurl.NullValueHandling.Remove is enacted.

```
public static Url SetQueryParamWithDefault(this Url url, string name, object? value, object?  
defaultValue, bool isEncoded = false)
```

Parameters

url Url

name [string](#)

value [object](#)

defaultValue [object](#)

isEncoded [bool](#)

Returns

Url

Interface IApiEngine

Namespace: [GoogleMapsWrapper.Engine](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IApiEngine
```

Properties

BaseUrl

```
string BaseUrl { get; }
```

Property Value

[string](#)

Methods

GetBytesAsync(IRequest)

```
Task<IResponse<byte[]>> GetBytesAsync(IRequest request)
```

Parameters

request [IRequest](#)

Returns

[Task](#) <[IResponse](#)<[byte](#)[]>>

GetJsonAsync(IRequest)

```
Task<IResponse<JsonDocument>> GetJsonAsync(IRequest request)
```

Parameters

request [IRequest](#)

Returns

[Task](#) < [IResponse](#)< [JsonDocument](#)>>

Namespace GoogleMapsWrapper.Exceptions

Classes

[GoogleMapsApiException](#)

[GoogleMapsJavascriptException](#)

Class GoogleMapsApiException

Namespace: [GoogleMapsWrapper.Exceptions](#)

Assembly: GoogleMapsWrapper.dll

```
public class GoogleMapsApiException : Exception, ISerializable
```

Inheritance

[object](#) ← [Exception](#) ← GoogleMapsApiException

Implements

[ISerializable](#)

Inherited Members

[Exception.GetBaseException\(\)](#) , [Exception.GetObjectData\(SerializationInfo, StreamingContext\)](#) ,
[Exception.GetType\(\)](#) , [Exception.ToString\(\)](#) , [Exception.Data](#) , [Exception.HelpLink](#) ,
[Exception.HResult](#) , [Exception.InnerException](#) , [Exception.Message](#) , [Exception.Source](#) ,
[Exception.StackTrace](#) , [Exception.TargetSite](#) , [Exception.SerializeObjectState](#) ,
[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

GoogleMapsApiException()

```
public GoogleMapsApiException()
```

GoogleMapsApiException(string)

```
public GoogleMapsApiException(string message)
```

Parameters

message [string](#)

GoogleMapsApiException(string, Exception)

```
public GoogleMapsApiException(string message, Exception innerException)
```

Parameters

message [string](#)

innerException [Exception](#)

Class GoogleMapsJavascriptException

Namespace: [GoogleMapsWrapper.Exceptions](#)

Assembly: GoogleMapsWrapper.dll

```
public class GoogleMapsJavascriptException : Exception, ISerializable
```

Inheritance

[object](#) ← [Exception](#) ← GoogleMapsJavascriptException

Implements

[ISerializable](#)

Inherited Members

[Exception.GetBaseException\(\)](#) , [Exception.GetObjectData\(SerializationInfo, StreamingContext\)](#) ,
[Exception.GetType\(\)](#) , [Exception.ToString\(\)](#) , [Exception.Data](#) , [Exception.HelpLink](#) ,
[Exception.HResult](#) , [Exception.InnerException](#) , [Exception.Message](#) , [Exception.Source](#) ,
[Exception.StackTrace](#) , [Exception.TargetSite](#) , [Exception.SerializeObjectState](#) ,
[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#)

Constructors

GoogleMapsJavascriptException()

```
public GoogleMapsJavascriptException()
```

GoogleMapsJavascriptException(string)

```
public GoogleMapsJavascriptException(string message)
```

Parameters

message [string](#)

GoogleMapsJavascriptException(string, Exception)

```
public GoogleMapsJavascriptException(string message, Exception innerException)
```

Parameters

message [string](#)

innerException [Exception](#)

Namespace GoogleMapsWrapper.JavascriptApi

Classes

[BrowserErrorEventArgs](#)

[MarkerMouseEventArgs](#)

Interfaces

[IMapBoundElement](#)

Class BrowserErrorEventArgs

Namespace: [GoogleMapsWrapper.JavascriptApi](#)

Assembly: GoogleMapsWrapper.dll

```
public class BrowserErrorEventArgs : EventArgs
```

Inheritance

[object](#) ← [EventArgs](#) ← BrowserErrorEventArgs

Inherited Members

[EventArgs.Empty\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#)

Constructors

BrowserErrorEventArgs(string)

```
public BrowserErrorEventArgs(string message)
```

Parameters

message [string](#)

Properties

Message

```
public string Message { get; }
```

Property Value

[string](#)

Interface IMapBoundElement

Namespace: [GoogleMapsWrapper.JavascriptApi](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IMapBoundElement
```

Properties

Id

```
string? Id { get; }
```

Property Value

[string](#) ↗

Methods

Serialize()

```
string Serialize()
```

Returns

[string](#) ↗

Class MarkerMouseEventArgs

Namespace: [GoogleMapsWrapper.JavascriptApi](#)

Assembly: GoogleMapsWrapper.dll

```
public class MarkerMouseEventArgs : EventArgs
```

Inheritance

[object](#) ← [EventArgs](#) ← MarkerMouseEventArgs

Inherited Members

[EventArgs.Empty\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#)

Constructors

MarkerMouseEventArgs(string)

```
public MarkerMouseEventArgs(string id)
```

Parameters

id [string](#)

Properties

Id

```
public string Id { get; }
```

Property Value

[string](#)

Namespace GoogleMapsWrapper.Javascript

Api.Browser

Classes

[GoogleMapsBrowser](#)

[GoogleMaps_READONLYRepository](#)

[GoogleMapsRepository](#)

[ScriptResult](#)

Interfaces

[IBrowser](#)

Defines the minimum requirements needed for a browser-like object to interact with an IGoogleMapsBrowser.

[IGoogleMapsBrowser](#)

[IGoogleMapsJs_READONLYRepository](#)

A repository for storing map state. Data is loaded into this object by IGoogleMapsJsRepository

Class GoogleMapsBrowser

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

```
[ClassInterface(ClassInterfaceType.AutoDual)]
[ComVisible(true)]
public class GoogleMapsBrowser : IGoogleMapsBrowser, IGoogleMapsJsSendable,
IGoogleMapsJsListenable
```

Inheritance

[object](#) ← GoogleMapsBrowser

Implements

[IGoogleMapsBrowser](#), [IGoogleMapsJsSendable](#), [IGoogleMapsJsListenable](#)

Inherited Members

[object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#),
[object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

GoogleMapsBrowser(IBrowser)

```
public GoogleMapsBrowser(IBrowser browser)
```

Parameters

browser [IBrowser](#)

Properties

Browser

```
public IBrowser Browser { get; }
```

Property Value

[IBrowser](#)

Repository

```
public IGoogleMapsJs_READONLYRepository Repository { get; }
```

Property Value

[IGoogleMapsJs_READONLYRepository](#)

Methods

AddMarkerAsync(BoundMarker)

```
public Task AddMarkerAsync(BoundMarker boundMarker)
```

Parameters

boundMarker [BoundMarker](#)

Returns

[Task](#)

Close()

```
public void Close()
```

LoadAsync()

```
public Task LoadAsync()
```

Returns

[Task ↗](#)

Navigate(GoogleMapsHtmlTemplate)

```
public void Navigate(GoogleMapsHtmlTemplate template)
```

Parameters

template [GoogleMapsHtmlTemplate](#)

RemoveMarkerAsync(BoundMarker)

```
public Task RemoveMarkerAsync(BoundMarker boundMarker)
```

Parameters

boundMarker [BoundMarker](#)

Returns

[Task ↗](#)

UpdateMarkerAsync(BoundMarker)

```
public Task UpdateMarkerAsync(BoundMarker boundMarker)
```

Parameters

boundMarker [BoundMarker](#)

Returns

[Task ↗](#)

_OnError(string)

```
public void _OnError(string message)
```

Parameters

message [string](#)

_OnMapClick(string)

```
public void _OnMapClick(string coordinate)
```

Parameters

coordinate [string](#)

_OnMapDblClick(string)

```
public void _OnMapDblClick(string coordinate)
```

Parameters

coordinate [string](#)

_OnMapRightClick(string)

```
public void _OnMapRightClick(string coordinate)
```

Parameters

coordinate [string](#)

_OnMarkerClick(string)

```
public void _OnMarkerClick(string id)
```

Parameters

id [string](#)

_OnMarkerDbClick(string)

```
public void _OnMarkerDbClick(string id)
```

Parameters

id [string](#)

_OnMarkerDrag(string, string)

```
public void _OnMarkerDrag(string id, string coordinate)
```

Parameters

id [string](#)

coordinate [string](#)

_OnMarkerMouseOut(string)

```
public void _OnMarkerMouseOut(string id)
```

Parameters

id [string](#)

_OnMarkerMouseOver(string)

```
public void _OnMarkerMouseOver(string id)
```

Parameters

[id string ↗](#)

_OnMarkerRightClick(string)

```
public void _OnMarkerRightClick(string id)
```

Parameters

[id string ↗](#)

Events

OnMapClick

```
public event EventHandler<MapClickEventArgs>? OnMapClick
```

Event Type

[EventHandler ↗ <MapClickEventArgs>](#)

OnMapDblClick

```
public event EventHandler<MapClickEventArgs>? OnMapDblClick
```

Event Type

[EventHandler ↗ <MapClickEventArgs>](#)

OnMapRightClick

```
public event EventHandler<MapClickEventArgs>? OnMapRightClick
```

Event Type

[EventHandler](#) <[MapClickEventArgs](#)>

OnMarkerClick

```
public event EventHandler<MarkerClickEventArgs>? OnMarkerClick
```

Event Type

[EventHandler](#) <[MarkerClickEventArgs](#)>

OnMarkerDblClick

```
public event EventHandler<MarkerClickEventArgs>? OnMarkerDblClick
```

Event Type

[EventHandler](#) <[MarkerClickEventArgs](#)>

OnMarkerDrag

```
public event EventHandler<MarkerDragEventArgs>? OnMarkerDrag
```

Event Type

[EventHandler](#) <[MarkerDragEventArgs](#)>

OnMarkerMouseOut

```
public event EventHandler<MarkerMouseEventArgs>? OnMarkerMouseOut
```

Event Type

[EventHandler](#) <[MarkerMouseEventArgs](#)>

OnMarkerMouseOver

```
public event EventHandler<MarkerMouseEventArgs>? OnMarkerMouseOver
```

Event Type

[EventHandler](#) <[MarkerMouseEventArgs](#)>

OnMarkerRightClick

```
public event EventHandler<MarkerClickEventArgs>? OnMarkerRightClick
```

Event Type

[EventHandler](#) <[MarkerClickEventArgs](#)>

Class GoogleMaps_READONLYRepository

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

```
public class GoogleMaps_READONLYRepository : IGoogleMapsJs_READONLYRepository
```

Inheritance

[object](#) ← GoogleMaps_READONLYRepository

Implements

[IGoogleMapsJs_READONLYRepository](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

GoogleMaps_READONLYRepository(IReadOnlyList<BoundMarker>
)

```
public GoogleMaps_READONLYRepository(IReadOnlyList<BoundMarker> markers)
```

Parameters

markers [IReadOnlyList](#)<BoundMarker>

Properties

Markers

```
public IReadOnlyList<BoundMarker> Markers { get; }
```

Property Value

[IReadOnlyList](#) <[BoundMarker](#)>

Class GoogleMapsRepository

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

```
public class GoogleMapsRepository
```

Inheritance

[object](#) ← GoogleMapsRepository

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

GoogleMapsRepository()

```
public GoogleMapsRepository()
```

Properties

Markers

```
public IReadOnlyList<BoundMarker> Markers { get; }
```

Property Value

[IReadOnlyList](#)<[BoundMarker](#)>

Source

```
public IGoogleMapsBrowser? Source { get; }
```

Property Value

[IGoogleMapsBrowser](#)

Methods

AddMarker(BoundMarker)

```
public void AddMarker(BoundMarker marker)
```

Parameters

marker [BoundMarker](#)

AsReadonly()

```
public IGoogleMapsJs_READONLYRepository AsReadonly()
```

Returns

[IGoogleMapsJs_READONLYRepository](#)

ContainsMarker(BoundMarker)

```
public bool ContainsMarker(BoundMarker marker)
```

Parameters

marker [BoundMarker](#)

Returns

[bool](#)

RemoveMarker(BoundMarker)

```
public void RemoveMarker(BoundMarker marker)
```

Parameters

marker [BoundMarker](#)

UpdateMarker(BoundMarker)

```
public void UpdateMarker(BoundMarker marker)
```

Parameters

marker [BoundMarker](#)

Interface IBrowser

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

Defines the minimum requirements needed for a browser-like object to interact with an IGoogleMapsBrowser.

```
public interface IBrowser
```

Properties

Html

```
string Html { get; }
```

Property Value

[string](#)

Methods

BindObject(string, object)

```
void BindObject(string name, object sourceObject)
```

Parameters

name [string](#)

sourceObject [object](#)

Close()

```
void Close()
```

ExecuteScriptAsync(string)

```
Task<ScriptResult> ExecuteScriptAsync(string script)
```

Parameters

script [string](#)

Returns

[Task](#) <[ScriptResult](#)>

ExecuteScriptAsyncInvoke(string)

```
Task<ScriptResult> ExecuteScriptAsyncInvoke(string script)
```

Parameters

script [string](#)

Returns

[Task](#) <[ScriptResult](#)>

Navigate(string)

```
void Navigate(string html)
```

Parameters

html [string](#)

Navigate(Uri)

`void Navigate(Uri source)`

Parameters

`source Uri`

SourceObject()

`object SourceObject()`

Returns

`object`

Interface IGoogleMapsBrowser

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IGoogleMapsBrowser : IGoogleMapsJsSendable, IGoogleMapsJsListenable
```

Inherited Members

[IGoogleMapsJsSendable.AddMarkerAsync\(BoundMarker\)](#),
[IGoogleMapsJsSendable.RemoveMarkerAsync\(BoundMarker\)](#),
[IGoogleMapsJsSendable.UpdateMarkerAsync\(BoundMarker\)](#), [IGoogleMapsJsListenable.OnMapClick](#),
[IGoogleMapsJsListenable.OnMapDbClick](#), [IGoogleMapsJsListenable.OnMapRightClick](#),
[IGoogleMapsJsListenable.OnMarkerClick](#), [IGoogleMapsJsListenable.OnMarkerDbClick](#),
[IGoogleMapsJsListenable.OnMarkerRightClick](#), [IGoogleMapsJsListenable.OnMarkerDrag](#),
[IGoogleMapsJsListenable.OnMarkerMouseOver](#), [IGoogleMapsJsListenable.OnMarkerMouseOut](#),
[IGoogleMapsJsListenable.OnError\(string\)](#), [IGoogleMapsJsListenable.OnMapClick\(string\)](#),
[IGoogleMapsJsListenable.OnMapDbClick\(string\)](#), [IGoogleMapsJsListenable.OnMapRightClick\(string\)](#),
[IGoogleMapsJsListenable.OnMarkerClick\(string\)](#), [IGoogleMapsJsListenable.OnMarkerDbClick\(string\)](#),
[IGoogleMapsJsListenable.OnMarkerRightClick\(string\)](#),
[IGoogleMapsJsListenable.OnMarkerDrag\(string, string\)](#),
[IGoogleMapsJsListenable.OnMarkerMouseOver\(string\)](#),
[IGoogleMapsJsListenable.OnMarkerMouseOut\(string\)](#).

Properties

Browser

```
IBrowser Browser { get; }
```

Property Value

[IBrowser](#)

Repository

```
IGoogleMapsJs_READONLYRepository Repository { get; }
```

Property Value

[IGoogleMapsJs_READONLYRepository](#)

Methods

Close()

```
void Close()
```

Navigate(GoogleMapsHtmlTemplate)

```
void Navigate(GoogleMapsHtmlTemplate template)
```

Parameters

template [GoogleMapsHtmlTemplate](#)

Interface IGoogleMapsJsReadonlyRepository

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

A repository for storing map state. Data is loaded into this object by IGoogleMapsJsRepository

```
public interface IGoogleMapsJsReadonlyRepository
```

Properties

Markers

IReadOnlyList<BoundMarker> Markers { [get](#); }

Property Value

[IReadOnlyList](#) <[BoundMarker](#)>

Class ScriptResult

Namespace: [GoogleMapsWrapper.JavascriptApi.Browser](#)

Assembly: GoogleMapsWrapper.dll

```
public record ScriptResult : IEquatable<ScriptResult>
```

Inheritance

[object](#) ← ScriptResult

Implements

[IEquatable](#)<[ScriptResult](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ScriptResult(string?, bool, string)

```
public ScriptResult(string? Result, bool IsSuccess, string ExceptionMessage)
```

Parameters

Result [string](#)

IsSuccess [bool](#)

ExceptionMessage [string](#)

Properties

ExceptionMessage

```
public string ExceptionMessage { get; init; }
```

Property Value

[string](#) ↗

IsSuccess

```
public bool IsSuccess { get; init; }
```

Property Value

[bool](#) ↗

Result

```
public string? Result { get; init; }
```

Property Value

[string](#) ↗

Methods

TryDeserialize<T>(out T?)

```
public bool TryDeserialize<T>(out T? obj)
```

Parameters

[obj](#) T

Returns

[bool](#) ↗

Type Parameters

Namespace GoogleMapsWrapper.Javascript

Api.Elements

Classes

[BoundMarker](#)

[BoundMarkerJsonConverter](#)

[LockSafeHashSet<T>](#)

A HashSet that is modified within a thread lock mechanism.

[MapBoundElementEqualityComparer](#)

An equality comparer for IMapBoundElement type, to check if two IMapBoundElements have equal ID values.

[MapLabel](#)

[MapSvgIcon](#)

Class BoundMarker

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

```
public record BoundMarker : IMapBoundElement, IEquatable<BoundMarker>
```

Inheritance

[object](#) ← BoundMarker

Implements

[IMapBoundElement](#), [IEquatable](#)<BoundMarker>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

BoundMarker(GpsCoordinate?, MapLabel, string?, bool)

```
public BoundMarker(GpsCoordinate? coordinates, MapLabel label, string? info = null, bool  
draggable = false)
```

Parameters

coordinates [GpsCoordinate](#)?

label [MapLabel](#)

info [string](#)

draggable [bool](#)

BoundMarker(GpsCoordinate?, MapSvgIcon, MapLabel, string?, bool)

Overload constructor, Id property is produced internally as a GUID.

```
public BoundMarker(GpsCoordinate? coordinates, MapSvgIcon icon, MapLabel label, string? info  
= null, bool draggable = false)
```

Parameters

coordinates [GpsCoordinate?](#)

icon [MapSvgIcon](#)

label [MapLabel](#)

info [string](#)

draggable [bool](#)

BoundMarker(string?, GpsCoordinate?, MapSvgIcon, MapLabel, string?, bool)

```
public BoundMarker(string? Id, GpsCoordinate? Coordinates, MapSvgIcon Icon, MapLabel Label,  
string? Info = null, bool Draggable = false)
```

Parameters

Id [string](#)

Coordinates [GpsCoordinate?](#)

Icon [MapSvgIcon](#)

Label [MapLabel](#)

Info [string](#)

Draggable [bool](#)

Properties

Coordinates

```
public GpsCoordinate? Coordinates { get; init; }
```

Property Value

[GpsCoordinate?](#)

Draggable

```
public bool Draggable { get; init; }
```

Property Value

[bool](#) ↗

Icon

```
public MapSvgIcon Icon { get; init; }
```

Property Value

[MapSvgIcon](#)

Id

```
public string? Id { get; init; }
```

Property Value

[string](#) ↗

Info

```
public string? Info { get; init; }
```

Property Value

[string](#)

Label

```
public MapLabel Label { get; init; }
```

Property Value

[MapLabel](#)

Methods

CopyAssignNewId(BoundMarker)

```
public static BoundMarker CopyAssignNewId(BoundMarker source)
```

Parameters

source [BoundMarker](#)

Returns

[BoundMarker](#)

CopyAssignNewId(string?, BoundMarker)

```
public static BoundMarker CopyAssignNewId(string? id, BoundMarker source)
```

Parameters

`id` [string](#)

`source` [BoundMarker](#)

Returns

[BoundMarker](#)

FromJson(string)

```
public static BoundMarker FromJson(string json)
```

Parameters

`json` [string](#)

Returns

[BoundMarker](#)

Serialize()

```
public string Serialize()
```

Returns

[string](#)

Class BoundMarkerJsonConverter

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

```
public class BoundMarkerJsonConverter : JsonConverter<BoundMarker>
```

Inheritance

[object](#) ← [JsonConverter](#) ← [JsonConverter](#)<[BoundMarker](#)> ← BoundMarkerJsonConverter

Inherited Members

[JsonConverter](#)<[BoundMarker](#)>.CanConvert([Type](#))[,](#)
[JsonConverter](#)<[BoundMarker](#)>.ReadAsPropertyName([ref](#) [Utf8JsonReader](#), [Type](#), [JsonSerializerOptions](#))[,](#)
[JsonConverter](#)<[BoundMarker](#)>.WriteAsPropertyName([Utf8JsonWriter](#), [BoundMarker](#),
[JsonSerializerOptions](#))[,](#)
[JsonConverter](#)<[BoundMarker](#)>.HandleNull[,](#) [object.Equals](#)([object](#))[,](#) [object.Equals](#)([object](#), [object](#))[,](#)
[object.GetHashCode](#)()[,](#) [object.GetType](#)()[,](#) [object.MemberwiseClone](#)()[,](#)
[object.ReferenceEquals](#)([object](#), [object](#))[,](#) [object.ToString](#)()[,](#)

Methods

Read([ref](#) [Utf8JsonReader](#), [Type](#), [JsonSerializerOptions](#))

Reads and converts the JSON to type [BoundMarker](#).

```
public override BoundMarker Read(ref Utf8JsonReader reader, Type typeToConvert,  
JsonSerializerOptions options)
```

Parameters

[reader](#) [Utf8JsonReader](#)[,](#)

The reader.

[typeToConvert](#) [Type](#)[,](#)

The type to convert.

[options](#) [JsonSerializerOptions](#)[,](#)

An object that specifies serialization options to use.

Returns

[BoundMarker](#)

The converted value.

Write(Utf8JsonWriter, BoundMarker, JsonSerializerOptions)

Writes a specified value as JSON.

```
public override void Write(Utf8JsonWriter writer, BoundMarker value,  
JsonSerializerOptions options)
```

Parameters

[writer](#) [Utf8JsonWriter](#)

The writer to write to.

[value](#) [BoundMarker](#)

The value to convert to JSON.

[options](#) [JsonSerializerOptions](#)

An object that specifies serialization options to use.

Class LockSafeHashSet<T>

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

A HashSet that is modified within a thread lock mechanism.

```
public class LockSafeHashSet<T>
```

Type Parameters

T

The type of object to store in the hash set. Null ref types are rejected during Add method. Note: the type should have an IEqualityComparerT for this hashset to determine equality. The equality comparer used for a given type can be checked with: EqualityComparerT.Default

Inheritance

[object](#) ← LockSafeHashSet<T>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

LockSafeHashSet(IEqualityComparer<T>, bool)

```
public LockSafeHashSet(IEqualityComparer<T> comparer, bool ignoreExistsException = false)
```

Parameters

comparer [IEqualityComparer](#)<T>

ignoreExistsException [bool](#)

Properties

Items

```
public IReadOnlyList<T> Items { get; }
```

Property Value

[IReadOnlyList](#)<T>

Methods

Add(T, bool)

Add item.

```
public void Add(T item, bool throwIfExists = true)
```

Parameters

item T

throwIfExists [bool](#)

Throw exception if item exists. Else ignore quietly.

Exceptions

[ArgumentNullException](#)

[InvalidOperationException](#)

AddOrReplace(T)

Add or replace item.

```
public void AddOrReplace(T item)
```

Parameters

item T

Clear()

```
public void Clear()
```

Contains(T)

```
public bool Contains(T item)
```

Parameters

item T

Returns

[bool](#)

Remove(T)

Removes item from set.

```
public void Remove(T item)
```

Parameters

item T

Ignored if doesn't exist.

Exceptions

[ArgumentNullException](#)

Replace(T)

Replace an item in the set with a new item. Existing item is determined by the comparer.

```
public void Replace(T item)
```

Parameters

item T

Class MapBoundElementEqualityComparer

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

An equality comparer for IMapBoundElement type, to check if two IMapBoundElements are have equal ID values.

```
public class MapBoundElementEqualityComparer : IEqualityComparer<IMapBoundElement>
```

Inheritance

[object](#) ← MapBoundElementEqualityComparer

Implements

[IEqualityComparer](#) < [IMapBoundElement](#) >

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

Equals(IMapBoundElement?, IMapBoundElement?)

Determines whether the specified objects are equal.

```
public bool Equals(IMapBoundElement? x, IMapBoundElement? y)
```

Parameters

x [IMapBoundElement](#)

The first object of type T to compare.

y [IMapBoundElement](#)

The second object of type T to compare.

Returns

[bool](#)

[true](#) if the specified objects are equal; otherwise, [false](#).

GetHashCode(IMapBoundElement)

Returns a hash code for the specified object.

```
public int GetHashCode(IMapBoundElement obj)
```

Parameters

[obj](#) [IMapBoundElement](#)

The [object](#) for which a hash code is to be returned.

Returns

[int](#)

A hash code for the specified object.

Exceptions

[ArgumentNullException](#)

The type of [obj](#) is a reference type and [obj](#) is [null](#).

Class MapLabel

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

```
public record MapLabel : IEquatable<MapLabel>
```

Inheritance

[object](#) ← MapLabel

Implements

[IEquatable](#)<[MapLabel](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

MapLabel(string)

```
public MapLabel(string Text)
```

Parameters

Text [string](#)

MapLabel(string, Color, double, int, Color)

```
public MapLabel(string Text, Color Color, double Scale = 1, int FontWeight = 400, Color  
BackgroundColor = default)
```

Parameters

Text [string](#)

Color [Color](#)

Scale [double](#)

FontWeight [int](#)

BackgroundColor [Color](#)

Properties

BackgroundColor

```
public Color BackgroundColor { get; init; }
```

Property Value

[Color](#)

Color

```
public Color Color { get; init; }
```

Property Value

[Color](#)

FontWeight

```
public int FontWeight { get; init; }
```

Property Value

[int](#)

Scale

```
public double Scale { get; init; }
```

Property Value

double ↗

Text

```
public string Text { get; init; }
```

Property Value

string ↗

Methods

Serialize()

```
public string Serialize()
```

Returns

string ↗

Class MapSvgIcon

Namespace: [GoogleMapsWrapper.JavascriptApi.Elements](#)

Assembly: GoogleMapsWrapper.dll

```
public record MapSvgIcon : IEquatable<MapSvgIcon>
```

Inheritance

[object](#) ← MapSvgIcon

Implements

[IEquatable](#)<[MapSvgIcon](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

MapSvgIcon(string, Color, double, Color, double, double)

```
public MapSvgIcon(string SvgPath, Color Color, double Scale = 1, Color OutlineColor =  
default, double OutlineWeight = 1, double Opacity = 1)
```

Parameters

SvgPath [string](#)

Color [Color](#)

Scale [double](#)

OutlineColor [Color](#)

OutlineWeight [double](#)

Opacity [double](#)

Properties

Color

```
public Color Color { get; init; }
```

Property Value

[Color](#) ↗

Opacity

```
public double Opacity { get; init; }
```

Property Value

[double](#) ↗

OutlineColor

```
public Color OutlineColor { get; init; }
```

Property Value

[Color](#) ↗

OutlineWeight

```
public double OutlineWeight { get; init; }
```

Property Value

[double](#) ↗

Scale

```
public double Scale { get; init; }
```

Property Value

[double](#) ↗

SvgPath

```
public string SvgPath { get; init; }
```

Property Value

[string](#) ↗

Methods

CircleHollowIcon(Color, double)

```
public static MapSvgIcon CircleHollowIcon(Color color, double scale = 1)
```

Parameters

color [Color](#) ↗

scale [double](#) ↗

Returns

[MapSvgIcon](#)

CircleIcon(Color, double)

```
public static MapSvgIcon CircleIcon(Color color, double scale = 1)
```

Parameters

color [Color](#)

scale [double](#)

Returns

[MapSvgIcon](#)

PinIcon(Color, double)

```
public static MapSvgIcon PinIcon(Color color, double scale = 1)
```

Parameters

color [Color](#)

scale [double](#)

Returns

[MapSvgIcon](#)

Serialize()

```
public string Serialize()
```

Returns

[string](#)

Namespace GoogleMapsWrapper.Javascript Api.Html

Classes

[GoogleMapsHtmlTemplate](#)

Class GoogleMapsHtmlTemplate

Namespace: [GoogleMapsWrapper.JavascriptApi.Html](#)

Assembly: GoogleMapsWrapper.dll

```
public class GoogleMapsHtmlTemplate
```

Inheritance

[object](#) ← GoogleMapsHtmlTemplate

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

GoogleMapsHtmlTemplate(string, string, string, Map?)

```
public GoogleMapsHtmlTemplate(string templateHtml, string apiKey, string  
objectBindingScript, Map? loadMap = null)
```

Parameters

templateHtml [string](#)

apiKey [string](#)

objectBindingScript [string](#)

loadMap [Map](#)

Properties

Html

```
public string Html { get; }
```

Property Value

[string](#) ↗

TemplateHtml

```
public string TemplateHtml { get; }
```

Property Value

[string](#) ↗

Namespace GoogleMapsWrapper.Javascript Api.Listener

Classes

[MapClickEventArgs](#)

[MarkerClickEventArgs](#)

[MarkerDragEventArgs](#)

Interfaces

[IGoogleMapsJsListenable](#)

Interface IGoogleMapsJsListenable

Namespace: [GoogleMapsWrapper.JavascriptApi.Listener](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IGoogleMapsJsListenable
```

Methods

_OnError(string)

```
void _OnError(string message)
```

Parameters

message [string](#)

_OnMapClick(string)

```
void _OnMapClick(string coordinate)
```

Parameters

coordinate [string](#)

_OnMapDblClick(string)

```
void _OnMapDblClick(string coordinate)
```

Parameters

coordinate [string](#)

_OnMapRightClick(string)

```
void _OnMapRightClick(string coordinate)
```

Parameters

coordinate [string ↗](#)

_OnMarkerClick(string)

```
void _OnMarkerClick(string id)
```

Parameters

id [string ↗](#)

_OnMarkerDblClick(string)

```
void _OnMarkerDblClick(string id)
```

Parameters

id [string ↗](#)

_OnMarkerDrag(string, string)

```
void _OnMarkerDrag(string id, string coordinate)
```

Parameters

id [string ↗](#)

coordinate [string ↗](#)

_OnMarkerMouseOut(string)

```
void _OnMarkerMouseOut(string id)
```

Parameters

id [string](#)

_OnMarkerMouseOver(string)

```
void _OnMarkerMouseOver(string id)
```

Parameters

id [string](#)

_OnMarkerRightClick(string)

```
void _OnMarkerRightClick(string id)
```

Parameters

id [string](#)

Events

OnMapClick

```
event EventHandler<MapClickEventArgs>? OnMapClick
```

Event Type

[EventHandler](#)<[MapClickEventArgs](#)>

OnMapDbClick

event EventHandler<MapClickEventArgs>? OnMapDbClick

Event Type

[EventHandler](#) <MapClickEventArgs>

OnMapRightClick

event EventHandler<MapClickEventArgs>? OnMapRightClick

Event Type

[EventHandler](#) <MapClickEventArgs>

OnMarkerClick

event EventHandler<MarkerClickEventArgs>? OnMarkerClick

Event Type

[EventHandler](#) <MarkerClickEventArgs>

OnMarkerDbClick

event EventHandler<MarkerClickEventArgs>? OnMarkerDbClick

Event Type

[EventHandler](#) <MarkerClickEventArgs>

OnMarkerDrag

```
event EventHandler<MarkerDragEventArgs>? OnMarkerDrag
```

Event Type

[EventHandler](#)<[MarkerDragEventArgs](#)>

OnMarkerMouseOut

```
event EventHandler<MarkerMouseEventArgs>? OnMarkerMouseOut
```

Event Type

[EventHandler](#)<[MarkerMouseEventArgs](#)>

OnMarkerMouseOver

```
event EventHandler<MarkerMouseEventArgs>? OnMarkerMouseOver
```

Event Type

[EventHandler](#)<[MarkerMouseEventArgs](#)>

OnMarkerRightClick

```
event EventHandler<MarkerClickEventArgs>? OnMarkerRightClick
```

Event Type

[EventHandler](#)<[MarkerClickEventArgs](#)>

Class MapClickEventArgs

Namespace: [GoogleMapsWrapper.JavascriptApi.Listener](#)

Assembly: GoogleMapsWrapper.dll

```
public class MapClickEventArgs : EventArgs
```

Inheritance

[object](#) ← [EventArgs](#) ← MapClickEventArgs

Inherited Members

[EventArgs.Empty\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#)

Constructors

MapClickEventArgs(GpsCoordinate)

```
public MapClickEventArgs(GpsCoordinate coordinates)
```

Parameters

coordinates [GpsCoordinate](#)

Class MarkerClickEventArgs

Namespace: [GoogleMapsWrapper.JavascriptApi.Listener](#)

Assembly: GoogleMapsWrapper.dll

```
public class MarkerClickEventArgs : EventArgs
```

Inheritance

[object](#) ← [EventArgs](#) ← MarkerClickEventArgs

Inherited Members

[EventArgs.Empty](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#)

Constructors

MarkerClickEventArgs(string)

```
public MarkerClickEventArgs(string id)
```

Parameters

id [string](#)

Properties

Id

```
public string Id { get; }
```

Property Value

[string](#)

Class MarkerDragEventArgs

Namespace: [GoogleMapsWrapper.JavascriptApi.Listener](#)

Assembly: GoogleMapsWrapper.dll

```
public class MarkerDragEventArgs : EventArgs
```

Inheritance

[object](#) ← [EventArgs](#) ← MarkerDragEventArgs

Inherited Members

[EventArgs.Empty\(\)](#) , [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#)

Constructors

MarkerDragEventArgs(string, GpsCoordinate)

```
public MarkerDragEventArgs(string id, GpsCoordinate coordinates)
```

Parameters

id [string](#)

coordinates [GpsCoordinate](#)

Properties

Coordinates

```
public GpsCoordinate Coordinates { get; }
```

Property Value

[GpsCoordinate](#)

Id

```
public string Id { get; }
```

Property Value

[string ↗](#)

Namespace GoogleMapsWrapper.Javascript Api.Sender

Interfaces

[IGoogleMapsJsSendable](#)

Interface IGoogleMapsJsSendable

Namespace: [GoogleMapsWrapper.JavascriptApi.Sender](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IGoogleMapsJsSendable
```

Methods

AddMarkerAsync(BoundMarker)

Task **AddMarkerAsync**(BoundMarker boundMarker)

Parameters

boundMarker [BoundMarker](#)

Returns

[Task](#)

RemoveMarkerAsync(BoundMarker)

Task **RemoveMarkerAsync**(BoundMarker boundMarker)

Parameters

boundMarker [BoundMarker](#)

Returns

[Task](#)

UpdateMarkerAsync(BoundMarker)

Task **UpdateMarkerAsync**(BoundMarker boundMarker)

Parameters

boundMarker [BoundMarker](#)

Returns

[Task](#)

Namespace GoogleMapsWrapper.Parsers

Classes

[ElevationParser](#)

[GeocodeParser](#)

Interfaces

[IParser<TOutput, TInput>](#)

Class ElevationParser

Namespace: [GoogleMapsWrapper.Parsers](#)

Assembly: GoogleMapsWrapper.dll

```
public class ElevationParser : IParser<ElevationContainer, JsonDocument>
```

Inheritance

[object](#) ← ElevationParser

Implements

[IParser<ElevationContainer, JsonDocument>](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

Parse(JsonDocument)

```
public ElevationContainer Parse(JsonDocument input)
```

Parameters

[input](#) [JsonDocument](#)

Returns

[ElevationContainer](#)

TryParse(JsonDocument, out ElevationContainer?)

```
public bool TryParse(JsonDocument input, out ElevationContainer? output)
```

Parameters

input [JsonDocument](#)

output [ElevationContainer](#)

Returns

[bool](#)

Class GeocodeParser

Namespace: [GoogleMapsWrapper.Parsers](#)

Assembly: GoogleMapsWrapper.dll

```
public class GeocodeParser : IParser<GeocodeContainer, JsonDocument>
```

Inheritance

[object](#) ← GeocodeParser

Implements

[IParser<GeocodeContainer, JsonDocument>](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

Parse(JsonDocument)

```
public GeocodeContainer Parse(JsonDocument input)
```

Parameters

input [JsonDocument](#)

Returns

[GeocodeContainer](#)

TryParse(JsonDocument, out GeocodeContainer?)

```
public bool TryParse(JsonDocument input, out GeocodeContainer? output)
```

Parameters

input [JsonDocument](#)

output [GeocodeContainer](#)

Returns

[bool](#)

Interface IParser<TOutput, TInput>

Namespace: [GoogleMapsWrapper.Parsers](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IParser<TOutput, TInput>
```

Type Parameters

TOutput

TInput

Methods

Parse(TInput)

```
TOutput Parse(TInput input)
```

Parameters

input TInput

Returns

TOutput

TryParse(TInput, out TOutput?)

```
bool TryParse(TInput input, out TOutput? output)
```

Parameters

input TInput

output TOutput

Returns

[bool](#)

Namespace GoogleMapsWrapper.Requests

Interfaces

[IRequest](#)

Interface IRequest

Namespace: [GoogleMapsWrapper.Requests](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IRequest
```

Properties

Api

```
ApiTypes Api { get; }
```

Property Value

[ApiTypes](#)

Category

```
RequestTypes Category { get; }
```

Property Value

[RequestTypes](#)

Id

```
string? Id { get; }
```

Property Value

[string](#) ↗

Query

```
string Query { get; }
```

Property Value

[string](#) ↗

Url

```
Uri Url { get; }
```

Property Value

[Uri](#) ↗

Namespace GoogleMapsWrapper.Responses

Classes

[ByteResponse](#)

[JsonResponse](#)

Interfaces

[IResponse<TResponse>](#)

Class ByteResponse

Namespace: [GoogleMapsWrapper.Responses](#)

Assembly: GoogleMapsWrapper.dll

```
public class ByteResponse : IResponse<byte[]>
```

Inheritance

[object](#) ← ByteResponse

Implements

[IResponse<byte\[\]>](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

ByteResponse(IRequest, byte[], HttpResponseMessage)

```
public ByteResponse(IRequest SentRequest, byte[] Content, HttpResponseMessage  
ResponseMessage)
```

Parameters

SentRequest [IRequest](#)

Content [byte\[\]](#)

ResponseMessage [HttpResponseMessage](#)

Fields

content

```
public byte[]? content
```

Field Value

[byte](#)[]

Properties

Content

```
public byte[]? Content { get; }
```

Property Value

[byte](#)[]

ResponseMessage

```
public HttpResponseMessage ResponseMessage { get; }
```

Property Value

[HttpResponseMessage](#)

SentRequest

```
public IRequest SentRequest { get; }
```

Property Value

[IRequest](#)

Methods

Parse<T>(IParser<T, byte[]>)

```
public T Parse<T>(IParser<T, byte[]> parser)
```

Parameters

parser [IParser<T, byte\[\]>](#)

Returns

T

Type Parameters

T

Interface IResponse<TResponse>

Namespace: [GoogleMapsWrapper.Responses](#)

Assembly: GoogleMapsWrapper.dll

```
public interface IResponse<TResponse>
```

Type Parameters

TResponse

Properties

Content

```
TResponse? Content { get; }
```

Property Value

TResponse

ResponseMessage

```
HttpResponseMessage ResponseMessage { get; }
```

Property Value

[HttpResponseMessage](#) ↗

SentRequest

```
IRequest SentRequest { get; }
```

Property Value

[IRequest](#)

Methods

Parse<T>(IParser<T, TResponse>)

T Parse<T>(IParser<T, TResponse> parser)

Parameters

parser [IParser](#)<T, TResponse>

Returns

T

Type Parameters

T

Class JsonResponse

Namespace: [GoogleMapsWrapper.Responses](#)

Assembly: GoogleMapsWrapper.dll

```
public class JsonResponse : IResponse<JsonDocument>
```

Inheritance

[object](#) ← JsonResponse

Implements

[IResponse<JsonDocument>](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Constructors

JsonResponse(IRequest, JsonDocument, HttpResponseMessage)

```
public JsonResponse(IRequest SentRequest, JsonDocument Content,  
HttpResponseMessage ResponseMessage)
```

Parameters

SentRequest [IRequest](#)

Content [JsonDocument](#)

ResponseMessage [HttpResponseMessage](#)

Properties

Content

```
public JsonDocument Content { get; }
```

Property Value

[JsonDocument](#)

ResponseMessage

```
public HttpResponseMessage ResponseMessage { get; }
```

Property Value

[HttpResponseMessage](#)

SentRequest

```
public IRequest SentRequest { get; }
```

Property Value

[IRequest](#)

Methods

Parse<T>(IParser<T, JsonDocument>)

```
public T Parse<T>(IParser<T, JsonDocument> parser)
```

Parameters

parser [IParser](#)<T, [JsonDocument](#)>

Returns

T

Type Parameters

T

Namespace GoogleMapsWrapper.Types

Structs

[GpsCoordinate](#)

Enums

[ApiTypes](#)

Type of API per google. For categorization purposes.

[MapImageFormats](#)

Static map image formats.

[MapScaleTypes](#)

Type of scale that a map is displayed at. 1 = normal, 2 = high resolution.

[MapTypes](#)

[MarkerIconAnchorTypes](#)

Anchor type when using a custom static map icon.

[MarkerScaleTypes](#)

Scale type of a marker.

[MarkerSizes](#)

Type of scale that a map is displayed at. 1 = normal, 2 = high resolution.

[RequestTypes](#)

Type of request. For categorization purposes.

Enum ApiTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Type of API per google. For categorization purposes.

```
public enum ApiTypes
```

Fields

Environment = 3

Maps = 0

Places = 2

Routes = 1

Struct GpsCoordinate

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

```
public readonly struct GpsCoordinate : IEquatable<GpsCoordinate>, IFormattable
```

Implements

[IEquatable](#)<[GpsCoordinate](#)>, [IFormattable](#)

Inherited Members

[object.Equals\(object, object\)](#), [object.GetType\(\)](#), [object.ReferenceEquals\(object, object\)](#)

Constructors

GpsCoordinate(decimal, decimal)

```
public GpsCoordinate(decimal latitude, decimal longitude)
```

Parameters

latitude [decimal](#)

longitude [decimal](#)

Properties

Latitude

```
public decimal Latitude { get; }
```

Property Value

[decimal](#)

Longitude

```
public decimal Longitude { get; }
```

Property Value

[decimal](#)

Methods

Equals(GpsCoordinate)

Indicates whether the current object is equal to another object of the same type.

```
public bool Equals(GpsCoordinate other)
```

Parameters

other [GpsCoordinate](#)

An object to compare with this object.

Returns

[bool](#)

[true](#) if the current object is equal to the **other** parameter; otherwise, [false](#).

Equals(object?)

Indicates whether this instance and a specified object are equal.

```
public override bool Equals(object? obj)
```

Parameters

obj [object](#)

The object to compare with the current instance.

Returns

[bool](#)

[true](#) if [obj](#) and this instance are the same type and represent the same value; otherwise, [false](#).

GetHashCode()

Returns the hash code for this instance.

```
public override int GetHashCode()
```

Returns

[int](#)

A 32-bit signed integer that is the hash code for this instance.

Parse(string)

```
public static GpsCoordinate Parse(string s)
```

Parameters

[s](#) [string](#)

Returns

[GpsCoordinate](#)

ToString()

Returns the fully qualified type name of this instance.

```
public override string ToString()
```

Returns

[string](#)

The fully qualified type name.

ToString(string?, IFormatProvider?)

Formats the value of the current instance using the specified format.

```
public string ToString(string? format, IFormatProvider? formatProvider)
```

Parameters

format [string](#)

The format to use.

-or-

A null reference ([Nothing](#) in Visual Basic) to use the default format defined for the type of the [IFormattable](#) implementation.

formatProvider [IFormatProvider](#)

The provider to use to format the value.

-or-

A null reference ([Nothing](#) in Visual Basic) to obtain the numeric format information from the current locale setting of the operating system.

Returns

[string](#)

The value of the current instance in the specified format.

TryParse(ReadOnlySpan<char>, out GpsCoordinate)

```
public static bool TryParse(ReadOnlySpan<char> s, out GpsCoordinate result)
```

Parameters

s [ReadOnlySpan](#)<char>

result [GpsCoordinate](#)

Returns

[bool](#)

TryParse(string?, out GpsCoordinate)

```
public static bool TryParse(string? s, out GpsCoordinate result)
```

Parameters

s [string](#)

result [GpsCoordinate](#)

Returns

[bool](#)

Operators

operator ==(GpsCoordinate, GpsCoordinate)

```
public static bool operator ==(GpsCoordinate left, GpsCoordinate right)
```

Parameters

left [GpsCoordinate](#)

right [GpsCoordinate](#)

Returns

[bool](#)

operator !=(GpsCoordinate, GpsCoordinate)

```
public static bool operator !=(GpsCoordinate left, GpsCoordinate right)
```

Parameters

[left](#) [GpsCoordinate](#)

[right](#) [GpsCoordinate](#)

Returns

[bool](#)

Enum MapImageFormats

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Static map image formats.

```
public enum MapImageFormats
```

Fields

Gif = 2

Jpg = 3

Png = 0

Png32 = 1

Enum MapScaleTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Type of scale that a map is displayed at. 1 = normal, 2 = high resolution.

```
public enum MapScaleTypes
```

Fields

HighRes = 2

Normal = 1

Enum MapTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

```
public enum MapTypes
```

Fields

Hybrid = 3

RoadMap = 0

Satellite = 1

Terrain = 2

Enum MarkerIconAnchorTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Anchor type when using a custom static map icon.

```
public enum MarkerIconAnchorTypes
```

Fields

Bottom = 1

BottomLeft = 7

BottomRight = 8

Center = 4

Left = 2

Right = 3

Top = 0

TopLeft = 5

TopRight = 6

Enum MarkerScaleTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Scale type of a marker.

```
public enum MarkerScaleTypes
```

Fields

Large = 4

Medium = 2

Normal = 1

Enum MarkerSizes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Type of scale that a map is displayed at. 1 = normal, 2 = high resolution.

```
public enum MarkerSizes
```

Fields

Mid = 1

Small = 2

Tiny = 0

Enum RequestTypes

Namespace: [GoogleMapsWrapper.Types](#)

Assembly: GoogleMapsWrapper.dll

Type of request. For categorization purposes.

```
public enum RequestTypes
```

Fields

Elevation = 1

Geocoding = 2

StaticMaps = 0

Namespace GoogleMapsWrapper.Utilities

Classes

[PolylineEncoder](#)

A static class to encode a list of GPS coordinates using Google's polyline shortening encoding algorithm.

[Utilities](#)

A static class for generic utility functions that may be used in this application.

Class PolylineEncoder

Namespace: [GoogleMapsWrapper.Utilities](#)

Assembly: GoogleMapsWrapper.dll

A static class to encode a list of GPS coordinates using Google's polyline shortening encoding algorithm.

```
public static class PolylineEncoder
```

Inheritance

[object](#) ← PolylineEncoder

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

Encode(IList<GpsCoordinate>)

```
public static string Encode(IList<GpsCoordinate> coordinates)
```

Parameters

coordinates [IList](#)<[GpsCoordinate](#)>

Returns

[string](#)

Class Utilities

Namespace: [GoogleMapsWrapper.Utilities](#)

Assembly: GoogleMapsWrapper.dll

A static class for generic utility functions that may be used in this application.

```
public static class Utilities
```

Inheritance

[object](#) ← Utilities

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Methods

ColorToHex(Color)

Convert a .NET Color object to a hexadecimal notation. If transparency (alpha) is provided in the color parameter, outputs 32 bit hex, else 24.

```
public static string ColorToHex(Color color)
```

Parameters

color [Color](#)

Returns

[string](#)

UrlEncodeChar(char)

Convert a char to a URL encoded string representation.

```
public static string UrlEncodeChar(char c)
```

Parameters

c [char](#)

Returns

[string](#)