

Ultra MAC Address 08:00:20:HOSTID
Sun Blade 150 MAC Address 08:00:20:HOSTID / 00:03:ba:HOSTID / 00:00:00:HOSTID

press stop + a
ok show-devs
ok cd /pci@1f,0/ebus@c/eprom@1,0
ok .properties
ok <device address> >physical
ok showstack
ok 2000 memmap
ok 1fd0 +
ok 30 dump
ok 01 <Address value>d8 c!
Address value : take 6 digits only + d8 c!

ok <80 or 83> <Address value>d9 c!
80 : machine type sun ultra
83 : machine type sunblade

MAC Address : 08-00-20-31-82-20
ok <first letter MAC address> <Address value>da c!
ok <second letter MAC address> <Address value>db c!
ok <third letter MAC address> <Address value>dc c!
ok <fourth letter MAC address> <Address value>dd c!
ok <fifth letter MAC address> <Address value>de c!
ok <sixth letter MAC address> <Address value>df c!

Write 00 (if not already) for production date :
ok 00 <Address value>e0 c!
ok 00 <Address value>e1 c!
ok 00 <Address value>e2 c!
ok 00 <Address value>e3 c!

Write host ID (Three last letters MAC Address)
ok <host ID> <Address value>e4 c!
ok <host ID> <Address value>e5 c!
ok <host ID> <Address value>e6 c!

Calculate XOR-Checksum value starting d8-e6 (except e0-e3)
ok <d8> <d9> xor
ok <da> xor
ok <db> xor
ok <dc> xor
ok <dd> xor
ok <de> xor
ok <df> xor
ok <e4> xor
ok <e5> xor
ok <e6> xor

Calculate checksum
ok <value beside the prompt> <Address value>e7 c!
ok banner
ok reset-all

