

# Amiga ROM Kernel Reference Manual

## DOS

THOMAS RICHTER

Copyright © 2023 by Thomas Richter, all rights reserved. This publication is freely distributable under the restrictions stated below, but is also Copyright © Thomas Richter.

Distribution of the publication by a commercial organization without written permission from the author to any third party is prohibited if any payment is made in connection with such distribution, whether directly (as in payment for a copy of the publication) or indirectly (as in payment for some service related to the Publication, or payment for some product or service that includes a copy of the publication “without charge”; these are only examples, and not an exhaustive enumeration of prohibited activities).

However, the following methods of distribution involving payment shall not in and of themselves be a violation of this restriction:

1. Distributing the Program on a physical data carrier (e.g. CD-ROM, DVD, USB-Stick, Disk...) provided that:
  - (a) the Archive is reproduced entirely and verbatim on such data carrier, including especially this licence agreement;
  - (b) the data carrier is made available to the public for a nominal fee only, i.e. for a fee that covers the costs of the data carrier, and shipment of the data carrier;
  - (c) a data carrier with the Program installed is made available to the author for free except for shipment costs, and
  - (d) provided further that all information on said data carrier is redistributable for non-commercial purposes without charge.

Redistribution of a modified version of the publication is prohibited in any way, by any organization, regardless whether commercial or non-commercial. Everything must be kept together, in original and unmodified form.

DISCLAIMER: THIS PUBLICATION IS PROVIDED “AS IS” WITHOUT ANY WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE. FURTHER, THE AUTHOR DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATION REGARDING THE USE OF, OR THE RESULTS OF THE USE OF, THE INFORMATION CONTAINED HEREIN IN TERM OF CORRECTNESS, ACCURACY, RELIABILITY, CURRENTNESS, OR OTHERWISE; THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY IS ASSUMED SOLELY BY THE USER. SHOULD THE INFORMATION PROVE INACCURATE, THE USER (AND NOT THE AUTHOR) ASSUMES THE EITHER COST OF ALL NECESSARY CORRECTION. IN NO EVENT WILL THE AUTHOR BE LIABLE FOR DIRECT, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS PUBLICATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. SOME LAWS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF IMPLIED WARRANTIES OR LIABILITIES FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY.

*Amiga* is a registered trademark, *Amiga-DOS*, *Exec* and *Kickstart* are registered trademarks of Amiga Intl. *Motorola* is a registered trademark of Motorola, inc. *Unix* is a trademark of the Open Group.



---

# Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Introduction</b>                              | <b>3</b>  |
| 1.1      | Purpose . . . . .                                | 3         |
| 1.2      | Language and Type Setting Conventions . . . . .  | 3         |
| <b>2</b> | <b>Elementary Data Types</b>                     | <b>5</b>  |
| 2.1      | The dos.library . . . . .                        | 5         |
| 2.2      | Booleans . . . . .                               | 5         |
| 2.3      | Pointers and BPTRs . . . . .                     | 6         |
| 2.4      | C Strings and BSTRs . . . . .                    | 7         |
| 2.5      | Files . . . . .                                  | 7         |
| 2.6      | Locks . . . . .                                  | 7         |
| 2.7      | Processes . . . . .                              | 8         |
| 2.8      | Handlers and File Systems . . . . .              | 8         |
| <b>3</b> | <b>Date and Time</b>                             | <b>9</b>  |
| 3.1      | Elementary Time and Date Functions . . . . .     | 9         |
| 3.1.1    | Obtaining the Time and Date . . . . .            | 9         |
| 3.1.2    | Comparing two Times and Dates . . . . .          | 10        |
| 3.1.3    | Delaying Program Execution . . . . .             | 10        |
| 3.2      | Conversion Into and From Strings . . . . .       | 10        |
| 3.2.1    | Converting a Time and Date to a String . . . . . | 12        |
| 3.2.2    | Convert a String to a Date and Time . . . . .    | 12        |
| <b>4</b> | <b>Files</b>                                     | <b>15</b> |
| 4.1      | What are Files? . . . . .                        | 15        |
| 4.2      | Interactive vs. non-Interactive Files . . . . .  | 15        |
| 4.3      | Paths and File Names . . . . .                   | 15        |
| 4.3.1    | Devices, Volumes and Assigns . . . . .           | 16        |
| 4.3.2    | Relative and Absolute Paths . . . . .            | 18        |
| 4.3.3    | Maximum Path Length . . . . .                    | 19        |
| 4.3.4    | Flat vs. Hiearchical File Systems . . . . .      | 19        |
| 4.3.5    | Case Sensitivity . . . . .                       | 20        |
| 4.4      | Opening Files . . . . .                          | 20        |
| 4.5      | Closing Files . . . . .                          | 21        |
| 4.6      | Types of Files and Handlers . . . . .            | 21        |
| 4.6.1    | Obtaining the Type from a File . . . . .         | 21        |
| 4.6.2    | Obtaining the Type from a Path . . . . .         | 22        |
| 4.7      | Unbuffered Input and Output . . . . .            | 22        |
| 4.7.1    | Reading Data . . . . .                           | 22        |
| 4.7.2    | Testing for Availability of Data . . . . .       | 23        |

|          |  |           |
|----------|--|-----------|
| 4.7.3    | Writing Data . . . . .   | 23        |
| 4.7.4    | Adjusting the File Pointer . . . . .                                 | 23        |
| 4.7.5    | Setting the Size of a File . . . . .                                 | 24        |
| 4.8      | Buffered Input and Output . . . . .                                  | 25        |
| 4.8.1    | Buffered Read From a File . . . . .                                  | 25        |
| 4.8.2    | Buffered Write to a File . . . . .                                   | 26        |
| 4.8.3    | Buffered Write to the Output Stream . . . . .                        | 26        |
| 4.8.4    | Adjusting the Buffer . . . . .                                       | 26        |
| 4.8.5    | Synchronize the File to the Buffer . . . . .                         | 27        |
| 4.8.6    | Write a Character Buffered to a File . . . . .                       | 28        |
| 4.8.7    | Write a String Buffered to a File . . . . .                          | 28        |
| 4.8.8    | Write a String Buffered to the Output Stream . . . . .               | 28        |
| 4.8.9    | Read a Character from a File . . . . .                               | 29        |
| 4.8.10   | Read a Line from a File . . . . .                                    | 29        |
| 4.8.11   | Revert a Single Byte Read . . . . .                                  | 29        |
| 4.9      | File Handle Documentation . . . . .                                  | 30        |
| 4.9.1    | The struct FileHandle . . . . .                                      | 30        |
| 4.9.2    | String Streams . . . . .   | 31        |
| 4.9.3    | An FSkip() Implementation . . . . .                                  | 32        |
| 4.9.4    | An FGet() Implementation . . . . .                                   | 33        |
| 4.10     | Formatted Output . . . . .   | 33        |
| 4.10.1   | Print Formatted String using C-Syntax to a File . . . . .            | 33        |
| 4.10.2   | Print Formatted String using C-Syntax to the Output String . . . . . | 34        |
| 4.10.3   | BCPL Style Formatted Print to a File . . . . .                       | 34        |
| 4.11     | Record Locking . . . . .   | 35        |
| 4.11.1   | Locking a Portion of a File . . . . .                                | 35        |
| 4.11.2   | Locking Multiple Portions of a File . . . . .                        | 36        |
| 4.11.3   | Unlocking a Portion of a File . . . . .                              | 37        |
| 4.11.4   | Unlocking Multiple Records of a File . . . . .                       | 37        |
| <b>5</b> | <b>Locks</b>   | <b>39</b> |
| 5.1      | Obtaining and Releasing Locks . . . . .                              | 39        |
| 5.1.1    | Obtaining a Lock from a Path . . . . .                               | 39        |
| 5.1.2    | Duplicating a Lock . . . . .   | 40        |
| 5.1.3    | Obtaining the Parent of an Object . . . . .                          | 40        |
| 5.1.4    | Creating a Directory . . . . .                                       | 41        |
| 5.1.5    | Releasing a Lock . . . . .   | 41        |
| 5.1.6    | Changing the Type of a Lock . . . . .                                | 41        |
| 5.1.7    | Comparing two Locks . . . . .  | 42        |
| 5.1.8    | Compare to Locks for the Device . . . . .                            | 42        |
| 5.2      | Locks and Files . . . . .  | 42        |
| 5.2.1    | Duplicate the Implicit Lock of a File . . . . .                      | 43        |
| 5.2.2    | Obtaining the Directory a File is Located in . . . . .               | 43        |
| 5.2.3    | Opening a File from a Lock . . . . .                                 | 43        |
| 5.2.4    | Get Information on the State of the Medium . . . . .                 | 44        |
| 5.2.5    | The struct FileLock . . . . .  | 46        |

|          |   |           |
|----------|---|-----------|
| <b>6</b> | <b>Working with Directories</b>                       | <b>49</b> |
| 6.1      | Examining Objects on File Systems                     | 49        |
| 6.1.1    | Retrieving Information on an Directory Entry          | 51        |
| 6.1.2    | Retrieving Information from a File Handle             | 52        |
| 6.1.3    | Scanning through a Directory Step by Step             | 52        |
| 6.1.4    | Examine Multiple Entries at once                      | 53        |
| 6.1.5    | Aborting a Directory Scan                             | 55        |
| 6.2      | Modifying Directory Entries                           | 55        |
| 6.2.1    | Deleting Objects on the File System                   | 56        |
| 6.2.2    | Rename or Relocate an Object                          | 56        |
| 6.2.3    | Set the File Comment                                  | 56        |
| 6.2.4    | Setting Protection Bits                               | 57        |
| 6.2.5    | Set the Modification Date                             | 57        |
| 6.2.6    | Set User and Group ID                                 | 57        |
| 6.3      | Working with Paths                                    | 58        |
| 6.3.1    | Find the Path From a Lock                             | 58        |
| 6.3.2    | Find the Path from a File Handle                      | 58        |
| 6.3.3    | Append a Component to a Path                          | 59        |
| 6.3.4    | Find the last Component of a Path                     | 59        |
| 6.3.5    | Find End of Next-to-Last Component in a Path          | 59        |
| 6.3.6    | Extract a Component From a Path                       | 60        |
| 6.4      | Links   | 60        |
| 6.4.1    | Creating Links  | 62        |
| 6.4.2    | Resolving Soft-Links                                  | 62        |
| 6.5      | Notification Requests                                 | 63        |
| 6.5.1    | Request Notification on File or Directory Changes     | 63        |
| 6.5.2    | Canceling a Notification Request                      | 65        |
| <b>7</b> | <b>File System Support Functions</b>                  | <b>67</b> |
| 7.0.1    | Adjusting File System Buffers                         | 67        |
| 7.0.2    | Inhibiting a File System                              | 67        |
| 7.0.3    | Change the Name of a Volume                           | 68        |
| 7.0.4    | Initializing a File System                            | 68        |
| <b>8</b> | <b>Administration of Volumes, Devices and Assigns</b> | <b>71</b> |
| 8.1      | The Device List and the Mount List                    | 74        |
| 8.1.1    | Keywords defining the DosList structure               | 74        |
| 8.1.2    | Keywords controlling the FileSysStartupMsg            | 75        |
| 8.1.3    | Keywords controlling the Environment Vector           | 75        |
| 8.2      | Finding Handler or File System Ports                  | 80        |
| 8.2.1    | Iterate through Devices Matching a Path               | 80        |
| 8.2.2    | Releasing DevProc Information                         | 81        |
| 8.2.3    | Legacy Handler Port Access                            | 82        |
| 8.2.4    | Obtaining the Current Console Handler                 | 82        |
| 8.2.5    | Obtaining the Default File System                     | 82        |
| 8.3      | Iterating and Accessing the Device List               | 83        |
| 8.3.1    | Gaining Access to the Device List                     | 83        |
| 8.3.2    | Requesting Access to the Device List                  | 83        |
| 8.3.3    | Release Access to the Device List                     | 84        |
| 8.3.4    | Iterate through the Device List                       | 84        |
| 8.3.5    | Find a Device List Entry by Name                      | 84        |

|           |  |            |
|-----------|--|------------|
| 8.3.6     | Accessing Mount Parameters . . . . .                     | 85         |
| 8.4       | Adding or Removing Entries to the Device List . . . . .  | 87         |
| 8.4.1     | Adding an Entry to the Device List . . . . .             | 88         |
| 8.4.2     | Removing an Entry from the Device List . . . . .         | 88         |
| 8.5       | Creating and Deleting Device List Entries . . . . .      | 89         |
| 8.5.1     | Creating a Device List Entry . . . . .                   | 89         |
| 8.5.2     | Releasing a Device List Entry . . . . .                  | 90         |
| 8.6       | Creating and Updating Assigns . . . . .                  | 91         |
| 8.6.1     | Create and Add a Regular Assign . . . . .                | 91         |
| 8.6.2     | Create a Non-Binding Assign . . . . .                    | 91         |
| 8.6.3     | Create a Late Assign . . . . .                           | 92         |
| 8.6.4     | Add a Directory to a Multi-Assign . . . . .              | 92         |
| 8.6.5     | Remove a Directory From a Multi-Assign . . . . .         | 92         |
| <b>9</b>  | <b>Pattern Matching</b>                                  | <b>95</b>  |
| 9.1       | Scanning Directories . . . . .                           | 96         |
| 9.1.1     | Starting a Directory Scan . . . . .                      | 99         |
| 9.1.2     | Continuing a Directory Scan . . . . .                    | 99         |
| 9.1.3     | Terminating a Directory Scan . . . . .                   | 100        |
| 9.2       | Matching Strings against Patterns . . . . .              | 100        |
| 9.2.1     | Tokenizing a Case-Sensitive Pattern . . . . .            | 100        |
| 9.2.2     | Tokenizing a Case-Insensitive Pattern . . . . .          | 101        |
| 9.2.3     | Match a String against a Pattern . . . . .               | 101        |
| 9.2.4     | Match a String against a Pattern ignoring Case . . . . . | 101        |
| <b>10</b> | <b>Processes</b>   | <b>103</b> |
| 10.1      | Creating and Terminating Processes . . . . .             | 106        |
| 10.1.1    | Creating a New Process from a TagList . . . . .          | 106        |
| 10.1.2    | Create a Process (Legacy) . . . . .                      | 109        |
| 10.1.3    | Terminating a Process . . . . .                          | 109        |
| 10.2      | Process Properties Accessor Functions . . . . .          | 110        |
| 10.2.1    | Retrieve the Process Input File Handle . . . . .         | 110        |
| 10.2.2    | Replace the Input File Handle . . . . .                  | 110        |
| 10.2.3    | Retrieve the Output File Handle . . . . .                | 111        |
| 10.2.4    | Replace the Output File Handle . . . . .                 | 111        |
| 10.2.5    | Retrieve the Error File Handle . . . . .                 | 111        |
| 10.2.6    | Replace the Error File Handle . . . . .                  | 111        |
| 10.2.7    | Retrieve the Current Directory . . . . .                 | 112        |
| 10.2.8    | Replace the Current Directory . . . . .                  | 112        |
| 10.2.9    | Return the Latest Error Code . . . . .                   | 112        |
| 10.2.10   | Setting IoErr . . . . .                                  | 116        |
| 10.2.11   | Select the Console Handler . . . . .                     | 116        |
| 10.2.12   | Select the Default File System . . . . .                 | 116        |
| 10.2.13   | Retrieve the Lock to the Program Directory . . . . .     | 117        |
| 10.2.14   | Set the Program Directory . . . . .                      | 117        |
| 10.2.15   | Retrieve Command Line Arguments . . . . .                | 117        |
| 10.2.16   | Set the Command Line Arguments . . . . .                 | 117        |

|  |            |
|--|------------|
| <b>11 Binary File Structure</b>                            | <b>119</b> |
| 11.1 Executable File Format                                | 120        |
| 11.1.1 HUNK_HEADER   | 122        |
| 11.1.2 HUNK_CODE   | 122        |
| 11.1.3 HUNK_DATA   | 123        |
| 11.1.4 HUNK_BSS  | 123        |
| 11.1.5 HUNK_RELOC32  | 124        |
| 11.1.6 HUNK_RELOC32SHORT                                   | 124        |
| 11.1.7 HUNK_RELRELOC32                                     | 125        |
| 11.1.8 HUNK_NAME   | 125        |
| 11.1.9 HUNK_SYMBOL   | 126        |
| 11.1.10 HUNK_DEBUG   | 127        |
| 11.1.11 HUNK_END   | 128        |
| 11.2 The AmigaDOS Loader                                   | 128        |
| 11.2.1 Loading an Executable                               | 128        |
| 11.2.2 Loading an Executable with Additional Parameters    | 128        |
| 11.2.3 Loading an Executable through Call-Back Functions   | 129        |
| 11.2.4 Unloading a Binary                                  | 130        |
| 11.2.5 UnLoading a Binary through Call-Back Functions      | 130        |
| 11.3 Overlays  | 131        |
| 11.3.1 The Overlay File Format                             | 131        |
| 11.3.2 The Hierarchical Overlay Manager                    | 132        |
| 11.3.3 HUNK_OVERLAY  | 132        |
| 11.3.4 HUNK_BREAK  | 135        |
| 11.3.5 Loading an Overload Node                            | 135        |
| 11.3.6 Loading an Overlay Node through Call-Back Functions | 135        |
| 11.3.7 Unloading Overlay Nodes                             | 136        |
| 11.3.8 Unloading Overlay Binaries                          | 137        |
| 11.3.9 Internal Working of the Overlay Manager             | 137        |
| 11.4 Structures within Hunks                               | 142        |
| 11.4.1 The Version Cookie                                  | 142        |
| 11.4.2 The Stack Cookie                                    | 143        |
| 11.4.3 Runtime binding of BCPL programs                    | 143        |
| 11.5 Object File Format                                    | 145        |
| 11.5.1 HUNK_UNIT   | 146        |
| 11.5.2 HUNK_RELOC16  | 147        |
| 11.5.3 HUNK_RELOC8   | 147        |
| 11.5.4 HUNK_DRELOC32                                       | 148        |
| 11.5.5 HUNK_DRELOC16                                       | 148        |
| 11.5.6 HUNK_DRELOC8  | 148        |
| 11.5.7 HUNK_EXT  | 149        |
| 11.6 Link Library File Format                              | 150        |
| 11.6.1 HUNK_LIB  | 151        |
| 11.6.2 HUNK_INDEX  | 152        |
| <b>12 Handlers, Devices and File Systems</b>               | <b>155</b> |
| 12.1 The DosPacket Structure                               | 155        |
| 12.1.1 Send a Packet to a Handler and Wait for Reply       | 156        |
| 12.1.2 Send a Packet to a Handler Asynchronously           | 157        |
| 12.1.3 Waiting for a Packet to Return                      | 158        |
| 12.1.4 Aborting a Packet                                   | 158        |

|         |  |     |
|---------|--|-----|
| 12.1.5  | Reply a Packet to its Caller . . . . .                             | 158 |
| 12.2    | Implementing a Handler . . . . .                                   | 159 |
| 12.2.1  | Handler Startup . . . . .  | 159 |
| 12.2.2  | Handler Main Processing Loop . . . . .                             | 161 |
| 12.2.3  | Handler Shutdown . . . . .   | 162 |
| 12.3    | Packets for File Interactions . . . . .                            | 162 |
| 12.3.1  | Opening a File for Shared Access . . . . .                         | 163 |
| 12.3.2  | Opening a File for Exclusive Access . . . . .                      | 164 |
| 12.3.3  | Opening or Creating a File for Shared Access . . . . .             | 164 |
| 12.3.4  | Opening a File from a Lock . . . . .                               | 164 |
| 12.3.5  | Closing a File . . . . .   | 165 |
| 12.3.6  | Reading from a File . . . . .                                      | 165 |
| 12.3.7  | Writing to a File . . . . .  | 166 |
| 12.3.8  | Adjusting the File Pointer . . . . .                               | 166 |
| 12.3.9  | Setting the File Size . . . . .                                    | 167 |
| 12.3.10 | Locking a Record of a File . . . . .                               | 167 |
| 12.3.11 | Release a Record of a File . . . . .                               | 168 |
| 12.4    | Packets for Interacting with Locks . . . . .                       | 169 |
| 12.4.1  | Obtaining a Lock . . . . .   | 169 |
| 12.4.2  | Duplicating a Lock . . . . .                                       | 170 |
| 12.4.3  | Finding the Parent of a Lock . . . . .                             | 170 |
| 12.4.4  | Duplicating a Lock from a File Handle . . . . .                    | 171 |
| 12.4.5  | Finding the Parent Directory of a File Handle . . . . .            | 171 |
| 12.4.6  | Creating a new Directory . . . . .                                 | 171 |
| 12.4.7  | Comparing two Locks . . . . .                                      | 172 |
| 12.4.8  | Changing the Mode of a Lock or a File Handle . . . . .             | 172 |
| 12.4.9  | Releasing a Lock . . . . .   | 173 |
| 12.5    | Packets for Examining Objects . . . . .                            | 173 |
| 12.5.1  | Examining a Locked Object . . . . .                                | 173 |
| 12.5.2  | Scanning Directory Contents . . . . .                              | 174 |
| 12.5.3  | Examining Multiple Entries at once . . . . .                       | 175 |
| 12.5.4  | Aborting a Directory Scan . . . . .                                | 177 |
| 12.5.5  | Examining from a File Handle . . . . .                             | 177 |
| 12.6    | Packets for Working with Links . . . . .                           | 178 |
| 12.6.1  | Creating Links . . . . .   | 178 |
| 12.6.2  | Resolving a Soft Link . . . . .                                    | 179 |
| 12.7    | Packets for Adjusting Metadata . . . . .                           | 181 |
| 12.7.1  | Renaming or Moving Objects . . . . .                               | 181 |
| 12.7.2  | Deleting an Object . . . . .                                       | 182 |
| 12.7.3  | Changing the Protection Bits . . . . .                             | 182 |
| 12.7.4  | Setting the Comment to an Object . . . . .                         | 183 |
| 12.7.5  | Setting the Creation Date of an Object . . . . .                   | 183 |
| 12.7.6  | Setting the Owner of an Object . . . . .                           | 184 |
| 12.8    | Packets for Starting and Canceling Notification Requests . . . . . | 185 |
| 12.8.1  | Registering a Notification Request . . . . .                       | 185 |
| 12.8.2  | Canceling a Notification Request . . . . .                         | 186 |
| 12.9    | Packets Operating on Entire Volumes . . . . .                      | 186 |
| 12.9.1  | Determining the Currently Inserted Volume . . . . .                | 187 |
| 12.9.2  | Retrieving Information on a Volume from a Lock . . . . .           | 187 |
| 12.9.3  | Retrieving Information on the Currently Inserted Volume . . . . .  | 188 |
| 12.9.4  | Relabeling a Volume . . . . .                                      | 188 |





|           |   |            |
|-----------|---|------------|
| 12.9.5    | Initializing a New File System . . . . .                  | 189        |
| 12.9.6    | Inhibiting the File System . . . . .                      | 190        |
| 12.9.7    | Write Protecting a Volume . . . . .                       | 190        |
| 12.9.8    | Adjusting the File System Cache . . . . .                 | 191        |
| 12.9.9    | Check if a Handler is a File System . . . . .             | 191        |
| 12.9.10   | Write all Pending Modifications . . . . .                 | 192        |
| 12.10     | Packets for Interactive Handlers . . . . .                | 192        |
| 12.10.1   | Waiting for Input Becoming Available . . . . .            | 193        |
| 12.10.2   | Setting the Line Buffer Mode . . . . .                    | 193        |
| 12.11     | The Console-Handler . . . . .                             | 194        |
| 12.12     | The Port-Handler . . . . .                                | 195        |
| <b>13</b> | <b>The AmigaDOS Shell</b>                                 | <b>197</b> |
| 13.0.1    | Start Programs in a Shell . . . . .                       | 197        |
| 13.0.2    | Executing a Program in a Shell (Legacy) . . . . .         | 197        |
| 13.0.3    | Retrieving the CLI . . . . .                              | 197        |
| 13.0.4    | Obtaining the Name of the Current Directory . . . . .     | 197        |
| 13.0.5    | Set the Current Directory Name . . . . .                  | 198        |
| 13.0.6    | Obtaining the Current Program Name . . . . .              | 198        |
| 13.0.7    | Set the Current Program Name . . . . .                    | 198        |
| 13.0.8    | Obtaining the Shell Prompt . . . . .                      | 198        |
| 13.0.9    | Setting the Shell Prompt . . . . .                        | 198        |
| 13.0.10   | Runs a Command Overloading the Calling Process . . . . .  | 198        |
| 13.0.11   | Finding a Shell . . . . .                                 | 198        |
| 13.0.12   | Retrieve the Size of the Shell Process Table . . . . .    | 199        |
| 13.0.13   | Request a Function of the Shell . . . . .                 | 199        |
| 13.0.14   | Read a Shell Variable . . . . .                           | 199        |
| 13.0.15   | Setting a Shell Variable . . . . .                        | 199        |
| 13.0.16   | Finding a Shell Variable . . . . .                        | 199        |
| 13.0.17   | Deleting a Shell Variable . . . . .                       | 199        |
| 13.1      | Parsing Arguments . . . . .                               | 199        |
| 13.1.1    | Parsing Command Line Arguments . . . . .                  | 199        |
| 13.1.2    | Reading a Single Argument from the Command Line . . . . . | 200        |
| 13.1.3    | Finding an Argument . . . . .                             | 200        |
| 13.1.4    | Releasing the Argument Parser . . . . .                   | 200        |
| 13.1.5    | Initializing a new Shell . . . . .                        | 200        |
| 13.1.6    | Finding a Resident Command . . . . .                      | 200        |
| 13.1.7    | Adding a Resident Command . . . . .                       | 200        |
| 13.1.8    | Removing a Resident Command . . . . .                     | 200        |
| 13.2      | Miscellaneous Functions . . . . .                         | 201        |
| 13.2.1    | Allocating a DOS Object . . . . .                         | 201        |
| 13.2.2    | Releasing a DOS Object . . . . .                          | 201        |
| 13.2.3    | Checking for Signals . . . . .                            | 201        |
| 13.2.4    | Display an Error Requester . . . . .                      | 201        |
| 13.2.5    | Generating an Error Message . . . . .                     | 201        |
| 13.2.6    | Printing an Error Message . . . . .                       | 201        |
| 13.2.7    | Printing a String to the Error Stream . . . . .           | 202        |
| 13.2.8    | Receive Information when a Volume is Request . . . . .    | 202        |



---

# Chapter 1

## Introduction

### 1.1 Purpose

The purpose of this manual is to provide a comprehensive documentation of the AmigaDOS subsystem of the Amiga Operation System. This subsystem is represented by the *dos.library*, and it provides services around files, file systems and stream-based input and output. While the Amiga ROM Kernel Reference Manuals [7] document major parts of the AmigaOs, they do not include a volume on AmigaDOS itself. This is due to the history of AmigaDOS which is nothing but a port of the TRIPOS to the Amiga, and thus its documentation became available as the AmigaDOS manual[1] separately. This book itself is, similar to AmigaDOS, based on the TRIPOS manual which has been augmented and updated to reflect the changes that were necessary to fit TRIPOS into AmigaOs. Unfortunately, the book is hard to obtain, and also leaves a lot to deserve.

Good third party documentation is available in the form of the Guru Book[10], though this source is out of print and even harder to obtain. It covers also other aspects of AmigaOs that go beyond AmigaDOS such that its focus is a bit different than this work.

This work attempts to fill this gap by providing a comprehensive and complete documentation of the AmigaDOS library and its subsystems in the style of the ROM Kernel Reference Manuals.

### 1.2 Language and Type Setting Conventions

The words *shall* and *shall not* indicate normative requirements software shall or shall not follow or in order to satisfy the interface requirements of AmigaOs. The words *should* and *should not* indicate best practise and recommendations that are advisable, but not strictly necessary to satisfy a particular interface. The word *may* provides a hint to a possible implementation strategy.

The word *must* indicates a logical consequence from existing requirements or conditions that follows necessarily without introducing a new restriction, such as in “if *a* is 2, *a + a must* be 4”.

**|** *Worth to remember!* Important aspects of the text are indicated with a bold vertical bar like this.

Terms are indicated in *italics*, e.g. the *dos.library* implements interface of *AmigaDOS*. Data structures and components of source code are printed in `courier` in fixed-width font, reassembling the output of a terminal, e.g.

```
typedef unsigned char UBYTE; /* an 8-bit unsigned integer */
typedef long LONG;          /* a 32-bit integer          */
```



---

## Chapter 2

# Elementary Data Types

### 2.1 The dos.library

*AmigaDOS* as part of the *Amiga Operating System* or short *AmigaOs* is represented by the ROM-based *dos.library*. This library is typically opened by the startup code of most compilers anyhow, and its base pointer is placed into `DOSBase` by this startup code:

```
struct DosLibrary *DOSBase;
```

Hence, in general, there is no need to open this library manually.

The structure *struct DosLibrary* is defined in `dos/dosextens.h`, but its layout and its members are usually not required and should rather not be accessed directly. Instead, the library provides accessor functions to read many objects contained within it.

If you do not link with compiler startup code, the base pointer of the *dos.library* can be obtained similar to that of any other library:

```
#include <proto/exec.h>
#include <proto/dos.h>
#include <exec/libraries.h>
#include <dos/dos.h>

...
if ((DOSBase = (struct DosLibrary *) (OpenLibrary(DOSNAME, 47))) {
    ...
    CloseLibrary((struct Library *)DOSBase);
}
```

Unlike many other operating system, the *dos.library* does not manage disks or files itself, neither does it provide access to hardware interface components. It rather implements a *virtual file system* which forwards requests to its subsystems, called *handlers* or *file systems*, see 2.8.

### 2.2 Booleans

AmigaDOS uses a somewhat different convention for booleans, i.e. truth values defined in the file `dos/dos.h`:

**Table 1: DOS Truth Values**

| Define   | Value |
|----------|-------|
| DOSFALSE | 0     |
| DOSTRUE  | -1    |

---

Note that the C language instead uses the value 1 for TRUE. Code that checks for zero or non-zero return codes will function normally, however code shall not compare to TRUE in boolean tests.

## 2.3 Pointers and BPTRs

AmigaDOS is a descendent of the *TRIPOS* system and as such originally implemented in the BCPL language. As of Kickstart 2.0, AmigaDOS was re-implemented in C and assembler, but this implementation had to preserve the existing interface based on BCPL conventions.

BCPL is a typeless language that structures the memory of its host system as an array of 32-bit elements enumerated contiguously from zero up. Rather than pointers, BCPL communicates the position of its data structures in the form of indices of the first 32-bit element of such structures. As each 32-bit group is assigned its own index, one can obtain this index by dividing the byte-address of an element by 4, or equivalently, by right-shifting the address by two bits. This has the consequence that (most) data structures passed into and out of the `dos.library` shall be aligned to 32-bit boundaries. Similarly, in order to obtain the byte-address of a BPCL structure, the index is multiplied by 4, or left-shifted by 2 bits.

**Not on the Stack!** Since BPCL structures must have an address that is divisible by 4, you should not keep such structures on the stack as the average compiler will not ensure long word alignment for automatic objects. In the absense of a dedicated constructor function such as *AllocDosObject()*, a safe strategy is use the `exec.library` memory allocation functions such as *AllocMem()* or *AllocVec()* to obtain memory for holding them.

These indices are called *BCPL pointers* or short *BPTRs*, even though they are not pointers in the sense of the C language, but rather integer numbers as indices to an array of LONG (i.e. 32-bit) integers. In order to communicate this fact more clearly, the `dos/dos.h` include file defines the following data type:

```
typedef long BPTR; /* Long word pointer */
```

Conversion from BCPL pointers to conventional C pointers and back are formed by the following macros, also defined in `dos/dos.h`:

```
/* Convert BPTR to typical C pointer */
#define BADDR(x) ((APTR) ((ULONG) (x) << 2))
/* Convert address into a BPTR */
#define MKBADDR(x) (((LONG) (x)) >> 2)
```

Luckely, in most cases callers of the *dos.library* do not need to convert from and to BPTRs but can rather use such “pointers” as *opaque values* or *handles* representing some AmigaDOS objects.

It is certainly a burden to always allocate temporary BCPL objects from the heap, and doing so may also fragment the AmigaOs memory unnecessarily. However, allocation of automatic objects from the stack does not ensure long-word alignment in general. To work around this burden, one can use a trick and instead request from the compiler a somewhat longer object of automatic lifetime and align the requested object manually within the memory obtained this way. The following macro performs this trick:

```
#define D_S(type,name) char a_##name[sizeof(type)+3]; \
                        type *name = (type *) ((ULONG) (a_##name+3) & ~3UL)
```

It is used as follows:

```
D_S (struct FileInfoBlock, fib);
```

At this point, `fib` is pointer to a properly aligned `struct FileInfoBlock`, e.g. this is equivalent to

```
struct FileInfoBlock _tmp;
struct FileInfoBlock *fib = &tmp;
```

except that the created pointer is properly aligned and can safely be passed into the *dos.library*.

Similar to the C language, a pointer to a non-existing element is expressed by the special pointer value 0. While this is called the NULL pointer in C, it is better to reserve another name for it in BCPL as its pointers are rather indices. The following convention is suggested to express an invalid *BPTR*:

```
#define ZERO 0L
```

Clearly, with the above convention, the BCPL ZERO pointer converts to the C NULL pointer and back, even though the two are conceptionally something different: The first being the index to the first element of the host memory array, the later the pointer to the first address.

## 2.4 C Strings and BSTRs

While the C language defines *strings* as 0-terminated arrays of `char`, and AmigaOs in particular to 0-terminated arrays of `UBYTE`s, that is, unsigned characters, the BCPL language uses a different convention, namely that of a `UBYTE` array whose first element contains the size of the string to follow. They are not necessarily 0-terminated either. If BCPL strings are passed into BCPL functions, or are part of BCPL data structures, then typically in the form of a *BPTR* to the 32-bit element containing the size of the string its 8 most significant bits. The include file `dos/dos.h` provides its own data type for such strings:

```
typedef long BSTR; /* Long word pointer to BCPL string */
```

Luckely, functions of the *dos.library* take C strings as arguments and perform the conversion from C strings to their BCPL representation as *BSTR*s internally, such that one rarely gets in contact with this type of strings. They appear as part of some AmigaDOS structures to be discussed, and as part of the interface between the *dos.library* and its handlers, e.g. file systems. However, even though users of the *dos.library* rarely come in contact with *BSTR*s themselves, the *BCPL* convention has an important consequence, namely that (most) strings handled by the *dos.library* cannot be longer than 255 characters as this is the limit imposed by the BCPL convention.

**Length-Limited Strings** Remember that most strings that are passed into the *dos.library* are internally converted to *BSTR*s and thus cannot exceed a length of 255 characters.

Unfortunately, even as of the latest version of *AmigaDos*, the *dos.library* is ill-prepared to take longer strings, and will likely fail or mis-interpret the string passed in. If longer strings are required, e.g. as part of a *path*, it is (unfortunately) in the responsibility of the caller to take this path appart into components and iterate through the components manually, see also section ??.

## 2.5 Files

Files are streams of bytes together with a file pointer that identifies the next position to be read, or the next byte position to be filled. Files are explained in more detail in section 4.

## 2.6 Locks

Locks are access rights to a particular object on a file system. A locked object cannot be altered by any other process. Section 12.9.7 provides more details on locks.

---

## 2.7 Processes

AmigaDOS is a multi-tasking system operating on top of the *exec* kernel [7]. As such, it can operate multiple tasks at once, where the tasks are assigned to the CPU in a round-robin fashion. A *Process* is an extension of an AmigaOs *Task* that includes additional state information relevant to AmigaDOS, such as a *current directory* *Current Directory* it operates in, a *default file system*, a *console* it is connected to, and default input, output and error streams. Processes are explained in more detail in section 10.

## 2.8 Handlers and File Systems

*Handlers* are special processes that manage files on a volume, or that input or output data to a physical device. AmigaDOS itself delegates all operations on files to such handlers. Handlers are introduced in section ??.

*File systems* are special handlers that organize the contents of data carriers such as hard disks, floppies or CD-Roms in the form of files and directories, and provides access to such objects through the *dos.library*. File systems interpret paths (see 4.3) in order to locate objects such as files and directories on such data carriers.



---

## Chapter 3

# Date and Time

Due to its history, AmigaOs uses two incompatible representations of date and time. The `timer.device` represents a date as the number of seconds and microseconds since January 1<sup>st</sup> 1978. As AmigaDOS is based on TRIPOS as an independently developed operating system, the *dos.library* uses a different representation as `DateStamp` structure defined in `dos/dos.h`:

```
struct DateStamp {
    LONG    ds_Days;
    LONG    ds_Minute;
    LONG    ds_Tick;
};
```

The elements of this structure are as follows:

`ds_Days` counts the number of days since January 1<sup>st</sup> 1978.

`ds_Minute` counts the number of minutes past midnight, i.e. the start of the day.

`ds_Tick` counts the ticks since the start of the minute. The number of ticks per second is defined as `TICKS_PER_SECOND` in `dos/dos.h`.

***Ticking 50 Times a Second*** A system “tick” is always 1/50<sup>th</sup> of a second, regardless whether the system is an NTSC or PAL system. AmigaDOS detects the clock basis during setup and will scale times appropriately such that the definition of the “tick” is independent of the clocking of the system or the monitor refresh frequency.

### 3.1 Elementary Time and Date Functions

The functions in this section obtain the current system time, compare two times, or delay the system for a given time. They represent times — and dates if appropriate — in the `DateStamp` structure as a triple of days, minutes and ticks.

#### 3.1.1 Obtaining the Time and Date

The `DateStamp()` function obtains the current date and time from AmigaDOS:

```
ds = DateStamp( ds );
D0          D1
```

```
struct DateStamp *DateStamp(struct DateStamp *)
```

---

This function retrieves the current system time and fills it into a `DateStamp` structure pointed to by `ds`. It also returns a pointer to the structure passed in. This function cannot fail.

Unlike many other *dos.library* functions, there is no requirement to align `ds` to a long-word boundary.

### 3.1.2 Comparing two Times and Dates

The `CompareDates()` function compares two dates as given by `DateStamp` function and returns an indicator which of the dates are earlier.

```
result = CompareDates(date1, date2)
D0                      D1      D2

LONG CompareDates(struct DateStamp *, struct DateStamp *)
```

This function takes two pointers to `DateStamp` structures as `date1` and `date2` and returns a negative number if `date1` is later than `date2`, a positive number if `date2` is later than `date1`, or 0 if the two dates are identical.

### 3.1.3 Delaying Program Execution

The `Delay()` function delays the execution of the calling process by a specific amount of ticks.

```
Delay( ticks )
      D1

void Delay(ULONG)
```

This function suspends execution of the calling process by `ticks` AmigaDOS ticks. The delay is system-friendly and does not burn CPU cycles; instead, the process is suspended from the CPU the indicated amount of time, making it available for other processes. Thus, this function is the preferred way of delaying program execution. A tick is 1/50<sup>th</sup> of a second.

AmigaDOS variants below version 36 could not handle delays of 0 appropriately.

## 3.2 Conversion Into and From Strings

Functions in this section convert date and time in the (binary) AmigaDOS representation to human-readable strings, and in the reverse direction. Both the input and output of these functions are kept in the `DateTime` structure that is defined in `dos/datetime.h` and reads as follows:

```
struct DateTime {
    struct DateStamp dat_Stamp;
    UBYTE   dat_Format;
    UBYTE   dat_Flags;
    UBYTE   *dat_StrDay;
    UBYTE   *dat_StrDate;
    UBYTE   *dat_StrTime;
};
```

`dat_Stamp` contains the input or output date represented as a `DateStamp` structure.

`dat_Format` defines the format of the date string to create, and the order in which days, months and years appear within the string. The following formats are available, all defined in `dos/datetime.h`:

**Table 2: Date formatting options**

| Format Definition | Description                  |
|-------------------|------------------------------|
| FORMAT_DOS        | The AmigaDOS default format  |
| FORMAT_INT        | International (ISO) format   |
| FORMAT_USA        | USA date format              |
| FORMAT_CDN        | Canadian and European format |

FORMAT\_DOS represents the date as day of the month in two digits, followed by the month as three-letter abbreviation, followed by a two-digit year counting from the start of the century. An example of this formatting is 30-Sep-23.

FORMAT\_INT starts with a two-digit year, followed by the month represented as two digits starting from 01 for January, followed by two digits for the day of the month. An example of this string is 23-09-30.

FORMAT\_USA places the month first, encoded as two numerical digits, followed by two digits of the day of the month, followed by two digits of the year. An example of this formatting is 09-30-23.

FORMAT\_CDN follows the European convention and places the day of the month first, followed by the month represented as two numerical digits, followed by the year as two digits.

dat\_Flags defines additional flags that control the conversion process. They are also defined in `dos/datetime.h`:

**Table 3: Date conversion flags**

| Flag       | Description   |
|------------|---|
| DTF_SUBST  | Substitute dates by relative description if possible    |
| DTF_FUTURE | Reference direction for relative dates is to the future |

The include file `dos/datetime.h` defines in addition also bit numbers for the above flags that start with DTB instead of DTF. The meaning of these flags are as follows:

DTF\_SUBST allows, if set, the conversion to substitute dates nearby today's date by descriptions relative to today. This flag is only honored when converting a time and date in AmigaDOS representation to human-readable strings. In particular, the following substitutions are made:

If the date provided is identical to the system date, the output date is set to "Today".

If the date is one day later than the current system date, the output date is set to "Tomorrow".

If the date is one day before the current system date, the output date is set to "Yesterday".

If the date is in the past week, the function substitutes it by the name of the day of the week, e.g. "Saturday".

DTF\_FUTURE is only honored when converting a string to the AmigaDOS representation, that is into `DateStamp` structure. It indicates whether weekdays such as "Monday" are interpreted as dates in the past, i.e. "last Monday", or as dates in the future, i.e. "next Monday". If the flag is cleared, weekdays are interpreted as being in the past, same as the `DateToStr()` function would generate them. If the flag is set, weekdays are assumed as references into the future.

`dat_StrDay`: This buffer is only used by converting `DateStamps` to strings, and — if present — is then filled by the week of the day, e.g. "Saturday".

`dat_StrDate`: This element points to a buffer that is either filled with the human-readable date, or is input to the conversion then containing a human-readable date. The buffer is formatted, or expected to be formatted according to `dat_Format` and `dat_Flags`.

`dat_StrTime`: This element points to a buffer that is either filled with a human-readable time, or is the input time to be converted. AmigaDOS expects here a 24h clock, hours, minutes and seconds in this order, separated by colon, e.g. 21:47:16.

The functions in this section are patched by the *locale.library* once it is loaded, and then replaced the English strings by the corresponding localized output. The localized versions may also accept (or provide) different formats, such as four-digit years.

---

### 3.2.1 Converting a Time and Date to a String

The `DateToStr()` function converts a date and time into a human readable string. The date and time, as well as formatting instructions are given by a `DateTime` structure.

```
success = DateToStr( datetime )
D0                      D1
```

```
BOOL DateToStr(struct DateTime *)
```

This function takes the date and time in the AmigaDOS binary representation contained in `dat_Stamp` of the passed in `DateTime` structure introduced in section 3.2 and converts it into human readable strings. The elements of this structure shall be populated as follows:

`dat_Stamp` shall be initialized to the date and time to be converted.

`dat_Format` defines the format of the date string to create. It shall be a value from table 2.

`dat_Flags` defines additional flags that control the conversion process. This function only honors the `DTF_SUBST` flag which indicates that `DateToStr()` is supposed to represent the date relative to the current system date if possible. That is, if possible, the date is represented as “today”, “tomorrow”, “yesterday” or a weekday. Week days always correspond to past days, e.g. “Friday” corresponds to the past Friday, not a day in the future.

`dat_StrDay`: If this pointer is non-NULL, it shall point to a string buffer at least `LEN_DATSTRING` bytes large into which the day of the week is filled, e.g. “Saturday”.

`dat_StrDate`: If this pointer is non-NULL, it shall also point to a string buffer at least `LEN_DATSTRING` bytes large. This buffer will then be filled by a description of the date according to the format in `dat_Format` and `dat_Flags`.

`dat_StrTime`: This buffer, if the pointer is non-NULL, is filled by the time of the day, using a 24h clock. The format is always hours, minutes, seconds, separated by colon.

This function is patched by the *locale.library* once it is loaded, and then replaced the English output by the corresponding localized output.

The function returns 0 on error; the only source of error here is if `dat_Stamp` is invalid, e.g. the number of minutes is larger than  $60 \times 24$  or the number of ticks is larger than  $50 \times 60$ . This makes this function probably unsuitable to handle leap seconds correctly. This function does not touch `IoErr()`, even in case of failure.

### 3.2.2 Convert a String to a Date and Time

The `StrToDate()` function converts a date from a human-readable string to its binary AmigaDOS representation.

```
success = StrToDate( datetime )
D0                      D1
```

```
BOOL StrToDate( struct DateTime *)
```

This function takes a `DateTime` structure as defined in section 3.2 and converts the date and time strings in this structure to a `DateStamp` structure in `dat_Stamp`. In particular, the elements of the `DateTime` shall be initialized as follows:

`dat_DateTime` may remain uninitialized and is rather filled by this function with the converted date. In other words, this element is used to provide the result of this function.

---

`dat_Format` shall be initialized by the format that is used by the input date. Table 2 lists the available input formats. In particular, the ROM code within the *dos.library* only accepts two-digit years and interprets the anything between 78 and 99 as 1978 to 1999, and years between 00 and 45 as 2000 to 2045. It refuses all other numbers. However, `StrToDate()` is patched by the *locale.library* whose replacement implementation also accepts four-digit years.

`dat_Flags` shall be initialized by a combination of the flags from table 3. As `StrToDate()` always accepts relative dates such as “yesterday”, the `DTF_SUBST` flag is ignored and only `DTF_FUTURE` is honored. This flag indicates whether weekdays are considered a date in the past or in the future.

`dat_StrDay` is ignored by this function. If a relative date given by a day of a week is to be converted, this weekday goes directly into `dat_StrDate`.

`dat_StrDate`, if it is non-NULL, points to a string describing the date, in the format according to `dat_Format`. If this string is not given, the output date is taken from the system date, i.e. is today’s date.

`dat_StrTime`, if it is non-NULL, points to a human-readable string describing the time of the day. This time shall be formatted as a 24h clock, in the order hours, minutes and seconds, each separated by colon. If this pointer is NULL, the current system time is used.

This function returns non-zero on success, and 0 on error. It does not set `IoErr()` in case of error. Possible errors include ill-formatted input strings the function cannot interpret.

Also note that this function is patched by the *locale.library* once loaded. It adds conventions of the current locale how dates and times are supposed to be formatted. Interpretation of date and time will then follow the conventions of this library.



---

## Chapter 4

# Files

### 4.1 What are Files?

*Files* are streams of sequences of bytes that can be read from and written to, along with a file pointer that points to the next byte to be read, or the next byte to be written or overwritten. Files may have an *End-of-File position*, beyond which the file pointer can not advance when reading bytes from it.

### 4.2 Interactive vs. non-Interactive Files

AmigaDOS knows two types of files: *Interactive* and *non-interactive* files.

*Non-interactive* files are stored on some persistent data carrier; unless modified by a process, the contents of such non-interactive files does not change. They also have a defined *file size*. The file size is the number of bytes between the start of the file and the end-of-file position, or short *EOF position*. This file size does not change unless some process writes to the file, which may or may not be the same process that reads from the file.

Examples for non-interactive files are data on a disk, such as a floppy or a harddisk. Such files have a name, possibly a path within a hierarchical file system, and possibly multiple protection flags that define which type of actions can be applied to a file; such flags define whether the file can be read from, written to, and so on.

*Interactive* files depend on the interaction of the computer system with the outside world, and their contents can change due to such interaction. Interactive files may not define a clear end-of-file position, and an attempt to read from them or write to them may block an indefinite amount of time until triggered by an external event.

Examples for interactive files are the console, where reading from it depends on the user entering data in a console window and output corresponds to printing to the console; or the serial port, where read requests are satisfied by serial data arriving at the serial port and written bytes are transmitted out of the port. The parallel port is another example of an interactive file. Requests to read from it result in an error condition, while writing prints data on a printer connected to the port. Writing may block indefinitely if the printer runs out of paper or is turned off.

### 4.3 Paths and File Names

Files are identified by *paths*, which are strings from which AmigaDOS locates a process through which access to the file is managed. Such a process is called the *Handler* of the file, or, in case of files of on a data

---

carrier, also the *File System*. AmigaDOS itself does not operate on files directly, but delegates such work to its handler.

A *path* is broken up into two parts: An optional device or volume name terminated by a colon (“:”), followed by string that identifies the file within the handler identified by the first part.

The first part, if present, is interpreted by AmigaDOS itself. It relates to the name of a handler (or file system) of the given name, or a known disk volume, or a logical volume of the name within the AmigaDOS *device list*. These concepts are presented in further detail in section 8.

The second, or only part is interpreted by the handler identified by the first part.

### 4.3.1 Devices, Volumes and Assigns

The first part of a path, up to the colon, identifies the device, the volume or the assign a file is located in.

#### 4.3.1.1 Devices

A *device name* identifies the handler or file system directly. Handlers are typically responsible for particular hardware units within the system, for example for the first floppy drive, or the second partition of a harddisk. For example, `df0` is the name of the handler responsible for the first floppy drive, regardless of which disk is inserted into it.

Table 4 lists all devices AmigaDOS mounts itself even without a boot volume available. They can be assumed present any time.

**Table 4: System defined devices**

| Device Name | Description                |
|-------------|----------------------------|
| DF0         | First floppy drive         |
| PRT         | Printer                    |
| PAR         | Parallel port              |
| SER         | Serial port                |
| CON         | Line-interactive console   |
| RAW         | Character based console    |
| PIPE        | Pipeline between processes |
| RAM         | RAM-based file handler     |

If more than one floppy drives are connected to the system, they are named `DF1` through `DF3`. If a hard disk is present, then the device name(s) of the harddisk partitions depend on the contents of Rigid Disk Block, see `??`. These names can be selected upon installation of the harddisks, e.g. through *HDToolBox*. The general convention is to name them `DH0` and following.

The following device names have a special meaning and do not belong to a particular device:

**Table 5: System defined devices**

| Name    | Description                        |
|---------|------------------------------------|
| *       | the console of the current process |
| CONSOLE | the console of the current process |
| NIL     | the data sink                      |

The `NIL` device is a special device without a handler that is maintained by AmigaDOS itself. Any data written into it vanishes completely, and any attempt to read data from it results in an end-of-file condition.

The `*`, if used as complete path name without a trailing colon, is the current console of the process, if such a console exists. Any data output to the file named `*` will be printed on the console. Any attempt to read from `*` will wait on the user to input data on the console, and will return such data.



---

**Not a wildcard!** Unlike other operating systems, the asterisk `*` is *not* a wildcard under AmigaDOS. It rather identifies the current console of a process, or is used as escape character in AmigaDOS shell scripts

The `CONSOLE` device is the default console of the process. Unlike `*`, but like any other device name, it shall be followed by a colon, and an optional job name. Such job names form *logical consoles* that are used by the shell for job control purposes.

**Prefer the stars** The difference between `*` and `CONSOLE` is subtle, and the former should be preferred as it identifies the process as part of a particular shell job. An attempt to output to `CONSOLE:` may block the current process as it does not identify it properly as part of its job, but rather denotes the job started when creating the shell. Thus, in case of doubt, use the `*` without any colon if you mean the console.

Additional devices can be loaded into the system by the *Mount* command, see section ??.

#### 4.3.1.2 Volumes

A *volume name* identifies a particular data carrier within a physical drive. For example, it may identify a particular floppy disk, regardless of the drive it is inserted in. For example, the volume name “Workbench3.2” relates always to the same floppy, regardless of whether it is inserted in the first `df0` or second `df1` drive.

#### 4.3.1.3 Assigns

An *assign* or *logical volume* identifies a subset of a files within a file system under a unique name. Such assigns are created by the system or by the user helping to identify portions of the file system containing files that are of particular relevance for the system. For example, the assign `C` contains all commands of the boot shell, and the assign `LIBS` contains dynamically loadable system libraries. Such assigns can be changed or redirected, and by that the system can be instructed to take system resources from other parts of a file system, or entirely different file systems.

Assigns can be of three types: *Regular assigns*, *non-binding assigns* and *late assigns*. *Regular assigns* bind to a particular directory on a particular volume. If the *assign* is accessed, and the original volume the bound directory is not available, the system will ask to insert this particular volume, and no other volume will be accepted.

*Regular assigns* can also bind to multiple directories at once, in which case a particular file or directory within such a *multi-assign* is searched in all directories bound to the assign. A particular use case for this is the `FONTS` assign, containing all system-available fonts. Adding another directory to `FONTS` makes additional fonts available to the system without losing the original ones.

*Regular assigns* have the drawback that the volume remains known to the system, and the corresponding volume icon will not vanish from the workbench. They also require the volume to be present at the time the assign is created.

*Non-binding assigns* avoid these problems by only storing the symbolic path the assign goes to; whenever the assign is accessed, any volume of the particular name containing the particular path will work. However, if this also implies that the target of the assign is not necessarily consistent, i.e. if the assign is accessed later on, another volume with different content will be accepted by the system.

*Late assigns* are a compromise between *regular assigns* and *non-binding assigns*. AmigaDOS initially only stores a target path for the assign, but when the assign is accessed the first time, the assign is converted to a *regular assign* and thus then binds to the particular directory of the particular volume that was inserted at the time of the first access.

Table 6 lists the assigns made by AmigaDOS automatically during bootstrap; except for the `SYS` assign, they all go to a directory of the same name on the boot volume. They are all *regular assigns*, except for `ENVARC`, which is *late assign*.

**Table 6: System defined assigns**

| Assign Name | Description                        |
|-------------|------------------------------------|
| C           | Boot shell commands                |
| L           | AmigaDOS handlers and file systems |
| S           | AmigaDOS Scripts                   |
| LIBS        | AmigaOs libraries                  |
| DEVS        | AmigaOs hardware drivers           |
| FONTS       | AmigaOs fonts                      |
| ENVARC      | AmigaOs preferences (late)         |
| SYS         | The boot volume                    |

In addition to the above table, the following assigns are handled by AmigaDOS internally and are not part of the *device list*, (see section 8):

**Table 7: System defined assigns**

| Assign Name | Description                |
|-------------|----------------------------|
| PROGDIR     | Location of the executable |

Thus, PROGDIR is the directory the currently executed binary was loaded from. Note that PROGDIR does not exist in case an executable file was not loaded from disk, probably because it was either taken from ROM or was made resident. More on resident executables is found in section ??.

Additional assigns can become necessary for a fully operational system, though these assigns are created through the *Startup-sequence*, a particular AmigaDOS script residing in the S assign which is executed by the boot shell. Table 8 lists some of them.

**Table 8: Assigns made during bootstrap**

| Assign Name | Description   |
|-------------|---|
| ENV         | Storage for active preferences and global variables |
| T           | Storage for temporary files                         |
| CLIPS       | Storage for clipboard contents                      |
| KEYMAPS     | Keymap layouts                                      |
| PRINTERS    | Printer drivers                                     |
| REXX        | ARexx scripts                                       |
| LOCALE      | Catalogs and localization                           |

Additional assigns can always be made with the *Assign* command, see section ??.

### 4.3.2 Relative and Absolute Paths

As introduced in section 4.3, a path consists either of an device, volume or assign name followed by a colon followed by a second part, or the second part alone. If a device, volume or assign name is present, such a path is said to be an *absolute path* because it identifies a location within a logical or physical volume.

If no first part is present, or if it is empty, i.e. the colon is the first part of the path, AmigaDOS uses information from the calling process to identify a suitable handler. Details on this are provided in section 10. Such a path is called a *relative path*.

This second part is forwarded to the handler and is not interpreted by the *dos.library*. It is then within the responsibility of the handler to interpret this path and locate a file within the data carrier it manages, or to configure an interface to the outside world according to this path.

In general, the *dos.library* does not impose a particular syntax on how this second part looks like. However, several support functions of AmigaDOS implicitly define conventions file systems should follow to make these support functions workable and it is therefore advisable for file system implementors to follow these conventions.

---

### 4.3.3 Maximum Path Length

The *dos.library* does not enforce a limit on the size of file or directory names, except that the total length of a path including all of its components shall not be larger than 255 characters. This is because it is converted to a BSTR within the *dos.library*. How large a component name can be is a matter of the file system itself. The *Fast File System* includes variants that limit file names to 30, 56 or 106 characters.

File systems typically do not report an error if the maximum file name is exceeded; instead, the name is clamped to the maximum size without further notice, which may lead to undesired side effects. For example, a file system may clip or remove a trailing `.info` from a workbench icon file name without ever reporting this, resulting in unexpected side effects. The *icon.library* and *workbench.library* of AmigaOs take care to avoid such file names and double check created objects for correct names.

### 4.3.4 Flat vs. Hierarchical File Systems

?? A flat file system organizes files as a single list of all files available on a physical data carrier. For large amounts of files, such a representation is clearly burdensome as files may be hard to find and hard to identify.

For this reason, all file systems provided by AmigaOs are *hierarchical* and organize files in nested sets of *directories*, where each directory contains files or additional directories. The topmost directory of a volume forms the *root directory* of this volume.

While AmigaDOS itself does not enforce a particular convention, all file systems included in AmigaDOS follow the convention that a path consists of a sequence of zero or more directory names separated by a forwards slash (“/”), and a final file or directory name.

#### 4.3.4.1 Locating Files or Directories

When attempting to locate a particular file or directory, the *dos.library* first checks whether an absolute path name is present. If so, it starts from the root directory on the device, physical or logical volume identified by the device or volume name and delegates the interpretation of the path to the handler.

Otherwise, it uses the *current directory* of the calling process to locate a handler responsible for the interpretation of the path name. If this current directory is `ZERO` (see section 2.3), it uses the *default file system* of the process, which by itself, defaults to the boot file system.

The second part of the path interpretation is up to the file system identified by the first step and is performed there, outside of the *dos.library*. If the path name includes a colon (“:”), then locating a file starts from the root of the inserted volume. This also includes the special case of an absent device or volume name, though a present colon, i.e. “:” represents the root directory of the volume to which the current directory belongs.

The following paragraphs describe a recommended set of operations an AmigaDOS file system should follow. A path consists of a sequence of components separated by forward slashes (“/”).

To locate a file, the file system should work iteratively through the path, component by component: A single isolated “/” without a preceeding component indicates the parent directory of the current directory. The parent directory of the root directory is the root directory itself.

Otherwise, a component followed by “/” instructs the handler to enter the directory of given by the component, and continue searching there.

Scanning terminates when the file system reaches the last component. The file or directory to find is then the given by the last component reached during the scan.

As scanning through directories starts with the current directory and stops when the end of the path has been reached, the empty string indicates the current directory.

---

**No Dots Here** Unlike other operating systems, AmigaDOS does not use “.” and “..” to indicate the current directory or the parent directory. Rather, the current directory is represented by the empty string, and the parent directory is represented by an isolated forwards slash without a preceeding component.

Thus, for example, “:S” is a file or directory named “S” in the root directory of the current directory of the process, and “//Top/Hi” is a file or directory named “Hi” two directories up from the current directory, in a directory named “Top”.

### 4.3.5 Case Sensitivity

The *dos.library* does not define whether file names are case-sensitive or insensitive, except for the device or volume name which is case-insensitive. Most if not all AmigaDOS file-systems are also case-insensitive, or rather should. Some variants of the *Fast File System* do not handle case-insensitive comparisons correctly on non-ASCII characters, i.e. ISO-Latin code points whose most-significant bit is set, see section ?? for details. These variants should be avoided and the “international” variants should be preferred.

## 4.4 Opening Files

To read data from or write data to a file, it first needs to be opened by the `Open()` function:

```
file = Open( name, accessMode )  
D0          D1      D2  
  
BPTR Open(STRPTR, LONG)
```

The `name` argument is the *path* the file to be opened, which is interpreted according to the rules given in section 4.3. The argument `accessMode` identifies how the file is opened. The function returns a BPTR to a *file handle* on success, or `ZERO` on failure. A secondary return code can be retrieved from `IoErr()` described in section ?. It is 0 on success, or an error code from `dos/dos.h` in case opening the file failed.

The access mode shall be one of the following, defined in `dos/dos.h`:

**Table 9: Access Modes for Opening Files**

| Access Name    | Description                            |
|----------------|--|
| MODE_OLDFILE   | Shared access to existing files        |
| MODE_READWRITE | Shared access to new or existing files |
| MODE_NEWFILE   | Exclusive access to new files          |

**Length Limited** As this function needs to convert the path argument from a C string to a BSTR, path names longer than 255 characters are not supported and results are unpredictable if such names are passed into `Open()`. If such long path names cannot be avoided, it is the responsibility of the caller to split the path name accordingly and potentially walk through the directories manually if necessary. Note that this strategy may not be suitable for interactive files or handlers that follow conventions for the path name that are different from the conventions described in section 4.3.4.1.

The access mode `MODE_OLDFILE` attempts to find an existing file. If the file does not exist, the function fails. If the file exists, it can be read from or written from, though simultaneous access from multiple processes is possible and does not create an error condition. If multiple processes write to the same file simultaneously, the result is undefined and no particular order of the write operations is imposed.

---

The access mode `MODE_READWRITE` first attempts to find an existing file, but if the file does not exist, it will be created under the name given by the last component of the path. The function does not attempt to create directories within the path if they do not exist. Once the file is opened, access to the file is shared, even if it has been just created. That is, multiple processes may then access it for reading or writing. If multiple processes write to the file simultaneously, the order in which the writes are served is undefined and depends on the scheduling of the processes.

The access mode `MODE_NEWFILE` creates a new file, potentially erasing an already existing file of the same name if it already exists. The function does not attempt to create directories within the path if they do not exist. Access to the file is exclusive, that is, any attempt to access the file from a second process fails with an error condition.

**No Wildcards** The `Open()` function, similar to most *dos.library* functions, does not attempt to resolve wild cards. That is, any character potentially reassembling a wild card, such as “?” or “#” will be taken as a literal and will be used as part of the file name. While these characters are valid, they should be avoided as they make such files hard to access from the Shell.

## 4.5 Closing Files

The `Close()` function writes all internally buffered data to disk and makes an exclusively opened file accessible to other processes again.

```
success = Close( file )
D0                      D1
```

```
BOOL Close(BPTR)
```

The `file` is a `BPTR` to a *FileHandle* identifying the file. The return code indicates whether the file system could successfully close the file and write back any data. If the result code is `DOSFALSE`, an error code can be obtained through `IoErr()` described in section ???. Otherwise, `IoErr()` will not be altered.

Unfortunately, not much can be done if closing a file fails and no general advice is possible how to handle this situation.

Attempting to close the `ZERO` file handle returns success immediately.

## 4.6 Types of Files and Handlers

As introduced in 4.2, AmigaDOS distinguishes between non-interactive files managed by file systems and interactive files that interact with the outside world. Typically, *file systems* create non-interactive files; all other *handlers* create interactive or non-interactive files, depending on the nature of the handler.

### 4.6.1 Obtaining the Type from a File

A file can be either interactive, in which case attempts to read or write data to the file may block indefinitely, or non-interactive where the amount of available data is determined by file itself. The `IsInteractive()` function returns the nature of an already opened file.

```
status = IsInteractive( file )
D0                      D1
```

```
BOOL IsInteractive(BPTR)
```

---

The `IsInteractive()` function returns `TRUE` in case the *file handle* passed in is interactive, or `FALSE` in case it corresponds to a non-interactive stream of bytes, potentially on a file system. This function cannot fail and does not alter `IoErr()`.

## 4.6.2 Obtaining the Type from a Path

A *handler* that manages physical data carriers and allows to access named files on such data carriers is a *file system*. The `IsFileSystem()` function determines the nature of a handler given a path (see 4.3) to a candidate handler.

```
result = IsFileSystem(name)
D0                                     D1
```

```
BOOL IsFileSystem(STRPTR)
```

The `name` argument is a path that does not need to identify a physically existing object. Instead, it is used to identify a handler that would be responsible to such a hypothetical object regardless whether it exists or not.

It is of advisable to provide a path that identifies the handler uniquely, i.e. a string that is terminated by a colon (":"). Otherwise, the call checks whether the *handler* responsible for the current directory of the calling process is a file system.

The returned result is `DOSTRUE` in case the handler identified by the path is a file system, and as such allows access to multiple files on a physical data carrier and examining directories. Otherwise, it returns `DOSFALSE`.

## 4.7 Unbuffered Input and Output

The functions described in this section read bytes from or write bytes to already opened files. These functions are *unbuffered*, that is, any request goes directly to the handler. Since a request performs necessarily a task switch from the caller to the handler managing the file, these functions are inefficient on small amounts of data and should be avoided. Instead, files should be read or written in larger chunks, either by buffering data manually, or by using the buffered I/O functions described in section ??.

### 4.7.1 Reading Data

The following function reads data from an opened file by directly invoking the handler for performing the read:

```
actualLength = Read( file, buffer, length )
D0                                     D1      D2      D3
```

```
LONG Read(BPTR, void *, LONG)
```

The `Read()` function reads `length` bytes from an opened file identified by the *file handle* `file` into the buffer pointed to by `buffer`. The buffer is a standard C pointer, not a `BPTR`.

The return code `actualLength` is the amount of bytes actually read, or -1 for an error condition. A secondary return code can be retrieved from `IoErr()` described in section ??. It is 0 on success, or an error code from `dos/dos.h` in case reading failed.

The amount of data read may be less data than requested by the `length` argument, either because the *EOF* position has been reached (see section 4.2) for non-interactive files, or because the interactive source is depleted. Note that for interactive files, the function may block indefinitely until data becomes available.

---

### 4.7.2 Testing for Availability of Data

An issue of the `Read` function is that it may block indefinitely on an interactive file if the user does not enter any data. The `WaitForChar()` tests for the availability of a character on an interactive file for limited amount of time and returns if no data becomes available.

```
status = WaitForChar( file, timeout )
D0                      D1      D2
```

```
BOOL WaitForChar(BPTR, LONG)
```

This function waits for a maximum of `timeout` microseconds for the availability of input on `file`. If data is already available, or becomes available within this time, the function returns `DOSTRUE`. Otherwise, the function returns `DOSFALSE`.

A secondary return code can be obtained from `IoErr()`. If it is 0, the handler was able check the availability of a byte from the given file. Otherwise, an error code from `dos/dos.h` indicates failure of the function.

This function requires an interactive file to operate, file systems will typically not implement this function as they do not block.

### 4.7.3 Writing Data

The following call writes an array of bytes unbuffered to a file, interacting directly with the corresponding handler:

```
returnedLength = Write( file, buffer, length )
D0                      D1      D2      D3
```

```
LONG Write (BPTR, void *, LONG)
```

The `Write` function writes `length` bytes in the buffer pointed to by `buffer` to the *file handle* given by the `file` argument. On success, it returns the number of bytes written as `returnedLength`, and advances the file pointer of the file by this amount. Note that this amount of bytes may even be 0 in case the file cannot absorb any more bytes. On error, `-1` is returned.

A secondary return code can be retrieved from `IoErr()` described in section ???. It is 0 on success, or an error code from `dos/dos.h` in case writing failed.

For interactive files, this function may block indefinitely until the corresponding handler is able to take additional data.

### 4.7.4 Adjusting the File Pointer

The `Seek()` adjusts the file pointer of a non-interactive file such that subsequent reading or writing is performed from an alternative position of the file.

```
oldPosition = Seek( file, position, mode )
D0                      D1      D2      D3
```

```
LONG Seek (BPTR, LONG, LONG)
```

This function adjusts the file pointer of `file` relative to the position determined by `mode` by `position` bytes. The value of `mode` shall be one of the following options, defined in `dos/dos.h`:

**Table 10: Seek Modes**

| Mode Name        | Description                                |
|------------------|--|
| OFFSET_BEGINNING | Seek relative to the start of the file     |
| OFFSET_CURRENT   | Seek relative to the current file position |
| OFFSET_END       | Seek relative to the end of the file       |

**Undefined on Interactive Files** The `Seek` function will typically indicate failure if applied to interactive files. Some handlers may assign this function, however, a particular meaning. See the handler definition for details.

If mode is `OFFSET_BEGINNING`, then the new file pointer is placed `position` bytes from the start of the file, i.e. the new file pointer is equal to `position`.

If mode is `OFFSET_CURRENT`, then `position` is added to the file pointer. That is, the file pointer is advanced if `position` is positive, or rewinded if `position` is negative.

If mode is `OFFSET_END`, then the end-of-file position is determined, and `position` is added to this position. This, in particular, requires that `position` should be negative.

The `Seek()` function returns the file pointer before its adjustment, or `-1` in case of an error.

A secondary return code can be retrieved from `IoErr()` described in section ?? . It is 0 on success, or an error code from `dos/dos.h` in case adjusting the file pointer failed.

**Not 64bit safe** Unfortunately, it is not quite clear how `Seek` operates on files that are larger than 2GB, and it is file system dependent how such files could be handled. `OFFSET_BEGINNING` can probably only reach the first 2GB of a larger file as the file system may interpret negative values as an attempt to reach a file position upfront the start of the file and may return an error. Similarly, `OFFSET_END` may possibly only reach the last 2GB of the file. Any other position within the file may be reached by splitting the seek into chunks of at most 2GB and perform multiple `OFFSET_CURRENT` seeks. However, whether such a strategy succeeds is pretty much file system dependent. Note in particular that the return code of the function does not allow to distinguish between a file pointer just below the 4GB barrier and an error condition. A zero result code of `IoErr()` should be then used to learn whether a result of `-1` indicates a file position of `0xffffffff` instead. Most AmigaDOS file systems may not be able to handle files larger than 2GB.

Even though `Seek()` is an unbuffered function, it is aware of a buffer and implicitly flushes the file system internal buffer. That is, it can be safely used by buffered and unbuffered functions.

### 4.7.5 Setting the Size of a File

The `SetFileSize()` function truncates or extends the size of an opened file to a given size. Not all handlers support this function.

```
newsize = SetFileSize(fh, offset, mode)
D0                      D1      D2      D3

LONG SetFileSize(BPTR, LONG, LONG)
```

This function extends or truncates the size of the file identified by the *file handle* `fh`; the target size is determined by the current file pointer, `offset` and the mode. Interpretation of mode and `offset` is similar to `Seek()`, except that the end-of-file position of the file is adjusted, and not the file pointer.

The mode shall be selected from to table 10. In particular, it is interpreted as follows:



---

If mode is `OFFSET_BEGINNING`, then the file size is set to the value of `offset`, irrespective of the current file pointer.

If mode is `OFFSET_CURRENT`, then the new end-of-file position is set `offset` bytes relative to the current file pointer. That is, the file is truncated if `offset` is negative, and extended if `offset` is positive.

If mode is `OFFSET_END`, the new file size is given by the current file size plus `offset`. That is, the file is extended by `offset` bytes if positive, or truncated otherwise. The value of the current file pointer is irrelevant and ignored.

If the current file pointer of any *file handle* opened on the same file is, after a potential truncation, beyond the new end-of-file, it is clamped to the end-of-file. They remain unchanged otherwise.

If the file is enlarged, the values within the file beyond the previous end-of-file position are undetermined.

The return value `newsize` is the size of the file after the adjustment, i.e. the position of the end-of-file location.

**Not 64bit safe** Similar to `Seek()`, `SetFileSize()` cannot be assumed to work properly if the (old or new) file size is larger than 2GB. What exactly happens if an attempt is made to adjust the file by more than 2GB depends on the file system performing the operation. A possible strategy to adjust the file size to a value above 2GB is to first seek to the closest position, potentially using multiple seeks of maximal size, and then perform one or multiple calls to `SetFileSize()` with the mode set to `OFFSET_CURRENT`. However, whether this strategy succeeds is file system dependent.

## 4.8 Buffered Input and Output

AmigaDOS also offers buffered input and output functions that stores data in an intermediate buffer. AmigaDOS then transfers data only in larger chunks between the buffer and the handler, minimizing the task switching overhead and offering better performance if data is to be read or written in smaller units.

**Performance Improved** While buffered I/O functions of AmigaOs 3.1.4 and below were designed around single-byte functions and thus caused massive overhead in the buffered functions described in this section, the functions in this section were redesigned in AmigaOs 3.2 and now offer significantly better performance. Unfortunately, the default buffer size AmigaDOS uses is quite small and should be significantly increased by `SetVBuf()`. A suggested buffer size is 4096 bytes which corresponds to a disk block of modern hard drives.

### 4.8.1 Buffered Read From a File

The `FRead()` function reads multiple equally-sized records from a file through a buffer, and returns the number of records retrieved.

```
count = FRead(fh, buf, blocklen, blocks)
      D0          D1  D2      D3      D4

LONG FRead(BPTR, STRPTR, ULONG, ULONG)
```

This function reads `blocks` records each of `blocklen` bytes from the file `fh` into the buffer `buf`. It returns the number of complete records retrieved from the file. If the file runs out of data, the last record may be incomplete.

---

From AmigaOs 3.2 onwards, `FRead()` first attempts to satisfy the request from the file handle internal buffer, but if the number of remaining bytes is larger than the buffer size, the handler will be invoked directly for “bursting” the data into the target buffer, bypassing the file buffer.

This function does not modify `IoErr()` in case the request can be satisfied completely from the file handle buffer. It neither returns `-1` in case of an error. Callers should instead use `SetIoErr(0)` to clear the error state before calling this function, and then use `IoErr()` to learn if any error occurred if the number of records read is smaller than the number of records requested.

### 4.8.2 Buffered Write to a File

The `FWrite()` function writes multiple equally-sized records to a file through a buffer, and returns the number of records it could write.

```
count = FWrite(fh, buf, blocklen, blocks)
D0          D1  D2      D3      D4

LONG FWrite(BPTR, STRPTR, ULONG, ULONG)
```

This function write `blocks` records each of `blocklen` bytes from the buffer `buf` to the file `fh`. It returns the number of complete records written to the file. On an error, the last record written may be incomplete.

From AmigaOs 3.2 onwards, `FWrite()` first checks whether the file handle internal buffer is partially filled. If so, the file handle internal buffer is filled from `buf`. If any bytes remain to be written, and the number of bytes is larger than the internal buffer size, the handler will be invoked to write the data in a single block, bypassing the buffer. Otherwise, the data will be copied to the internal buffer.

This function does not modify `IoErr()` in case the request can be satisfied completely by using the file handle buffer. It neither returns `-1` in case of an error. Callers should instead use `SetIoErr(0)` to clear the error state before calling this function, and then use `IoErr()` to learn if any error occurred if the number of records written is smaller than the number of records passed in.

### 4.8.3 Buffered Write to the Output Stream

The `WriteChars()` writes an array of bytes buffered to the output stream.

```
count = WriteChars(buf, buflen)
D0          D1  D2

LONG WriteChars(STRPTR, LONG)
```

This function is equivalent to `FWrite(Output(), buf, 1, buflen)`, that is, the bytes in the buffer `buf` of size `buflen` is writing to the output stream, and the number of characters written is returned. Therefore, this function has similar quirks concerning error reporting as `FWrite()`: It does not set `IoErr()` consistently, namely only when the buffer is written to the stream. It neither returns `-1` on an error. It is therefore recommended to reset the error upfront with `SetIoErr(0)`.

### 4.8.4 Adjusting the Buffer

The `SetVBuf()` function allows to adjust the internal buffer size for buffered input/output functions such as `FRead()` or `FWrite()`. It also sets the buffer mode. The default buffer size is 204 characters, which is too low for many applications.

```
error = SetVBuf(fh, buff, type, size)
D0          D1    D2    D3    D4
```

```
LONG SetVBuf(BPTR, STRPTR, LONG, LONG)
```

This function sets the internal buffer of the *file handle* `fh` to `size` bytes. Sizes smaller than 204 characters will be rounded up to 204. If `buff` is non-NULL, it is a pointer to a user-provided buffer that will be used for buffering. This buffer shall be aligned to a 32-bit boundary. A user provided buffer will not be released when the file is closed.

Otherwise, if `buff` is NULL AmigaDOS will allocate the buffer for you, and will also release it when the file is closed.

The `type` argument identifies the type of buffering according to Table 11; the modes there are defined in the include file `dos/stdio.h`.

**Table 11: Buffer Modes**

| Buffer Name | Description              |
|-------------|--------------------------|
| BUF_LINE    | Buffer up to end of line |
| BUF_FULL    | Buffer everything        |
| BUF_NONE    | No buffering             |

The buffer mode `BUF_LINE` automatically flushes the buffer when writing a line feed (0x0a), carriage return (0x0c) or ASCII NUL (0x00) character to the buffer, and the target file is interactive. Otherwise, the characters remain in the buffer until it either overflows or is flushed manually, see `Flush()`.

The buffer mode `BUF_FULL` buffers all characters until the buffer either overflows or is flushed.

The buffer mode `BUF_NONE` effectively disables the buffer and writes all characters to the target file immediately.

On reading, `BUF_LINE` and `BUF_FULL` are equivalent and fill the entire buffer from the file; `BUF_NONE` disables buffering.

The function returns non-zero on success, or 0 on error. Error conditions are either out-of-memory, an invalid buffer mode or an invalid file handle. Unfortunately, `IoErr()` is only set on an out-of-memory condition and remains otherwise unchanged.

## 4.8.5 Synchronize the File to the Buffer

The `Flush()` function flushes the internal buffer of a *file handle* and synchronizes the file pointer to the buffer position.

```
success = Flush(fh)
D0          D1
```

```
LONG Flush(BPTR)
```

Synchronizes the file pointer to the buffer, that is, if bytes were written to the buffer, writes out buffer content to file. If bytes were read from the file and non-read files remained in the buffer, such bytes are dropped and the function attempts to seek back to the position of the last read byte. This can fail for interactive files.

The return code is currently always `DOSTRUE` and thus cannot be used as an indication of error, even if not all bytes could be written, or if seeking failed. If error detection is desired, the caller should first use `SetIoErr(0)` to erase an error condition, then call `flush`, and then use `IoErr()` to check whether an error occurred.

---

**Flush when switching between reading and writing** The `Flush()` function shall be called when switching from writing to a file to reading from the same file, or vice versa. The internal buffer logic is unfortunately not capable to handle this case correctly. Also, `Flush()` shall be called when switching from buffered to unbuffered input/output.

#### 4.8.6 Write a Character Buffered to a File

The `FPutC()` function writes a single character to a file, using the *file handle* internal buffer.

```
char = FPutC(fh, char)
D0          D1  D2
```

```
LONG FPutC(BPTR, LONG)
```

This function writes the single character `char` to the *file handle* `fh`. Depending on the buffer mode, the character and the type of file, the character may go to the buffer first, or may cause the buffer to be emptied. See `SetVBuf()` for details on buffer modes and conditions for implicit buffer flushes.

It returns the character written, or `ENDSTREAMCH` on an error. The latter constant is defined in `dos/stdio.h` and equals to `-1`.

This function does not touch `IoErr()` if the character only goes into the internal buffer.

#### 4.8.7 Write a String Buffered to a File

The `F_puts()` function writes a NUL-terminated string to a file, using the *file handle* internal buffer.

```
error = F_puts(fh, str)
D0          D1  D2
```

```
LONG F_puts(BPTR, STRPTR)
```

This function writes the NUL-terminated (C-style) string `str` to the *file handle* `fh`. The terminating NUL character is not written.

Depending on the buffer mode, the string will first go into the buffer, or may be written out immediately. See `SetVBuf()` for details on buffer modes and conditions for implicit buffer flushes.

This function returns 0 on success, or `ENDSTREAMCH` on an error. The latter constant is defined in `dos/stdio.h` and equals to `-1`. The error code `IoErr()` is only adjusted when the buffer is flushed.

#### 4.8.8 Write a String Buffered to the Output Stream

The `PutStr()` function writes a NUL-terminated string to the output. No newline is appended.

```
error = PutStr(str)
D0          D1
```

```
LONG PutStr(STRPTR)
```

This function is equivalent to `F_puts(Output(), str)`, that is, it writes the NUL-terminated string pointed to by `str` to the output. It returns 0 on success and `-1` on error. The `IoErr()` is only adjusted when the buffer of the `Output() FileHandle` is flushed. When this happens depends on the buffer mode installed by `SetVBuf()`.

---

### 4.8.9 Read a Character from a File

The `FGetC()` function reads a single character from a file through the internal buffer of the *file handle*.

```
char = FGetC(fh)
D0          D1

LONG FGetC(BPTR)
```

This function attempts to read a single character from the *file handle* `fh` using the buffer of the handle. If characters are present in the buffer, the request is satisfied from the buffer first, then the function attempts to refill the buffer from the file and tries again.

The function returns the character read, or `ENDSTREAMCH` on an end-of-file condition or an error. The latter constant is defined in `dos/stdio.h` and equals to `-1`.

To distinguish between the error and the end-of-file case, the caller should first reset the error condition with `SetIoErr(0)`, and then check `IoErr()` when the function returns with `ENDSTREAMCH`.

### 4.8.10 Read a Line from a File

The `FGets()` function reads a newline-terminated string from a file, using the *file handle* internal buffer.

```
buffer = FGets(fh, buf, len)
D0          D1  D2  D3

STRPTR FGets(BPTR, STRPTR, ULONG)
```

This function reads a line from the *file handle* into the buffer pointed to by `buf`, capable of holding `len` characters.

Reading terminates either if `len-1` characters have been read, filling up the buffer completely; or a line-feed character is found, which is copied into the buffer; or if an end-of-file condition or an error condition is encountered. In either event, the string is NUL terminated.

The function returns `NULL` in case not even a single character could be read. Otherwise, the function returns the buffer passed in.

To distinguish between the error and end-of-file condition, the caller should first use `SetIoErr(0)`, and then test `IoErr()` in case the function returns `NULL`.

### 4.8.11 Revert a Single Byte Read

The `UnGetC()` function reverts a single byte read from a stream and makes this byte available for reading again.

```
value = UnGetC(fh, ch)
D0          D1  D2

LONG UnGetC(BPTR, LONG)
```

The character `ch` is pushed back into the *file handle* `fh` such that the next attempt to read a character from `fh` returns `ch`. If `ch` is `-1`, the last character read will be pushed back. If the last read operation indicated an error or end-of-file condition, `UnGetC(fh, -1)` pushes an end-of-file condition back.

This function returns non-zero on success or 0 if the character could not be pushed back. At most a single character can be pushed back after each read operation, an attempt to push back more characters can fail.

---

## 4.9 File Handle Documentation

So far, the *file handle* has been used as an opaque value bare any meaning. However, the BPTR, once converted to a regular pointer, is a pointer to `FileHandle` structure:

```
BPTR file = Open("S:Startup-Sequence,MODE_OLDFILE");
struct FileHandle *fh = BADDR(file);
```

In the following sections, this structure and its functions are documented.

### 4.9.1 The struct FileHandle

When opening a file via `Open()`, the *file handle* is allocated by the *dos.library* by going through `AllocDosObject()`, and then forwarded to the file system or handler for second-level initialization. It is documented in `dos/dosextens.h` as replicated here:

```
struct FileHandle {
    struct Message *fh_Link;
    struct MsgPort *fh_Port;
    struct MsgPort *fh_Type;
    BPTR fh_Buf;
    LONG fh_Pos;
    LONG fh_End;
    LONG fh_Funcs;
#define fh_Func1 fh_Funcs
    LONG fh_Func2;
    LONG fh_Func3;
    LONG fh_Args;
#define fh_Arg1 fh_Args
    LONG fh_Arg2;
};
```

`fh_Link` is actually not a pointer, but an AmigaDOS internal value that shall not be interpreted or touched, and of which one cannot make productive use.

`fh_Port` is similarly not a pointer, but a `LONG`. If it is non-zero, the file is interactive, otherwise it is a file system. `IsInteractive()` makes use of this member. The file system or handler shall initialize this value when opening a file and shall initialize it according to the nature of the handler.

`fh_Type` points to the `MsgPort` of the handler or file system that implements all input and output operations. Section ?? provides additional information on how handlers and file systems work. If this pointer is `NULL`, no handler is associated to the file handle. This is also the value AmigaDOS will deposit here when opening a file to the `NIL:` (pseudo-)device. Attempting to `Read()` from this handle results in an end-of-file situation, and calling `Write()` on such a handle does nothing, ignoring any data written.

`fh_Buf` is a BPTR to the file handle internal buffer all buffered I/O function documented in this section use.

`fh_Pos` is the next read or write position within this buffer.

`fh_End` is the size of the buffer in bytes.

`fh_Func1` is a function pointer that is called whenever the buffer is to be filled through the handler. Users shall not call this function itself, and the function prototype is intentionally not documented.

`fh_Func2` is a second function pointer that is called whenever the buffer is full and is to be written by the handler. Users shall not call this function itself, and the function prototype is intentionally undocumented.

---

`fh_Func3` is a final function pointer that is called whenever the file handle is closed. This function then potentially writes the buffer content out when dirty, releases the buffer if it is system-allocated, and finally forwards the close request to the handler.

`fh_Arg1` is a file-system internal value the handler or file system uses to identify the file. The interpretation of this value is to the file system or handler, and the *dos.library* does not attempt to interpret it. The handler deposits the file identification here when opening a file, and the *dos.library* forwards it to the handler on `Read()` and `Write()`. See section ?? for details.

`fh_Arg2` is currently unused.

## 4.9.2 String Streams

It is sometimes useful to provide programs with (temporary) input not coming from a file system or handler directly, even though the program uses a file interface to access it. One solution to this problem is to deposit the input data on the RAM disk, then opening this file and providing it as input to such a program. The drawback of this approach is that additional tests are necessary to ensure that the file name is unique, and to avoid that other than the intended program accesses it.

AmigaDOS uses the technique documented here itself, for example to provide the command to be executed by the `Run` command. There, the string stream contains the command to be run in background, which is then provided as input file to the shell. The `System()` function of the *dos.library* makes use of the same trick to feed the command to be executed as input file. Thus, even though the shell can only execute commands from a file, AmigaDOS can generate *file handles* that do not correspond to a handler, but to a string in memory containing the commands.

The shell itself is using the same technique to pass arguments to the commands it executes; it deposits the command arguments in the file handle buffer of the input stream where `ReadArgs()` collects them.

The idea is to allocate a `struct FileHandle` and initialize its buffer to contain the string within the file. For this `fh->Buf` needs to point to the buffer containing the string, and `fh->End` needs to be its size. The function pointers in the *file handle* remain 0 such as to avoid that the *dos.library* reads, writes or flushes the buffer. The `FileHandle` shall be allocated by `AllocVec()` as the *dos.library* releases the handle through `FreeVec()`.

The following program demonstrates this technique:

```
#include <exec/memory.h>
#include <dos/dos.h>
#include <dos/stdio.h>
#include <string.h>
#include <proto/dos.h>
#include <proto/exec.h>

int main(int argc, char **argv)
{
    const char *test = "Hello World!\n";
    const int len = strlen(test)+1;
    struct FileHandle *fh;
    BPTR file;

    fh = AllocVec(sizeof(struct FileHandle) + len, MEMF_PUBLIC|MEMF_CLEAR);
    if (fh) {
        UBYTE *c = (UBYTE *) (fh + 1);
        file = MKBADDR(fh);
        memcpy(c, test, len);
    }
```

```

    fh->fh_Buf = MKBADDR(c);
    fh->fh_End = len;
    {
        BPTR out = Output();
        LONG ch;
        while((ch = FGetC(file)) >= 0) {
            FPutC(out, ch);
        }
    }
    Close(file);
}
return 0;
}

```

Here the buffer is allocated along with the file handle, and thus released along with it. Setting `MEMF_PUBLIC` is of utter importance as it clears all function pointers, and in particular the `fh_Link` field to zero; the latter is an indication to the *dos.library* that this structure was not allocated through itself.

### 4.9.3 An FSkip() Implementation

Unlike most unbuffered functions, `Seek()` can be safely mixed with buffered input and output functions. However, this function is not very efficient, and seeking should be avoided if buffer manipulation is sufficient. Buffer manipulation has the advantage that small amounts of bytes can be skipped easily without going through the file system; skipping over larger amounts of bytes can be performed by a single function without requiring to read bytes.

The following function implements an `FSkip()` function that selects the most viable option and is more efficient than `Seek()` for buffered reads.

```

LONG FSkip(BPTR file, LONG skip)
{
    LONG res;
    struct FileHandle *fh = BADDR(file);
    if (fh->fh_Pos >= 0 && fh->fh_End > 0 && fh->fh_Func3) {
        LONG newpos = fh->fh_Pos + skip;
        if (newpos >= 0 && newpos < fh->fh_End) {
            fh->fh_Pos = newpos;
            return DOSTRUE;
        }
    }
    skip += fh->fh_Pos - fh->fh_End;
    fh->fh_Pos = -1;
    fh->fh_End = -1;
    if (Seek(fh, skip, OFFSET_CURRENT) != -1)
        return DOSTRUE;
    return DOSFALSE;
}

```

The first if-condition checks whether the buffer is actually present. Then, the new buffer position is computed. If it is within the buffer, the new buffer position is installed as the work is done.

Otherwise, the skip distance is adjusted by the buffer position. Initializing the buffer size and position to `-1` ensures that the following `Seek()` does not attempt to call `Flush()` internally.



---

There is one particular catch, namely that the `file` needs to be initialized for reading immediately after opening the file, or the buffer will not be in the right state for the trick:

```
BPTR file = Open(filename,MODE_OLDFILE);
UnGetC(file,-1); /* initialize buffer */
```

This is only necessary if the first access to the file is an `FSkip()`.

#### 4.9.4 An FGet() Implementation

While the `FRead()` function already provides a buffered read function, it is not very efficient prior release 47 of AmigaDOS. The following simple function provides in such cases a faster implementation that even allows inlining:

```
LONG FGet(BPTR f,void *buf, LONG size)
{
    struct FileHandle *cis = BADDR(f);

    if (cis->fh_Pos) {
        LONG end = cis->fh_Pos + size;
        if (end < cis->fh_End) {
            memcpy(buf, (UBYTE *)BADDR(cis->fh_Buf) + cis->fh_Pos, (size_t)(size));
            cis->fh_Pos = end;
            return size;
        }
    }

    return FRead(f,buf,1,size);
}
```

It reads `size` bytes from the file `fh` into the buffer `buf`, and returns the number of bytes read.

As seen from this implementation, the function attempts to satisfy the read if a partial buffer is present. If not, the above implementation runs into the operating system function. As for the `FSkip()` implementation presented in section 4.9.3, the file handle requires some preparation by a dummy `UnGetC()`, see there.

### 4.10 Formatted Output

The functions in this section print strings formatted to a file. Both files use the internal buffer of the *file handle*.

#### 4.10.1 Print Formatted String using C-Syntax to a File

The `VFPrintf()` function prints multiple datatypes using a format string that closely resembles the syntax of the C syntax. `FPrintf()` is based on the same entry point of the *dos.library*, though the prototype for the C language is different and thus arguments are expected directly as function arguments instead of requiring them to be collected in an array upfront.

```
count = VFPrintf(fh, fmt, argv)
D0          D1  D2  D3

LONG VFPrintf(BPTR, STRPTR, LONG *)
```

---

```
count = FPrintf(fh, fmt, ...)

LONG FPrintf(BPTR, STRPTR, ...)
```

This function uses the `fmt` string to format an array of arguments pointed to by `argv` and outputs the result to the file `fh`. The syntax of the format string is identical to that of the `exec` function `RawDoFmt()`, and shares its problems. In particular, format strings indicating integer arguments such as `%d` and `%u` assume 16bit integers, independent of the integer model of the compiler. On compilers working with a 32bit integer models, the format modifier `l` should be used, e.g. `%ld` for signed and `%lu` for unsigned integers.

As `RawDoFmt()` is also patched by the *locale.library*, additional syntax elements from the `FormatString()` function of this library become available for `VFPrintf()` and `FPrintf()`.

The result `count` delivers the number of characters written to the file, or `-1` for an error. In the latter case, `IoErr` provides an error code.

## 4.10.2 Print Formatted String using C-Syntax to the Output String

```
count = VPrintf(fmt, argv)
D0          D1    D2

LONG VPrintf(STRPTR, LONG *)

count = Printf(fmt, ...)

LONG Printf(STRPTR, ...)
```

## 4.10.3 BCPL Style Formatted Print to a File

The `VFWritef()` function formats several arguments according to a format string similar to `VFPrintf()`, but uses the formatting syntax of the BCPL language. The main purpose of this function is to offer formatted output for legacy BCPL programs where this function appears as an entry of the BCPL *Global Vector*. New code should not use this function but rather depend on `VFPrintf()` which also gets enhanced by the *locale.library*.

The `FWritef()` uses the same entry point of the *dos.library*, though the compiler prototype imposes a different calling syntax where the objects to be formatted are directly delivered as function arguments rather requiring the caller to collect them in an array upfront.

```
count = VFWritef(fh, fmt, argv)
D0          D1    D2    D3

LONG VFWritef(BPTR, STRPTR, LONG *)

count = FWritef(fh, fmt, ...)

LONG FWritef(BPTR, STRPTR, ...)
```

This function formats the arguments from the array pointed to by `argv` according to the format string in `fmt` and writes the output to the file `fh`. The format string follows the syntax of the BCPL language. The following format identifiers are supported:

`%S` Write a NUL terminated string from the array to the output.

- 
- `%Tx` Writes a NUL terminated string left justified in a field whose width is given by the character `x`. The length indicator is always a single character; a digit from 0 to 9 indicates the field widths from 0 to 9 directly. Characters A to Z indicate field widths from 10 onwards.
  - `%C` Writes a single character whose ISO-Latin-1 code is given as a 32-bit integer on the `argv` array.
  - `%Ox` Writes an integer in octal to the output where `x` indicates the maximal field width. The field width is a single character that is encoded similarly to the `%T` format string.
  - `%Xx` Writes an integer in hexadecimal to the output in a field that is at most `x` characters long. `x` is a single character and encodes the width similar to that `%T` format string.
  - `%Ix` Writes a (signed) integer in decimal to the output in field that is at most `x` characters long. The field length is again indicated by a single character.
  - `%N` Writes a (signed) integer in decimal to the output without any length limitation.
  - `%Ux` Writes an unsigned integer in decimal to the output, limiting the field length to at most `x` characters, where `x` is encoded in a single character.
  - `%$` Ignores the next argument, i.e. skips over it.

This function is *not* patched by the *locale.library* and therefore is not localized or enhanced.

While the same function can also be found in the BPCL *Global Vector*, it there takes BSTRs instead of regular C strings for the format string and arguments of the `%S` and `%T` formats.

## 4.11 Record Locking

While locks control access to a *file system* object in total, record locks provide access control on portions of a file. Unlike locks, however, the *file system* does not block read or write access to the locked region. Instead, a record lock on a portion of a file only prevents another record lock on a region that overlaps with the locked region. Record locks therefore require the locking processes to follow the same locking protocol.

Record locks are a relatively modern protocol not all file systems implement. The Ram-Handler and the Fast File System support it.

### 4.11.1 Locking a Portion of a File

The `LockRecord` function locks a single region of a file, potentially waiting for a timeout for the region to become available.

```
success = LockRecord(fh, offset, length, mode, timeout)
D0          D1    D2    D3    D4    D5
```

```
BOOL LockRecord(BPTR, ULONG, ULONG, ULONG, ULONG)
```

This function attempts to lock the region of the file identified by `fh` starting from the byte offset `offset` and the byte size `length`. The `mode` shall be taken from the following constants, defined in `dos/record.h`:

**Table 12: Record Locking Modes**

| Record Locking Mode | Description  |
|---------------------|--|
| REC_EXCLUSIVE       | Exclusive access to a region, honoring the timeout |
| REC_EXCLUSIVE_IMMED | Exclusive access to a region, ignoring the timeout |
| REC_SHARED          | Shared access to a region, honoring the timeout    |
| REC_SHARED_IMMED    | Shared access to a region, ignoring the timeout    |

While the same byte within a file can be included in multiple regions locked through a shared record lock, only a single exclusive lock can be held on each byte of a file. Or put differently, shared regions can overlap with each other without failure, exclusively locked regions cannot overlap with shared locked regions or with each other.

For the `REC_EXCLUSIVE` and `REC_SHARED` modes, the `timeout` value provides a time limit in ticks, i.e.  $1/50^{\text{th}}$  of a second, after which an attempt to obtain a lock times out. This time limit may also be 0 in which case an attempt to lock a region fails immediately.

The `REC_EXCLUSIVE_IMMED` and `REC_SHARED_IMMED` modes ignore the timeout, i.e. they act as if the timeout is 0 and fail as soon as they can determine that the requested record cannot be locked.

This function returns 0 in case of failure and then returns a non-zero error code with `IoErr()`. In case the record lock cannot be obtained because the region overlaps with another locked region, the error will be `ERROR_LOCK_COLLISION`. If the region can be locked, the call returns a non-zero result code and sets `IoErr()` to 0.

## 4.11.2 Locking Multiple Portions of a File

The `LockRecords()` function locks multiple records at once, potentially within multiple files.

```
success = LockRecords(record_array, timeout)
D0                      D1                      D2
```

```
BOOL LockRecords(struct RecordLock *, ULONG)
```

This function attempts to lock multiple records at once that are included in the `RecordLock` structure. This structure is defined in `dos/record.h` and looks as follows:

```
struct RecordLock {
    BPTR    rec_FH;           /* filehandle */
    ULONG    rec_Offset;      /* offset in file */
    ULONG    rec_Length;      /* length of file to be locked */
    ULONG    rec_Mode;        /* Type of lock */
};
```

The `record_array` is a pointer to an array of the above structure that is terminated by a `RecordLock` structure with `rec_FH` equal to `NULL`. The elements of this structure correspond to the arguments of the `LockRecord()` function:

`rec_FH` is the file handle to the file within which a record is to be locked. It shall be `NULL` for the last element in the array.

`rec_Offset` and `rec_Length` specify the region in the file to be locked.

`rec_Mode` specifies the type of the lock that is to be obtained. It shall be one of the modes listed in table 12; the modes are all defined in `dos/record.h`.

The `timeout` specifies how long each of the attempts to obtain a lock is supposed to wait for a record to become available if a non-immediate record lock is requested. The `timeout` is applied to each of the records in the `RecordLock` array sequentially until either all records could be locked, or until locking one of the records fail. In such a case, the call unlocks all locks obtained so far, and then returns with failure.

On failure, i.e. if one of the records cannot be locked, the function returns 0 and sets `IoErr()` to an error code. On success, the function returns a non-zero result and sets `IoErr()` to 0.

Unlike what the function prototype suggests, this function is *not atomic*. Instead, it attempts to lock the records sequentially one after another, applying the same timeout for each call. Thus, it can happen that another task attempts for a lock of a conflicting region while the first caller is executing this function. It is

---

therefore recommended to establish an order in which records within a file are locked, e.g. from smallest to largest start offset. Note that this also implies that the maximal time this function may take is given by the number of elements in the `record_array` times `timeout`.

### 4.11.3 Unlocking a Portion of a File

The `UnLockRecord()` function unlocks a region of a file, releasing it for further locks. The provided region shall be identical to one of the regions locked before, i.e. it is not possible to partially unlock a region and leave the remaining bytes of the region locked.

```
success = UnLockRecord(fh, offset, length)
D0          D1      D2          D3
```

```
BOOL UnLockRecord(BPTR, ULONG, ULONG)
```

This function unlocks a region of a file locked before by `LockRegion()` or `LockRegions()`. The region starts `offset` bytes within the file identified by `fh` and is `length` bytes large.

This function returns 0 on failure and sets an error code that can be obtained by `IoErr()`. A possible error code is `ERROR_RECORD_NOT_LOCKED` if an attempt is made to unlock a record that is actually not locked, or to partially unlock a record. On success, the function returns a non-zero result code and sets `IoErr()` to 0.

### 4.11.4 Unlocking Multiple Records of a File

The `UnLockRecords()` function unlocks multiple records provided in an array of `RecordLock` structures at once, sequentially releasing one record after another.

```
success = UnLockRecords(record_array)
D0          D1
```

```
BOOL UnLockRecords(struct RecordLock *)
```

This function releases multiple records provided in an array of `RecordLock` structures. The last element of the structure is indicated by its `rec_FH` element set to `NULL`. This structure is defined in section 4.11.2.

The function calls `UnLockRecord()` in a loop, and is therefore *not atomic*. In case unlocking any of these records fails, the function returns 0 but attempts to unlock also any remaining records in the array. On success, it returns a non-zero result code and sets `IoErr()` to 0. Unfortunately, the function does not set `IoErr()` consistently in case of failure as the error code is not saved on a failed unlock.



---

## Chapter 5

# Locks

*Locks* are access rights to objects, such as files or directories, on a file system. Once an object has been locked, it can no longer be deleted, or in case of files, it can no longer be altered either. Depending on the file system, locks may also prevent other forms of changes of the object.

Locks come in two types: *Exclusive* and *shared locks*. Only a single exclusive lock can exist on a file system object at a time, and no other locks on an exclusively locked object can exist. An attempt to lock an exclusively locked object results in failure, and attempting to exclusively lock an object that is already shared locked will also fail.

Multiple *shared locks* can be kept on the same object at the same time, though once a shared lock has been obtained, any attempt to lock the same object exclusively fails.

One particular use case of *locks* is to serve as an identifier of a particular directory or file on a file system. Since paths are limited to 255 characters, see 4.3, locks are the preferred method of indicating a position within a file system. Even though paths are length limited, there is no restriction on the depth within the directory structure of a file system. The `ZERO` lock identifies the boot volume, also known as `SYS :`, see also section 4.3.1.3.

*Locks* are also the building stone of files; in fact, every file is internally represented by a lock on the corresponding object, even if the file system does not expose this lock to the caller.

As long as at least a single lock is held of an object on a particular volume, the file system will keep the volume within the *device list* of the *dos.library*, see section 8. This has, for example, the consequence that the workbench will continue to show an icon representing the volume in its window.

## 5.1 Obtaining and Releasing Locks

*Locks* can be obtained either explicitly from a path, or can be derived from another lock or file. As locks block altering accesses to an object of a file system, locks need to be released as early as possible to allow other accesses to the locked object.

### 5.1.1 Obtaining a Lock from a Path

The `Lock()` function obtains a lock on an object given a path to the object. The path can be either absolute, or relative (see section 4.3) to the current directory of the calling process.

```
lock = Lock( name, accessMode )  
D0          D1          D2
```

---

BPTR Lock (STRPTR, LONG)

This function locks the object identified by *name*, which is the path to the object. The type of the lock is identified by *accessMode*. This mode shall be one of the two following modes, defined in *dos/dos.h*:

**Table 13: Lock Access Modes**

| Access Mode    | Description   |
|----------------|---|
| SHARED_LOCK    | Lock allowing shared access from multiple sources         |
| ACCESS_READ    | Synonym of the above, identical to SHARED_LOCK            |
| EXCLUSIVE_LOCK | Exclusive lock, only allowing a single lock on the object |
| ACCESS_WRITE   | Synonym of the above, identical to EXCLUSIVE_LOCK         |

The access mode *SHARED\_LOCK* or *ACCESS\_READ* allows multiple shared locks on the same object. This type of lock should be preferred. The access mode *EXCLUSIVE\_LOCK* or *ACCESS\_WRITE* only allows a single, exclusive lock on the same object.

The return code *lock* identifies the lock. It is non-ZERO (see 2.3) on success, or ZERO on failure. In either case, *IoErr()* is set to 0 indicating success, or an error code on failure.

**No Wildcards Here!** Note that this function does not attempt to resolve wild cards, similar to *Open()*. All characters in the path are literals.

### 5.1.2 Duplicating a Lock

The *DupLock()* function replicates a given *lock*, returning a copy of the *lock* given as argument. This requires that the original *lock* is a *shared lock*, and it returns a *shared lock* if successful.

```
lock = DupLock( lock )
D0                      D1
```

BPTR DupLock (BPTR)

This function copies the (shared) lock passed in as *lock* and returns a copy of it in *lock*. In case of error, it returns ZERO, and then *IoErr()* returns an error code identifying the error. On success, *IoErr()* is reset. It is not possible to copy an *exclusive lock*.

### 5.1.3 Obtaining the Parent of an Object

The *ParentDir()* function obtains a *shared lock* on the directory containing the locked object passed in. For directories, this is the parent directory, for files, this is the directory containing the file.

```
newlock = ParentDir( lock )
D0                      D1
```

BPTR ParentDir (BPTR)

The *lock* argument identifies the object whose parent is to be found; the function returns a *lock* on the directory containing the object. If such parent does not exist, or an error occurs, the function returns ZERO. The former case applies to the topmost directory of a file system, or the ZERO lock itself.

To distinguish the two cases, the caller should check the *IoErr()* function; if this function returns 0, then no error occurred and the passed in object is topmost and no parent exists. If it returns a non-zero error code, then the file system failed to identify the parent directory.



### 5.1.4 Creating a Directory

The `CreateDir()` object creates a new empty directory whose name is given by the last component of the path passed in. It does not create any intermediate directories between the first component of the path and its last component, such directories need potentially be created manually by multiple calls to this function.

```
lock = CreateDir( name )
D0                                D1
```

```
BPTR CreateDir(STRPTR)
```

The `name` argument is the path to the new directory to be created; that is, the directory given by the last component of the path (see section 4.3) will be created. If successful, the function returns an *exclusive lock* in `lock`, otherwise it returns `ZERO`.

In either case, `IoErr()` is set to either an error code, or to 0 in case the function succeeds.

Note that not all file systems support directories, i.e. flat file systems (see section ??) do not.

### 5.1.5 Releasing a Lock

Once you are done with a *lock* and no part of your program is using it anymore, you should release it to allow other processes or functions to access or modify the locked object. Note that setting the `CurrentDir()` to a particular lock implies usage of the lock, i.e. the lock installed as `CurrentDir()` shall not be unlocked.

```
UnLock( lock )
D1
```

```
void UnLock(BPTR)
```

This function releases the *lock* passed in as `lock` argument. Passing `ZERO` as a lock is fine and performs no activity.

### 5.1.6 Changing the Type of a Lock

Once a *lock* has been granted, it is possible to change the nature of the lock, either from `EXCLUSIVE_LOCK` to `SHARED_LOCK`, or — if this is the only *lock* on the object — vice versa.

```
success = ChangeMode(type, object, newmode)
D0                                D1      D2      D3
```

```
BOOL ChangeMode(ULONG, BPTR, ULONG)
```

This function changes the access mode of `object` whose type is identified by `type` to the access mode `newmode`. The relation between `type` and the nature of the object shall be as in table 14, where the types are defined in `dos/dos.h`:

**Table 14: Object Types for ChangeMode()**

| type                     | object Type                          |
|--------------------------|--------------------------------------|
| <code>CHANGE_LOCK</code> | object shall be a <i>lock</i>        |
| <code>CHANGE_FH</code>   | object shall be a <i>file handle</i> |

The argument `newmode` shall be one of the modes indicated in Table 13, i.e. `SHARED_LOCK` to make either the file or the lock accessible for shared access, and `EXCLUSIVE_LOCK` for exclusive access.

On success, the function returns a non-zero result code, and `IoErr()` is set to 0. Otherwise, the function returns 0 and sets `IoErr()` to an appropriate error code.

Unfortunately, this function may not work reliable for *file handles* under all versions of AmigaDOS. In particular, the *RAM-Handler* does not interpret `newmode` correctly for `CHANGE_FH`.

### 5.1.7 Comparing two Locks

The `SameLock()` function compares two locks and returns information whether they are identical, or at least correspond to objects on the same volume.

```
value = SameLock(lock1, lock2)
      D0          D1      D2
```

```
LONG SameLock(BPTR, BPTR)
```

This function compares `lock1` with `lock2`. The return code, all of them defined in `dos/dos.h`, can be one of the following:

**Table 15: Lock Comparison Return Code**

| Return Code                 | Description  |
|-----------------------------|--|
| <code>SAME_LOCK</code>      | Both locks are on the same object                      |
| <code>SAME_VOLUME</code>    | Locks are on different objects, but on the same volume |
| <code>LOCK_DIFFERENT</code> | Locks are on different volumes                         |

This function does not set `IoErr()` consistently, and callers cannot depend on its value. Furthermore, the function does not compare a `ZERO` lock with lock on the boot volume, e.g `SYS:` as identical. It is recommended not to pass in the `ZERO` lock for either `lock1` or `lock2`.

### 5.1.8 Compare to Locks for the Device

The `SameDevice()` function attempts to check whether two locks refer to two file systems that reside on the same physical device, even if on potentially different partitions.

```
same = SameDevice(lock1, lock2)
D0    D1      D2
```

```
BOOL SameDevice( BPTR, BPTR )
```

The `SameDevice()` function takes two *Locks* `lock1` and `lock2` and checks whether they were created by file systems that operate on the same physical device, even if the two *Locks* refer to different file systems or different partitions. Only the *exec device* and the corresponding unit is compared, that is, this function is not able to determine whether the locks refer to file systems on the same or different physical volumes.

This function returns a non-zero result if the responsible file systems operate on the same *exec device*, and it returns 0 otherwise. If the function is not able to identify the file systems, or cannot identify the lower level *exec device* on which the file systems operate, the function also returns 0.

A possible use case of this function is to determine whether the involved *file systems* can operate in parallel without imposing speed penalties due to conflicting medium accesses. Thus, copy functions may be optimized depending on the result as no intermediate buffering need to be used if source and destination are on different physical devices.

This function does not set `IoErr()`, even if it cannot determine the device a file system operates on.

## 5.2 Locks and Files

Each *file handle* is associated to a lock to the file that has been opened. The type of the *lock* depends on the access mode the file has been opened with, table 16 for how lock types and access modes relate.

**Table 16: Lock and File Access Modes**

| Access Mode    | Lock Type      |
|----------------|----------------|
| MODE_OLDFILE   | SHARED_LOCK    |
| MODE_READWRITE | SHARED_LOCK    |
| MODE_NEWFILE   | EXCLUSIVE_LOCK |

The association of `MODE_READWRITE` to `SHARED_LOCK` is unfortunate, and due to a defect in the *RAM-Handler* implementation in AmigaDOS 2.0 which was then later copied into the *Fast File System* implementation. Exclusive access to a file without deleting its contents can, however, be established through the `OpenFromLock()` function passing in an *exclusive lock* to the function as argument.

### 5.2.1 Duplicate the Implicit Lock of a File

The `DupLockFromFH()` function performs a copy of a lock implicit to a *file handle* of an openend file. For this to succeed, the file must be opened in the mode `MODE_OLDFILE` or `MODE_READWRITE`. Files openend with `MODE_NEWFILE` are based on an implicit *exclusive lock* that cannot be copied.

```
lock = DupLockFromFH(fh)
D0                                     D1
```

```
BPTR DupLockFromFH(BPTR)
```

This function returns a copy of the lock the *file handle* `fh` is based on and returns it in `lock`. In case of failure, `ZERO` is returned. In either case, `IoErr()` is set to either 0 in case of succes, or an error code on failure.

### 5.2.2 Obtaining the Directory a File is Located in

The `ParentOfFH()` function obtains a *shared lock* on the parent directory of the file associated to the *file handle* passed in. That is, it is roughly equivalent to first obtaining a lock on the file through `DupLockFromFile()`, and then calling `ParentDir()` on it, except that this function also applies to files opened in the `MODE_NEWFILE` mode.

```
lock = ParentOfFH(fh)
D0                                     D1
```

```
BPTR ParentOfFH(BPTR)
```

This function returns in `lock` a shared lock on the directory containing the file opened through the *file handle*. It returns `ZERO` on failure or in case there is no parent directory because `fh` already represents the root directory.

In either case, `IoErr()` is set, namely to 0 in case of success or to an error code on failure. Attempting to obtain the parent of the root directory is not a failure case, and thus `IoErr()` is set to 0 in this case.

### 5.2.3 Opening a File from a Lock

The `OpenFromLock()` function uses a *lock* and opens the locked file, returning a *file handle*. If the lock is associated to a directory, the function fails. The *lock* passed in is then absorbed into the *file handle* and shall not be unlocked. It will be released by the file system upon closing the file.

```
fh = OpenFromLock(lock)
D0                                     D1
```

```
BPTR OpenFromLock(BPTR)
```

---

This function attempts to open the object locked by `lock` as file, and creates the *file handle* `fh` from it. It fails in case the `lock` argument belongs to a directory and not a file.

In case of success, the *lock* becomes an implicit part of the *file handle* and shall not be unlocked by the caller anymore. In case of failure, the function returns `ZERO` and the *lock* remains available to the caller, and also needs to be unlocked at a later time. In either case, `IoErr()` is set, to an error code in case of failure, or 0 on success.

This function allows to open files in exclusive mode without deleting its contents. For that, obtain an *exclusive lock* on the file to be opened, and then call `OpenFromLock()` as second step.

## 5.2.4 Get Information on the State of the Medium

The `Info()` function returns information on the medium on which the locked object is located, and fills an `InfoData` structure with the status of the *file system*. If it is instead intended to retrieve information on the currently inserted volume, i.e. without requiring a *lock*, direct communication with the *file system* on the packet level is required by sending a packet type of `ACTION_DISK_INFO`, see section ??.

```
success = Info( lock, parameterBlock )
D0 D1      D2
```

```
BOOL Info(BPTR, struct InfoData *)
```

The *lock* is a *lock* to an arbitrary object on the volume to be queried; its only purpose is to identify it. The function fills out an `InfoData` structure that shall be aligned to long-word boundaries.

This structure is defined in `dos/dos.h` and reads as follows:

```
struct InfoData {
    LONG    id_NumSoftErrors;
    LONG    id_UnitNumber;
    LONG    id_DiskState;
    LONG    id_NumBlocks;
    LONG    id_NumBlocksUsed;
    LONG    id_BytesPerBlock;
    LONG    id_DiskType;
    BPTR    id_VolumeNode;
    LONG    id_InUse;
};
```

The elements of this structure are interpreted as follows:

`id_NumSoftErrors` counts the number of read or write errors the file system detected during its life-time. It is not particularly bound to the currently inserted medium.

`id_UnitNumber` is the unit number of the exec device on which the *file system* operates, and hence into which the volume identified by the *lock* is inserted.

`id_DiskState` identifies the status of the file system, whether the volume is writable and whether it is consistent. Disk states are also defined in `dos/dos.h` and set according to the following table:

**Table 17: Disk States**

| Disk State         | Description                                      |
|--------------------|--|
| ID_WRITE_PROTECTED | The volume is write protected                    |
| ID_VALIDATING      | The volume is currently validating               |
| ID_VALIDATED       | The volume is consistent and read- and writeable |

A volume in the state `ID_WRITE_PROTECTED` has been identified as consistent, but does not accept modifications, either because the medium is physically write-protected, or because it has been locked by software, see section ??.

A volume gets the state `ID_VALIDATING` if its *file system* detected inconsistencies; some file systems, including the Fast File System, then trigger a consistency check of the volume. The Fast File System rebuilds the bitmap of the volume that describes which blocks are allocated and which are free. It cannot fix more severe errors and then presents a requester to the user indicating the problem. During validation, file systems typically refuse to accept write requests. If validation cannot bring the volume into a consistent state, the disk state will remain `ID_VALIDATING`.

A volume in state `ID_VALIDATED` is consistent and read- and writeable.

`id_NumBlocks` is the total number of blocks into which the medium is divided. This includes both free and occupied blocks, and thus indicates the total capacity of the volume. This number is not necessarily constant. The RAM-Handler adjusts this value according to the available memory; RAM-Handler versions prior version 45 set this to 0. In means, in particular, that care needs to be taken when the disk fill state in percent is computed by a dividing the number of used blocks by this number.

`id_NumBlocksUsed` is the number of blocks occupied by file system on the disk. As it is dependent on the file system how many blocks it needs in addition to the actual payload data, no conclusion can be derived from this number whether a particular file fits on the volume. RAM-Handlers prior to release 45 did not even fill this with a useful value.

`id_BytesPerBlock` is the number of bytes available for payload in a physical block of the medium, and not necessarily the physical block size into which the storage medium is divided. Some file systems require additional bytes of the physical block for administrating files. Even the RAM-Handler segments data into blocks and provides in this member the number of data bytes stored there.

`id_DiskType` identifies whether the *file system* that generated the `lock` argument can identify the disk structure and claims responsibility for it. Unlike what the name suggests, it is *not* a general identifier of the type *file system* itself and shall not be used to identify a particular file system. For legacy reasons, the various flavours of the Fast File System also leave their identifier here, though this principle should not be carried over to new designs. Instead, a file system should rather return the generic `ID_DOS_DISK` if it finds a medium for which it claims responsibility. Even if the file system recognizes the disk structure as one of its own, it is possible that the structure is considered inconsistent by setting `id_DiskState` to `ID_VALIDATING`.

AmigaDOS currently defines the following disk types in `dos/dos.h`:

**Table 18: Disk Types**

| Disk Type                       | Description  |
|---------------------------------|--|
| <code>ID_NO_DISK_PRESENT</code> | No disk is inserted  |
| <code>ID_UNREADABLE_DISK</code> | Reading disk data failed at exec device level                          |
| <code>ID_DOS_DISK</code>        | The disk is in a format the file system attempts to interpret          |
| <code>ID_NOT_REALLY_DOS</code>  | While disk contents can be accessed, it is not in a suitable structure |
| <code>ID_KICKSTART_DISK</code>  | A disk containing an A1000 kickstart                                   |
| <code>'BUSY'</code>             | The file system is currently inhibited                                 |
| <code>'CON\0'</code>            | Not a file system, but the Con-Handler                                 |
| <code>'RAW\0'</code>            | Not a file system, but the Con-Handler                                 |
| All others                      | The first long word of the first block of the medium                   |

As mentioned above `ID_DOS_DISK` is the `id_DiskType` *file systems* should return in case they recognize the structure and attempt to interpret them. Despite this fact, the Fast File System returns erroneously the `dostype` as reported in table 27.

---

**Not the DosType** While mount lists include a DOSTYPE field that identifies the *file system* uniquely, the `id_DiskType` member *does not* represent this DOSTYPE. That it coincides with the DOSTYPE for the variants of the FFS is a historical error that shall not be mirrored by new *file system* designs. It is therefore advisable to check the first 3 bytes of the `id_DiskType` for the characters DOS, and if so, assume that the disk is valid and can be interpreted by the *file system*. Unfortunately, some third-party designs do not follow this convention.

`ID_NOT_REALLY_DOS` and `ID_UNREADABLE_DISK` both indicates disks the file system cannot make use of. The first because the logical structure of the disk content cannot be interpreted, and the second because the underlying exec device cannot gain access to the contents of the blocks, i.e. the physical layer of the disk is not readable.

'BUSY' is a four-character constant that is not documented in `dos/dos.h`, but returned whenever a file system has been inhibited, i.e. its access to the physical layer has been stopped. Thus, any attempt to access this file system is currently suspended, probably because some program attempts to operate on the medium on a lower level. Disk editors or disk salvage programs will typically make use of this practise to avoid file systems from touching the medium while they work on it.

'CON\0' and 'RAW\0' are indicators left by the Con-Handler (or console-type handlers) which use the `InfoData` structure for other purposes, see section 12.11. As they do not (in general) hand out locks, the `Info()` function will usually not return these two types, but direct handler communication with a packet type of `ACTION_DISK_INFO` can.

All other types are returned in case the *file system* cannot interpret the disk structure, and are then copied from the first 4 bytes of the medium or partition into `id_DiskType`. In case these bytes are all 0, it is changed to `ID_NOT_REALLY_DOS`.

`id_VolumeNode` in the `InfoData` structure is a `BPTR` to the `DosList` structure corresponding to the volume on which the object identified by the `lock` is located. For this structure, see section 8.

`id_InUse` counts the number of locks and files currently open on the medium identified by `lock`.

This function returns a non-zero result code on success and sets then `IoErr()` to 0. On failure, it returns 0 and sets `IoErr()` to an error code.

## 5.2.5 The struct FileLock

*Locks* have been so far been opaque identifiers; in fact, they are *BPTRs* to a `struct FileLock` that is defined in `dos/dosextens.h`.

```
#include <dos/dosextens.h>
lock = Lock("S:Startup-Sequence", SHARED_LOCK);
struct FileLock *flock = BADDR(lock);
```

While this structure is defined there, it is not allocated by the *dos.library* but by the *file system* itself. The file system may therefore allocate a structure that is somewhat larger and can have additional members that are not shown here.

```
struct FileLock {
    BPTR          fl_Link;          /* bcpl pointer to next lock */
    LONG          fl_Key;           /* disk block number */
    LONG          fl_Access;        /* exclusive or shared */
    struct MsgPort * fl_Task;        /* handler task's port */
    BPTR          fl_Volume;        /* bptr to DLT_VOLUME DosList entry */
};
```

---

Most of the members of this structure are of no practical value, and they should not be interpreted in any way. What is listed here is the information callers can depend upon.

The `fl_Link` member has no practical value for users; the *file system* can use it to keep multiple links on object on the same volume in a list. This is particularly important if the volume is ejected from its drive and another file system needs to take over the *locks* if the volume is later inserted into another drive.

The `fl_Key` member can be used by the file system to identify the object that has been locked. It may not necessarily be an integer, but can be any data type, potentially a pointer to some internal management object. It shall not be interpreted in any particular way.

The `fl_Access` member keeps the type of the lock. It is either `SHARED_LOCK` or `EXCLUSIVE_LOCK`.

The `fl_Task` member points to the message port of the file system for processing requests on the lock. Any activity on the lock goes through this port.

The `fl_Volume` is a *BPTR* to the *volume node* on the *Device list*. The *volume node* identifies the volume the locked object is located on. Section 8 provides further information on this list and its entries.





---

## Chapter 6

# Working with Directories

As objects on a file system can be identified by a name, these names need to be stored somewhere on the data carrier. This object is called a *directory*. While a flat file system only contains a single, topmost directory which then contains all files, a directory of a hierarchical file system can contain other directories, thus creating a *tree* of nested objects, see also section ??.

AmigaDOS provides functions to list the directory contents, to move objects in the file system hierarchy or change their name, and to access adjust their metadata, such as comments, protection bits, or creation dates.

AmigaDOS also supports *links*, that is, entries in the file system that point to some other object in the same, or some other file system. Therefore, links circumvent the hierarchy otherwise imposed by the tree structure of the file system.

### 6.1 Examining Objects on File Systems

Given a lock on a file or a directory, further information on such an object can be requested by the `Examine()` function of the `dos.library`. To read multiple directory entries at once and minimizing the calling overhead, `ExAll()` provides an advantage that is, however, harder to use, but also provides options to filter entries.

**May go away while you look!** As AmigaDOS is a multitasking operating system, the directory may change under your feed while scanning; in particular, entries you received through the above functions may not be up to date, may have been deleted already when the above functions return, or new entries may have been added the current scan will not reach. While a *Lock* on a directory prevents that this directory goes away, it does *not* prevent other processes to add or remove objects to this directory, so beware.

While `ExAll()` seems to provide an advantage by reading multiple directory entries in one go, the AmigaOS ROM file system does usually not profit from this feature, at least not unless a directory cache is used. The latter has, however, other drawbacks and should be avoided for different reasons, see section ??. Actually, `ExAll()` is (even more) complex to implement, and it is probably not surprising that multiple file systems have issues. The `dos.library` provides an `ExAll()` implementation for those file systems that do not implement it themselves, but even this (ROM-based) implementation had issues in the past. Therefore, `ExAll()` has probably less to offer than it seems.

`Examine()` and `ExNext()` fill a `FileInfoBlock` structure that collects information on an examined object in a directory. It is defined in `dos/dos.h` and reads as follows:

```
struct FileInfoBlock {  
    LONG    fib_DiskKey;
```

```

LONG    fib_DirEntryType; /* Type of Directory. If < 0, then a plain file.
                          * If > 0 a directory */
char    fib_FileName[108]; /* Null terminated. Max 30 chars used for now */
LONG    fib_Protection;    /* bit mask of protection, rwx are 3-0. */
LONG    fib_EntryType;
LONG    fib_Size;          /* Number of bytes in file */
LONG    fib_NumBlocks;     /* Number of blocks in file */
struct DateStamp fib_Date; /* Date file last changed */
char    fib_Comment[80];   /* Null terminated comment associated with file */

/* Note: the following fields are not supported by all filesystems. */
/* They should be initialized to 0 sending an ACTION_EXAMINE packet. */
/* When Examine() is called, these are set to 0 for you. */
/* AllocDosObject() also initializes them to 0. */
UWORD   fib_OwnerUID;      /* owner's UID */
UWORD   fib_OwnerGID;      /* owner's GID */
char    fib_Reserved[32];
}; /* FileInfoBlock */

```

The meaning of the members of this structure are as follows:

`fib_DiskKey` is a file system internal identifier of the object. It shall not be used, and programs shall not make any assumptions on its meaning.

`fib_DirEntryType` identifies the type of an object. Object types are defined in `dos/dosextens.h`, replicated in table 19:

**Table 19: Directory Entry Types**

| Value of <code>fib_DirEntryType</code> | Description                             |
|--|---|
| <code>ST_SOFTLINK</code>               | Object is a soft link to another object |
| <code>ST_LINKDIR</code>                | Object is a hard link to a directory    |
| <code>ST_LINKFILE</code>               | Object is a hard link to a file         |

All other types  $> 0$  indicate directories, and all other types  $< 0$  indicate files. Section ?? provides more details on soft links and hard links.

`fib_FileName` is the name of the object as NUL terminated string.

`fib_Protection` are the protection bits of the object. It defines which operations can be performed on it. The following protection bits are currently defined in `dos/dos.h`:

**Table 20: Protection Bits**

| Protection Bits           | Description   |
|---------------------------|---|
| <code>FIBB_DELETE</code>  | If this bit is 0, the object can be deleted.                |
| <code>FIBB_EXECUTE</code> | If this bit is 0, the file is an executable binary.         |
| <code>FIBB_WRITE</code>   | If this bit is 0, the file can be written to.               |
| <code>FIBB_READ</code>    | If this bit is 0, the file content can be read.             |
| <code>FIBB_ARCHIVE</code> | This bit is set to 0 on every write access.                 |
| <code>FIBB_PURE</code>    | If 1, the executable is reentrant and can be made resident. |
| <code>FIBB_SCRIPT</code>  | If 1, the file is a script.                                 |
| <code>FIBB_HOLD</code>    | If 1, the executable is made resident on first execution.   |

The flags `FIBB_DELETE` to `FIBB_READ` are shown inverted in the output of most tools, i.e. they are shown active if the corresponding flag is 0, i.e. a particular protection function is *not* active. The `FIBB_READ` and

---

FIBB\_WRITE bits were ignored by early implementations of the ROM *file system*. This was fixed in release 36.

The FIBB\_EXECUTE flag is only interpreted by the *Shell* (see section ??) and the Workbench; if the bit is 1, the *Shell* and the Workbench refuse to load the file as command or program.

The FIBB\_ARCHIVE flag is typically used by archival software. Such software will set this flag upon archiving the flag, whereas the file system will reset the flag when writing to or modifying a file, or when creating new files. The archiving software is thus able to learn which files had been altered since the last backup.

The FIBB\_PURE flag indicates an additional property of executable binaries; if the flag is set, the binaries do not alter their segments and their code can be loaded in *RAM* and stay there to be executed from multiple processes in parallel. This avoids loading the binary multiple times. The *Shell* command `resident` can load such binaries into *RAM* for future usage.

The FIBB\_SCRIPT flag indicates whether a file is a *Shell* or an *ARexx* script. If this flag is set, and the script is given as command to the *Shell*, it will forward this file to a suitable script interpreter, such as *ARexx* or *Execute*.

The FIBB\_HOLD flag indicates whether a command shall be made resident upon loading it the first time. If the flag is 1, and the shell loads the file as executable binary, and the FIBB\_PURE bit is also set, the file is kept in *RAM* and stays there for future execution.

The `fib_EntryType` member shall not be used; it can be identical to the `fib_DirEntryType`, but its use is not documented.

The `fib_Size` member indicates the size of the file in bytes. It should have probably be defined as an unsigned type. Its value is undefined for directories.

The `fib_NumBlocks` member indicates how many blocks a file occupies on the storage medium, if such a concept applies. Disks and harddisk organize their storage into blocks of equal size, and the file system manages these blocks to store data on the medium. The number of blocks can be meaningless for directories.

The `fib_Date` member indicates when the file was changed last; depending on the file system, the date may also indicate when the last modification was made for a directory, such as creating or deleting a file within. Which operations exactly trigger a change of a directory is file system dependent. The `DateStamp` structure is specified in section ??.

The `fib_Comment` member contains a NUL terminated string to a comment on the file. Not all file systems support comments. The comment has no particular meaning, it is only shown by some *Shell* commands or utilities and can be set by the user.

The `fib_OwnerUID` and `fib_OwnerGID` are filled in by some multi-user aware file systems. The AmigaDOS ROM file systems do not support these fields, and no provision is made to moderate access to a particular file according to an owner or its group. The two concepts are alien to AmigaDOS itself.

The `fib_Reserved` field is currently unused and shall not be accessed.

### 6.1.1 Retrieving Information on an Directory Entry

The `Examine()` function retrieves information on the object identified by a *lock* and fills a `FileInfoBlock` from it.

```
success = Examine( lock, FileInfoBlock )
D0                      D1                      D2

BOOL Examine(BPTR, struct FileInfoBlock *)
```

---

This function fills out the `FileInfoBlock` providing information on the object identified by `lock`. The structure is discussed in section 6.1 in more detail. The function returns non-zero in case of success, and 0 for failure. In either case, `IoErr()` is filled, by 0 on success, on an error code on failure.

**Keep it Aligned!** As with most BCPL structures, the `FileInfoBlock` shall be aligned to a long-word boundary. For that reason, it should be allocated from the heap. Section 2.3 provides some additional hints on how to allocate such structures.

### 6.1.2 Retrieving Information from a File Handle

While `Examine()` retrieves information a locked object, `ExamineFH()` retrieves the same information from a *file handle*, or rather from the *lock* implicit to the handle.

```
success = ExamineFH(fh, fib)
D0                      D1  D2

BOOL ExamineFH(BPTR, struct FileInfoBlock *)
```

This function examines the object accessed through the *file handle* `fh`, and returns the information in the *FileInfoBlock*. Note that the file content and thus its change can be changed any time, and thus the information returned by this function may not be fully up-to-date, see also the general information in section 6.1.

This function returns non-zero in case of success, or 0 on error. In either case, `IoErr()` is set, namely to 0 on success and to an error code otherwise.

As for `Examine()`, the *FileInfoBlock* shall be aligned to a 4-byte boundary.

### 6.1.3 Scanning through a Directory Step by Step

The `ExNext()` function iterates through entries of a directory, retrieving information on one object after another contained in this directory. For scanning through a directory, first `Lock()` the directory itself. Then use `Examine()` on the *lock*. This provides information on the directory itself.

To learn about the objects in the directory, iteratively call `ExNext()` on the same *lock* and on the same *FileInfoBlock* until the function returns `DOSFALSE`. Each iteration provides then information on the subsequent element in the directory of the *lock*.

```
success = ExNext( lock, FileInfoBlock )
D0                      D1  D2

BOOL ExNext(BPTR, struct FileInfoBlock *)
```

This call returns information on the subsequent entry of a directory identified by *lock* and deposits this information in the *FileInfoBlock* described in 6.1. The *lock* shall be a *lock* on a directory, in particular.

On success, `ExNext()` returns non-zero. If there is no further element in the scanned directory, or on an error, it returns `DOSFALSE`. In either event, `IoErr()` is set, namely to 0 in case of success, or to an error code otherwise.

At the end of the directory, the function returns `DOSFALSE`, and the error code as obtained from `IoErr()` is set to `ERROR_NO_MORE_ENTRIES`.

---

**Same Lock, Same FIB** To iterate through a directory, a lock to the same directory as passed into `Examine()` shall be used. Actually, the same *lock* should be used, and the same *FileInfoBlock* should be used. As important state information is associated to the *lock* and *FileInfoBlock*, `UnLock()`ing the original *lock* and obtaining a new *lock* on the same directory loses this information; using a different *FileInfoBlock* also loses this state information, requiring the *file system* to rebuild this state information, which is not only complex, but also slows down scanning the directory. In particular, you shall *not* use the same *FileInfoBlock* you used for scanning one directory for scanning a second, different directory as this can confuse the *file system*. Also, as for `Examine()`, the *FileInfoBlock* shall be aligned to a long-word boundary.

### 6.1.4 Examine Multiple Entries at once

While scanning a directory with `ExNext()` requires one interaction with the *file system* for each entry and is therefore potentially slow, `ExAll()` retrieves as many entries as possible in one go. Whether a particular file system can take advantage of such a block transfer is a matter of its original organization, however.

```
continue = ExAll(lock, buffer, size, type, control)
D0                D1      D2      D3      D4      D5
```

```
BOOL ExAll(BPTR, STRPTR, LONG, LONG, struct ExAllControl *)
```

This function examines as many directory entries belonging to the directory identified by `lock` as fit into the buffer `buffer` of `size` bytes. This buffer is filled by a linked list of `ExAllData` structures, see below for their layout. `type` determines which elements of `ExAllData` is filled.

The `lock` shall be a lock on the directory to be examined. It shall not be `ZERO`.

To start a directory scan with `ExAll()`, first allocate a `ExAllControl` structure through `AllocDosObject()`, see ???. This structure looks as follows:

```
struct ExAllControl {
    ULONG   eac_Entries;      /* number of entries returned in buffer      */
    ULONG   eac_LastKey;     /* Don't touch inbetween linked ExAll calls! */
    UBYTE   *eac_MatchString; /* wildcard string for pattern match or NULL */
    struct Hook *eac_MatchFunc; /* optional private wildcard function      */
};
```

`eac_Entries` is provided by the *file system* upon returning from `ExAll` and then contains the number of entries that fit into the buffer. Note that this number may well be 0, which does not need to indicate termination of the scan. Callers shall instead check the return code of `ExAll()` to learn on whether scanning may continue or not.

`eac_LastKey` is a *file system* internal identifier of the current state of the directory scanner. This member shall not be interpreted nor modified in any way.

`eac_MatchString` filters the directory entry names, and returns only those that match the wildcard pointed to by this member. This entry shall be either `NULL`, or a pre-parsed pattern as generated by `ParsePatternNoCase()`.

`eac_MatchFunc` is a even more flexible option to filter directory entries. It shall be either `NULL` or point to a `struct Hook` as defined in `utility/hooks.h`. If set, then for each directory entry the hook function `h_Entry` is called as follows:

```
match = (hook->h_Entry)(struct Hook *hook, LONG *datap,
                        d0                a0                a2
                        struct ExAllData *buf )
                        a1
```

---

that is, register `a0` points to the called hook, register `a1` to the data buffer that is part of the buffer supplied by the caller of `ExAll()` and which is already filled in with a candidate `ExAllData` structure to be checked for acceptance. Register `a2` points to a `LONG`, which is a copy of the `type` argument supplied to `ExAll()`. If the hook function returns non-zero, a match is assumed and the directory entry remains in the output buffer. Otherwise, the data is discarded.

`eac_MatchFunc` and `eac_MatchString` shall not be filled in simultaneously, only one of the two shall be non-NULL. If both members are NULL, all entries match.

The buffer supplied to `ExAll()` is filled by a singly linked list of `ExAllData` structures that look as follows:

```
struct ExAllData {
    struct ExAllData *ed_Next;
    UBYTE  *ed_Name;
    LONG    ed_Type;
    ULONG   ed_Size;
    ULONG   ed_Prot;
    ULONG   ed_Days;
    ULONG   ed_Mins;
    ULONG   ed_Ticks;
    UBYTE  *ed_Comment;      /* strings will be after last used field */
    UWORD   ed_OwnerUID;     /* new for V39 */
    UWORD   ed_OwnerGID;
};
```

The members of this structure are as follows:

`ed_Next` points to the next `ExAllData` structure within buffer, or NULL for the last structure filled in.

`ed_Name` points to the file name of a directory entry, and supplies the same name as `fib_FileName` as in the `FileInfoBlock`.

`ed_Type` identifies the type of the entry. It identifies directory entries according to table 19 and corresponds to `fib_DirEntryType`.

`ed_Size` is the size of the directory element for files. It is undefined for directories. It corresponds to `fib_Size`.

`ed_Prot` collects the protection bits of the directory entry according to table 20 and by that corresponds to `fib_Protection`.

`ed_Days`, `ed_Mins` and `ed_Ticks` identifies the date of the last change to the directory element. It corresponds to `fib_Date`. Section 6.2.5 defines these elements more rigorously.

`ed_Comment` points to a potential comment on the directory entry and corresponds to `fib_Comment`.

`ed_OwnerUID` and `ed_OwnerGID` contain potential user and group IDs if the file system is able to provide such information. All the AmigaDOS native file systems do not.

Which members of the `ExAllData` structure are filled in is selected by the `type` argument. It shall be selected according to table 21, whose elements are defined in `dos/exall.h`:

**Table 21: Type Values**

| Type          | Filled Members   |
|---------------|--|
| ED_NAME       | Fill only <code>ed_Next</code> and <code>ed_Name</code>            |
| ED_TYPE       | Fill all members up to <code>ed_Type</code>                        |
| ED_SIZE       | Fill all members up to <code>ed_Size</code>                        |
| ED_PROTECTION | Fill all members up to <code>ed_Prot</code>                        |
| ED_DATE       | Fill all members up to <code>ed_Ticks</code> , i.e. up to the date |
| ED_COMMENT    | Fill all members up to <code>ed_Comment</code>                     |
| ED_OWNER      | Fill all members up to <code>ed_OwnerGID</code>                    |

The return code `continue` is non-zero in case the directory contents was too large to fit into the supplied buffer completely. In such a case, either `ExAll()` shall be called again to read additional entries, or `ExAllEnd()` shall be called to terminate the call and release all internal state information.

If `ExAll()` is called again, the `lock` shall be identical to the `lock` passed into the first call, and not only a copy on the same directory as for the first call.

The return code `continue` is `DOSFALSE` in case the scan result fit entirely into `buffer` or in case an error occurred.

Regardless of the return code, `IoErr()` is set to 0 in case `continue` is non-zero, or to an error code otherwise. If the error code is `ERROR_NO_MORE_ENTRIES`, then `ExAll()` terminated because all entries have been read and scanning the directory completed. In this case, `ExAllEnd()` should not be called.

Not all file systems — actually, none delivered with AmigaOs — support `ED_OWNER`. If `continue` is `DOSFALSE` and `IoErr()` is `ERROR_BAD_NUMBER`, try to reduce `type` and call `ExAll()` again.

Some file systems do not implement `ExAll()` themselves; in such a case, the *dos.library* provides a fallback implementation keeping `ExAll()` workable regardless of the completeness of the target *file system*.

## 6.1.5 Aborting a Directory Scan

To abort an `ExAll()` scan through a directory, `ExAllEnd()` shall be called to explicitly release all state information associated to the scan. This is unlike an item-by-item scan through `ExNext()` which does not require explicit termination.

```
ExAllEnd(lock, buffer, size, type, control)
          D1      D2      D3      D4      D5
```

```
void ExAllEnd(BPTR, STRPTR, LONG, LONG, struct ExAllControl *)
```

This function aborts an `ExAll()` driven directory scan before it terminates due to an error or due to the end of the directory, i.e. whenever `ExAll()` returns with a non-zero result code which would indicate that the function should be called again.

`ExAll()` may also be the fastest way to terminate a directory scan once it is running, for example on network file systems where the scan may proceed offline on a separate server. The arguments to `ExAllEnd()` shall be exactly those supplied to `ExAll()` which it is supposed to terminate. Note in particular that the `lock` shall be identical to the `lock` passed into `ExAll()`, and not just a `lock` to the same object.

## 6.2 Modifying Directory Entries

While the functions in section 6.1 read directory entries, the functions listed here modify the directory and its entries.

---

### 6.2.1 Deleting Objects on the File System

The `DeleteFile()` function removes — despite its name — not only files, but also directories and links from a directory. For this to succeed, the object need to allow deletion through its protection bits (see section 6.1), and no *locks* are held on the object (see section 12.4). To be able to delete a directory, this directory needs to be empty in addition.

```
success = DeleteFile( name )
D0                      D1
```

```
BOOL DeleteFile(STRPTR)
```

This function deletes the object given by the last component of the path passed in as `name`. It returns non-zero in case of success, or 0 in case of error. In either case, `IoErr()` is set, namely 0 on success or an error code in case of failure.

### 6.2.2 Rename or Relocate an Object

The `Rename()` function changes the name of an object, or even relocates it from one directory to another.

```
success = Rename( oldName, newName )
D0                      D1      D2
```

```
BOOL Rename(STRPTR, STRPTR)
```

This function renames and optionally relocates an object between directories. The `oldName` is the current path to the object, and its last component is the current name of the object to relocate and rename; `newName` is the target path and its last component the target name of the object. The target directory may be different from the directory the object is currently located in, and the target name may be different from the current name. However, current path and target path shall be on the same volume, and the target directory shall not already contain an object of the target name; otherwise, current and target path may be either relative or absolute paths.

A third condition is that if the object to relocate is a directory, then the target path shall not be a position within the object to relocate, i.e. you cannot move a directory into itself.

This function returns a boolean success indicator. It is non-zero on success, or 0 on error. In either case, `IoErr()` is set, to 0 on success, or to an error code otherwise.

### 6.2.3 Set the File Comment

The `SetComment()` function sets the comment of an directory entry, provided the *file system* supports comments.

```
success = SetComment( name, comment )
D0                      D1      D2
```

```
BOOL SetComment(STRPTR, STRPTR)
```

This function sets the comment of the *file system* object whose path is given by `name` to `comment`. It depends on the file system whether or how long comments can grow. The maximum comment length AmigaDOS supports is 79 characters, due to the available space in the `FileInfoBlock` structure.

This function returns non-zero on success and 0 on error. In either case, the function sets `IoErr()` to 0 on success or to an error code otherwise.



---

### 6.2.4 Setting Protection Bits

The `SetProtection()` function modifies the protection bits of a *file system* object, i.e. either a file or a directory.

```
success = SetProtection( name, mask )
D0      D1      D2
```

```
BOOL SetProtection (STRPTR, LONG)
```

This function sets the protection bits of the file system object name in the current directory to the combination given by mask. The protection bits are defined in `dos/dos.h` and their function is listed in table 20. The mask value corresponds to what `Examine()` returns in the `FileInfoBlock` structure in `fib_Protection`, see also section 6.1.

This function returns a non-zero result code on success, or zero on error. In either case, `IoErr()` is altered, either to 0 on success or to an error code otherwise.

### 6.2.5 Set the Modification Date

The `SetFileDate()` function sets the modification date of an object of a *file system*. Despite its name, the function can also set the modification date of directories and links if the file system supports them.

```
success = SetFileDate(name, date)
D0                                D1      D2
```

```
BOOL SetFileDate(STRPTR, struct DateStamp *)
```

This function adjusts the modification date of the *file system* object identified by path as given by name to date. The `DateStamp` structure is specified in section ??.

This function returns 0 on error or non-zero on success. In either case, `IoErr()` is set, either to 0 on success or to an error code otherwise.

Note that not all file systems may be able to set the date precisely to ticks, e.g. FAT has only a precision of 2 seconds. Some file systems may refuse to set the modification date if an object is exclusively locked, this is unfortunately not handled consistently.

### 6.2.6 Set User and Group ID

The `SetOwner()` function sets the user and group ID of an object within a *file system*. Both are concatenated to a 32-bit ID value. While this function seems to imply that the file system or AmigaDOS seems to offer some multi-user capability, this is not the case. User and group ID are purely metadata that is returned by the functions discussed in section 6.1, they usually ignore them. AmigaDOS has no concept of the current user of a *file system* and thus cannot decide whether a user is privileged to access an object on a file system. In fact, all ROM based file systems delivered with AmigaDOS do not support setting the user or group ID.

```
success = SetOwner( name, owner_info )
D0                                D1      D2
```

```
BOOL SetOwner (STRPTR, LONG)
```

This function sets the user and group ID of the *file system* object identified by the path in name to the value `owner_info`. How exactly the `owner_info` is encoded is *file system* specific. Typically, the owner is encoded in the topmost 16 bits, and the group in the least significant 16 bits.

This function returns a boolean success indicator which is non-zero on success and 0 on error. This function always sets `IoErr()`, either to 0 on success or to an error code otherwise.

---

## 6.3 Working with Paths

The *dos.library* contains a couple of support functions that help working with paths, see also section 4.3. What is different from the remaining functions is that the paths are not interpreted by the file system, but rather by the *dos.library* itself. This has several consequences: First, there is no 255 character limit as the path is never communicated into the *file system* as it was stated in section 4.3.3. Second, as the paths are constructed or interpreted by the library and not the *file system*, the syntax of the path is also that imposed by the library.

That is, for these functions to work, the separator between component must be the forwards slash ('/') and the parent directory must be indicated by an isolated single forward slash without a component upfront. This implies, in particular, that the involved file systems follow the conventions of AmigaDOS.

### 6.3.1 Find the Path From a Lock

The `NameFromLock()` function constructs a path to the locked object, i.e. if the constructed path is used to create a lock, it will refer to the same object.

```
success = NameFromLock(lock, buffer, len)
D0                      D1      D2      D3
```

```
BOOL NameFromLock(BPTR, STRPTR, LONG)
```

This function constructs in `buffer` an absolute path that identifies the object locked by `lock`. At most `len` bytes will be filled into `buffer`, including NUL termination of the string. The created string is always NUL-terminated, even if the buffer is too short. However, in such a case the function returns 0, and `IoErr()` is set to `ERROR_LINE_TOO_LONG`.

If the path cannot be constructed due to an error, `success` is also set to 0 and `IoErr()` is set to an error code. However, on success, `IoErr()` is not set consistently and cannot be depended upon. Possible cases of failure are that the volume the locked object is located on is currently not inserted in which case it will be requested. The `ZERO` lock is correctly interpreted, and resolves into the string `SYS:.` The `lock` remains valid after the call.

### 6.3.2 Find the Path from a File Handle

The `NameFromFH()` function constructs a path name from a *file handle*, i.e. it finds a path that is suitable to identify the file identified by the passed in *file handle*.

```
success = NameFromFH(fh, buffer, len)
D0                      D1      D2      D3
```

```
BOOL NameFromFH(BPTR, STRPTR, LONG)
```

This function takes a *file handle* in `fh` and from that constructs an absolute path of the opened file in the supplied `buffer` capable of storing `len` bytes, including a terminating NUL byte.

On success, the function returns a non-zero return code and sets `IoErr()` to 0. On error, it returns 0 and sets `IoErr()` to an error code. In particular, if the supplied buffer is not large enough, it is set to `ERROR_LINE_TOO_LONG`. Even in the latter case, the created path is NUL terminated, though not useful.

---

### 6.3.3 Append a Component to a Path

The `AddPart()` adds an absolute or relative path to an existing path; the resulting path is constructed as if the input path is a directory, and the attached (second) path identifies an object relative to this given directory. The function handles special cases such as the colon (':') and one or multiple leading slashes ( '/') correctly and are interpreted according to the rules explained in section 4.3: The colon identifies the root of the volume, and a leading slash the parent directory, upon which the trailing component of the input path is removed.

```
success = AddPart( dirname, filename, size )
D0                      D1          D2          D3
```

```
BOOL AddPart( STRPTR, STRPTR, ULONG )
```

This function attaches to the existing path in `dirname` another path in `filename`. The constructed path will overwrite the buffer in `dirname`, which is able to hold `size` bytes, including a terminating NUL byte.

If the required buffer for the constructed path, including termination, is larger than `size` bytes, then the function returns 0 and `IoErr()` is set to `ERROR_LINE_TOO_LONG`, and the input buffers are not altered. Otherwise, the function returns non-zero, and `IoErr()` is not altered.

This function does not interact with a *file system* and does not check whether the paths passed in correspond to accessible objects. The output path is constructed purely based on the AmigaDOS syntax of paths.

### 6.3.4 Find the last Component of a Path

The `FilePart()` function finds the last component of a path; the function name is a bit misleading since the last component does not necessarily correspond to a file, but could also correspond to a directory once identified by a *file system*. If there is only a single component in the path passed in, this component is returned. If the path passed in terminates with at least two slashes ( '/') indicating that the last component is at least one level above, a pointer to the terminating slash is returned.

```
fileptr = FilePart( path )
D0                      D1
```

```
STRPTR FilePart( STRPTR )
```

This function returns in `fileptr` a pointer to the last component of the path passed in as `path`, or a pointer to '/' in case the input path terminates with at least two slashes.

This function cannot fail, and does not touch `IoErr()`.

### 6.3.5 Find End of Next-to-Last Component in a Path

The `PathPart()` identifies the end of the next-to-last component in a path. That is, if a NUL is injected at the pointer returned by this function, the resulting string starting at the passed in buffer corresponds to a path that corresponds to the directory containing the last component of the path. If the passed in path consists only of a single component, the returned pointer is identical to the pointer passed in.

```
fileptr = PathPart( path )
D0                      D1
```

```
STRPTR PathPart( STRPTR )
```

---

This function returns in `fileptr` a pointer to the end of the next-to-last component of the path passed in. This function cannot fail and does not alter `IoErr()`.

The only difference between this function and `FilePart()` is that the latter advanced over a potential trailing slash. That is, if the last character of the input path of `PathPart()` would be a slash, then `PathPart()` would return a pointer to this slash, but `FilePart()` would advance beyond this slash. That is, the “file part” of a path that explicitly indicates a directory is empty, though the “path part” is the same path without the trailing slash.

### 6.3.6 Extract a Component From a Path

The `SplitName()` function extracts a component starting at a given offset from a path and delivers the component in a buffer. It also returns a new position at which to continue parsing a path. By iteratively calling `SplitName()`, a path can be resolved directory by directory, walking the *file system* tree from top to bottom.

```
newpos = SplitName(name, separator, buf, oldpos, size)
D0                      D1      D2      D3      D4      D5
```

```
WORD SplitName(STRPTR, UBYTE, STRPTR, WORD, LONG)
```

This function scans a path as given by `name` starting from position `oldpos`. It copies all characters starting from this position into the buffer `buf` which is `size` bytes large, terminating either at the end of the path, or at `separator`, or when `buf` runs full. The component string constructed in `buf` is NUL-terminated in either case. If the provided separator is found, the separator is not copied into `buf`.

If no separator is found, the function returns `-1` as `newpos` indicating that the entire path has been scanned. Otherwise, it returns the offset into `name` at which the next component starts, i.e. the offset behind the found separator. These return values are also valid even in case the found component was too large to fit into `buf` and it had to be truncated.

This function does not set error codes, even in case `buf` was too small to hold the copied component.

The intended purpose of this function is to walk a path component by component, identifying the names of the directories as scanning proceeds. That is, if result code `newpos` is not negative, it should be passed back into this function as `oldpos` for a subsequent scan which then extracts the next component of the path. The main user of this function are therefore *file systems* when locating an object in the file system tree. For most AmigaDOS *file systems* the separator is therefore the forwards slash (“/”).

## 6.4 Links

*Links* are tools to escape the tree-like hierarchy of directories, sub-directories and files. A *link* mirrors one object of a file system to another location such that if the object is changed using the path of one location, the changes are reflected in another location. Put differently, creating a link is like copying an object except that copy and original are always in sync. The storage for the payload data of a file is only required once, the link just points to the same data as the original directory entry. The same goes for links between directories: Whenever a new entry is made in one directory, the change also appears in the other.

AmigaDOS supports two (or, actually, three) types of links: *Hard-links* and *Soft-links*. The *RAM-Handler* supports a third type that will be discussed below. *Hard-links* establish the relation between two *file-system* objects on the same volume at the level of the file system. That is, whenever a link is accessed, the file system resolves the link, transparent to its user. While for the Amiga *Fast File System* and the *RAM-Handler* a *hard-link* is a distinct directory entry type, some file systems do not distinguish between the original object and a *hard-link* to it. For such file systems, the same payload data is just referenced by two directory entries. If the target of a link is deleted on the *Fast File System* or the *RAM-Handler*, and (at least one) link to the

object still exists, then (one of) the link(s) takes over and becomes the object itself. For other file systems, only a file system internal reference counter is decreased, and the payload data is removed only if this counter becomes zero.

*Soft-Links* work differently and can also be established between two different *file systems*, or between two different volumes. Here, the *soft-link* is a type of its own that contains the path of the referenced object. If such a *soft-link* is accessed, an error code is reported by the *file-system* and it is then up to a higher layer such as the *dos.library* or an application program to read the link destination, and use it to create a path from the original path and the link destination. The access is then (hopefully) retried under the updated path. As this object may also be a *soft-link*, this process can continue; in worst case, indefinitely if one link refers to another in a circular way. To avoid this situation, the *dos.library* follows at most 15 links.

The *dos.library* supports *Soft-Links* through the functions listed in Table 22:

**Table 22: Softlink aware functions**

| Function         | Purpose                             |
|------------------|-------------------------------------|
| Open ()          | Open a file                         |
| Lock ()          | Obtain access rights to an object   |
| CreateDir ()     | Create a directory                  |
| SetProtection () | Modify protection bits              |
| SetFileDate ()   | Set the modification date of a file |
| DeleteFile ()    | Delete an object on a file system   |
| SetComment ()    | Modify object comment               |
| MakeLink ()      | Create a link to an object          |
| SetOwner ()      | Set User and Group ID               |

All of the above functions take a path of its first argument. If the path consists of multiple components, i.e. identifies an object in a nested directory, and one of the intermediate components are, in fact, *soft-links*, the *dos.library* will automatically resolve such an intermediate link and construct internally the true path to the link destination. Whether a soft-link at the last component is resolved is typically *file system* and function dependent. For example, Open () will always resolve *soft-links*, but Lock () or SetProtection () may not and may instead affect the link, not the target object. DeleteFile () will never resolve a link at the final component of the path, and will therefore delete the link, not the object linked to.

Note that Rename () is currently not on the list supporting softlinks as part of the path to the object to be renamed, or as part of the target path.

If the target of a *Soft-Link* is deleted (and not the link itself), a link pointing to it becomes invalid, even though remains in the *file system*. Any attempt to resolve the link then, obviously, fails. AmigaDOS does not attempt to identify such invalid links. The same cannot happen for *hard-links*.

Finally, the *RAM-Handler* supports a special type of *hard-links* that goes across volumes. These *external links* copy the linked object on a read-access into the RAM disk, i.e. the *RAM-Handler* implements a *copy on access*. This feature is used for the ENV: assign containing all active system settings. This assign points to a directory in the RAM disk which itself is externally linked to ENVARC:. Thus, whenever a program attempts to access its settings — such as the preferences programs — the *RAM-Handler* automatically copies the data from ENVARC: to ENV:, avoiding a manual copy and also saving RAM space for settings that are currently not accessed and thus unused.

The FileInfoBlock introduced in section 6.1 identifies links through the fib\_DirEntryType member. As seen from table 19, *hard-links* to files are indicated by ST\_LINKFILE and *hard-links* to directories by ST\_LINKDIR. Note, however, that not all file systems are able to distinguish *hard-links* from regular directory entries, so this feature cannot be depended upon. In particular, *external links* of the *RAM-Handler* cannot be identified by any particular value of the fib\_DirEntryType.

Table 19 also provides the `fib_DirEntryType` for *soft-links*, namely `ST_SOFTLINK`. As the target of a *soft-link* may not under control of the *file system*, it cannot know whether the link target is a file or a directory (or maybe another link), and therefore a single type is sufficient to identify them.

## 6.4.1 Creating Links

The `MakeLink()` function creates a *hard-link* or a *soft-link* to an existing object on a *file system*.

```
success = MakeLink( name, dest, soft )
D0          D1      D2      D3
```

```
BOOL MakeLink( STRPTR, LONG, LONG )
```

This function creates a new link at the path `name` of the type given by `soft`. The destination the link points to is given by `dest`.

The third argument, `soft`, identifies the type of the link to be created. It shall be taken from table 23, defined in `dos/dos.h`:

**Table 23:** Link Types

| Link Types             | Description                 |
|------------------------|-----------------------------|
| <code>LINK_HARD</code> | Hard link, or external link |
| <code>LINK_SOFT</code> | Soft link                   |

If `soft` is `LINK_HARD`, `dest` is a *lock* represented by `BPTR`. For most *file systems*, `dest` shall be on the same volume as the one identified by the path in `name`. The currently only exception is the *RAM-Handler* for which the destination *lock* may be on a different volume. In such a case, an *external link* is created. While the target object will be created, it may look initially like an empty file or an empty directory, depending on the type of the link destination. Its contents is copied, potentially recursively creating directories, by copying the contents of the link destination into the link, or to a file or directory within the link. Thus, the link becomes a mirror of the link destination whenever an object within the link or the link itself is accessed.

If `soft` is `LINK_SOFT`, `dest` is a `const UBYTE *` that shall be casted to a `LONG`. Then, this function creates a *soft-link* that is relative to the path of the link, i.e. `name`. For details on *soft-link* resolution, see section 6.4.2.

This function returns in `success` non-zero if creation of the lock succeeded, or 0 in case of failure. In either case, `IoErr()` is set to an error code on failure, or 0 on success.

## 6.4.2 Resolving Soft-Links

The `ReadLink()` function locates the destination of a *soft-link* and constructs from the path and directory of the link a new path that identifies the target of the link. A typical use case for this function is if a *dos.library* function returns with the error `ERROR_IS_SOFT_LINK`, indicating that the *file system* needs help from a higher layer to grant access to the object. You then typically retry the access to the object with the path constructed by this function. Note well that this path may be that of yet another *soft-link*, requiring recursive resolution of the link. To avoid endless recursion, this loop should be aborted after a maximum number of attempts, then generating an error such as `ERROR_TOO_MANY_LEVELS`. A suggested maximum level of nested *soft-links*, also used by the *dos.library*, is 15 links.

Note, however, that such steps would not be necessary for the functions listed in table 22 as they already perform such steps internally.

```
success = ReadLink( port, lock, path, buffer, size)
D0          D1      D2      D3      D4      D5
```

```
BOOL ReadLink( struct MsgPort *, BPTR, STRPTR, STRPTR, ULONG)
```

---

This function creates in `buffer` of `size` bytes a path to the target of a *soft-link* contained in the input `path` relative to the directory represented by `lock`. Typically, `path` is the path given to some object you attempted to access, and `lock` is the *lock* as given by the current directory to which the path is relative. The output path constructed in `buffer` is then an updated path relative to the same directory, i.e. relative to `lock`.

The `port` is the message port of the file system that is queried to resolve the *soft-link*; this port should be obtained from `GetDeviceProc()`, see section ?? . For relative paths, this port is identical to the one in the `fl_Task` member of the `FileLock` structure representing `lock`, see section 5.2.5.

If `size` is too small to hold the adjusted path, the function returns 0 and sets `IoErr()` to `ERROR_LINE_TOO_LONG`.

The function returns non-zero in case of success, or 0 in case of error. In either case, `IoErr()` is set to either 0 on success, or an error code otherwise.

## 6.5 Notification Requests

Notification requests allow programs to monitor file or directory changes. If so, either a signal or a message can be sent to a specific task, informing it on the modification. If the notification request is issued on a file, any attempt to modify the contents of the file will trigger the notification request. However, in order to avoid too many request to be sent out, the triggering the request is delayed until after the corresponding file is closed.

If issued on a directory, attempts to add or remove files or links will trigger the request, as well as renaming files. Whether changes of metadata such as protection bits or comments are considered modifications is not clearly defined and not all versions of all AmigaDOS file systems handle it consistently. The most recent version of AmigaDOS will consider such modifications sufficient to trigger a notification.

A typical application of notification requests is the `IPrefs` program which uses such requests to monitor changes of the preferences files. If it detects any changes of the preferences, it reloads the contents of the files and re-installs the preferences into the components it serves, most importantly `intuition`.

### 6.5.1 Request Notification on File or Directory Changes

The `StartNotify()` function starts monitoring a file or directory for changes, and if such modifications are found, a signal or a message is sent to a task.

```
success = StartNotify(notifystructure)
D0                                             D1
```

```
BOOL StartNotify(struct NotifyRequest *)
```

This function starts a notification request as described by the `notifystructure` argument. This structure shall be initialized by the caller, and is then enqueued in the file system until the notification request is terminated by `EndNotify()`. Once issued, the request shall not be touched anymore as the *file system* may access it any time. As some field require zero-initialization at this point, it is advisable to allocate it through `exec` with the `MEMF_CLEAR` flag set.

The `NotifyRequest` structure is defined in `dos/notify.h` and reads as follows:

```
struct NotifyRequest {
    UBYTE *nr_Name;
    UBYTE *nr_FullName;
    ULONG nr_UserData;
    ULONG nr_Flags;
```

```

union {
    struct {
        struct MsgPort *nr_Port;
    } nr_Msg;

    struct {
        struct Task *nr_Task;
        UBYTE nr_SignalNum;
        UBYTE nr_pad[3];
    } nr_Signal;
} nr_stuff;
ULONG nr_Reserved[4];
/* internal use by handlers */
ULONG nr_MsgCount;
struct MsgPort *nr_Handler;
};

```

The elements of this structure shall be initialized as follows:

**nr\_Name:** The path to the object to be monitored, relative to the current directory. While it seems plausible that issuing a notification request on a not yet existing object will trigger a notification once such an object is created, this type of notification is currently not supported by AmigaDOS.

**nr\_FullName** is initialized by the file system and shall be left alone by the caller. The *dos.library* uses it to store the full path of the object to monitor.

**nr\_UserData** is free for use by the calling application. It may be used to distinguish multiple notification requests that have been issued in parallel.

**nr\_Flags** identifies the activity that is performed when a change has been detected by a *file system*. Currently, the following flags are defined in *dos/notify.h*:

**Table 24: Notification Flags**

| Flag               | Purpose                                     |
|--------------------|---|
| NRF_SEND_MESSAGE   | Send a message on a file system change      |
| NRF_SEND_SIGNAL    | Set a signal on a change                    |
| NRF_WAIT_REPLY     | Wait for a reply before notifying again     |
| NRF_NOTIFY_INITIAL | Notify immediately when queuing the request |

All other bits are currently reserved. In specific, bits 16 upwards are free for the file system to use.

The flags **NRF\_SEND\_MESSAGE** and **NRF\_SEND\_SIGNAL** are mutually exclusive. Exactly one of the two shall be included in the request to identify the activity that is performed when the monitored object changes.

**NRF\_WAIT\_REPLY** indicates to the file system that it should not continue to send a notification message while it has already send one message before that has not yet been replied. Thus, setting this flag prevents notification requests to pile up at the receipient. However, if one or multiple changes were detected while the first request was triggered but not yet responded, replying to this first notification message will immediately trigger a *single* subsequent request.

**NRF\_NOTIFY\_INITIAL** will instruct the file system to trigger a notification message or signal immediately after the request has been received. This allows applications to roll both the intial action and the response of the notification into a single function — for example, for reading or re-reading a preferences file.

**nr\_Port** is only used if the **NRF\_SEND\_MESSAGE** flag is set in **nr\_Flags**. It points to a **MsgPort** structure to which a **NotifyMessage** is send when a change has been detected. This structure is specified at the end of this section.



---

`nr_Task` and `nr_SignalNum` are only used if the `NRF_SEND_SIGNAL` flag is set in `nr_Flags`. `nr_Task` is a pointer to the Task that will be informed, and `nr_SignalNum` the bit number of the signal that is set. It is not a bit mask. Clearly, `NRF_WAIT_REPLY` does not work in combination with signal bits.

`nr_Pad` are only present for alignment and shall be left alone.

`nr_Reserved` shall be zero-initialized by the caller and are reserved for future extensions.

`nr_MsgCount` shall not be touched by the caller and reserved purely for the purpose of the *file system*. It is there used to count the number of messages that have been send out to the client, but have not yet been responded. The client, i.e. the caller, shall not interpret or modify this member.

`nr_Handler` shall neither be touched by the caller; it is used by AmigaDOS to store the `MsgPort` of the *file system* responsible for this notification request, and in particular, which to contact for ending a notification request.

If `NRF_SEND_MESSAGE` is set, then the *file system* sends a `NotifyMessage` to `nr_Port` upon detection of a change; this structure is also defined in `dos/notify.h` and looks as follows:

```
struct NotifyMessage {
    struct Message nm_ExecMessage;
    ULONG    nm_Class;
    UWORD    nm_Code;
    struct NotifyRequest *nm_NReq;
    ULONG    nm_DoNotTouch;
    ULONG    nm_DoNotTouch2;
};
```

`nm_ExecMessage` is a standard `exec` message as documented in `exec/ports.h`.

`nm_Class` is always set to `NOTIFY_CLASS`, also defined in `dos/notify.h`, to identify this message as notification.

`nm_Code` is always set to `NOTIFY_CODE`, again defined in `dos/notify.h`. This again may be used to identify notifications.

`nm_NReq` is a pointer to the `NotifyRequest` through which this message was triggered. This may allow clients to identify the source of the request and by that the object that has been changed.

`nm_DoNotTouch` and `nm_DoNotTouch2` are strictly for use by the *file system* and shall not be touched or interpreted by the caller or the client.

This function returns a boolean success indicator. It returns a non-zero result code on success and then sets `IoErr()` to 0. On error, the function returns 0 and sets `IoErr()` to a non-zero error code.

## 6.5.2 Canceling a Notification Request

The `EndNotify()` function cancels an issued notification request.

```
EndNotify(notifystructure)
D1
```

```
void EndNotify(struct NotifyRequest *)
```

This function cancels the notification request identified by `notifystructure`. This function shall only be called on notification requests that have been successfully issued by `StartNotify()`. If caller did not yet reply all `NotifyMessage` messages and some are still piled up in the `nr_Port`, the *file system* will manually dequeue them from this port.

Afterwards, the `notifystructure` is again available for the caller, for example to either release its memory, or to start another notification request.



---

## Chapter 7

# File System Support Functions

Functions in this section act on a *file system* as a whole; thus, they do not need a file or a lock to operate on, but modify the file system globally.

### 7.0.1 Adjusting File System Buffers

The `AddBuffers()` function increases or reduces the number of buffers of a file system.

```
success = AddBuffers(filesystem, number)
D0          D1          D2
```

```
BOOL AddBuffers(STRPTR, LONG)
```

This function adds `number` buffers to the file system whose name is given by `filesystem`. This name consists of a filename, volume, or assign on the *file system* whose buffer count shall be modified, see also `GetDeviceProc()` in section ?? how a file system is located.

The `number` argument may be both positive — for adding buffers to the file system — or negative, to reduce the number of buffers. The purpose of these buffers is file-system dependent. The Fast File System in ROM uses it to buffer administrative information such as directory contents, but also blocks that describe the location of file content on the disk; thus adding more buffers can help to improve the performance of random-access into the file with `Seek()`.

A third purpose of the buffers is to store input and output data of `Read()` or `Write()` if the operation is not aligned to block boundaries or if the source or target buffer is considered unsuitable for direct transfer to the underlying hardware exec device.

This function returns a non-zero result on success and 0 on failure. In first case, it sets `IoErr()` to 0, otherwise it is set to an error code. Some file systems return the current number of buffers allocated; callers should thus be prepared that the return code is not equal to `DOSTRUE` to indicate success.

### 7.0.2 Inhibiting a File System

The `Inhibit()` function disables or enables access of the *file system* to the underlying exec device driver. Typical application for this function are disk editors or file system salvage tools that require exclusive access to the file system structure.

```
success = Inhibit(filesystem, flag)
D0          D1          D2
```

```
BOOL Inhibit(STRPTR, LONG)
```

---

This call controls whether the file system identified by the path name given as `filesystem` is allowed to access the medium or partition it usually operates on. The `filesystem` argument is interpreted through `GetDeviceProc()` to find the process responsible for the medium. That is, the function resolves relative and absolute paths, device and volume names, and even assigns. As `filesystem` is interpreted as a path, a device or volume name passed in shall include a colon (":") as it would be otherwise interpreted as a path relative to the current directory.

The `flag` argument controls whether access to the medium is allowed or disallowed. If `flag` is set to `DOSTRUE`, access is inhibited and the *file system* stops accessing the partition or volume. It also sets `id_DiskType` to the four-character code 'BUSY', which will be interpreted by the workbench to ghost the corresponding drive icon. Application programs are then allowed to access the exec device driver directly to access or modify blocks within the partition managed by the inhibited *file system*.

If `flag` is set to `DOSFALSE`, access to the medium is allowed again. The *file system* then performs a consistency check of the file system structure of the disk, i.e. validates it.

This function returns a non-zero result code for success and then sets `IoErr()` to 0. On error, it returns 0 and provides an error code in `IoErr()`.

### 7.0.3 Change the Name of a Volume

The `Relabel()` function changes the name of a volume a file system operates on.

```
success = Relabel(volumename, name)
D0                      D1      D2
```

```
BOOL Relabel (STRPTR, STRPTR)
```

This function relabels the volume that resides on the *file system* corresponding to the `volumename` path. This path is resolved through `GetDeviceProc()` and thus may be a relative or absolute path, the device or the volume name. As `filesystem` is interpreted as a path, a device or volume name passed in shall include a colon (":") as it would be otherwise interpreted as a path relative to the current directory.

The volume name of the medium or partition is then changed to `name`. Unlike the first argument, `name` shall *not* contain a colon (":") nor a slash ("/").

This function returns a non-zero result code for success or 0 for an error. In the first case, it sets `IoErr()` to 0, in the latter case to an error code.

### 7.0.4 Initializing a File System

The `Format()` function initializes a complete file system, writing administration information on the file system that corresponds to an empty medium. Thus, this function erases all information stored in it.

```
success = Format(filesystem, volumename, dostype)
D0                      D1      D2      D3
```

```
BOOL Format (STRPTR, STRPTR, ULONG)
```

This function erases all information on the medium or partition identified by `filesystem`, which is interpreted as a path. Thus, it may be a device or volume name, which shall then be terminated by a colon (":"). However, all other path names also work; however, if they do not include a colon, the argument is interpreted as a path name relative to the current directory, and thus will initialize the file system corresponding to it. This is probably not desirable.

To block processes from accessing information on the file system while it is initializing, it should be inhibited upfront, e.g. by `Inhibit(filesystem, DOSTRUE)` or lower level direct communication to

---

the handler, see section ??). Initializing is the only operation file systems are able to perform while being inhibited.

The `Format()` function *does not* attempt a low-level initialization of the corresponding medium; that is, it does not attempt to low-level format it on the physical layer as required when a floppy disk shall be prepared for initial use. This step needs to be performed manually by first blocking access of the file system to the floppy through `Inhibit()`, then initializing the physical layer through the exec device driver upfront, e.g. by the command `TD_FORMAT`, and then finally by calling this function.

The volume name of the medium or partition is initialized to `volumename`, which *shall not* contain a colon (":") nor a slash ("/"). Note that not all file systems support volume names. In such cases, this argument is ignored.

The `dostype` defines the flavour of file system created on the device if the file system allows multiple variations. The variations the Fast File System supports along with other file systems are listed in table 27. This corresponds to the `DOSTYPE` in the mount list. File systems may also ignore this argument if they only support a single flavour.

Unfortunately, AmigaDOS does not provide an easy way to access the flavours supported by a file system. The `Format` command of the workbench offers the types listed in the first half of table 27 if the mount entry of the file system indicates that it is the FFS, and otherwise does not offer any choices and just copies the `dostype` from the `de_DosType` of the `DosEnvec` structure, see also section ??).

After initializing the *file system*, use `Inhibit(filesystem, DOSFALSE)` or the corresponding lower level packet `ACTION_INHIBIT` to grant the file system access to the partition or medium again. As the volume name can be different and *locks* or *file handles* on the original file system clearly became invalid, it is advisable to pass the *device name* of the *file system* to `Inhibit()` if this call is used, see also sections 4.3.1.1 and 7.0.2.

This function returns a boolean success indicator that is non-zero on success or 0 on error. In either case, `IoErr()` is set to 0 on success or an error code on failure.



---

## Chapter 8

# Administration of Volumes, Devices and Assigns

The *dos.library* is just a layer of AmigaDOS that provides a common API for input/output operations; these operations are not implemented by the library itself, but forwarded to *file systems* or *handlers*. This forwarding is based on the *exec message* and *message port* system, and to this end, the `FileLock` structure and the `FileHandle` structure contain a pointer to a `MsgPort`.

However, the *dos.library* also needs to obtain this port from somewhere; for relative paths (see section 4.3), the current directory (see section 10.2.8) provides it. For absolute paths, i.e. paths that contain a colon (':'), the string upfront the colon identifies handler, directly or indirectly. If this string is empty, i.e. the path starts with a colon, it is again the handler of the current directory that is contacted, but otherwise, the dos searches the *device list* to find a suitable *message port*. This algorithm is also available as a function, namely `GetDeviceProc()`, which is documented in section ??.

Internally, the *dos.library* keeps the relation between such names and the corresponding ports in the `DosList` structure. Such a structure is also created when *mounting* a handler, i.e. advertizing the handler to the system, or when creating an *Assign*, see section 4.3.1.3, or when inserting a disk into a drive, thus making a particular *volume* available to the system (see also 4.3.1.2). Only the names from table 5 in 4.3.1.1 are special cases and hard-coded into the *dos.library* without requiring an entry in the *device list* in the form of a `DosList` structure.

This structure, defined in `dos/dosextens.h` reads as follows:

```
struct DosList {
    BPTR          dol_Next;
    LONG          dol_Type;
    struct MsgPort *dol_Task;
    BPTR          dol_Lock;
    union {
        struct {
            BSTR    dol_Handler;
            LONG    dol_StackSize;
            LONG    dol_Priority;
            ULONG   dol_Startup;
            BPTR    dol_SegList;
            BPTR    dol_GlobVec;
        } dol_handler;

        struct {
```

```

        struct DateStamp      dol_VolumeDate;
        BPTR                 dol_LockList;
        LONG                 dol_DiskType;
    } dol_volume;

    struct {
        UBYTE    *dol_AssignName;
        struct AssignList *dol_List;
    } dol_assign;

} dol_misc;

BSTR                 dol_Name;
};

```

and its members have the following purpose:

`dol_Next` is a *BPTR* to the corresponding next entry in a singly linked list of `DosList` structures. However, this list should not be walked manually, but instead `FindDosEntry()` should be used for iterating through this list.

`dol_Type` identifies the type of the entry, and by that also the layout of the structure, i.e. which members of the unions are used. The following types are defined in `dos/dosextens.h`:

**Table 25: *DosList* Entry Types**

| <b>dol_Type</b> | <b>Description</b>                                   |
|-----------------|--|
| DLT_DEVICE      | A <i>file system</i> or <i>handler</i> , see 4.3.1.1 |
| DLT_DIRECTORY   | A regular assign, see 4.3.1.3                        |
| DLT_VOLUME      | A volume, see 4.3.1.2                                |
| DLT_LATE        | A late binding assign, see 4.3.1.3                   |
| DLT_NONBINDING  | A non-binding assign, see 4.3.1.3                    |

`dol_Task` is the *MsgPort* of the handler to contact for the particular *handler*, *assign* or *volume*. It may be `NULL` if the *handler* is not started, or a new handler process is supposed to be started for each file opened. This is, for example, the case for the console which requires a process for each window it handles. *File systems* usually provide their port here such that the same process is used for all objects on the volume. *Volumes* keep here the *MsgPort* of the *file system* that operates the volume, but it to `NULL` in case the volume goes away, e.g. is ejected. For *regular assigns*, this is also the pointer to the *MsgPort* of the *file system* the assign binds to; in case the assign is a *multi-assign*, this is the *MsgPort* of the first directory bound to. All additional ports are part of the `AssignList`. For *late assigns* this member is initially `NULL`, but will be filled in as soon as the assign is bound to a particular directory, and then becomes the pointer to the *MsgPort* of the handler the assign is bound to. Finally, for *non-binding assigns* this member always stays `NULL`.

`dol_Lock` is only used for *assigns*, and only if it is bound to a particular directory. That is, the member remains `ZERO` for *non-binding assigns* and is initially `ZERO` for *late assigns*. For all other types, this member stays `ZERO`.

`dol_Name` is a *BPTR* to a *BSTR* is the name under which the *handler*, *volume* or *assign* is accessed. That is, this string corresponds to the path component upfront the colon. As a courtesy to C and assembler functions, AmigaDOS ensures that this string is NUL terminated, i.e. `dol_Name + 1` is a regular C string whose length is available in `dol_Name[0]`.

The members within `dol_handler` are used by *handlers* and *file systems*, i.e. if `dol_Type` is `DLT_DEVICE`.



`dol_Handler` is a *BPTR* to a *BSTR* containing the file name from which the *handler* or *file system* is loaded from. It corresponds to the `Handler`, `FileSystem` and `EHandler` fields of the mount list. They all deposit the file name here.

`dol_StackSize` specifies the size of the stack for creating the *handler* or *file system* process. Interestingly, the unit of the stack size depends on the `dol_GlobVec` entry. If `dol_GlobVec` is negative indicating a C or assembler handler, `dol_StackSize` is in bytes. Otherwise, that is, for BCPL handlers, it is in 32-bit long words. This member corresponds to the `Stacksize` entry of the mount list.

`dol_Priority` is priority of the handler process. Even though it is a `LONG`, it shall be a number between `-128` and `127` because priorities of the exec task scheduler are `BYTES`. For all practical purposes, the priority should be a value between `0` and `19`. It corresponds to the `Priority` entry of the mount list.

`dol_Startup` is a handler-specific startup value that is used to communicate a configuration to the handler during startup. While this value may be whatever the handler requires, the `mount` command either deposits here a small integer, or a pointer to the `FileSysStartupMsg` structure defined in `dos/filehandler.h`. Section ?? provides more details on mounting handlers and how the startup mechanism works. Unfortunately, it is hard to interpret `dol_Startup` correctly. One way to set this member is to set `Startup` in the mount list, see 8.1.2 for details.

`dol_SegList` is a *BPTR* to the chained segment list of the handler if it is loaded. For disk-based handlers, this member is initially `ZERO`. When a program attempts to access a file on the handler, the *dos.library* first checks whether this field is `ZERO`, and if so, attempts to find a segment, i.e. a binary, for the handler. If the `FORCELOAD` entry of the mount list is non-zero, the `mount` command already performs this activity. The process of loading a handler depends on the nature of the handler and explained in more detail in section ??.

`dol_GlobVec` identifies the nature of the handler as AmigaDOS supports (still) BPCL and C/assembler handlers and defines how access to the *dos list* is secured for handler loading and startup. BCPL handlers use a somewhat more complex loading and linking mechanism as the language-specific *global vector* needs to be populated. This is not required for C or assembler handlers where a simpler mechanism is sufficient, more on this in section ??.

Another aspect of the startup process is how the *device list* is protected from conflicting accesses from multiple processes. Two types of access protection are possible: Exclusive access to the list, or shared access to the list. Exclusive access protects the *device list* from any changes while the handler is loaded and until handler startup completed. This prevents any other modification to the list, but also read access from any other process to the list. Shared access allows read accesses to the list while preventing exclusive access to it.

The value in `dol_GlobVec` corresponds to the `GlobVec` entry in the mount list. It shall be one of the values in table 26.

**Table 26: GlobVec Values**

| dol_Type | Description   |
|----------|---|
| -1       | C/assembler handler, exclusive lock on the <i>dos list</i>          |
| -2       | C/assembler handler, shared lock on the <i>dos list</i>             |
| 0        | BCPL handler using system GV, exclusive lock on the <i>dos list</i> |
| -3       | BCPL handler using system GV, shared lock on the <i>dos list</i>    |
| >0       | BPCL handler with custom GV, exclusive lock on the <i>dos list</i>  |

The values `0`, `-3` and `> 0` all setup a BCPL handler, but differ in the access type to the *device list* and how the BCPL *global vector* is populated. This vector contains all global objects and all globally reachable functions of a BCPL program, including functions of the *dos.library*. The values `0` and `-3` fill this vector with the system functions first, and then use the BPCL binding mechanism to extend or override entries in this vector with the values found in the loaded code. Any values `> 0` defines a *BPTR* to a custom vector which is used instead for initializing the handler. This startup mechanism has never been used in AmigaDOS and is not quite practical as this vector needs to be communicated into the *dos.library* somehow. For new code, BCPL linkage and binding should not be used anymore.

---

Members of the `dol_volume` structure are used if `dol_Type` is `DLT_VOLUME`, identifying this entry as belonging to a known specific data carrier.

`dol_VolumeDate` is the creation date of the volume. It is a `DateStamp` structure that is specified in section ???. It is used to uniquely identify the volume, and to distinguish this volume from any other volume of the same name.

`dol_LockList` is a pointer to a singly-linked list of *locks* on the volume. This list is created by the *file system* when the volume is ejected, and contains all locks on this volume. It is stored here to allow a similar file system to pick up the locks once the volume is re-inserted, even if it is re-inserted into another device. Note that the linkage is performed with *BPTRs* and the `fl_Link` member of the `FileLock` structure.

`dol_DiskType` is an identifier of the *file system type* that operated the volume and placed here such that an alternative process of the same file system is able to pick up or refuse the locks stored here for non-available volumes.

Members of the `dol_assign` structure are used for all other types, i.e. all types of *assigns*.

`dol_AssignName` is pointer to the target name of the assign for *non-binding* and *late assigns*. The *dos.library* uses this string to locate the target of the assign. For *late assigns*, this member is used only on the first attempt to access the assign at which `dol_Lock` is populated.

`dol_List` contains additional locks for *multi-assigns* and is only used if `dol_Type` is `DLT_DIRECTORY`. In such a case, `dol_Lock` is the lock to the first directory of the *multi-assign*, while `dol_List` contains all following *locks* in a singly-linked list of `AssignList` structures:

```
struct AssignList {
    struct AssignList *al_Next;
    BPTR               al_Lock;
};
```

`al_Next` points to the next *lock* that is part of the *multi-assign* and `al_Lock` is the lock itself. This structure is also defined in `dos/dosextens.h`.

## 8.1 The Device List and the Mount List

Entries of the type `DLT_DEVICE` can be created through a `Mountlist` and the `Mount` command. Other sources of these entries are the *expansion.library* which is called from autoconfiguring boot devies, such as SCSI hostadapters or other media interfaces.

Many keywords in the `Mountlist` map directly to entries in the `DosList` structure, others to entries in the `FileSysStartupMsg` and the `DosEnvec` structure pointed to there.

### 8.1.1 Keywords defining the `DosList` structure

The `HANDLER`, `EHANDLER` and `FILESYSTEM` keywords in the `Mountlist` do all three into the `dol_Handler` member. Which keyword is used impacts, however, other elements of the `DosList`, most notably `dol_Startup`.

The `STACKSIZE` keyword sets `dol_StackSize` element. This is in bytes for C and assembler handlers, and in long-words for BCPL handlers. The type of the handler is determined by `GLOBVEC`.

The `PRIORITY` keyword sets `dol_Priority` and with that the priority of the process running the handler.

The `GLOBVEC` keyword sets `dol_GlobVec` element, and by that also the type of the handler. Table 26 in 8 lists the possible values and their interpretation.

If the `HANDLER` keyword is present, the `STARTUP` entry in the `Mountlist` sets `dol_Startup`. It can be either an integer value, or if the argument is enclosed in double quotes, a string. In the latter case,

---

`dol_Startup` is set to a *BPTR* to a *BSTR* that is, to ease handler implementation, also NUL terminated. The terminator is, however, not included in the size of the *BSTR*. It is therefore up to the user to ensure that the arguments in the `Mountlist` are what the handler expects.

### 8.1.2 Keywords controlling the FileSysStartupMsg

If the `EHANDLER` or `FILESYSTEM` keyword is present, `dol_Startup` is instead a *BPTR* to a `FileSysStartupMsg` structure, defined in `dos/filehandler.h`:

```
struct FileSysStartupMsg {
    ULONG      fssm_Unit;
    BSTR        fssm_Device;
    BPTR        fssm_Environ;
    ULONG      fssm_Flags;
};
```

It is again up to the user to ensure that the handler is really expecting such a structure and setup the `Mountlist` appropriately.

The elements of the above structure identify an exec type device on top of which the *handler* or *file system* is supposed to operate. Some extended handlers, i.e. `EHANDLERS`, also use this structure; the `V47 Port-Handler` can be setup this way to operate on top of a third-party serial device driver.

The `DEVICE` keyword of the `Mountlist` sets `fssm_Device` entry. This element is initialized to a *BSTR*. To avoid further string conversion when calling `OpenDevice()`, this *BSTR* is NUL-terminated.

The `UNIT` keyword sets `fssm_Unit` and therefore the unit number of the exec device on top of which the file system or handler should operate.

The `FLAGS` keyword sets `fssm_Flags` element, and thus the flags for opening an exec type. Its purpose and meaning is specific to the device identified by `fssm_Device`.

### 8.1.3 Keywords controlling the Environment Vector

The `fssm_Environ` element of the `FileSysStartupMsg` is a *BPTR* to another structure that describes, amongst others, the layout of a *file system* on a disk; beyond *file systems*, extended handlers mounted by the `EHANDLER` keyword may also make use of it.

This structure is also defined in `dos/filehandler.h` and looks as follows:

```
struct DosEnvec {
    ULONG de_TableSize;      /* Size of Environment vector */
    ULONG de_SizeBlock;      /* in longwords: physical disk block size */
    ULONG de_SecOrg;         /* not used; must be 0 */
    ULONG de_Surfaces;       /* # of heads (surfaces). drive specific */
    ULONG de_SectorPerBlock; /* physical sectors per logical block */
    ULONG de_BlocksPerTrack; /* blocks per track. drive specific */
    ULONG de_Reserved;       /* DOS reserved blocks at start of partition. */
    ULONG de_PreAlloc;       /* DOS reserved blocks at end of partition */
    ULONG de_Interleave;     /* usually 0 */
    ULONG de_LowCyl;         /* starting cylinder. typically 0 */
    ULONG de_HighCyl;        /* max cylinder. drive specific */
    ULONG de_NumBuffers;     /* Initial # DOS of buffers. */
    ULONG de_BufMemType;     /* type of mem to allocate for buffers */
    ULONG de_MaxTransfer;    /* Max number of bytes to transfer at a time */
    ULONG de_Mask;           /* Address Mask to block out certain memory */
};
```



```
LONG   de_BootPri;          /* Boot priority for autoboot */
ULONG  de_DosType;          /* ASCII (HEX) string showing filesystem type;
                             * 0X444F5300 is old filesystem,
                             * 0X444F5301 is fast file system */
ULONG  de_Baud;             /* Baud rate for serial handler */
ULONG  de_Control;          /* Control word for handler/filesystem */
ULONG  de_BootBlocks;       /* Number of blocks containing boot code */

};
```

The elements in this structure, except the first one, are also initialized by keywords in the mount list.

`de_TableSize` defines how many elements in this structure are actually valid and thus may be accessed by the *handler* or *file system*. It is *not* a byte count, but an element count, excluding `de_TableSize`. In other words, the `DosEnvec` is a typical BCPL vector whose vector size is indicated in its first element — note that all elements of the structure are 32-bits wide.

The keyword `SECTORSIZE` and `BLOCKSIZE` set both `de_SizeBlock`. While the `Mountlist` keywords take a byte count, this byte count is divided by 4 to form a long-word count that is inserted into `de_SizeBlock`. As the name suggests, it defines the size of a storage unit on a medium. Typical values are 128 for 512 byte blocks, or 1024 for 4096 byte blocks. However, not all file systems support all block sizes, and some only support the default value of 128, i.e. 512 byte blocks, the `Mount` command fills in without further information.

`de_SecOrg` is not used and shall be 0; consequently, the `Mount` command does not provide a keyword to set it.

The `SURFACES` keyword sets `de_Surfaces`. A possible meaning for this member is to interpret it as the number of read-write heads of a magnetic disk drive. However, as the `exec` device `trackdisk` interface for magnetic storage media does not actually allow access to such low-level features that are rather abstracted away by the device, *file systems* rather use this value along with `de_BlocksPerTrack` the number of cylinders computed from `de_LowCyl` and `de_HighCyl` to determine the capacity of the medium.

The `SECTORS PER BLOCK` keyword sets the `de_SectorsPerBlock`, and thus the number of physical sectors on a disk the *file system* combines to one logical storage block. Not all *file systems* support values different from 1 here; the FFS does, and always reads and writes data in units of `de_SectorsPerBlock` times `de_SizeBlock` of long-words. For the `exec trackdisk` interface, the byte size is the only value that matters; however, the “direct SCSI” transfer latest FFS releases offer addresses the disk in terms of physical sectors, and then `de_SizeBlock` defines the size of a sector in long-words as addressed by SCSI commands, whereas `de_SectorsPerBlock` is the number of physical sectors the FFS reads for one logical block.

The `SECTORS PER TRACK` and `BLOCKS PER TRACK` keywords set both the `de_BlocksPerTrack` element of the `DosEnvec` structure. The first name is actually most appropriate as this element defines the number of physical sectors, and not the number of logical blocks a track of a disk contains. Thus, naming is a historical accident. As for the `SURFACES` keyword, the number of sectors per track is only in so far relevant as it defines along with the first and last cylinder the storage capacity of the medium or partition. The values never enter the `exec` layer.

The `RESERVED` keyword sets the `de_Reserved` element of `DosEnvec` and defines the number of (logical) blocks not used by the *file system* at the start of the disk or partition. For floppies, these reserved blocks hold a (minimal) boot procedure that initializes the *dos.library*.

The `PREALLOC` keyword installs the `de_PreAlloc` element, which is supposed to be the number of logical blocks set aside at the end of the partition. However, current FFS versions completely ignore this element.

The `INTERLEAVE` keyword defines the lower 16 bits of the `de_Interleave` element. TRIPOS might have reserved the entire long-word to define the interleave factor of the disk, and the difference between two

---

sector addresses the file system is supposed to reserve for subsequent storage. This interleave factor helped to speed up transfers for ancient harddisks, but neither the original OFS nor the latest FFS make use of this mechanism and allocate sectors contiguously, i.e. with an interleave factor of 1. The upper 16 bits of `de_Interleave` suit now a different purpose and are set by separate keywords of `Mount`.

The `LOWCYL` keyword initializes the `de_LowCyl` element of the `DosEnvec` structure. It sets the lower end of the partition on the storage medium, i.e.  $\text{de\_LowCyl} \times \text{de\_Surfaces} \times \text{de\_BlocksPerTrack} + \text{de\_Reserved} \times \text{de\_SectorsPerBlock}$  is the first physical sector number on a disk that can carry payload data of the file system.

The `HIGHCYL` keyword sets the `de_HighCyl` element; it defines the (inclusive) upper end of the partition in units of cylinders. That is,  $(\text{de\_HighCyl} + 1) \times \text{de\_Surfaces} \times \text{de\_BlocksPerTrack} - 1$  is the last sector of the partition or medium the *file system* can allocate for payload data.

The `BUFFERS` keyword sets the `de_NumBuffers` element; it defines the (initial) number of file system buffers allocated for caching metadata and storing data not directly accessible through the `exec` device driver. The number of buffers may be changed later with `AddBuffers()`, see section 7.0.1. Each buffer is one (logical) block large.

The `BUFMEMTYPE` defines the `de_BufMemType` element. It defines the memory type, i.e. the second argument of `AllocMem()`, for allocating memory keeping the file system buffers. While `exec` device drivers should be able read and write data to any memory type, several legacy rivers may not be able reach all memory; this may be due to limitations of the hardware such that Zorro-II hardware cannot reach 32-bit memory. Thus, depending on limitations of the `fssm_Device`, it is unfortunately up to the user to provide a suitable `BUFMEMTYPE`.

The `MASK` keyword defines the `de_Mask` element of the `DosEnvec` structure. The mask is a workaround for defect device drivers that cannot read or write to all memory types. In particular, if the address of the host memory buffer has bits set in positions where the mask contains 0 bits, the *file system* shall assume that the device cannot reach this memory. Instead, it shall perform input or output indirectly through its buffers, and copy with the CPU between those buffers and the target or source memory block.

**Masking Defects** The purpose of the mask is to hide defects in device drivers and provide a working system in the absense of a fully functional device driver. A rather typical value for the mask is `0x00ffffff`, indicating that the device cannot reach 32-bit memory. A suitable memory type would then be `MEMF_24BITDMA | MEMF_PUBLIC`, i.e. 513 as decimal value. This requests 24-bit memory for the buffers. Note that providing a mask is useless if the memory type does not allocate memory that fits to the mask.

The `MAXTRANSFER` keyword sets `de_MaxTransfer`. This value sets the maximum number of bytes the *file system* shall read or write by a single I/O operation. Similar to `MASK`, it is a workaround required to avoid problems with defect device drivers that corrupt data if too many bytes are read or written in one go.

**MaxTransfer is not a rate** The `MaxTransfer` keyword or element describe a byte count that, when exceeded, requests the file system to break up transfers. While that implicitly limits the throughput of the device, it does not define a rate (i.e. in units of bytes per second), as the problem device drivers have is typically not the transfer rate, but the amount of data to transfer.

The `BOOTPRI` keyword sets the `de_BootPri` element which defines the order in which the system attempts to boot from a partition or medium. Obviously, it makes little sense to set this keyword in a `Mountlist` that is interpreted after the system had already booted. However, autobooting devices may set an appropriate value here, for example by reading it from the RDB of its disk.

The `DOSTYPE` keyword sets the `de_DosType` element, identifying the type and flavour of the file system to use for the medium or partitiion. If the `FILESYSTEM` keyword is present, but the `FORCELOAD` is either not present or set to 0, then the `Mount` command first attempts to find a suitable file system in the

FileSystem.resource whose fse\_DosType matches de\_DosType, avoiding to load the same file system again. If a match is found, the FileSysEntry of the resource is used to initialize the DosEnvec, in particular dol\_SegList. Table 27 in lists the available file systems.

**Table 27: Fast File System Flavours**

| <b>FFS Flavour</b>   | <b>Description</b>                                 |
|----------------------|--|
| ID_DOS_DISK          | Original file system (OFS)                         |
| ID_FFS_DISK          | First version of FFS                               |
| ID_INTER_DOS_DISK    | International variant of OFS                       |
| ID_INTER_FFS_DISK    | International variant of FFS                       |
| ID_FASTDIR_DOS_DISK  | OFS variant with directory cache                   |
| ID_FASTDIR_FFS_DISK  | FFS variant with directory cache                   |
| ID_LONG_DOS_DISK     | OFS variant with 106 character file name size      |
| ID_LONG_FFS_DISK     | FFS variant with 106 character file name size      |
| ID_COMPLONG_FFS_DISK | FFS with 54 character file names compatible to FFS |
| 'MSD\0'              | FAT on a disk without partition table              |
| 'MDD\0'              | identical to the above, FAT on a floppy            |
| 'MSH\0'              | FAT on a partition                                 |
| 'FAT\0'              | FAT, switched by the SuperFloppy disk              |
| 'CD0\0'              | Original CD File system                            |
| 'CD0\1'              | CD File System with Joliet support                 |

The first part of the table indicates various versions of the ROM file system; the original version from TRIPOS is here denoted as OFS, though this name mostly distinguishes it from its later reimplementations, the FFS.

The OFS variants embed additional administration information into the data blocks and thus carry less payload data per block, and for that are more robust, but are slower as the data cannot be transmitted by DMA into the host memory but requires an additional copy. The first FFS variant addresses this issue. Both first types use, however, a non-suitable algorithm for case-insensitive comparison of file names and thus do not interpret character from the extended ISO-Latin-1 set (i.e. printable characters outside the ASCII range) correctly. Thus, the first two types should be avoided.

Proper case-insensitive interpretation of file names was added afterwards, leading to the next two flavours which are otherwise identical. All types from that point on in table 27 until its end use the correct algorithm to compare file names.

The next two versions administrate an additional directory cache; while this cache typically speeds up listing the directory, it also requires additional update steps when adding or renaming files, making such operations slower and more error prone. These variants unfortunately also lack a good algorithm to clean up the cache if objects are continuously added and removed from directories. These variants are not generally recommended and should be considered experimental.

The LONG variants of OFS and FFS allow file names of up to 106 characters by using a slightly modified block syntax which overcomes the 30 character file name limit all above variants suffer from. They also use the correct case-insensitive file name comparison. In some rare cases, the administration information is augmented by one additional block keeping a long comment.

The last variant offers a compatible form of long file names that is backwards compatible to earlier variants of the FFS. The file name limit is here 54 characters, though older versions of the FFS can still read the disk correctly, even though they will not be able to locate or list longer file names. This variant is also experimental.

The next group of types indicates various flavours of the MS-DOS FAT file system. The first two types are identical and correspond to a file system on a single disk without a partition table, as found on floppy disks. They are unsuitable for harddisk partitions and thumbdrive partitions.

---

The second type indicates FAT on a Master Boot Record (MBR) partition as used on (legacy) PC hardware. As AmigaDOS does not natively support the MBR, the file system here (as an architectural tweak) interprets the partition table. Which partition is used is then depending on the last character of the device name, i.e. `do1_Name`. The C character indicates the first partition, adopting the convention of the operating system to which FAT is native, the second partition is indicated by the last character of `do1_Name` being D and so on.

The last type indicates a file system either on a floppy or the first partition of a MBR-formatted disk, depending on the `SUPERFLOPPY` keyword, see below.

The last group indicates various versions of the CD-Rom — actually ISO Rock Ridge — file system. The first type is the original file system that came with V40 of AmigaDOS, the second the extended version that includes support for Joliet extensions and audio track support. Otherwise, the types are identical.

The `BAUD` keyword fills the `de_Baud` element; it is obviously not used by *file systems* but extended handlers that are indicated by the `EHANDLER` keyword. For them, it provides the baud rate for an (assumed) serial connection.

The `CONTROL` keyword sets the `de_Control` element. Even though this element is here indicated as an `ULONG`, it can be either an integer or a string. In the latter case, the argument to `CONTROL` shall be enclosed in double quotes, and the `Mount` command then places a *BPTR* to a *BSTR* in this element. Again, it is up to the user to learn from the handler documentation what the handler expects to find in the `DosEnvec` structure as there is no type check and no place where the type is indicated.

The `BOOTBLOCKS` keyword initializes the `de_BootBlocks` element; it is currently not used by any AmigaDOS file system. The FFS instead depends on `de_Reserved`.

The `SUPERFLOPPY` keyword takes a boolean 0 or 1 argument and by that either sets or clears the `ENVF_SUPERFLOPPY` flag. This flag has been cut off (or reserved) from the otherwise deprecated and thus unused `de_Interleave` element. It is by default cleared.

If this flag in `de_Interleave` is set, then the file system is informed that the partition extends over the entire medium and no partition table or RDB is found. Instead, to find the size of the medium, the file system is authorized to issue a `TD_GETGEOMETRY` command to the low level device driver which will report the layout of the disk. This driver information is then used to adjust `de_LowCyl`, `de_HighCyl`, `de_SizeBlock` and `de_Surfaces`. Thus, a file system mounted with this flag set is able to extract the device layout directly from the hardware driver. This is important for drives that allow variously sized media, such as floppy disks (supporting both DD and HD disks) as well as ZIP drives (supporting 100MB to 250MB drives).

AmigaDOS up to release V40 hardwired this special case to the `trackdisk.device` and `carddisk.device`, i.e. the floppy and memory cards in the PCMCIA slot, though newer releases allow to extend this mechanism to other device drivers as well. As of V47, the FAT and ROM file system both support this mechanism, though it has to be enabled with the `'FAT\0'` `dostype` for the former driver.

The `SCSIDIRECT` keyword is also a boolean 0/1 indicator and controls the `ENVF_SCSIDIRECT` flag which is also part of the otherwise deprecated `de_Interleave` element. It is cleared by default, indicating that the file system should use the `trackdisk` command set to access data.

If this flag is enabled, the file system is instructed to communicate with the underlying device through the `HD_SCSICMD` interface, i.e. SCSI commands. This may help some legacy device drivers that do not speak the 64-bit dialect of the `trackdisk` commands to access data beyond the 4GB barrier. Very ancient device drivers may not even support this command type.

The `ENABLENSD` keyword is again a boolean 0/1 indicator for the `ENVF_DISABLENSD` flag cut off from the `de_Interleave` field; it is, however, set in inverse logic, i.e. the `ENVF_DISABLENSD` is set if the mount parameter is 0, and reverse.

If the flag in `de_Interleave` is set, and thus `ENABLENSD` is set to 0 in the mount list, the file system is instructed not to attempt to use NSD-style commands to access data beyond the 4GB barrier. This may

---

be necessary on some device drivers that ignore the most significant bits of the `io_Command` field or react otherwise allergic to commands beyond the usual range.

Unfortunately, multiple command sets exist to access (moderately) large disks. If `DIRECTSCSI` is enabled, SCSI commands will always be used, even for probing the medium size if `SUPERFLOPPY` is set. If SCSI commands are not enabled, the FFS first attempts to use regular `trackdisk` commands if the requested region of the device does not cross the 4GB barrier. If that is not possible, it probes the TD64 command set as it is historically the most popular extension. As last resort, it tries NSD commands. This last step can be disabled by the line `ENABLENSD = 0` in the `Mountlist` if it creates problems.

The `ACTIVATE` keyword in the `Mountlist` is synonym to the `MOUNT` keyword, and it also takes a boolean 0/1 indicator. If it is set, then the `Mount` command will already load and initiate the handler corresponding to the mount entry, even if it is at this point not yet needed.

The `FORCELOAD` keyword of the `Mountlist`, finally, is another boolean 0/1 flag. If it is set to 1, it indicates to the `Mount` command not to scan the `FileSystem.resource` for a fitting `dostype` but rather forcibly load the *file system* from the path indicated by the `FILESYSTEM` keyword. This option is, for example, useful for testing.

## 8.2 Finding Handler or File System Ports

The following functions find the *MsgPort* of the *handler* or *file system* that is responsible for a given object. The functions search the *device list*, check whether the handler is already loaded or load it if necessary, then check whether the handler is already running, and if not, launch an instance of it. If *multi-assigns* are involved, it can become necessary to contact multiple *file systems* to resolve the task and thus to iterate through multiple potential *file systems* to find the right one.

### 8.2.1 Iterate through Devices Matching a Path

The `GetDeviceProc()` find a handler, or the next handler responsible for a given path. Once the handler has been identified, or iteration through matching handlers is to be aborted, `FreeDeviceProc()` shall be called to release temporary resources.

```
devproc = GetDeviceProc(name, devproc)
D0          D1          D2

struct DevProc *GetDeviceProc(STRPTR, struct DevProc *)
```

This function takes a path in `name` and either `NULL` on the first iteration or a `DevProc` structure from a previous iteration and returns either a `DevProc` structure in case a matching handler could be identified, or `NULL` if no matching handler could be found or all possible matches have been iterated over already.

**Give back what you got** To release all temporary resources, the `DevProc` structure returned by `GetDeviceProc()` shall be either be released through `FreeDeviceProc()` then aborting the scan, or used as first argument for `GetDeviceProc()` to continue the iteration. The last call to this function will return `NULL` and then also release all resources.

The `DevProc` structure, defined in `dos/dosextens.h` looks as follows:

```
struct DevProc {
    struct MsgPort *dvp_Port;
    BPTR          dvf_Lock;
    ULONG         dvf_Flags;
    struct DosList *dvp_DevNode; /* DON'T TOUCH OR USE! */
};
```



---

`dvp_Port` is a pointer to a candidate *MsgPort* that should be tried to resolve *name*.

If the matching handler is a *file system*, then `dvp_Lock` is a *lock* of a directory. The path in *name* is a path relative to this directory. This *lock* shall not be released, but it may be copied with `DupLock`.

`dvp_Flags` identifies the nature of the found port. If the bit `DVPB_ASSIGN` is set, i.e. `dvp_Flags & DVPF_ASSIGN` is non-zero, then the found match is part of a *multi-assign* and `GetDeviceProc()` may be called again with the `devproc` argument just returned as second argument. This will return another candidate for a path. `DVPB_UNLOCK` is another bit of the flags but shall not be interpreted and is only used internally by the function.

The member `dvp_DevNode` shall not be touched or used and is required internally by the function.

If the function returns `NULL`, then `IoErr()` provides additional information on the failure. If the error code is `ERROR_NO_MORE_ENTRIES`, then the last directory of a *multi-assign* has been reached. If the error code is `ERROR_DEVICE_NOT_MOUNTED`, then no matching device could be found. Other errors may be returned, e.g. if the function could not allocate sufficient memory for its operation.

Unfortunately, the function does not set `IoErr()` consistently if `GetDeviceProc()` is called again on an existing `DevProc` structure as second argument with `DVPB_ASSIGN` cleared. `IoErr()` remains then unaltered and it is therefore advisable to clear it upfront.

The function also returns `NULL` if *name* corresponds to the `NIL:` pseudo-device and then sets `IoErr()` to `ERROR_DEVICE_NOT_MOUNTED`. This is not fully correct, and callers need to be aware of this defect.

Also, `GetDeviceProc` does not handle the path “\*” at all, even though it indicates the current console and the *Console-Handler* is responsible for it. This case also needs to be detected by the caller, and in such a case, `GetConsoleTask()` delivers the correct port.

**Does not like all paths** The `GetDeviceProc()` function unfortunately does not handle all device specifiers correctly, and some special cases need to be filtered out by the caller. Namely “\*” indicating the current console, and `NIL:` for the `NIL` pseudo-device are not handled here.

## 8.2.2 Releasing DevProc Information

The `FreeDeviceProc()` function releases a `DevProc` structure previously returned by `GetDeviceProc()` and releases all temporary resources allocated by this function. It shall be called as soon as the `DevProc` structure is no longer needed.

```
FreeDeviceProc(devproc)
                D1
```

```
void FreeDeviceProc(struct DevProc *)
```

This function releases the `DevProc` structure and all its resources from an iteration through one or multiple `GetDeviceProc()` calls. If `GetDeviceProc()` returned `NULL` itself it had already released such resources itself and no further activity is necessary.

The `dvp_Port` or `dvp_Lock` within the `DevProc` structure shall not be used after releasing it with `FreeDeviceProc()`. If a *lock* is needed afterwards, a copy of `dvp_Lock` shall be made with `DupLock()`. If the port of the *handler* or *file system* is needed afterwards, a resource of this handler shall be obtained, e.g. by opening a file or obtaining a lock on it. Both the `FileHandle` and the `FileLock` structures contain a pointer to the port of the corresponding handler.

It is safe to call `FreeDeviceProc()` with a `NULL` argument; this performs no activity.

This function does not set `IoErr()` consistently and no particular value may be assumed. It may or may not alter its value.

---

### 8.2.3 Legacy Handler Port Access

The `DeviceProc()` function is a legacy variant of `GetDeviceProc()` that should not be used anymore. It is not able to reliably provide locks to *assigns* and will not work through all directories of a *multi-assign*.

```
process = DeviceProc( name )
D0                                     D1
```

```
struct MsgPort *DeviceProc (STRPTR)
```

This function returns a pointer to a port of a *handler* or *file system*able to handle the path `name`. It returns `NULL` on error in which case it sets `IoErr()`.

If the passed in `name` is part of an *assign*, the handler port of the directory the assign binds to is returned, and `IoErr()` is set to the *lock* of the assign. Unfortunately, one cannot safely make use of this *lock* as the *device list* may be altered any time, including the time between the return from this function and its first use by the caller. Thus, `GetDeviceProc()` shall be used instead which locks resources such as the *device list*; they are released through `FreeDeviceProc()`.

**Obsolete and not fully functional** `DeviceProc()` function does not operate properly on *multi-assigns* where it only provides the port and *lock* to the first directory participating in the assign. It also returns `NULL` for *non-binding assigns* as there is no way to release a temporary lock obtained on the target of the *assign*. Same as `GetDeviceProc()`, it does not properly handle `NIL:` and `"*"`.

### 8.2.4 Obtaining the Current Console Handler

The `GetConsoleTask()` function returns the *MsgPort* of the handler responsible for the console of the calling process, that is, the process that takes care of the file name `"*"` or paths relative to `CONSOLE:`.

```
port = GetConsoleTask()
D0
```

```
struct MsgPort *GetConsoleTask(void)
```

This function returns a port to the handler of the console of the calling process, or `NULL` in case there is no console associated to the caller. The latter holds for example for programs started from the workbench. It does not alter `IoErr()`.

### 8.2.5 Obtaining the Default File System

The `GetFileSysTask()` function returns the *MsgPort* of the default *file system* of the caller. The default *file system* is used as fall-back if a *file system* is required for a path relative to the `ZERO` lock, and the path itself does not contain an indication of the responsible handler, i.e. is a relative path itself.

The default *file system* is typically the boot file system, or the file system of the `SYS:` *assign*, though it can be changed with `SetFileSysTask()` at any point.

```
port = GetFileSysTask()
D0
```

```
struct MsgPort *GetFileSysTask(void)
```

This function returns the port of the default file system of this task. It does not alter `IoErr()`. Note that `SYS:` itself is an *assign* and paths starting with `SYS:` do therefore not require resolution through this function, though the default *file system* and the file system handling `SYS:` are typically identical. However, as the former is returned by `GetFileSysTask()` and the latter is part of the *device list assign*, they can be different.

---

## 8.3 Iterating and Accessing the Device List

While `GetDeviceProc()` uses the *device list* to locate a particular *MsgPort* and *Lock*, all other members of the `DosList` structure remain unavailable. For them, the *device list* containing these structures need to be scanned manually. The *dos.library* provides functions to grant access, search and release access to this list.

### 8.3.1 Gaining Access to the Device List

The `LockDosList()` function requests shared or exclusive access to a subset of entries of the *device list* containing all *handlers*, *volumes* and *assigns* and blocks until access is granted. It requires as input multiple sets that specify which parts of the list to access:

```
dlist = LockDosList(flags)
      D0                      D1
```

```
struct DosList *LockDosList(ULONG)
```

This function grants access to a subset of entries of the *device list* indicated by `flags`, and returns an opaque handle through which elements of the list can be accessed. For this, see `FindDosEntry()`.

The `flags` value shall be combination of the following values, all defined in `dos/dosextens.h`:

**Table 28: LockDosList Flags**

| Flags       | Description  |
|-------------|--|
| LDF_DEVICES | Access <i>handlers</i> and <i>file system</i> entries, see 4.3.1.1 |
| LDF_VOLUMES | Access <i>volumnes</i> , see 4.3.1.2                               |
| LDF_ASSIGNS | Access <i>assigns</i> , see 4.3.1.3                                |
| LDF_ENTRY   | Lock access to a <code>DosList</code> entries                      |
| LDF_DELETE  | Lock <i>device list</i> for deletion                               |
| LDF_READ    | Shared access to the <i>device list</i>                            |
| LDF_WRITE   | Exclusive access to the <i>device list</i>                         |

At least `LDF_READ` or `LDF_WRITE` shall be included in the flags, they shall not be set both. The three first flags may also be combined to access multiple types.

`LDF_ENTRY` and `LDF_DELETE` are additional flags that moderate access to entries of the *device list*. If `LDF_ENTRY` is set, then exclusive access to the selected entries is requested and entries shall not be altered or removed. The `LDF_ENTRY` flag shall not be combined with `LDF_READ`. If `LDF_DELETE` is set, then access is granted for removing entries from the list.

The result code `dlist` is *not* a pointer to a `DosList` structure, but only a handle that may be passed into `FindDosEntry()` or `NextDosEntry()`. If `dlist` is `NULL`, then locking failed because the combination of flags passed in was invalid.

This function does not alter `IoErr()`.

### 8.3.2 Requesting Access to the Device List

The `AttemptLockDosList()` requests access to the *device list* or a subset of its entries, and, in case it cannot gain access, returns `NULL`. Unlike `LockDosList()`, it does not block.

```
dlist = AttemptLockDosList(flags)
      D0                      D1
```

```
struct DosList *AttemptLockDosList(ULONG)
```

---

The `flags` argument specifies which elements of the *device list* are requested for access, and which type of access is required. The flags are a combination of the flags listed in table 28, and the semantics of the flags are exactly as specified for `LockDosList()`, see there for details.

The result code is either a (non-NULL) handle that may be passed into `FindDosEntry()` or `NextDosEntry()` in case access could be granted, or NULL. In the latter case, the list is either currently locked and access cannot be granted without blocking, or flags are invalid. These two cases of failure cannot be distinguished unfortunately.

This function does not alter `IoErr()`.

### 8.3.3 Release Access to the Device List

The `UnLockDosList()` function releases access to the *device list* once obtained through `LockDosList()`.

```
UnLockDosList(flags)
                D1
```

```
void UnLockDosList(ULONG)
```

This function releases access to the *device list* again. The `flags` argument shall be identical to the `flags` argument provided to `LockDosList()`.

### 8.3.4 Iterate through the Device List

The `NextDosEntry()` iterates to the next entry in the *device list* given the current entry or the handle returned by `LockDosList()`.

```
newdlist = NextDosEntry(dlist, flags)
D0                D1    D2
```

```
struct DosList *NextDosEntry(struct DosList *, ULONG)
```

This function returns the next `DosList` structure of the *device list* which shall have been locked with `LockDosList()`. The `dlist` argument shall be either the return code of a previous `NextDosEntry()` or `FindDosEntry()` call, or the handle returned by `LockDosEntry()`.

The `flags` argument shall be a subset of the `flags` argument into `LockDosList()` and specifies the type of `DosList` structures that shall be found. Only the first 3 elements of Table 28 are relevant here, all other flags are ignored but may be included.

The `newdlist` result is either a pointer to a `DosList` structure of the requested type, or NULL if the end of list has been reached. This function does not alter `IoErr()`.

### 8.3.5 Find a Device List Entry by Name

The `FindDosEntry()` function finds a `DosList` structure of a particular type and particular name, from a particular entry on, or the handle returned by `LockDosList()`.

```
newdlist = FindDosEntry(dlist, name, flags)
D0                D1    D2    D3
```

```
struct DosList *FindDosEntry(struct DosList *, STRPTR, ULONG)
```

---

This function scans through the *device list* starting at the entry `dlist`, or the handle returned by `LockDosList()`, and returns the next `DosList` structure that is of the type indicated by `flags` and has the name `name`.

The `flags` shall be a subset of the `flags` argument passed into `LockDosList()`. Only the first 3 elements of Table 28 are relevant here, all other flags are ignored but may be included.

The `name` argument is the (case-insensitive) name of the assign, handler, file system or volume the function should look for. The name *shall not* include the colon (':') that separates the name from the remaining components of a path, see section 4.3. It may be `NULL` in which case every entry of the requested type matches.

The returned `newdlist` is a pointer to a `DosList` structure that matches the name (if provided) and flags passed in, or `NULL` in case no match could be found and the entire list has been scanned. Note that the returned `DosList` may be identical to the `dlist` passed in if it already fits the requirements. Thus potentially, `NextDosList()` may be called upfront to scan from the subsequent entry.

Passing `NULL` as `dlist` is safe and returns `NULL`, i.e. the end of the list. Note that the (pseudo-) devices from tables 5 and 7 are not part of the *device list*, i.e. `NIL`, `CONSOLE`, `*` and `PROGDIR` cannot be found and are special cases of `GetDeviceProc()`.

This function does not alter `IoErr()`.

### 8.3.6 Accessing Mount Parameters

Once a `DosList` structure has been identified, e.g. by `FindDosEntry()`, it is tempting to understand whether the entry belongs to an assign or a volume, or a handler or file system, and in the latter two cases, to find the mount parameters of the handler or file system.

The first level of identification is easy and works through the `dol_Type` element of the `DosList` structure; table 25 in section 8 lists the possible entry types. As seen there, however, *handlers* and *file systems* share the same type, namely `DLT_DEVICE`.

Information on how a *file system* or a *handler* should be configured is found in the `dol_Startup` field; it is, however, up to the handler to interpret it, and AmigaDOS does not define what exactly it can contain. The `Mount` command can place three different types of objects here: An integer value, a *BPTR* to a *BSTR*, or a *BPTR* to a *FileSysStartupMsg*.

Unfortunately, there is no totally safe way how to distinguish these types, and AmigaDOS does not provide any further source of information to learn which type a handler expects here — thus a heuristics is needed to tell them apart.

In the first step, one should check whether the `dol_Startup` field is actually a *BPTR* pointing to valid memory. This is even the case for *file systems* mounted by the ROM, e.g. the `df0:` device:

```
void AnalyzeDosList(struct DosList *dl)
{
    LONG *startup;

    s=(LONG *) (dl->dol_Startup);
    if (s && TypeOfMem(BADDR(s)) && (LONG)s!=-1L && (LONG)s>0x100
        && ((LONG)s & 0xc0000000)==0) {
        /* Looks like a plausible BPTR */
        AnaylzeStartup((LONG *) (BADDR(s)));
    } else {
        /* Likely some sort of handler, and s is
        ** probably some integer
        */
    }
```

```

        ....
    }
}

```

The above algorithm uses `TypeOfMem()` to test whether a pointer goes into valid memory, and also checks the topmost two bits of the *BPTR*. As *BPTR*s are created by right-shifting a pointer by 2 bits, the two MSBs should thus be zero.

In the second step, the heuristics attempts to understand whether the *BPTR* in `dol_Startup` actually points to a `FileSysStartupMsg` or to a *BSTR*. For that, it attempts to learn whether the `fssm_Device` element is a valid *BSTR* and whether the `fssm_Envion` element is also a valid *BPTR*.

```

void AnalyzeStartup(LONG *startupmsg)
{
    BOOL isfsstart=TRUE;
    UBYTE *text;

    /* This checks whether fssm_Device
    ** is meaningful in order to derive
    **
    if (startupmsg[1] & 0xc0000000) {
        /* Certainly not a BPTR to
        ** a device name, bail out
        */
        isfsstart = FALSE;
    } else {
        /* Hopefully, a BPTR to a BSTR */
        text=((char *)BADDR(startupmsg[1]))+1;
        if (!TypeOfMem(text)) {
            /* No, that does not work. */
            isfsstart = FALSE;
        } else {
            /* Now check the want-to-be fssm_Envion */
            if (startupmsg[2] & 0xc0000000) {
                isfsstart = FALSE;
            } else if (startupmsg[2]!=NULL &&
                (!TypeOfMem(BADDR(startupmsg[2])))) {
                isfsstart = FALSE;
            }
        }
    }

    /*
    ** But could possibly be a string
    */
    if (isfsstart==FALSE) {
        if (TypeOfMem(startupmsg)) {
            /* This is probably a string.
            ** "mount" puts NUL-terminated strings in
            ** here.
            */
            text = ((UBYTE *)startupmsg)+1;
            ...

```

```

} else {
    struct FileSysStartupMsg *fssm;
    fssm = (struct FileSysStartupMsg *)startupmsg;
    /*
    ** Access fssm->fssm_Device, fssm_Unit, fssm_Flags
    */
    ...
    if ((fssm->fssm_Environ & 0xc0000000) == 0) {
        LONG *ptr = BADDR(fssm->fssm_Environ);
        if (ptr && (TypeOfMem(ptr))) {
            struct DosEnvec *env;
            env = (struct DosEnvec *)ptr;
            /* Hopefully an environment */
            if (env->de_TableSize > 0) {
                /* Ok, this is probably good enough... use the
                ** elements of the environment up to the
                ** one indicated by env->de_TableSize
                */
            }
        }
    }
}
}
}

```

Even if this function is able to identify an `DosEnvec` structure with high probability, it can happen that the environment vector identified this way does not contain all the elements documented in `dos/filehandler.h`. Only the first `de_TableSize` elements are present and can be accessed, so some additional care shall be taken when interpreting this structure.

While the above is just a heuristic and is therefore not guaranteed to work, practical experience of the author has shown that it has so far been able to extract environment information from all handlers or file systems that came into his hand.

Nevertheless, getting hands on the `FileSysStartupMsg` from an unknown handler is not completely waterproof at this moment, and to this end the author of [10] proposed to introduce a `DosPacket` (see section ??) by which a handler can be requested to reveal its startup message. Unfortunately, to date this packet has not found wide adoption, and the above heuristics may be used as an interim solution.

Authors of *handlers* and *file systems* have less to worry about. When they document their requirements properly, e.g. by including an example `Mountlist` with their product, “only” user errors can generate startup messages the handler cannot interpret properly. Thus, in general, handlers should be written in an “optimistic” way (unlike the above heuristic) assuming that `dol_Startup` is what they do expect. All AmigaDOS handlers are written in such a way, e.g. the FFS expects without verification that the value in `dol_Startup` is, indeed, a `FileSysStartupMsg`, even though it can be fooled by an incorrect `Mountlist` and by that crash the system.

## 8.4 Adding or Removing Entries to the Device List

The *dos.library* provides two service functions to add or remove `DosList` structures from the *device list*. They secure the *dos.library* internal state from inconsistencies as other processes may attempt to access the *device list* simultaneously, and they also ensure proper linkage of the structures.

---

*Locking the device list in file systems* There is one particular race condition *file system* authors should be aware of. When opening a file, or obtaining a *lock*, the *dos.library* calls through `GetDeviceProc()` to identify a *handler* responsible for the requested path. As `GetDeviceProc()` requires access to the *device list*, it will secure access to it through `LockDosList()`, then possibly start up the *handler*, and then unlock the list. Thus, at the time the handler is initiated, it may find the *device list* unaccessible. Attempting to lock it would result in a *deadlock* situation as the *dos.library* waits for the *handler* to reply its startup packet, and the *handler* waits for the *dos.library* to grant access to the *device list*. The following sections provide workarounds how to avoid this situation, see also section ?? for details on the *handler* and *file system* startup mechanism.

### 8.4.1 Adding an Entry to the Device List

The `AddDosEntry()` adds an initialized `DosList` structure to the *device list*.

```
success = AddDosEntry(dlist)
D0                      D1

LONG AddDosEntry(struct DosList *)
```

This function takes an initialized `DosList` entry pointed to by `dlist` and attempts to add it to the *device list*. For this, it requests write access to the list, i.e. locking of the *device list* through the caller is not necessary. The `DosList` may be either created manually, by `MakeDosEntry()` of the *dos.library* or by `MakeDosNode()` of the *expansion.library*. While there the structure is called a `DeviceNode`, it is still a particular incarnation of a `DosList` and may be safely used here.

*Assigns shall not* be added to the *device list* through this function, but rather through the functions in section 8.6. This avoids memory management problems when releasing or changing assigns.

Particular care needs to be taken if this function is called from within a *handler* or *file system*, e.g. to add a *volume* representing an inserted medium. As the list may be locked by the *dos.library* to secure the list from modifications within a `GetDeviceProc()` function, a deadlock may result where *file system* and *dos.library* mutually block access. To prevent this from happening handlers should check upfront whether the *device list* is available for modifications by `AttemptLockDosList()`, e.g.

```
if (AttemptLockDosList(LDF_VOLUMES|LDF_WRITE)) {
    rc = AddDosEntry(volumenode);
    UnlockDosList(LDF_VOLUMES|LDF_WRITE);
}
```

when adding a `DosList` entry of type `DLT_VOLUME`. If attempting to get write access failed, the handler should check for incoming requests, handle them, and attempt adding the entry later.

The function fails if an entry is to be added and an entry of the same name, regardless its type, is already present on the list. The only exception is that the list may contain two *volumes* of the same name, provided provided their creation date `dol_VolumeDate` differs, see section 8.

If successful, the function returns non-zero, but then does not alter `IoErr()`. The `DosList` is then enqueued in the *dos.library* database and it and its members shall then no longer be altered or released by the caller. On failure, the function returns 0 and `IoErr()` is set to `ERROR_OBJECT_EXISTS`.

### 8.4.2 Removing an Entry from the Device List

The `RemDosEntry()` removes a `DosList` entry from the *device list*, making it unaccessible for AmigaDOS.



```

success = RemDosEntry(dlist)
D0                                     D1

BOOL RemDosEntry(struct DosList *)

```

This function attempts to find the `DosList` structure pointed to by `dlist` in the *device list* and, if present, removes it. Unlike what some other documentation says, this function locks the *device list* properly before attempting to remove an entry, locking it upfront is not necessary.

The function does *not* attempt to release the memory allocated for the `DosList` passed in, or any of its members, it just removes the `DosList` from the *device list*. While *file systems* may know how they allocated the `DosList` structures representing their *volumes* and hence should be aware how to release the memory taken by them, there is no good solution on how to recycle memory for `DosList` structures representing *handlers*, *file systems* or *assigns*. Some manual footwork is currently required, see also `FreeDosNode()`. In particular, as entries representing *handlers* and *file systems* may have been created in multiple ways, their memory cannot be safely recycled.

Particular care needs to be taken if this function is called from within a *handler* or *file system*, e.g. to remove a *volume* representing a removed medium. As the list may be locked by the *dos.library* to secure the list from modifications within a `GetDeviceProc()` function, a deadlock may result where *file system* and *dos.library* mutually block access. To prevent this from happening handlers should check upfront whether the *device list* is available for modifications by `AttemptLockDosList()`, e.g.

```

if (AttemptLockDosList(LDF_DELETE|LDF_ENTRY|LDF_WRITE)) {
    rc = RemDosEntry(volumenode);
    UnlockDosList(LDF_DELETE|LDF_ENTRY|LDF_WRITE);
}

```

when removing a `DosList` entry. If attempting to get write access failed, the handler should check for incoming requests, handle them, and attempt adding the entry later.

This function returns a success indicator; it returns non-zero if the function succeeds, and 0 in case it fails. The only reason for failure is that `dlist` is not a member of the *device list*. This function does not touch `IoErr()`.

## 8.5 Creating and Deleting Device List Entries

AmigaOs offers multiple functions to create `DosList` structures. The `MakeDosEntry()` function is a low-level function that allocates a `DosList` but only performs minimal initialization of the structure. For *assigns*, the functions in section 8.6 shall be used as they include complete initialization of the `DosList`, and for *handlers* and *file systems*, the *expansion.library* function `MakeDosNode()` is a proper alternative. Releasing `DosLists` along with all its resources is unfortunately much harder. For *assigns*, the algorithm in section 8.5.2 provides a workable function based on `FreeDosEntry()`.

`DosLists` representing *Volumes* are build and released by *file systems*; it depends on them which resources need to be released along with the `DosList` structure itself. While it is recommended that *file systems* should go through `MakeDosEntry()` and `FreeDosEntry()`, it is not a requirement.

Releasing a `DosList` representing a *handler* or *file system* is currently not possible in a completely robust way. It is suggested just to unlink such nodes if absolutely necessary, but tolerate the memory leak.

### 8.5.1 Creating a Device List Entry

The `MakeDosEntry()` creates an empty `DosList` structure of the given type, and makes all elementary initializations. It does not acquire any additional resources, and neither inserts it into the *device list*.

---

If an *assign* is to be created, the functions in section 8.6 are better alternatives and should be preferred as they perform a more sophisticated initialization.

```
newdlist = MakeDosEntry(name, type)
D0                      D1      D2

struct DosList *MakeDosEntry(STRPTR, LONG)
```

This function allocates a `DosList` structure and initializes its `dol_Type` to `type`. The `type` argument shall be one of the values from table 25. The function also makes a copy of `name` and initializes the `dol_Name` to a *BSTR* copy of `name`, which is a NUL terminated C string.

Note that this function performs only minimal initialization of the `DosList` structure. All other members except `dol_Type` and `dol_Name` are initialized to 0.

This function either returns the allocated structure, or NULL for failure. In the latter case, `IoErr()` is set to `ERROR_NO_FREE_STORE`. On success, `IoErr()` remains unaltered.

### 8.5.2 Releasing a Device List Entry

The `FreeDosEntry()` function releases a `DosList` structure allocated by `MakeDosEntry()`. The `DosList` shall be already removed from the *device list* by `RemDosEntry()`. While this call releases the memory holding the name of the entry, and also the `DosList` structure itself, it does not release any other resources. They shall be released by the caller of this function. Furthermore, this function shall not be called if the `DosList` structure was allocated by any other means than `MakeDosEntry()`.

```
FreeDosEntry(dlist)
D1

void FreeDosEntry(struct DosList *)
```

This function releases the `DosList` structure pointed to by `dlist` and its name, but only these two resources, and no other resources.

If `dol_Type` is `DLT_DEVICE`, corresponding to *handlers* or *file systems*, this function should better not be called at all as the means of how the `DosList` was allocated is unclear. In such a case, a memory leak is the least dangerous side effect.

If `dol_Type` is `DLT_DIRECTORY` or `DLT_LATE`, then `dol_Lock` should be unlocked. If `dol_List` is non-NULL, then each entry of the `AssignList` structure shall be released, along with the lock kept within. For `DLT_LATE` and `DLT_NONBINDING`, the `dol_AssignName` function shall also be released. The following code segment releases all resources for *assigns*:

```
struct AssignList *al, *next;
UnLock(dol->dol_Lock);
al = dol->dol_misc.dol_assign.dol_List;
while(al) {
    next = al->al_Next;
    UnLock(al->al_Lock);
    FreeVec(al);
    al = next;
}
FreeVec(dol->dol_misc.dol_assign.dol_AssignName);
FreeDosEntry(dol);
```

---

The above code reflects the way how resources were originally allocated by the *dos.library*.

If the type is `DLT_VOLUME`, it is up to the *file system* to release any resources it allocated along with the `DosList`. It is file system dependent which resources can or should be released. `DosList` entries of this type should only be touched by the *file system* that created them.

This function cannot fail, and it does not touch `IoErr()`.

## 8.6 Creating and Updating Assigns

While `MakeDosEntry()` creates a `DosList` entry for the *device list*, it only performs minimal initialization of the structure. For *assigns*, specifically, the *dos.library* provides specialized functions that allocate, initialize and enqueue `DosList` structures representing assigns in a single call and are thus easier to use.

### 8.6.1 Create and Add a Regular Assign

The `AssignAdd()` function creates a new assign to a directory from a *lock*, and then enqueues it into the *device list*.

```
success = AssignLock(name, lock)
D0          D1    D2
```

```
BOOL AssignLock(STRPTR, BPTR)
```

This function creates a (regular) *assign* onto the directory identified by `lock`. The *assign* created under the name as given by `name`. The name shall not include a trailing colon (":") that separates the *assign* name from the rest of the path. The *lock* shall be a *shared lock*.

If the function is successful, it returns a non-zero result code. The `lock` is then absorbed into the *assign* and shall no longer be used by the calling program. On success, `IoErr()` is not altered.

On error, the function returns 0 and the `lock` remains available to the caller. `IoErr()` is set to an error code identifying the cause of the failure. `ERROR_NO_FREE_STORE` is returned if the function run out of memory. If a `DosList` of the same name (regardless of which type) already exists, the error code is `ERROR_OBJECT_EXISTS`.

### 8.6.2 Create a Non-Binding Assign

The `AssignPath()` function creates a *non-binding assign* and adds it to the *device list*. This type of assign binds to a path independent of the volume the path is located on; that is, the *assign* resolves to whatever *volume*, *handler* or even other *assign* matches the path.

```
success = AssignLate(name, path)
D0          D1    D2
```

```
BOOL AssignLate(STRPTR, STRPTR)
```

This function creates a *non-binding assign* whose name is given by the first argument, and which resolves to the path given as second argument, and then adds the *assign* to the *device list*. The name shall not contain a trailing colon (":"). While not a formal requirement of the function or *non-binding assigns*, the path should better be an absolute path as otherwise resolution of the created *assign* can be very confusing — it is then resolved relative to the current directory of the calling process.

If the function is successful, it returns a non-zero result code. On success, `IoErr()` is not altered.

On error, the function returns 0 and `IoErr()` is set to an error code identifying the cause of the failure. `ERROR_NO_FREE_STORE` is returned if the function run out of memory. If a `DosList` of the same name (regardless of which type) already exists, the error code is `ERROR_OBJECT_EXISTS`.

---

### 8.6.3 Create a Late Assign

The `AssignLate()` function creates a *late assign* whose target is initially given by a path; but after its first resolution, the *assign* reverts to a *regular assigns* such that the target of the *assign* will point to the same directory of the volume from that point on. This has the advantage that the target of the assign does not need to be available at creation time of the assign, yet remains unchanged after its first usage.

```
success = AssignLate(name, path)
D0                      D1    D2
```

```
BOOL AssignLate(STRPTR, STRPTR)
```

This function creates a *late binding assign* of the name `name` pointing to `path` as its destination and adds it to the *device list*. The name shall not contain a trailing colon (":"). While not explicitly required by this function, the `path` should better be an absolute path as otherwise resolving the *assign* can be very confusing. The `path` is then relative to the current directory of the process using the *assign* the first time.

If the function is successful, it returns a non-zero result code. On success, `IoErr()` is not altered.

On error, the function returns 0 and `IoErr()` is set to an error code identifying the cause of the failure. `ERROR_NO_FREE_STORE` is returned if the function run out of memory. If a `DosList` of the same name (regardless of which type) already exists, the error code is `ERROR_OBJECT_EXISTS`.

### 8.6.4 Add a Directory to a Multi-Assign

The `AssignAdd()` function adds a directory, identified by a *lock*, to an already existing *regular* or *multi-assign*. On success, a *regular assign* is then converted into a *multi-assign*.

```
success = AssignAdd(name, lock)
D0                      D1    D2
```

```
BOOL AssignAdd(STRPTR, BPTR)
```

This function adds the `lock` at the end of the target directory list of the *assign* identified by `name`. The `name` does not contain a trailing colon (":").

A `DosList` of the given `name` shall already when entering this function, and this `DosList` shall be a *regular assign*. Attempting to add a directory to a *handler*, *file system*, *volume* or any other type of *assign* fails.

On success, the function returns a non-zero result code. In such a case, the `lock` is absorbed into the *assign* and shall no longer be used by the caller. The *assign* is converted into a *multi-assign* on access if it is not already one. The `lock` is added at the end of the directory list, i.e. the new directory is scanned last when resolving the *assign*.

On error, the function returns 0 and the `lock` remains available to the caller. Unfortunately, this function does not set `IoErr()` consistently, i.e. it is unclear on failure what caused the error, i.e. whether the function run out of memory, whether no fitting *device list* entry was found, or whether the entry found was not a *regular assign*.

### 8.6.5 Remove a Directory From a Multi-Assign

The `RemAssignList()` function removes a directory, represented by a `lock`, from a *multi-assign*. If only a single directory remains in the *multi-assign*, it is converted into a *regular assign*. If the *assign* was a *regular assign*, and the only directory is removed from it, the *assign* itself is removed from the *device list* and released, destroying it and releasing all resources.

---

```
success = RemAssignList(name, lock)
```

```
D0                      D1    D2
```

```
BOOL RemAssignList (STRPTR, BPTR)
```

This function removes the directory identified by `lock` from a *regular* or *multi-assign* identified by `name`. The name shall not contain a trailing colon (":"). If only a single directory remains in the *assign*, it is converted to a *regular assign*. If no directory remains at all, the *assign* is deleted and removed from the *device list*. The `lock` remains available to the caller, regardless of the result code. Note that the `lock` passed in does not need to be identical to the *lock* contained in the *assign*, but it needs to be a *lock* on the same directory. This function uses `SameLock()` function to compare the two locks.

On success, the function returns a non-zero result code in `success`. On error, the function returns 0. Unfortunately, it does not set `IoErr()` consistently in all cases, and thus, the cause of an error cannot be determined upon return. Possible causes of error are that `name` does not exist, or that it is not a *assign* or a *multi-assign*.



---

## Chapter 9

# Pattern Matching

Unlike other operating systems, it is neither the file system nor the shell that expands wild cards, or patterns. Instead, separate functions exist that, given a wildcard, scan a directory or an entire directory tree and deliver all files, links and directories that match a given pattern.

The pattern matcher syntax is build on special characters or *tokens* that define which names to match. The following tokens are currently defined:

- ? The question mark matches a single, arbitrary character within a component. When using the pattern matcher for scanning directories, the question mark does not match the component separator, i.e. the slash (“/”) and the colon (“:”) that separates the path from the device name. Note in particular that the question mark also matches the dot (“.”) which is not a special character under AmigaDOS.
- # The hash mark matches zero or more repeats of the token immediately following it. In particular, the combination “#?” matches zero or more arbitrary characters. If a group of more than one token is required to describe which combination needs to match, this group needs to be enclosed in brackets.
- () The brackets bind tokens together forming a single token. This is particularly useful for the hash mark # as it allows to formulate repeats of longer character or token groups. For example, # (ab) indicates zero or more repeats of the character sequence ab, such as ab, abab or ababab.
- ~ The ASCII tilde (“~”) matches names that do not match the next token. This is particularly valuable for filtering out the workbench icon files that end on .info, i.e. ~(#?.info) matches all files that do not end with .info.
- [] The square brackets (“[]”) matches a single character from a range, e.g. [a-z] matches a single alphabetic character and [0-9] matches a single digit. Multiple ranges and individual characters can be combined, for example [ab] matches the characters a and b, whereas [a-cx-z] matches the characters from a to c and from x to z. If the minus sign (“-”) is supposed to be part of the range, it shall appear first, directly within the bracket, e.g. [-a-c] matches the dash and the characters a to c. If the dash is the last character in the range, all characters up to the end of the ASCII range, i.e. 0x7f match, but none of the extended ISO Latin 1 characters match. If the closing square bracket (“]”) is to be matched, it shall be escaped by an apostroph (“’”), i.e. [ [-’ ] ] matches the opening and the closing bracket. If the pattern matcher is used for scanning directories, the above example does not match the slash (“/”) even though its code point lies between the opening and closing bracket because the slash cannot be part of a component name and rather separates components. If the first character of the range is an ASCII tilde (“~”), then the character class matches all characters *not* in the class, i.e. [~a-z] matches all characters except alphabetic characters. In all other places, the tilde stands for itself.

- ' The apostroph (') is the escape character of the pattern matcher and indicates that the next character is not a token of the matcher, but rather stands for itself. Thus, ' ? matches the question mark, and only the question mark, and no other character.
- % The percent sign ("%") matches the empty string.
- | The vertical bar ("|") defines alternatives and matches the token to its left or the token to its right. The alternatives along with the vertical bar shall be enclosed in round brackets to bind them, i.e. (a|b) is either the character a or b and therefore matches the same strings [ab] matches. A particular example is ~((#?.info)|.backdrop) which matches all files not used by the workbench for storing meta-information.

**The Asterisk \* is not a Wildcard** Unlike many other operating systems, the asterisk ("\*") has a (two) other meanings under AmigaDOS. It rather refers to the current console as file name, or is the escape character for quotation and control sequences; those are properties AmigaDOS inherits from the BCPL syntax and TRIPOS. While there is a flag in the *dos.library* that makes the asterisk *also* available as a wildcard, such usage is discouraged because it can lead to situations where the asterisk is interpreted differently than intended — as it has already two other meanings.

Pattern matching works in in two steps: In the first step, the pattern is tokenized into an internal representation, which is then later on used to perform the actual match of a string against a wildcard. The directory scanning function `MatchFirst()` performs this conversion internally, and thus no additional preparation is required by the caller in this case. However, if the pattern matcher is used to search for strings or wildcards within a text file, the pattern tokenizers `ParsePattern()` or its case-insensitive counterpart `ParsePatternNoCase()` shall be called first.

**Only ISO-Latin Codepoints** The pre-parsing step that prepares from the input pattern its tokenized version uses the code points 0x80 to 0x9f for tokenized versions of wild-cards and other instructions for the pattern matcher. This is identical to the extended ISO-Latin control sequence region, and does not represent printable charactes. While file names on AmigaDOS *file systems* may in principle include such code-points, patterns of the pattern matcher *shall not* contain unprintable code points from the region 0x00 to 0x1f or from 0x80 to 0x9f. These regions are reserved for the pattern matcher.

## 9.1 Scanning Directories

The prime purpose of the pattern matcher is to scan a directory, or even a tree of directories, identifying all *file system* objects such as files, links or directories that match a given pattern. The pattern matcher can even descend recursively into sub-directories if instructed to do so. This service is used by many shell commands stored in the C: *assign*. The directory scanner requires the following steps:

First, the user shall provide an `AnchorPath` structure. This structure contains the state of the directory matcher, including the `FileInfoBlock` structure of the matched object. This structure is defined in section 6.1. Optionally, the `AnchorPath` structure may also contain the complete (relative) path of the matched object. This structure shall then be initialized, setting all flags required, see below for their definition.

**Must be Long-Word Aligned** As the `AnchorPath` structure embedds a `FileInfoBlock` structure that requires long-word alignment, the `AnchorPath` structure shall be aligned to long-word boundaries as well. The simplest way to ensure this is to allocate it with either `AllocMem()` or `AllocVec()`, see also section 2.3.



---

Then, with the initialized `AnchorPath` structure, `MatchFirst()` shall be called, returning the first match of the pattern if there is any. The `AnchorPath` structure then contains all information on the found match.

If there is any match, and the match is a directory the caller wants to enter recursively, the `APF_DODIR` flag of the `AnchorPath` structure may be set. Then, `MatchNext()` may be called to continue the scan, potentially entering this directory. Once the end of a recursively entered directory has been reached, `MatchNext()` sets the `APF_DIDDIR` flag, then reverts back to the parent directory continuing the scan there. As `APF_DIDDIR` is never cleared by the pattern matcher, the caller should clear it once the end of a sub-directory had been noticed.

The above iterative procedure of `MatchNext()` may continue, either until the user or the running program requests termination, or until `MatchNext()` returns an error. Then, finally, the scan is aborted and all resources but the `AnchorPath` structure shall be released by calling `MatchNext()`.

The `AnchorPath` structure is defined in `dos/dosasl.h` and looks as follows:

```
struct AnchorPath {
    struct AChain    *ap_Base;
#define ap_First ap_Base
    struct AChain    *ap_Last;
#define ap_Current ap_Last
    LONG             ap_BreakBits;
    LONG             ap_FoundBreak;
    BYTE             ap_Flags;
    BYTE             ap_Reserved;
    WORD             ap_Strlen;
    struct FileInfoBlock ap_Info;
    UBYTE            ap_Buf[1];
};
```

The members of this structure are as follows:

`ap_Base` and `ap_Last` are pointers to an `AChain` structure that is also defined in `dos/dosasl.h`. This structure is allocated and released by the *dos.library*, transparently to the caller. The `AChain` structure describes a directory in the potentially recursive scan through a directory tree. `ap_Base` describes the topmost directory at which the scan started, whereas `ap_Last` describes the directory which is currently being scanned.

The `AChain` structure is also defined in `dos/dosasl.h`:

```
struct AChain {
    struct AChain *an_Child;
    struct AChain *an_Parent;
    BPTR an_Lock;
    struct FileInfoBlock an_Info;
    BYTE an_Flags;
    UBYTE an_String[1];
};
```

`an_Child` and `an_Parent` are only used internally and shall not be interpreted by the caller.

`an_Lock` is a lock to the directory described by this `AChain` structure. In particular, `ap_Last->an_Lock` is a lock to the directory that is currently being scanned, and `ap_Base->an_Lock` a lock to the topmost directory at which the scan started. These two locks have been obtained and will be unlocked by the *dos.library*; they may be used by the caller provided they are not unlocked manually.

---

`an_Info` is only used internally and is the `FileInfoBlock` of the directory being describes by the `AChain` structure, see section 6.1.

`an_Flags` is only used internally, and `an_String` can contain potentially the path to the directory; both shall not be modified or interreted by the caller.

`ap_BreakBits` of the `AnchorPath` structure shall be initialized to the signal mask upon which `MatchNext()` aborts a directory scan. This is typically a combination of signal masks found in `dos/dos.h`, e.g. `SIGBREAKF_CTRL_C` to abort on `Ctrl-C` in the console.

`ap_FoundBreak` contains, if `MatchNext()` aborts with `ERROR_BREAK`, the signal mask that caused the abortion.

`ap_Flags` contains multiple flags that can be set or inspected by the caller while scanning a directory. In particular:

`APF_DOWILD` while documented, is not used nor set at all by the pattern matcher.

`APF_ITSWILD` is set by `MatchFirst()` if the pattern includes a wildcard and more than a single *file system* object may match. Otherwise, no directory scan is performed. The user may also set this flag to enforce a scan. This may resolve situations in which matching an explicit path without a wildcard is not possible because the object is locked exclusively.

`APF_DODIR` may be set or reset by the caller of `MatchNext()` to enforce entering a directory recursively, or avoid entering a directory. This flag is cleared by `MatchNext()` when entering a directory, and it shall only be set by the caller if a match describes a directory.

`APF_DIDDIR` is set by `MatchNext()` if the end of a recursively entered directory has been reached, and thus the parent directory is re-entered. As this flag is never cleared by the pattern matcher, it should be cleared by the caller.

`APF_NOMEMERR` is an internal flag that should not be interpreted; it is set if an error is encountered while scanning a directory. It is not necessarily restricted to memory allocation errors.

`APF_DODOT` is, even though documented, not actually used.

`APF_DirChanged` is a flag that is set by `MatchNext()` if the scanned directory changes, either by entering a directory recursively, or by leaving a directory. It is also cleared if the directory is the same as in the previous call.

`APF_FollowHLinks` may be set by the caller to indicate that hard links to directories shall be followed, and such directories shall be recursively entered if `APF_DODIR` is set as well. Otherwise, hard links to directories are not entered. Softlinks are neither entered, this this cannot be changed by any flag. A potential danger of links is that they may cause endless recursion if a link within a directory points to a parent directory. Thus, callers should be aware of such situations and store directories that have already been analyzed. Otherwise, it is safer to keep this flag cleared.

`ap_Strlen` is the size of the buffer `ap_Buf` that contains the full path of the matched entry. This buffer shall be allocated by the user at the end of the `AnchorPath` structure. Unlike what the name suggests, this is not a string length, but the byte size of the buffer, including the terminating `NUL` byte of a string. If the full path of the match does not fit into this buffer, it is truncated *without* proper string termination and the error code `ERROR_BUFFER_OVERFLOW` is returned. If the full path is not required, this member shall be set to 0.

`ap_Info` contains the `FileInfoBlock` of the matched entry, including all metadata the file system has available for it. Note that `fib_FileFile` only contains the name of the object, not its full path.

`ap_Buf` is filled with the full path to the matched object if `ap_Strlen` is non-zero. This buffer shall be allocated by the caller at the end of the `AnchorPath` structure, i.e. for a buffer of `l` bytes, in total `sizeof(AnchorPath)+l-1` bytes are required to store the structure and the buffer. The byte size of this additional buffer shall be placed in `ap_Strlen`. If this buffer is not required, `ap_Strlen` shall be set to 0.

---

### 9.1.1 Starting a Directory Scan

The `MatchFirst()` function starts a directory scan, locating all objects matching a pattern and potentially entering directories recursively.

```
error = MatchFirst(pat, AnchorPath)
D0          D1          D2

LONG MatchFirst(STRPTR, struct AnchorPath *)
```

This function starts a directory scan, locating all objects matching the pattern `pat`. This pattern does *not* require pre-parsing (e.g. the functions in section 9.2), `MatchFirst()` performs the parsing.

`AnchorPath` shall be a pointer to an `AnchorPath` structure allocated and initialized by the caller. In particular, `ap_BreakBits` shall be initialized to a signal mask on which the scan terminates, `ap_FoundBreak` to 0, and `ap_Stren` to the size of the buffer `ap_Buf` which is filled by the path name of the matching objects. If this path name is not required, `ap_Stren` shall be set to 0. `ap_Flags` shall be set to the flags you need, see the parent section.

Unlike many other functions, `MatchFirst()` returns an error code directly, and not a success/failure indicator. That is, 0 indicates success. In particular, if `ERROR_BREAK` is returned in case any of the signal bits in `ap->ap_BreakBits` have been received during the scan.

On success, `ap->ap_Info.fib_FileName` contains the name of the first matched object, the directory represented as a *lock* containing the object is available in `ap->ap_Current->an_Lock`. You would typically set the current directory to this lock, then access this object, then revert the lock. This lock *shall not* be released; this is performed by the pattern matcher itself as needed.

If the full path of the matching object is needed, an additional buffer shall be allocated at the end of the `AnchorPath`, and the size of the buffer shall be placed into `ap_Stren`. The function then fills in the path into `ap_Buf`.

If the matching object is a directory, i.e. `ap->ap_Info.fib_DirEntryType` is positive and not equal to `ST_SOFTLINK`, the caller may request to enter this directory by setting `APF_DODIR` in `ap->ap_Flags`.

### 9.1.2 Continuing a Directory Scan

The `MatchNext()` function continues a directory scan initiated by `MatchFirst()`, returning the next matching object, or an error.

```
error = MatchNext(AnchorPath)
D0          D1

LONG MatchNext(struct AnchorPath *)
```

This function takes an existing `AnchorPath` structure, as prepared by a previous `MatchFirst()` or `MatchNext()` function, and finds the next matching object. Unlike most other functions of the *dos.library*, this function returns an error code on failure and 0 for success. It does *not* return a boolean success indicator. In particular, if `ERROR_BREAK` is returned in case any of the signal bits in `ap->ap_BreakBits` have been received.

As for `MatchFirst()`, this call fills `ap->ap_Info` with meta information on the found object, in particular its file name, and `ap->ap_Current->an_Lock` the lock of the directory containing the object. As for `MatchFirst()`, `APF_DODIR` can be set to enter directories recursively, and `ap->ap_Buf` will be filled with the full path of the found object if `ap->ap_Stren` is non-zero.

---

### 9.1.3 Terminating a Directory Scan

The `MatchEnd()` function terminates a running scan, and releases all resources associated with the scan. It does not release the `AnchorPath` structure.

```
MatchEnd(AnchorPath)
        D1
```

```
VOID MatchEnd(struct AnchorPath *)
```

This function ends a directory scan started by `MatchFirst()` and releases all resources associated to the scan. This function shall be called regardless whether the scan is aborted due to exhaustion (i.e. `ERROR_NO_MORE_ENTRIES`, by error, or by choice of the scanning program (i.e. the desired object has been detected and no further matches are required).

## 9.2 Matching Strings against Patterns

While the prime purpose of the pattern matcher is to scan directories, it can also be used to check whether an arbitrary string matches a wildcard, for example to scan for a pattern within a text document. This requires two steps: In the first step, the wildcard is prepared, generating a tokenized version of the pattern. The second step checks whether a given input string matches the pattern. You would typically tokenize the pattern once, and then use it to match multiple strings to the pattern.

Two versions of the tokenizer and pattern matcher exist: One pair that is case-sensitive, and the second pair is case-insensitive. Note that AmigaDOS file names are case-insensitive, so the `MatchFirst()` and `MatchNext()` functions internally only use the second pair.

The buffer for the tokenized version of the pattern shall be allocated by the caller. It requires a buffer that is at least  $2 + (n \ll 1)$  bytes large, where  $n$  is the length of the input wildcard.

### 9.2.1 Tokenizing a Case-Sensitive Pattern

The `ParsePattern()` function tokenizes a pattern for case-sensitive string matching. This tokenized version is then later on used to test a string for a match.

```
IsWild = ParsePattern(Source, Dest, DestLength)
d0              D1      D2      D3
```

```
LONG ParsePattern(STRPTR, STRPTR, LONG)
```

This function tokenizes a wildcard pattern in `Source`, generating a tokenized version of the pattern in `Dest`. The size (capacity) of the target buffer is `DestLength` bytes. This size shall be at least  $2 + (n \ll 1)$  bytes large, where  $n$  is the length of the input pattern. However, as future implementations can require larger buffers, the result code shall be checked nevertheless for error conditions. The result code `IsWild` is one of the following:

1 is returned if the source contained wildcards.

0 is returned if the source contains no wildcards. In this case, the tokenized pattern may still be used to match a string against the pattern, though a simple string comparison would also work.

-1 is returned in case of an error, either because the input pattern is ill-formed, or because `DestLength` is too short. In such a case, `IoErr()` should be used to obtain the reason of the failure.

---

## 9.2.2 Tokenizing a Case-Insensitive Pattern

The `ParsePatternNoCase()` function tokenizes a pattern for case-insensitive string matching. This tokenized version is then later on used to test a string for a match. This version is suitable for matching file names, but is otherwise similar to `ParsePattern()`.

```
IsWild = ParsePatternNoCase(Source, Dest, DestLength)
D0                      D1      D2      D3
```

```
LONG ParsePatternNoCase(STRPTR, STRPTR, LONG)
```

This function tokenizes a wildcard pattern in `Source`, generating a tokenized version of the pattern in `Dest`. The size (capacity) of the target buffer is `DestLength` bytes. This size shall be at least  $2 + (n \ll 1)$  bytes large, where  $n$  is the length of the input pattern. However, as future implementations can require larger buffers, the result code shall be checked nevertheless for error conditions. The result code `IsWild` is one of the following:

- 1 is returned if the source contained wildcards.

- 0 is returned if the source contains no wildcards. In this case, the tokenized pattern may still be used to match a string against the pattern, though a simple case-insensitive string comparison would also work.

- 1 is returned in case of an error, either because the input pattern is ill-formed, or because `DestLength` is too short. In such a case, `IoErr()` should be used to obtain the reason of the failure.

## 9.2.3 Match a String against a Pattern

The `MatchPattern()` function matches an input string against a tokenized pattern, in a case sensitive way.

```
match = MatchPattern(pat, str)
D0                      D1      D2
```

```
BOOL MatchPattern(STRPTR, STRPTR)
```

This function matches the string `str` against the tokenized pattern `pat`, returning an indicator whether the string matches the pattern. This function is case-sensitive. The pattern `pat` shall have been tokenized by `ParsePattern()`.

The result code `match` is non-zero in case the string matches, or 0 in case either the string did not match, or the function run out of stack. The latter two cases can be distinguished by `IoErr()`. In case the string did not match, `IoErr()` returns 0, or a non-zero error code otherwise. A possible error code is `ERROR_TOO_MANY_LEVELS` indicating that the pattern matcher run out of stack due to too many levels of recursion.

The caller shall have at least 1500 bytes of stack space available to avoid race conditions, despite the function checking for out-of-stack conditions.

## 9.2.4 Match a String against a Pattern ignoring Case

The `MatchPatternNoCase()` function matches an input string against a tokenized pattern ignoring the case.

```
match = MatchPatternNoCase(pat, str)
D0                      D1      D2
```

```
BOOL MatchPatternCase(STRPTR, STRPTR)
```

---

This function matches the string `str` against the tokenized pattern `pat`, returning an indicator whether the string matches the pattern. This function is case-insensitive. The pattern `pat` shall have been tokenized by `ParsePatternNoCase()`.

The result code `match` is non-zero in case the string matches, or 0 in case either the string did not match, or the function run out of stack. The latter two cases can be distinguished by `IoErr()`. In case the string did not match, `IoErr()` returns 0, or a non-zero error code otherwise. A possible error code is `ERROR_TOO_MANY_LEVELS` indicating that the pattern matcher run out of stack due to too many levels of recursion.

The caller shall have at least 1500 bytes of stack space available to avoid race conditions, despite the function checking for out-of-stack conditions.

---

## Chapter 10

# Processes

*Processes* are extensions of *exec tasks*, and as such scheduled by *exec*. The most important extensions are that processes include a message port in the form of a *MsgPort* structure for inter-process communication to *handlers*, a current directory to resolve relative paths, and the last input/output error as returned by the `IoErr()` function.

*Processes* are represented by the `Process` structure documented in `dos/dosextens.h`. It reads as follows:

```
struct Process {
    struct Task    pr_Task;
    struct MsgPort pr_MsgPort;
    WORD          pr_Pad;
    BPTR          pr_SegList;
    LONG          pr_StackSize;
    APTR          pr_GlobVec;
    LONG          pr_TaskNum;
    BPTR          pr_StackBase;
    LONG          pr_Result2;
    BPTR          pr_CurrentDir;
    BPTR          pr_CIS;
    BPTR          pr_COS;
    APTR          pr_ConsoleTask;
    APTR          pr_FileSystemTask;
    BPTR          pr_CLI;
    APTR          pr_ReturnAddr;
    APTR          pr_PktWait;
    APTR          pr_WindowPtr;

    /* following definitions are new with 2.0 */
    BPTR          pr_HomeDir;
    LONG          pr_Flags;
    void          (*pr_ExitCode)();
    LONG          pr_ExitData;
    UBYTE         *pr_Arguments;
    struct MinList pr_LocalVars;
    ULONG         pr_ShellPrivate;
    BPTR          pr_CES;
}; /* Process */
```

---

The members of this structure are as follows:

`pr_Task` is the exec task structure defined in `exec/tasks.h`. It is required by the exec scheduler. The only difference between an exec Task and a Process is that `pr_Task.tc_Node.ln_Type` is set to `NT_PROCESS` instead to `NT_TASK`. Prior starting the process, the *dos.library* also pushes the stack size onto the stack, i.e. `(ULONG *) (pr_Task.tc_Upper) [-1]` contains the size of the stack in bytes. Some binaries, in particular those compiled with the Aztec (Manx) compiler depend on this value.

`pr_MsgPort` is a message port structure as defined in `exec/ports.h`. This port is used by many functions of the *dos.library* to communicate with *handlers* and *file systems*. Details of the communication protocol are given in section ??.

`pr_Pad` is unused and only included in the structure to ensure that all following members are aligned to 32-bit boundaries.

`pr_SegList` contains an array of *segments* containing AmigaDOS functions. The first entry in this array is a 32-bit integer indicating the number of valid elements, the remaining entries are *BPTR*s to segments of AmigaDOS and the loaded binary. Some entries may be `ZERO` indicating that the corresponding entry is currently not used. Segments are explained in more detail in section ??. Typically, entries 1 and 2 are system segments containing AmigaDOS functions, entry 3 is used for the loaded binary, and entry 4 the segment of the shell. This, however, only reflects the current usage of segments, and later versions of AmigaDOS may populate this vector differently. The segments contained in this vector are used by the AmigaDOS runtime binder to build the *Global Vector* of processes using BCPL linkage. As BPCL is phased out, this vector is of no particular importance today anymore, and can be ignored for almost all purposes. The only exception is the *Shell* which shall prepare this vector to ensure that commands written in BCPL function properly. More on this in section ??.

`pr_StackSize` is the size of the process stack in bytes. It is always a multiple of 4 bytes long.

`pr_GlobVec` is another BCPL legacy. It contains the *Global Vector* of the process. For binaries using the BCPL linkages, this is a custom-build array of global data and function entry points from `pr_SegList`. For C and assembler binaries, the *Global Vector* is the system shared vector; it contains *dos.library* global data required by some of its functions, such as base pointers to system libraries. As no particular advantage can be taken from this vector (anymore) as all functions available in it are also available as *dos.library* entry points, it should be left alone.

`pr_TaskNum` is an integer allocated by the system for processes that execute a shell, or are binaries that have been launched by the shell. The number here corresponds to the integer printed by the `Status` command. Note that AmigaDOS does not use task numbers consistently, i.e. processes that are started from the workbench or have been created by some other means are not identified by a task number. In such a case, this member remains 0.

`pr_StackBase` is a *BPTR* to the address of the lower end of the stack, i.e. the end of the C or assembler stack. As the BCPL stack grows in opposite direction, it is the start of the BCPL stack. While it is initialized, it is not used by the *dos.library* at all.

`pr_Result2` is the secondary result code set by many functions of the *dos.library*. The value stored here is delivered by `IoErr()`.

`pr_CurrentDir` is the *lock* representing the current directory of the process. All relative paths are resolved from this *lock*, i.e. they are relative to `pr_CurrentDir`. If this member is `ZERO`, the current directory is the root directory of the file system stored in `pr_FileSystemTask`. As the latter is (unless altered) the file system of the boot volume, this is usually identical to the directory identified by the `SYS` assign.

`pr_CIS` is *file handle* of the standard input stream of the process. It is also returned by `Input()`. It can be `ZERO` in case the process does not have a standard input stream. This is *not* equivalent to a `NIL`: input handle — in fact, any attempt to read from a non-existing input stream will crash. Processes started from the workbench do not have an input stream, unless one is installed here with `SelectInput()`.



---

`pr_COS` is the *file handle* of the standard output stream of the process. It is also returned by the `Output()` function of the *dos.library*. It can be `ZERO` in case the process does not have a standard output stream, which is not equivalent to a `NIL:` file handle. Any attempt to output to `ZERO` will crash the system. Processes started from the workbench do not have an output stream, unless one is installed with `SelectOutput()`.

`pr_ConsoleTask` is the *MsgPort* of the console within which this process is run, if such a console exists. This *handler* is contacted when opening “\*” or a path relative to `CONSOLE:`. Processes started from the workbench do not have a console, unless one is installed with `SetConsoleTask()`.

`pr_FileSystemTask` is the *MsgPort* of the file system that is contacted in case a relative path is to be resolved relative to the `ZERO` lock. This member is initialized to the *MsgPort* of the file system the system was booted from, but can be changed by `SetFileSysTask()`. This member is also returned by `GetFileSysTask()`.

`pr_CLI` is a *BPTR* to the `CommandLineInterface` structure containing information on the Shell this process is running in. If this process is not part of a Shell, this member is `ZERO`. This is for example the case for programs started from the workbench, or *handler* or *file system*.

`pr_ReturnAddr` is another *BCPL* legacy and should not be used by new implementations. It points to the *BCPL* stack frame of the process or the command overloading the process, and used there to restore the previous stack frame for the `Exit()` function. This is typically the process cleanup code for processes initialized by `CreateProc()` or `CreateNewProc()`, or the shell command shutdown code placed there by `RunCommand()`. This cleanup process does not, however, release any other resources obtained by user code. *BCPL* code or custom startup code could deposit here pointer to a *BCPL* stack frame for a custom shutdown mechanism.

The *BCPL* stack frame is described by the following (undocumented) structure:

```
struct BCPLStackFrame {
    ULONG bpsf_StackSize;
    APTR  bpsf_PreviousStack;
};
```

where `bpsf_StackSize` is the stack size of the current (active) stack, and `bpsf_PreviousStack` the stack of the caller; to restore the previous stack, this value is placed in the CPU register `A7`.

`pr_PktWait` is a function that is called when waiting for inter-process communication, in particular when waiting for a returning packet set out to a handler. If this is `NULL`, the system default function is used. The signature of this function is

```
msg = (*pr_PktWait)(void)
D0
```

```
struct Message *(*pr_PktWait)(void)
```

that is, no particular arguments are delivered, the process must be obtained from `exec`, and the message received shall be delivered back into register `D0`. The returned pointer shall not be `NULL`, rather, this function shall block until a message has been received. For details, see the `DoPkt()` function and section ??.

`pr_WindowPtr` is, unlike what the name suggests, a pointer to an *intuition* `Screen` structure, see `intuition/screens.h`, on which error requesters will appear. If this is `NULL`, error requesters appear on the workbench screen, and if this is set to `(APTR) (-1L)`, error requesters will be suppressed at all, and the implied reponse to them is to cancel the operation. This error requester is specified in more detail with the `ErrorReport()` function.

`pr_HomeDir` is the *lock* to the directory containing the binary that is currently executed as this process, if such a directory exists. It is `ZERO` if the binary is resident. This *lock* is filled in by the Shell or the

---

Workbench when loading and starting a process. It is used to resolve paths relative to the `PROGDIR` pseudo-assign, see section 7. If this lock is `ZERO`, any attempt to resolve a path within `PROGDIR:` will create a request to insert a volume `PROGDIR:`, which is probably not a very useful reaction of AmigaDOS.

`pr_Flags` are system-use only flags that shall not be used or interpreted. They are used by the system process shutdown code to identify which resources need to be released, but future systems may find additional uses for this member.

`pr_ExitCode()` is a pointer to a function that is called by AmigaDOS as part of the process shutdown code, and as such quite more useful than `pr_ReturnAddr`. This function prototype is as follows:

```
returncode = ExitFunc(rc, exitdata)
D0                                D0 D1

LONG ExitFunc(LONG, LONG)
```

The value of `rc` is the return code process, i.e. the value left in register `D0` when the code drops off the final RTS, and `exitdata` is taken from `pr_ExitData`. The `returncode` is a modified version of the process return code that is, however, ignored.

`pr_ExitData` is used as argument for the `pr_ExitCode()` function, see above.

`pr_Arguments` is a pointer to the command line arguments of the process if it corresponds to a command started from the Shell. This is a NUL terminated string. This argument string can also be found in register `A0` for programs started from the Shell, or in the buffer of `pr_CIS`. The `ReadArgs()` function takes it from the latter source, and not from `pr_Arguments`. Otherwise, this member remains `NULL`.

`pr_LocalVars` is a `MinList` structure, as defined in `exec/lists.h`, that contains local variables specific to the shell within which the process is executed, if any. The structure of such variables is defined in `dos/var.h`. This structure is specified in section ??.

`pr_ShellPrivate` is reserved for the Shell and its value shall not be used, modified or interpreted. It is currently unused, but can be used by future releases.

`pr_CES` is the *file handle* to be used for error output. This stream goes usually to the console the process runs in, if such a console exists. This handle can be changed by `SelectError()`. If `pr_CES` is `NULL`, processes should fall back to `pr_COS` for printing errors. Preferably, processes should use the `ErrorOutput()` function to obtain an error stream, though.

## 10.1 Creating and Terminating Processes

AmigaDOS provides several functions to create functions: `CreateNewProc()` is the revised and most flexible function for launching a process, taking many parameters in the form of a tag list. The legacy function `CreateProc()` supports less options, but available under all OS versions. Shells as created by the `System()` function implicitly also create processes, but are not discussed here, but in section ??. Therefore, `System()` shares a couple of options with `CreateNewProc()`.

There is surprisingly not a single function to delete processes. Processes die whenever their execution drops off at the end of the `main()` function, or whenever execution reaches the final RTS instruction of the main program function. The `Exit()` function also terminates a process, but shall be called from within the process, and is typically not suitable as it does not release resources acquired by the program itself, but only those allocated by the system itself.

### 10.1.1 Creating a New Process from a TagList

The `CreateNewProc()` function takes a `TagItem` array as defined in `utility/tagitem.h` and launches a new process from this list. The tags this function takes are defined in `dos/dostags.h`.

```

process = CreateNewProc(tags)
D0                                     D1

struct Process *CreateNewProc(struct TagItem *)

process = CreateNewProcTagList(tags)
D0                                     D1

struct Process *CreateNewProcTagList(struct TagItem *)

process = CreateNewProcTags(Tag1, ...)

struct Process *CreateNewProcTags(ULONG, ...)

```

The above functions are all equivalent, just the calling conventions are different. For `CreateNewProcTags()`, the `TagList` is created by the compiler on the stack and a pointer is then implicitly passed into the function. The following tags are recognized by the function:

`NP_Seglist` takes a *BPTR* to a segment list as returned by `LoadSeg()` and launches the process at the first byte of the first segment of the list.

`NP_FreeSeglist` is a boolean indicator that defines whether the segment provided to `NP_Seglist` is released when the process terminates. Unlike what the official documentation claims, the default value of this tag is `DOSFALSE`, i.e. the segment is *not* released.

`NP_Entry` is mutually exclusive to `NP_Seglist` and defines an absolute address (and not a segment) as entry point of the process to be created. If this tag is provided, then `NP_FreeSeglist` shall *not* be set a non-zero value. Either `NP_Entry` or `NP_Seglist` shall be included.

`NP_Input` sets the input file handle, i.e. `pr_CIS` of the process to be created. This tag takes a *BPTR* to a *file handle*. The default is *not* to set the input file handle, e.g. to leave it `ZERO`.

`NP_CloseInput` selects whether the input file handle, if provided, will be closed when the process terminates. If non-zero, the input file handle will be closed, otherwise it remains opened. The default is to close the input file handle.

`NP_Output` sets the output file handle, i.e. `pr_COS` of the process to be created. This tag takes a *BPTR* to a *file handle*. The default is to leave the output at `ZERO`.

`NP_CloseOutput` selects whether the output file handle, if provided, will be closed when the process terminates. If non-zero, the output file handle will be closed, otherwise it remains open. The default is to close the output file handle.

`NP_Error` sets the error file handle, i.e. `pr_CES` of the process to be created. This tag also takes a *BPTR* to a *file handle*. The default is to leave the error output handle at `ZERO`.

`NP_CloseError` selects whether the error file handle, if provided, will be closed when the process terminates. If non-zero, the error file handle will be closed, otherwise it remains open. The default is *not* to close the error file handle. This (different) default is to ensure backwards compatibility.

`NP_CurrentDir` sets the current directory of the process to be created. The argument is a *Lock*. The default is to duplicate the current directory of the caller with `DupLock()` if the caller is a process, or leave the current directory at `ZERO`. The current directory of the process, i.e. `pr_CurrentDir`, is released when the process terminates, unless `NP_CurrentDir` is set to `ZERO`.

`NP_StackSize` sets the stack size of the process to be created in bytes. The default is a stack size of 4000 bytes.

`NP_Name` is a pointer to a NUL terminated string to which the task name of the process to be created is set. This string is copied before the process is launched, and the copy is released automatically when the process terminates. The default process name is "New Process".

---

`NP_Priority` sets the priority of the process to be created. The tag value shall be an integer in the range  $-128$  to  $127$ , though useful values are in the range of  $0$  to  $20$ . The default is  $0$ .

`NP_ConsoleTask` specifies a pointer to a *MsgPort* to the handler that is responsible for the console of the process to be created. That is, if the created process opens “\*” or a path relative to `CONSOLE:`, it will use the specified handler. The default is to use the console handler if the caller is a process, or `NULL` if the caller is only a task.

While not explicitly available as a tag, the default file system of the created process, i.e. `pr_FileSystemTask`, is set to the default file system of the calling process if the caller is a process, or otherwise use the default file system from the *dos.library*. This file system is contacted to resolve paths relative to the `ZERO` lock.

`NP_WindowPtr` specifies a pointer to a *Screen* on which error requesters will be displayed,  $0$  to display requesters on the workbench, or  $-1$  to suppress error requesters. It will be installed in the `pr_WindowPtr` of the process to be created. The default is to copy the pointer from the calling process if the window pointer of the parent is  $0$  or  $-1$ . The tag does not copy any other value of `pr_WindowPtr` from the parent. To set the `pr_WindowPtr` of the created process to the value of the calling process, the tag must be explicitly provided. If called from a task and not a process, the default is `NULL`. The reason why `pr_WindowPtr` is not explicitly copied is that the caller shall ensure that the screen is not closed while any pointers are still pointing to its structure.

`NP_HomeDir` sets the `pr_HomeDir` lock which is used to resolve paths relative to the `PROGDIR:` pseudo-assign. The default is to copy `pr_HomeDir` of the calling process, or `ZERO` in case the caller is a task. This lock is released when the process terminates, i.e. the lock provided as argument here remains available to the caller, and shall be released by the caller in one way or another.

`NP_CopyVars` determines if the local shell variables in `pr_LocalVars` of the calling process are copied into the variables of the process to be created. If set to non-zero, a copy of the variables of the calling process are made, otherwise the new process does not receive any shell variables by itself. The latter also happens if the caller is a task and not a process. The variables are automatically released when the new process terminates.

`NP_Cli` determines whether the new process will receive a new shell environment in the form of a *CommandLineInterface* structure. If non-zero, a new CLI structure will be created and a *BPTR* to this structure will be filled into the `pr_CLi` member of the process to be created. The new shell environment will be a copy of the shell environment of the caller if one is present, or a shell environment initialized with all defaults. This means that the prompt, the path, and the command name will be copied over. If  $0$ , no such environment will be created. The latter is also the default.

`NP_Path` provides a chained list of locks within which commands are searched. This is the same list the `PATH` command adjusts, see section ?? for details on this structure. This tag only applies if `NP_Cli` is non-zero to create a shell environment. This chained list is *not* copied, and will be released when the created process terminates; hence, the locks provided here are *no longer* available to the caller if `CreateNewProc()` succeeds. If `CreateNewProc()` fails, the entire lock list remains a property of the caller and thus needs to be potentially released there. The default, if this tag is not provided, is to copy the paths of the caller if the calling process has a non-zero `pr_CLi` structure.

`NP_CommandName` provides the name of the command being executed within the shell environment if `NP_Cli` indicates that one is to be created. The default is to copy the command name of the shell environment of the calling process if one exists, or to leave the command name empty if none is provided. The command name is copied into the shell environment of the process being created and thus remains available to the caller. More on the shell environment is found in section ??.

`NP_Arguments` provides command line arguments for the process to be created. This is a `NUL` terminated string that is copied into the process to be created, and will also be released there. If provided, the arguments are copied in `pr_Arguments` of the process to be created, and will also be loaded into registers `A0` and its length into `D0`. If `NP_Arguments` are non-zero, a non-ZERO `NP_Input` file handle shall also be provided. This is because the arguments are also copied into the buffer associated to the input file handle to

---

make them available to `ReadArgs()`, or any other function that performs buffered read from `pr_CIS`, see section 4.8 for details.

`NP_ExitCode` determines a pointer to function that is called when the created process terminates. This pointer is filled into `pr_ExitCode`. See section 10 for the description and the signature of this function.

`NP_ExitData` provides an argument that will be passed into the `NP_ExitCode` function in register `D1` when the process terminates.

While the official documentation also mentions the tags `NP_NotifyOnDeath` and `NP_Synchronous`, these tags are currently ignored and do not perform any function.

The `CreateNewProc()` function returns on success a pointer to the `Process` structure just created. At this stage, the process has already been launched and, depending on its priority, may already be running. On failure, the function returns `NULL`. Unfortunately, it does not set `IoErr()` consistently on failure.

### 10.1.2 Create a Process (Legacy)

The `CreateProc()` function creates a process from a segment list, a name, a priority and a stack size. It is a legacy call that is not as flexible as `CreateNewProc()`, and only exists for backwards compatibility reasons.

```
process = CreateProc( name, pri, seglist, stackSize )
D0                      D1      D2      D3          D4
```

```
struct MsgPort *CreateProc(STRPTR, LONG, BPTR, LONG)
```

This function creates a process of the name `name` running at priority `pri`. The process starts at the first byte of the first segment of the segment list passed in as `seglist`, and a stack size of `stackSize` bytes will be allocated for the process.

The process is initialized as follows: `pr_ConsoleTask` and `pr_WindowPtr` are copied from the calling process, or are set to `NULL` respective 0 if called from the task. The member `pr_FileSystemTask` is also copied from the calling process, or is initialized from the default file system from the *dos.library* if called from a task.

Input, output and error file handles are set to `ZERO`, and no shell environment is created either. The current directory and home directory are also left at `ZERO`. No arguments are provided to the called function, and no shell variables are copied.

If the call succeeds, the returned value `process` is a pointer to the *MsgPort* of the created process. It is *not* a pointer to a process itself.

On failure, the function returns `NULL`. Unfortunately, it does not set `IoErr()` consistently in case of failure, thus the cause of the problem cannot be easily identified.

### 10.1.3 Terminating a Process

The `Exit()` function terminates the calling process or the calling command line executable. In the latter case, control is returned to the calling shell, in the former case, the process is removed from the exec scheduler.

However, this function does not release any resources except those implicitly allocated when creating the process through `CreateNewProc()`, `CreateProc()` or `RunCommand()` and the calling shell. As it misses to release resources allocated by you or the compiler startup code, this function *should not be used* and rather a compiler or language specific shutdown function should be preferred. The C standard library provides `exit()` which releases resources allocated through this library.

---

```
Exit( returnCode )
    D1
```

```
void Exit(LONG)
```

This call either terminates the calling process, in which case the argument is ignored, or returns to the calling shell, then delivering `returnCode` as result code. It uses the BCPL stack frame pointed to by `pr_ReturnAddr`, removes this stack frame, initializes the new stack from the stack frame there and then returns to whatever created the stack frame. This is typically either the process shutdown code of AmigaDOS, or the shell command shutdown code installed by `RunCommand()`. In the former code, `pr_ExitCode()` may be used to implement additional cleanup activities.

This function is a BCPL legacy function that is also part of the *Global Vector*; BCPL programs would typically overload its entry in this vector to implement a custom shutdown mechanism.

## 10.2 Process Properties Accessor Functions

The most important members of the process structure described in section 10 are accessible through getter and setter functions. They implicitly relate to the calling process, and are the preferred way of getting access to the `Process` structure. The functions listed in this section do not touch `IoErr()` except explicitly stated.

### 10.2.1 Retrieve the Process Input File Handle

The `Input()` function returns the input file handle of the calling process if one is installed. If no input file handle is provided, the function returns `ZERO`.

```
file = Input()
    D0
```

```
BPTR Input(void)
```

This function returns a *BPTR* to the input *file handle* of the calling process, or `ZERO` if none is defined. This is approximately identical to `stdin` of ANSI-C. Depending on process creation, this file handle can be closed by the process shutdown code or the calling shell and thus should in general not be closed explicitly. It can be changed through `SelectInput()`.

### 10.2.2 Replace the Input File Handle

The `SelectInput()` function replaces the input *file handle* of the calling process with its argument and returns the previously used input handle.

```
old_fh = SelectInput(fh)
    D0          D1
```

```
BPTR SelectInput(BPTR)
```

This call replaces the input *file handle* of the calling process with the file handle given by `fh` and returns the previously used input *file handle*.

---

### 10.2.3 Retrieve the Output File Handle

The `Output()` function returns the output file handle of the calling process if one is installed. If no output file handle is provided, the function returns `ZERO`.

```
file = Output()  
D0
```

```
BPTR Output(void)
```

This function returns a *BPTR* to the output *file handle* of the calling process, or `ZERO` if none is defined. This is approximately identical to `stdout` of ANSI-C. Depending on process creation, this file handle can be closed by the process shutdown code or the calling shell and thus should in general not be closed explicitly. It can be changed through `SelectOutput()`.

### 10.2.4 Replace the Output File Handle

The `SelectOutput()` function replaces the output *file handle* of the calling process with its argument and returns the previously used output handle.

```
old_fh = SelectOutput(fh)  
D0                                     D1
```

```
BPTR SelectOutput(BPTR)
```

This call replaces the output *file handle* of the calling process with the file handle given by `fh` and returns the previously used output *file handle*.

### 10.2.5 Retrieve the Error File Handle

The `ErrorOutput()` function returns the file handle through which diagnostic or error outputs should be printed. It uses either `pr_CES` if this handle is non-`ZERO`, or `pr_COS` if the former is `ZERO`. If neither an error output nor a regular output is provided, this function returns `ZERO`.

```
file = ErrorOutput()  
D0
```

```
BPTR ErrorOutput(void)
```

This function returns a *BPTR* to the error *file handle* of the calling process, or falls back to the *BPTR* of the output *file handle* if the former is not available. This is the file handle through which diagnostic output should be printed and is therefore approximately identical to `stderr` of ANSI-C. Depending on process creation, this file handle can be closed by the process shutdown code or the calling shell and thus should in general not be closed explicitly. It can be changed through `SelectError()`.

### 10.2.6 Replace the Error File Handle

The `SelectError()` function replaces the error *file handle* of the calling process with its argument and returns the previously used error handle.

```
old_fh = SelectError(fh)  
D0                                     D1
```

```
BPTR SelectError(BPTR)
```

---

This call replaces the error *file handle* of the calling process with the file handle given by `fh` and returns the previously used error *file handle*.

### 10.2.7 Retrieve the Current Directory

The `GetCurrentDir()` function retruns the current directory of the directory, indicated by a *lock* on this object. This *lock*, and the *file system* that created the lock are used to resolve relative paths, see also section 4.3.

```
lock = GetCurrentDir(void)
D0
```

```
BPTR GetCurrentDir()
```

This function returns the *lock* to the current directory, unlike the `CurrentDir()` function which also changes it.

### 10.2.8 Replace the Current Directory

The `CurrentDir()` selects and retrieves the current directory of the calling process. The directory is indicated by a *lock* to this object. This *lock*, and the *file system* that created the lock are used to resolve relative paths, see also section 4.3.

```
oldLock = CurrentDir( lock )
D0                                D1
```

```
BPTR CurrentDir(BPTR)
```

This function sets the current directory to `lock` and returns in `oldLock` the previously installed current directory. The passed in `lock` then becomes part of the process and shall not be released by `UnLock()` until another *lock* is installed as current directory.

If the current directory is `ZERO`, paths are relative to the root directory of the *file system* set in the `pr_FileSystemTask` member of the calling process. It may be changed by `SetFileSysTask()` described in section 10.2.12. AmigaDOS installs there the *file system* of the boot volume, unless a user installs a different default *file system*.

### 10.2.9 Return the Latest Error Code

The `IoErr()` function returns the secondary result code of the most recent AmigaDOS operation. This code is, in case of failure, typically an error code indicating the nature of the failure.

```
error = IoErr()
D0
```

```
LONG IoErr(void)
```

This function returns the secondary result code of the last call to the *dos.library* that provides such result. Unfortunately, not all functions set `IoErr()` consistently; all unbuffered operations in section 4.7 provide an error code in case of failure, or deliver 0 as secondary result in case of success. The buffered functions in section 4.8 generally only set a secondary result code in case an I/O operation is required, but do not touch `IoErr()` if the call can be satisfied from the caller. Whether a function of the *dos.library* touches `IoErr()` is stated in the description of the corresponding function — unfortunately, the *dos.library* does not handle `IoErr()` consistently.



---

Some functions provide a secondary result code different from an error code, and thus make such additional return value available through `IoErr()`. Such additional return values are also explicitly mentioned in the description of the corresponding function. A particular example is `DeviceProc()`, which returns the (first) lock of a regular assign in `IoErr()`, but additional functions exist.

Most error codes are defined in `dos/dos.h`, with some additional error codes only used by the pattern matcher (see section 9) in `dos/dosasl.h`. Generally, *handlers* and *file systems* can select error codes as they seem fit, the list below provides a general indication how the codes are used by the *dos.library* itself, or what their suggested usage is:

**ERROR\_NO\_FREE\_STORE:** This error code is set if the system run out of memory. Actually, this error code is not set by the *dos.library*, but rather by the *exec.library* memory allocation functions.

**ERROR\_TASK\_TABLE\_FULL:** This error code is no longer in use. Previous releases of AmigaDOS created it if more than 10 shell processes were about to be created. As this limitation was removed, the error code remains currently unused.

**ERROR\_BAD\_TEMPLATE:** This error code indicates that the command line template for `ReadArgs()` is syntactical incorrect. It is also set by the pattern matcher in case the pattern is syntactically incorrect.

**ERROR\_BAD\_NUMBER:** This error code indicates that a string could not be converted to a number.

**ERROR\_REQUIRED\_ARG\_MISSING:** This error code is set by `ReadArgs()` if a non-optional argument is not provided.

**ERROR\_KEY\_NEEDS\_ARG:** This error code is also used by the argument parser `ReadArgs()` if an argument key is provided on the command line, but a corresponding argument value is missing.

**ERROR\_TOO\_MANY\_ARGS:** This error code can also be set by `ReadArgs()`; it indicates that more arguments are provided than indicated in the template.

**ERROR\_UNMATCHED\_QUOTES:** This error code indicates that a closing quote is missing for at least one opening quote. It is also set by the argument parser and `ReadItem()`.

**ERROR\_LINE\_TOO\_LONG:** This error code is a general indicator that a user provided buffer is too small to buffer a string. It is for example used again by the argument parser and the path manipulation functions in section 6.3.

**ERROR\_FILE\_NOT\_OBJECT:** This error code is generated by the *Shell* if an attempt is made to execute a file that is neither a script, nor an executable nor a file that can be opened by a viewer.

**ERROR\_INVALID\_RESIDENT\_LIBRARY:** While this error code is not in use by the *dos.library*, several *handlers* and other Os components use it to indicate that a required library or device is not available.

**ERROR\_NO\_DEFAULT\_DIR:** This is error code is also not in use. Its intended purpose is unclear.

**ERROR\_OBJECT\_IN\_USE:** This error code is used by multiple Os components to indicate that a particular operation cannot be performed because the object to be modified is in use. AmigaDOS uses it, for example, to indicate that a *lock* was obtained on an object that is supposed to be modified or deleted, and thus cannot be modified or removed.

**ERROR\_OBJECT\_EXISTS:** This error code is a generic error indicator that an operation could not be performed because another object already exists in place, and is used as such by multiple Os components. AmigaDOS *file systems* use it, for example, when attempting to create a directory, but a file or a directory of the requested name is already present.

**ERROR\_DIR\_NOT\_FOUND:** This error code indicates that the target directory is not found. Of the AmigaDOS ROM components, only the shell uses it on an attempt to change the working directory to a non-working target directory.

**ERROR\_OBJECT\_NOT\_FOUND:** This is a generic error code that indicates that the object on which a particular operation is to be performed does not exist. It is for example generated on an attempt to open a non-existing file or to lock a file or directory that could not be found.

---

**ERROR\_BAD\_STREAM\_NAME:** This error code is currently not in use by AmigaDOS ROM components. Its purpose is unclear.

**ERROR\_OBJECT\_TOO\_LARGE:** This error could be used to indicate that an object is beyond the size a *handler* or *file system* is able to handle. Note that a full disk (or full storage medium) is indicated by **ERROR\_DISK\_FULL**, and not this error. However, currently no AmigaDOS component uses this error, even though the FFS should probably return it on an attempt to create or access files larger than 2GB.

**ERROR\_ACTION\_NOT\_KNOWN:** This is a generic error code that is returned by many *handlers* or *file systems* when an action (in the form of a *packet*) is requested the handler does not support or understand. For example, this error is created when attempting to create a directory on a console handler.

**ERROR\_INVALID\_COMPONENT\_NAME:** This is an error that is raised by file systems when providing an invalid path, or a path that contains components that are syntactically incorrect. For example, the colon (":") shall only appear one in a path as separator between the device name and the path within the device. A colon within a component is therefore a syntactical error. Also, all Amiga ROM file systems do not accept code points below 0x20, i.e. ASCII control characters.

**ERROR\_INVALID\_LOCK:** This error is raised if a value is passed in as a *lock* that is, in fact, not a valid lock of the target *file system*. For example, an attempt to use a *file handle* as a lock will result in such an error condition. Note, however, that *file systems* can, but do not need to check locks for validity. Passing incorrect objects to *file systems* can raise multiple error conditions of which this error code is probably the most harmless.

**ERROR\_OBJECT\_WRONG\_TYPE:** This error code indicates that a particular operation is not applicable to a target object, even though the target object is valid and existing. For example, an attempt to open an existing directory for reading as a file will raise this error.

**ERROR\_DISK\_NOT\_VALIDATED:** This error indicates that the inserted medium is currently not validated, i.e. not checked for consistency. Such a consistency check (or validation) may be currently ongoing. This error is for example generated if a write operation is attempted on an FFS volume whose validation is still ongoing. In such a case, retrying the operation later may solve the problem already.

**ERROR\_DISK\_WRITE\_PROTECTED:** This indicates that an attempt was made to write to a medium, e.g. a disk, that is write-protected, or that cannot be written to, such as an attempt to write to a CD-ROM.

**ERROR\_RENAME\_ACROSS\_DEVICES:** Generated if an attempt is made to move an object to a target directory that is located on a different medium or different *file system* than the source directory. This cannot succeed, instead the object (and its subobjects) need to be copied manually.

**ERROR\_DIRECTORY\_NOT\_EMPTY:** Indicates that an attempt was made to delete a directory that is not empty. First, all the files within a directory must be deleted before the directory itself may be deleted.

**ERROR\_TOO\_MANY\_LEVELS:** This error code is generated if too many softlinks refer iteratively to other softlinks. In order to avoid an endless indirection of softlinks referring to each other, the *dos.library* aborts following softlinks after 15 passes; application programs attempting to resolve softlinks themselves through `ReadLink()` should implement a similar mechanism, see also section 6.4.2.

**ERROR\_DEVICE\_NOT\_MOUNTED:** This error indicates that an access was attempted to either a *handler*, *file system* or *assign* that is not known to the system, or to a volume that is currently not inserted in any known drive.

**ERROR\_SEEK\_ERROR:** This error is generated by an attempt to `Seek()` to a file position that is either negative, or behind the end of the file. It is also signalled if the mode of `Seek()` or `SetFileSize()` is none of the modes indicated in table 10. The FFS also sets this mode if it cannot read one of its administration blocks.

**ERROR\_COMMENT\_TOO\_BIG:** This error is raised if the size of the comment is too large to be stored in the metadata of the *file system*. Note that while *file systems* shall validate the size of the comment, it shall silently truncate file names to the maximal size possible.

---

**ERROR\_DISK\_FULL:** Generated by *file systems* when an attempt is made to write more data to a medium than it is possible to hold, i.e. when the target medium is full.

**ERROR\_DELETE\_PROTECTED:** This error is generated by *file systems* if an attempt is made to delete a file that is delete protected, i.e. whose `FIBB_DELETE` protection bit is set, see table 20 in section 6.1.

**ERROR\_WRITE\_PROTECTED:** This error is generated by *file systems* if a write is attempted to a file that is write protected, i.e. whose `FIBB_WRITE` bit is set.

**ERROR\_READ\_PROTECTED:** This error is generated on an attempt to read from a while whose `FIBB_READ` bit is set to indicate read protection.

**ERROR\_NOT\_A\_DOS\_DISK:** This error is generated by a *file system* on an attempt to read a disk that is not structured according to the requirements of the *file system*, i.e. that is initialized by another incompatible *file system* different from the mounted one. Unfortunately, AmigaDOS does not have a control instance that selects file systems according to the disk layout.

**ERROR\_NO\_MORE\_ENTRIES:** This secondary result code does not really indicate an error condition, it just reports to the caller that the end of a directory has been reached when scanning it by `ExNext()` or `ExAll()`.

**ERROR\_IS\_SOFT\_LINK:** This error code is generated by *file systems* on an attempt to access a *soft link*. For many functions, the *dos.library* recognizes this error and then resolves the link through `ReadLink()` within the library, not requiring intervention of the caller. However, not all functions of the *dos.library* are aware of *soft links*, see section 6.4 for the list.

**ERROR\_OBJECT\_LINKED:** This error code is currently not used by AmigaDOS and its intended use is not known.

**ERROR\_BAD\_HUNK:** Generated by `LoadSeg()` and `NewLoadSeg()`, this error code indicates that the binary file includes a hunk type that is not supported or recognized by AmigaDOS. The hunk format for binary executables is documented in section ??.

**ERROR\_NOT\_IMPLEMENTED:** This error code is not used by any ROM component, but several workbench components signal this error indicating that the requested function is not supported by this component. For example, the `Format` command generates it on an attempt to format a disk with long file names if the target file system does not support them.

**ERROR\_RECORD\_NOT\_LOCKED:** Issued by *file systems* and their record-locking subsystem if an attempt is made to release a record that is, actually, not locked.

**ERROR\_LOCK\_COLLISION:** This error is also created by the record-locking subsystem of *file systems* if attempt is made to exclusively lock the same region within a file by two write locks.

**ERROR\_LOCK\_TIMEOUT:** Also generated by the record-locking mechanism of *file systems* if an attempt was made to exclusively lock a region of a file that is exclusively locked already, and the attempt failed because the region did not become available before the lock timed out.

**ERROR\_UNLOCK\_ERROR:** This error is currently not generated by any *file system*, though could be used to indicate that an attempt to unlock a record failed for an unknown reason.

**ERROR\_BUFFER\_OVERFLOW:** This error is raised by the pattern matcher and indicates that the buffer allocated in the `AnchorPath` structure is too small to keep the fully expanded matching file name, see also section ??.

**ERROR\_BREAK:** This error is also raised by the pattern matcher if it received an external signal for aborting a directory scan for objects. Such signals are raised, for example, by the user through the console by pressing `Ctrl + C` through `Ctrl + F`.

**ERROR\_NOT\_EXECUTABLE:** This error is generated by the workbench on an attempt to start an application icon from a file whose `FIBB_EXECUTE` is set, indicating that the file is not executable. Why the workbench does not use the same error code as the *Shell* remains unclear.

---

### 10.2.10 Setting IoErr

The `SetIoErr()` function sets the value returned by the next call to `IoErr()` and thus initializes or resets the next IO error.

```
oldcode = SetIoErr(code)
D0                      D1

LONG SetIoErr(LONG);
```

This function sets the next value returned by `IoErr()`; this can be necessary because some functions of the *dos.library* do not update this value in all cases. A particular example are the buffered I/O functions introduced in section ?? that do not touch `IoErr()` in case the input or output operation can be satisfied from the buffer. A good practise is to call `SetIoErr(0)` upfront to ensure that these functions leave a 0 in `IoErr()` on success.

This function returns the previous value of `IoErr()`, and thus the same value `IoErr()` would return.

### 10.2.11 Select the Console Handler

The `SetConsoleTask()` function selects the *handler* responsible for the “\*” file name and `CONSOLE:` pseudo-device.

```
oldport = SetConsoleTask(port)
D0                      D1

struct MsgPort *SetConsoleTask(struct MsgPort *)
```

This function selects the *MsgPort* of the console handler. AmigaDOS will contact this handler for opening the “\*” as file name, or a file relative to the `CONSOLE:` pseudo-device. Note that the argument is not a pointer to the *handler* process, but rather to a *MsgPort* through which this process can be contacted. It returns the previously used console handler *MsgPort*.

This function is the setter function corresponding to the `GetConsoleTask()` getter function introduced in section 8.2.4.

### 10.2.12 Select the Default File System

The `SetFileSysTask()` function selects the handler responsible for resolving paths relative to the `ZERO` lock.

```
oldport = SetFileSysTask(port)
D0                      D1

struct MsgPort *SetFileSysTask(struct MsgPort *)
```

This function selects the *MsgPort* of the default *file system*. AmigaDOS will contact this *file system* if a path relative to the `ZERO` lock is resolved, e.g. a relative path name if the current directory is `ZERO`. This *file system* should be identical to the *file system* of the `SYS:` assign, and should therefore not be relaced as otherwise resolving file names may be inconsistent between processes.

Note that the argument is not a pointer to the *handler* process, but rather to a *MsgPort* through which this process can be contacted. It returns the previously used default file system *MsgPort*. This function is the setter equivalent of `GetFileSysTask()` introduced in section 8.2.5.

---

### 10.2.13 Retrieve the Lock to the Program Directory

The `GetProgramDir()` returns a lock to the directory that contains the binary from which the caller executes, if such a directory exists. If the executable was made resident, this function returns `ZERO`.

```
lock = GetProgramDir()
D0
```

```
BPTR GetProgramDir(void)
```

The lock returned by this function corresponds to the `PROGDIR:` (pseudo)-assign and the `pr_HomeDir` member of the `Process` structure, with the only exception that `ZERO` does not correspond to the root directory of the boot volume, but rather indicates that no home directory exists.

### 10.2.14 Set the Program Directory

The `SetProgramDir` sets the directory within which the executing program is made to believe of getting started from, and the directory that corresponds to the `PROGDIR:` pseudo-assign.

```
oldlock = SetProgramDir(lock)
D0          D1
```

```
BPTR SetProgramDir(BPTR)
```

This function installs `lock` into `pr_HomeDir` of the `Process` structure. This lock is supposed to belong to the directory the currently executing program was loaded from and is used to resolve the `PROGDIR:` pseudo-assign. If `ZERO` is installed, the current process will be unable to resolve this pseudo-assign.

### 10.2.15 Retrieve Command Line Arguments

The `GetArgStr()` function returns the command line arguments, if any, of the calling process. If called from the workbench, this function returns `NULL`.

```
ptr = GetArgStr()
D0
```

```
STRPTR GetArgStr(void)
```

This function returns the command line arguments as NUL-terminated string. This is the same string the process finds in register `a0` on startup, or that is placed into the file buffer of the `Input()` file handle. This function returns `NULL` if the program was run from the workbench; it is equivalent to reading the `pr_Arguments` member of the `Process` structure.

### 10.2.16 Set the Command Line Arguments

The `SetArgStr()` function sets the string returned by `GetArgStr()`. It cannot set the command line arguments as seen by `ReadArgs()`.

```
oldptr = SetArgStr(ptr)
D0      D1
```

```
STRPTR SetArgStr(STRPTR)
```

This function requires a pointer to a NUL terminated string as `ptr` and installs it to `pr_Arguments` member of the `Process` structure. This is unfortunately of limited use as the `ReadArgs()` function takes the command line arguments from a different source, namely the input buffer of the `Input()` file handle.



---

## Chapter 11

# Binary File Structure

The AmigaDOS *Hunk* format represents executable and linkable object files. While both formats are related, they are not identical; executables can be loaded from the shell or the workbench from disk to RAM, and then either overload the shell process, or a new process is created from them. Object files are created as intermediate compiler outputs; typically, each translation unit is compiled into one object file which are then, in a final step, linked with a startup code and object code libraries to form an executable.

An object or executable file in this format consists of multiple *hunks* (thus, the name). Hunks define either payload data as indivisible *segments* of code or data that is initialized or loaded from disk, or additional meta-information interpreted by the AmigaDOS loader, the `LoadSeg()` function. The meta-information is used to relocate the payload to their final position in memory, to define the size of the sections, to select the memory type that is allocated for the segment, or to interrupt or terminate the loading process.

Loaded executables are represented as singly linked list of segments in memory, by a structure that looks as follows:

```
struct LoadedSegment {
    BPTR  NextSegment; /* BPTR to next segment or ZERO */
    ULONG Data[1];     /* Payload data */
};
```

The above structure is *not* documented and is not identical to the `Segment` in `dos/dosextens.h`. The latter describes a resident executable, see section ??, but also contains a *BPTR* to a segment in the above sense. Each segment of a binary is allocated through `AllocVec()` which is sometimes helpful as it allows to retrieve size of the segment from the size of the allocated memory block.

The hunk format distinguishes three types of *segments*, each represented by a hunk: *code hunks* that should contain constant data, most notably executable machine code and constant data associated to this code, *data hunks* that contain (variable) data, and so called *BSS* hunks that contain data that is initialized to zero. Thus, the contents of *BSS* hunks is not represented on disk.

**Const is not enforced** While *code hunks* should contain executable code and other constant data, and *data hunks* should contain variable data, nothing in AmigaDOS is able to enforce these conventions. In principle, *data hunks* may contain executable machine code, and *code hunks* may contain variable data. Note, however, that some third party tools may require programs to follow such conventions. Many commercial compilers structure their object code according to these conventions, or at least do so in their default configuration.

Additional *hunks* describe how to relocate the loaded code and data. Relocation means that data within the hunk is corrected according to the addresses this and other hunks are loaded to. The relocation process takes an offset into one hunk, and adds to the longword at this offset the absolute address of this or any other

hunk. That is, hunks on disk are represented as if their first byte is placed at address 0, and relocation adjusts longwords within hunks to the final positions in memory.

An extension of the executable file format is the *overlay format* also supported by `LoadSeg()`. Here, only a part of the file is loaded into memory, while the remaining parts are only loaded on demand, potentially releasing other already loaded parts from memory. Overlaid executables thus take less main memory, though requires the volume containing the executable available all the time.

AmigaDOS also contains a simple run-time binder that is only used by compiled BCPL code, or by code that operates under such requirements. The purpose of this binder is to populate the BCPL *global vector* of the loaded program. While this runtime binder implements a legacy protocol, certain parts of AmigaDOS still expect. These are *handlers* or *file systems* that use the `dol_GlobVec` value of 0 or -2, or corresponding `GlobVec` entry in the mount list. While new handlers should not use this BCPL legacy protocol, the ROM file system (the FFS) and the port-handler currently still depend (or require) it, despite not being written in BCPL. A second application of this run-time binding protocol is the shell which also depends on BCPL binding.

## 11.1 Executable File Format

The hunk format of executable files consists of 4-byte (longword) hunk identifiers and subsequent data that is interpreted by the AmigaDOS loader according to the introducing hunk identifier. The syntax of such a file, and its hunks, is here presented in a pseudo-code, in three-column tables.

The first column identifies the number of bits a syntax element takes. Bits within a byte are read from most significant to least significant bit, and bytes within a structure that extends over multiple bytes are read from most significant to least significant bit. That is, the binary file format follows the big-endian convention. If the first column contains a question mark (“?”), the structure is variably-sized, and the number of removed bits is defined by the second column, or the section it refers to. If the first column is empty, no bits are removed from the file.

The second column either identifies the member of a structure to which the value removed from the stream is assigned, or contains pseudo-code that describes how to process the values parsed from the stream. These syntax elements follow closely the convention of the C language. In particular `if (cond)` formulates a condition that is only executed if *cond* is true, `else` describes code that is executed following an `if` clause that is executed if *cond* is false, and `do ... while (cond)` indicates a loop that continues as long as *cond* is non-zero, and that may alternatively be terminated by a `break` within the body of the loop. The expression `i++` increments an internal state variable *i*, and the expression `--j` decrements an internal state variable. The value of `i++` is the value of *i* before the increment, and the value of `--j` is the value of *j* after decrementing it.

The following pseudo-code describes the top-level syntax of a binary executable file AmigaDOS is able to bring to memory:

**Table 29: Regular Executable File**

| Size | Code                 | Syntax   |
|------|----------------------|--|
| ?    | HUNK_HEADER          | Defines all segments, see section 11.1.1 for details   |
|      | $i = t_{\text{num}}$ | Start with the first hunk, $t_{\text{num}}$ is defined in the HUNK_HEADER  |
|      | do {                 | Repeat until all hunks done  |
| 2    | $\hat{m}_t[i]$       | These two bits are unused, but some utilities set it identical to $m_t[i]$ , the memory type of the hunk, see 11.1.1 |
| 1    | $a_f$                | Advisory hunk flag.  |



|        |  |  |
|--------|--|--|
| 29     | h  | This is the hunk type  |
|        | if (EOF) break;  | Terminate loading on end of file   |
|        | if (a <sub>f</sub> ) {                                     | Check for bit 29, these are advisory hunks   |
| 32     | l  | Read length of advisory hunk   |
| 32 × l |  | l long words of hunk contents ignored  |
|        | }  |  |
|        | else if (h == HUNK_END)<br>i++;                            | Advance to next segment, see 11.1.11   |
|        | else if (h == HUNK_BREAK)<br>break;                        | Terminate loading an overlay, see 11.3.4   |
| ?      | else if (h == HUNK_NAME)<br>parse_NAME;                    | See section 11.1.8   |
| ?      | else if (h == HUNK_CODE)<br>parse_CODE;                    | See section 11.1.2   |
| ?      | else if (h == HUNK_DATA)<br>parse_DATA;                    | See section 11.1.3   |
| ?      | else if (h == HUNK_BSS)<br>parse_BSS;                      | See section 11.1.4   |
| ?      | else if (h ==<br>HUNK_RELOC32) parse_RELOC32;              | See section 11.1.5   |
| ?      | else if (h ==<br>HUNK_SYMBOL) parse_SYMBOL;                | See section 11.1.9   |
| ?      | else if (h == HUNK_DEBUG)<br>parse_DEBUG;                  | See section 11.1.10  |
| ?      | else if (h ==<br>HUNK_OVERLAY) {<br>parse_OVERLAY; break } | See section 11.3.3   |
| ?      | else if (h<br>== HUNK_DREL32)<br>parse_RELOC32SHORT;       | This is a compatibility kludge for some<br>older versions of the <i>dos.library</i> , new tools<br>should use HUNK_RELOC32SHORT in-<br>stead, see section 11.1.6 |
| ?      | else if (h ==<br>HUNK_RELOC32SHORT)<br>parse_RELOC32SHORT; | See section 11.1.6   |
| ?      | else if (h ==<br>HUNK_RELRELOC32)<br>parse_RELRELOC32;     | See section 11.1.7   |
|        | else ERROR_BAD_HUNK;                                       | Everything else is invalid   |
|        | } while(true)  | repeat until all hunks done  |

In particular, every executable shall start with the HUNK\_HEADER identifier, the big-endian long-word 0×3f3. The following stream contains long-word identifiers of which the first 2 bits are ignored and masked out. Some tools (e.g. the Atom tool by CBM) places there memory requirements similar to what is indicated in the HUNK\_HEADER. They have there, however, no effect as the segments are allocated within the HUNK\_HEADER and not at times the hunk type is encountered.

Bit 29 (HUNKB\_ADVISORY) has a special meaning. If this bit is set, then the hunk contents is ignored. The size of such an *advisory* hunk is defined by a long-word following the hunk type.

Loading a binary executable terminates on three conditions. Either, if an end of file is encountered. This closes the file handle and returns to the caller with the loaded segment list. Or, if a HUNK\_BREAK or HUNK\_OVERLAY are found. This mechanism is used for *overlayed* files. In the latter two cases, the file

remains open, and for `HUNK_OVERLAY`, information on the loaded file is injected into the first hunk of the loaded data. More information on this mechanism is provided in section 11.3.

### 11.1.1 HUNK\_HEADER

The `HUNK_HEADER` is the first hunk of every executable file. It identifies the number of segments in an executable, and the amount of memory to reserve for each segment.

**Table 30: Hunk Header Syntax**

| Size | Code  | Syntax   |
|------|---|--|
| 32   | <code>HUNK_HEADER [0x3f3]</code>  | Every executable file shall start with this hunk         |
| 32   | 0   | Number of resident libraries, BCPL legacy, shall be zero |
| 32   | $t_{\text{size}} \in [1, 2^{31} - 1]$   | Number of segments in binary                             |
| 32   | $t_{\text{num}} \in [0, t_{\text{size}} - 1]$   | First segment to load                                    |
| 32   | $t_{\text{max}} \in [t_{\text{num}}, t_{\text{size}} - 1]$  | Last segment to load (inclusive)                         |
|      | <code>for (i=t<sub>num</sub>; i ≤ t<sub>max</sub>; i++) {</code>  | Iterate over all hunks                                   |
| 2    | $m_t[i]$  | Read memory type of the segment as 2 bits                |
| 30   | $m_s[i]$  | Read memory size in long words as 30 bits                |
|      | <code>if (m[i] == 3) {</code>   | if the memory type is 3                                  |
| 32   | $m_t[i]$  | Memory type is explicitly provided                       |
|      | <code>}</code>  | End of special memory condition                          |
|      | $m_a[i] =$<br><code>AllocVec(sizeof(BPTR) +</code><br><code>m<sub>s</sub>[i] × sizeof(LONG), m<sub>t</sub>[i])</code><br><code>MEMF_PUBLIC) + sizeof(BPTR)</code> | Get memory for segment                                   |
|      | <code>}</code>  | End of loop over segments                                |

The first member of a `HUNK_HEADER` shall always be 0; it was used by a legacy mechanism which allowed run-time binding of the executable with dynamic libraries. While first versions of AmigaDOS inherited this mechanism from TRIPOS, it was not particularly useful as the calling conventions for such libraries did not follow the usual conventions of AmigaDOS, i.e. with the library base in register `a6`. Later versions of AmigaDOS, in particular its re-implementation as of Kickstart v37, removed support for such libraries. As this mechanism is no longer supported, it is not documented here. More information is found in [10].

The second entry  $t_{\text{size}}$  contains the number of segments the executable consists of. In case of overlays, it is the total number of segments that can be resident in memory at all times. See section 11.3 for more information. This value shall be consistent for all `HUNK_HEADERS` within an overlayed file. In regular executables, only a single `HUNK_HEADER` exists at the beginning of the file.

The members  $t_{\text{num}}$  and  $t_{\text{max}}$  define the 0-based index of the first and last segment to load within the branch of the overlay tree described by this `HUNK_HEADER`. For a regular (non-overlayed) file and for the root node of the overlay tree,  $t_{\text{num}}$  shall be 0, that is, the first segment to load is 0, the first index in the segment table.

For regular files,  $t_{\text{max}}$  shall be identical to  $t_{\text{size}} - 1$ , that is, the last segment to load is the last entry in the segment table described by this `HUNK_HEADER`. For overlayed files, the number may be smaller, i.e. not all segments may be populated initially and loading may continue later on when executing the binary.

### 11.1.2 HUNK\_CODE

This hunk should contain executable machine code and constant data. As executables are started from the first byte of the first segment, the first hunk of an executable should be a `HUNK_CODE`, and it should start

with a valid opcode.

Compilers use typically this hunk to represent the `text` segment, i.e. compiled code and constant data. The structure of this hunk is as follows:

**Table 31: Hunk Code Syntax**

| Size          | Code              | Syntax  |
|---------------|-------------------|---|
|               | HUNK_CODE [0x3e9] | A hunk describing a segment of code and constant data |
| 32            | $l \leq m_s[i]$   | Size of the payload                                   |
| $1 \times 32$ | Code              | $l$ long words of payload                             |

Note that the size of the payload loaded from the file may be less than the size of the allocated segment as defined in `HUNK_HEADER`. In such a case, all bytes of the segment not included in the `HUNK_CODE` are zero-initialized. AmigaDOS versions earlier than v37 skipped this initialization. Due to a bug in the loader in later versions, the initialization is also skipped of the hunk length  $l$  is 0.

### 11.1.3 HUNK\_DATA

This hunk should contain variable data, and it should not contain executable code. Compilers typically use this hunk to represent initialized data.

The structure of this hunk is otherwise identical to `HUNK_CODE`:

**Table 32: Hunk Data Syntax**

| Size          | Code              | Syntax                              |
|---------------|-------------------|-------------------------------------|
|               | HUNK_CODE [0x3ea] | A hunk describing a segment of data |
| 32            | $l \leq m_s[i]$   | Size of the payload                 |
| $1 \times 32$ | Code              | $l$ long words of payload           |

Similar to `HUNK_CODE`, the size of the payload defined by this hunk may be less than the size of the segment allocated by `HUNK_HEADER`. Excess bytes are zero-initialized in all AmigaDOS releases from v37 onwards. Due to a bug in the loader in later versions, the initialization is also skipped of the hunk length  $l$  is 0.

### 11.1.4 HUNK\_BSS

This hunk contains zero-initialized data; it does not define actual payload.

The structure of this hunk is as follows:

**Table 33: Hunk BSS Syntax**

| Size | Code              | Syntax                                  |
|------|-------------------|---|
|      | HUNK_CODE [0x3eb] | A hunk describing zero-initialized data |
| 32   | $l \leq m_s[i]$   | Size of the segment in long-words       |

Note that this hunk does not contain any payload; the segment allocated from this hunk is always zero-initialized.

Due to a defect in AmigaDOS prior release v37, the BSS segment will not be completely initialized to zero if the segment size is larger than 256K, i.e. if  $l > 2^{16}$ . Also, these releases do not initialize long words beyond the  $l^{\text{th}}$  long-word to zero, i.e. the excess bytes included if  $l < m_s[i]$ .

### 11.1.5 HUNK\_RELOC32

This hunk contains relocation information for the previously loaded segment; that is, it corrects addresses within this segment by adding the absolute address of this or other segments to long words at indicated offsets of the previous segments.

The structure of this hunk is as follows:

**Table 34: Hunk Reloc32 Syntax**

| Size | Code                                      | Syntax  |
|------|---|---|
|      | HUNK_RELOC32 [0x3ec]                      | A hunk containing relocation information                  |
|      | do {                                      | Loop over relocation entries                              |
| 32   | $c$                                       | Number of relocation entries                              |
|      | if ( $c == 0$ ) break;                    | Terminate the hunk if the count is zero                   |
| 32   | $j \in [0, t_{\text{size}} - 1]$          | Read the hunk to which the relocation is relative to      |
|      | do {                                      | Loop over the relocation entries                          |
| 32   | $r_o \in [0, m_s[i] \times 4 - 4]$        | Relocation offset into this hunk as byte address          |
|      | (UBYTE **) ( $m_a[j] + r_o$ ) += $m_a[j]$ | Fixup this hunk by the start address of the selected hunk |
|      | } while (--c);                            | until all entries are used                                |
|      | } while(true);                            | until a zero-count is read.                               |

That is, the hunk consists first of a counter that indicates the number of relocation entries, followed by the hunk index relative to which an address should be relocated. Then relocation entries follow; each long-word defines an offset into the previously loaded segment to relocate, that is, to fix up the address.

For AmigaDOS versions 37 and up (Kickstart 2.0 and later), the number of relocation entries  $c$  shall not be larger than  $2^{16}$ . This is a known defect of the loader that has currently not yet fixed. If more relocation entries are needed, they shall be split into multiple chunks.

### 11.1.6 HUNK\_RELOC32SHORT

This hunk contains relocation information for the previously loaded segment, and is almost similar to HUNK\_RELOC32, except that hunk indices, counts and offsets are only 16 bits in size. To ensure that all hunks start at long-word boundaries, the hunk contains an optional padding field at its end to align the next hunk appropriately.

The structure of this hunk is as follows:

**Table 35: Hunk Reloc32Short Syntax**

| Size | Code                               | Syntax   |
|------|------------------------------------|--|
|      | HUNK_RELOC32SHORT [0x3fc]          | A hunk containing relocation information             |
|      | $p=1$                              | Padding count  |
|      | do {                               | Loop over relocation entries                         |
| 16   | $c$                                | Number of relocation entries                         |
|      | if ( $c == 0$ ) break;             | Terminate the hunk if the count is zero              |
| 16   | $j \in [0, t_{\text{size}} - 1]$   | Read the hunk to which the relocation is relative to |
|      | $p += c$                           | Update padding count                                 |
|      | do {                               | Loop over the relocation entries                     |
| 16   | $r_o \in [0, m_s[i] \times 4 - 4]$ | Relocation offset into this hunk as byte address     |

|    |  |   |
|----|--|---|
|    | <code>(UBYTE **)(m<sub>a</sub>[i] + r<sub>o</sub>) +=</code> | Fixup this hunk by the start address of the selected hunk |
|    | <code>m<sub>a</sub>[j]</code>                                |   |
|    | <code>} while(--c);</code>                                   | until all entries are used                                |
|    | <code>} while(true);</code>                                  | until a zero-count is read.                               |
|    | <code>if (p &amp; 1) {</code>                                | check whether padding is required.                        |
| 16 |  | dummy for long-word alignment                             |
|    | <code>}</code>   |   |

Due to an oversight, some versions of AmigaDOS do not understand the hunk type `0x3fc` properly and use instead `0x3f7`. This alternative (but incorrect) hunk type for the short version of the relocation hunk is still supported currently.

### 11.1.7 HUNK\_RELRELOC32

This hunk contains relocation information for 32-bit relative displacements the 68020 and later processors offer. Its purpose is to adjust the offsets of a 32-bit wide PC-relative branches between segments.

The structure of this hunk is as follows:

**Table 36: Hunk RelReloc32 Syntax**

| Size | Code   | Syntax  |
|------|--|---|
|      | <code>HUNK_RELRELOC32 [0x3fd]</code>                             | A hunk containing relocation information                  |
|      | <code>do {</code>  | Loop over relocation entries                              |
| 32   | <code>c</code>   | Number of relocation entries                              |
|      | <code>if (c == 0) break;</code>                                  | Terminate the hunk if the count is zero                   |
| 32   | <code>j ∈ [0, t<sub>size</sub> - 1]</code>                       | Read the hunk to which the relocation is relative to      |
|      | <code>do {</code>  | Loop over the relocation entries                          |
| 32   | <code>r<sub>o</sub> ∈ [0, m<sub>s</sub>[i] × 4 - 4]</code>       | Relocation offset into this hunk as byte address          |
|      | <code>(UBYTE **)(m<sub>a</sub>[i] + r<sub>o</sub>) +=</code>     | Fixup this hunk by the start address of the selected hunk |
|      | <code>m<sub>a</sub>[j] - m<sub>a</sub>[i] - r<sub>o</sub></code> |   |
|      | <code>} while(--c);</code>                                       | until all entries are used                                |
|      | <code>} while(true);</code>                                      | until a zero-count is read.                               |

For AmigaDOS versions 37 and up (Kickstart 2.0 and later), the number of relocation entries  $c$  shall not be larger than  $2^{16}$ . This is a known defect of the loader that has currently not yet fixed. If more relocation entries are needed, they shall be split into multiple chunks.

Due to another defect, all elements of this hunk, namely  $c$ ,  $r_o$ ,  $j$  and  $r_o$  are only 16 bit wide, which limits the usefulness of this hunk. It is therefore recommended not to depend on this hunk type at all and avoid 32-bit wide branches between segments. Luckily, the support for this hunk type is very limited.

### 11.1.8 HUNK\_NAME

This hunk defines a name for the current segment. The AmigaDOS loader completely ignores this name, and it does not serve a particular purpose for the executable file format. However, linkers that bind object files together use the name to decide which segments to merge together to a single segment.

The structure of this hunk is as follows:

**Table 37: Hunk Name Syntax**

| Size   | Code              | Syntax   |
|--------|-------------------|--|
|        | HUNK_NAME [0x3e8] | A hunk assigning a name to the current segment |
| 32     | 1                 | Size of the name in long-words                 |
| 32 × 1 | $h_n$             | Hunk name                                      |

The size of the name is not given in characters, but in 32-bit units. The name is possibly zero-padded to the next 32-bit boundary to fill an integer number of long-words. If the name fills an entire number of long-words already, it is *not* zero-terminated.

While the specification does not define a maximum size of the name, the AmigaDOS loader fails on names longer than 124 character, i.e. 31 long-words.

### 11.1.9 HUNK\_SYMBOL

This hunk defines symbol names and corresponding symbol offsets or values within the currently loaded segment. Again, the AmigaDOS loader ignores this hunk, but the linker uses it to resolve symbols with external linkage to bind multiple object files together. If the symbol information is retained in the executable file, it may be used for debugging purposes.

The syntax of this hunk reads as follows:

**Table 38: Hunk Symbol Syntax**

| Size       | Code                    | Syntax   |
|------------|-------------------------|--|
|            | HUNK_SYMBOL [0x3f0]     | A hunk assigning symbols to positions within a segment |
|            | do {                    | Repeat ...   |
| 8          | $s_t$                   | Symbol type  |
| 24         | $s_l$                   | Symbol length in long-words                            |
|            | if ( $s_l == 0$ ) break | Terminate the hunk                                     |
| 32 × $s_l$ | $s_n$                   | Symbol name, potentially zero-padded                   |
| 32         | $s_v$                   | Symbol value   |
|            | } while (true)          | until zero-sized symbol                                |

The length of the symbol name is encoded in long-words, not in characters. If it does not fill an integer number of long-words, it is zero-padded; the name is not zero-terminated if it does fill an integer number of long-words, though. The AmigaDOS loader is currently limiting the maximum size of the symbol name to 124 characters, i.e.  $s_i < 32$ .

The symbol type  $s_t$  defines the nature of the symbol. The symbol types are defined in `dos/doshunks.h` and shared with the HUNK\_EXT hunk; the latter hunk type shall not appear in an executable file, but may only appear in an object file, see section 11.5.7.

The symbol type can be roughly classified into two classes: If bit 7 of the type is clear, a symbol is *defined* that may be referenced by another object file. If bit 7 is set, the symbol is *referenced* and requires resolution by a symbol definition with bit 7 cleared upon linking. Executable files, and thus symbols within HUNK\_SYMBOL, may only contain symbol definitions as references had been resolved by the linker before.

The following table contains the symbol types for definitions and those may therefore may appear in both HUNK\_SYMBOL as part of executables and HUNK\_EXT as part of object files; actually, HUNK\_SYMBOL will typically only include the first type of entry, i.e. EXT\_SYMB:

**Table 39: Symbol types in HUNK\_SYMBOL and HUNK\_EXT**

|          |        |  |
|----------|--------|--|
| EXT_SYMB | [0x00] | Definition of a symbol, $s_v + m_a[i]$ is the address of the symbol  |
| EXT_DEF  | [0x01] | Relocation definition, $s_v + m_a[i]$ is the address of the symbol. References to this symbol are converted into a relocation information to the offset $s_v$ in hunk $i$ .            |
| EXT_ABS  | [0x02] | Absolute value, $s_v$ is the value of the symbol which is substituted into the executable by the linker. No relocation information is created, the absolute value is just substituted. |
| EXT_RES  | [0x03] | Not longer supported as it is part of the obsolete dynamic library run-time binding interface, see [10] for more details.  |

Additional symbol types representing references used within HUNK\_EXT are documented in section 11.5.7.

### 11.1.10 HUNK\_DEBUG

This hunk contains debug information such as function names and line number information. Generally, the contents of this hunk is compiler or assembler specific, and the AmigaDOS loader does not interpret the contents of this hunk at all, it is just skipped over.

However, the debug information emitted by the SAS/C compiler for the “line-debug” option is also shared by other development tools such as the DevPac assembler and will be documented here. In this format, the debug hunk contains for each line of the source file an offset into the hunk to the code that was compiled from this line.

The syntax of this hunk is as follows:

**Table 40: Hunk Debug Syntax**

| Size   | Code                | Syntax   |
|--|---------------------|--|
|  | HUNK_DEBUG [0x3f1]  | Hunk including debug information   |
| 32   | $l > 3$             | Size of the hunk in long-words   |
| Compiler- and configuration specific data for line-debug data: |                     |  |
| 32   | $h_o$               | Offset of symbols into the hunk  |
| 32   | 'LINE'              | These four bytes shall contain the ASCII characters 'L', 'I', 'N', 'E' identifying the type of the debug information                     |
| 32   | $l_n$               | Size of the source file name in long-words   |
| $32 \times l_n$  | $n_f$               | source file name that compiled to the current segment in $l_n$ long-words  |
|  | $l- = 3 + l_n$      | Remove long-words read so far  |
|  | while ( $l > 0$ ) { | Repeat for all entries   |
| 8  |                     | Dummy byte   |
| 24   | $l_l$               | Line number within the source file   |
| 8  |                     | Dummy byte   |
| 24   | $l_v$               | Offset into the source file. The source file at line $l_l$ is compiled or assembled to the code at address $m_a[i] + l_v$ and following. |
|  | $l- = 2$            | Remove the read data   |
|  | };                  | Loop over the hunk.  |

The file name  $n_f$  is encoded in  $l_n$  long-words, and potentially padded with 0-bytes to fill an integer number of long-words. If it already is an integer number of long-words sized, it is *not* zero-terminated.

The hunk offset  $h_o$  is added to all offsets  $l_v$  into the hunk to determine the position of a symbol in the hunk.

While [1] documents the entire hunk contents except the hunk length  $l$  to be compiler dependent, it is is

recommended for custom debug hunks to always include the hunk offset  $h_o$  and the ID field — 'LINE' in this case — to simplify linker designs.

### 11.1.11 HUNK\_END

This hunk terminates the current segment and advances to the next segment, if any. It does not contain any data.

**Table 41: Hunk End Syntax**

| Size | Code             | Syntax              |
|------|------------------|---------------------|
|      | HUNK_END [0x3f2] | Terminate a segment |

## 11.2 The AmigaDOS Loader

The *dos.library* provides service functions for loading and releasing binary executables in the *Hunk* format introduced in section 11. The functions discussed in this section load such binaries into memory, constructing a segment list from the hunks found in the files, or release such files. Overlay files are discussed separately in section 11.3 due to their additional complexity.

A segment list is a linearly linked list as defined in section 11, i.e. the first four bytes of every segment form a *BPTR* to the following segment of the loaded binary, or ZERO for the last segment.

The `seglist` returned from the loader functions may be, for example, passed into `CreateNewProc()` as argument to the `NP_Seglist` tag for starting a new process.

### 11.2.1 Loading an Executable

The `LoadSeg()` function loads an executable binary in the Hunk format and returns a *BPTR* to the first segment:

```
seglist = LoadSeg( name )
D0                      D1
```

```
BPTR LoadSeg(STRPTR)
```

This function loads the binary executable named `name` and returns a *BPTR* to its first segment in case of success, or ZERO in case of failure. The `name` is passed into the `Open()` function and follows the conventions of this function for locating the file.

The segment list shall be removed from memory via `UnLoadSeg()`.

This function sets `IoErr()` to an error code in case of failure, or 0 in case of success.

### 11.2.2 Loading an Executable with Additional Parameters

The `NewLoadSeg()` function loads an executable providing additional data for loading.

```
seglist = NewLoadSeg(file, tags)
D0                      D1    D2
```

```
BPTR NewLoadSeg(STRPTR, struct TagItem *)
```

```
seglist = NewLoadSegTagList(file, tags)
D0                      D1    D2
```



---

```
BPTR NewLoadSegTagList (STRPTR, struct TagItem *)
```

```
seglist = NewLoadSegTags (file, ...)
```

```
BPTR NewLoadSegTags (STRPTR, ...)
```

This function loads a binary executable from `file` and returns a *BPTR* to its first segment, similar to `LoadSeg()`.

Additional parameters may be provided in the form of a `TagList`, passed in as `tags`. The first two functions are identical and differ only by their naming convention; the last function prototype also refers to the same entry within the *dos.library*, though uses a different calling convention where the second and all following arguments form the `TagList` itself. This `TagList` is build on the stack, and the pointer to this stack-based `TagList` is passed in.

While this function looks quite useful, AmigaDOS does currently not define any tags for this function, and thus no additional functionality over `LoadSeg()` is provided.

The segment list returned by this function shall be removed from memory via `UnLoadSeg()`, a specialized unloader function is not required for this call.

### 11.2.3 Loading an Executable through Call-Back Functions

The `InternalLoadSeg()` function loads a binary executable, retrieving data and memory through call-back functions. While `LoadSeg()` always goes through the *dos.library* and the *exec.library* for reading data and allocating memory, this function instead calls through user-provided functions.

```
seglist = InternalLoadSeg (fh, table, funcs)
D0                                     D0  A0  A1
```

```
BPTR InternalLoadSeg (BPTR, BPTR, struct LoadSegFuncs *)
```

This function loads a binary executable in the hunk format from an opaque file handle `fh` through functions in the `funcs`. The `table` argument shall be `ZERO` when loading regular binaries or the root node of an overlay file, and shall be a *BPTR* to the array containing pointers to all segments when loading a non-root overlay node, see section 11.3.

The `LSFuncs` structure contains function pointers through which this function loads data or retrieves memory. It looks as follows:

```
struct LoadSegFuncs {
    LONG __asm ReadFunc (register __d1 BPTR fh,
                        register __a0 APTR buffer,
                        register __d0 ULONG size,
                        register __a6 struct DosLibrary *DOSBase);
    APTR __asm AllocMem (register __d0 ULONG size,
                        register __d1 ULONG flags,
                        register __a6 struct ExecBase *SysBase);
    void __asm FreeMem (register __a1 APTR mem,
                        register __d0 ULONG size,
                        register __a6 struct ExecBase *SysBase);
}
```

The `ReadFunc()` function retrieves `d0` bytes from an opaque file handle passed into register `d1` and places the read bytes into the buffer pointed to by register `a0`, it shall return the number of bytes read in register `d0`,

---

or a negative value in case of error. Note that the file handle `d1` need not to be a file handle as returned by the `Open()` function, it is only a copy of the `fh` argument provided to `InternalLoadSeg()`. Register `a6` is loaded by a pointer to the *dos.library*.

The `AllocMem()` function allocates `d0` bytes of memory, using requirement flags from `exec/memory.h` such as `MEMF_CHIP` to require chip memory or `MEMF_FAST` for fast memory. This function shall return a pointer to the allocated memory in register `d0`, or `NULL` in case of failure. Register `a6` is loaded with a pointer to the *exec.library*.

The `FreeMem()` function releases a block of `d0` bytes pointed to by `a0`. Register `a6` is loaded with a pointer to the *exec.library*.

The purpose of this function is to load a segment or a binary without having access to a file or a *file system*; for example, this function could load binaries from ROM-space, or from the Rigit Disk Block of a boot partition. In particular, the `fh` argument does not need to be a regular *file handle*; it is rather an opaque value identifying the source. The `InternalLoadSeg()` function does not interpret this argument, but rather passes it into `funcs->ReadFunc()` in register `d1`.

When allocating memory, the `InternalLoadSeg()` function follows the conventions of the `AllocVec()` and `FreeVec()` functions and stores the number of allocated bytes in the first four bytes of the allocated memory block. In specific, the memory allocator and memory releaser functions provided in the `LoadSegFuncs` structure *do not need* to store the memory sizes, and the `exec AllocMem()` and `FreeMem()` functions satisfy the interfaces for `InternalLoadSeg()` function already.

This function does not set `IoErr()` consistently, unless the functions within `LoadSegFuncs` do. Callers should also call `SetIoErr(0)` upfront this function to identify all errors.

### 11.2.4 Unloading a Binary

The `UnLoadSeg()` function releases a linked list of segments as returned by `LoadSeg()` or `NewLoadSeg()`.

```
success = UnLoadSeg( seglist )
D0                      D1
```

```
BOOL UnLoadSeg(BPTR)
```

This function releases all segments chained together by `LoadSeg()` and `NewLoadSeg()` and returns their memory back into the system pool. This function *also* accepts overlayed segments, see section 11.3, and releases additional resources acquired for them.

Segment lists loaded through `InternalLoadSeg()` require in general a more generic unloader. They shall be released through `InternalUnLoadSeg()` instead, see 11.2.5.

This function returns a non-zero result in case of success, or 0 in case of error. Currently, the only source of error is passing in `ZERO` as segment list, all other cases will indicate success. In particular, this function does not attempt to check return codes of the function calls required to release resources associated to overlayed files.

### 11.2.5 UnLoading a Binary through Call-Back Functions

The `InternalUnLoadSeg()` function releases a segment list loaded through `InternalLoadSeg()`.

```
success = InternalUnLoadSeg(seglist, FreeFunc)
D0                      D1      A1
```

```
BOOL InternalUnLoadSeg(BPTR,
                      void __asm (*) (register __a1 APTR,
```

```

register __d0 ULONG,
register __a6 struct ExecBase
               *SysBase) )

```

This function releases a segment list created by `InternalLoadSeg()` passed in as `seglist`. To release memory, it uses a function pointed to by `a1`. This function expects the memory block to release in register `a1` and its size in register `d0`. Additionally, register `a6` will be populated by a function to the *exec.library*.

This function pointer should be identical to the `FreeMem` function pointer in the `LoadSegFuncs` structure provided to `InternalAllocMem()`, or at least shall be able to release memory allocated by the `AllocMem` function pointer in this structure. Note that the `InternalLoadSeg()` stores the sizes of the allocated memory blocks itself and that `FreeFunc` does not need to retrieve them.

This function is also able to release overlayed binaries, but then closes the file stored in the root node of the overlay tree (see section 11.3) through the `Close()` function of the *dos.library*. It therefore can only release overlayed files that were loaded from regular *file handles* obtained through `Open()`.

This function returns a non-negative result code in case of success, or 0 in case of failure. Currently, the only cause of failure is to pass in a `ZERO` segment list, the function does not check of the result code of `Close()` on the file handle of overlayed files. It therefore neither sets `IoErr()` consistently in case of failure.

## 11.3 Overlays

While regular binary executables are first brought to memory in entity and then brought to execution, overlayed binaries only keep a fraction of the executable code in memory and then load additional code parts as required, potentially releasing other currently unused code parts and thus making more memory available.

Overlays are an extension of the AmigaDOS hunk format that splits the executable into a root node that is loaded initially and stays resident for the lifetime of the program, and one or multiple extension or overlay nodes that are loaded and unloaded on demand. Locating the overlay nodes, loading them to memory and releasing unused nodes is performed by the *overlay manager*, a short piece of program.

AmigaDOS does not provide a ROM-resident overlay manager itself, i.e. the *dos.library* does not provide an overlay manager itself, though it provides services overlay managers may use. Instead, the overlay manager is part of the root node of an overlayed binary, and thus overlay management is fully under control of the application.

However, the Amiga linker *ALink*, the Software Distillery linker *BLink* and the SAS/C linker *SLink* include a standard overlay manager, and this manager and its properties are discussed in greater detail in this section.

### 11.3.1 The Overlay File Format

A binary file making use of overlays consists of several nodes, one root node and several overlayed nodes. Nodes contain multiple segments, defined through `HUNK_CODE`, `HUNK_DATA` or `HUNK_BSS` as in regular (non-overlayed) binary files.

Each node, the root node and all overlayed nodes start with a `HUNK_HEADER` identifying which segments are contained in the node. The root node is terminated by a `HUNK_OVERLAY` on which loading stops; this hunk contains additional data for the purpose of the overlay manager, and therefore the data within this hunk depends on the overlay manager.


Every other overlay node terminates with a `HUNK_BREAK`, and loading stops there as well. This hunk does not contain any data. The overall structure of an overlayed binary therefore looks as follows:

**Table 42: Overlay File Format**

| Hunk Type              | Description  |
|------------------------|--|
| HUNK_HEADER            | Defines segments for the root node                   |
| HUNK_CODE              | Contains the overlay manager and other resident code |
| ...                    | Other hunks, such as relocation information          |
| HUNK_END               | Terminates the previous segment                      |
| HUNK_OVERLAY           | Metadata for the overlay manager, see 11.3.3         |
| do {                   | Repeats over all overlay nodes                       |
| HUNK_HEADER            | Defines the segments in this overlay node            |
| HUNK_CODE or HUNK_DATA | First segment of the overlay node                    |
| ...                    | Other hunks of this overlay node                     |
| HUNK_END               | Terminates the last segment                          |
| HUNK_BREAK             | Terminates the first overlay node, see 11.3.4        |
| } while(!end of file); | This pattern repeats until end of file               |

### 11.3.2 The Hierarchical Overlay Manager

The overlay manager that comes with the standard Amiga linkers *ALink*, *BLink* and *SLink* structures overlay nodes into a tree such as the following:



Only those nodes that form a path from the root to one of the nodes of the tree can be in memory at a time. Thus, for the above example, the root node and nodes *a*, *c* and *e* can be in memory simultaneously, or the root node, and nodes *k* and *m* can be loaded at the same time, but not the nodes *a*, *g* and *h* because they do not form a path from the root to one of the nodes.

Thus, in the above example, if nodes *a* and *f* are in memory, and node *l* is required, the nodes *a* and *f* will be removed from memory, and nodes *k* and *l* are loaded. Even though *k* is not explicitly requested, it needs to be loaded as it is the parent of *l*.

Every node in the overlay tree is identified by two numbers: The depth of the node, which identifies the level within the tree where a node is located. The root node is at level 0, the nodes *a*, *h* and *k* forms level 1 in the above example, nodes *b*, *c*, *f*, *g* and *l* and *m* form level 2, and nodes *d* and *e* are level 3.

The second number is the ordinate number of a node. The ordinate enumerates nodes from left to right within a level, and it starts from 1 in the standard overlay manager. In the above example, *a* is at ordinate 1, *h* at ordinate 2, and *k* at ordinate 3. At level 2, node *b* has ordinate 1, node *c* ordinate 2 and so on.

### 11.3.3 HUNK\_OVERLAY

This hunk terminates the loading process and indicates the end of the main (first) segments. The `HUNK_OVERLAY` contains meta-data — the overlay table — for the overlay manager. This table contains information where symbols within the overlayed segments are located. Section ?? provides more information on overlays. The format of the data within this hunk depends on the overlay manager which shall be included in the first segment of the executable itself as AmigaDOS does not contain a resident overlay manager.

The standard AmigaDOS linkers, `ALink` and `BLink` both include an overlay manager. Each entry in its overlay table describes a symbol that is located in one of the overlay nodes. The format of `HUNK_OVERLAY` reads as follows:

**Table 43: Hunk Overlay Syntax**

| Size   | Code   | Syntax   |
|--|--|--|
|  | <code>HUNK_OVERLAY [0x3f5]</code>                        | Overlay table definition   |
| 32   | $l$  | Size of the overlay table, it is $l + 1$ long-words large.   |
| Format for the standard overlay manager, $l + 1$ long-words. |  |  |
| 32   | $o_d$  | Number of levels in the overlay tree, including the root node  |
|  | <code>for (<math>i = 1; i &lt; o_d; i++</math>) {</code> | For all nodes, excluding the root node   |
| 32   | 0  | Currently loaded ordinate, shall be zero   |
|  | <code>}</code>   | That is, $o_d - 1$ zeros   |
|  | $l -= o_d$   | Count removed long-words   |
|  | $s = 0$  | Start with symbol 0  |
|  | <code>while (<math>l \geq 0</math>) {</code>             | Repeat over the overlay table  |
| 32   | $o_p[s]$   | Absolute file offset of the <code>HUNK_HEADER</code> of the overlay node containing the symbol.            |
| 64   |  | Two reserved long-words.   |
| 32   | $o_l[s]$   | Level of the overlay node containing the symbol, the root level containing the overlay manager is level 0. |
| 32   | $o_n[s]$   | Ordinate of the overlay node, enumerating overlay nodes of the same depth.                                 |
| 32   | $o_h[s]$   | Hunk index of the first hunk within the overlay node.  |
| 32   | $o_s[s]$   | Hunk index of the hunk containing the symbol described by this entry in the overlay node.                  |
| 32   | $o_o[s]$   | Symbol offset within hunk $o_s$  |
|  | $l -= 8$   | Remove 8 long words.   |
|  | $s++$  | Advance to next symbol.  |
|  | <code>}</code>   | End of loop over table   |

Note that the overlay table is  $l + 1$  and not  $l$  long-words large, i.e. a table only defining a single symbol would be indicated by a value of  $l = 7$ . While the payload data of `HUNK_OVERLAY` is always  $l + 1$  long-words large, with  $l$  indicated in the first long-word of the hunk, the format of the subsequent data is specific to the overlay manager used.

Irrespective of the overlay manager used, the AmigaDOS loader injects overlay-specific data into the first segment loaded from disk, that is, into the root-node. The data placed there is also required to release all resources associated to overlays and is expected there by `UnLoadSeg()` and `InternalUnLoadSeg()`.

The first bytes of the root node shall therefore form the following structure:

```
struct OverlayHeader {
    UWORD      oh_Jump[2];    /* Forms a branch to the startup code */
    LONG       oh_Magic;      /* Shall be 0x0000abcd */
    BPTR       oh_FileHandle; /* Filled by the loader with the fh */
    struct OVTab *oh_OVTab;   /* Overlay table from HUNK_OVERLAY */
}
```

```

        BPTR          oh_Segments; /* Array of segment BPTRs          */
        BPTR          oh_GV;      /* standard Global Vector      */
};

```

As said earlier, this structure is expected to be present at the start of the first hunk of the root node. The members `oh_FileHandle` to `oh_GV` are filled in by the AmigaDOS loader, i.e. `LoadSeg()` and related functions, but `oh_Jump` and `oh_Magic` shall be part of the segment itself.

`oh_Jump` form valid 68K opcodes, and shall contain a jump or branch branch around this structure. This is because loaded binaries are executed from the first byte of the first segment loaded. Otherwise, the CPU would run into the data of the structure which likely forms invalid or illegal opcodes. The AmigaDOS Loader itself does not interpret the values here, just expects them to be present.

`oh_Magic` shall contain the “magic” long-word `0xabcd`. This value is neither filled or interpreted by the loader, but nevertheless shall be present. It is, however, checked by `UnLoadSeg()` and used there as an identifier for the `OverlayHeader` structure. If this identifier is not present, `UnLoadSeg()` will not be able to release resources associated to overlays.

`oh_FileHandle` will be filled by the AmigaDOS loader with a *BPTR* to the *FileHandle* from which the root node has been loaded, or with the first argument of `InternalLoadSeg()`. This handle is used by the overload manager to load all subsequent overlay nodes. Also, `UnLoadSeg()` and related functions call `Close()` on the handle stored here as the file needs to stay open for the life time of the loaded program.

`oh_OVTab` is filled by the AmigaDOS loader to a pointer to the payload data of `HUNK_OVERLAY`. The standard overlay manager stores here for every externally referenced symbol in an overlay node a structure that records for each tree level the ordinate of the currently loaded overlay node, and for all externally referenced symbols the position of the symbol within the overlay tree:

```

struct OVTab {
    ULONG ot_TreeDepth; /* Depth of the tree, including the root */
    ULONG ot_LoadedOrd[]; /* The loaded ordinate, indexed by level-1 */
}
struct SymTab {
    ULONG ot_FilePosition; /* File position of HUNK_HEADER of the node */
    ULONG ot_Reserved[2]; /* Not in use */
    ULONG ot_Level; /* Level of the overlay node */
    ULONG ot_Ordinate; /* Ordinate of the overlay node */
    ULONG ot_FirstHunk; /* First segment of the overlay node */
    ULONG ot_SymbolHunk; /* Segment containing the referenced symbol */
    ULONG ot_SymbolOffset; /* Offset of the segment within the segment */
} [] /* Repeats for each symbol */

```

That is, the overlay table starts with the tree depth  $o_d$  and an array of  $o_d - 1$  elements where each element stores the ordinate of the currently loaded overlay node. If an entry in this array is 0, no overlay node at this tree level is loaded, otherwise it is the 1-based ordinate of the node.

The ordinate table is followed by the symbol table. The purpose of this structure is that it allows the overlay manager on a reference to such an external symbol to find and load the overlay node containing the symbol, and then resolve references to it. How exactly it does so is explained in more detail in section ?? . The elements of this structure are already briefly introduced in table 43.

`oh_Segments` is filled by the AmigaDOS loader to a *BPTR* to the segment table of the loaded binary. The size of this table is taken from  $t_{size}$  in the `HUNK_HEADER` of the root node, see table 30. Each element in this array contains a *BPTR* to a segment of the loaded binary, and it is indexed by the segment number, counting from 0 for the first segment of the root node.

When parsing a `HUNK_HEADER`, the array entries  $t_{num}$  to  $t_{max}$  will be populated with the *BPTRs* to the segments allocated of the node described by this hunk, and when unloading an overlay node, the corresponding segments will be unlinked, released and then cleared out.

oh\_GV is, finally, filled with the *Global Vector* of the *dos.library* containing all regular functions in the library, as required by BCPL code. Overlay managers implemented in C or assembler will not make use of it and instead call vectors of the *dos.library* through the *dos.library* base address loaded in register a6.

### 11.3.4 HUNK\_BREAK

This hunk terminates the loading process and indicates the end of an overlay node. The hunk itself does not contain any data.

**Table 44: Hunk Break Syntax**

| Size | Code               | Syntax              |
|------|--------------------|---------------------|
|      | HUNK_BREAK [0x3f6] | Terminate a segment |

### 11.3.5 Loading an Overload Node

The LoadSeg() function is not only able to load the root segments of an overlayed binary, it can also be used for loading an overlayed node and all segments within it. For that, the file pointer shall first be placed with Seek() to the file offset of the HUNK\_HEADER of the overlayed node. This file offset may, for the standard hierarchical overlay manager, be taken from the ot\_FilePosition of the overlay table.

```
seglist = LoadSeg( name ,table, fh)
D0          D1      D2      D3
```

```
BPTR LoadSeg(STRPTR ,BPTR, BPTR)
```

For overlayed node loading, the first argument name shall be NULL, which is used as an indicator to this function to interpret two additional (usually hidden) arguments.

table is a BPTR to the segment table, and may be taken from oh\_Segments. It contains BPTRs to all allocated segments, see section 11.3.3.

fh is a BPTR to the FileHandle from which the overlay node is to be loaded. This handle may be taken from oh\_FileHandle, see section 11.3.3.

While this function allocates and loads the segments in the overlayed node, it does not attempt to release already allocated segments populating the same entries in the segment table; it is instead up to the overlay manager to clean up the segment table upfront, see 11.3.7. The information which segments will be populated by an overlay node may be taken from the ot\_FirstHunk member of the overlay table. Due to the tree structure imposed by the hierarchical overlay manager, it has to release all segments from ot\_FirstHunk onwards up to the end of the table, unlink the segments contained therein, and then load another overlay node through LoadSeg().

Note that this function populates the same offset in the *dos.library* as the regular LoadSeg() function; the function distinguishes loading regular binaries through a file name from loading overlay nodes by the first argument.

As the regular LoadSeg() call, this function returns the BPTR to the first segment loaded on success, links all loaded segments together, populates the segment table, and then sets IoErr() to 0. On error, it returns ZERO and installs an error code in IoErr().

### 11.3.6 Loading an Overlay Node through Call-Back Functions

The InternalLoadSeg() function can also load an overlay node.

```
seglist = InternalLoadSeg(fh,table,funcs)
```

```
D0                                D0  A0  A1
```

```
BPTR InternalLoadSeg(BPTR,BPTR,struct LoadSegFuncs *)
```

The `fh` argument is an opaque file handle that is suitable for the `ReadFunc()` provided by the `funcs` structure. The corresponding file pointer shall first be placed to the file offset of the `HUNK_HEADER` of the overlayed node, e.g. by a functionality similar to `Seek()` for regular *FileHandles*. This file offset may, for the standard hierarchical overlay manager, be taken from the `ot_FilePosition` within the overlay table.

The `table` shall be the *BPTR* to the segment table; this may be taken from `oh_Segments`. This argument determines whether a regular binary load is requested, or an overlay node is to be loaded. In the latter case, this argument is non-ZERO.

Like `LoadSeg()`, this function does not release segments in populated entries in the segment list, it is up to the overlay manager to unload these segments. The information which entries of the segment table will be populated by an overlay node may be taken from the `ot_FirstHunk` member of the overlay table, see also 11.3.5.

The `funcs` argument points to a `LoadSegFuncs` structure as defined in section 11.2.3 and contains functions for reading data and allocating and releasing memory.

This function does not set `IoErr()` consistently, unless the functions in the `LoadSegFuncs` structure do. The function returns the segment of the first segment of the overlay node on success, or ZERO on error.

### 11.3.7 Unloading Overlay Nodes

Unloading overlay nodes (and *not* the root node) of an overlayed binary requires some manipulation of the segment table as the *dos.library* does not provide a function for such operation. This algorithm is part of the overlay manager, but its implementation within the standard hierarchical overlay manager documented here for completeness. Other custom overlay managers perform potentially different algorithms.

First, it finds the previous segment upfront the segment to be unloaded, and cleans there the `NextSegment` pointer to unlink all following segments. Then these following segments are released through `FreeVec()` or, in case a custom allocator was provided for `InternalLoadSeg()`, whatever memory release function is appropriate.

The following sample code releases the overlay node starting at segment  $i > 0$  from a segment table of an overlay header:

```
void UnloadOverlayNode(struct OverlayHeader *oh,ULONG i)
{
    BPTR *segtbl = (BPTR *)BADDR(oh->oh_Segments);
    BPTR *segment = (BPTR *)BADDR(segtbl[i - 1]);
    BPTR next;

    /* Release the linkage from the last loaded to
    ** the first segment to release */
    *segment = NULL;

    do {
        /* Get the segment to release */
        if (segment = (BPTR *)BADDR(segtbl[i++])) {
            next = *segment;
            FreeVec(segment);
        }
    } while (next);
}
```



```

    } else break;
    /* Repeat until the last segment */
    } while(next);
}

```

Note that a previous segment always exists because the root node populates at least entry 0 of the segment table. The above loop makes use of the fact that the first long-word of a segment is a *BPTR* to the next segment, and this linkage is *ZERO* for the final node.

If a custom memory allocator has been used for loading overlay nodes through `InternalLoadSeg()`, the `FreeVec()` in the above function is replaced by the corresponding memory release function.

### 11.3.8 Unloading Overlay Binaries

To unload the root node, and thus unload the entire program including all overlay nodes, `UnLoadSeg()` on the first segment of the root node is sufficient if neither custom I/O nor a custom memory allocator has been used to load the binary, independent on which overlay manager has been used. `UnLoadSeg()` will detect the overlay manager from the magic value in `oh_Magic` and will then not only release the segments, but also close the overlay file handle and release the segment table.

If `InternalLoadSeg()` has been used for loading the root node through custom I/O functions or with a custom memory allocator, `InternalUnLoadSeg()` shall be used instead to release the root node. Unfortunately, it *always* uses `Close()` on `oh_FileHandle`, even if `oh_FileHandle` does not correspond to a *FileHandle* as returned by `Open()`, e.g. because `ReadFunc()` upon loading the overlay program pointed to a custom I/O function. The best strategy in this case is probably to close `oh_FileHandle` manually upfront with whatever method is appropriate, then zero it out manually and then finally call into `InternalUnLoadSeg()` to perform all the necessary cleanup steps. This strategy works because `Close()` on a *ZERO* file handle performs no operation and is legit.

### 11.3.9 Internal Working of the Overlay Manager

Several versions of the hierarchical overlay manager exist. The version described here stems from the SAS/C *SLink* utility and is designed for the *registerized parameters* configuration within which some function arguments are passed in CPU registers. Earlier versions require stack-based parameter passing.

When binding objects together to an overlay binary together, the linker checks whether a reference to a symbol crosses a boundary of overlay nodes. References that go to a parent node or the node itself can be resolved by the linker by creating a relocation entry in a `HUNK_RELOC32` hunk as it can assume that the corresponding segment is already loaded.

References to symbols within child nodes receive each a unique integer identifier, and an entry in the overlay table in `HUNK_OVERLAY` at the index given by the identifier. The actual call to a function in a child node is then replaced to call into a trampoline function that looks as follows:

```

@symX:
    jsr @ovlyMgr
    dc.w symbX

```

where `@ovlyMgr` is the entry point of the overlay manager and `symbX` is the identifier of the referenced symbol. The overlay manager reads the return PC which points to the identifier, and from the identifier finds the entry in the symbol table.

The symbol table contains both the ordinate and the level of the symbol with which the overlay manager is able to check whether the node containing the symbol is currently loaded. If this is not the case, it needs to unload the currently loaded node at this level and all its children, and then progresses to loading the required node from the file offset in the symbol table, and then progresses to updating the overlay table.

If the overlay node containing the symbol is already loaded, or just has been loaded, the symbol address is computed from the offset in the symbol table and the address of the segment containing the symbol from the segment table, and injected into the return address that contained a pointer to the symbol identifier. Thus, when returning from the overlay manager, the code will continue to execute from the target symbol. Other versions of the overlay manager use a trampoline function that loads register d0 with the symbol identifier and thus require stack-based function calls.

Regardless of the version of the overlay manager, only symbols corresponding to function can be resolved as the overlay manager must be called to resolve a symbol. In particular, data cannot be referenced across overlay nodes — instead, an accessor function may be used that returns the object to be accessed.

The following code provides an overlay manager for register-based calls:

```

        xdef      @ovlyMgr
;*****
;** Offsets in the overlay-table          **
;*****
        rsreset
ot_FilePosition:      rs.l 1          ;File position
ot_reserved:          rs.l 2          ;for whatever
ot_OverlayLevel:      rs.l 1          ;Overlay-Level
ot_Ordinate:          rs.l 1          ;Overlay-Ordinate
ot_InitialHunk:        rs.l 1          ;Initial hunk for loading
ot_SymbolHunk:         rs.l 1          ;Hunk containing symbol
ot_SymbolOffset:       rs.l 1          ;Offset of symbol
ot_len:                rs.b 0

;*****
;** Other stuff                          **
;*****
MajikLibWord          =      23456

        section  NTRYHUNK, CODE
;*****
;** Manager starts here                  **
;*****
Start:
        bra.w NextModule              ;Jump to the next segment...

;* This next word serves to identify the overlay
;* supervisor to 'unloader', i.e. UnLoadSeg()

        dc.l      $ABCD                ;Magic longword for UnLoadSeg

;* The next four LWs are filled by the loader (LoadSeg())
ol_FileHandle:        dc.l 0            ;Overlay file handle (points to me)
ol_OverlayTab:         dc.l 0            ;Overlay table as found in the overlay hunk
ol_HunkTable:          dc.l 0            ;BPTR to Overlay hunk table
ol_GlobVec:            dc.l 0            ;BPTR to global vector (what for ?)

                        dc.l MajikLibWord ;Majik library word as identifier
                        dc.b 7, "Overlay" ;Majik identifier

```

```

; * the following data is specific to this manger

ol_SysBase:      dc.l 0                      ;additional pointer
ol_DOSBase:      dc.l 0                      ;to libraries

                dc.b "THOR Overlay Mananger 1.0",0      ;another ID

@ovlyMgr:        ;Entry-points
                saveregs d0-d3/a0-a4/a6      ;Saveback register

                moveq #0,d0
                move.l 10*4(a7),a0
                move.w (a0),d0                ;get the overlay reference ID

                move.l ol_OverlayTab(pc),a3    ;get pointer to overlay table
                move.l a3,a4                  ;to a4
                add.l (a3),d0                 ;add length
                lsl.l #2,d0                   ;get offset
                add.l d0,a3                   ;address of overlay entry
                move.l ot_OverlayLevel(a3),d0 ;get overlay
                lsl.l #2,d0
                adda.l d0,a4
                move.l ot_Ordinate(a3),d0     ;get required ordinate level
                cmp.l (a4),d0                 ;compare with current ordinate level
                beq.s .gotsegment              ;not correct level

                ;clear all other entries behind this
                move.l d0,(a4)+                ;fill with new overlay entries

                moveq #0,d1
                do                             ;macros in action! ;- )
                    tst.l (a4)                 ;terminate, if end of table found
                    break.s eq
                    move.l d1,(a4)+            ;clear this
                loop.s

                move.l ot_InitialHunk(a3),d0   ;first hunk number to load
                add.l ol_HunkTable(pc),d0      ;plus BPTR of hunk table
                lsl.l #2,d0                    ;address of entry in hunk table
                move.l d0,a4
                move.l -4(a4),d0               ;get previous hunk
                beq.s .noprevious
                lsl.l #2,d0
                move.l d0,a2
                move.l d1,(a2)                 ;unlink fields before loading

                ;now free all hunks

                move.l ol_SysBase(pc),a6

                do
                    move.l (a4)+,d0            ;next hunk ?

```

```

        break.s eq
        lsl.l #2,d0
        move.l d0,a1
        move.l -(a1),d0
        jsr FreeMem(a6)
loop.s
        ;->a1
        ;get length
        ;free this hunk
        ;and now the next

.retry:
        move.l ol_DOSBase(pc),a6
        move.l ol_FileHandle(pc),d1
        move.l ot_FilePosition(a3),d2
        moveq #-1,d3
        jsr Seek(a6)
        tst.l d0
        bmi.s .loaderror

        ;get our stream
        ;get file position
        ;relative to beginning of file
        ;seek to this position
        ;found something ?
        ;what to do on failure ?

        ;now call the loader
        move.l ol_HunkTable(pc),d2
        moveq #0,d1
        move.l ol_FileHandle(pc),d3
        jsr LoadSeg(a6)
        tst.l d0
        beq.s .loaderror
        move.l d0,(a2)

        ;hunk table
        ;no file (is overlay)
        ;filehandle
        ;load this stuff
        ;found
        ;add new chain

        ;found this stuff

.gotsegment:
        move.l ot_SymbolHunk(a3),d0
        add.l ol_HunkTable(pc),d0
        lsl.l #2,d0
        move.l d0,a4
        move.l (a4),d0
        lsl.l #2,d0
        add.l ot_SymbolOffset(a3),d0

        ;get hunk # containing symbol
        ;get APTR to hunk
        ;BPTR to hunk
        ;Offset

        move.l d0,10*4(a7)
        ;Set RETURN-Address

        loadregs
        rts

;*****
;** Go here if we find an error
;*****
.loaderror:
        saveregs d7/a5
        move.l ol_SysBase(pc),a6
        move.l #$0700000C,d7
        move.l $114(a6),a5
        jsr Alert(a6)
        loadregs
        bra.s .retry

        ;Post alert
        ;Retry or die

```

```

.noprevious:
    move.l ol_SysBase(pc),a6
    move.l #$8700000C,d7          ;dead end !
    move.l $114(a6),a5
    jsr Alert(a6)                ;Post alert
    bra.s .noprevious

;*****
;** NextModule                      **
;** Open stuff absolutely necessary and **
;** continue with main program code    **
;*****
NextModule:
                                ;why safe registers ?
    move.l a0,a2
    move.l d0,d2                ;keep arguments
    lea ol_SysBase(pc),a3
    move.l ExecBase,a6
    move.l a6,(a3)              ;fill in Sysbase
    lea DOSName(pc),a1          ;get name of DOS
    moveq #33,d0                ;at least 1.2 MUST be used
    jsr OpenLibrary(a6)
    move.l d0,4(a3)             ;Save back DOS base for loader
    beq.s .nodosexit           ;exit if no DOS here

    move.l d0,a6
    move.l Start-4(pc),a0        ;Get BPTR of next hunk
    adda.l a0,a0
    adda.l a0,a0
    exg.l a0,a2                ;move to a2
    move.l d2,d0                ;restore argument
    jsr 4(a2)                   ;jump in
    move.l d0,d2                ;Save return code

    move.l ol_SysBase(pc),a6
    move.l ol_DOSBase(pc),a1
    jsr CloseLibrary(a6)        ;Close the lib

    move.l d2,d0                ;Returncode in d0
    rts

.nodosexit:
    move.l #$07038007,d7        ;DOS didn't open
    move.l $114(a6),a5
    jsr Alert(a6)
    moveq #30,d0                ;Something went really wrong !
    rts

DOSName:      dc.b "dos.library",0

```

---

## 11.4 Structures within Hunks

While the AmigaDOS loader, i.e. `LoadSeg()` and related functions, do not care about the contents of the segments it loaded, some other components of AmigaDOS do actually analyze their contents.

### 11.4.1 The Version Cookie

The `Version` command scans a ROM-resident modules or all segments of a binary for the character sequence `$VER:` and if such a sequence is found, the string following is scanned. The syntax of the string consists of the following elements:

- The version cookie `$VER:`
- one or multiple blank spaces
- a program name, which is output by the `Version` command
- a decimal number, representing the *version* of the program
- a single dot (`“.”`)
- a decimal number, representing the *revision* of the program
- one or multiple blank spaces
- an opening bracket (`“(”`)
- a decimal number, representing the day of the month of the revision
- a single dot (`“.”`)
- a decimal number, representing the month of the revision
- a single dot (`“.”`)
- a decimal number, representing the year of the revision
- a closing bracket (`“)”`)
- an optional comment that is only output if the `FULL` option of the `Version` is given.

If the number representing the year is below 1900, the `Version` command assumes a two-digit year and either adds 200 if the year is below 78, or 1900 otherwise. The command then re-formats the date according to the currently active locale and prints it to the console, along with the program name and, optionally, the comment string.

An example for the version cookie is

```
const char version[] = "$VER: RKRM-Dos 45.3 (12.9.2023) (c) THOR";
```

Note that the date follows the convention date of the month, month and year, here September 12, 2023. The version in this example is 45, the version is 3. The string behind the date is a comment and usually not printed by the `Version` command.

---

### 11.4.2 The Stack Cookie

The workbench, the shell, and also `GetDeviceProc()` when loading *handlers* scan the loaded binary for the string sequence `$STACK:`. If this string sequence is found, AmigaDOS attempts to read a following decimal number, and interprets this as stack size in bytes.

The stack of the program is then, potentially increased to the provided size. Note that AmigaDOS also scans alternative sources for a stack size: The `Stack` setting in the icon information window of the workbench, the `Stack` command of the shell, or the `STACKSIZE` entry in the mount list. The stack size indicated by the above stack cookie does not override these settings, it can only *increase* the stack size. This allows program authors to ensure that the stack of their program has a necessary minimal size, though still allows users to increase it if necessary.

An example for the stack cookie is

```
const char stack[] = "$STACK: 8192";
```

This ensures that the stack size of the program is at least 8192 bytes.

The *dos.library* provides with the `ScanStackToken()` an optimized function to quickly scan segments for the stack cookie and potentially adjust a default stacksize upwards to the value found in the stack cookie.

```
stack = ScanStackToken(segment, defaultstack)
D0                      D1          D2

LONG ScanStackToken(BPTR segment, LONG defaultstack)
```

This function scans the segment list starting at `segment` for a stack cookie, potentially adjusting the `defaultstack` size in bytes passed in. If a stack cookie is found, and the minimal stack size it finds is larger than the default stack, the stack size found in the stack cookie is returned in `stack`. If no stack cookie is found, or the value in the stack cookie is smaller than the `defaultstack` size, the default size is returned.

The `segment` is a *BPTR* to a singly linked list of segments, e.g. as returned by `LoadSeg()` function.

### 11.4.3 Runtime binding of BCPL programs

BPCL programs depend on a *Global Vector* that includes function entries and data available to all its modules. AmigaDOS includes a runtime binder functionality that creates the *Global Vector* from data found in the segments of the loaded binary and the *dos.library Global Vector*.

Even though this mechanism is deprecated and AmigaDOS has long been ported to C and assembler, some components still depend on this legacy mechanism, namely all *handlers* and *file systems* mounted with the `GLOBVEC = 0` or `GLOBVEC = -2` entry in the mount list. While newer *handlers* should not depend on this mechanism anymore, the `Port-Handler` mount entry is created in the Kickstart ROM as BCPL handler, beyond control of the user. The same goes for the `Shell`, which is also initiated as BCPL process.

If the above components — the `Port-Handler` or the *Shell* — are attempted to be customized, implementors need to be aware that these processes are not started from the first byte of the first segment, but from the *Global Vector* entry #1, which contains the address of the `START` function from which the process is run. All other entries of the vector are of no concern, and should not be used anymore.

The *Runtime Binder* of AmigaOs, initiated only for BCPL handlers and BCPL processes such as the *Shell*, now scans the segments of such programs for information on how to populate the *Global Vector*.

The *first long-word* of the segment, usually the entry point of the process, contains the long-word offset from the start of the process to the start of the *Global Vector* initialization data. This initialization data is

*scanned backwards* from the given offset towards lower addresses, starting with the long-word before the offset.

The first long-word of the initialization data is the required size of the *Global Vector* the program requires. This value is only used to check the following initializers for validity. The standard system global vector currently requires 150 entries, which is a safe choice.

All following entries consist of pairs of long-words, scanned again towards smaller addresses, where each pair defines one entry in the global vector. The first (higher address) long-word is the offset of the function which will populate the *Global Vector*, the second (lower) address is the index of the *Global Vector* entry. An offset of 0 terminates the list.

The following assembler stub may be used as initial segment of an (otherwise C-based) handler that instructs the *Runtime Binder* to populate the *START* vector, and then calls into the @main function. BCPL unfortunately also uses a custom call syntax, register a6 is the address of the BCPL return code which cleans up the BCPL stack frame and returns to the caller.

```
SECTION text,code

XREF    _main          ; handler or shell main

G_GLOBMAX EQU    150      ; size of GV
G_START  EQU    1        ; BCPL START functions
G_CLISTART EQU    133     ; shell startup

CodeHeader: DC.L    (CodeEnd-CodeHeader)/4

*
*      C Startup function, called for GlobVec=-1 or -3
*      see text below why this works
CStart:   sub.l    a0,a0      ; no startup message
          bsr.w    _main      ; need to GetMsg() in main
          rts

          CNOP      0,4

*
*      BCPL startup function, called for GlobVec=0 or -2
BCPLStart: movem.l  a0-a6,-(a7) ; save for BCPL use
          lsl.l    #2,d1      ; get startup packet
          move.l    d1,a0      ; move to a0
          bsr.w    _main      ; get the ball rolling
          movem.l  (a7)+,a0-a6 ; restore everyone
          jmp      (a6)        ; BCPL-style return

BCPLTable: CNOP      0,4

          DC.L      0          ; End of global list
          DC.L      G_CLISTART,BCPLStart-CodeHeader ;for the shell
          DC.L      G_START,BCPLStart-CodeHeader
          DC.L      G_GLOBMAX  ; max global used (default)

CodeEnd:
```

Note that there are other differences for BCPL handlers the `main()` function of the handler needs to take care of, see also section ?? . BCPL handlers do not receive their startup message in the process *MsgPort*, but



rather receive it as first BCPL argument in register d1. It is here converted to a C-style pointer and provided as first argument to the main function, assuming the SAS/C registerized parameters ABI.

The `CStart` label is not called at all if the handler is mounted with `GLOBVEC=0` or `GLOBVEC=-2`, and thus would be, in this example, not required. It is included here to demonstrate another technique, namely *dual use* handlers that can be mounted both as C and as BCPL handlers.

The above startup code also allows `GLOBVEC=-1` in the mount list. In this case, the code *is* started from the first byte, which is, actually, the long-word offset to the BCPL initializer. In this particular case, it also assembles to a harmless `ORI` instruction, provided the offset to the end of the code is short enough, i.e. below 64K. It is therefore harmless. As the calling syntax is different, the main function is now called with a `NULL` argument, and then needs to wait for the startup package itself, see again section ??.

For the *Shell*, in particular, a second entry in the *Global Vector* shall be populated, namely the entry `G_CLISTART` at offset #133. It may point to the same entry code, more on this in section ??. As this entry is not used for handler startup, it does not hurt to include it in the BCPL initializer in either case, and thus the above code may be used as universal “BCPL kludge” for both the shell and legacy handlers that depend on BCPL startup.

## 11.5 Object File Format

Object files are intermediate output files of a compiler or assembler, generated from one translation unit, i.e. typically one source code file. Such files can still contain references to symbols that could not be resolved within the translation unit because the corresponding symbol is defined in another unit. The linker then combines multiple object codes, resolving all unreferenced symbol, and generates an executable binary file as output.

The overall structure of an object file is depicted in table 45:

**Table 45: Object File Format**

| Size | Code   | Syntax   |
|------|--|--|
| ?    | <code>HUNK_UNIT</code>   | Defines the start of a translation unit, see 11.5.1  |
|      | <code>do {</code>  | Multiple segments follow                             |
| ?    | <code>HUNK_NAME</code>   | Name of the hunk, defines hunks to merge, see 11.1.8 |
| 2    | <code>m<sub>t</sub></code>   | Read the memory type of the next hunk                |
| 30   | <code>h<sub>t</sub></code>   | Read the next hunk type                              |
|      | <code>if (h<sub>t</sub> == HUNK_CODE)<br/>parse_CODE</code>                          | Code and constant data, see 11.1.2                   |
|      | <code>else if (h<sub>t</sub> == HUNK_DATA)<br/>parse_DATA</code>                     | Data, see 11.1.3                                     |
|      | <code>else if (h<sub>t</sub> == HUNK_BSS)<br/>parse_BSS</code>                       | Zero-initialized data, see 11.1.4                    |
|      | <code>else if (m<sub>t</sub> != 0)<br/>ERROR_BAD_HUNK</code>                         | Upper bits shall be 0 for all other hunks            |
|      | <code>else do {</code>   | Loop over auxiliary information                      |
|      | <code>if (h<sub>t</sub> == HUNK_RELOC32)<br/>parse_RELOC32</code>                    | 32-bit relocation, see 11.1.5                        |
|      | <code>else if (h<sub>t</sub> ==<br/>HUNK_RELOC32SHORT)<br/>parse_RELOC32SHORT</code> | 32-bit relocation, see 11.1.6                        |

|    |  |   |
|----|--|---|
|    | else if ( $h_t ==$<br>HUNK_RELRELOC32)<br>parse_RELRELOC32 | 32-bit PC-relative relocation, see 11.1.7       |
|    | else if ( $h_t ==$<br>HUNK_RELOC16) parse_RELOC16          | 16-bit PC-relative relocation, see 11.5.2       |
|    | else if ( $h_t ==$<br>HUNK_RELOC8) parse_RELOC8            | 8-bit PC-relative relocation, see 11.5.2        |
|    | else if ( $h_t ==$<br>HUNK_DRELOC32) parse_RELOC32         | 32-bit base-relative relocation, see 11.5.4     |
|    | else if ( $h_t ==$<br>HUNK_DRELOC16) parse_RELOC16         | 16-bit base-relative relocation, see 11.5.5     |
|    | else if ( $h_t ==$<br>HUNK_DRELOC8) parse_RELOC8           | 8-bit base-relative relocation, see 11.5.6      |
|    | else if ( $h_t ==$ HUNK_EXT)<br>parse_EXT                  | External symbol definition, see 11.5.7          |
|    | else if ( $h_t ==$<br>HUNK_SYMBOL) parse_SYMBOL            | Symbol definition, see 11.1.9                   |
|    | else if ( $h_t ==$<br>HUNK_DEBUG) parse_DEBUG              | Debug information, see 11.1.10                  |
|    | else if ( $h_t ==$ HUNK_END)<br>break                      | abort this segment                              |
|    | else ERROR_INVALID_HUNK                                    | an error  |
| 32 | $h_t$  | Read next hunk type                             |
|    | } while(true)  | Repeated until HUNK_END                         |
|    | } while(!EOF)  | Repeated with the next hunk until the file ends |

Since there is no HUNK\_HEADER in object files, the memory attributes for the hunk are instead stored in the topmost two bits of the hunk type itself. Unlike in HUNK\_HEADER, there is no documented way how to indicate a memory type beyond MEMF\_CHIP and MEMF\_FAST. As the interpretation of object files is up to the linker, a suggested implementation strategy is to set the topmost two bits and store the memory type in the following long-word, similar to how HUNK\_HEADER expects it.

### 11.5.1 HUNK\_UNIT

This hunk identifies a translation unit and provides it a unique name. This hunk shall be the first hunk of an object file. A translation unit typically refers to one source code file that has been processed by the compiler or assembler. Typically, the name of the unit is ignored by linkers.

The structure of this hunk is as follows:

**Table 46: Hunk Unit Syntax**

| Size   | Code              | Syntax                                |
|--------|-------------------|---------------------------------------|
|        | HUNK_UNIT [0x3e7] | A hunk identifying a translation unit |
| 32     | 1                 | Size of the name in long-words        |
| 32 × 1 | $h_n$             | Unit name                             |

The size of the name is not given in characters, but in 32-bit units. The name is possibly zero-padded to the next 32-bit boundary to fill an integer number of long-words. If the name fills an entire number of long-words already, it is *not* zero-terminated.

Even though not enforced by the format, linkers can limit the size of the unit.

### 11.5.2 HUNK\_RELOC16

This hunk defines relocation information of one hunk into another hunk, and its format is identical to HUNK\_RELRELOC32, see section 11.1.7 and table 36.. Relocation offsets are therefore 32 bits long, though the elements to relocate at offset  $r_o$  within the segment are only 16 bits in size, and refer to PC-relative addressing modes, including PC-relative 16-bit wide branches.

**Table 47: Hunk Reloc16 Syntax**

| Size | Code                 | Syntax                                    |
|------|----------------------|---|
|      | HUNK_RELOC16 [0x3ed] | 16-bit PC-relative relocation information |
|      | ...                  | See table 36                              |

This restricts possible displacements to 16 bits, and thus the segment containing the 16-bit value to be relocated and the segment the hunk is relative to shall be linked together to form a single segment in the final output. In the notation of section 36, the segments  $i$  and  $j$  shall thus be merged. To make this happen, their names as provided by HUNK\_NAME shall be identical; alternatively the linker shall be configured to the small data or small code model that forcefully merges hunks of the same type.

However, it may still happen that the joined segment generated by merging two or more segments together is too long to allow 16-bit displacements. In such a case, the relocation can obviously not be performed. Then linkers either abort with a failure, or generate an *automatic link vector*. The PC-relative branch or jump to an out-of-range target symbol is then replaced by the linker with a branch or jump to an intermediate “automatic” vector that performs a 32-bit absolute jump to the intended target.

While such *automatic link vectors* or short *ALVs* solve the problem of changing the program flow by 16-bit displacements over distances exceeding 16-bit, *ALVs* do not work correctly for data that is addressed by 16-bit PC relative modes. Instead of referencing the intended data, the executing code would then see the *ALV* as data.

Thus, authors of compilers or assemblers should disallow data references across translation unit boundaries with 16-bit PC-relative addressing modes as those can trigger linkers to incorrectly generate *ALVs*. Linkers should also generate a warning when creating *ALVs*.

### 11.5.3 HUNK\_RELOC8

This hunk defines relocation information of one hunk into another hunk, and its format is identical to HUNK\_RELRELOC32, see section 11.1.7 and table 36.. Relocation offsets are therefore 32 bits long, though the elements to relocate at offset  $r_o$  within the current segment are only 8 bits in size, and thus refer to short branches.

The same restrictions as for HUNK\_RELOC16 applies, i.e. the hunk within which the relocation offset is to be adjusted and the target hunk shall be merged to a single hunk as the AmigaDOS loader cannot resolve 8-bit relocations. This can be either arranged by giving the two hunks the same name, or by configuring the linker to the small code or small data model, depending on the type of the hunk. This will instruct the linker to merge hunks of the same type.

**Table 48: Hunk Reloc8 Syntax**

| Size | Code                | Syntax                                   |
|------|---------------------|--|
|      | HUNK_RELOC8 [0x3ee] | 8-bit PC-relative relocation information |
|      | ...                 | See table 36                             |

As for HUNK\_RELOC16, the linker can generate *ALVs* in case the target offset is not reachable with an 8-bit offset. However, as the possible range for displacement is quite short, it is quite likely that the generated *ALV* itself is not reachable, and thus relocation during the linking phase is not possible at all. Thus, short branches between translation units should be avoided.

Otherwise, the same precautions as for HUNK\_RELOC16 should be taken, i.e. short displacements to data over translation unit boundaries should be avoided as proper linkage cannot be ensured.

#### 11.5.4 HUNK\_DRELOC32

This hunk defines relocation of 32-bit data elements within a hunk that is addressed relative to a base register. The name of this hunk shall be `__MERGED`, indicating that the hunk contains data and zero-initialized elements in the *small data model*.

The format of this hunk is identical to HUNK\_RELOC32, see section 11.1.5 and table 34, where each 32-bit wide relocation offset  $r_o$  points to a long-word within the preceeding data or BSS hunk. The long-word at this offset is then adjusted by the position of the first byte of this hunk relative to the start of the target `__MERGED` hunk into which this hunk is merged; in some cases, linkers can include an additional adjustment, see the next paragraph for details.

**Table 49: Hunk DReloc32 Syntax**

| Size | Code                  | Syntax                                      |
|------|-----------------------|---|
|      | HUNK_DRELOC32 [0x3f7] | 32-bit base-relative relocation information |
|      | ...                   | See table 34                                |

The hunks named `__MERGED` are typically generated by comilers or assemblers when implementing the *small data model* within which all non-static objects are addressed relative to a base register. Typically, register `a4` is used for this purpose, and it is loaded by the compiler startup code to point either to the start of the `__MERGED` hunk, or 32K into the hunk such that both negative and positive offsets relative to `a4` can be used. In the latter case, linkers need to subtract an additional 32K displacement from the  $r_o$  offsets when performing relocation. The name *small data model* stems for the limitation to 64K of data as the 68000 uses only 16-bit for base-relative addressing.

#### 11.5.5 HUNK\_DRELOC16

This hunk defines relocation of 16-bit data elements within a hunk that is addressed relative to a base register, i.e. `__MERGED` hunks in the *small data memory model*.

The format of this hunk is identical to HUNK\_RELOC32, see section 11.1.5 and table 34, where each 32-bit wide relocation offset  $r_o$  points to an unsigned 16-bit word within the preceeding data or BSS segment. The word at this offset is then adjusted by the position of the first byte of this hunk relative to the start of the `__MERGED` hunk into which this hunk is merged.

**Table 50: Hunk DReloc16 Syntax**

| Size | Code                  | Syntax                                      |
|------|-----------------------|---|
|      | HUNK_DRELOC16 [0x3f8] | 16-bit base-relative relocation information |
|      | ...                   | See table 34                                |

Similar to the comments made in section 11.5.4, this hunk is typically used to resolve symbols that are reached relative through a base register, e.g `a4`. As base-relative addressing is restricted to 16-bit displacements for the 68000, linkers typically adjust the base register to point 32K into the `__MERGED` hunk if this hunk exceeds 32K in size. In such a case, they need to include an additional negative offset of -32K in  $r_0$  when performing relocation.

#### 11.5.6 HUNK\_DRELOC8

This hunk defines relocation of 8-bit data elements within a hunk that is addressed relative to a base register, i.e. `__MERGED` hunks in the *small data memory model*.

The format of this hunk is identical to HUNK\_RELOC32, see section 11.1.5 and table 34, where each 32-bit wide relocation offset  $r_o$  points to a byte within the preceeding data or BSS hunk. The byte at this offset is then adjusted by the position of the first byte of this hunk relative to the start of the `__MERGED` hunk into which this hunk is merged.

**Table 51: Hunk DReloc8 Syntax**

| Size | Code                 | Syntax                                     |
|------|----------------------|--|
|      | HUNK_DRELOC8 [0x3f9] | 8-bit base-relative relocation information |
|      | ...                  | See table 34                               |

### 11.5.7 HUNK\_EXT

This hunk defines symbol names and corresponding symbol offsets or values within the currently loaded segment. It is quite similar to HUNK\_SYMBOL except that it not only includes symbol definitions, but also symbol references. The linker uses this hunk to resolve symbols with external linkage.

The syntax of this hunk reads as follows:

**Table 52: Hunk EXT Syntax**

| Size            | Code                                  | Syntax   |
|-----------------|---------------------------------------|--|
|                 | HUNK_EXT [0x3ef]                      | A hunk assigning symbols to positions within a segment |
|                 | do {                                  | Repeat ...   |
| 8               | $s_t$                                 | Symbol type  |
| 24              | $s_l$                                 | Symbol length in long-words                            |
|                 | if ( $s_l == 0$ ) break               | Terminate the hunk                                     |
| $32 \times s_l$ | $s_n$                                 | Symbol name, potentially zero-padded                   |
|                 | if ( $s_t < 0x80$ ) {                 | Symbol definition?                                     |
| 32              | $s_v$                                 | Symbol value   |
|                 | } else {                              | Symbol reference                                       |
|                 | if ( $s_t == 0x82$    $s_t == 0x89$ ) | A common block?  |
| 32              | $s_c$                                 | Size of the common block in bytes                      |
|                 | }                                     | End of common block                                    |
| 32              | $s_n$                                 | Number of references of this symbol                    |
|                 | while ( $--s_n \geq 0$ ) {            | Repeat over the references                             |
| 32              | $s_o[s_n]$                            | Offset into the hunk of the reference                  |
|                 | }                                     | End of loop over symbols                               |
|                 | } while(true)                         | until zero-sized symbol                                |

The length of the symbol name is encoded in long-words, not in characters. If it does not fill an integer number of long-words, it is zero-padded; the name is not zero-terminated if it does fill an integer number of long-words, though.

The symbol type  $s_t$  defines the nature of the symbol. The symbol types are defined in `dos/doshunks.h` and shared with the HUNK\_SYMBOL hunk, see section 11.1.9.

Entries of a symbol type with  $s_t < 0x80$  are symbol definitions, the symbol value is defined by  $s_v$ . See table 53 for possible types of symbol definitions.

The next table includes symbol types that identify symbol references, i.e. they are referenced within a segment of an object file, though not defined there. These types can clearly not be contained within an executable binary, but they may appear within an object file and are then resolved by corresponding symbol definitions from the above table by the linker:

**Table 53: Symbol types in HUNK\_EXT**

|               |        |   |
|---------------|--------|---|
| EXT_REF32     | [0x81] | Reference to a 32-bit symbol that is resolved by a corresponding EXT_ABS to an absolute value or by a EXT_DEF definition to a relocation information to this or another segment.  |
| EXT_COMMON    | [0x82] | Reference to a 32-bit symbol that may be resolved by a EXT_ABS or EXT_DEF definition, but if no such definition is found, a BSS hunk of the maximal size of all references to the symbol is created by the linker. Thus, this type generates a zero-initialized object if no definition is found. |
| EXT_REF16     | [0x83] | Reference to a 16-bit PC relative offset within the same segment.   |
| EXT_REF8      | [0x84] | Reference to a 8-bit PC relative offset within the same segment.  |
| EXT_DREF32    | [0x85] | 32-bit reference relative to a base register (typically a4), resolved by the linker through an entry in a HUNK_DRELOC32 hunk.   |
| EXT_DREF16    | [0x86] | 16-bit reference relative to a base register, resolved by the linker through an entry in a HUNK_DRELOC16 hunk.  |
| EXT_DREF8     | [0x87] | 8-bit reference relative to a base register, resolved by the linker through an entry in a HUNK_DRELOC8 hunk.  |
| EXT_RELREF32  | [0x88] | 32-bit PC-relative reference for 32-bit address, this will be resolved by an EXT_DEF definition into an entry into a HUNK_RELRELOC32 hunk by the linker.  |
| EXT_RELCOMMON | [0x89] | 32-bit PC relative common reference for a 32-bit address. Similar to a EXT_COMMON definition, this will be resolved into an HUNK_RELRELOC32 entry where potentially space for the symbol will be allocated in a BSS segment if no corresponding definition is found.                              |
| EXT_ABSREF16  | [0x8a] | 16-bit absolute reference, resolved by the linker to a 16-bit value by an EXT_ABS definition.   |
| EXT_ABSREF8   | [0x8b] | 8-bit absolute reference, resolved by the linker to an 8-bit value through an EXT_ABS definition.   |

For references,  $s_n$  identifies the number of times the symbol is referenced, while  $s_o$  defines the offsets into the current segment where the symbol is used and into which the symbol value will be resolved during linking. This value comes from an  $s_v$  entry in a HUNK\_EXT hunk from another translation unit.

Common symbols are symbols that are defined in multiple translation units. The size of the symbol required by the translation  $s_c$ . If no corresponding symbol definition is found, the linker then allocates space of a size that is determined by the maximum of all  $s_c$  values found for the same symbol in all translation units. The symbol will then be created within a BSS segment by the linker without an explicit symbol definition. This mechanism is mostly used by FORTRAN and is therefore rarely used. SAS/C can also be configured to emit common symbols as well.

## 11.6 Link Library File Format

Link Library files are collections of small compiled or assembled program sections that provide multiple commonly used symbols or functions. Unlike AmigaOs libraries, which are loaded dynamically at run time, link libraries resolve undefined symbols at link time; functions or symbols within them become a permanent part of the generated executable.

The *amiga.lib* is a typical example for a link library. It contains functions such as `CreateExtIO()`. While newer versions of the *exec.library* contains with `CreateIORequest()` a similar function, some

manual work was required for creating an `IORequest` structure in `exec` versions prior v37. To ease development, it was made available in a (static) library whose functions are merged with the compiled code.

Link libraries come in two forms: Old-style non-indexed libraries, and indexed libraries that are faster to process. Old-style or non-indexed link libraries are simply a concatenation of object files in the form presented in section 11.5 and table 45. Then, of course, one translation unit as introduced by `HUNK_UNIT` ?? is not necessarily terminated by an EOF as specified in table 45, but possibly by the subsequent program unit, starting with another `HUNK_UNIT`.

Non-indexed link libraries do not require any tools beyond a compiler or assembler for buliding them. The AmigaDOS `JOIN` command is sufficient to build them. The drawback of such libraries is that they are slow to process as the linker needs to scan the entire library to find a specific symbol.

Indexed libraries are faster to parse as they contain a compressed index of all symbols defined in the library. It consists at its topmost level of two hunks: one containing the program units, and a symbol table with an index that are repeated until the end of the file.

The overall format of indexed libraries is depicted in table 54.

**Table 54: Indexed Library**

| Size | Code               | Syntax                                  |
|------|--------------------|---|
|      | do {               | Multiple repetitions of the following   |
| ?    | HUNK_LIB [0x3fa]   | Object code modules, see section 11.6.1 |
| ?    | HUNK_INDEX [0x3fb] | Indicies into HUNK_LIB, see section ??  |
|      | } while(!EOF)      | Until the end of the file               |

### 11.6.1 HUNK\_LIB

The `HUNK_LIB` hunk contains the actual payload in the form of multiple code, data or BSS hunks along with their relocation, symbol and debug information. It looks almost like the contents of a `HUNK_UNIT` hunk, with a couple of changes noted below.

Table 55 depicts the syntax of this hunk.

**Table 55: Hunk LIB Format**

| Size | Code  | Syntax   |
|------|---|--|
| ?    | HUNK_LIB [0x3fa]  | Identifies the start of an indexed library                                       |
| 32   | <i>l</i>  | Length of this hunk in long-words not including the header and this length field |
|      | do {  | Multiple segments follow   |
| 2    | <i>m<sub>t</sub></i>  | Read the memory type of the next hunk  |
| 30   | <i>h<sub>t</sub></i>  | Read the next hunk type  |
|      | if ( <i>h<sub>t</sub></i> == HUNK_CODE)<br>parse_CODE       | Code and constant data, see 11.1.2   |
|      | else if ( <i>h<sub>t</sub></i> == HUNK_DATA)<br>parse_DATA  | Data, see 11.1.3   |
|      | else if ( <i>h<sub>t</sub></i> == HUNK_BSS)<br>parse_BSS    | Zero-initialized data, see 11.1.4  |
|      | else if ( <i>m<sub>t</sub></i> != 0)<br>ERROR_BAD_HUNK      | Upper bits shall be 0 for all other hunks  |
|      | else do {   | Loop over auxiliary information  |
|      | if ( <i>h<sub>t</sub></i> == HUNK_RELOC32)<br>parse_RELOC32 | 32-bit relocation, see 11.1.5  |

|    |  |   |
|----|--|---|
|    | else if ( $h_t ==$<br>HUNK_RELOC32SHORT)<br>parse_RELOC32SHORT | 32-bit relocation, see 11.1.6                   |
|    | else if ( $h_t ==$<br>HUNK_RELRELOC32)<br>parse_RELRELOC32     | 32-bit PC-relative relocation, see 11.1.7       |
|    | else if ( $h_t ==$<br>HUNK_RELOC16) parse_RELOC16              | 16-bit PC-relative relocation, see 11.5.2       |
|    | else if ( $h_t ==$<br>HUNK_RELOC8) parse_RELOC8                | 8-bit PC-relative relocation, see 11.5.2        |
|    | else if ( $h_t ==$<br>HUNK_DRELOC32) parse_RELOC32             | 32-bit base-relative relocation, see 11.5.4     |
|    | else if ( $h_t ==$<br>HUNK_DRELOC16) parse_RELOC16             | 16-bit base-relative relocation, see 11.5.5     |
|    | else if ( $h_t ==$<br>HUNK_DRELOC8) parse_RELOC8               | 8-bit base-relative relocation, see 11.5.6      |
|    | else if ( $h_t ==$ HUNK_EXT)<br>parse_EXT                      | External symbol definition, see 11.5.7          |
|    | else if ( $h_t ==$<br>HUNK_SYMBOL) parse_SYMBOL                | Symbol definition, see 11.1.9                   |
|    | else if ( $h_t ==$<br>HUNK_DEBUG) parse_DEBUG                  | Debug information, see 11.1.10                  |
|    | else if ( $h_t ==$ HUNK_END)<br>break                          | abort this segment                              |
|    | else ERROR_INVALID_HUNK  | an error  |
| 32 | $h_t$  | Read next hunk type                             |
|    | } while(true)  | Repeated until HUNK_END                         |
|    | } while(!EOF)  | Repeated with the next hunk until the file ends |

Additional restrictions arise for the HUNK\_EXT hunk; as symbol definitions are included in the HUNK\_INDEX hunk, they shall be removed from this hunk; the corresponding symbol types to be removed are listed in table 39. Unlike symbol definitions, symbol references as given by table 53 shall be retained as only the reference, but not the type of the reference is included in HUNK\_INDEX.

The translation unit name and the hunk names shall also stripped, i.e. neither HUNK\_UNIT nor HUNK\_NAME shall be included in HUNK\_LIB. The corresponding names are also defined in HUNK\_INDEX by means of the string table included there.

Due to restrictions of HUNK\_INDEX, the size of a HUNK\_LIB shall not exceed  $2^{16}$  long-words and shall be split over multiple HUNK\_LIB, HUNK\_INDEX pairs otherwise.

## 11.6.2 HUNK\_INDEX

The HUNK\_INDEX hunk contains a string table and indices into the preceeding HUNK\_LIB.

Table 56 depicts the syntax of this hunk.

**Table 56: Hunk Index Format**

| Size | Code               | Syntax  |
|------|--------------------|---|
| 32   | HUNK_INDEX [0x3fb] | Defines symbols and references into the library |



|    |                                    |  |
|----|------------------------------------|--|
| 32 | $l$                                | Length of this hunk in long-words                              |
| 16 | $s_l$                              | Length of the string table in <b>bytes</b>                     |
|    | do {                               | Repeat over the strings  |
| ?  | $s_y[i]$                           | A NUL-terminated (C-style) string                              |
|    | $s_l -= \text{strlen}(s_y[i]) + 1$ | Remove from the length of the symbol table                     |
|    | } while ( $s_l > 0$ )              | Repeat until all $s_l$ bytes are parsed                        |
|    | do {                               | Loop over translation units                                    |
| 16 | $u_o$                              | Byte offset of the unit name into the string table             |
| 16 | $h_o$                              | Long-word offset of the first hunk of the unit within HUNK_LIB |
| 16 | $h_c$                              | Number of hunks within the unit                                |
|    | for ( $j=0; j<h_c; j++$ ) {        | Loop over all hunks  |
| 16 | $h_n$                              | Byte offset of the hunk name into the string table             |
| 2  | $m_t$                              | Memory type of the hunk  |
| 14 | $h_t$                              | (Shortened) hunk type  |
| 16 | $x_c$                              | Number of references in the hunk                               |
|    | for ( $k=0; k<x_c; k++$ ) {        | Loop over references   |
| 16 | $x_n$                              | Byte offset of the reference name into the string table        |
|    | }                                  |  |
| 16 | $d_c$                              | Number of definitions in the hunk                              |
|    | for ( $k=0; k<d_c; k++$ ) {        | Loop over definitions  |
| 16 | $d_n$                              | Byte offset of the defined name into the string table          |
| 16 | $d_o$                              | Byte offset into the hunk or absolute value                    |
| 8  | $a_u$                              | Bits 23-16 of EXT_ABS definition                               |
| 1  | 0                                  | This bit shall be 0 to identify a definition                   |
| 1  | $a_s$                              | Sign bit and bits 30 to 24 of an EXT_ABS definition            |
| 6  | $d_t$                              | Type of the definition from table 39                           |
|    | }                                  |  |
|    | }                                  |  |
|    | } while (!end)                     | Repeated until the end of hunk is found                        |

The initial part, the string table, contains all strings that can be used by the rest of the hunk. Strings within this table are indexed as byte offset from the start of the string, i.e. the first string has offset 0. To enable unnamed hunks, the first entry in a string table shall be the empty string, that is, an isolated 0-byte.

The rest of HUNK\_INDEX contains the offsets into the hunks along with symbols referenced and defined within them. The memory type of the hunk is again expressed in two bits. The current specification does not define the meaning of both bits set. The hunk type itself is abbreviated, i.e. only the lower 14 bits of the hunk type are stored.

The first part of the subsequent data defines references, that is, symbols that are used but not defined within the hunk. The  $x_n$  values define the names of these symbols as offsets from the start of the string table. These names correspond to symbol types defined in table 53. The precise reference type of the symbols is then found in an HUNK\_EXT hunk as part of the preceeding HUNK\_LIB hunk.

Unlike symbol references, symbol definitions are stored directly in the HUNK\_INDEX hunk. While  $d_n$

---

identifies the name of the symbol as offset into the string table, the  $d_o$  value is either the offset of the defined symbol within the hunk, or the least significant 16 bits of an `EXT_ABS` definition. As some absolute values can exceed 16 bits,  $a_o$  stores bits 23 to 16 of the symbol value, and bit  $a_s$  is copied into bits 31 to 24 of the symbol to enable negative values. The type of the symbol definition is  $d_t$ , which shall be a value from table 39.

As seen from this definition, symbols can only be defined within the first 64K of a hunk. This is typically not a problem as link libraries typically contain short service functions. For absolute values, larger values are required, e.g. for the base address of the custom chips, and thus split into  $a_s$ ,  $a_o$  and  $d_o$ .

---

## Chapter 12

# Handlers, Devices and File Systems

Handlers are AmigaDOS processes that provide all the services to implement many functions of the *dos.library*. Operations on files, such as opening files, reading data or seeking in files are implemented in the corresponding handler and not the *dos.library* itself. *File systems* are special handlers that organize data streams on volumes such as hard disks in files, and also provide locks to reserve access rights to files. Most file systems also support directories and thus a hierarchical organization of files.

Handlers are recognized by an entry in the *device list* whose `dol_Task` element provides a pointer to a message port through which the *dos.library* communicates with the handler, section 8 provides further details on this structure.

To ease communication, the `FileHandle` structure representing a file also includes with its `fh_Type` element a pointer to such a port that is typically a copy of `dol_Task` when a file is opened, see section 4.9.1 for this structure. It is created by the *dos.library* when opening files.

Similarly, the `fh_Type` element of the `FileLock` structure includes the port through which communication with the file system concerning the lock is routed. Unlike `FileHandles`, the `FileLock` structure is created by the *file system* itself which initializes its `fh_Type`. This is again in many cases identical to the `dol_Task` message port within the *device list*.

### 12.1 The DosPacket Structure

While it is in many cases more practical to interact with handlers through the functions of the *dos.library*, it is also possible to communicate with the handler directly through this port. This communication is based on *packets*, represented by a `DosPacket` structure documented in `dos/dosextens.h`:

```
struct DosPacket {
    struct Message *dp_Link;
    struct MsgPort *dp_Port;
    LONG dp_Type;
    LONG dp_Res1;
    LONG dp_Res2;
    LONG dp_Arg1;
    LONG dp_Arg2;
    LONG dp_Arg3;
    LONG dp_Arg4;
    LONG dp_Arg5;
    LONG dp_Arg6;
    LONG dp_Arg7;
```

---

```
};
```

*Packets* ride on top of *exec* messages, see `exec/ports.h`, but they do not extend the `Message` structure as it would be usually the case. Instead, `mn_Node.ln_Name` of the *exec* message is (mis-)used to point to the `DosPacket`. The reply port of the message in `mn_ReplyPort` is *not* used; instead, the message carrying the packet is send back to `dp_Port`.

Members of the `DosPacket` structure shall be initialized as follows:

`dp_Link` shall point to the message which is used for transmitting the `DosPacket`. The message node name in `mn_Node.ln_Name` shall be initialized to point to the `DosPacket` itself.

`dp_Port` shall point to the `MsgPort` structure to which the packet shall be send back after the handler has completed the requested activity. This is typically, but not necessary `pr_MsgPort` of the process sending the packet. See section 10 for the defintion of the `Process` structure.

`dp_Type` identifies the action requested from the handler. It shall be filled by the process requesting an activity from a handler and is interpreted by the handler. Section ?? lists the currently documented packet types.

`dp_Res1` is the primary result code of the activity performed by the handler. For many, but not for all packet types, this is a boolean result code that is 0 for failure and non-zero for success. Many functions of the *dos.library* return `dp_Res1` as their return code.

`dp_Res2` is the secondary result code installed by the handler and is typically is 0 for success, or an error code on failure. Many functions of the *dos.library* install this error code into `IoErr()`. Section 10.2.9 lists the error codes defined by the *dos.library*.

`dp_Arg1` to `dp_Arg7` provide additional arguments to the handler. They shall be filled by the process submitting a packet to a handler. Most packet types do not require all 7 possible arguments; in such a case, only the necessary arguments may be initialized.

### 12.1.1 Send a Packet to a Handler and Wait for Reply

The `DoPkt()` function creates from its arguments a `DosPacket` structure along with an *exec* `Message` carrying it on the fly, transmits the packet to a target port and waits for the packet to return.

```
result1 = DoPkt(port, action, arg1, arg2, arg3, arg4, arg5)
D0                D1      D2      D3      D4      D5      D6      D7
```

```
LONG DoPkt(struct MsgPort *, LONG, LONG, LONG, LONG, LONG, LONG)
```

This function performs low-level packet IO to a target message port belonging to a handler. The `port` is the `MsgPort` of the handler to contact. Depending on the context, this port should be taken from various sources. If low-level file I/O is to be performed, the best source for the port is the `fh_Type` pointer in the `FileHandle` structure. If the communication is related to a *Lock*, the `fl_Task` member of the `FileLock` is the right source. For activities unrelated to locks or files, the `dol_Task` member of the *device list* is another source.

`action` identifies the activity to be performed by the handler or file system. Section ?? lists the packet types and how they relate to the functions of the *dos.library*.

`arg1` through `arg5` are arguments to the packet and filled into their `dp_Arg1` through `dp_Arg5` elements. If more arguments are required, the packet needs to be created and transmitted manually.

This function returns the primary result code of the handler from `dp_Res1` in `result1`, and `dp_Res2` in `IoErr()`.

If the caller is a process and the `pr_PktWait` pointer in the `Process` structure is set, `DoPkt()` calls through it to wait for the packet (or rather the message carrying it) to return, see section 10. Otherwise,

---

DoPkt () waits on pr\_MsgPort with WaitPort () and removes the message through GetMsg (). If the caller is a task, the function even builds an exec MsgPort on the fly and waits on this temporary port — thus unlike many other functions of the *dos.library*, this function is even callable from tasks.

If the return MsgPort contains a message different from the one carrying the issued packet, this function aborts with a deadend alert of type AN\_QPktFail, defined in *exec/alerts.h*. Note that this is quite different from exec-style communications with exec devices through DoIO (); this function is able to extract the send IOREquest from the port without creating a conflict if another message is still pending in the port. This problem of packet communication manifests itself typically when attempting to perform I/O operations through the *dos.library* while the workbench startup message is still queued in the process message port.

Because packets typically require less than 5 arguments, additional prototypes are supplied that do not take all arguments. They all access the same entry within the *dos.library*, the only difference is that the function prototypes do not enforce initialization of the data registers carrying the unneeded arguments. These functions are named DoPkt0 () to DoPkt5 () and carry 2 to 7 arguments: The target port, the type of the packet action and 0 to 5 additional arguments which are filled into dp\_Arg1 upwards.

### 12.1.2 Send a Packet to a Handler Asynchronously

The SendPkt () function transmits a packet to a target message port of a handler without waiting for it to return. Instead, a reply port is provided to which the packet will be returned once the handler acted upon it.

```
SendPkt(packet, port, replyport)
D1      D2 D3
```

```
void SendPkt(struct DosPacket *, struct MsgPort *, struct MsgPort *)
```

This function transmits packet to the handler port, requesting to return it to replyport. The function returns immediately without waiting for the packet to return.

The packet shall be partially initialized; in particular, dp\_Link shall point to an exec Message whose mn\_Node.ln\_Name field points back to packet. This function *does not* supply or initialize a suitable message, this is up to the caller.

dp\_Type shall be filled with the type of the packet, i.e. an identifier specifying the type of activity requested from the handler, see section ???. Depending on this type, dp\_Arg1 through dp\_Arg7 shall be initialized with additional arguments.

DosPackets can be constructed in multiple ways; the AllocDosObject () function may be called to construct a StandardPacket. This is a structure that contains both the Message and the DosPacket. It is defined in *dos/dosextens.h*:

```
struct StandardPacket {
    struct Message  sp_Msg;
    struct DosPacket sp_Pkt;
};
```

AllocDosObject () ensures that the linkage between Message and DosPackete are properly initialized.

Another option is to use AllocMem () to allocate sufficient storage to hold a StandardPacket and initialize the structure appropriately:

```
struct StandardPacket *sp;

sp->sp_Msg.mn_Node.ln_Name = (UBYTE *) &(sp->sp_Pkt);
sp->sp_Pkt.dp_Link          = &(sp->sp_Msg);
```

---

### 12.1.3 Waiting for a Packet to Return

The `WaitPkt()` function waits on the message port of the calling process for a packet to return.

```
packet = WaitPkt()  
D0
```

```
struct DosPacket *WaitPkt(void);
```

This function performs all activities to receive a message returning from a handler; it is also implicitly called by `DoPkt()` after sending the messages to the handler.

If the `pr_PktWait` pointer in the `Process` structure is set, `WaitPkt()` calls through this function to wait for the arrival of a message. Otherwise, the `WaitPkt()` calls `WaitPort()` to wait for a arrival of a message on `pr_MsgPort` of the calling process, and then calls `GetMsg()` to remove it from the port. The function then returns `mn_Node.ln_Name` of the received message, i.e. the packet corresponding to the message.

This function does not test whether the received message does, actually, belong to a packet. The caller shall ensure that only Messages corresponding to `DosPackets` can arrive at the process message port.

### 12.1.4 Aborting a Packet

The purpose of the `AbortPkt()` function is to attempt to abort a packet already send to a handler. However, as of the current Os release, it does nothing and is not functional.

```
AbortPkt(port, pkt)  
D1      D2
```

```
void AbortPkt(struct MsgPort *, struct DosPacket *)
```

What this function should do is to scan `port`, presumably the `MsgPort` of the handler to which `pkt` was send, and dequeue it there if the handler is not yet working on it. Then, it would be placed back into the port of its initiator. As of V747, this function does nothing.

### 12.1.5 Reply a Packet to its Caller

The `ReplyPkt()` function returns a packet to its initiator, filling the primary and secondary result codes. This function is intended to be used by handlers.

```
ReplyPkt(packet, result1, result2)  
D1      D2      D3
```

```
void ReplyPkt(struct DosPacket *, LONG, LONG)
```

This function fills `dp_Res1` and `dp_Res2` of the packet with `result1` and `result2`, and sends the packet to `dp_Port`, the initiating port. Note that `mn_ReplyPort` of the message pointed to by `dp_Link` is ignored, i.e. packets do *not* follow the exec protocol for replying messages.

The `result1` argument is the primary result code and identical to the return code of many *dos.library* functions. `dp_Res2` is the secondary result code and typically accessible through `IoErr()` if the packet is replied to a *dos.library* function.

---

## 12.2 Implementing a Handler

A *handler* or a *file system* is an Amiga process that retrieves commands in the form of `DosPackets`. The main loop of a handler is conceptionally similar to a program implementing a graphical user interface, except that the latter retrieves messages via the *intuition* IDCMP system and works them off, whereas the handlers receive commands from its handler port.

### 12.2.1 Handler Startup

When a user of the *dos.library* attempts to access an absolute path, i.e. a path including a device name, the *dos.library* walks the *device list* (see section 8) to find the handler responsible for it by comparing the device name in the path with the `dol_Name` element of the *device list*. Once a suitable entry has been found, the *dos.library* checks whether a handler is already running by checking the `dol_Task` field of the *device list*. If so, a packet corresponding to the called *dos.library* function is sent to the port pointed to by `dol_Task`. The relation between library functions and packet types is further explained in section ??.

If `dol_Task` is `NULL`, the *dos.library* checks next whether `dol_SegList` is `ZERO`. If it is, the handler code is not yet present and will be loaded from the file name indicated in `dol_Handler` through `LoadSeg()`, and its return code is used to initialize `dol_SegList`. Once the handler is present, a new process is created from the segment, and a startup packet is delivered to `pr_MsgPort` of the created handler process. The *dos.library* will not continue processing the initiating call until the handler replies to this packet.

How the startup packet is delivered depends on the `dol_GlobVec` element of the *device list* entry, see Table 26. For C or assembler handlers with a `dol_GlobVec` value of `-1` or `-2`, the startup packet is delivered to the `pr_MsgPort` of the handler process. For all other values of `dol_GlobVec`, the startup packet becomes the first argument of the `START` entry at offset 4 of the global vector of the process.

If the “fake” BCPL startup code from section 11.4.3 is used, this packet is delivered in register `a0` of the main function. The following code demonstrates this:

```
LONG __asm __savesd main(register __a0 struct DosPacket *pkt)
{
    SysBase = *((struct ExecBase **) (4L));
    struct Process *proc = (struct Process *)FindTask(NULL);
    struct Message *msg;
    const UBYTE *path;
    ULONG startup;
    struct DosList *dlist;
    LONG error = 0;

    /* if NULL, this was a C startup, retrieve
    ** the packet manually
    */
    if (pkt == NULL) {
        /* Wait and retrieve the startup message
        */
        WaitPort(&proc->pr_MsgPort);
        msg = GetMsg(&proc->pr_MsgPort);
        pkt = (struct DosPacket *)msg->mn_Node.ln_Name;
    }

    path      = (const UBYTE *)BADDR(pkt->dp_Arg1);
    startup   = pkt->dp_Arg2;
```

```

dlist    = (struct DosList *)BADDR(pkt->dp_Arg3);
... /* Handler initialization */

if (error) {
    ReplyPkt(pkt,DOSFALSE,error);
    ... /* shutdown, terminate */
    return;
} else {
    BOOL run = TRUE;
    ReplyPkt(pkt,DOSTRUE,0);
    /* main program loop */
    do {
        LONG res1 = DOSFALSE;
        LONG res2 = ERROR_ACTION_NOT_KNOWN;
        WaitPort(&proc->pr_MsgPort);
        msg = GetMsg(&proc->pr_MsgPort);
        pkt = (struct DosPacket *) (msg->mn_Node.ln_Name);
        switch(pkt->dp_Type) {
            case ACTION_....
                ....
        }
        ReplyPkt(pkt,res1,res2);
    } while(run);
}
}

```

The startup packet is populated as follows:

`dp_Type` is set to `ACTION_STARTUP`, which is defined to be 0. As the startup packet is always received first, there is no need to test for this particular type.

`dp_Arg1` is set to a *BPTR* to a *BSTR* representing the path name under which the client of the *dos.library* attempted to access the handler. Note that this is not a NUL-terminated C string, but a *BSTR* whose first element is the size of the string.

`dp_Arg2` is a copy of the `dol_Startup` element of the `DosList` structure, see section 8. It is used to configure the properties of the handler.

`dp_Arg3` is a *BPTR* to the `DosList` structure that triggered starting this handler.

Multiple strategies exist how handlers make use of this information. A *file system* process would typically handle multiple files at once through the same process. To ensure that the *dos.library* sends requests for the file system to the process just started, the *file system* shall place a pointer to the `MsgPort` incoming packets are supposed to be send to in `dol_Task` of the `DosList` structure received in `dp_Arg3`. This is typically, but not necessarily, the `pr_MsgPort` of the handler process.

The `dp_Arg2` element is used to configure file systems; it is a copy of the `dol_Startup` element of the `DosList`. While its use is file-system dependent, it is typically, but not necessarily, a *BPTR* to a `FileSysStartupMsg` structure. Other possibilities for `dol_Startup` are a *BPTR* to a *BSTR* or an integer. What exactly the handler will receive depends on the `Mountlist` and is discussed in more detail in section 8.1.1.

Whenever a client program opens a file on this *file system* or attempts to lock an object, the handler process will be contacted by sending a packet to the port listed in `dol_Task`.

A *handler* such as the `CON` handler requires a separate process for each window it manages. In such a case, `dol_Task` remains `NULL`. Thus, handlers can decide whether they require a new process for each file opened from the handler.



---

`dp_Arg1` is the *BPTR* to the path to be opened and thus taken from the first argument to `Open()`, just that it has been converted to a *BSTR* by the *dos.library*. For the *Console-Handler* for example, this is the window specification that instructs the handler on the position, size and title of the console.

While the *dos.library* will also send a packet to open the file for which the handler was launched, the path of this second packet or any subsequent packet to open a file on the same process is not relevant to the *Console-Handler* anymore as the window will be opened during startup, and not during opening a file. Even though the handler is started once for the initial open and does not fill in its port in `dol_Task`, multiple requests to open a file may arrive at the handler, e.g. when opening the “\*” file indicating the current console.

Once the *handler* or *file system* initiated itself from the startup packet, the packet shall be replied. If startup failed, the primary result code shall be `DOSFALSE` and the secondary result code shall be an error code suitable for reporting through `IoErr()`, see section 10.2.9 for a list of common error codes. Then, the handler shall release all resources acquired so far and terminate.

## 12.2.2 Handler Main Processing Loop

If startup succeeded, the primary result code for the packet shall be `DOSTRUE`, and the secondary result code shall be 0. Handler operations then proceed by waiting for incoming packets, and processing them one by another.

The *dos.library* keeps the *device list* locked while the handler is starting up. This means in particular that an attempt to gain access to the *device list* with `LockDosList()`, see section 8.3.1, can deadlock. Even if such a call is not made explicitly, *dos.library* functions can require implicitly such a lock, and thus attempting to access files or lock objects within handlers should be avoided, not only during startup.

If `dol_GlobVec` is `-2` or `-3`, the *dos.library* will only acquire a shared lock, and thus will allow the handler to retrieve a shared lock on the *device list* as well.

Once started up, handlers or file systems should wait for incoming packets. Depending on how a handler is contacted, the *dos.library* uses multiple sources to identify a suitable port:

If the handler is contacted through the special path “\*” or a path starting with “CONSOLE:”, the port in `pr_ConsoleTask` is used to send packets to.

If the handler is contacted through a path starting with “PROGDIR:” and the `pr_HomeDir` element of the calling process is non-NULL, the `fl_Task` element of the lock stored there is used to contact the handler.

If the handler is contacted through an absolute path, the *dos.library* scans the *device list* to locate a `DosList` structure whose `dol_Name` element matches the device name in the path. The `dol_Task` field, if non-NULL, is then used as destination of a packet. If it is NULL, a new process of the handler is created. From this follows that a handler or file system can customize the port through which it expects packets. File systems will typically place the `pr_MsgPort` of their process there.

If a handler is contacted through a relative path, and `pr_CurrentDir` of the calling process is non-ZERO, the `fl_Task` element of the current directory of the process attempting to resolve a path is used as target port. If `pr_CurrentDir` is ZERO, the `pr_FileSystemTask` is used as target port.

If the handler is contacted through a *File Handle*, for example to read or write bytes from a file, the `fh_Type` element of the handle is used as destination port. A file system may place a custom port in this element on opening files through `ACTION_FINDINPUT`, `ACTION_FINDOUTPUT` or `ACTION_FINDUPDATE` in the `fh_Type` element of the handle to receive all packets associated to this particular file on an alternative port. The *dos.library* places by default there the port it found through the path, see above.

If the handler is contacted through a lock, the `fl_Task` element of the `FileLock` structure is used to send out packets. A file system thus may customize a port through which all packets related to a particular lock are transmitted by placing this port in `fl_Task` when creating a lock.

---

The special path “NIL:” does not correspond to any handler but sets the `fh_Type` element to `ZERO`. Any attempt to write out data through such a handle ignores all bytes written, and any attempt to read bytes will return zero bytes. This is a special case in which the *dos.library* does not go through a handler at all.

The main loop of a handler then checks its own process port, or all ports it provided through the above mechanisms for incoming packets and tests their `dp_Type` field, identifying the requested action to be performed. Subsequent sections will provide information on all packets documented within AmigaDOS, though third-party handlers may implement additional packet types.

A handler or file system receiving a packet it does not implement shall set its `dp_Res2` element to `ERROR_ACTION_NOT_KNOWN`. `dp_Res1` shall be set for non-implemented packets according to the packet type as shown in the following table:

**Table 57: Primary Result Code for Unimplemented Packets**

| <code>dp_Type</code>              | <code>dp_Res1</code> |
|-----------------------------------|----------------------|
| <code>ACTION_READ</code>          | -1                   |
| <code>ACTION_WRITE</code>         | -1                   |
| <code>ACTION_SEEK</code>          | -1                   |
| <code>ACTION_SET_FILE_SIZE</code> | -1                   |
| all others                        | 0                    |

This ensures that clients of the handler or file system will receive a result that is an indication of an error.

### 12.2.3 Handler Shutdown

A *handler* that does not initialize the `dol_Task` element of its `DosList` structure should keep a counter that is incremented for each object it creates, and decremented for each object deleted or disposed. For example, if the handler supports opening files, then the initialization of each file handle should increment the counter, and each file handle closed through `ACTION_END` should decrement the counter. Once the use counter reaches zero, the handler process should die by releasing all of its resources and falling off its main function. This ensures that the system is not congested by creating more and more processes of the same handler that, effectively, cannot be contacted anymore because its process part is not referenced in any object passed out of the *dos.library*.

A typical example of a handler is the `Con-Handler` of the system that opens its window from its startup message but any file opened to it will interact with the same window. The window will be closed when each of these files had been closed<sup>1</sup>.

*File systems*, however, typically do initialize `dol_Task` and thus can be reached even if all files or locks on the volume they manage have been released. Thus, in addition to such resource tracking, file systems should check for incoming packets of the type `ACTION_DIE` and then attempt to shutdown. This is, of course, only possible if all open files have been closed and all locked objects have been unlocked.

A example for such a handler is the `FFS` which will not go away unless it is explicitly asked to.

## 12.3 Packets for File Interactions

The packet types listed in this section are used to implement file-specific functions, such as those listed in chapter 4. The arguments of the packets typically follow the calling conventions of the *dos.library* functions closely, though are typically represented in their BCPL equivalents, i.e. *BPTRs* instead of regular pointers or *BSTRs* instead of NUL-terminated C strings.

---

<sup>1</sup>This is a simplification, ignoring `AUTO` and `WAIT` parameters, see section 12.11 for details

### 12.3.1 Opening a File for Shared Access

The packet ACTION\_FINDINPUT initializes a FileHandle structure for shared access to a file.

**Table 58:** ACTION\_FINDINPUT

| DosPacket Element | Value                         |
|-------------------|-------------------------------|
| dp_Type           | ACTION_FINDINPUT (1005)       |
| dp_Arg1           | BPTR to <i>FileHandle</i>     |
| dp_Arg2           | BPTR to <i>FileLock</i>       |
| dp_Arg3           | BPTR to BSTR of the file name |
| dp_Res1           | Boolean result code           |
| dp_Res2           | Error code                    |

This packet is used by the `Open()` function of the *dos.library* where the packet type is taken copied from the second argument, i.e. the packet type is identical to the `accessMode` argument of `Open()`, and thus ACTION\_FINDINPUT is identical to MODE\_OLDFILE.

`dp_Arg1` is initialized to BPTR to a FileHandle structure whose `fh_Arg1` handle should be initialized to a value the handler or file system may use later on to identify the file it operates on. This is particularly important to *file systems* that handle multiple files by a single process. In a typical implementation, this opaque value may be the (internal) lock to the opened file.

A handler or file system may also replace the `fh_Type` element of the FileHandle structure request that packets concerning this particular file shall be delivered to an alternative port. This element otherwise defaults to the process port of the handler.

`dp_Arg2` is initialized to the BPTR to a FileLock structure describing the directory within which the file to be opened is located. Typically, this corresponds to the current directory of the caller of `Open()`. If this lock is ZERO, then the *file system* shall assume that the provided path is relative to the root directory of the currently inserted volume. Flat file systems or handlers may ignore this argument.

`dp_Arg3` is initialized to a BPTR to a BSTR providing the path of the file relative to the directory provided by `dp_Arg1`.

All other arguments of the packet shall be ignored. The handler should locate the file indicated by `dp_Arg3` relative to `dp_Arg2`, and fill in a boolean success code in `dp_Res1`. It shall be set to DOSTRUE for success or DOSFALSE for error. `dp_Res2` shall be set to an error code from `dos/dos.h` or 0 for success.

The purpose of this packet is to prepare a *FileHandle* for shared access, either for reading or for writing. If the file cannot be located, this packet *shall not* create it but rather fail with ERROR\_OBJECT\_NOT\_FOUND. This packet is used by the `Open()` function if its second argument is set to MODE\_OLDFILE.

Handlers such that the Port-Handler or the Console-Handler may already open its resources as part of the startup-packet handling and thus may not perform a lot of activities here. Note that both handlers do not initialize `dol_Task` of the DosList structure and thus each opened file will launch a new process. The FFS, however, runs on a single process and thus distinguishes its files through `fh_Arg1` in the FileHandle structure.

Note that both the Lock provided by `dp_Arg2` and the path `dp_Arg3` are required for locating a file on a hierarchical file system. The path from `dp_Arg3` is logically “appended” to the path implied by `dp_Arg2`, i.e. the file system starts interpreting the former by scanning the directory hierarchy at the position given by `dp_Arg2`, or the root directory if `dp_Arg2` is ZERO.

A special case arises if `dp_Arg3` is the empty string; in such a case, `dp_Arg2` shall be already a Lock to the file to open. This is implied by the above algorithm to locate a file that ends walking the directory tree whenever `dp_Arg3` ends.

The type of this packet, ACTION\_FINDINPUT, is intentionally identical to MODE\_OLDFILE as the `Open()` function currently initializes the packet type from its second argument.

### 12.3.2 Opening a File for Exclusive Access

The packet ACTION\_FINDOUTPUT initializes a FileHandle structure for exclusive access to a file and potentially creates the file if it does not yet exist.

**Table 59:** ACTION\_FINDOUTPUT

| DosPacket Element | Value                     |
|-------------------|---------------------------|
| dp_Type           | ACTION_FINDOUTPUT (1006)  |
| dp_Arg1           | BPTR to <i>FileHandle</i> |
| dp_Arg2           | BPTR to <i>FileLock</i>   |
| dp_Arg3           | BPTR to BSTR of file name |
| dp_Res1           | Boolean result code       |
| dp_Res2           | Error code                |

This packet is used by the Open() function of the *dos.library* where the packet type is taken copied from the second argument, i.e. the packet type is identical to the accessMode argument of Open(), and thus ACTION\_FINDOUTPUT is identical to MODE\_NEWFILE.

The arguments of the packet are initialized as for ACTION\_FINDINPUT, see section 12.3.1.

### 12.3.3 Opening or Creating a File for Shared Access

The packet ACTION\_FINDUPDATE initializes a FileHandle structure for shared access to a file, potentially creating the file if it does not yet exist.

**Table 60:** ACTION\_FINDUPDATE

| DosPacket Element | Value                     |
|-------------------|---------------------------|
| dp_Type           | ACTION_FINDUPDATE (1004)  |
| dp_Arg1           | BPTR to <i>FileHandle</i> |
| dp_Arg2           | BPTR to <i>FileLock</i>   |
| dp_Arg3           | BPTR to BSTR of file name |
| dp_Res1           | Boolean result code       |
| dp_Res2           | Error code                |

This packet is used by the Open() function of the *dos.library* where the packet type is taken copied from the second argument, i.e. the packet type is identical to the accessMode argument of Open(), and thus ACTION\_FINDUPDATE is identical to MODE\_READWRITE.

The arguments of the packet are initialized as for ACTION\_FINDINPUT, see section 12.3.1.

### 12.3.4 Opening a File from a Lock

The packet ACTION\_FH\_FROM\_LOCK initializes a FileHandle structure from a lock on an existing file. Whether this access is shared or exclusive depends on the type of the lock. Upon success, the lock is absorbed into the *FileHandle*.

**Table 61:** ACTION\_FH\_FROM\_LOCK

| DosPacket Element | Value                      |
|-------------------|----------------------------|
| dp_Type           | ACTION_FH_FROM_LOCK (1026) |
| dp_Arg1           | BPTR to <i>FileHandle</i>  |
| dp_Arg2           | BPTR to <i>FileLock</i>    |
| dp_Res1           | Boolean result code        |
| dp_Res2           | Error code                 |

This packet type implements the `OpenFromLock()` function of the *dos.library*, see section 5.2.3. It opens a file from a lock. On a hierarchical file system, this is equivalent to an `ACTION_FINDINPUT` packet with `dp_Arg3` set to an empty string.

To uniquely identify the file handle and resources associated to it later on, the handler may place an identifier or a handle or pointer to internal resources in the `fh_Arg1` element of the *FileHandle* provided by `dp_Arg1`. Before replying the packet, `dp_Res1` shall be set by the handler to `DOSTRUE` on success, or `DOSFALSE` on error. On success, `dp_Res2` shall be set to 0, and to an error code from `dos/dos.h` otherwise.

### 12.3.5 Closing a File

The packet `ACTION_END` releases all *file system* internal resources of a file handle.

**Table 62:** `ACTION_END`

| DosPacket Element    | Value   |
|----------------------|---|
| <code>dp_Type</code> | <code>ACTION_END (1007)</code>                |
| <code>dp_Arg1</code> | <code>fh_Arg1</code> of the <i>FileHandle</i> |
| <code>dp_Res1</code> | Boolean result code                           |
| <code>dp_Res2</code> | Error code                                    |

`dp_Arg1` is initialized to the `fh_Arg1` element of the *FileHandle* structure corresponding to the file that is supposed to be closed. This value may be used by the *File System* or *Handler* to uniquely identify the resources associated to the file, for example any implicit lock on the file system object.

Before replying to the packet, `dp_Res1` shall be set to `DOSTRUE` on success or `DOSFALSE` on failure. On success, `dp_Res2` shall be set to 0, or to an error code otherwise.

The *dos.library* uses this packet to implement the `Close()` function. If it receives an error code, the library will not release the memory of the *FileHandle* structure, and as such, it remains available to the caller of `Close()` to perform other activities on the file.

### 12.3.6 Reading from a File

The packet `ACTION_READ` reads data from a *file system* or *handler* and advances the file pointer accordingly.

**Table 63:** `ACTION_READ`

| DosPacket Element    | Value   |
|----------------------|---|
| <code>dp_Type</code> | <code>ACTION_READ (82)</code>                 |
| <code>dp_Arg1</code> | <code>fh_Arg1</code> of the <i>FileHandle</i> |
| <code>dp_Arg2</code> | Pointer to the buffer                         |
| <code>dp_Arg3</code> | Number of bytes to read                       |
| <code>dp_Res1</code> | Bytes read or <code>-1</code>                 |
| <code>dp_Res2</code> | Error code                                    |

This packet implements the `Read()` function of the *dos.library*. The elements of the packet are initialized as follows:

`dp_Arg1` is a copy from `fh_Arg1` of the *FileHandle* structure and may be used by the *file system* or *handler* to identify the file. Note that it is *not* the *FileHandle* itself; instead, the *handler* may create and insert such an identifier into the *FileHandle* when opening a file.

`dp_Arg2` is a pointer (not a `BPTR`) to the buffer to be filled.

`dp_Arg3` is the number of bytes to read.

Before replying this packet, the *handler* shall fill `dp_Res1` with the number of bytes that could be transferred into the buffer, or `-1` for an error condition. This number may also be 0 if no data could be transferred, either because the end of file has been reached, or because currently no data is available on an interactive file, such as the console or the serial port. In case of an error, i.e. for the primary result code `-1`, `dp_Res2` shall be filled with an error code, otherwise it shall be set to 0.

Note that there are no separate packet types corresponding to the buffered IO functions from section 4.8. Instead, the *dos.library* functions at the caller side manage the buffer, monitor its fill state and potentially call into `Read()` which then generates this packet.

### 12.3.7 Writing to a File

The packet `ACTION_WRITE` writes data to a *file system* or *handler* and advances the file pointer accordingly.

**Table 64:** ACTION\_WRITE

| DosPacket Element    | Value                            |
|----------------------|----------------------------------|
| <code>dp_Type</code> | <code>ACTION_WRITE (87)</code>   |
| <code>dp_Arg1</code> | <i>fh_Arg1 of the FileHandle</i> |
| <code>dp_Arg2</code> | Pointer to the buffer            |
| <code>dp_Arg3</code> | Number of bytes to write         |
| <code>dp_Res1</code> | Bytes written or <code>-1</code> |
| <code>dp_Res2</code> | Error code                       |

This packet implements the `Write()` function of the *dos.library*. The elements of the packet are initialized as follows:

`dp_Arg1` is a copy from `fh_Arg1` of the *FileHandle* structure and may be used by the *file system* or *handler* to identify the file.

`dp_Arg2` is a pointer (not a BPTR) to the buffer containing the data to be transferred.

`dp_Arg3` is the number of bytes to write.

Before replying this packet, the *handler* shall fill `dp_Res1` with the number of bytes that could be transferred from the buffer, or `-1` for an error condition. In case of an error, i.e. for the primary result code `-1`, `dp_Res2` shall be filled with an error code, otherwise it shall be set to 0.

Note that there are no separate packet types corresponding to the buffered IO functions from section 4.8. Instead, the *dos.library* functions at the caller side manage the buffer, monitor its fill state and potentially call into `Write()` which then generates this packet.

### 12.3.8 Adjusting the File Pointer

The packet `ACTION_SEEK` sets the file pointer relative to a base location.

**Table 65:** ACTION\_SEEK

| DosPacket Element    | Value                            |
|----------------------|----------------------------------|
| <code>dp_Type</code> | <code>ACTION_SEEK (1008)</code>  |
| <code>dp_Arg1</code> | <i>fh_Arg1 of the FileHandle</i> |
| <code>dp_Arg2</code> | File pointer offset              |
| <code>dp_Arg3</code> | Seek mode from Table 10          |
| <code>dp_Res1</code> | Previous file position           |
| <code>dp_Res2</code> | Error code                       |

This packet implements, to a major degree, the `Seek()` function of the *dos.library*. The elements of the packet are initialized as follows:

`dp_Arg1` is a copy from `fh_Arg1` of the *FileHandle* structure and may be used by the *file system* or *handler* to identify the file.

`dp_Arg2` defines the new location of the file pointer relative to a position identified by `dp_Arg3`.

`dp_Arg3` defines the position to which `dp_Arg2` is relative. It is one of the modes in table 10 and is therefore identical to the third argument of `Seek()`.

Before replying this packet, the *handler* shall fill `dp_Res1` with the previous value of the file pointer, i.e. before making the requested adjustment, or to `-1` in case an error occurred. In the latter case, `dp_Res2` shall be filled with an error code, otherwise it shall be set to 0.

While this packet type mostly implement the `Seek()` function, the latter is also aware of the (caller-side) buffer of the *FileHandle* and performs a flush of this buffer. The packet cannot, of course, perform a flush.

### 12.3.9 Setting the File Size

The packet `ACTION_SET_FILE_SIZE` adjusts the size of a file, either truncating or extends it beyond its current end of file.

**Table 66:** `ACTION_SET_FILE_SIZE`

| DosPacket Element    | Value   |
|----------------------|---|
| <code>dp_Type</code> | <code>ACTION_SET_FILE_SIZE (1022)</code>      |
| <code>dp_Arg1</code> | <code>fh_Arg1</code> of the <i>FileHandle</i> |
| <code>dp_Arg2</code> | File size adjustment                          |
| <code>dp_Arg3</code> | Mode from Table 10                            |
| <code>dp_Res1</code> | Boolean result code                           |
| <code>dp_Res2</code> | Error code                                    |

This packet implements the `SetFileSize()` function of the *dos.library*. The elements of the packet are initialized as follows:

`dp_Arg1` is a copy from `fh_Arg1` of the *FileHandle* structure and may be used by the *file system* or *handler* to identify the file.

`dp_Arg2` defines the new size of the file or equivalently the new position of the end of file, relative to a position identified by `dp_Arg3`.

`dp_Arg3` defines the position to which `dp_Arg2` is relative. It is one of the modes in table 10 and is therefore identical to the third argument of `SetFileSize()`. The new end-of-file position of the file can therefore be set relative to the start of the file, i.e. `dp_Arg2` is the new size of the file, relative to the current file pointer, or relative to the current end-of-file.

Before replying this packet, the *handler* shall fill `dp_Res1` with a boolean success indicator, `DOSTRUE` in case it could extend or truncate the file as requested, or `DOSFALSE` in case of error. In case of success, `dp_Res2` shall be set to 0, otherwise it shall be set to an error code.

Additional information on this packet is found in section 4.7.5 which describes the *dos.library* function that is based on it.

### 12.3.10 Locking a Record of a File

The packet `ACTION_LOCK_RECORD` locks a record of a file. Such a record lock neither provides reading nor writing to the locked region, it just prevents locking the same region with an exclusive lock, see section 4.11 for details how the protocol is supposed to use.

**Table 67:** ACTION\_LOCK\_RECORD

| DosPacket Element | Value                            |
|-------------------|----------------------------------|
| dp_Type           | ACTION_LOCK_RECORD (2008)        |
| dp_Arg1           | fh_Arg1 of the <i>FileHandle</i> |
| dp_Arg2           | Start offset of record           |
| dp_Arg3           | Length of record                 |
| dp_Arg4           | Type of lock from table 12       |
| dp_Arg5           | Timeout (if applicable) in ticks |
| dp_Res1           | Boolean result code              |
| dp_Res2           | Error code                       |

This packet implements the `LockRecord()` function of the *dos.library* and attempts to lock a record of a file, given as start offset from the beginning of the file and a byte size. The file is identified by `dp_Arg1` which is a copy from `fh_Arg1` of the *FileHandle* structure<sup>2</sup>. There is no packet corresponding to `LockRecords()`. Instead, the latter locks records sequentially.

The record to lock is identified by `dp_Arg2` and `dp_Arg3` which correspond to the `offset` and `length` arguments of the `LockRecord()` function.

The mode by which the record is supposed to be locked is given by `dp_Arg4`, it identifies whether the access is shared or exclusive, and whether a timeout is applied or not. The mode is a value from table 12, and more information on the modes is found in section 4.11.1.

If the mode from `dp_Arg4` includes a timeout the *file system* should wait for the record to become available, it is provided by `dp_Arg5`. Otherwise, this argument is ignored, see table 12.

If locking the record is possible, or possible within the timeout, then `dp_Res1` shall be set to `DOSTRUE` when replying this packet. In such a case, `dp_Res2` shall be set to 0. On failure to obtain the record lock, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

### 12.3.11 Release a Record of a File

The packet `ACTION_FREE_RECORD` releases a record lock on a portion of a file.

**Table 68:** ACTION\_FREE\_RECORD

| DosPacket Element | Value                            |
|-------------------|----------------------------------|
| dp_Type           | ACTION_FREE_RECORD (2009)        |
| dp_Arg1           | fh_Arg1 of the <i>FileHandle</i> |
| dp_Arg2           | Start offset of record           |
| dp_Arg3           | Length of record                 |
| dp_Res1           | Boolean result code              |
| dp_Res2           | Error code                       |

This packet implements the `UnLockRecord()` function of the *dos.library* and releases a lock on a subset of a file, identified by start position and length. There is no packet corresponding to `UnLockRecords()`; instead, the *dos.library* sequentially calls `UnLockRecord()` for each record.

The file itself is identified by `dp_Arg1` which is a copy from the `fh_Arg1` element of the *FileHandle* structure. The record to release is given by the start offset within the file provided by `dp_Arg2` and the byte size of the record in `dp_Arg3`.

On success, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` to 0. On error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

<sup>2</sup>The information on `dp_Arg1` in [1] is incorrect.



## 12.4 Packets for Interacting with Locks

The packets listed in this section implement the *dos.library* functions listed in section ; they create, release or duplicate locks or create directories.

### 12.4.1 Obtaining a Lock

The ACTION\_LOCATE\_OBJECT packet locates an object — a file or a directory — on a *file system* and creates from it a *Lock* identifying the object uniquely. The object can later be used as active directory, to open a file from it or to retrieve metadata such as comments or protection bits associated to the identified object.

**Table 69:** ACTION\_LOCATE\_OBJECT

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_LOCATE_OBJECT (8)        |
| dp_Arg1           | BPTR to <i>FileLock</i>         |
| dp_Arg2           | Mode of the Lock                |
| dp_Arg3           | BPTR to BSTR of the object name |
| dp_Res1           | BPTR to <i>FileLock</i>         |
| dp_Res2           | Error code                      |

This packet creates a lock from a path and a directory to which this path is relative, also represented as a lock. As such, it implements the `Lock()` function of the *dos.library*.

`dp_Arg1` is a BPTR to a *FileLock* structure that represents the object to which the path given in `dp_Arg3` is relative. This is usually a directory, and the `Lock()` function fills it from the current directory of the calling process. This argument can be ZERO in which case the *file system* shall assume that `dp_Arg3` is relative to the root of the currently inserted volume handled by the file system.

`dp_Arg2` is the type of the lock to be created as defined in table 13. The value `SHARED_LOCK` requests a non-exclusive lock on an object; multiple of such locks can be held on the same object. The value `EXCLUSIVE_LOCK` requests an exclusive an object; only a single exclusive lock can be held on an object at once, and no other locks, including shared locks, are permissible. Attempting to exclusively lock an object that is already locked shall fail, and attempting to lock an object that is already exclusively locked shall as well. Unfortunately, some programs call `Lock()` with an invalid argument for the mode, and thus *file systems* should be prepared to handle invalid values for `dp_Arg2`. Such values should be considered equivalent to `SHARED_LOCK`.

`dp_Arg3` is a BPTR to a BSTR of an absolute or relative path of the object to be locked. Relative paths are relative to the lock in `dp_Arg1`, and if this argument is ZERO, relative to the root — the topmost directory — of the volume currently managed by this file system. If this string is empty, the identified object to be locked is identical to the one identified by `dp_Arg1`.

On success, `dp_Res1` shall be a BPTR to a *FileLock* structure. These objects are created and maintained by the *file system*. This structure shall be initialized as indicated in section 5.2.5:

`fl_Task` shall point to a `MsgPort` through which the maintaining *file system* can be contacted, which is typically, but not necessarily the process message port `pr_Port` of the *file system* itself.

`fl_Volume` shall be a BPTR to the `DosList` structure representing the volume on which the locked object is located, see section 8.

`fl_Access` shall be filled by `dp_Arg2`, identifying the type of the lock.

`fl_Link` may be used to queue up locks on a volume that is currently not inserted. When a volume with locked objects is removed from the drive, the *file system* may store all these locks in a singly linked list starting at `dol_LockList` and chained by `fl_Link`. If the same volume is then re-inserted into another

drive, another instance of the same file system is able to pick up these locks and manage them instead. Thus, for example, a lock on an object in drive `df0:` will remain valid even if the volume is removed and re-inserted into `df1:`.

`fl_Key`, finally, may be used for the purpose of the *file system* for uniquely identifying the locked object. It is an opaque value as far as the *dos.library* is concerned.

On success, the BPTR to the created `FileLock` shall be stored in `dp_Res1` and `dp_Res2` shall be set to 0. On error, `dp_Res1` shall be set to ZERO and `dp_Res2` to an error code from `dos/dos.h` identifying the source of the problem, see also section 10.2.9.

## 12.4.2 Duplicating a Lock

Despite its misleading name, the packet `ACTION_COPY_DIR` makes a copy of a (shared) lock.

**Table 70:** `ACTION_COPY_DIR`

| DosPacket Element    | Value                             |
|----------------------|-----------------------------------|
| <code>dp_Type</code> | <code>ACTION_COPY_DIR</code> (19) |
| <code>dp_Arg1</code> | BPTR to <i>FileLock</i>           |
| <code>dp_Res1</code> | BPTR to <i>FileLock</i>           |
| <code>dp_Res2</code> | Error code                        |

This packet implements the `DupLock()` function of the *dos.library* and attempts to replicate the lock passed in `dp_Arg1`. If this argument is ZERO, the packet is supposed to create a lock on the root directory of the currently mounted volume.

On success, `dp_Res1` is filled with the BPTR to a copy of the `FileLock` passed in, and `dp_Res2` is set to 0. On error, `dp_Res1` is set to ZERO and `dp_Res2` to an error code. While [1] indicates that `dp_Res1` may be ZERO on an attempt to replicate the ZERO lock, this is not advisable as most users of this packet may misinterpret this result as failure case.

This packet is identical to `ACTION_LOCATE_OBJECT` with `dp_Arg2` set to `SHARED_LOCK` and `dp_Arg3` set to an empty string.

## 12.4.3 Finding the Parent of a Lock

The packet `ACTION_PARENT` obtains a shared lock on the directory containing a locked object.

**Table 71:** `ACTION_PARENT`

| DosPacket Element    | Value                           |
|----------------------|---------------------------------|
| <code>dp_Type</code> | <code>ACTION_PARENT</code> (29) |
| <code>dp_Arg1</code> | BPTR to <i>FileLock</i>         |
| <code>dp_Res1</code> | BPTR to <i>FileLock</i>         |
| <code>dp_Res2</code> | Error code                      |

This packet implements the `ParentDir()` function of the *dos.library* and attempts to create a lock on the directory containing the object identified by `dp_Arg1`. If no parent exists because `dp_Arg1` is a lock on the root directory or the ZERO lock, the *file system* shall set `dp_Res1` to ZERO and `dp_Res2` to 0, indicating that this is not a failure case.

Otherwise, this function returns on success a BPTR to the `FileLock` representing the parent directory in `dp_Arg1` and sets `dp_Arg2` to 0. On error, `dp_Res1` is set to ZERO and `dp_Arg2` to an error code.

## 12.4.4 Duplicating a Lock from a File Handle

The packet ACTION\_COPY\_DIR\_FH creates a shared lock from an object opened by a *file handle*; that is, it copies the implicit lock of the handle.

**Table 72:** ACTION\_COPY\_DIR\_FH

| DosPacket Element | Value                            |
|-------------------|----------------------------------|
| dp_Type           | ACTION_COPY_DIR_FH (1030)        |
| dp_Arg1           | fh_Arg1 of the <i>FileHandle</i> |
| dp_Res1           | BPTR to <i>FileLock</i>          |
| dp_Res2           | Error code                       |

This packet implements the DupLockFromFH() function of the *dos.library*, and thus creates a copy of the lock that is implicit to an open file handle. This works only if the file is open in a non-exclusive mode, i.e. either MODE\_READWRITE or MODE\_OLDFILE.

dp\_Arg1 is a copy of the fh\_Arg1 element of the FileHandle structure and thus serves to identify the opened file.

On success, dp\_Res1 is filled by the BPTR to the FileLock created, namely a lock to the object opened by the file handle. In such a case, dp\_Res2 is set to 0. On error, dp\_Res1 is set to ZERO and dp\_Res2 to an error code.

## 12.4.5 Finding the Parent Directory of a File Handle

The packet ACTION\_PARENT\_FH creates a lock on the directory containing a file identified by a file handle.

**Table 73:** ACTION\_PARENT\_FH

| DosPacket Element | Value                            |
|-------------------|----------------------------------|
| dp_Type           | ACTION_PARENT_FH (1031)          |
| dp_Arg1           | fh_Arg1 of the <i>FileHandle</i> |
| dp_Res1           | BPTR to <i>FileLock</i>          |
| dp_Res2           | Error code                       |

This packet implements the ParentOfFH() function of the *dos.library* and as such creates a lock on the directory that contains a given *file handle*. dp\_Arg1 is a copy of the fh\_Arg1 element of the FileHandle structure and thus identifies the handle.

On success, dp\_Res1 is filled with a BPTR to the FileLock created, and dp\_Res2 is set to 0. On error, dp\_Res1 is set to ZERO and dp\_Res2 to an error code.

## 12.4.6 Creating a new Directory

The packet ACTION\_CREATE\_DIR creates a new directory and represents it by an exclusive lock on the directory created.

**Table 74:** ACTION\_CREATE\_DIR

| DosPacket Element | Value                              |
|-------------------|------------------------------------|
| dp_Type           | ACTION_CREATE_DIR (22)             |
| dp_Arg1           | BPTR to <i>FileLock</i>            |
| dp_Arg2           | BPTR to BSTR of the directory name |
| dp_Res1           | BPTR to <i>FileLock</i>            |
| dp_Res2           | Error code                         |

This packet implements the `CreateDir()` function of the *dos.library* and creates a new directory of the name `dp_Arg2` within the directory identified by the lock `dp_Arg1`.

On success, it creates a new exclusive lock which is returned in `dp_Res1`, and `dp_Res2` is set to 0. On error, `dp_Res1` is set to `ZERO` and `dp_Res2` is set to an error code.

## 12.4.7 Comparing two Locks

The packet `ACTION_SAME_LOCK` compares two locks on the same file system and checks whether the two locks are on the same object.

**Table 75:** `ACTION_SAME_LOCK`

| DosPacket Element    | Value                              |
|----------------------|------------------------------------|
| <code>dp_Type</code> | <code>ACTION_SAME_LOCK (40)</code> |
| <code>dp_Arg1</code> | BPTR to <i>FileLock</i>            |
| <code>dp_Arg2</code> | BPTR to <i>FileLock</i>            |
| <code>dp_Res1</code> | Boolean result code                |
| <code>dp_Res2</code> | Error code                         |

This packet is the core of the `SameLock()` function of the *dos.library*, which, however, first checks whether the two locks to compare are on the same file system. Only if so, the file system corresponding the two locks is contacted with the above packet to compare the two locks. For this, `dp_Arg1` and `dp_Arg2` are BPTRs to the two *FileLock*s to compare.

Upon reply, `dp_Res1` shall be set to `DOSTRUE` if the two locks are on the same object, and in that case, `dp_Res2` shall be set to 0. If the two locks are on two different objects, then `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` shall also be set to 0. On error, `dp_Res1` is set to 0 and `dp_Res2` to an error code<sup>3</sup>.

## 12.4.8 Changing the Mode of a Lock or a File Handle

The packet `ACTION_CHANGE_MODE` changes the access mode of a lock or a file handle, thus potentially granting exclusive access — if possible — or lowering the rights to shared access.

**Table 76:** `ACTION_CHANGE_MODE`

| DosPacket Element    | Value  |
|----------------------|--|
| <code>dp_Type</code> | <code>ACTION_CHANGE_MODE (1028)</code>       |
| <code>dp_Arg1</code> | Object type from table 14                    |
| <code>dp_Arg2</code> | BPTR to <i>FileLock</i> or <i>FileHandle</i> |
| <code>dp_Arg3</code> | Target mode                                  |
| <code>dp_Res1</code> | Boolean result code                          |
| <code>dp_Res2</code> | Error code                                   |

This packet implements the `ChangeMode()` function of the *dos.library* and thus changes the access mode of files or locks to exclusive or shared access mode.

`dp_Arg1` identifies the object whose mode is to be changed. This is a value from table 14, i.e. either `CHANGE_LOCK` to adjust the type of the lock, or `CHANGE_FH` to change the access mode of a file handle.

`dp_Arg2` is the BPTR to the object whose mode is to be changed. If `dp_Arg1` is `CHANGE_LOCK`, this is a BPTR to a *FileLock* structure, if `dp_Arg1` is `CHANGE_FH`, it is a BPTR to a *FileHandle* structure. Note that this is unusual as files are typically identified by their `fh_Arg1` element and not by the handle itself. This packet is an exception.

<sup>3</sup>The documentation in [1] on `dp_Res1` is incorrect.

dp\_Arg3 is the target mode. This is either `SHARED_LOCK` for shared access to the file or the lock, or `EXCLUSIVE_LOCK` for exclusive access to the file or the lock<sup>4</sup>. However, as information on this packet is sparse and application programs can call the corresponding `ChangeMode()` function with incorrect target modes, *file handlers* should also accept `ACTION_FINDINPUT` and `ACTION_FINDUPDATE` for shared access and `ACTION_FINDOUTPUT` for exclusive access.

Note that it is not always possible to change the mode of a lock or a file to exclusive access, namely if it is accessed by a second file handle or locked a second time. This packet shall then fail.

Upon reply, dp\_Res1 shall include a boolean success indicator, `DOSTRUE` for success or `DOSFALSE` for failure. In the former case, dp\_Res2 shall be 0, in the latter case, it shall contain an error code.

## 12.4.9 Releasing a Lock

The packet `ACTION_FREE_LOCK` releases a lock on a file system.

**Table 77:** `ACTION_FREE_LOCK`

| DosPacket Element | Value                              |
|-------------------|------------------------------------|
| dp_Type           | <code>ACTION_FREE_LOCK</code> (15) |
| dp_Arg1           | BPTR to <i>FileLock</i>            |
| dp_Res1           | Boolean result code                |
| dp_Res2           | Error code                         |

This packet implements the *dos.library* function `UnLock()` and releases a *FileLock*. A BPTR to the lock to release is provided in dp\_Arg1. If this argument is `ZERO`, the *file system* shall ignore the request and return success.

When replying this packet, dp\_Res1 shall be set to `DOSTRUE` on success and `DOSFALSE` on error. On success, dp\_Res2 shall be set to 0, otherwise it shall be set to an error code. There are actually few reasons why this packet could fail, probably because the passed in BPTR is invalid and does not point to a valid *FileLock*. The `UnLock()` function does not return this result code, but adjusts `IoErr()` according to dp\_Res2.

## 12.5 Packets for Examining Objects

The packets in this section implement the functions of section 6.1 on packet level, i.e. they retrieve information from the file system on the metadata of objects and allow to scan all objects of a directory. Unfortunately, the packets in this section are the hardest to implement in a robust way as the directory contents can change while a directory scan is active, e.g. because files or directories are created or deleted.

### 12.5.1 Examining a Locked Object

The `ACTION_EXAMINE_OBJECT` packet retrieves metadata such as file name, comment and protection bits from a lock on an object on a file system and fills a *FileInfoBlock* with this data.

**Table 78:** `ACTION_EXAMINE_OBJECT`

| DosPacket Element | Value                                    |
|-------------------|--|
| dp_Type           | <code>ACTION_EXAMINE_OBJECT</code> (23)  |
| dp_Arg1           | BPTR to <i>FileLock</i>                  |
| dp_Arg2           | BPTR to a <i>FileInfoBlock</i> structure |
| dp_Res1           | Boolean result code                      |
| dp_Res2           | Error code                               |

<sup>4</sup>The information in [1] is incorrect on this subject matter.

This packet implements the `Examine()` function of the *dos.library* and retrieves meta-information on the object represented by the lock in `dp_Arg1`. This information is provided in a `FileInfoBlock` structure that is documented in section 6.1.

However, as the AmigaDOS handler design is due to historic reasons based on BCPL, small differences exist between how this packet operates and how the `Examine()` function provides its results to the caller. In specific, the `fib_FileName` and `fib_Comment` elements shall be filled with a BSTRs, i.e. the first character is the length of the file name or the comment. The conversion to a NUL-terminated C string is performed by the *dos.library*.

The elements `fib_DirEntryType` and `fib_EntryType` shall be filled with the same value as some programs check one and others the other element. In particular, the value filled in shall be taken from table 19. The value 0 shall be avoided as some programs check for directories by testing against a positive value whereas some others check for a non-negative value, i.e. accept 0 as a directory.

The fields `fib_OwnerUID` and `fib_OwnerGID` shall be set to 0, unless the file system has an idea on user and group IDs — unfortunately AmigaDOS cannot make use of these values anyhow, and it is not documented how these fields shall be interpreted; they are probably an opaque value. `fib_Reserved` shall be left alone, in particular file systems *shall not* use it to store internal state information. Such information may *only* go into `fib_DiskKey`, which is an element application programs, i.e. callers of the *dos.library*, shall not interpret.

This packet is also used to start a scan over the contents of a directory. In such a case, the examined object is the directory itself, i.e. the lock in `dp_Arg1` is on a directory. As such, the file system should prepare for a scan over this directory and potentially initialize an internal state machine.

This function returns a boolean success code in `dp_Res1`, it shall be either set to `DOSTRUE` in case information on the locked object could be retrieved and had been successfully deposited into the `FileInfoBlock` given by `dp_Arg2`, or shall be set to `DOSFALSE` in case of error. In the success case, `dp_Res2` shall be set to 0, or to an error code otherwise.

## 12.5.2 Scanning Directory Contents

The `ACTION_EXAMINE_NEXT` continues a scan over the directory contents and delivers meta-information on the subsequent entry in a directory. Such a scan is started by an `ACTION_EXAMINE_OBJECT` on the directory to be scanned; the first `ACTION_EXAMINE_NEXT` then provides information on the first entry in this directory and each subsequent packet to the corresponding next entry.

**Table 79:** `ACTION_EXAMINE_NEXT`

| DosPacket Element    | Value  |
|----------------------|--|
| <code>dp_Type</code> | <code>ACTION_EXAMINE_NEXT</code> (24)          |
| <code>dp_Arg1</code> | BPTR to <code>FileLock</code>                  |
| <code>dp_Arg2</code> | BPTR to a <code>FileInfoBlock</code> structure |
| <code>dp_Res1</code> | Boolean result code                            |
| <code>dp_Res2</code> | Error code                                     |

This function continues a directory scan by providing information on the next subsequent object in the directory identified by the lock in `dp_Arg1`. Meta-information on the object itself is copied into the `FileInfoBlock` structure pointed to by the BPTR in `dp_Arg2`. Similar to `ACTION_EXAMINE_OBJECT` discussed in 12.5.1, the file name and comment shall be provided as BSTRs and not as NUL-terminated C strings. Conversion to the latter format is performed within the *dos.library*.

Unlike Unixoid file systems, AmigaDOS does not keep entries in directories that correspond to the directory itself or its parent directory, i.e. AmigaDOS file systems do not carry “.” or “..” directory entries. When parsing paths, the current directory is identified by the empty string, and the parent directory by the isolated slash (“/”).

Unfortunately, this packet is one of the hardest to implement in a file system as the directory may change while the scan is active. In particular, file systems shall handle the situation gracefully in which the object from the previous iteration identified by `fib_DiskKey` has been deleted, moved or replaced by another object, or in which `dp_Arg1` is a different lock than the lock that was used to start the scan by `ACTION_EXAMINE_OBJECT`. The file system may only assume that the lock in `dp_Arg1` is a lock on the same directory on which the scan has been started. Similarly, `dp_Arg2` may have changed from the last iteration, and the file system shall only depend on `fib_DiskKey` and `fib_DirEntryType` being identical compared to the last iteration, all other entries can be potentially trashed or inconsistent. Thus, the file system shall only use these two elements to store state information. Also, file systems shall not depend on application programs scanning directories up to the last entry; application programs can abort a directory scan at an arbitrary point, yet file system shall release all resources required for storing state information of the scan after at least the lock on the scanned directory is released.

A possible implementation strategy is to store full state information in the lock given by `dp_Arg1`, though keep sufficient information in `fib_DiskKey` to rebuild the full information in case the lock is released and replaced during the scan. In the simplest possible case, `fib_DiskKey` could be a counter that enumerates the elements in the directory, whereas the lock contains the full state information to access the element directly. In case the lock is replaced, `ACTION_EXAMINE_NEXT` would find the state information in the lock missing, and would then scan forward to the element enumerated by `fib_DiskKey`. While this is less efficient than using the (now missing) state information in the lock, it will at least provide information on a valid object in the directory. Also, if an object is removed or moved out of the scanned directory, the file system would update the state information kept within the lock to the directory, though losing the lock would at least continue the scan within the directory, even though not necessary from the same object. Storing a block number (for disk-based file systems) or a pointer to an object (for RAM-based file systems) is, however, a bad strategy as the corresponding disk block or RAM location may have found other uses at the time the next object is examined. Unfortunately, such implementation defects are rather common and have been found in multiple file systems of AmigaDOS in the past.

This packet shall provide a boolean success code in `dp_Res1`. In case the next object in a directory could be successfully examined and information on it could be stored in `FileInformationBlock`, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` to 0. In case of an error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code. In case the end of the directory has been reached and no further entries remain to be examined, this error code shall be `ERROR_NO_MORE_ENTRIES`.

### 12.5.3 Examining Multiple Entries at once

The `ACTION_EXAMINE_ALL` packet scans a directory supplying multiple entries at once, potentially filtering entries through a pattern or through a hook.

**Table 80:** `ACTION_EXAMINE_ALL`

| DosPacket Element    | Value                                       |
|----------------------|---|
| <code>dp_Type</code> | <code>ACTION_EXAMINE_ALL</code> (1033)      |
| <code>dp_Arg1</code> | BPTR to <code>FileLock</code>               |
| <code>dp_Arg2</code> | APTR to a buffer to fill                    |
| <code>dp_Arg3</code> | Size of the buffer                          |
| <code>dp_Arg4</code> | Type defining the requested entries         |
| <code>dp_Arg5</code> | Pointer to struct <code>ExAllControl</code> |
| <code>dp_Res1</code> | Continuation flag                           |
| <code>dp_Res2</code> | Error code                                  |

This packet implements the `ExAll()` function of the *dos.library* and thus takes parameters similar to the above function. Note that unlike many other packets, `dp_Arg2` and `dp_Arg5` are regular pointers and

---

not BPTRs<sup>5</sup>. If the *file system* does not implement this packet, i.e. returns `ERROR_ACTION_NOT_KNOWN`, then the *dos.library* emulates it using `ACTION_EXAMINE_OBJECT` and `ACTION_EXAMINE_NEXT`.

`dp_Arg1` is a lock on the directory to be examined.

`dp_Arg2` is a pointer to the buffer to be filled with information on the objects found in the directory, it is *not* a BPTR. This buffer is filled with a singly linked list of `ExAllData` structures, see section 6.1.4 for the definition of this structure. Only the elements requested by `dp_Arg4` are filled, remaining entries are undefined.

`dp_Arg3` is the size of the buffer provided in `dp_Arg2` in bytes.

`dp_Arg4` defines which elements of the `ExAllData` are filled. The encoding of this argument is given by table 21 in section 6.1.4.

`dp_Arg5` is a pointer to a `ExAllControl` structure, also defined in section 6.1.4. A detailed description of this structure is also provided in section 6.1.4. Note that this is really a regular pointer, not a BPTR.

The *file system* shall provide in the `eac_Entries` element of this structure the number of `ExAllData` structures it could fit into the target buffer provided by `dp_Arg2`.

It may store internal state information of the directory scanner in `eac_LastKey`. This state information could, for example, correspond to the `fib_DiskKey` in the `FileInfoBlock` identifying an element in a directory. It is zero-initialized before the first packet, and thus the *file system* may assume that a value of 0 for the key identifies the start of the scan.

If non-NULL, `eac_MatchString` is a parsed pattern as generated by the `ParsePatternNoCase()` function, see section 9.2.2. If this pattern is present, only directory entries whose name matches the pattern shall be filled into the target buffer.

`eac_MatchFunc` provides even finer control of which elements are filled into the target buffer; it supplies a `Hook` structure whose `h_Entry` function is called for each candidate directory entry. If the hook returns non-zero, the `ExAllData` copied to the buffer shall be considered accepted and shall remain in the buffer; if it returns zero, this candidate entry is rejected and will be removed from the final output. Calling conventions of this hook are also described in section 6.1.4.

The same precautions as for `ACTION_EXAMINE_NEXT` hold for this packet, too. In particular, the *file system* shall be prepared for the directory to get modified between scans, by either adding, removing, renaming or moving objects out or into the directory. Using a disk block or a pointer to a structure representing a specific object as `eac_LastKey` is therefore discouraged. Similarly, `dp_Arg1` will be a lock to the same directory, though may not necessarily be the identical lock as used in the previous iteration over the same directory, only the directory that is locked may assumed to be the same. In other words, `eac_DiskKey` shall hold sufficient state information to reconstruct the point from which the scan is to be continued. What is, however, ensured is that the pointer to the `ExAllControl` structure stored in `dp_Arg5` did not change and the *file system* may depend on the pointer having the same value as on a the previous iteration over a directory. Also, *file systems* may depend on the client sending a packet of type `ACTION_EXAMINE_ALL_END` to abort a scan before reaching the end of the directory.

This packet shall be replied with `dp_Res1` set to `DOSTRUE` if not all entries could be fit into the buffer, i.e. if `dp_Arg3` bytes were not sufficient to hold all matching directory entries and at least another iteration over the directory is necessary to supply (some of) the missing entries. In such a case, `dp_Res2` shall also be set to 0. Such an incomplete scan is either continued with another `ACTION_EXAMINE_ALL` packet, or aborted by an `ACTION_EXAMINE_ALL_END` packet.

In case the end of the directory has reached and all directory entries could be supplied, `dp_Res1` shall be set to 0, and `dp_Res2` to `ERROR_NO_MORE_ENTRIES`. In case the directory scan had been aborted due to an error, `dp_Res1` shall be set to 0 and `dp_Res2` to an error code.

---

<sup>5</sup>The information on `dp_Arg5` in [1] is incorrect, it is really a pointer and not a BPTR



### 12.5.4 Aborting a Directory Scan

The packet ACTION\_EXAMINE\_ALL\_END aborts a directory scan started with ACTION\_EXAMINE\_ALL that returned with dp\_Res1 non-zero and thus indicated that the end of the directory has not yet been reached.

**Table 81:** ACTION\_EXAMINE\_ALL\_END

| DosPacket Element | Value                               |
|-------------------|-------------------------------------|
| dp_Type           | ACTION_EXAMINE_ALL_END (1035)       |
| dp_Arg1           | BPTR to FileLock                    |
| dp_Arg2           | APTR to a buffer to fill            |
| dp_Arg3           | Size of the buffer                  |
| dp_Arg4           | Type defining the requested entries |
| dp_Arg5           | Pointer to struct ExAllControl      |
| dp_Res1           | Boolean success flag                |
| dp_Res2           | Error code                          |

This packet implements the ExAllEnd() function of the *dos.library* and aborts a partial directory scan started with ExAll() but for which neither the end of the directory has been reached nor an error code has been received. This packet may be used by an implementing *file system* to release any temporary resources allocated for the purpose of the scan.

dp\_Arg1 is the lock on the directory on which a partial directory scan has been started. It is not necessarily the original lock passed into ACTION\_EXAMINE\_ALL, but a lock on the same directory.

dp\_Arg2 and dp\_Arg3 are a pointer to a buffer and its size. This buffer, however, will not be touched and no data will be deposited there; as this buffer is not necessarily the same as the one for which the scan has been started, this information is likely not very useful, but it is provided here anyhow.

dp\_Arg4 is a type information which would define the information that would go into the buffer provided by dp\_Arg2; however, as this packet does not request to add any data to the buffer, it is probably not very helpful and *file systems* should probably ignore it as no useful decisions can be derived from what the requested information actually was.

dp\_Arg5 is a pointer to a ExAllControl structure, and the pointer provided here is identical to the pointer provided to ACTION\_EXAMINE\_ALL. Thus, *file systems* may use this pointer value and specifically the eac\_DiskKey element therein to release any resources related to this scan.

Before replying this packet, the *file system* shall set dp\_Res1 to a boolean success code whether it could abort the scan. If dp\_Res1 is set to DOSTRUE indicating that the scan was aborted successfully, then dp\_Res2 shall also be set to 0.

If the *file system* does not implement this packet, it shall set dp\_Res1 to DOSFALSE and dp\_Res2 to ERROR\_ACTION\_NOT\_KNOWN. The *dos.library* then (attempts to) emulates this packet by setting the match pattern in the ExAllControl structure to a pattern that matches no entry, and then continues the scan with a ACTION\_EXAMINE\_ALL packet. This would then clearly reach the end of the directory without overrunning the buffer. However, due to a defect in the *dos.library* up to the latest release, the (non-matching) pattern is a literal pattern and not a pre-parsed pattern and thus, actually, could match an entry in the directory. Thus, it is advised to always implement ACTION\_EXAMINE\_ALL\_END if ACTION\_EXAMINE\_ALL is implemented, even if it is just replied with success and no additional resources need to be released.

On any other error, dp\_Res1 shall be set to DOSFALSE and dp\_Res2 to an error code from dos/dos.h.

### 12.5.5 Examining from a File Handle

The ACTION\_EXAMINE\_FH packet provides meta data on an object identified by a *file handle* rather than a *lock*; that is, it uses the (implied) lock of the opened file to retrieve information.

**Table 82:** ACTION\_EXAMINE\_FH

| DosPacket Element | Value                             |
|-------------------|-----------------------------------|
| dp_Type           | ACTION_EXAMINE_FH (1034)          |
| dp_Arg1           | fh_Arg1 of the FileHandle         |
| dp_Arg2           | BPTR to a FileInfoBlock structure |
| dp_Res1           | Boolean result code               |
| dp_Res2           | Error code                        |

This packet implements the `ExamineFH()` function of the *dos.library* and retrieves information on an object from a *file handle* rather than a *lock*.

dp\_Arg1 is a copy of the fh\_Arg1 element of the FileHandle that is to be examined and thus serves to identify the object to be examined<sup>6</sup>.

dp\_Arg2 is a BPTR to a FileInfoBlock structure as documented in section 6.1, and which shall be filled by the *file system* with the information on the object identified by dp\_Arg1. As for the packet type ACTION\_EXAMINE\_OBJECT specified in section 12.5.1, the FileInfoBlock passed out to the caller of the *dos.library* and what the packet shall deliver differ. In specific, fib\_FileName and fib\_Comment shall be BSTRs with the length of the string in the zeroth element, and not NUL-terminated C strings. The conversion to C strings happens within the *dos.library*.

Before replying this packet, the *file system* shall set dp\_Res1 to a boolean result code. On succes, dp\_Res1 shall be set to DOSTRUE and dp\_Res2 to 0. On failure, dp\_Res1 shall be set to DOSFALSE and dp\_Res2 to an error code.

## 12.6 Packets for Working with Links

The packets in this section interact with links; they create them, or in case of soft-links, resolve them and update a path given the link. Section 6.4 provides background information on links and on the interface within the *dos.library* for links.

### 12.6.1 Creating Links

The ACTION\_MAKE\_LINK packet creates a link in a file system.

**Table 83:** ACTION\_MAKE\_LINK

| DosPacket Element | Value                                |
|-------------------|--------------------------------------|
| dp_Type           | ACTION_MAKE_LINK (1021)              |
| dp_Arg1           | BPTR to a FileLock                   |
| dp_Arg2           | BPTR to BSTR of the link to create   |
| dp_Arg3           | BPTR to FileLock or APTR to C-string |
| dp_Arg4           | Type of the link, from table 23      |
| dp_Res1           | Boolean result code                  |
| dp_Res2           | Error code                           |

This packet implements the `MakeLink()` function of the *dos.library* and as such creates soft- or hardlinks within the *file system*.

dp\_Arg1 is a BPTR to a FileLock structure that identifies the directory within which the object is to be created.

dp\_Arg2 is a BPTR to a BSTR that provides the name of the link to be created.

<sup>6</sup>Note, again, that the information in [1] on dp\_Arg1 is incorrect.

---

`dp_Arg3` identifies the target of the link, i.e. the object the link points to. If `dp_Arg4` is `LINK_HARD`, then this argument is a BPTR to a `FileLock` structure identifying the target. If this `FileLock` identifies an object on the same file system as `dp_Arg1`, then a hard link is created. If the object locked by `dp_Arg3` is a file, then the created link will represent a file, otherwise a directory.

Resolution of hard links is up to the *file system*. That is, if the link is accessed, it is up to the *file system* to locate the target of the link and access it instead of the link. Multiple implementation strategies exist for hard links: Either, each object includes a reference count that is incremented for each directory entry pointing to it, that is for each link created; likewise, this counter is decremented each time a directory entry is removed. If the counter reaches 0, the object itself is deleted.

Alternatively, each link is pointing to the linked object, and the object itself contains a list of links that reference it. If a link is deleted, it is removed from its directory and from the list of links within the target object. If the object itself is deleted, one of the links becomes the object itself and the list of links is copied from the deleted object to this link. The FFS follows (mostly for backwards compatibility) this latter approach.

If `dp_Arg4` is `LINK_HARD` and the `FileLock` pointed to by `dp_Arg3` is on a different file system, then an external link shall be created. That is, the *file system* addressed by the packet shall create a file or directory within its own file system in the directory identified by `dp_Arg1`, and this file or directory shall mirror the contents of the link target given by `dp_Arg4` whenever the link or an object within the link is accessed; the file system shall thus implement a “copy on read” for the linked object and all objects within the linked object if this object is a directory.

If the target of such a link is deleted or an object within the linked target, the copy within the *file system* containing the link remains accessible as a regular file or directory. If no copy has been created so far, an attempt to access the linked object fails with `ERROR_OBJECT_NOT_FOUND`.

Currently, only the *RAM-Handler* implements this type of link, and it is there used to realize the `ENV :` assign containing all preferences settings. The external link pulls only those preferences settings into the RAM disk that are actually required, at the time they are required.

If `dp_Arg4` is `LINK_SOFT`, then `dp_Arg3` is a pointer to a NUL-terminated C string providing the target of the link. This string is interpreted as a path name relative to the location of the link source at the time the link is resolved<sup>7</sup>.

Resolution of soft links is performed within the *dos.library* or within the client application as not all functions of the library implement soft link resolution. For a list of functions that *do* implement it, see table 22.

Upon accessing a soft link, or a path containing a soft link, the *file system* shall create an error code `ERROR_IS_SOFT_LINK`. If this error is returned, the sender of a packet accessing the link — thus typically the *dos.library* itself — shall read the target of the link with the `ReadLink()` function specified in section 6.4.2. This function then again contacts the file system containing the link with a `ACTION_READ_LINK` which will construct from the link an updated path to the object.

From this follows that a *file system* is not aware whether the target of a soft link actually exists as it can only provide the path to the object, but not necessarily the object itself; in particular, soft links may cross file system boundaries. If the target of a soft link is deleted, the soft link itself remains and becomes a “dangling” link. When accessing such a link, its resolution fails with an error `ERROR_OBJECT_NOT_FOUND`.

Upon replying the packet, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` to 0 on success. On failure, `dp_Res2` shall be set to `DOSFALSE` and `dp_Res1` to an error code.

## 12.6.2 Resolving a Soft Link

The `ACTION_READ_LINK` packet constructs from a path containing a soft link an updated path by inserting the target of the link.

---

<sup>7</sup>This is quite unusual as AmigaDOS otherwise depends on BSTR representation for packets.

**Table 84:** ACTION\_READ\_LINK

| DosPacket Element | Value                     |
|-------------------|---------------------------|
| dp_Type           | ACTION_READ_LINK (1024)   |
| dp_Arg1           | BPTR to a FileLock        |
| dp_Arg2           | APTR to C string          |
| dp_Arg3           | APTR to buffer            |
| dp_Arg4           | Buffer size               |
| dp_Res1           | Actual buffer size needed |
| dp_Res2           | Error code                |

This packet implements the `ReadLink()` function of the *dos.library* and is used there to resolve soft links and obtain the link target. Implementing this packet correctly requires, however, some care as the soft link may be in the middle of the path provided by `dp_Arg2` and not just its last component, and the soft link itself may be an absolute or relative path. This packet needs to provide from the original path an updated path that points to the intended location relative to the location of the soft link, and not relative to `dp_Arg1`.

`dp_Arg1` is a lock to a directory in the *file system* to which this packet has been send and relative to which the path in `dp_Arg2` shall be interpreted. This *need not* to be the directory containing the link.

`dp_Arg2` is a pointer to a path name containing a soft link on this *file system*. This is, unlike in many other packets, not a BPTR to a BSTR but a pointer to a regular NUL-terminated C string.

The *file system* shall now proceed with soft link resolution as follows: Starting from the directory given by `dp_Arg1`, it shall interpret the path in `dp_Arg2` component by component as explained in section 4.3, until it finds a soft link. That is, colons (":") indicate that the scan should continue at the root directory of the volume, an isolated slash ("/") shall enter the parent directory, and all other components terminated by a slash shall be interpreted as names of directories that shall be recursively entered. This process continues until either the end of the path is found, or — and this is the purpose of this packet — a soft link is detected.

If a soft link is detected as part of the path, the target of the link as stored in the file system shall be read. Note that the link target may not only consist of an isolated file or directory name, but may well be an absolute or relative path that shall be merged with the path provided in `dp_Arg2`.

In particular, if the path stored in the soft link contains a colon (":"), and hence is an absolute path, the components parsed off from `dp_Arg2` up to the detection of the soft link shall be disregarded in order to start from the root directory. If no device or volume name is provided in the absolute link target, the *file system* shall insert the name of the current volume, and a colon, in order to provide an unambiguous anchor of the newly constructed path. The remaining of the path stored in the soft link is then concatenated to this device or volume specification. Finally, the rest of the components from `dp_Arg2` behind the component name of the soft link are concatenated to this intermediate path, forming the final link target.

If the path stored in the soft link is a relative path, then it shall be concatenated to the path from `dp_Arg2` up to the component name of the soft link at which iterating through `dp_Arg2` was interrupted. The remaining components from `dp_Arg2` behind the component name of the soft link is then attached to this intermediate path, forming the final result.

This procedure is tedious, but it ensures that the soft link is interpreted relative to the path from which the client application detected it, even if the soft link is the middle of the supplied path and not contained in the directory provided by `dp_Arg1`. Note that the above algorithm only resolves a single soft link in a path; this is intentional, the *dos.library* will send another ACTION\_READ\_LINK packet to the same or another file system if the remaining path contains additional soft links, or even in case the soft link points to another soft link. It is therefore important at the level of client application — or the *dos.library* — to detect endless loops of soft links pointing to each other. The *dos.library* aborts soft link resolution after 15 links.

`dp_Arg3` is the pointer (not a BPTR) to a target buffer into which the newly constructed path, with the soft link resolved, shall be provided as a NUL-terminated C string.

---

dp\_Arg4 is the size of this target buffer in bytes.

On an error, dp\_Res1 shall be set to  $-1^8$  and dp\_Res2 to an error code. In particular, if the target buffer size dp\_Arg4 is too small to hold the resolved path, dp\_Res2 shall be set to ERROR\_LINE\_TOO\_LONG.

If the source path in dp\_Arg2 does actually not contain a soft link and the scanning algorithm aborted without finding one, this also constitutes an error that shall be reported by setting dp\_Res1 to  $-1$ . This error is not handled consistently in AmigaDOS. The RAM-Handler reports ERROR\_OBJECT\_WRONG\_TYPE, the FFS the error code ERROR\_OBJECT\_NOT\_FOUND. The former error is probably more sensible.

On success, dp\_Res1 shall be set to the length of the constructed path, i.e. to the length of the string in dp\_Arg3 (not including the terminating NUL), and dp\_Res2 to 0.

## 12.7 Packets for Adjusting Metadata

Packets in this section change metadata associated with file system objects, such as name, comment, creation date or protection flags.

### 12.7.1 Renaming or Moving Objects

The ACTION\_RENAME\_OBJECT changes the name of an object such as a file, directory or a link, and relocates it within the directory tree of a volume.

**Table 85:** ACTION\_RENAME\_OBJECT

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_RENAME_OBJECT (17)       |
| dp_Arg1           | BPTR to source FileLock         |
| dp_Arg2           | BPTR to BSTR of the object path |
| dp_Arg3           | BPTR to target FileLock         |
| dp_Arg4           | BPTR to BSTR of the target path |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the `Rename()` function of the *dos.library* and relocates and renames objects within the directory structure of a volume. This packet cannot relocate accross volumes, i.e. dp\_Arg1 and dp\_Arg3 are locks to objects within the same volume, and dp\_Arg2 and dp\_Arg4 represent paths within this volume.

dp\_Arg1 represents the directory to which the source dp\_Arg2 is relative to.

dp\_Arg2 is the path of the original object location. This path need not to consist of a single component, though the object to rename or relocate is the last component of this path. The *file system* needs to walk the provided path, starting from dp\_Arg1, to identify the object that is to be renamed or moved.

dp\_Arg3 is the directory to which the target path dp\_Arg4 is relative to.

dp\_Arg4 is the target path of the object, relative to dp\_Arg3.

Several cases for renaming exist the *file system* shall consider: If the last component does not yet exist within the file system, the object identified by dp\_Arg1 and dp\_Arg2 shall be moved into the directory represented by the second to last component of dp\_Arg4 starting from dp\_Arg3, or directly into dp\_Arg3 if dp\_Arg4 only consists of a single component, and shall be renamed to the last component of the path in dp\_Arg4.

---

<sup>8</sup> [1] recommends to set it to  $-2$  on a target buffer overflow, though currently any negative value will do. Unfortunately, even the latest version of the FFS will *not* return a negative value but 0 in case of an error; this is a defect.

If the object identified by `dp_Arg3` and the path in `dp_Arg4` does already exist and represents a directory, the object shall be moved *into* this directory, retaining its original name.

If the last component does already exist and is a file, and this file is different from the source object, an error shall be generated. Renaming a file or directory to itself, or to a file name that only differs in case shall, however, be accepted, and shall adjust its case (i.e. changing letters in its name to lower or upper case is permissible).

Particular care needs to be taken if the object to be relocated is a directory. In such a case, the *file system* shall test whether an attempt is made to move the object into itself, i.e. into one of the subdirectories of its own. As this would render the directory unreachable, an error shall be generated.

Before replying the packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On error, `dp_Res1` shall be to `DOSFALSE` and `dp_Res2` to an error code.

## 12.7.2 Deleting an Object

The `ACTION_DELETE_OBJECT` removes an object from a directory, releasing the storage it occupies.

**Table 86:** `ACTION_DELETE_OBJECT`

| DosPacket Element    | Value                                  |
|----------------------|--|
| <code>dp_Type</code> | <code>ACTION_DELETE_OBJECT</code> (16) |
| <code>dp_Arg1</code> | BPTR to FileLock                       |
| <code>dp_Arg2</code> | BPTR to BSTR of the object path        |
| <code>dp_Res1</code> | Boolean result code                    |
| <code>dp_Res2</code> | Error code                             |

This packet implements the `DeleteFile()` function of the *dos.library*, which can delete files, directories and links.

`dp_Arg1` is a lock to the directory to which the path in `dp_Arg2` is relative. The `DeleteFile()` function fills it with the current directory of the calling process.

`dp_Arg2` is the path to the object to be deleted. The path can contain multiple components, in which case the file system need to walk the path starting at `dp_Arg1` until reaching its last component which is the object to be deleted. If the target is a directory, the *file system* shall check, in addition, if the directory is empty, and if not so, refuse to delete it.

Before replying the packet, `dp_Res1` shall be set to a boolean success indicator. In case of success, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` to 0. On error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.7.3 Changing the Protection Bits

The `ACTION_SET_PROTECT` changes the protection bits of a file system object.

**Table 87:** `ACTION_SET_PROTECT`

| DosPacket Element    | Value                                |
|----------------------|--------------------------------------|
| <code>dp_Type</code> | <code>ACTION_SET_PROTECT</code> (21) |
| <code>dp_Arg2</code> | BPTR to FileLock                     |
| <code>dp_Arg3</code> | BPTR to BSTR of the object path      |
| <code>dp_Arg4</code> | New protection bits                  |
| <code>dp_Res1</code> | Boolean result code                  |
| <code>dp_Res2</code> | Error code                           |

This packet implements the `SetProtection()` function of the *dos.library*; it changes the protection bits of an object on the file system to that given in `dp_Arg4`. For the definition of protection bits, see section 6.1, table 20. Some *file systems* may support only a subset of all protection bits, or may not be able to carry them on all objects, such as directories; in such a case, they may ignore the request, or may only implement a subset of all bits.

`dp_Arg2` is a lock of a directory which the path in `dp_Arg3` is relative to<sup>9</sup>.

`dp_Arg3` is a path relative to `dp_Arg2` whose last component is the object whose protection bits are to be changed.

`dp_Arg4` are the new protection bits as specified in table 20. Note that the first four bits are shown inverted by most system tools such as the `List` command.

Before replying to this packet, the *file system* shall set `dp_Res1` to a boolean result code. On success, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.7.4 Setting the Comment to an Object

The `ACTION_SET_COMMENT` packet changes, adds or removes a comment on a file system object such as a directory, file or link.

**Table 88:** `ACTION_SET_COMMENT`

| DosPacket Element    | Value                                |
|----------------------|--------------------------------------|
| <code>dp_Type</code> | <code>ACTION_SET_COMMENT</code> (28) |
| <code>dp_Arg2</code> | BPTR to <code>FileLock</code>        |
| <code>dp_Arg3</code> | BPTR to BSTR of the object path      |
| <code>dp_Arg4</code> | BPTR to BSTR of comment              |
| <code>dp_Res1</code> | Boolean result code                  |
| <code>dp_Res2</code> | Error code                           |

This packet implements the `SetComment()` function of the *dos.library* and as such changes, adds or removes a comment on a file, directory or link. Not all file systems will support this request, or may only support comments on a subset of objects.

`dp_Arg2` represents a directory relative to which the path in `dp_Arg3` shall be interpreted.

`dp_Arg3` is the path relative to `dp_Arg2` of the object whose comment is to be changed.

`dp_Arg4` is a BPTR to a BSTR of the new comment to be set. If this string is empty, the comment will be removed.

Before replying to this packet, the *file system* shall set `dp_Res1` to a boolean result code. On success, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.7.5 Setting the Creation Date of an Object

The `ACTION_SET_DATE` packet sets the creation date of an object on a file system.

<sup>9</sup>This not a typo, `dp_Arg1` is really unused

**Table 89:** ACTION\_SET\_DATE

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_SET_DATE (34)            |
| dp_Arg2           | BPTR to FileLock                |
| dp_Arg3           | BPTR to BSTR of the object path |
| dp_Arg4           | BPTR to DateStamp structure     |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the `SetFileDate()` function of the *dos.library* and sets the creation date of an object on a file system. Not all *file systems* will support this packet, or may only support it with reduced precision of the date.

dp\_Arg2 represents a directory relative to which the path in dp\_Arg3 is interpreted<sup>10</sup>.

dp\_Arg3 is the path of the object whose creation date is to be changed. This path shall be interpreted relative to dp\_Arg2, and its last component is the object whose creation date shall be changed.

dp\_Arg4 is a BPTR to a DateStamp structure as specified in section 3 and defines the target date to install for the object.

Before replying to this packet, the *file system* shall set dp\_Res1 to a boolean result code. On success, dp\_Res1 shall be set to DOSTRUE and dp\_Res2 shall be set to 0. On error, dp\_Res1 shall be set to DOSFALSE and dp\_Res2 to an error code.

### 12.7.6 Setting the Owner of an Object

The ACTION\_SET\_OWNER packet sets the owner and group ID of an object in a file system.

**Table 90:** ACTION\_SET\_OWNER

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_SET_OWNER (1036)         |
| dp_Arg2           | BPTR to FileLock                |
| dp_Arg3           | BPTR to BSTR of the object path |
| dp_Arg4           | Owner information               |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the `SetOwner()` function of the *dos.library* and is supposed to set a group and user ID of an object in a file system; the actual encoding of this information is specific to the *file system* and not defined by the *dos.library* or the packet. dp\_Arg4 is a literal copy of the second argument of `SetOwner()`. Note further that most if not all AmigaDOS *file systems* do not implement this packet, and as AmigaDOS is not a multi-user system, the value of this packet is questionable.

dp\_Arg2 represents a directory relative to which the path in dp\_Arg3 is interpreted.

dp\_Arg3 is the path of the object whose owner information is to be changed. This path shall be interpreted relative to dp\_Arg2.

dp\_Arg4 is a *file system* specific owner information; the *dos.library* does not define its meaning. This argument is a verbatim copy of the second argument of `SetOwner()`.

Before replying to this packet, the *file system* shall set dp\_Res1 to a boolean result code. On success, dp\_Res1 shall be set to DOSTRUE and dp\_Res2 shall be set to 0. On error, dp\_Res1 shall be set to DOSFALSE and dp\_Res2 to an error code.

<sup>10</sup>The information in [1] is incorrect, and dp\_Arg1 is, indeed, unused.



## 12.8 Packets for Starting and Canceling Notification Requests

The packets in this section implement notification requests. Once a notification request has been registered, the file system informs a task through a signal or through a message send to a port. Notification requests are explained in section 6.5.

### 12.8.1 Registering a Notification Request

The ACTION\_ADD\_NOTIFY packet registers a notification request at a file system.

**Table 91:** ACTION\_ADD\_NOTIFY

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_ADD_NOTIFY (4097)        |
| dp_Arg1           | APTR to NotifyRequest structure |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the StartNotify() function of the *dos.library*, registering a request at a *file system* to get informed on changes within the file system.

dp\_Arg1 is a C pointer<sup>11</sup> to a NotifyRequest structure that defines the object to be monitored, and the task, signal or message port to be triggered on such changes. This structure is specified in section 6.5.1.

The nr\_FullName element of the NotifyRequest structure is already filled by an absolute path to the object to be monitored which may or may not yet exist. This path is filled in by the *dos.library* within the StartNotify() function from the nr\_Name element and the current directory of the calling process, and the *file system* may depend on this path.

The *file system* should store this request in its internal structures, and then monitor the object identified by nr\_FullName for changes. The following table lists the packets which shall or may trigger a notification request upon a monitored object:

**Table 92:** Packets triggering a Notification

| Packet               | Notes                                  |
|----------------------|--|
| ACTION_WRITE         | After closing the file with ACTION_END |
| ACTION_SET_FILE_SIZE | After closing the file with ACTION_END |
| ACTION_FINDOUTPUT    | After closing the file with ACTION_END |
| ACTION_DELETE_OBJECT | Immediately                            |
| ACTION_SET_DATE      | Immediately                            |
| ACTION_RENAME        | Immediately                            |
| ACTION_SET_COMMENT   | Optionally                             |
| ACTION_SET_PROTECT   | Optionally                             |
| ACTION_SET_OWNER     | Optionally                             |

If the NRF\_NOTIFY\_INITIAL flag is set in nr\_Flags, the *file system* shall send a notification immediately after receiving this packet, regardless of whether or not the object has been modified already. If NRF\_WAIT\_REPLY is set, and a NotifyMessage has already been send out, it shall rather note the modification, though defer any further notification on the same object until the former NotifyMessage has been replied. This avoids queuing up too many notifications at the client port.

A notification event is either signalled through Signal() or by sending a message to a MsgPort:

<sup>11</sup>In [1] this argument is documented to be a BPTR, though this information incorrect.

If `NRF_SEND_MESSAGE` is set in `nr_Flags`, then a `NotifyMessage` is send to the port indicated in `nr_Msg.nr_Port`. This structure is also specified in section 6.5.1. Its `nm_Class` element shall be set to `NOTIFY_CLASS`, and its `nm_Code` element to `NOTIFY_CODE`, both are defined in `dos/notify.h`. In addition, `nm_NReq` shall point to the `NotifyRequest` structure through which the object is monitored. The elements `nm_DoNotTouch` and `nm_DoNotTouch2` may be used for internal administration of the *file system*.

If `NRF_SEND_SIGNAL` is set, then the *file system* should trigger a signal bit on the target task if the monitored object changes by

```
Signal(nr->nr_Signal.nr_Task, 1UL<<nr->nr_Signal.nr_SignalNum);
```

For this method, `NRF_WAIT_REPLY` is, of course, non-functional.

Upon replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.8.2 Canceling a Notification Request

The `ACTION_REMOVE_NOTIFY` packet cancels a notification request and aborts monitoring the object in the `NotifyRequest` structure.

**Table 93:** `ACTION_REMOVE_NOTIFY`

| DosPacket Element    | Value   |
|----------------------|---|
| <code>dp_Type</code> | <code>ACTION_REMOVE_NOTIFY (4097)</code>            |
| <code>dp_Arg1</code> | <b>APTR to <code>NotifyRequest</code> structure</b> |
| <code>dp_Res1</code> | Boolean result code                                 |
| <code>dp_Res2</code> | Error code  |

This packet implements the `EndNotify()` function of the *dos.library* and terminates monitoring the object in `nr_FullName` element of the `NotifyRequest` structure.

`nr_Arg1` is a C-pointer to the structure that indicates which notification request shall be canceled. The `NotifyRequest` structure is specified in section 6.5.1.

If any notifications are still pending, e.g. because the monitored object has already been changed through a file handle though this file handle has not yet been closed, such pending notifications shall be canceled as well. The *file system* shall be aware that even after this packet has been replied, some `NotifyMessages` send out to clients may come back because the client is still working on them. In particular, the memory associated to such messages shall not be released upon receiving the `ACTION_REMOVE_NOTIFY` packet, but only after the `NotifyMessage` has been replied and was received again by the *file system*. The *dos.library* replies all `NotifyMessages` it finds still pending in the port of the client application, but clearly cannot handle those messages that are still being processed.

Upon replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.9 Packets Operating on Entire Volumes

The packets in this section impact the volume mounted on a *file system* in total and do not interact with individual objects, such as files, directories or links on it.

### 12.9.1 Determining the Currently Inserted Volume

The packet ACTION\_CURRENT\_VOLUME determines from a *FileHandle* a BPTR to the *DosList* structure representing the volume on which the file is located.

**Table 94:** ACTION\_CURRENT\_VOLUME

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_CURRENT_VOLUME (7)       |
| dp_Arg1           | fh_Arg1 of a FileHandle or ZERO |
| dp_Res1           | BPTR to DosList structure       |
| dp_Res2           | 0                               |

This packet is not exposed by the *dos.library*, but it used by it when constructing an error requester through its `ErrorReport()` function. If an error is generated by a function taking a *FileHandle* as argument, this function is used to determine the *DosList* entry representing the volume. From there, the name is copied into the requester, for example to ask the user to insert it.

`dp_Arg1` shall be filled with a copy of the `fh_Arg1` element of a *FileHandle* structure, or shall be ZERO. If a handle is provided, a BPTR to the *DosList* of the volume the handle is located on shall be provided in `dp_Res1`. In such case, the packet is safe as the volume entry cannot go away as long as the lock implicit to the handle uses it<sup>12</sup>.

If `dp_Arg1` is ZERO, a BPTR to the *DosList* of the currently inserted volume, or ZERO if no volume is inserted, shall be returned. Unfortunately, as the volume may be ejected any time, it is unclear whether the *DosList* entry provided in `dp_Res1` is still valid at the time it is interpreted by the issuer of of this packet. In such a case, the issuer of the packet should lock the *device list* upfront, and should copy the name before the list is unlocked again, i.e.

```
char name[256];
struct DosList *dl;

LockDosList(LDF_VOLUMES|LDF_READ);
dl = (struct DosList *)BADDR(DoPkt0(port, ACTION_CURRENT_VOLUME));
if (dl) {
    /* dol_Name is always a 0-terminated BSTR */
    strncpy(name, dl->dol_Name + 1, sizeof(name));
    name[sizeof(name)-1] = 0;
} else name[0] = 0;
UnlockDosList(LDF_VOLUMES|LDF_READ);
```

The *file system* shall set `dp_Res1` to a BPTR to the *DosList* entry representing a volume, i.e. an entry on the device list whose `dol_Type` is `DLT_VOLUME` and whose `dol_Task` points to a *MsgPort* of this *handler*. In case no volume is inserted, `dp_Res1` shall be set to ZERO. This packet shall not fail, and `dp_Res2` is ignored by the *dos.library*. For practical purposes, `dp_Res2` shall be set to 0 indicating that no error has been detected.

### 12.9.2 Retrieving Information on a Volume from a Lock

The ACTION\_INFO packet retrieves information on a volume, given a lock on an object on the volume, and provides it in an *InfoData* structure.

<sup>12</sup>In [1], `dp_Arg1` is not mentioned, though providing it is important to avoid a race condition. The RAM-Handler is probably an exception as it only maintains a single volume that cannot go away during its lifetime.

**Table 95:** ACTION\_INFO

| DosPacket Element | Value               |
|-------------------|---------------------|
| dp_Type           | ACTION_INFO (26)    |
| dp_Arg1           | BPTR to FileLock    |
| dp_Arg2           | BPTR to InfoData    |
| dp_Res1           | Boolean result code |
| dp_Res2           | Error code          |

This packet implements the `Info()` function of the *dos.library* and provides information on the volume on which the locked object is located.

`dp_Arg1` is a BPTR to a lock, used to identify a volume from which information is to be requested. If the volume is not inserted, not validated or the lock is invalid, this packet will fail.

`dp_Arg2` is a BPTR to an `InfoData` structure as defined in section 5.2.4 into which information is provided such as the state of the volume, the number of errors detected on it, its capacity and the number of free blocks. Details on this structure are found in section 5.2.4.

Upon replying this packet, `dp_Res1` shall be set to a boolean success indicator that includes the result of the validity test of the lock. If the lock is valid and information on the volume could be retrieved, `dp_Res1` shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

### 12.9.3 Retrieving Information on the Currently Inserted Volume

The `ACTION_DISK_INFO` packet retrieves information on the volume currently mounted by the *file system* (if any) and provides this information in an `InfoData` structure.

**Table 96:** ACTION\_DISK\_INFO

| DosPacket Element | Value                 |
|-------------------|-----------------------|
| dp_Type           | ACTION_DISK_INFO (25) |
| dp_Arg1           | BPTR to InfoData      |
| dp_Res1           | Boolean result code   |
| dp_Res2           | Error code            |

This packet is currently not exposed by the *dos.library* and must be issued through the packet interface. It is almost identical to `ACTION_INFO`, except that it does not take a lock as argument. Therefore, it always refers to the currently inserted volume, and not to the volume the locked object is located on. Otherwise, the information provided by this packet and `ACTION_INFO` is identical.

This packet is also used to retrieve console specific information from the Con-Handler, and is documented as such again in section 12.11. The elements of the `InfoData` are then interpreted in an alternative way.

`dp_Arg1` is a BPTR to an `InfoData` structure as defined in section 5.2.4 into which information is provided such as the state of the currently inserted volume, the number of errors detected on it, its capacity and the number of free blocks. Details on this structure are found in section 5.2.4.

Upon replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

### 12.9.4 Relabeling a Volume

The `ACTION_RENAME_DISK` packet changes the volume name of a medium.

**Table 97:** ACTION\_RENAME\_DISK

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_RENAME_DISK (9)          |
| dp_Arg1           | BPTR to BSTR of new volume name |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the `Relabel()` function of the *dos.library* and changes the volume name of a medium. As such, it shall also change the name of the `DosList` representing the volume in the *device list*, i.e. adjust the `dol_Name` element of the `DosList` structure. Unfortunately, there is no guarantee that the volume that is inserted in the drive or partition managed by the file system when this packet is issued by the client is identical to the volume in the drive when the file system receives it.

`dp_Arg1` is a BPTR to a BSTR of the new volume name. Relabeling shall be applied on the currently inserted volume.

Before replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

### 12.9.5 Initializing a New File System

The `ACTION_FORMAT` packet initializes a new file system on a disk, writing all administration information on it represting a blank volume. It therefore deletes all information stored previously on the medium, drive or partition.

**Table 98:** ACTION\_FORMAT

| DosPacket Element | Value                           |
|-------------------|---------------------------------|
| dp_Type           | ACTION_FORMAT (1020)            |
| dp_Arg1           | BPTR to BSTR of new volume name |
| dp_Arg2           | Dos type or other private data  |
| dp_Res1           | Boolean result code             |
| dp_Res2           | Error code                      |

This packet implements the `Format()` function of the *dos.library*. It performs a soft-initialization of the drive, medium or partition currently inserted into the drive. Note, however, that it does not perform a low-level formatting, such as creating sectors on a floppy disk or issuing a low-level SCSI command. If this is intended, it must be performed by a client application, e.g. the `Format` command of the workbench disk. This packet only writes administrative information on a volume representing it in empty state. This packet is probably the only one that should be used while a *file system* is inhibited and would usually refuse to alter any information on disk, see also section 12.9.6.

`dp_Arg1` is a BPTR to a BSTR of the volume name the medium, partition or drive shall be given<sup>13</sup>. Typically, this packet will be issued while the drive is inhibited, and thus the `DosList` structure representing the volume will be created or updated at the time the *file system* is uninhibited. Otherwise, if the handler also allows an `ACTION_FORMAT` while not being inhibited, it should update the `DosList` immediately, in particular its `dol_Name`, to the name given by this argument.

`dp_Arg2` is *file system* specific information that may be used to define its flavour. For example, `dp_Arg2` carries for the FFS the `DosType`, which shall be one of the values documented in table 27 in section 8.1.3. If such a change of the `DosType` also happens, and the handler allows formatting while not being inhibited, the `de_DosType` in the environment vector linked through `dol_DosType` shall be updated as well. Otherwise,

<sup>13</sup>The information in [1] that the new volume name is in `dp_Arg2` and the `DosType` is in `dp_Arg3` is incorrect.

this update will happen when the *file system* is uninhibited. The `Format()` function will take `dp_Arg2` from its third argument.

Before replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.9.6 Inhibiting the File System

The `ACTION_INHIBIT` packet disables or enables access of the *file system* to the underlying device; once file system access is disabled, application programs such as `Format` may access the underlying device directly.

**Table 99:** `ACTION_INHIBIT`

| DosPacket Element    | Value                            |
|----------------------|----------------------------------|
| <code>dp_Type</code> | <code>ACTION_INHIBIT</code> (31) |
| <code>dp_Arg1</code> | Inhibit flag                     |
| <code>dp_Res1</code> | Boolean result code              |
| <code>dp_Res2</code> | Error code                       |

This packet implements the `Inhibit()` function of the *dos.library*. An inhibited file system is blocked from accessing its underlying medium for read and write access, with the exception of `ACTION_FORMAT` which remains operational. An inhibited file system changes its disk type as reported by `ACTION_INFO` or `ACTION_DISK_INFO` in the `InfoData` structure to 'BUSY', see table 18 in section 5.2.4.

Once the file system is uninhibited again, it shall perform a validation of the medium, as if the medium was been re-inserted. This is necessary because an application bypassing the file system to access it directly could have changed the file system structure, the volume name or the date, or may have even written a completely new file system structure to it. This check thus implies checking the flavour of the file system, e.g. the `DosType` for the FFS, and potentially creating and inserting a `DosList` entry into the *device list* representing the volume. Thus, first inhibiting and uninhibiting a file system is equivalent to simulating a medium change; in fact, the `DiskChange` command enforces a medium change by first inhibiting and then uninhibiting the file system.

`id_Arg1` is a boolean indicator that defines whether the file system shall be inhibited or uninhibited. If `dp_Arg1` is `DOSFALSE`, the file system is uninhibited and a file structure check shall be performed. In all other cases, the file system shall be inhibited and, with the exception of `ACTION_FORMAT`, should refrain from accessing the medium, partition or device.

Before replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.9.7 Write Protecting a Volume

The `ACTION_WRITE_PROTECT` packet enables or disables a software write-protection on the currently inserted medium, thus disallowing any write access through the file system on it.

**Table 100:** `ACTION_WRITE_PROTECT`

| DosPacket Element    | Value                                    |
|----------------------|--|
| <code>dp_Type</code> | <code>ACTION_WRITE_PROTECT</code> (1023) |
| <code>dp_Arg1</code> | Write protection flag                    |
| <code>dp_Arg2</code> | Password hash                            |
| <code>dp_Res1</code> | Boolean result code                      |
| <code>dp_Res2</code> | Error code                               |

This packet is not exposed by any function of the *dos.library*, though the `LOCK` command of the workbench uses this packet to enable or disable write protection on media. Optionally, write protection may be secured by a password of which only an integer hash key is provided to the file system. To re-enable write access, the file system shall check whether the password hash supplied matches the one when setting the write protection, and shall refuse to unblock it if the password hash keys do not match. How a password hash is computed is irrelevant to the file system, it only checks the keys for enabling and disabling the write protection for equality.

`dp_Arg1` is a boolean indicator that, if non-zero, enables write protection, and if `DOSFALSE` releases it. Any attempt to write data to the protected medium, device or partition shall fail with the error code `ERROR_DISK_WRITE_PROTECTED`, including an attempt to set a write protection on an already write protected file system, regardless of the password key used for re-protection.

`dp_Arg2` is an integer password hash key that is stored internally in the file system when the write protection is set, and compared against if it is to be released again. If the stored password hash is not equal to the original hash, releasing the write protection shall fail with the error code `ERROR_INVALID_COMPONENT_NAME`.

Before replying this packet, `dp_Res1` shall be set to a boolean success indicator. On success, it shall be set to `DOSTRUE` and `dp_Res2` shall be set to 0. On failure, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.9.8 Adjusting the File System Cache

The `ACTION_MORE_CACHE` packet increases or decreases the number of file system buffers.

**Table 101:** `ACTION_MORE_CACHE`

| DosPacket Element    | Value                               |
|----------------------|-------------------------------------|
| <code>dp_Type</code> | <code>ACTION_MORE_CACHE</code> (18) |
| <code>dp_Arg1</code> | Buffer increment                    |
| <code>dp_Res1</code> | Boolean result code                 |
| <code>dp_Res2</code> | Buffer count or error code          |

This packet implements the `AddBuffers()` function of the *dos.library*. It increases or decreases the number of buffers the file system may use to cache data. How exactly a file system uses these buffers and how large these buffers are is specific to the file system implementation and its configuration.

The FFS uses these buffers to temporarily store administrative data such as blocks describing the directory structure or information on which blocks a particular file occupies on disk. Providing additional buffers (within limits) can thus help to improve the performance of a file system by reducing the number of times the underlying device needs to be contacted. The FFS also uses these buffers to store payload data if the source or destination buffer of the client is not reachable by the exec device driver. The `de_Mask` element of the environment vector is used to determine such incompatibilities, see section 8.1.3.

`dp_Arg1` is the increment (or decrement, if negative) of the number of buffers to be added (or removed) from the pool of cache buffers of the file system. File systems may clamp this value to guarantee that a minimum number of buffers are available, or limit the buffer count to a useful value.

If this packet succeeds, the file system shall set `dp_Res1` to `DOSTRUE` and `dp_Res2` to the number of buffers currently allocated. Thus, the current buffer count can be obtained by sending this packet with `dp_Arg1` set to 0. On an error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

## 12.9.9 Check if a Handler is a File System

The `ACTION_IS_FILESYSTEM` tests whether a handler is a file system.

**Table 102:** ACTION\_IS\_FILESYSTEM

| DosPacket Element | Value                       |
|-------------------|-----------------------------|
| dp_Type           | ACTION_IS_FILESYSTEM (1027) |
| dp_Res1           | Boolean result code         |
| dp_Res2           | Buffer count or error code  |

This packet implements the `IsFileSystem()` function of the *dos.library* and tests whether a particular handler provide sufficient services to operate as a *file system*. A file system shall be able to access multiple separate files, shall be able to support locks and shall also be able to examine directories. A file system may be either a flat or a hierarchical file system, i.e. a file system is not required to support multiple directories on a storage medium, device or partition.

This packet does not take any arguments. It shall set `dp_Res1` to `DOSTRUE` and `dp_Res2` to 0 in case the handler qualifies as a file system. In case the handler supports this packet but does not implement a file system, it shall set `dp_Res1` to `DOSFALSE` and `dp_Res2` to 0.

If the handler sets `dp_Res1` to `DOSFALSE` and `dp_Res2` to `ERROR_ACTION_NOT_KNOWN`, then this is an indication that the handler cannot interpret this particular packet. If this secondary result code is identified by the `IsFileSystem()` function, it falls back to a heuristic for determining whether a handler is a file system: It uses `Lock(":", SHARED_ACCESS)`, i.e. `ACTION_LOCATE_OBJECT` on the file system root. If such a lock can be obtained, then this heuristic assumes that the handler is, in fact, a file system.

### 12.9.10 Write all Pending Modifications

The `ACTION_FLUSH` packet instructs the file system to write all pending or cached modifications out to disk<sup>14</sup>.

**Table 103:** ACTION\_FLUSH

| DosPacket Element | Value               |
|-------------------|---------------------|
| dp_Type           | ACTION_FLUSH (27)   |
| dp_Res1           | Boolean result code |
| dp_Res2           | 6 Error code        |

This packet is not exposed by the *dos.library* and thus can only be send manually through the packet interface, e.g. `DoPkt()`. File systems may cache writes in order to improve their performance, and may defer any write operations an arbitrary amount of time. This packet instructs the file system to write out all modifications immediately.

This packet shall not be replied before all changes have been written and, if applicable, the drive motor has been turned off. However, FFS versions of V40 and before replied `ACTION_FLUSH` immediately and thus only established a write barrier. This was fixed in V43.

Even though it is unclear how clients could make use of the result code, file systems should set `dp_Res1` to `DOSTRUE` and `dp_Res2` to 0 on success<sup>15</sup>. In case of error, file systems should set `dp_Res1` to `DOSFALSE` and `dp_Res2` to an error code.

## 12.10 Packets for Interactive Handlers

The packet types documented in this section are specific for handlers that interact with the environment of the computer system. Examples for interactive handlers are the Con-Handler interacting with the user

<sup>14</sup>Users of unixoid systems may consider this as the AmigaDOS equivalent of `sync`.

<sup>15</sup>The official reference [1] only states that `dp_Res1` shall be set to `DOSTRUE`. This is probably what most AmigaDOS file systems implement, though the value of unconditionally indicating success is questionable.



through a window, the Aux-Handler which makes a console available through the serial port, and the Port-Handler which reads and writes data through the serial or parallel port and also makes the printer accessible to AmigaDOS.

### 12.10.1 Waiting for Input Becoming Available

The packet ACTION\_WAIT\_CHAR waits for characters becoming available on an interactive *handler*.

**Table 104:** ACTION\_WAIT\_CHAR

| DosPacket Element | Value                 |
|-------------------|-----------------------|
| dp_Type           | ACTION_WAIT_CHAR (20) |
| dp_Arg1           | Timeout in ticks      |
| dp_Res1           | Boolean result code   |
| dp_Res2           | Error code            |

This packet implements the `WaitForChar()` function of the *dos.library*. As such, it checks whether (interactive) input is available to satisfy a potential `Read()`. Note that this packet does not receive an indicator of a file handle, thus even if input is available, it is not specified which ACTION\_READ packet will receive the available data.

`dp_Arg1` provides the timeout in ticks, where a tick is 20ms long, see also section 3.

This packet instructs the handler to wait at most `dp_Arg1` ticks. If no input becomes available within this time period, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to 0.

If at least a single character of input becomes available, `dp_Res1` shall be set to `DOSTRUE`. If the handler implements line buffering such as the Con-Handler, then `dp_Res2` shall be set to the number of lines available in the input buffer. This feature is, for example, used by the ARExx interpreter. If it does not implement line buffering, `dp_Res2` should be set to 0.

In case of an error, `dp_Res1` shall be set to `DOSFALSE` and `dp_Res2` to an error code.

### 12.10.2 Setting the Line Buffer Mode

The ACTION\_SCREEN\_MODE packet changes the buffer mode of an interactive console and disables or enables line buffering.

**Table 105:** ACTION\_SCREEN\_MODE

| DosPacket Element | Value                    |
|-------------------|--------------------------|
| dp_Type           | ACTION_SCREEN_MODE (994) |
| dp_Arg1           | Buffer mode              |
| dp_Res1           | Boolean result code      |
| dp_Res2           | Error code               |

This packet is not exposed by the *dos.library*; it must be issued manually through the packet interface, e.g. through `DoPkt()`.

The purpose of this packet is to adjust the buffer mode of a console. The CON-Handler, responsible for all types of consoles, serves both the CON:, the RAW: and (through an indirection layer) the AUX: device, all of which are incarnations of the same handler configured differently, more on the CON-Handler in section 12.11.

In particular, CON: and RAW: interact with the user through a window of the graphical user interface; they are just two modes of the in total three modes of the console. With this packet, a CON: window can be converted into a RAW: window and vice-versa, and into a third type of window for which no distinct device name exists.

The same type of mode switch can also be performed for the serial terminal represented by the `AUX:` window, which also exists in three modes in total, though usually only one of them is exposed to the user as `AUX:` device. This packet makes two additional configurations of the serial console available.

`dp_Arg1` defines the mode into which the console shall be switched. In total three modes are available, regardless whether the console is a graphical console in a window or a serial console on an external terminal:

**Table 106: Console Modes**

| Buffer Mode      | Description             |
|------------------|-------------------------|
| 0                | Cooked mode             |
| 1                | Raw mode                |
| 2                | Medium mode             |
| All other values | Reserved for future use |

In the *cooked mode*, the console buffers entire lines, provides line-editing features, but only makes the input data available when the user terminates the line with the `RETURN` key. The `CON:` device operates by default in this mode, but can be switched to any other buffer mode with this packet.

In the *raw mode*, every single keystroke is made available, including control sequences corresponding to all cursor and function keys. That implies, however, that line editing is not available and pressed keys are not echoed on the console, but rather transmitted to a client application. This mode corresponds to the `RAW:` device which is nothing but a console operating in this mode by default.

In the *medium mode*, the console also buffers lines, but some keystrokes are directly transmitted without requiring the user to press the `RETURN` key. In specific, key-combinations of the up- and down cursor keys and the `TAB` key are reported immediately to the caller through control sequences. The Amiga Shell uses this mode to offer a history and provides through it `TAB` expansion of commands and command line arguments. No device name corresponds to this mode; instead, the Shell switches a regular `CON:` window to this mode in order to offer additional services. Section 12.11 provides details.

Only values between 0 and 2 shall be provided in `dp_Arg1`; all other values are reserved for future use and may or may not correspond to modes that are currently not documented. The console does not generate an error if an invalid mode is requested, but may interpret this mode change request in an unexpected way.

Before replying this packet, the console shall set `dp_Res1` to `DOSTRUE` and `dp_Res2` to 0 in case the mode switch could be performed. Otherwise, if the mode switch is not possible, the console shall set `dp_Res1` to `DOSFALSE` and `dp_Res2` to 0.

## 12.11 The Console-Handler

The `Console-Handler` uses the following conventions for `dol_Startup`:

**Table 107: Console Handler Startup Code**

| <code>dol_Startup</code>              | Description  |
|---------------------------------------|--|
| < 0                                   | <code>RAW:</code> unprocessed keystrokes, within an intuition window pointed to by <code>dp_Arg1</code>  |
| 0                                     | <code>CON:</code> processed keystrokes, create a new window  |
| 1                                     | <code>RAW:</code> unprocessed keystrokes, create a new window  |
| 2                                     | <code>CON:</code> processed keystrokes with special CSI codes for history and <code>TAB</code> Expansion |
| 3                                     | <code>RAW:</code> reserved for future extensions   |
| <code>BPTR</code> with bit 30 cleared | <code>CON:</code> open on a device specified by a <code>FileSysStartupMsg</code>                         |
| <code>BPTR</code> with bit 31 set     | <code>RAW:</code> open on a device specified by a <code>FileSysStartupMsg</code>                         |

---

## 12.12 The Port-Handler

The `Port-Handler` uses the following conventions for `dol_Startup`:

**Table 108: Port Handler Startup Code**

| <code>dol_Startup</code> | Description   |
|--------------------------|---|
| 0                        | SER: serial output through the <code>serial.device</code>             |
| 1                        | PAR: parallel output through the <code>parallel.device</code>         |
| 2                        | PRT: printer output through the <code>printer.device</code>           |
| <i>BPTR</i>              | serial output with parameters from the <code>FileSysStartupMsg</code> |



---

## Chapter 13

# The AmigaDOS Shell

### 13.0.1 Start Programs in a Shell

```
error = SystemTagList(command, tags)
D0          D1          D2

LONG SystemTagList(STRPTR, struct TagItem *)

error = System(command, tags)
D0 D1          D2

LONG System(STRPTR, struct TagItem *)

error = SystemTags(command, Tag1, ...)

LONG SystemTags(STRPTR, ULONG, ...)
```

### 13.0.2 Executing a Program in a Shell (Legacy)

```
success = Execute( commandString, input, output )
D0      D1      D2  D3

BOOL Execute(STRPTR, BPTR, BPTR)
```

### 13.0.3 Retrieving the CLI

```
cli_ptr = Cli()
D0

struct CommandLineInterface *Cli(void)
```

### 13.0.4 Obtaining the Name of the Current Directory

```
success = GetCurrentDirName(buf, len)
D0          D1      D2

BOOL GetCurrentDirName(STRPTR, LONG)
```

---

### 13.0.5 Set the Current Directory Name

```
success = SetCurrentDirName(name)
D0                                     D1
```

```
BOOL SetCurrentDirName (STRPTR)
```

### 13.0.6 Obtaining the Current Program Name

```
success = GetProgramName(buf, len)
D0                                     D1   D2
```

```
BOOL GetProgramName (STRPTR, LONG)
```

### 13.0.7 Set the Current Program Name

```
success = SetProgramName(name)
D0                                     D1
```

```
BOOL SetProgramName (STRPTR)
```

### 13.0.8 Obtaining the Shell Prompt

```
success = GetPrompt(buf, len)
D0                                     D1   D2
```

```
BOOL GetPrompt (STRPTR, LONG)
```

### 13.0.9 Setting the Shell Prompt

```
success = SetPrompt(name)
D0                                     D1
```

```
BOOL SetPrompt (STRPTR)
```

### 13.0.10 Runs a Command Overloading the Calling Process

```
rc = RunCommand(seglist, stacksize, argptr, argsize)
D0                                     D1       D2       D3       D4
```

```
LONG RunCommand (BPTR, ULONG, STRPTR, ULONG)
```

### 13.0.11 Finding a Shell

```
proc = FindCliProc(num)
D0                                     D1
```

```
struct Process *FindCliProc (ULONG)
```

---

### 13.0.12 Retrieve the Size of the Shell Process Table

```
number = MaxCli()  
D0
```

```
LONG MaxCli(void)
```

### 13.0.13 Request a Function of the Shell

```
ptr = DoShellMethodTagList(method, tags)  
D0 D0 A0
```

```
APTR DoShellMethodTagList(ULONG, struct TagItem *)
```

```
ptr = DoShellMethod(method, Tag1, ...)
```

```
APTR DoShellMethod(ULONG, ULONG, ...)
```

### 13.0.14 Read a Shell Variable

```
len = GetVar( name, buffer, size, flags )  
D0 D1 D2 D3 D4
```

```
LONG GetVar( STRPTR, STRPTR, LONG, ULONG )
```

### 13.0.15 Setting a Shell Variable

```
success = SetVar( name, buffer, size, flags )  
D0 D1 D2 D3 D4
```

```
BOOL SetVar(STRPTR, STRPTR, LONG, ULONG )
```

### 13.0.16 Finding a Shell Variable

```
var = FindVar( name, type )  
D0 D1 D2
```

```
struct LocalVar * FindVar(STRPTR, ULONG )
```

### 13.0.17 Deleting a Shell Variable

```
success = DeleteVar( name, flags )  
D0 D1 D2
```

```
BOOL DeleteVar(STRPTR, ULONG )
```

## 13.1 Parsing Arguments

### 13.1.1 Parsing Command Line Arguments

```
result = ReadArgs(template, array, rdargs)
```

---

D0                                    D1                    D2                    D3

struct RArgs \* ReadArgs(STRPTR, LONG \*, struct RArgs \*)

### 13.1.2 Reading a Single Argument from the Command Line

value = ReadItem(buffer, maxchars, input)

D0                                    D1                    D2                    D3

LONG ReadItem(STRPTR, LONG, struct CSource \*)

### 13.1.3 Finding an Argument

index = FindArg(template, keyword)

D0                                    D1                    D2

LONG FindArg(STRPTR, STRPTR)

### 13.1.4 Releasing the Argument Parser

FreeArgs(rdargs)

D1

void FreeArgs(struct RArgs \*)

### 13.1.5 Initializing a new Shell

flags = CliInitRun( packet )

D0                    A0

LONG CliInitRun( struct DosPacket \* )

### 13.1.6 Finding a Resident Command

segment = FindSegment(name, start, system)

D0                    D1                    D2                    D3

struct Segment \*FindSegment(STRPTR, struct Segment \*, LONG)

### 13.1.7 Adding a Resident Command

success = AddSegment(name, seglist, type)

D0                    D1                    D2                    D3

BOOL AddSegment(STRPTR, BPTR, LONG)

### 13.1.8 Removing a Resident Command

success = RemSegment(segment)

D0                    D1

BOOL RemSegment(struct Segment \*)



---

## 13.2 Miscellaneous Functions

### 13.2.1 Allocating a DOS Object

```
ptr = AllocDosObject(type, tags)
D0          D1      D2

void *AllocDosObject(ULONG, struct TagItem *)

ptr = AllocDosObjectTagList(type, tags)
D0          D1      D2

void *AllocDosObjectTagList(ULONG, struct TagItem *)

ptr = AllocDosObjectTags(type, Tag1, ...)

void *AllocDosObjectTags(ULONG, ULONG, ...)
```

### 13.2.2 Releasing a DOS Object

```
FreeDosObject(type, ptr)
          D1      D2

void FreeDosObject(ULONG, void *)
```

### 13.2.3 Checking for Signals

```
signals = CheckSignal(mask)
D0          D1

ULONG CheckSignal(ULONG)
```

### 13.2.4 Display an Error Requester

```
status = ErrorReport(code, type, arg1, device)
D0          D1      D2      D3      D4

BOOL ErrorReport(LONG, LONG, ULONG, struct MsgPort *)
```

### 13.2.5 Generating an Error Message

```
len = Fault(code, header, buffer, len)
D0          D1      D2      D3      D4

LONG Fault(LONG, STRPTR, STRPTR, LONG)
```

### 13.2.6 Printing an Error Message

```
success = PrintFault(code, header)
D0          D1      D2

BOOL PrintFault(LONG, STRPTR)
```

---

### 13.2.7 Printing a String to the Error Stream

```
error = PutErrStr(str)
D0          D1
```

```
LONG PutErrStr(STRPTR)
```

### 13.2.8 Receive Information when a Volume is Request

```
res = VolumeRequestHook(volume)
D0   D1
```

```
LONG VolumeRequestHook(UBYTE *volume)
```

---

# Bibliography

- [1] Commodore-Amiga Inc: *AmigaDOS Manual, 3<sup>rd</sup> Edition* Random House Information Group (1991)
- [2] Motorola MC68030UM/AD Rev. 2: *MC68030 Enhanced 32-Bit Microprocessor User's Manual, 3<sup>rd</sup> ed.* Prentice Hall, Englewood Cliffs, N.J. 07632 (1990)
- [3] Motorola MC68040UM/AD Rev. 1: *MC68040 Microprocessor User's Manual, revised ed.* Motorola (1992,1993)
- [4] Motorola MC68060UM/AD Rev. 1: *MC68060 Microprocessor User's Manual.* Motorola (1994)
- [5] Motorola MC68000PM/AD Rev. 1: *Programmer's Reference Manual.* Motorola (1992)
- [6] Yu-Cheng Liu: *The M68000 Microprocessor Family.* Prentice-Hall Intl., Inc. (1991)
- [7] Dan Baker (Ed.): *Amiga ROM Kernal Reference Manual: Libraries. 3<sup>rd</sup> ed.* Addison-Wesley Publishing Company (1992)
- [8] Dan Baker (Ed.): *Amiga ROM Kernal Reference Manual: Devices. 3<sup>rd</sup> ed.* Addison-Wesley Publishing Company (1992)
- [9] Dan Baker (Ed.): *Amiga ROM Kernal Reference Manual: Includes and Autodocs. 3<sup>rd</sup> ed.* Addison-Wesley Publishing Company (1991)
- [10] Ralph Babel: *The Amiga Guru Book.* Ralph Babel, Taunusstein (1993)

---

# Index

\* (file name), 16

AbortPkt(), 158

ACCESS\_READ, 40

AChain, 97

ACTION\_ADD\_NOTIFY, 185

ACTION\_CHANGE\_MODE, 172

ACTION\_COPY\_DIR, 170

ACTION\_COPY\_DIR\_FH, 171

ACTION\_CREATE\_DIR, 171

ACTION\_CURRENT\_VOLUME, 187

ACTION\_DELETE\_OBJECT, 182, 185

ACTION\_DISK\_INFO, 188, 190

ACTION\_END, 165

ACTION\_EXAMINE, 174

ACTION\_EXAMINE\_ALL, 175, 176, 177

ACTION\_EXAMINE\_ALL\_END, 176, 177

ACTION\_EXAMINE\_FH, 177

ACTION\_EXAMINE\_NEXT, 174, 175, 176

ACTION\_EXAMINE\_OBJECT, 173, 174, 176, 178

ACTION\_EXAMINE\_OBJECT, 175

ACTION\_FH\_FROM\_LOCK, 164

ACTION\_FINDINPUT, 163, 164

ACTION\_FINDOUTPUT, 164, 185

ACTION\_FINDUPDATE, 164

ACTION\_FLUSH, 192

ACTION\_FORMAT, 189

ACTION\_FREE\_LOCK, 173

ACTION\_FREE\_RECORD, 168

ACTION\_INFO, 187, 188, 190

ACTION\_INHIBIT, 190

ACTION\_IS\_FILESYSTEM, 191

ACTION\_KEY, 165

ACTION\_LOCATE\_OBJECT, 169

ACTION\_LOCK\_RECORD, 167

ACTION\_MAKE\_LINK, 178

ACTION\_MORE\_CACHE, 191

ACTION\_PARENT, 170

ACTION\_PARENT\_FH, 171

ACTION\_READ\_LINK, 179, 179

ACTION\_REMOVE\_NOTIFY, 186

ACTION\_RENAME, 185

ACTION\_RENAME\_DISK, 188

ACTION\_RENAME\_OBJECT, 181

ACTION\_SAME\_LOCK, 172

ACTION\_SCREEN\_MODE, 193

ACTION\_SEEK, 166

ACTION\_SET\_COMMENT, 183, 185

ACTION\_SET\_DATE, 183, 185

ACTION\_SET\_FILE\_SIZE, 167, 185

ACTION\_SET\_OWNER, 184, 185

ACTION\_SET\_PROTECT, 182, 185

ACTION\_WAIT\_CHAR, 193

ACTION\_WRITE, 166, 185

ACTION\_WRITE\_PROTECT, 190

AddBuffers(), 67, 77, 191

AddDosEntry(), 88

AddPart(), 59

AllocDosObject(), 6, 30, 53, 157

AllocMem(), 6

AllocVec(), 6

AnchorPath, 97

Assign, 17, 18

AssignAdd(), 91, 92

AssignLate(), 92

AssignList, 74

AssignPath(), 91

AttemptLockDosList(), 83, 88, 89

Automatic Link Vector (ALV), 147, 147

BADDR(), 6

BCPL stack frame, 105

BPTR, 6, 6, 7

BSTR, 7

ChangeMode(), 172

Close(), 21, 134, 137, 165

CommandLineInterface, 105

CompareDates(), 10

Console, 15

console, 8, 16

CONSOLE (device), 17

CreateDir(), 172

---

CreateNewProc(), 105, 106, *106*, 109  
 CreateProc(), 105, 106, 109, *109*  
 CurrentDir(), 41, 63, 71, 112, *112*  
  
 DateStamp, 9, 10, 51, 57  
 DateStamp(), 9  
 DateTime, *10*  
 DateToStr(), 11  
 Default file system, 8, 19  
 Delay(), *10*  
 DeleteFile(), 56, 182  
 Device List, 16  
 Device list, 18, 47, 187  
 Device name, *16*  
 DeviceProc(), 82, 113  
 DevProc, 80, 81  
 Directory, *19*  
 DoPkt(), 105, *156*, 158  
 DosEnvec, 75  
 DosLibrary, 5  
 DosList, 46, 71, 84, 163  
 DupLock(), 40, 81, 107, 170  
 DupLockFromFH(), 43, 171  
 DupLockFromFile(), 43  
  
 EndNotify(), 63, 65, 186  
 EOF, *15*, 16, 24  
 ERROR\_NO\_FREE\_STORE, 91, 92  
 ERROR\_OBJECT\_EXISTS, 91, 92  
 ERROR\_OBJECT\_NOT\_FOUND, 163  
 ErrorOutput(), 106, *111*  
 ErrorReport(), 105, 187  
 ExAll(), 49, 53, 55, 115, 175, 177  
 ExAllControl, 53  
 ExAllData, *54*  
 ExAllEnd(), 55, 55, 177  
 Examine(), 49, *51*, 52, 53, 57, 174  
 ExamineFH(), 52, 178  
 EXCLUSIVE\_LOCK, 40, 41, 47  
 Exit(), 105, 106, *109*  
 ExNext(), 52, 53, 55, 115  
  
 FGetC(), 29  
 FGets(), 29  
 File, 7, *15*  
 File System, 16, 21  
 FileHandle, 30, 81, 163, 164  
 FileInfoBlock, 49, 52, 56, 96, 98  
 FileLock, 46, 81, 163  
 FilePart(), 59, 60  
 FileSysStartupMsg, 75, 160  
 FindDosEntry(), 72, 83, 84, *84*

Flush(), 27, 27  
 Format(), 189  
 FPrintf(), 33  
 FPutC(), 28  
 Fputs(), 28  
 FRead(), 25, 26, 33  
 FreeDeviceProc(), 81  
 FreeDosEntry(), 89, *90*  
 FreeDosNode(), 89  
 FSkip(), 32  
 FWrite(), 26, 26  
 FWritef(), 34  
  
 GetArgStr(), 117, *117*  
 GetConsoleTask(), 81, 82, 116  
 GetCurrentDir(), *112*  
 GetDeviceProc(), 63, 67, 68, 71, 80, 81–83, 85, 88, 89, 143  
 GetFileSysTask(), 82, 116  
 GetProgramDir(), *117*  
 Global Vector, 34, 35, 104, 110, 135, *143*  
  
 Handler, 15  
 handler, 22  
 Handlers, 21  
 HUNK\_BREAK, 121, *135*  
 HUNK\_BSS, *123*  
 HUNK\_CODE, *123*  
 HUNK\_DATA, *123*  
 HUNK\_DEBUG, *127*  
 HUNK\_DRELOC16, 150  
 HUNK\_DRELOC32, 150  
 HUNK\_DRELOC8, 150  
 HUNK\_END, *128*  
 HUNK\_EXT, 126, 127, *149*, 152  
 HUNK\_HEADER, 121, 122, 131, 134, 146  
 HUNK\_INDEX, 152  
 HUNK\_NAME, *125*, 147  
 HUNK\_OVERLAY, 122, 131, *132*  
 HUNK\_RELOC16, *147*  
 HUNK\_RELOC32, *124*, 148, 149  
 HUNK\_RELOC32SHORT, *124*  
 HUNK\_RELOC8, *147*  
 HUNK\_RELRELOC32, *125*, 147  
 HUNK\_SYMBOL, *126*, 149  
 HUNK\_UNIT, *146*  
 HUNKB\_ADVISORY, *121*  
  
 Info(), 44, 188  
 InfoData, *44*  
 Inhibit(), 67, 190  
 Input(), 104, *110*

---

InternalLoadSeg(), 129, 130, 134, 135, 137  
 InternalUnLoadSeg(), 130, 130, 133, 137  
 IoErr(), 26, 28, 34, 36, 37, 40–43, 46, 52, 56–58, 63,  
     65, 68, 81, 82, 91, 92, 101–104, 112,  
     116, 128, 130, 135, 158, 161  
 IsFileSystem(), 22, 192  
 IsInteractive(), 22, 30  
  
 Level (overlay), 132  
 LoadedSegment, 119  
 LoadSeg(), 115, 119, 120, 128, 129, 130, 135, 136,  
     142, 143, 159  
 LoadSegFuncs, 129  
 Lock, 7, 39, 169  
 Lock (Exclusive), 39  
 Lock (Shared), 39  
 Lock(), 39, 52, 169  
 LockDosList(), 83, 83, 84, 88, 161  
 LockRecord, 35  
 LockRecord(), 36, 168  
 LockRecords(), 36  
 LockRegion(), 37  
 LockRegions(), 37  
  
 MakeDosEntry(), 88, 89, 89, 90, 91  
 MakeDosNode(), 88, 89  
 MakeLink(), 62, 178  
 MatchEnd(), 100  
 MatchFirst(), 96, 99, 100  
 MatchNext(), 99, 99, 100  
 MatchPattern(), 101  
 MatchPatternNoCase(), 101  
 MKBADDR(), 6  
 MODE\_NEWFILE, 21, 43  
 MODE\_OLDFILE, 20, 43, 163  
 MODE\_READWRITE, 21, 43  
 Mount, 17  
  
 NameFromFH(), 58  
 NameFromLock(), 58  
 NewLoadSeg(), 115, 128, 130  
 NextDosEntry, 83  
 NextDosEntry(), 84, 84  
 NIL, 16  
 NotifyMessage, 65  
 NotifyRequest, 63  
 NULL, 7  
  
 Open(), 20, 128, 130, 131, 137, 161, 163, 164  
 OpenDevice(), 75  
 OpenFromLock(), 43, 165  
 Ordinate (overlay), 132  
  
 OutPut(), 28  
 Output(), 105, 111  
 OVTAB, 134  
  
 ParentDir(), 40, 43, 170  
 ParentOfFH(), 43, 171  
 ParsePattern(), 96, 100, 101  
 ParsePatternNoCase(), 53, 96, 101, 176  
 Path, 15  
 path, 7  
 PathPart(), 59  
 Process, 8, 15–19, 103  
 PROGDIR, 18  
 PutStr(), 28  
  
 RawDoFmt(), 34  
 Read(), 22, 30, 67, 165  
 ReadArgs(), 106, 109, 113, 117  
 ReadItem(), 113  
 ReadLink(), 62, 114, 115, 179, 180  
 RecordLock, 36  
 Relabel(), 189  
 RemAssignList(), 92  
 RemDosEntry(), 88  
 Rename(), 56, 61, 181  
 ReplyPkt(), 158  
 Root Directory, 19  
 Run, 31  
 RunCommand(), 109  
 Runtime Binder, 143  
  
 SameDevice(), 42  
 SameLock(), 42, 93  
 ScanStackToken(), 143  
 Seek, 32  
 Seek(), 23, 67, 114, 135, 136, 167  
 SelectError(), 106, 111, 111  
 SelectInput(), 104, 110, 110  
 SelectOutput(), 105, 111, 111  
 SendPkt(), 157  
 SetArgStr(), 117  
 SetComment(), 56, 183  
 SetConsoleTask(), 105, 116  
 SetFileDate(), 57, 184  
 SetFileSize(), 24, 114, 167  
 SetFileSysTask(), 105, 112, 116  
 SetIoErr(), 26, 27, 29, 116  
 SetOwner(), 57, 184  
 SetProgramDir(), 117  
 SetProtection(), 57, 183  
 SetVBuf(), 25, 26, 28  
 SHARED\_LOCK, 40, 41, 47

---

Shell, 143  
Small Data Model, 148  
Small data model, 148  
SplitName(), 60  
StandardPacket, 157  
StartNotify(), 63, 185  
Startup-Sequence, 18  
String, 7  
StrToDate(), 12  
System(), 31, 106  
  
Task, 8  
  
UnLoadSeg(), 130, 133, 134, 137  
UnloadSeg(), 128, 129  
UnLock(), 112, 173  
UnLockDosList(), 84  
UnLockRecord(), 37, 168  
  
VFPrintf(), 33  
VFprintf(), 34  
VFwrite(), 34  
Volume, 16  
Volume name, 17  
  
WaitForChair(), 193  
WaitForChar(), 23  
WaitPkt(), 158  
Write, 23  
Write(), 67, 166  
WriteChars(), 26  
  
ZERO, 7