Self-Supervised Learning for Tumor Segmentation in MRI Scans

2025 3rd International Conference on Computational Intelligence and Network Systems (CINS) | 979-8-3315-8881-6/25/$31.00 ©2025 IEEE | DOI: 10.1109/CINS67018.2025.11412222

[1]Dr.Naim Shaikh,
Global Business School & Research Centre, Tathawade, Pune, Pimpri-Chinchwad, Maharashtra 411033
naim.shaikh@dpu.edu.in

[2*]Mrs. Rani Patil,
Dr. D. Y. Patil School of Science and Technology, Dr. D. Y. Patil Vidyapeeth, Tathawade, Pune, India 411033.
rani.patil@dpu.edu.in

[3]Dr. Juliana R
Professor, Department of Information Technology, Loyola-ICAM College of Engineering and Technology, Chennai, Tamil Nadu, India,
julianar16@gmail.com

[4]Priya L
Department of Electronics and Communication Engineering, Sri Eshwar College of Engineering, Coimbatore, Tamil Nadu, India.
priya.l@sece.ac.in

[5]Ashish Sharma
Department of Computer Engineering & Applications, GLA University, Mathura
ashish.sharma@gla.ac.in

[6]JAYAPAL LANDE
School of Computer Science and Artificial Intelligence, SR University, Warangal - 506371, Telangana, India
jaipal5554@gmail.com

Corresponding Author: rani.patil@dpu.edu.in

***Abstract*-Precise tumor segmentation from MRI scans is an important medical image analysis task, but is generally marred by a lack of annotated datasets to train supervised deep learning algorithms on. To overcome this, the present paper introduces a self-supervised learning (SSL) approach that utilises massive sets of unlabelled MRI scans to pretrain models and then fine-tunes them using small collections of labelled examples. The strategy adopts masked image modeling and contrastive learning as pretext tasks and fine-tunes through a U-Net-based segmentation network. The model is capable of learning spatial and contextual information for tumor detection with this strategy. Experimental results indicate that SSL + Fine-Tuned U-Net performs better than the classical supervised models with a Dice Similarity coefficient of 89.6% and an IoU of 81.4%, and its precision and recall are enhanced. These results suggest that SSL is capable of greatly improving segmentation accuracy and robustness, even from limited amounts of labeled data. This work is a contribution as a scalable and effective methodology towards improving AI-assisted diagnosis in resource-limited clinical settings.**

Keywords-MRI segmentation, self-supervised learning, tumor detection, U-Net, medical image analysis, contrastive learning, deep learning

I. Introduction

Magnetic Resonance Imaging (MRI) is an important diagnostic technique for the detection and follow-up of tumors, especially in the brain and soft tissues [1]. Segmentation of tumors from MRI images with precision is essential for clinical evaluation, treatment planning, and patient follow-up [2]. Supervised learning algorithms and manual annotation are conventional techniques that rely on large image databases annotated by doctors [3]. This is a time-consuming process, and there is always the risk of inter-observer variation that results in divergences of clinical interpretation [4].

Over the last few years, deep learning has gone quite well in medical image analysis, and it has made very nice progress in segmentation and classification [5]. But the problem is here: Deep algorithms need millions of labeled training data and thus become a serious limitation. Labeling medical images, especially 3D MRI volumes, is costly and very time-consuming, and thus is not feasible for large datasets [6]. These constraints maintain writers' attention on learning techniques capable of leveraging unlabeled data, and therefore, self-supervised learning (SSL) has gained considerable attention [7].

Self-supervised learning provides a stable solution by facilitating models to learn useful representations from unlabeled data through pretext tasks [8]. In tumor segmentation, SSL has the potential to pretrain the models using a huge amount of unlabeled MRI scans, before fine-tuning them with a small labeled dataset. [9] The method reduces dependency upon human annotations without compromising high segmentation accuracy [10]. The recent advances in contrastive learning, masked image modeling, and generative SSL have shown potential for capturing structural and semantic information relevant to medical segmentation. As a result, the use of SSL in tumor segmentation pipelines can significantly improve model performance, especially for limited available data [11].

This paper resolves the challenge of accurately delineating tumor contours in MRI slices without using extensive human annotations. Building on self-supervised learning (SSL) approaches, the proposed framework acquires descriptive representations of large amounts of unlabeled MRI scans found in typical clinical archives. These are then tuned on a small labeled set to achieve realistic tumor segmentation with minimal human intervention.

Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.

Motivation for the research comes from the exhaustive time and skill required for manual annotation of tumors, where even experienced radiologists may disagree on boundary delineations. Traditional supervised models perform well with highly annotated data but flounder with sparse data. SSL methods enable models, though, to learn structural boundaries and spatial patterns of lesions autonomously and, in fact, scale back annotation dependence and scale up for clinical applicability.

Recent studies have started exploring this paradigm by pretraining models over huge unlabeled MRI collections and fine-tuning them on small sets of labeled instances. This paper continues along this trajectory, providing a thorough methodological pipeline, experimental analysis, and comparison to assert the dominance of the SSL-based model on accuracy, generalization, and robustness. Lastly, the paper explores how this approach can aid clinical diagnostics and marks out future research horizons for more extensive medical imaging uses.

II. Literature Review

In this existing study, progress on tumor segmentation from MRI has been reviewed and focused specifically on self-supervised and deep learning-based approaches. The survey outlines how increasing interest in accurate and automatic segmentation has driven researchers to investigate data-efficient methods, especially in situations where the availability of annotated data is limited [12]. Special attention is given to research that combines self-supervised learning, transfer learning, and hybrid deep models for enhancing performance in medical image analysis.

The existing study identifies a number of methods created to realize successful AI value alignment, as tabulated in Table 1 Literature Review table. Zhou et al. [13] investigated contrastive learning in conjunction with CNNs and showed increased generalization for brain tumor segmentation. Similarly, Xie et al. [14] used masked image modeling to pretrain transformers and thus partly alleviated dependence on large labeled data. Jiang et al. [15] proposed a self-supervised U-Net model that demonstrated strong performance for various tumor types. Find is also presented as a proof of concept that other researchers like Zeng et al. [16] performed tasks such as jigsaw solving and image inpainting with CNN encoders to retrieve tumor-related features in a weakly-supervised manner. Khan et al. [17] also suggested a transformer-CNN hybrid model, wherein token-based features were found useful for segmenting 3D MRI volumes. All these methods invariably indicate that self-supervised methods not only lessen dependency on labeled data but also promote model generalizability, adaptability, and segmentation accuracy in diverse imaging situations [18].

TABLE I. LITERATURE REVIEW TABLE

Study	Method	Key Finding
[13]	Contrastive learning + CNN	Better generalization in tumor segmentation
[14]	Masked modeling + Transformer	Less need for labeled data, accurate segmentation
[15]	Self-supervised U-Net	Robust across tumor types and scan variations
[16]	Jigsaw + Inpainting (CNN)	Captured tumor context with minimal labels
[17]	CNN-Transformer hybrid	Improved 3D MRI segmentation with token features

Even with the increase in successful applications of self-supervised learning (SSL) to medical image segmentation, it still has some challenges. Some of the key challenges include the fact that there are no standardized pretext tasks specifically designed for medical imaging. While methods such as contrastive learning and masked image modeling have been demonstrated to be effective, they are typically derived from natural image spaces and may not be suited for capturing the nuance of anatomy you might find in MRI scans. Similarly, current SSL approaches suffer from generalizability, as they do not promote high-performance for different imaging modalities, tumor types, and resolutions. Another drawback can be tied to the SSL approaches relying on the quality of pretraining data and hyperparameter tuning, which can lead to a significant impact on the final segmentation result.

One sees a clear gap in the existing there is little work on task-specific SSL methods that are specifically tuned toward volumetric medical imaging, such as 3D MRI. Most research focuses on 2D slice-based techniques, which can potentially lose valuable spatial context. Additionally, although numerous works show better segmentation with SSL, few compare extensively against fully supervised or weakly supervised methods on the same experimental conditions. There also exists a requirement for benchmark datasets and test frameworks specifically tailored to evaluate SSL methods within clinical settings. There is a lack in the existing work with such gaps calling for more tailored SSL frameworks that integrate domain-related knowledge, sound evaluation criteria, and systematic validation over a variety of medical imaging scenarios.

III. Methodology

The proposed approach in this research aims to develop a fast and precise tumor segmentation model for brain MRI scans via self-supervised learning (SSL). In contrast to traditional deep learning techniques that need heavily labeled medical images, the approach utilizes the vast majority of unlabeled medical images to learn relevant features via pretext tasks. With the integration of SSL, the model can learn structural and semantic features of MRI scans from data directly without the need for annotations, thus avoiding the limitation of scarce labeled medical image data. This reduces the burden of annotations for radiologists and facilitates scalable training using large amounts of data. The method is formulated to preserve generalization and clinical validity by progressively fitting the learnt representations to the task of tumor segmentation.

The entire pipeline consists of several interconnected steps: preprocessing of MRI (medical imaging and radiation) scans, self-supervised feature learning, supervised fine-tuning, tumor mapping, and performance evaluation. During the self-supervised stage, the model learns on tasks such as masked image reconstruction or contrastive representation learning. The features are transferred to a supervised fine-tuning stage with a small number of labelled images to tune the model for accurate tumor identification. After this, the tumour segmentation masks can be refined and evaluated using traditional metrics such as the Dice Similarity Coefficient and IoU (Intersection over Union). This approach also improves performance with fewer annotations and is

Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.

robust against variations in tumour and imaging environment. Therefore, there is a high degree of viability for use in an applied medical context, where there is little annotated data available, yet an accurate diagnosis of a patient is required.




Fig.1 Workflow of the proposed methodology

A. MRI Data Pipeline Initialization

The first process is the acquisition of labeled and unlabeled MRI brain scan datasets from open-source databases like the BraTS 2021 dataset, which comprises multi-institutional glioma, meningioma, and pituitary tumor scans. The training and fine-tuning used about 2,500 unlabeled and 300 labeled slices. The images are preprocessed to obtain a balanced and high-quality dataset by intensity normalization to eliminate scanner differences, resizing of the images to a constant size (256 × 256 pixels) compatible with deep learning model inputs, and skull-stripping or artifact removal to separate the brain tissue from non-relevant areas surrounding it. Data augmentation strategies, including rotation (±15°), horizontal and vertical flipping, and contrast modification, are implemented to increase variability and model strength during training. In the case of 3D MRI volumes, slices are sampled along standard axial, coronal, and sagittal planes to create 2D representations; however, it is recognized that such a transformation may result in some loss of volumetric context, which will be remediated in future work using 3D self-supervised modeling. The final goal of this stage is to acquire a clean, standardized, and domain-aligned input dataset appropriate for self-supervised feature learning and subsequent fine-tuning on labeled sets. The result of this block is a structured set of enhanced MRI slices in the form of:

$$X = \{x_1, x_2, x_3, \dots, x_n\} \quad (1)$$

where X It is the set of preprocessed MRI images ready for model input.

B. Feature Discovery via Self-Supervised Pretraining

During SSL pretraining, the model acquired latent feature representations of the unlabeled MRI slices under a masked autoencoding and contrastive learning setup. The pretraining setup consisted of a 0.35 masking ratio, contrast temperature $\tau = 0.1$, batch size of 32, and Adam optimizer with learning rate 1×10^{-4}. These parameters were chosen empirically to trade off convergence speed and stability. In masked image modeling, certain parts of the MRI scans are hidden, and the model learns to reconstruct them, promoting an ability to understand spatial context. In contrastive learning, the model learns to map augmented views of the same image to each other and distinguish them from others. The images are processed through a convolutional neural network (CNN) or transformer-based encoder to yield deep feature embeddings. This procedure enables the model to learn structural and semantic information related to tumor attributes, building a strong base for downstream segmentation.

$$Z = f_\theta(X) \quad (2)$$

Where X represents the preprocessed MRI image input and f_θ It is the self-supervised encoder.

C. Knowledge Transfer through Fine-Tuning

Fine-tuning was done on the labeled subset of 300 MRI slices with supervised segmentation objectives. Pretrained encoder weights were kept frozen in the beginning epochs to preserve learned structural features prior to gradual unfreezing for joint optimization. The training employed early stopping with patience for 10 epochs to avoid overfitting and ensure reproducibility across runs. Following the self-supervised pretraining stage, the learned encoder is then fine-tuned with a reduced labeled dataset in order to make it specifically for tumor segmentation. It does this by transferring the knowledge gained from the unlabeled data into the supervised task. The encoder of the model is kept, and a segmentation head (decoder) is incorporated to learn to predict tumor masks. At training, input MRI scans are fed through the pretrained encoder, and the decoder projects the features learned into pixel-level classifications of tumors. Loss functions, including Dice Loss and Cross-Entropy Loss, are applied to optimize the model against the ground-truth annotations. Fine-tuning not just speeds up convergence but also improves segmentation performance with small amounts of labeled data. This process guarantees that the model is particularly designed to identify the borders of tumors with high precision.:

$$\hat{Y} = g_\emptyset(f\theta(X)) \quad (3)$$

Where X is the labeled input image, is$f\theta$ the pretrained encoder, $g_\emptyset$ Is the segmentation head, and $\hat{Y}$ This is the predicted tumor mask.

D. Tumor Mapping and Prediction Phase

During the Tumor Mapping and Prediction Stage, the encoder-decoder model that has been trained is utilized to segment tumors on unobserved MRI images. The input image is passed to the encoder, which maps the feature representations acquired through the self-supervised pretraining and supervised fine-tuning steps. The features are then passed through the decoder and through several layers to generate a pixel-wise segmentation map that separates tumor tissue from regular tissue. The segmentation result creates a clear visual edge of the tumor, which is more convenient for medical professionals to measure the size, shape, and position of the tumor. Not only does this save time, but it also decreases inter-observer variation in diagnosis.

Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.

To improve precision and clinical application, the post-processing methods of thresholding, noise elimination, and morphological processing can be employed on the predicted masks. The improvements remove false small positive areas and enhance the boundary smoothness, such that the resultant segmentation is sharp and readable. The segmentation output is returned in the form of binary or multi-class masks based on whether or not the classification of the tumor is necessary.

The output of this stage is a sequence of accurate tumor segmentation masks for every input MRI scan. These masks are accurate diagnostic instruments, allowing clinicians to easily identify tumor areas and inform subsequent treatment planning or analysis.

E. Performance Evaluation and Benchmarking

For the Performance Evaluation and Benchmarking phase, the performance of the deployed tumor segmentation model is thoroughly validated using a combination of popular evaluation metrics. DSC, IoU, Precision, Recall, and F1-Score are used as metrics and, in combination, assess the accuracy, overlap, and agreement between expert-ground truth labeling and tumor mask prediction. Dice and IoU measure the overlap extent in space, while Precision and Recall highlight the accuracy with which the model classifies regions of tumors without creating too many false positives and false negatives. They are computed across different test cases for stability and statistical significance.

Additionally, the performance of the model is pitted against conventional fully supervised segmentation models using the same annotated data. Such a comparison highlights the robustness of self-supervised training under constrained annotated data conditions. Particular attention is brought to the extent to which the model is able to generalize to novel MRI scans and maintain top-notch segmentation performance. Qualitative evaluations, such as visual overlays of predictions on MRI slices, complement numerical evaluations by demonstrating real-world utility.

This phase creates an end-to-end performance profile of the model that ensures its stability, accuracy, and clinical deployability, particularly in situations where there are data-scarce environments with not densely filled labeled MRI scans.

IV. Result

The proposed SSL approach to MRI scan tumor segmentation was compared to traditional fully supervised methods based on traditional performance indicators. Experiments were conducted on a standard brain tumor MRI dataset, where only a minute fraction of images were labeled for fine-tuning. Compared to the minimal amount of labeled data, the SSL-based approach demonstrated improved generalization and boundary accuracy performance. The masked image modeling-learned model and contrastive learning outperformed baseline CNNs and U-Nets trained on labeled data alone.


One of the most significant results of the evaluation is that the SSL-pretrained model possessed significantly higher values of Dice Similarity Coefficient (DSC) and Intersection over Union (IoU). It also showed more accuracy in segmenting tumor edges and made fewer positive false predictions. All these optimizations confirm the advantage of using unlabeled data for learning representations. Also, the results highlight how the SSL method is still adaptable to different tumor types and scan quality fluctuations, and therefore is an effective solution for low-annotation cases. The next table provides a comparative study of the technique compared to classical models.

TABLE II. Comparative Performance Analysis of Tumor Segmentation Methods

Method	Dice Similarity (%)	IoU (%)	Precision (%)	Recall (%)
Supervised U-Net	84.2	75.6	82.1	85.3
Supervised CNN	81.7	72.8	80.2	83.0
SSL + Fine-Tuned U-Net (Proposed)	89.6	81.4	87.9	90.2
SSL + CNN Decoder	87.3	79.0	85.5	88.1

Table 2 presents a precise comparison of tumor segmentation performance across various models, including fully supervised architectures and recently introduced self-supervised learning (SSL) based techniques. The performance is evaluated on four key metrics: Dice Similarity, Intersection over Union (IoU), Precision, and Recall, all of which are important in segmentation accuracy and reliability evaluation. The Supervised U-Net also fared relatively well with a Dice value of 84.2% and IoU of 75.6%, as expected given its performance trained on fully labeled data. The Supervised CNN also performed similarly, but with less-than-optimal performance, indicative of the compromise with the lack of big data sets employing only the traditional convolutional models.

In comparison, the designed SSL-based approaches performed significantly under all the measures. SSL + Fine-Tuned U-Net had a better performance than the baselines with 89.6% Dice score and 81.4% IoU, in addition to maximum Precision and Recall values. It indicates improved ability to detect tumor regions in a proper way with reduced false positives and fewer false negatives. The SSL + CNN Decoder also demonstrated significant improvement over its supervised counterpart. These results verify that self-supervised pretraining enables models to learn more substantial feature representations from unlabeled data and improve segmentation performance, even in low-annotation settings that are prevalent in medical imaging.



Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.

Fig.2 Comparative performance analysis of tumor segmentation methods

Figure 2 depicts glioma and meningioma slice segmentation outputs from the BraTS dataset with boundary variations across models.: Dice Similarity, IoU (Intersection over Union), Precision, and Recall (all percentages). Out of these approaches, the proposed SSL + Fine-Tuned U-Net scores the best on all parameters overall. In particular, it exhibits better values in Dice Similarity, Precision, and Recall, which means that it has more precise and consistent tumor segmentation outputs compared to the other methods.

In comparison, Supervised U-Net and Supervised CNN models have relatively lower values, especially in IoU and Recall, meaning lower overlap with the true tumor areas and false negatives. At the same time, SSL + CNN Decoder outperforms the completely supervised approaches, yet is not as good as the introduced SSL + Fine-Tuned U-Net. This indicates that the integration of semi-supervised learning (SSL) and a fine-tuned U-Net architecture effectively boosts the model's generalization ability and segmentation accuracy, and hence it is a good option for tasks such as tumor detection in medical image analysis.

TABLE III. QUANTITATIVE COMPARISON OF TUMOR SEGMENTATION MODELS

Model Type	**Dice Similarity (%)**	**IoU (%)**	**Sensitivity (%)**	**Specificity (%)**
Supervised U-Net	84.2	75.6	86.5	82.3
Semi-supervised Mean Teacher	86.8	78.9	88.2	84.1
SSL + Fine-Tuned U-Net (Proposed)	89.6	81.4	91.5	86.7

Besides Dice and IoU scores, validation through sensitivity and specificity measures also validated the reliability of the model at 91.5% and 86.7%, respectively. These percentages not only verify that segmentation accuracy is improved but also that there is a good balance between detecting true positives and true negatives. The experiments were performed using an NVIDIA RTX 4090 GPU with 24 GB memory at a batch size of 32. Every training run took around 4 hours for SSL pretraining and 1.5 hours for fine-tuning. This indicates that the suggested framework is computationally efficient and can be deployed in real-time or at a hospital scale without undue hardware requirements.




Fig.3 Comparative Performance Metrics of Tumor Segmentation Models

Table 2 and Figure 3 show that the results clearly illustrate that the proposed SSL + Fine-Tuned U-Net makes outstanding gains in segmentation accuracy and generalization. Precisely, the model makes a 5.4% increase in Dice Similarity and a 5.8% increase in IoU over the baseline supervised U-Net. The Semi-supervised Mean Teacher method is better than the baseline but worse than the SSL model, demonstrating the value of leveraging enormous quantities of unlabeled data to achieve stable feature learning. A paired t-test ($p < 0.05$) verified these improvements as statistically significant, which helps ensure that improvements seen are not due to random variability.

V.DISCUSSION

Self-supervised learning (SSL) model for tumor segmentation of MRI images is of great potential to surpass the limitations of conventional supervised techniques. The ability to work with unsupervised data at the pretraining stage of the model allows the model to learn relevant representations that can greatly improve performance during the fine-tuning stage of training the model, even when labeled data is limited. This model solves one of the main issues of medical imaging, i.e., the absence of data, with high accuracy and reliability in segmentation for different MRI scans.

One of the significant advantages of using such an approach is that it generalizes more strongly over shape and size differences of the tumors and even image differences. In addition, while conventional models only have access to the labeled data, the SSL-based model extracts richer contextual and spatial information using contrastive learning and masked image modeling. When mapped to the segmentation task, these features enable more precise demarcation of tumor margins. The comparative evaluation verifies that the SSL model performs equally to or even better than current techniques, particularly in annotation-limited environments.

Although the suggested SSL-based method presented good performance, its institution and tumor type rarity are still issues. Variations in scanner protocols, image quality, and data distribution influence model consistency. Moreover,

Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.

underrepresented tumor classes in pretraining datasets may result in biased segmentation results, suggesting further cross-domain and cross-institutional validation.

VI.CONCLUSION

In this work, a self-supervised learning (SSL) methodology for tumor segmentation in MRI scans is proposed to tackle the key problem of shortages in labeled medical imaging data. Through making use of large numbers of unlabeled MRI data for pretraining, the model learns efficiently spatial and semantic features appropriate for tumor areas prior to fine-tuning on a small annotated set. The approach combines contrastive learning and masked image modeling to facilitate deep feature learning, which is subsequently transferred to the segmentation model of the U-Net architecture. This approach greatly reduces the reliance on costly human annotations and improves the robustness of the model.

The results of experiments convincingly prove the dominance of the newly proposed SSL-based approach. Fine-tuned SSL U-Net yielded 89.6% Dice Similarity and 81.4% IoU, surpassing conventional supervised U-Net and CNN models, which attained Dice values of 84.2% and 81.7%, respectively. Precision and recall also improved significantly, validating the performance of the model in tumor detection with reduced false positives and false negatives. These results reaffirm the viability of self-supervised pretraining to improve generalization to more tumor types and other MRI conditions, and as a tool for clinical practice. However, there are limitations. The model's generalizability can diminish when applied to multimodal MRI data or rare tumors that are undersampled during pretraining. Additionally, success with self-supervised learning is dependent upon the choice of pretext task design. Next steps include the development of standardized benchmark datasets and a suite of SSL testbeds for clinical MRI segmentation so that models can be benchmarked and subsequently validated in other medical settings.

REFERENCES

[1] N. Mittal and S. Tayal, “Advanced computer analysis of magnetic resonance imaging (MRI) for early brain tumor detection,” Int. J. Neurosci., vol. 131, no. 6, pp. 555–570, 2021

[2] S. A. Jalalifar, H. Soliman, A. Sahgal and A. Sadeghi-Naini, “Automatic assessment of stereotactic radiation therapy outcome in brain metastasis using longitudinal segmentation on serial MRI,” IEEE J. Biomed. Health Inform., vol. 27, no. 6, pp. 2681–2692, 2023.

[3] M. Yenugula et al., “A Graph Neural Diffusion Network for Sophisticated Persistent Threat Hunting in IoT Environments,” in 2025 IEEE Conf. Comput. Appl. (ICCA), Yangon, Myanmar, 2025, pp. 1–6, doi: 10.1109/ICCA65395.2025.11011108.

[4] J. M. Webb et al., “Comparing deep learning-based automatic segmentation of breast masses to expert interobserver variability in ultrasound imaging,” Comput. Biol. Med., vol. 139, p. 104966, 2021.

[5] T. Mahmood, A. Rehman, T. Saba, L. Nadeem and S. A. O. Bahaj, “Recent advancements and future prospects in active deep learning for medical image segmentation and classification,” IEEE Access, vol. 11, pp. 113623–113652, 2023.

[6] B. Konda et al., “Homomorphic encryption and federated attribute-based multi-factor access control for secure cloud services in integrated space-ground information networks,” Int. J. Commun. Inf. Technol., vol. 3, no. 2, pp. 33–40, 2022.

[7] J. Gui et al., “A survey on self-supervised learning: Algorithms, applications, and future trends,” IEEE Trans. Pattern Anal. Mach. Intell., 2024.

[8] S. Albelwi, “Survey on self-supervised learning: auxiliary pretext tasks and contrastive learning methods in imaging,” Entropy, vol. 24, no. 4, p. 551, 2022.

[9] A. R. Yadulla, “Leveraging Secure Multi-Party Computation and Blockchain for Collaborative AI in IoT Networks on Cloud Platforms,” J. Recent Trends Comput. Sci. Eng. (JRTCSE), vol. 11, no. 2, pp. 54–59, 2023.

[10] S. Wang et al., “Annotation-efficient deep learning for automatic medical image segmentation,” Nat. Commun., vol. 12, no. 1, p. 5915, 2021.

[11] A. Pati et al., “Artificial Intelligence in improving disease diagnosis,” in Artificial Intelligence in Medicine and Healthcare, pp. 24–49, Jan. 2025, doi: 10.1201/9781003508595-2.

[12] A. Adadi, “A survey on data‐efficient algorithms in big data era,” J. Big Data, vol. 8, no. 1, p. 24, 2021.

[13] T. Zhou, “Multi-modal brain tumor segmentation via disentangled representation learning and region-aware contrastive learning,” Pattern Recognit., vol. 149, p. 110282, 2024.

[14] Z. Xie et al., “On data scaling in masked image modeling,” in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit., 2023, pp. 10365–10374.

[15] J. Jiang, A. Rangnekar and H. Veeraraghavan, “Self-supervised learning improves robustness of deep learning lung tumor segmentation to CT imaging differences,” arXiv preprint, arXiv:2405.08657, 2024.

[16] H. Zheng, J. Bao, Z. Dong and X. Wan, “A data-efficient visual analytics method for human-centered diagnostic systems to endoscopic ultrasonography,” Appl. Intell., vol. 53, no. 24, pp. 30822–30842, 2023.

[17] A. Khan et al., “A recent survey of vision transformers for medical image segmentation,” arXiv preprint, arXiv:2312.00634, 2023.

[18] N. K. C. M., S. R. Addula, R. Seranmadevi and A. K. Tyagi, “Advanced Banking Solutions for Industry 5.0,” in Adv. Bus. Inf. Syst. Anal., pp. 1–24, Aug. 2024, doi: 10.4018/979-8-3693-4187-2.ch001.

Authorized licensed use limited to: East West University. Downloaded on October 04,2026 at 07:44:23 UTC from IEEE Xplore. Restrictions apply.