

SeaCharted — Test Suite Report

Automated coverage for the SeaChartedFunctionality specification

Generated 2026-07-14 · Repo: `~/Developer/SeaCharted` · Branch: `main`

161 tests · 100% pass · 0 failures

152 Jest (unit + component, ~1.5 s) + 9 Playwright E2E (~5 s)

152

Jest tests across 16 suites

9

Playwright E2E across 3 specs

Scope

Coverage was built from `SeaChartedFunctionality.pages` — every numbered feature in the spec has multiple tests, and the universal `#hashtag` rule is exercised at parser, DB-sync, and end-to-end levels.

Coverage by spec section

Spec section	Tests	Test files
§1 Diver profile name, age, dives, cert, nationality, gender, interests, gallery	27	profile/labels.test.ts, profile/getProfile.test.ts, photos/getUserPhotos.test.ts
§2 Dive basics + sites + GPS + map date, max depth, Cozumel sites, GPS coords, site lookup	33	sites/seed-cozumel.test.ts, sites/getSites.test.ts, sites/submitSite.test.ts, dives/getDives.test.ts
§3 Sightings by keyword 7 spec categories, species catalog, seeded species DB	34	species/getSpecies.test.ts, sightings/getSightings.test.ts, migrations/seed_species.test.ts, profile/labels.test.ts
§4 Weather + underwater + moon sky, wind, current, direction, visibility, temp, moon phase	25	dives/moon.test.ts, conditions/openMeteo.test.ts, components/dive/DiveConditions.test.tsx
§5 Observations + universal #hashtag rule disease, anomaly,	28	hashtags/parse.test.ts, hashtags/resolve.test.ts, observations/getObservations.test.ts

Spec section	Tests	Test files
unlisted-species, mating; hashtag parse + DB sync		
Shared picker component (used across §1/§3/§4)	6	components/form/PillSelect.test.tsx
Browser E2E (routes + mocked backends)	9	e2e/research-portal.spec.ts, e2e/landing-map.spec.ts, e2e/auth-gate.spec.ts

Test infrastructure

Config files added

- `jest.config.js` — jest-expo preset, `@/` path alias, CSS stub, transform pattern for RN modules
- `jest.setup.js` — env vars, AsyncStorage/reanimated/expo-glass mocks
- `jest.css-stub.js` — no-op for CSS imports at test time
- `playwright.config.ts` — serves `dist-e2e/` on `:8081`, headless Chromium
- `e2e/mock-supabase.ts` — Playwright route interceptor for Supabase REST + Auth + Storage + Mapbox tiles
- `src/lib/supabase/__mocks__/client.ts` — chainable Jest mock for the supabase client, queryable per test

Dev dependencies added

- `jest`, `jest-expo@57.0.1`, `@types/jest`
- `@testing-library/react-native@14.0.1`, `test-renderer@1` (React-19 replacement for the deprecated `react-test-renderer`)
- `@playwright/test` + Chromium headless

npm scripts

```

npm test          # 152 tests, ~1.5s
npm run test:watch # jest --watch
npm run test:e2e   # 9 tests, ~5s (requires dist-e2e/)
npm run e2e:build  # produce dist-e2e/ with mock env baked in

```

Design decisions

- **External services fully mocked.** Supabase mocked via a chainable jest module mock; Open-Meteo mocked via `global.fetch`; in E2E, all Supabase + Mapbox traffic intercepted by Playwright routes. Zero contamination of the real DB, deterministic runs, offline-safe.
- **Species-catalog verification is structural, not book-content.** Every seeded species must have a valid slug, common name, scientific name, and one of the 7 spec categories; the `source_reference` must cite *Caribbean Reef Life*. Book-exact matching isn't feasible from code.

- **Collocated tests.** `*.test.ts(x)` live next to the code they cover; E2E lives at `e2e/` at repo root.
- **E2E serves a pre-built static export.** Faster and closer to production than a live Expo dev server.

Observations flagged during test authoring

Not test failures — spec/data notes surfaced while reading source

1. The Caribbean Reef Life seed has a few rows where `scientific_name` looks like a common name (e.g. row 32: `'oscillatoria', 'Oscillatoria', 'Red Band', 'invertebrate'` — "Red Band" isn't a scientific name; common name also suggests a plant, not an invertebrate). Tests verify structural invariants only, so these don't fail the suite. Ready to add stricter regex-based data-quality checks on request.
2. Spec §4 says current is "strong, normal, or moderate"; code uses `light / moderate / strong` — `light` plays the "normal" role. Test accepts this mapping.
3. Spec §4 lists sky as "cloudy, rainy, or sunny"; code adds `partly_cloudy` . Superset — accepted.

Environment

Repo	~/Developer/SeaCharted (branch main, clean tree pre-run)
Node / npm	System defaults
Expo	57.0.1
React / React Native	19.2.3 / 0.86.0
Jest	29.7.0 via jest-expo@57.0.1
Playwright	@playwright/test 1.61.1, Chromium 149
Total run time	~7 s combined (Jest 1.5 s + Playwright 5 s + server boot)