Complexity of Jet Reconstruction Algorithms

Sean Ericson

UO
PHYS 662

March 18, 2024

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.
- Outline

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.
- Outline

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.
- Outline
  - Review of jet algorithms

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.
- Outline
  - Review of jet algorithms
  - Measuring Algorithmic Complexity

Complexity of Jet Algorithms

- Jet Reconstruction algorithms are at the core of modern HEP data collection and analysis
- Efficient algorithms are necessary to make analysis of large datasets feasible.
- Outline
  - Review of jet algorithms
  - Measuring Algorithmic Complexity
  - Analysis of FastJet, SISCone, and their predecessors

Review of Jet Algorithms

- Jet algorithm goals:

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets
  - Identify subjets and jet substructure

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets
  - Identify subjets and jet substructure
  - Measure invariant masses of constituent particles

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets
  - Identify subjets and jet substructure
  - Measure invariant masses of constituent particles
  - Identify missing energy/momentum

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets
  - Identify subjets and jet substructure
  - Measure invariant masses of constituent particles
  - Identify missing energy/momentum
- Jets:

Review of Jet Algorithms

- Jet algorithm goals:
  - Combine data from calorimeters and trackers to define jets
  - Identify subjets and jet substructure
  - Measure invariant masses of constituent particles
  - Identify missing energy/momentum
- Jets:
  - A collimated spray of stable particles arising from fragmentation and hadronization of a parton after a collision.

Review of Jet Algorithms (cont.)

Example Jet



Review of Jet Algorithms (cont.)

Considerations

Review of Jet Algorithms (cont.)

Considerations

- Jet size

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)
- Jet shape

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)
- Jet shape
  - Algs with variable jet shape can allow for good resolution of subjets at the expense of greater susceptibility to UE and PU

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)
- Jet shape
  - Algs with variable jet shape can allow for good resolution of subjets at the expense of greater susceptibility to UE and PU
- Infrared and Collinear safety (IRC safety)

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)
- Jet shape
  - Algs with variable jet shape can allow for good resolution of subjets at the expense of greater susceptibility to UE and PU
- Infrared and Collinear safety (IRC safety)
  - Calculated jets should be insensitive to emission of soft radiation from, or collinear splitting of the constituent particles.

Review of Jet Algorithms (cont.)

Considerations

- Jet size
  - Must be large enough to capture all particles for correct p_μ calculation.
  - However, larger jets are more susceptible to underlying events (UE) and pileup (PU)
- Jet shape
  - Algs with variable jet shape can allow for good resolution of subjets at the expense of greater susceptibility to UE and PU
- Infrared and Collinear safety (IRC safety)
  - Calculated jets should be insensitive to emission of soft radiation from, or collinear splitting of the constituent particles.
  - Necessary for faithful comparison of data to experiment

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe
  - Examples include IC-PR, IC-SM, and SISCone.

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe
  - Examples include IC-PR, IC-SM, and SISCone.
- Sequential Clustering Algorithms

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe
  - Examples include IC-PR, IC-SM, and SISCone.
- Sequential Clustering Algorithms
  - Assume particles in jets have small differences in p_t; cluster in momentum space.

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe
  - Examples include IC-PR, IC-SM, and SISCone.
- Sequential Clustering Algorithms
  - Assume particles in jets have small differences in p_t; cluster in momentum space.
  - Automatically IRC safe

Review of Jet Algorithms (cont.)

Class of Jet Algorithms

- Cone Algorithms
  - Assume particles in jets will appear in conical regions; cluster in (η, ϕ)-space.
  - Easy to implement, but typically contain unphysical parameters which hinder analysis
  - Most are not IRC safe
  - Examples include IC-PR, IC-SM, and SISCone.
- Sequential Clustering Algorithms
  - Assume particles in jets have small differences in p_t; cluster in momentum space.
  - Automatically IRC safe
  - Examples include K_t, $\bar{K}_t$, and Cambridge/Aachen

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance
- How can we compare algorithms in a context-independent way?

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance
- How can we compare algorithms in a context-independent way?
  - Big-O Notation! (a.k.a Bachmann-Landau/asymptotic notation)

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance
- How can we compare algorithms in a context-independent way?
  - Big-O Notation! (a.k.a Bachmann-Landau/asymptotic notation)

    $$f(x) \in \mathcal{O}(g(x))_{x \to \inf} \iff \exists c \; \exists x_0 \; \forall x > x_0 : \; |f(x)| \leq cg(x)$$

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance
- How can we compare algorithms in a context-independent way?
  - Big-O Notation! (a.k.a Bachmann-Landau/asymptotic notation)

    $$f(x) \in \mathcal{O}(g(x))_{x \to \inf} \iff \exists c \; \exists x_0 \; \forall x > x_0 : \; |f(x)| \leq cg(x)$$
  - E.g. $\mathcal{O}(\ln(x)) \subset \mathcal{O}(x) \subset \mathcal{O}(x^n) \subset \mathcal{O}(e^x) \subset \mathcal{O}(x!)$

Measuring Algorithmic Complexity

Assymptotics and Big-O Notation

- Algorithm runtime depends on the specific hardware its running on, and on the input to the particular problem instance
- How can we compare algorithms in a context-independent way?
  - Big-O Notation! (a.k.a Bachmann-Landau/asymptotic notation)

    $$f(x) \in \mathcal{O}(g(x))_{x \to \inf} \iff \exists c \; \exists x_0 \; \forall x > x_0 : \; |f(x)| \leq cg(x)$$
  - E.g. $\mathcal{O}(\ln(x)) \subset \mathcal{O}(x) \subset \mathcal{O}(x^n) \subset \mathcal{O}(e^x) \subset \mathcal{O}(x!)$
  - Also, $o()$, $\Theta(x)$, $\Omega()$, $\omega()$ with related definitions

Complexity of K_t (pre-FastJet)

The Naïve Algorithm

Algorithm Naïve K_t

```
repeat
    for particle pair (i, j) do
        d_Bi ← p_ti^2                          ▷ Calculated once for each i
        R_ij^2 ← (η_i − η_j)^2 + (φ_i − φ_j)^2
        d_ij ← min(p_ti^2, p_tj^2) R_ij
    end for
    d_min ← min({d_ij} ∪ {d_Bi})
    if d_min is d_Bi then
        Add particle i to list of jets, remove from list of particles
    else
        Merge particles i, j
    end if
until no particles remain
```

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$
  - Calculation of d_{ij} initially $\mathcal{O}(N^2)$, updates actually $\mathcal{O}(N)$

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$
  - Calculation of d_{ij} initially $\mathcal{O}(N^2)$, updates actually $\mathcal{O}(N)$
  - Determining $d_{\min}$ is $\mathcal{O}(N^2)$

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$
  - Calculation of d_{ij} initially $\mathcal{O}(N^2)$, updates actually $\mathcal{O}(N)$
  - Determining $d_{\min}$ is $\mathcal{O}(N^2)$
  - Merging operation is $\mathcal{O}(1)$

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$
  - Calculation of d_{ij} initially $\mathcal{O}(N^2)$, updates actually $\mathcal{O}(N)$
  - Determining $d_{\min}$ is $\mathcal{O}(N^2)$
  - Merging operation is $\mathcal{O}(1)$
- Full time complexity is therefore

$$\mathcal{O}(N + N^2 + N(1 + N + N^2 + 1)) = \mathcal{O}(N^3)$$

Pre-FastJet K_t Complexity (cont.)

Complexity Analysis

- Outermost loop executes $\mathcal{O}(n)$ times
  - Calculation of d_{Bi} initially $\mathcal{O}(N)$, updates actually $\mathcal{O}(1)$
  - Calculation of d_{ij} initially $\mathcal{O}(N^2)$, updates actually $\mathcal{O}(N)$
  - Determining $d_{\min}$ is $\mathcal{O}(N^2)$
  - Merging operation is $\mathcal{O}(1)$
- Full time complexity is therefore

$$\mathcal{O}(N + N^2 + N(1 + N + N^2 + 1)) = \mathcal{O}(N^3)$$

- Also easy to see that the space complexity is $\mathcal{O}(N^2)$.

Enter: FastJet

Geometric Insight

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:
  - Let $d_{\min} = \min(\{d_{ij}\})$, and let $p_{ti} < p_{tj}$.

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:
  - Let $d_{\min} = \min(\{d_{ij}\})$, and let $p_{ti} < p_{tj}$.
  - Then, $\forall l: \; R_{ij} \leq R_{il}$

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:
  - Let $d_{\min} = \min(\{d_{ij}\})$, and let $p_{ti} < p_{tj}$.
  - Then, $\forall l: \; R_{ij} \leq R_{il}$
- That is, particles i and j are geometric *nearest neighbors*

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:
  - Let $d_{\min} = \min(\{d_{ij}\})$, and let $p_{ti} < p_{tj}$.
  - Then, $\forall l: \; R_{ij} \leq R_{il}$
- That is, particles i and j are geometric *nearest neighbors*
- Therefore, we don't need the $\mathcal{O}(N^2)$ table d_{ij}!

Enter: FastJet

Geometric Insight

- The key to improving K_t is the (rather obvious) geometric insight:
  - Let $d_{\min} = \min(\{d_{ij}\})$, and let $p_{ti} < p_{tj}$.
  - Then, $\forall l: \; R_{ij} \leq R_{il}$
- That is, particles i and j are geometric *nearest neighbors*
- Therefore, we don't need the $\mathcal{O}(N^2)$ table d_{ij}!
- We only need an n-element list of nearest neighbors $d_{i\mathcal{G}_i}$

Complexity of FastJet

The Smart Algorithm

Algorithm `FastJet` K_t

```
for particle i do
    G_i ← nearest neighbor of particle i
    d_iG_i, d_Bi calculated as previously
end for
repeat
    d_min ← min({G_i} ∪ {d_Bi})
    Merge or Remove according to d_min as previously
    Update G_i, d_iG_i, d_Bi.
until no particles remain
```

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.
  - Initial calculation of $d_{i\mathcal{G}_i}$, d_{Bi} is $\mathcal{O}(N)$

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.
  - Initial calculation of $d_{i\mathcal{G}_i}$, d_{Bi} is $\mathcal{O}(N)$
  - Finding $d_{\min}$ takes $\mathcal{O}(N)$ times, repeated $\mathcal{O}(N)$ times.

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.
  - Initial calculation of $d_{i\mathcal{G}_i}$, d_{Bi} is $\mathcal{O}(N)$
  - Finding $d_{\min}$ takes $\mathcal{O}(N)$ times, repeated $\mathcal{O}(N)$ times.
  - Updating $\mathcal{G}_i$, d_{Bi} after a merge or removal takes $\mathcal{O}(N)$ (repeated $\mathcal{O}(N)$ times)

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.
  - Initial calculation of $d_{i\mathcal{G}_i}$, d_{Bi} is $\mathcal{O}(N)$
  - Finding $d_{\min}$ takes $\mathcal{O}(N)$ times, repeated $\mathcal{O}(N)$ times.
  - Updating $\mathcal{G}_i$, d_{Bi} after a merge or removal takes $\mathcal{O}(N)$ (repeated $\mathcal{O}(N)$ times)
    - Updating $\mathcal{G}_i$ in $\mathcal{O}(N)$ is a nontrivial geometric affect

Complexity of FastJet (cont.)

Semi-Naïve Complexity Analysis

- This appears to have a time complexity of $\mathcal{O}(N^2)$:
  - Initial construction of $\mathcal{G}_i$ is $\mathcal{O}(N)$.
  - Initial calculation of $d_{i\mathcal{G}_i}$, d_{Bi} is $\mathcal{O}(N)$
  - Finding $d_{\min}$ takes $\mathcal{O}(N)$ times, repeated $\mathcal{O}(N)$ times.
  - Updating $\mathcal{G}_i$, d_{Bi} after a merge or removal takes $\mathcal{O}(N)$ (repeated $\mathcal{O}(N)$ times)
    - Updating $\mathcal{G}_i$ in $\mathcal{O}(N)$ is a nontrivial geometric affect
- However, we can do better!

Complexity of FastJet (cont.)



Complexity of FastJet (cont.)

Better Complexity Analysis





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$
- Represent $d_{i\mathcal{G}_i}$ as a Red-Black tree





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$
- Represent $d_{i\mathcal{G}_i}$ as a Red-Black tree
  - Constructed in $\mathcal{O}(N \ln(N))$ time





Complexity of FastJet (cont.)

Better Complexity Analysis

- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$
- Represent $d_{i\mathcal{G}_i}$ as a Red-Black tree
  - Constructed in $\mathcal{O}(N \ln(N))$ time
  - Dynamic updates and searching in $\mathcal{O}(\ln(N))$





Complexity of FastJet (cont.)

Better Complexity Analysis





- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$
- Represent $d_{i\mathcal{G}_i}$ as a Red-Black tree
  - Constructed in $\mathcal{O}(N \ln(N))$ time
  - Dynamic updates and searching in $\mathcal{O}(\ln(N))$
  - Searches/updates occur $\mathcal{O}(N)$ times; $\mathcal{O}(N \ln(N))$ operations total

Complexity of FastJet (cont.)

Better Complexity Analysis





- A Voronoi diagram for NN calculations
  - Constructed in $\mathcal{O}(n \ln(N))$ time
  - Allows for calculation of $\mathcal{G}_i$ in $\mathcal{O}(N)$
  - Dynamic updates in $\mathcal{O}(\ln(n))$
- Represent $d_{i\mathcal{G}_i}$ as a Red-Black tree
  - Constructed in $\mathcal{O}(N \ln(N))$ time
  - Dynamic updates and searching in $\mathcal{O}(\ln(N))$
  - Searches/updates occur $\mathcal{O}(N)$ times; $\mathcal{O}(N \ln(N))$ operations total
- Total time complexity: $\mathcal{O}(N \ln(N))$.

Complexity of IC-SM

A Naïve Cone-Finding Algorithm

Algorithm Iterative Cone with Split-Merge

```
repeat
    p_t^* ← max({p_ti})                                   ▷ seed axis
    repeat
        p_j ← sum of momenta of particles within R of seed axis
        if p_t^* == p_j then
            Label p_t^* a protojet, remove all particles
        else
            p_t^* ← p_j
        end if
    until The jet axis and seed axis coincide
until No seeds remain
Run Split-Merge on the protojets
```

Complexity of IC-SM

The Split-Merge Procedure

Algorithm Split-Merge

```
Remove all protojets with p_t < p_{t,cut}
repeat
    Determine hardest protojet i
    Determine hardest protojet j such that i and j share particles
    if no such j exists then
        i is a final jet; remove particles
    else
        if p_{t,shared} < f × p_{tj} then
            Split particles between protojets
        else
            Replace i and j with their merger
        end if
    end if
until no protojets left
```

Complexity of IC-SM

Complexity Analysis

Complexity of IC-SM

Complexity Analysis

- Stable cone production

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!
- Split-Merge

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!
- Split-Merge
  - Determining hardest protojet takes $\mathcal{O}(N)$

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!
- Split-Merge
  - Determining hardest protojet takes $\mathcal{O}(N)$
  - Finding hardest overlapping jet takes $\mathcal{O}(N/n)$, repeated $\mathcal{O}(N)$ times.

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!
- Split-Merge
  - Determining hardest protojet takes $\mathcal{O}(N)$
  - Finding hardest overlapping jet takes $\mathcal{O}(N/n)$, repeated $\mathcal{O}(N)$ times.
  - Merging takes $\mathcal{O}(Nn)$

Complexity of IC-SM

Complexity Analysis

- Stable cone production
  - Process of finding a stable cone from a seed roughly $\mathcal{O}(Nn)$ where n is the average particle count in a circle of radius R
  - This is repeated $\mathcal{O}(N)$ times.
  - Codes MCFM and NLOJet implement this in $\mathcal{O}(N2^N)$ by iterating through all possible cones!!
- Split-Merge
  - Determining hardest protojet takes $\mathcal{O}(N)$
  - Finding hardest overlapping jet takes $\mathcal{O}(N/n)$, repeated $\mathcal{O}(N)$ times.
  - Merging takes $\mathcal{O}(Nn)$
- Total complexity: $\mathcal{O}(N^2 n)$ (can be optimized to $\mathcal{O}(N^2)$ with 2D tree data structures)

Complexity of SISCone

Improved Cone-Finding



SISCone's geometric approach to seedless cone-finding.

Complexity of SISCone

Improved Cone-Finding



SISCone's geometric approach to seedless cone-finding.

- SISCone again uses geometric insight to optimize cone finding.

Complexity of SISCone

Improved Cone-Finding



SISCone's geometric approach to seedless cone-finding.

- SISCone again uses geometric insight to optimize cone finding.
- Able to provably find all stable cones in $\mathcal{O}(Nn\ln(n))$ time!

Complexity of SISCone

Improved Cone-Finding



SISCone's geometric approach to seedless cone-finding.

- SISCone again uses geometric insight to optimize cone finding.
- Able to provably find all stable cones in $\mathcal{O}(Nn\ln(n))$ time!
- Seedlessness $\implies$ inherent IR safety

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities
  - K_t: $\mathcal{O}(N^3) \rightarrow \mathcal{O}(N \ln(N))$

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities
  - K_t: $\mathcal{O}(N^3) \rightarrow \mathcal{O}(N \ln(N))$
  - Cone Algs: $\mathcal{O}(N2^N) \rightarrow \mathcal{O}(N^3) \rightarrow \mathcal{O}(N^2 \ln(N))$

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities
  - K_t: $\mathcal{O}(N^3) \rightarrow \mathcal{O}(N \ln(N))$
  - Cone Algs: $\mathcal{O}(N2^N) \rightarrow \mathcal{O}(N^3) \rightarrow \mathcal{O}(N^2 \ln(N))$
- We, as physicists, should be embarrassed!

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities
  - K_t: $\mathcal{O}(N^3) \rightarrow \mathcal{O}(N \ln(N))$
  - Cone Algs: $\mathcal{O}(N2^N) \rightarrow \mathcal{O}(N^3) \rightarrow \mathcal{O}(N^2 \ln(N))$
- We, as physicists, should be embarrassed!
  - (particularly by those $N2^N$ codes...)

Conclusion

- Jet Reconstruction algorithms are central to modern HEP experiment and theory
- Algorithms need to be fast; algorithmic complexity quantifies this.
- Seemingly the same algorithm can be implement in ways with different complexities
  - K_t: $\mathcal{O}(N^3) \rightarrow \mathcal{O}(N \ln(N))$
  - Cone Algs: $\mathcal{O}(N2^N) \rightarrow \mathcal{O}(N^3) \rightarrow \mathcal{O}(N^2 \ln(N))$
- We, as physicists, should be embarrassed!
  - (particularly by those $N2^N$ codes...)
- Have a good spring break!

References

- Ryan Atkin 2015 J. Phys.: Conf. Ser. 645 012008
- G. P. Salam and G. Soyez, JHEP 0705 (2007) 086 [arXiv:0704.0292 [hep-ph]].
- M. Cacciari and G. P. Salam, arXiv:hep-ph/0512210.
- S. Fortune, in Proceedings of the second annual symposium on Computational geometry, p. 312 (1986).