

## LAB 2: Live Object Detection and Tracking

Due: Tuesday, February 28<sup>th</sup> 2pm

The objective of the second lab is to make Cozmo find and navigate to a cube with a specific color marker. In the template, we have used yellow, but you are free to use other colors as well. In order to complete this lab, you must enhance your color detection code from Lab 1 with new code to make Cozmo search for the cube and drive towards it. You are provided with the following files:

`go_to_cube/`

- `go_to_cube.py` – This file is where you will enter your navigation code. We have given you a framework which will run Cozmo and provided an image annotator, which can help you see detected cubes for debugging. To use the annotator set `BoxAnnotator.cube` to a keypoint from `find_cube()` within your main loop.
- `find_cube.py` – This file is a slightly altered version of the `count_cubes.py` file from Lab 1. You will need to copy most of your `filter_image()` and `detect_blob()` functions to this file.
- `marker.pdf` – This is a printable set of colored markers that can be cut out and taped over the symbol on Cozmo's cubes. You can use any of the colors on the template or even make your own color marker, but we suggest start from yellow. Also you don't need to cover all sides of a cube with these markers, taping these templates to two sides of the cube should be enough. **Do not use any kind of glue that damages Cozmo's cubes, just use normal tape.**

**Lab Checkpoint [10 points]:** Complete the installation of the Cozmo SDK. Instructions for this can be found on Blackboard and the Cozmo website.

**Main Lab [90 points]:** Add code to `go_to_cube.py` and `find_cube.py` to make Cozmo search for a cube with yellow labels and drive to within 5cm (2 inches) of it, and to search for the cube again if it is moved.

*Evaluation:* This lab will be evaluated with an in-class demo. During the demo we will see if your code allows Cozmo to search for the cube [30 points], drive towards the cube [40 points], stop within 5cm (2 inches) of the cube [10 points], and automatically restart the search if the cube is moved [10 points].

**Submission:** By 2pm on Tuesday February 28<sup>th</sup> 2019, submit `go_to_cube.py` and `find_cube.py` on Blackboard. Make sure your code is entirely contained within these files. If you relied significantly on any external resources to complete the lab, please reference them in the submission comments.



**Tips:**

- The method `robot.drive_wheels()` allows you to control Cozmo's motor speeds directly, and can help achieve smoother motion than just using `robot.drive_straight()` and `robot.turn_in_place()`.
- You might need to change the size parameters in the blob detector from Lab 1, since the cubes are no longer in a fixed location relative to Cozmo.
- Most action methods (drive commands, etc.) need to be called with the `await` expression in order to work properly (e.g., `await robot.drive_wheels()`).