

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#1 Two pieces of code are said to be “execution equivalent” if they each produce the same output. Determine if the following pairs of code fragments are execution equivalent.

Code Pair A: equivalent_____ not
equivalent_____

<pre>for(int i=0 ; i<10 ; i++) { System.out.println(i); }</pre>	<pre>int i=0; while(i<10) { i++; System.out.println(i); }</pre>
---	--

Code Pair B: equivalent_____ not
equivalent_____

<pre>for(int i=10 ; i>0 ; i = i-2) { System.out.println(i); }</pre>	<pre>int i=10; while(i>0) { System.out.println(i); i = i-2; }</pre>
--	--

Code Pair C: equivalent_____ not
equivalent_____

<pre>for(int i=1 ; i<10 ; i++) { System.out.println(i); }</pre>	<pre>int number = 1; for(int i=9 ; i>0 ; i--) { System.out.println(number); number++; }</pre>
--	--

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#2 Fill in the blanks in the code fragment, so that when executed, it produces the output indicated below.

Desired Output:

```
0 10 0
1 9 9
2 8 16
3 7 21
4 6 24
```

Code Fragment:

```
int forwardCounter = _____;
int backwardCounter = _____;

while( forwardCounter _____ backwardCounter )
{
    System.out.println( forwardCounter + " " +
                        backwardCounter + " " +
                        ( _____ ) );

    forwardCounter _____;
    backwardCounter _____;
}
```

Q#3 Write the output that these lines of code generate. Use the following variables and methods.

<pre>// MAIN int a = 6; int b = 8; int c = 2;</pre>	<pre>private static int foo(int b, int c) { return b-c; }</pre>	<pre>private static void bar(int a, int b) { int temp = a; a = b; b= temp; }</pre>

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Code as called from main

Output

1pt	A.	<code>System.out.println(a / c);</code>	
1pt	B.	<code>System.out.println(a % b);</code>	
1pt	C.	<code>System.out.println(a + b * c);</code>	
1pt	D.	<code>System.out.println(a > b b > c);</code>	
1pt	E.	<code>System.out.println(a < b && b < c);</code>	
1pt	F.	<code>System.out.println((double)(a+b+c)/3);</code>	
1pt	G.	<code>System.out.println(foo(a, b));</code>	
1pt	H.	<code>bar(a, b);</code> <code>System.out.println("a = " + a +</code> <code> ", b = " + b);</code>	

Q#4 Write the output that these lines of code generate.

```
A.  String s = new String("Pittsburgh");
    int index = 0;
    while( s.charAt(index) != 's' )
    {    System.out.print(s.charAt(index));
        index++;
    }
```

Outputs:

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

B.

```
String city = new String("Colorado Springs");
System.out.println( city.substring(11, city.length()-1) );
```

Outputs:

C.

```
int i = 15;
do{
    System.out.print( i + "\t" );
    i = i * 2 / 3;
}while( i > 10 );
```

Outputs:

D.

```
for( int j=0 ; j<10 ; j++ )
    if( j/3 == 0 )
        System.out.print( j + "\t" );
```

Outputs:

Q#5 Trace this matrix code and determine what it outputs.

```
char [][] charMat = new char[7][7];
for( int i=0 ; i<charMat.length ; i++ )
    for( int j=0 ; j<charMat[i].length ; j++ )
    {
        if( i==charMat.length/2 || j==charMat[i].length/2 ||
            i == j || i+j == charMat.length-1 )
            charMat[i][j] = '*';
        else
            charMat[i][j] = ' ';
    }
for( int i=0 ; i<charMat.length ; i++ )
{
    for( int j=0 ; j<charMat[i].length ; j++ )
        System.out.print( charMat[i][j] );
    System.out.println();
} // Outputs:
```

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#6

- a) What does it mean to overload a method?
- b) How does the compiler resolve the overloads (tell them apart)?

Q#7

- a) Assume `int x=3;`

`expr => (x/10)` evaluates to: _____

`expr => (x/2.0)` evaluates to: _____

`expr=> (x + 5 * 4 + 3 / 2)` evaluates to: _____

- b) Assume `boolean b1 = true, b2 = false; int i = 100, j = -4;`

`b1 || (j>0) || (b2 && i==100)` evaluates to: _____

`b1 && (b2 || i>j) && (b1 != b2)` evaluates to: _____

`(b2 || !b2)` evaluates to: _____

- c) Go back to (b) and circle the operators that short circuit

- d) Write `INVALID` after any of the following statements if they are invalid

Assume: `String s1,s2; int i,j ; double d1,d2;`

`s1 = "Hello World";`

`s2 = "3" + "14159";`

`s1 = 3.14159;`

`d1 = s2;`

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

e) Assume these definitions:

```
int i = 9; boolean b;
```

then trace this code

```
if (i>0)
{
    b = (1 % 2) != 0;
    i = i % 2;
}
else
{
    i = i + (i%2);
    b = false;
}

if (i%2 ==0 )
{
    if (i>0)
    {
        i = 7;
        b = true;
    }
}
else
{
    if (b)
        i = 9 - (i%5);
    else
        b = (i%2) != 0 ;
}
```

What are the final values of b and i ?

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#8 What is the output of this code segment?

```
boolean inputOk = true;

if (inputOk)
    System.out.println("Thank you");
    System.out.println("Your Input was OK");

if (!inputOk)
    System.out.println("Sorry - try again you");
    System.out.println("Your Input was bad");
```

Q#9 What is the output of this code segment?

After each of the description, write "FOR", "WHILE" or "DO" to indicate which loop form is best suited for the task.

Assume you must use a loop to do the given task

- a) Prompt a user for a number in a desired range until they get it right
- b) Calculate the sum of all the numbers from 1 to 100
- c) Divide a given number by 2 until the number reaches 1.

Q#10 Write a method that that receives an int and returns it as a String

CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#11 What's wrong with this code?

```
int[] x = null;
x = new String[5];
for (int i = 0; i < x.length; i++)
    System.out.println(x[i]);
```

Q#12 What's wrong with this code?

```
public static void main(String[] args)
{
    int x = 5;
    System.out.println(multiply(x,5));
}
public static int multiply(int num1, int y)
{
    return (x * y);
}
```

Q#13 What's wrong with this code?

```
int[] x = null;
x = new int[10];
for (int i = 0; i < x.length; x = null)
{
    // do whatever
}
```


CS 401 MIDTERM REVIEW: SAMPLE PROBLEM SET #1

Q#14 What's wrong with this code?

```
int[] x = null;
x = new int[10];
for (int i = 0; i <= x.length; ++i)
{
    x[i] = i;
}
```

Q#15 What's the output of this program?

```
public static void main(String[] args)
{
    int[] arr = new int[10];
    fillArray(arr);
    System.out.print(arr[t] + " ");
}
static void fillArray(int[] arr)
{
    arr = new int[5];
    for (int i = 0; i < arr.length; i++)
        arr[i] = i * 2;
}
```