

Task 2:

SCHEMA #1: ROOM(bldg-number, room-number, room-area)

primary key = (bldg-number, room-number)

Functional Dependencies:

bldg-number, room-number → room-area

Minimal keys:

bldg-number, room-number

Current normal form:

BCNF because all LHS are superkeys

Denormalise to 1NF by adding attribute: (faculty) so that bldg-number → faculty

ie. new schema ROOM(bldg-number, room-number, room-area, faculty)

primary key = (bldg-number, room-number)

-Now schema is not in 2NF because non-prime faculty is partially dependent on primary key (bldg-number, room-number)

SCHEMA #2: FLIGHT(flight-number, from-city, to-city)

primary key = (flight-number)

Functional Dependencies:

flight-number → from-city, to-city

Minimal keys:

Flight-number

Current normal form:

BCNF because LHS is superkeys

Denormalise to 2NF by adding attribute: (arrivalCityTemperature) So that to-city → arrivalCityTemperature

-2NF because no non-prime is partially dependent on primary key

-NOT in 3NF because non-prime attribute 'arrivalCityTemperature' is transitively dependent on primary key

ie. flight-number → to-city and to-city → arrivalCityTemperature

SCHEMA #3: ORDER(order-number, supplier)

primary key = (order-number)

Functional Dependencies:

order-number → supplier

Minimal keys:

order-number

Current normal form:

BCNF all LHS are superkeys

Denormalise to 3NF by adding attribute: (customerID) so that customerID, supplier → order-number

NOT BCNF because customerID, supplier on LHS is not a prime attribute

But schema is in 3NF because for all functional dependencies:

- LHS is a primary key (ie. order-number → supplier, customerID)

- or

- RHS is a prime attribute (part of minimal key) (customerID, supplier → order-number)