What Do Linguistic Feature Groups Contribute to Early Depression Detection? A Repeated Cross-Validation and Error Analysis on Reddit Users

Anonymous ACL submission

Abstract

Early depression detection systems are usually compared on a single split with few positive users, so it remains unclear what individual linguistic features contribute, how early they help, and which users they fail on. We analyse feature groups (PHQ-9 item similarity, LIWC categories, language style matching, parent-text similarity, posting behaviour) with a shared causal Transformer, using 5×3 repeated cross-validation over 891 Reddit users (102 labelled depressed), alarm rules chosen only on training users, and family-wise corrected paired tests. PHQ-9 similarity is the strongest single group (ROC-AUC 0.952, PR-AUC 0.742) and is significantly better than both style-matching variants; its advantage over LIWC is smaller and less robust across tests, and groups added to it give no significant gain. A control that knows only post position and volume already reaches ROC-AUC 0.662. Text-based groups rank users after one post, whereas style matching needs several. An adapter-tuned MentalRoBERTa has the best scores (ROC-AUC 0.963) and is better than TF-IDF and, more narrowly, frozen embeddings, but its advantage over a 74-feature combination is not significant after correction. Users missed by the stronger groups have little mental-health vocabulary in their histories, a pattern we describe without a causal claim. Because labels come from self-reported diagnoses, "early" means after fewer posts, not before disclosure or onset.

1 Introduction

Early risk detection asks a system to read a user's writings in order and to raise an alarm as soon as there is enough evidence of a condition. The eRisk lab has run such tasks on Reddit users since 2017 (Losada et al., 2017, 2018), and its 2025 edition introduced a contextualised early depression detection task (Parapar et al., 2025). Systems range from classifiers over hand-crafted linguistic features (Trotzek et al., 2020) to fine-tuned Transformers, but they are typically compared on one train/test split that contains a few dozen positive users. On such splits, differences of a few points in F1 cannot be resolved, and it is rarely clear which linguistic signals a system actually relies on.

Three properties of the data make the question harder. First, positives are rare: the collection we use has 102 depressed users among 891. Second, depressed users write much more: the median depressed user has 525 posts, the median control user 216. Position and volume of posts are therefore informative on their own, and any claim about a linguistic feature needs a control that knows nothing but position and volume. Third, labels come from self-reported diagnoses, so errors are not necessarily model errors, and the kinds of users that features miss or wrongly flag are informative about what the features measure. Throughout, *depressed* and *control* denote these collection labels, not independently established clinical states (Chancellor and De Choudhury, 2020), and the disclosure statements remain in the histories: *early* means after fewer observed posts, not before disease onset or before a user's first disclosure.

We separate three kinds of evidence that can lead to different conclusions: *standalone* signal (does a group beat the control for position and volume?), *incremental* signal (does it add to a stronger group?) and *early* signal (is it available after few posts?). We therefore ask four questions. **RQ1:** which feature groups carry signal beyond post position and volume? **RQ2:** how early does each group detect? **RQ3:** do features beyond PHQ-9 similarity, or a fine-tuned encoder, add anything? **RQ4:** which users does each group get wrong, and why? To answer them, we make three contributions:

- an evaluation protocol that is free of leakage across folds, uses repeated cross-validation

over all labelled users, selects the alarm rule only on out-of-fold predictions of the training users, and tests differences in pre-specified families with Holm correction;

- a comparison of single feature groups and their combinations with a position-and-volume control, in terms of ranking quality, earliness (AUC after n posts, alarm delay) and decision quality, with frozen and adapter-tuned MentalRoBERTa and a TF-IDF classifier as references;
- an error analysis by feature group: which depressed users are missed and which control users are flagged, by which groups, and how this depends on the history length and on explicit self-reports.

2 Related Work

Early detection in eRisk. The eRisk collection pairs Reddit users with labels derived from explicit mentions of a diagnosis and introduced the ERDE measure of early-detection performance (Losada and Crestani, 2016); the lab has since repeated depression tasks and added others (Losada et al., 2017, 2018; Parapar et al., 2022, 2025). Sadeque et al. (2018) proposed a latency-weighted F1, which we use. Early detection systems include the text classification framework of Burdisso et al. (2019) and neural networks with linguistic metadata (Trotzek et al., 2020); we use a causal Transformer over per-post features so that the alarm rule can be applied to a probability after every post.

Linguistic and psychometric signals. De Choudhury et al. (2013) predicted depression from social media with behavioural and linguistic features, and Coppersmith et al. (2014) and Yates et al. (2017) built corpora around self-reported diagnoses. We use signals with a psychological motivation: similarity to the items of the PHQ-9 questionnaire (Kroenke et al., 2001), scored with the embedding-similarity item scoring of Lahnala et al. (2025); category rates from LIWC (Pennebaker et al., 2015); and language style matching between a comment and the text it replies to (Ireland and Pennebaker, 2010). Mental-health encoders such as MentalRoBERTa, a RoBERTa model (Liu et al., 2019) further pre-trained on mental-health posts (Ji et al., 2022), and parameter-efficient adapters (Houlsby et al., 2019; Pfeiffer et al., 2020; Poth et al., 2023) serve as references.

	Depressed	Control
Users	102	789
Posts	66,679	276,474
Posts per user, median [IQR]	525 [131, 1005]	216 [50, 705]
Words per post, median	22	13
Comments among posts	93.4%	89.6%
Posts with parent text	64.0%	59.3%
Time span (days), median	1181	388
Users with a self-report phrase	83 (81%)	27 (3.4%)

Table 1: Data. "Self-report phrase": at least one post matching a first-person pattern such as "I was diagnosed with depression" (Appendix D).

Validity of evaluation. Proxy labels have limited external validity (Ernala et al., 2019; Harrigian et al., 2020), available datasets differ in quality (Harrigian et al., 2021), and studies rarely validate their methodology (Chancellor and De Choudhury, 2020). On the statistical side, small samples give large error bars (Varoquaux, 2018), paired tests need care when training sets overlap (Dietterich, 1998; Nadeau and Bengio, 2003; Demšar, 2006), and selecting a configuration on the data used for evaluation biases the estimate (Cawley and Talbot, 2010). We follow these recommendations with repeated cross-validation, a selection of the alarm rule that never uses held-out users, and paired tests with multiplicity correction.

3 Data and Task

Data. We use the labelled collection released for eRisk 2025 Task 2: Reddit users with the submissions and comments they wrote, the text they replied to, and a label stating whether the user explicitly mentioned a depression diagnosis (Parapar et al., 2025). The release has 909 users; we drop empty posts and posts whose text was removed or deleted, after which 18 control users have no post left, giving 891 users (102 depressed) and 343,153 posts, without truncation or down-sampling. Table 1 summarises the data. Depressed users write more posts, longer posts, over longer periods, and more of their posts are comments with a known parent text.

Task and alarm rule. After each post t the system outputs a probability p_t that the user is depressed. An alarm is raised at the first post d such that $p_{d-k+1}, \ldots, p_d \geq \theta$, and d is the delay; users without an alarm are predicted negative. The pair (θ, k) is chosen with $\theta \in \{0.05, \ldots, 0.95\}$

and $k \in \{1, 3, 5, 10\}$ to maximise the latency-weighted F1,

$$F_{\text{lat}} = F_1 \cdot \left(1 - \text{median}_{\text{TP}}\left(-1 + \frac{2}{1+e^{-\rho(d-1)}}\right)\right),$$

with $\rho = 0.0078$ as in eRisk (Sadeque et al., 2018), where the median is over detected depressed users. We also report ROC-AUC and PR-AUC of the maximum probability of a user, AUC after n posts (the probability after n posts, or after the last post for users with fewer), the share of users flagged within n posts, precision, recall, F1 and the median delay.

4 Features and Models

Per-post feature groups. Every group is described by features of the current post plus history features (running maximum and minimum, their difference, change from the previous post, rolling standard deviation over 5 posts, running mean), standardised with training statistics and clipped to ± 10. **PHQ** (28 features including context): cosine similarity between a post and nine first-person archetype sentences, one per PHQ-9 item (Appendix A), computed with mxbai-embed-large-v1 (Lee et al., 2024; Li and Li, 2023) following Lahnala et al. (2025), their mean, and running maxima per item. These are similarities inspired by symptoms, not observed PHQ responses or validated estimates of severity. **LIWC** (33): rates of 15 categories in the post's own text (e.g. sadness, anxiety, health, negative emotion, first-person singular) from LIWC2015 (Pennebaker et al., 2015). **LSM** (73): language style matching (Ireland and Pennebaker, 2010) between a comment and its parent on ten LIWC-based group scores computed on word counts, as in our initial pipeline (defined below). **LSM alignment** (43): the same score on word rates, plus the signed difference of the group rates between comment and parent. **Cosine similarity** (10): similarity of sentence embeddings (all-MiniLM-L6-v2; Reimers and Gurevych, 2019) between a comment and its parent. **Behaviour** (9): log word count, posting between 00:00 and 05:59 UTC, log time since the previous post. LSM, alignment and cosine similarity exist only for comments whose parent text is known (about 60% of the rows). In every single-group run we add three **context** features: log post index, comment indicator and parent-known indicator. **Context only** uses just these three and is our control for position and volume.

Style matching. For a comment and its parent, count LSM scores each LIWC category c with word counts a_c, b_c as $1 - |a_c - b_c|/(a_c + b_c + \epsilon)$ and averages the categories into ten groups G (function words, social, positive, negative, four person and pronoun groups, cognitive, perceptual). The alignment variant uses category rates r_c (comment) and q_c (parent):

$$m_G = \frac{1}{|G|} \sum_{c \in G} \left(1 - \frac{|r_c - q_c|}{r_c + q_c + 10^{-6}}\right),$$
$$\delta_G = \frac{1}{|G|} \sum_{c \in G} (r_c - q_c).$$

Two zero rates give a score of one, which can make sparse texts look aligned, and normalisation does not remove topical or interaction-selection effects. Counts mix in text length; we keep this variant as an empirical comparator, not as canonical LSM.

Sequence model. A linear projection feeds a 3-layer Transformer encoder (hidden size 256, 4 heads, dropout 0.3, 4.0M parameters) with a causal mask, so the output after post t depends only on posts $1..t$ (Vaswani et al., 2017). It is trained with a per-post binary cross-entropy against the user label, each user weighted equally, a class weight equal to the ratio of negative to positive users, AdamW (Loshchilov and Hutter, 2017) (learning rate $3 \cdot 10^{-5}$) and early stopping on 12% of the training users.

Reference systems. **Frozen MentalRoBERTa**: mean-pooled last-layer embeddings (768 dimensions) of each post, used in place of the hand-crafted features. **Adapter-tuned MentalRoBERTa**: a bottleneck adapter and classification head on the same encoder, trained on posts with the user label (3 epochs, at most 200 posts per user and epoch); its logit is the only input apart from the context features. **TF-IDF**: word 1–2-gram TF-IDF with logistic regression on posts; the user score after n posts is the running mean of the post logits. **Self-report rule**: no learning; an alarm at the first post that matches the self-report pattern. It is not a model of depression but shows what the labelling alone yields.

5 Evaluation Protocol

We pool the 891 users and run stratified 5-fold cross-validation three times (15 outer folds). In each outer fold the sequence model is trained exactly as above on the outer training users with an inner 5-fold cross-validation; the pooled inner

out-of-fold probabilities of the training users select (θ, k), and the five inner models are averaged on the held-out users. Every user is therefore predicted once per repeat by models that never saw it, and the rule is never tuned on held-out users (Cawley and Talbot, 2010). Components fitted with labels are refitted inside every outer fold: the adapter is retrained on the outer training users (three inner models) and the TF-IDF classifier is refitted. A relative-entropy feature from language models fitted on depressed and control posts would need the same nested refitting and is not used. All configurations share splits and seeds.

Metrics are means over the three repeats, with 95% intervals from a stratified bootstrap over users (2000 draws, identical for all configurations, repeats averaged inside each draw). Differences are tested in three pre-specified families (9 comparisons among references; 4 against the TF-IDF baseline; 9 among feature groups and against the control) with two-sided bootstrap p-values of the mean difference and Holm adjustment inside each family (Holm, 1979). With 2000 draws the smallest attainable p is $1/2001$, so Holm-adjusted values of .004 (families of nine) and .002 (four) mean p at the resolution limit. Nadeau–Bengio corrected resampled t-tests (Nadeau and Bengio, 2003), DeLong tests (DeLong et al., 1988) and McNemar tests (McNemar, 1947) are in Appendix C. Error analysis uses the decisions of the three repeats: a user is an error of a configuration if it is misclassified in at least two of them.

6 Results

6.1 Which feature groups carry signal (RQ1)

Table 2 ranks the groups: PHQ (ROC-AUC .952, PR-AUC .742) > LIWC (.926, .660) > LSM counts (.874, .556) > LSM alignment (.851, .478) > behaviour (.808, .375) > cosine similarity (.727, .303). PHQ is better than LIWC (ROC $+.027$, PR $+.082$; Holm $p = .004$ and .024), than LSM counts and than LSM alignment (PR $+.186$ and $+.264$; $p = .004$). Every group exceeds the context-only control in ROC-AUC (Holm $p \leq .018$), but in PR-AUC only PHQ, LIWC and the two LSM variants do ($p \leq .042$); behaviour and cosine similarity do not ($p = .686$). The control matters: position and volume alone reach ROC-AUC .662 and PR-AUC .333, and its decision rule flags 583 of the 789 control users (precision .137). The differences in ROC-AUC between PHQ and the other groups, and between each group and the control, also hold under the Nadeau–Bengio test; the PR-AUC and F1 differences between PHQ and LIWC are significant only under the bootstrap test, so we regard them as suggestive (Appendix C).

6.2 How early each group detects (RQ2)

After a single post (Figure 1, left; Table 3), LIWC (AUC .763) and PHQ (.748) already rank users, as do behaviour (.702) and the two references that read the post text (.80–.82), whereas LSM, LSM alignment and cosine similarity are at .53–.56: they exist only for comments with a known parent and need several posts to accumulate. At 10 posts PHQ reaches .875 and LIWC .847; at 100 posts PHQ (.922) is close to the adapter-tuned encoder (.936). Among the informative groups, LIWC alarms earliest (median delay 14 posts, 44% of its detected users within 10 posts) but is less precise than PHQ (.613 against .699); LSM counts is slowest (median 40 posts). The combination of PHQ and three LIWC categories alarms earlier than either (median 10.3 posts) at PHQ's precision; this comparison was not pre-specified. TF-IDF and the encoders alarm earliest (median 5.7 to 9.5 posts). Among the pre-specified tests of the median delay, TF-IDF alarms earlier than the adapter, the frozen encoder, PHQ and the 74-feature set (by 3.8, 2.7, 8.3 and 10.7 posts; Holm $p = .002$), LSM counts later than PHQ (26 posts; $p = .004$), and PHQ and LIWC do not differ (Holm $p = 1$). Delays are medians over different sets of detected users, so these differences mix speed with who is detected. After 500 posts the false-alarm rate on control users is under 6% for PHQ and LIWC, about 11% for behaviour and LSM alignment, and 68% for the context-only rule (Figure 1, right).

6.3 Beyond PHQ, and encoders (RQ3)

Adding three LIWC categories to PHQ, additionally four LSM scores, or the LSM alignment features (74 features in total) does not change ROC-AUC or PR-AUC significantly relative to PHQ alone (74 features against PHQ: ΔROC $+.001$, ΔPR $+.010$, Holm $p = 1$; Tables 2 and 4). The four-score variant is slightly better than the alignment variant in ROC-AUC (Holm $p = .042$, not significant under Nadeau–Bengio). The adapter-tuned MentalRoBERTa is best overall (ROC-AUC .963, PR-AUC .792, F1 .788). It is better than TF-IDF (ΔROC $+.049$, ΔPR $+.111$, ΔF1 $+.073$; Holm $p \leq .004$) and, more narrowly, than frozen

Configuration	#feat.	ROC-AUC	PR-AUC	AUC@10	F1	F_{lat}
Single feature groups (plus three context features)						
PHQ	28	.952 [.935, .968]	.742 [.677, .815]	.875	.718	.681
LIWC (15 categories)	33	.926 [.901, .949]	.660 [.586, .745]	.847	.653	.620
LSM (counts)	73	.874 [.837, .909]	.556 [.476, .641]	.764	.564	.479
LSM alignment	43	.851 [.811, .886]	.478 [.403, .568]	.745	.507	.464
Behaviour	9	.808 [.763, .849]	.375 [.314, .458]	.745	.438	.416
Cosine similarity	10	.727 [.676, .778]	.303 [.244, .381]	.621	.272	.255
Context only (control)	3	.662 [.607, .718]	.333 [.259, .419]	.620	.236	.225
Combinations and reference systems						
PHQ + 3 LIWC categories	34	.952 [.934, .968]	.749 [.679, .820]	.891	.732	.706
PHQ + 3 LIWC + 4 LSM scores	42	.958 [.942, .974]	.777 [.710, .846]	.892	.751	.713
PHQ + 3 LIWC + LSM alignment	74	.953 [.934, .970]	.753 [.689, .822]	.883	.723	.680
MentalRoBERTa, frozen	771	.938 [.914, .960]	.726 [.659, .798]	.889	.729	.708
MentalRoBERTa, adapter-tuned	4	.963 [.947, .977]	.792 [.732, .852]	.878	.788	.762
TF-IDF + logistic regression	–	.914 [.884, .940]	.680 [.601, .759]	.902	.715	.702
First self-report phrase (no learning)	–	.897	.754	.578	.783	.621

Table 2: 5×3 cross-validation over 891 users (102 depressed): mean over repeats with 95% bootstrap intervals for ROC-AUC and PR-AUC (prevalence 0.114); AUC@10 intervals are about ±0.04. #feat. includes three context features. F_{lat} is the latency-weighted F1. We call PHQ + 3 LIWC + LSM alignment the 74-feature set. The last row is not a cross-validated model; its ROC-AUC and PR-AUC rank users by the number of matching posts.




Figure 1: Left: AUC after n posts (score after the last post for users with fewer posts). Middle and right: share of depressed and of control users flagged within n posts under the rule chosen in each outer fold. Solid: single feature groups; dashed: PHQ + 3 LIWC and the references. Bands: 95% bootstrap intervals (500 draws).

embeddings (+.024, +.065, +.059; $p = .004$, .045, .018; the PR-AUC difference has Nadeau–Bengio $p = .057$). Against the 74-feature handcrafted set the difference is borderline: ΔROC +.010, ΔPR +.039, ΔF1 +.065, with unadjusted bootstrap $p = .032$, .135, .011 and Holm $p = .19$, .81, .088. This does not establish equivalence: an F1 gap of .065 may matter in practice. TF-IDF ranks users worse (ROC-AUC .914) but has the highest AUC@10 (.902) and the shortest delay. The self-report rule reaches F1 .783, close to the adapter-tuned model (.788), but alarms much later (median 55 posts against 9.5): within the observed histories the learned models mainly gain earliness, although the detected users differ, so this does not show that they alarm before each user's first disclosure.

6.4 Errors by feature group (RQ4)

The groups err on different users (Figure 2). The false-negative sets overlap strongly between PHQ and PHQ with LIWC (Jaccard .89, the combination mostly inherits PHQ's misses), moderately between PHQ and LIWC (.56), and little between PHQ and LSM alignment (.27) or the adapter-tuned model (.36); false-positive sets overlap much less (.07 to .26 between groups, .37 between the two LSM variants).

False negatives. Users missed by the stronger groups have long histories with sparse evidence:

Configuration	AUC@1	AUC@10	Flagged ≤10	Precision	Median delay [Q1–Q3]
PHQ	.748	.875	.281	.699	14.0 [10–46]
LIWC	.763	.847	.307	.613	14.0 [6–45]
LSM (counts)	.559	.764	.039	.517	40.0 [17–96]
LSM alignment	.532	.745	.193	.421	22.8 [8–74]
Behaviour	.702	.745	.226	.365	14.2 [6–120]
Cosine sim.	.556	.621	.281	.163	17.0 [9–54]
Context only	.481	.620	.422	.137	12.5 [4–52]
PHQ + 3 LIWC	.774	.891	.372	.700	10.3 [5–35]
MentalRoBERTa frozen	.824	.889	.516	.722	8.3 [5–12]
MentalRoBERTa adapter	.803	.878	.425	.783	9.5 [5–32]
TF-IDF	.806	.902	.516	.749	5.7 [5–10]
First self-report phrase	–	.578	–	.754	55 [–]

Table 3: Earliness. Flagged ≤10: share of all depressed users flagged within 10 posts. Precision and delay are over the decisions of the chosen rule; delay is the median over detected depressed users, averaged over repeats.




Figure 2: Left: misclassified users per configuration (wrong in ≥ 2 of 3 repeats). Middle and right: overlap (Jaccard index) of the sets of false negatives and of false positives. LSM-al.: LSM alignment; Beh.: behaviour; PHQ+L: PHQ + 3 LIWC; Adapter: adapter-tuned MentalRoBERTa.

Comparison (A − B)	ΔROC	ΔPR	ΔF1
PHQ − LIWC	+.027 (.004)	+.082 (.024)	+.064 (.017)
PHQ − LSM (counts)	+.078 (.004)	+.186 (.004)	+.154 (.004)
PHQ − LSM alignment	+.102 (.004)	+.264 (.004)	+.211 (.004)
74 feat. − PHQ	+.001 (1)	+.010 (1)	+.005 (1)
74 feat. − PHQ+3 LIWC+4 LSM	−.005 (.042)	−.025 (.322)	−.028 (.182)
Adapter − frozen	+.024 (.004)	+.065 (.045)	+.059 (.018)
Adapter − TF-IDF	+.049 (.002)	+.111 (.002)	+.073 (.004)
Adapter − 74 feat.	+.010 (.192)	+.039 (.810)	+.065 (.088)

Table 4: Key paired differences (mean over repeats; Holm-adjusted p in parentheses; .004 and .002 are the smallest attainable values). 74 feat.: PHQ + 3 LIWC + LSM alignment. All 22 comparisons are in Appendix C.

the median is 622 posts for PHQ and LIWC (854 for the adapter), and only 5% of their posts contain mental-health terms (adapter: 2.8% against 15.5% for its true positives, unadjusted $p < .001$). The history length itself does not differ significantly between the adapter's false negatives and true positives (854 against 464 posts, $p = .236$), so this is an evidence-density pattern, not a demonstrated effect of length. Reading the highest-scoring posts of the 20 users missed by the adapter-tuned model, 17 contain a first-person statement of a diagnosis or of ongoing depression, which the post-level model scores highly; yet 15 of the 20 never reach the threshold, which suggests that the sequence model does not retain such isolated evidence (we did not test alternative pooling). Weaker groups also miss users with shorter histories (304 posts for LSM alignment, 336 for behaviour).

False positives. Semantic groups flag control users who write about depression: 23%, 20% and 18% of the false positives of PHQ, LIWC and LSM match the self-report pattern, against 3.4% of all control users (adapter: 38%). In a reading of the false positives of the adapter-tuned model

			False negatives			False positives		Recall by self-report	
Configuration	FN	FP	Posts	MH	SR	Posts	SR	with	without
PHQ	25	31	622	5.1%	64%	412	23%	0.81	0.53
LIWC	31	41	622	5.3%	58%	231	20%	0.78	0.32
LSM (counts)	36	61	546	9.5%	67%	483	18%	0.71	0.37
LSM alignment	36	83	304	11.5%	67%	368	13%	0.71	0.37
Behaviour	47	96	336	12.6%	72%	660	7%	0.59	0.32
PHQ + 3 LIWC	24	34	746	3.1%	62%	416	21%	0.82	0.53
MentalRoBERTa adapter	20	21	854	2.8%	60%	241	38%	0.86	0.58
TF-IDF	32	22	954	3.2%	69%	172	27%	0.73	0.47

Table 5: Misclassified users (wrong in ≥ 2 of 3 repeats). Posts: median posts per user; MH: median share of posts with mental-health terms; SR: share with a self-report phrase. Recall is split by whether a depressed user has a self-report phrase (83 users) or not (19 users).

Posts	<100 (23/280)	100–499 (25/243)	≥500 (54/266)
PHQ	.609 (.021)	.880 (.053)	.759 (.045)
LIWC	.609 (.050)	.760 (.062)	.704 (.045)
LSM (counts)	.391 (.029)	.840 (.099)	.667 (.109)
LSM alignment	.435 (.071)	.760 (.132)	.685 (.117)
Behaviour	.391 (.050)	.480 (.128)	.630 (.192)
PHQ + 3 LIWC	.696 (.021)	.880 (.058)	.741 (.053)
Frozen encoder	.913 (.032)	.800 (.058)	.667 (.026)
Adapter	.870 (.014)	.840 (.041)	.759 (.026)
TF-IDF	.870 (.025)	.760 (.049)	.574 (.011)

Table 6: Recall of depressed users (false-alarm rate of control users) by number of posts per user (depressed/control users in parentheses); decisions as in Table 5.

and of the 74-feature set, most flagged users describe their own depression, another condition, a chronic illness, everyday distress, or support others in mental-health communities (Appendix E). Behaviour flags heavy posters (median 660 posts against 182 for its true negatives; 7% self-reports). The alarm is usually raised on an unremarkable post and reflects the accumulated history.

History length. Table 6 splits the users by the number of posts. The recall of the systems that score post text falls as histories grow (TF-IDF .87, .76, .57; frozen encoder .91, .80, .67; adapter .87, .84, .76), which is consistent with evidence dilution, whereas PHQ and LIWC are weak on short histories (.61 below 100 posts, against .87 to .91 for the text systems) and best at 100–499 posts (.88 and .76). Features that accumulate over the history thus need a minimum of posts, and text systems lose evidence in long ones. With 23, 25 and 54 depressed users per bin these values are indicative.

Self-reports. Depressed users without a self-report phrase are harder for every configuration (19 users, so values are indicative): recall falls from .81 to .53 for PHQ, from .86 to .58 for the adapter-tuned model, and more for LIWC (.78 to .32) and behaviour (.59 to .32).

7 Discussion

Standalone, incremental and early signal lead to different conclusions. Style matching improves over the control but not demonstrably over PHQ with LIWC; PHQ leads the single groups in full-history ranking, whereas TF-IDF has the highest AUC@10 among the references; a ranking winner need not be an early-alarm winner. PHQ similarity is the strongest and among the earliest signals, and no other group we tested adds a significant gain to it. This is consistent with its construction: it scores each post against symptom statements and therefore responds to symptom-like content from the first post on. LIWC categories give a coarser lexical version of this signal. Style matching and parent similarity are properties of an exchange, are undefined for submissions and for comments without a parent, and need several posts; they also add little to PHQ. Behaviour and context mostly reflect how much a user writes; a control for this is necessary, since position and volume alone give ROC-AUC .662.

That a control for position and volume is needed echoes the concern that confounding factors can lead to an overestimate of performance on social-media mental-health data (Harrigian et al., 2020); here the control is cheap, since the three context features are available in every setting. The two families depend differently on the history length (Table 6), but a simple concatenation of the adapter logit and the 74 hand-crafted features did not improve on the adapter alone (ΔPR $-.020$, Holm $p = 1$; Appendix C). For early detection systems, the error analysis suggests two directions that we did not test: aggregation that keeps the strongest evidence instead of an average-like sum-

mary (misses are users with a few strong posts in long histories), and a distinction between writing about depression and having it (many false positives come from mental-health communities). Because labels are derived from self-reported diagnoses, the results describe the detection of users who have disclosed a diagnosis; a rule that only looks for the disclosure reaches an F1 close to the best model and differs mainly in delay, so absolute F1 values should be read with the labelling in mind.

8 Conclusion

In a repeated cross-validation over 891 Reddit users, PHQ-9 item similarity is the strongest single feature group, features beyond it add no significant gain, post position and volume are a necessary control, text-based groups detect from the first post whereas style matching needs several, and an adapter-tuned encoder is best but not significantly better than hand-crafted features after correction. Groups fail on different users, but distinct errors do not guarantee useful fusion: adding the hand-crafted features does not improve the adapter. Misses are associated with sparse mental-health evidence in long histories (recall of the text systems falls as histories grow), and false alarms with topic; both are descriptive. The results support feature analysis, not a claim of state-of-the-art detection, and they concern users who disclosed a diagnosis.

Limitations

The collection has 102 depressed users from one platform, so intervals are wide (about ± 0.07 in PR-AUC), non-significant differences are not evidence of equality, and the findings may not transfer to other data. Labels come from self-reported diagnoses; control users are not verified as non-depressed, and some describe their own depression. We use one sequence-model seed and one adapter run per outer fold; hyper-parameters and the feature groups were chosen earlier on users who are part of the cross-validation, which favours those choices. The alarm rule is chosen on single-model out-of-fold probabilities but applied to averaged models, which may shift threshold-based metrics slightly. A relative-entropy feature is not evaluated because it needs nested refitting. The categories of errors come from one reader who read the highest-scoring posts of each user, and the keyword patterns are not validated. Delay differences are computed over different sets of detected users. Peak ranking rewards observation opportunity, and fixed-prefix AUC keeps the final score of shorter histories instead of using a common-length cohort. Adapter logits are cross-fitted inside each outer training set and reused across the classifier's inner folds, so the inner procedure is not a fully nested end-to-end selection. PHQ extraction uses a 335M-parameter encoder, so a compact feature vector does not mean lower inference cost than MentalRoBERTa. We do not evaluate on the official eRisk test servers, which provide full conversational context.

Ethical Considerations

The data were obtained under the eRisk 2025 user agreement; we quote no posts and report only aggregate statistics. Depression detection can harm users through false accusations, exposure and misuse for profiling. Our results are for research on evaluation; the systems must not be used to screen, label or monitor people, and they do not provide a diagnosis. Code will be released without data and without the LIWC dictionary, which is licensed separately.

References

Sergio G. Burdisso, Marcelo Errecalde, and Manuel Montes-y Gómez. 2019. A text classification framework for simple and effective early depression detection over social media streams. *Expert Systems with Applications*, 133:182–197.

Gavin C. Cawley and Nicola L. C. Talbot. 2010. On over-fitting in model selection and subsequent selection bias in performance evaluation. *Journal of Machine Learning Research*, 11:2079–2107.

Stevie Chancellor and Munmun De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: A critical review. *npj Digital Medicine*, 3.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in Twitter. In *Proceedings of the Workshop on Computational Linguistics and Clinical Psychology: From Linguistic Signal to Clinical Reality*, pages 51–60, Baltimore, Maryland, USA. Association for Computational Linguistics.

Munmun De Choudhury, Michael Gamon, Scott Counts, and Eric Horvitz. 2013. Predicting depression via social media. In *Proceedings of the Seventh International AAAI Conference on Weblogs and Social Media*, pages 128–137.

Elizabeth R. DeLong, David M. DeLong, and Daniel L. Clarke-Pearson. 1988. Comparing the areas under two or more correlated receiver operating characteristic curves: A nonparametric approach. *Biometrics*, 44(3):837–845.

Janez Demšar. 2006. Statistical comparisons of classifiers over multiple data sets. *Journal of Machine Learning Research*, 7(1):1–30.

Thomas G. Dietterich. 1998. Approximate statistical tests for comparing supervised classification learning algorithms. *Neural Computation*, 10(7):1895–1923.

Sindhu Kiranmai Ernala, Michael L. Birnbaum, Kristin A. Candan, Asra F. Rizvi, William A. Sterling, John M. Kane, and Munmun De Choudhury. 2019. Methodological gaps in predicting mental health states from social media: Triangulating diagnostic signals. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems*. ACM.

Keith Harrigian, Carlos Aguirre, and Mark Dredze. 2020. Do models of mental health based on social media data generalize? In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 3774–3788, Online. Association for Computational Linguistics.

Keith Harrigian, Carlos Aguirre, and Mark Dredze. 2021. On the state of social media data for mental health research. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 15–24, Online. Association for Computational Linguistics.

Sture Holm. 1979. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6:65–70.

Neil Houlsby, Andrei Giurgiu, Stanislaw Jastrzebski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. 2019. Parameter-efficient transfer learning for NLP. In *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 2790–2799.

Molly E. Ireland and James W. Pennebaker. 2010. Language style matching in writing: Synchrony in essays, correspondence, and poetry. *Journal of Personality and Social Psychology*, 99(3):549–571.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. MentalBERT: Publicly available pretrained language models for mental healthcare. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 7184–7190, Marseille, France. European Language Resources Association.

Kurt Kroenke, Robert L. Spitzer, and Janet B. W. Williams. 2001. The PHQ-9: Validity of a brief depression severity measure. *Journal of General Internal Medicine*, 16(9):606–613.

Allison Lahnala, Vasudha Varadarajan, Lucie Flek, H. Andrew Schwartz, and Ryan L. Boyd. 2025. Unifying the extremes: Developing a unified model for detecting and predicting extremist traits and radicalization. *Proceedings of the International AAAI Conference on Web and Social Media*, 19(1):1051–1067.

Sean Lee, Aamir Shakir, Darius Koenig, and Julius Lipp. 2024. Open source strikes bread – new fluffy embeddings model. `https://www.mixedbread.ai/blog/mxbai-embed-large-v1`.

Xianming Li and Jing Li. 2023. AnglE-optimized text embeddings. ArXiv:2309.12871.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A robustly optimized BERT pretraining approach. ArXiv:1907.11692.

David E. Losada and Fabio Crestani. 2016. A test collection for research on depression and language use. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 28–39. Springer International Publishing.

David E. Losada, Fabio Crestani, and Javier Parapar. 2017. eRISK 2017: CLEF lab on early risk prediction on the internet: Experimental foundations. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 346–360. Springer International Publishing.

David E. Losada, Fabio Crestani, and Javier Parapar. 2018. Overview of eRisk: Early risk prediction on the internet. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 343–361. Springer International Publishing.

Ilya Loshchilov and Frank Hutter. 2017. Decoupled weight decay regularization. ArXiv:1711.05101.

Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157.

Claude Nadeau and Yoshua Bengio. 2003. Inference for the generalization error. *Machine Learning*, 52(3):239–281.

Javier Parapar, Patricia Martín-Rodilla, David E. Losada, and Fabio Crestani. 2022. Overview of eRisk 2022: Early risk prediction on the internet. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 233–256. Springer International Publishing.

Javier Parapar, Anxo Perez, Xi Wang, and Fabio Crestani. 2025. Overview of eRisk 2025: Early risk prediction on the internet. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 242–265. Springer Nature Switzerland.

James W. Pennebaker, Ryan L. Boyd, Kayla Jordan, and Kate Blackburn. 2015. The development and psychometric properties of LIWC2015. Technical report, University of Texas at Austin.

Jonas Pfeiffer, Andreas Rücklé, Clifton Poth, Aishwarya Kamath, Ivan Vulić, Sebastian Ruder, Kyunghyun Cho, and Iryna Gurevych. 2020. AdapterHub: A framework for adapting transformers. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 46–54, Online. Association for Computational Linguistics.

Clifton Poth, Hannah Sterz, Indraneil Paul, Sukannya Purkayastha, Leon Engländer, Timo Imhof, Ivan Vulić, Sebastian Ruder, Iryna Gurevych, and Jonas Pfeiffer. 2023. Adapters: A unified library for parameter-efficient and modular transfer learning. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 149–160, Singapore. Association for Computational Linguistics.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Farig Sadeque, Dongfang Xu, and Steven Bethard. 2018. Measuring the latency of depression detection in social media. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining*, pages 495–503. ACM.

Marcel Trotzek, Sven Koitka, and Christoph M. Friedrich. 2020. Utilizing neural networks and linguistic metadata for early detection of depression indications in text sequences. *IEEE Transactions on Knowledge and Data Engineering*, 32(3):588–601.

Gaël Varoquaux. 2018. Cross-validation failure: Small sample sizes lead to large error bars. *NeuroImage*, 180:68–77.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30.

Andrew Yates, Arman Cohan, and Nazli Goharian. 2017. Depression and self-harm risk assessment in online forums. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 2968–2978, Copenhagen, Denmark. Association for Computational Linguistics.

A PHQ-9 Archetype Sentences

We wrote one first-person sentence per PHQ-9 item; the PHQ feature of a post is the cosine similarity between the embedding of the post and the embedding of each sentence: (1) *I haven't been wanting to do anything.* (2) *I've been feeling really low lately.* (3) *I can't sleep properly—either too little or too much.* (4) *I barely have any energy to do things.* (5) *My appetite is totally messed up.* (6) *I feel like I'm not good enough.* (7) *I can't focus on anything for long.* (8) *I feel like I'm moving in slow motion.* (9) *I just feel like giving up sometimes.*

B Implementation Details

Sequence model and training. Input projection to 256 dimensions, 3 Transformer encoder layers (4 heads, feed-forward width 2048, dropout 0.3), a two-layer head (256→64→1) producing one logit per post, no positional encoding (order enters through the causal mask and the post-index feature), at most 30 epochs, patience 5, weight decay 0.01, gradient clipping 1.0, length-bucketed batches of at most 32 users. Hyper-parameters (learning rate $3 \cdot 10^{-5}$, 256×3) were chosen on a 16-configuration grid by out-of-fold PR-AUC on the 712 training users of an earlier fixed split; the spread across the grid is about 0.075 PR-AUC. (θ, k) is selected by F_{lat}, ties by F1, then shorter delay, then lower threshold.

Adapter. Bottleneck adapter and a two-class head on mental/mental-roberta-base (126.8M parameters, 2.13M trained), post-level training with the user label, 3 epochs, learning rate $3 \cdot 10^{-4}$, batch size 32, maximum length 256, at most 200 random posts per user and epoch, best epoch chosen on 10% of the fit users. In the cross-validation three inner models are trained per outer fold on the outer training users; training users receive the logit of the inner model that did not see them, held-out users the mean of the three.

TF-IDF. Word 1–2-grams, minimum document frequency 5, at most 200,000 terms, sublinear tf, vocabulary fitted on the outer training text without labels; logistic regression ($C = 1$, user-weighted, class-balanced); C was fixed and not tuned.

Single split versus cross-validation. On a fixed split with 21 test positives, the 74-feature set reached PR-AUC .820 on the test users (mean of

three seeds; .831 with the relative-entropy feature), against .753 pooled over all users in the cross-validation; single-split estimates of this kind are optimistic.

Artifacts and licences. The eRisk data are used under the lab's user agreement and are not redistributed. LIWC2015 is licensed separately and not redistributed. mental-roberta-base is used under CC BY-NC 4.0 for non-commercial research; all-MiniLM-L6-v2 and mxbai-embed-large-v1 are Apache-2.0. Our own code and the archetype sentences will be released with the paper.

Compute. The cross-validation (15 outer folds, 15 configurations) and the adapter runs used two 24 GB GPUs; the sequence models train in about a minute per outer fold.

C Paired Tests

Table 7 gives all 22 pre-specified comparisons. Holm: bootstrap p-value adjusted within the family; NB: Nadeau–Bengio corrected resampled t-test over the 15 folds; DeLong and McNemar: median over the three repeats. The tests agree for the main findings (PHQ against LSM and against the control; adapter against TF-IDF). They differ for borderline comparisons: PHQ against LIWC in PR-AUC (NB $p = .209$) and F1 (McNemar $p = .060$); the adapter against the frozen encoder in PR-AUC (NB $p = .057$); the four-score variant against the alignment variant in ROC-AUC (NB $p = .215$). We therefore describe these as suggestive.

D Self-Report Patterns

The self-report pattern matches first-person statements such as "I have/had/suffer from/struggle with/deal with/was diagnosed with (up to two words) depression", "my depression", "I'm depressed" and "diagnosed with (up to two words) depression" (case-insensitive). The mental-health vocabulary pattern covers terms such as depression, anxiety, therapy, psychiatric, antidepressant, suicide, bipolar, PTSD and self-harm. Both were fixed before the errors were inspected and are not validated; they miss phrasings such as "I've been depressed" or "diagnosed with MDD".

E Error Categories

One reader assigned each false positive of the adapter-tuned model (21 users) and of the 74-feature set (34 users) to the first matching category, from the highest-scoring posts; there was no second annotator, so counts are indicative. *Own depression described in the first person*: 8 and 6; *other mental-health condition or treatment*: 4 and 9; *chronic physical illness*: 3 and 4; *everyday distress*: 4 and 9; *supportive commenters in mental-health communities*: 2 and 5; *no clear depression-related content*: 0 and 1. Of the 20 users missed by the adapter-tuned model, 17 contain a first-person statement of a diagnosis or ongoing depression (the keyword pattern finds 12).

Fam.	A − B	ΔROC	Holm	NB	DeLong	ΔPR	Holm	NB	ΔF1	Holm	McNemar
1	74 feat. − PHQ	+0.001	1	.504	.747	+0.010	1	.715	+0.005	1	.243
1	74 feat. − PHQ + 3 LIWC	+0.001	1	.825	.574	+0.004	1	.657	−0.009	1	.377
1	74 feat. − PHQ + 3 LIWC + 4 LSM	−0.005	.042	.215	.066	−0.025	.322	.269	−0.028	.182	.180
1	74 feat. − MentalRoBERTa frozen	+0.015	.192	.194	.168	+0.027	1	.925	−0.006	1	.392
1	74 feat. − MentalRoBERTa adapter	−0.010	.192	.032	.096	−0.039	.810	.033	−0.065	.088	.019
1	MentalRoBERTa adapter − MentalRoBERTa frozen	+0.024	.004	.024	.004	+0.065	.045	.057	+0.059	.018	.041
1	Adapter + 74 feat. − MentalRoBERTa adapter	−0.005	1	.142	.432	−0.020	1	.119	−0.050	.270	.044
1	Adapter + 74 feat. − 74 feat.	+0.005	.004	.041	.010	+0.019	.192	.080	+0.015	.570	.289
1	Frozen + 74 feat. − 74 feat.	+0.004	1	.222	.580	−0.011	1	.158	−0.004	1	.362
2	MentalRoBERTa adapter − TF-IDF	+0.049	.002	<.001	<.001	+0.111	.002	.003	+0.073	.004	.073
2	MentalRoBERTa frozen − TF-IDF	+0.024	.002	.022	.008	+0.046	.204	.007	+0.014	1	1
2	PHQ − TF-IDF	+0.038	.002	.012	<.001	+0.062	.204	.061	+0.003	1	.784
2	74 feat. − TF-IDF	+0.039	.002	.006	<.001	+0.072	.138	.031	+0.008	1	.341
3	PHQ − Context only	+0.291	.004	<.001	<.001	+0.409	.004	<.001	+0.482	.004	<.001
3	LIWC − Context only	+0.264	.004	<.001	<.001	+0.326	.004	<.001	+0.417	.004	<.001
3	LSM (counts) − Context only	+0.212	.004	<.001	<.001	+0.223	.004	.019	+0.328	.004	<.001
3	LSM alignment − Context only	+0.189	.004	<.001	<.001	+0.144	.042	.035	+0.271	.004	<.001
3	Cosine sim. − Context only	+0.066	.018	.026	.029	−0.030	.686	.962	+0.036	.004	<.001
3	Behaviour − Context only	+0.146	.004	<.001	<.001	+0.042	.686	.241	+0.202	.004	<.001
3	PHQ − LIWC	+0.027	.004	.014	.007	+0.082	.024	.209	+0.064	.017	.060
3	PHQ − LSM alignment	+0.102	.004	<.001	<.001	+0.264	.004	<.001	+0.211	.004	<.001
3	PHQ − LSM (counts)	+0.078	.004	.001	<.001	+0.186	.004	.011	+0.154	.004	.007

Table 7: Pre-specified paired comparisons. Families: 1 references, 2 TF-IDF baseline, 3 feature groups and control. Differences are A − B, mean over repeats. 74 feat.: PHQ + 3 LIWC + LSM alignment; 4 LSM: four count-LSM scores. Holm values of .004 and .002 are the smallest attainable with 2000 draws.