

All Training materials are provided "as is" and without warranty and RStudio disclaims any and all express and implied warranties including without limitation the implied warranties of title, fitness for a particular purpose, merchantability and noninfringement.

The Training Materials are licensed under the Creative Commons Attribution-Noncommercial 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc/3.0/us/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

How to start with Shiny, Part 3

How to customize appearance



Garrett Grolemond

Data Scientist and Master Instructor

May 2015

Email: garrett@rstudio.com

Twitter: @StatGarrett

Code and slides at:
bit.ly/shiny-quickstart-3

Shiny Apps for the Enterprise



Shiny Dashboard Demo

A dashboard built with Shiny.



Location tracker

Track locations over time with streaming data.



Download monitor

Streaming download rates visualized as a bubble chart.



Supply and Demand

Forecast demand to plan resource allocation.

Shiny Showcase

www.rstudio.com/products/shiny/shiny-user-showcase/

Industry Specific Shiny Apps



Economic Dashboard

Economic forecasting with macroeconomic indicators.




ER Optimization

An app that models patient flow.



CDC Disease Monitor

Alert thresholds and automatic weekly updates.




Ebola Model

An epidemiological simulation.



How to start with Shiny



1. How to build a Shiny app (www.rstudio.com/resources/webinars/)
2. How to customize reactions (www.rstudio.com/resources/webinars/)
3. How to customize appearance (Today)

The story
so far

Every Shiny app is maintained by a computer running R



Sharing apps



Shiny Server (Pro)

App template

The shortest viable shiny app




```
library(shiny)
```

```
ui <- fluidPage()
```



```
server <- function(input, output) {}
```

```
shinyApp(ui = ui, server = server)
```

Reactivity



User Interface



Work with the
HTML UI

The HTML that builds the user interface for your app

```
ui <- fluidPage()
```

```
fluidPage()
```

```
<div class="container-fluid"></div>
```



```
library(shiny)


ui <- fluidPage(

)

server <- function(input, output) {

}

shinyApp(ui = ui, server = server)
```




```
library(shiny)

ui <- fluidPage(
  sliderInput(inputId = "num",
    label = "Choose a number",
    value = 25, min = 1, max = 100)
)

server <- function(input, output) {

}

shinyApp(ui = ui, server = server)
```




```
library(shiny)

ui <- fluidPage(
  sliderInput(inputId = "num",
    label = "Choose a number",
    value = 25, min = 1, max = 100),
  plotOutput("hist")
)

server <- function(input, output) {

}

shinyApp(ui = ui, server = server)
```



```
sliderInput(inputId = "num",  
  label = "Choose a number",  
  value = 25, min = 1, max = 100)
```

```
<div class="form-group shiny-input-container">  
  <label class="control-label" for="num">Choose a number</label>  
  <input class="js-range-slider" id="num" data-min="1" data-max="100"  
    data-from="25" data-step="1" data-grid="true" data-grid-num="9.9"  
    data-grid-snap="false" data-prettify-separator="," data-keyboard="true"  
    data-keyboard-step="1.01010101010101"/>  
</div>
```

```
plotOutput("hist")
```

```
<div id="hist" class="shiny-plot-output" style="width: 100% ; height: 400px"></div>
```


Recap: User Interface



Call R functions to assemble HTML

```
fluidPage()
```

Use **fluidPage()** to quickly set up a UI



Use **input*()** and **output*()** functions to add reactive content.

```
ui <-
```


Save the output to **ui**

Add

static content


How do you add content to a web page?

```
<div class="container-fluid"></div>
```




```
<div class="container-fluid">
```


```
</div>
```




```
<div class="container-fluid">  
  <h1>My Shiny App</h1>  
</div>
```





```
<div class="container-fluid">  
  <h1>My Shiny App</h1>  
  <p>See other apps in the</p>  
</div>
```




```
<div class="container-fluid">  
  <h1>My Shiny App</h1>  
  <p>See other apps in the  
  
</p>  
</div>
```




```
<div class="container-fluid">
  <h1>My Shiny App</h1>
  <p>See other apps in the
    <a href="http://www.rstudio.com/
      products/shiny/shiny-user-
      showcase/">Shiny Showcase</a>
  </p>
</div>
```



```
<div class="container-fluid">
  <h1>My Shiny App</h1>
  <p>See other apps in the
    <a href="http://www.rstudio.com/
      products/shiny/shiny-user-
      showcase/">Shiny Showcase</a>
  </p>
</div>
```



```
<div class="container-fluid">
  <h1>My Shiny App</h1>
  <p style="font-family:Impact">
    See other apps in the
    <a href="http://www.rstudio.com/
      products/shiny/shiny-user-
      showcase/">Shiny Showcase</a>
  </p>
</div>
```



How do you add content to a web page?

When writing HTML, you add content with **tags**.

```
<h1></h1>
```

```
<a></a>
```

How do you add content to a web page?

When writing R, you add content with **tags** functions.

`tags$h1()` ↔ `<h1></h1>`

`tags$a()` ↔ `<a>`

Shiny HTML tag functions

Shiny provides R functions to recreate HTML tags.

`tags$h1()` ↔ `<h1></h1>`

`tags$a()` ↔ `<a>`

tags

Each element of the tags list is a function that recreates an html tag.

`names(tags)`

```
## [1] "a" "abbr" "address" "area"
## [5] "article" "aside" "audio" "b"
## [9] "base" "bdi" "bdo" "blockquote"
## [13] "body" "br" "button" "canvas"
## [17] "caption" "cite" "code" "col"
## [21] "colgroup" "command" "data" "datalist"
## [25] "dd" "del" "details" "dfn"
## [29] "div" "dl" "dt" "em"
## [33] "embed" "eventsource" "fieldset" "figcaption"
## [37] "figure" "footer" "form" "h1"
## [41] "h2" "h3" "h4" "h5"
```

A list of functions

```
tags$h1
```

```
function (...)  
tag("h1", list(...))  
<environment: namespace:htmltools>
```

```
tags$h1()
```

```
<h1></h1>
```

tags syntax

```
tags$a(href = "www.rstudio.com", "RStudio")
```

the list
named tags

the function/tag name
(followed by parentheses)

named arguments
appear as tag attributes
(set boolean attributes to NA)



unnamed arguments
appear inside the tags
(call tags\$...() to create nested tags)

```
<a href="www.rstudio.com">RStudio</a>
```


h1() - h6()

Headers



```
fluidPage(  
  tags$h1("First level"),  
  tags$h2("Second level"),  
  tags$h3("Third level"),  
  tags$h4("Fourth level"),  
  tags$h5("Fifth level"),  
  tags$h6("Sixth level")  
)
```



a()

hyperlink with the href argument



```
fluidPage(  
  tags$a(href= "http://www.git.com",  
    "Git")  
)
```



text

Character strings do not need a tag.



```
fluidPage(  
  "This is a Shiny app.",  
  "It is also a web page."  
)
```



p()

A new paragraph



```
fluidPage(  
  tags$p("This is a Shiny app."),  
  tags$p("It is also a web page.")  
)
```



em()

Emphasized (*italic*) text



```
fluidPage(  
  tags$em("This is a Shiny app.")  
)
```



strong()

Strong (**bold**) text


```
fluidPage(  
  tags$strong("This is a Shiny app.")  
)
```



code()

Monospaced text (code)



```
fluidPage(  
  tags$code("This is a Shiny app.")  
)
```



nesting

You can also nest functions inside of others



```
fluidPage(  
  tags$p("This is a",  
    tags$strong("Shiny"),  
    "app.")  
)
```



br()

A line break



```
fluidPage(  
  "This is a Shiny app.",  
  tags$br(),  
  "It is also a web page."  
)
```



hr()

A horizontal rule



```
fluidPage(  
  "This is a Shiny app.",  
  tags$hr(),  
  "It is also a web page."  
)
```



img()


Add an image. Use **src** argument to point to the image URL.

```
fluidPage(  
  tags$img(height = 100,  
    width = 100,  
    src = "http://www.rstudio.com/  
    images/RStudio.2x.png")  
)
```



Adding Images



To add an image from a file, save the file in a subdirectory named **www**



img()

Add an img from a file in www

```
fluidPage(  
  tags$img(height = 100,  
           width = 100,  
           src = "bigorb.png")  
)
```



Some tags functions come with a wrapper function, so you do not need to call tags\$

```
h1
```


```
function (...)
```

```
tags$h1(...)
```

```
<environment: namespace:htmltools>
```

Function	Creates
<code>a()</code>	A Hyperlink
<code>br()</code>	A line break
<code>code()</code>	Text formatted like computer code
<code>em()</code>	Italicized (emphasized) text
<code>h1()</code> , <code>h2()</code> , <code>h3()</code> , <code>h4()</code> , <code>h5()</code> , <code>h6()</code>	Headers (First level to sixth)
<code>hr()</code>	A horizontal rule (line)
<code>img()</code>	An image
<code>p()</code>	A new paragraph
<code>strong()</code>	Bold (strong) text

```
<div class="container-fluid">
  <h1>My Shiny App</h1>
  <p style="font-family:Impact">
    See other apps in the
    <a href="http://www.rstudio.com/
      products/shiny/shiny-user-
      showcase/">Shiny Showcase</a>
  </p>
</div>
```



fluidPage(

```
<h1>My Shiny App</h1>
```


```
<p style="font-family:Impact">
```

```
  See other apps in the
```


```
  <a href="http://www.rstudio.com/  
    products/shiny/shiny-user-  
    showcase/">Shiny Showcase</a>
```

```
</p>
```


)




```
fluidPage(  
  h1("My Shiny App"),  
  <p style="font-family:Impact">  
    See other apps in the  
    <a href="http://www.rstudio.com/  
      products/shiny/shiny-user-  
      showcase/">Shiny Showcase</a>  
  </p>  
)
```





```
fluidPage(  
  h1("My Shiny App"),  
  p(style = "font-family:Impact",  
    "See other apps in the",  
    <a href="http://www.rstudio.com/  
      products/shiny/shiny-user-  
      showcase/">Shiny Showcase</a>  
  )  
)
```



```
fluidPage(  
  h1("My Shiny App"),  
  p(style = "font-family:Impact",  
    "See other apps in the",  
    a("Shiny Showcase",  
      href = "http://www.rstudio.com/  
products/shiny/shiny-user-showcase/")  
    )  
)
```




```
fluidPage(  
  tags$h1("My Shiny App"),  
  tags$p(style = "font-family:Impact",  
    "See other apps in the",  
    tags$a("Shiny Showcase",  
      href = "http://www.rstudio.com/  
        products/shiny/shiny-user-showcase/")  
    )  
  )  
)
```



```
fluidPage(
```

```
  <div class="container-fluid">  
    <h1>My Shiny App</h1>  
    <p style="font-family:Impact">  
      See other apps in the  
      <a href="http://www.rstudio.com/  
        products/shiny/shiny-user-  
        showcase/">Shiny Showcase</a>  
    </p>  
  </div>
```


```
)
```





```
fluidPage(
```

```
  '    <h1>My Shiny App</h1>  
    <p style="font-family:Impact">  
      See other apps in the  
      <a href="http://www.rstudio.com/  
        products/shiny/shiny-user-  
        showcase/">Shiny Showcase</a>  
    </p>  
  </div>'
```

```
)
```





```
fluidPage(  
  HTML(  
    '<div class="container-fluid">  
      <h1>My Shiny App</h1>  
      <p style="font-family:Impact">  
        See other apps in the  
        <a href="http://www.rstudio.com/  
          products/shiny/shiny-user-  
            showcase/">Shiny Showcase</a>  
      </p>  
    </div>'  
  )  
)
```



Raw HTML

Use `HTML()` to pass a character string as raw HTML

```
fluidPage(  
  HTML("<h1>My Shiny App</h1>")  
)
```



Recap: Reactive values

```
names(tags)
## [1] "a"          "abbr"        "address"     "area"
## [5] "article"    "aside"       "audio"       "b"
## [9] "base"       "bdi"         "bdo"         "blockquote"
## [13] "body"       "button"      "caption"     "code"
## [17] "colgroup"  "command"    "col"         "colspan"
## [21] "del"        "details"    "del"         "dfn"
## [25] "div"        "div"        "div"         "div"
## [29] "div"        "div"        "div"         "div"
## [33] "div"        "div"        "div"         "div"
## [37] "div"        "div"        "div"         "div"
## [41] "div"        "div"        "div"         "div"
## [45] "div"        "div"        "div"         "div"
```


Add elements with the **tags\$** functions

```
<p id="foo">
  foo
</p>
```

unnamed arguments are passed into HTML tags

```
<p id="foo">
  foo
</p>
```

named arguments are passed as HTML tag attributes



Add raw html with **HTML()**

HTML UI

shiny.rstudio.com/articles/html-ui.html

Build your entire UI from HTML

```
<html>


<head>
  <script src="shared/jquery.js" type="text/javascript"></script>
  <script src="shared/shiny.js" type="text/javascript"></script>
  <link rel="stylesheet" type="text/css" href="shared/shiny.css"/>
</head>

<body>
  <h1>HTML UI</h1>


  <p>
    <label>Distribution type:</label><br />
```

Create a
layout

Use layout functions to position elements within your app



Use layout functions to position elements
within your app



Layout functions

Add HTML that divides the UI into a grid

```
fluidRow()
```

```
<div class="row"></div>
```



```
column(width = 2)
```

```
<div class="col-sm-2"></div>
```

fluidRow()

`fluidRow()` adds rows to the grid. Each new row goes below the previous rows.

```
ui <- fluidPage(  
  fluidRow(),  
  fluidRow()  
)
```





column()

`column()` adds columns within a row. Each new column goes to the left of the previous column.

Specify the **width** and **offset** of each column out of 12

```
ui <- fluidPage(  
  fluidRow(  
    column(3),  
    column(5)),  
  fluidRow(  
    column(4, offset = 8)  
  )  
)
```



To place an element in the grid, call it as an argument of a layout function

`fluidRow()`

```
<div class="row"></div>
```

`column(2)`

```
<div class="col-sm-2">  
</div>
```

To place an element in the grid, call it as an argument of a layout function

```
fluidRow("In the row")
```

```
<div class="row"></div>
```

```
column(2)
```

```
<div class="col-sm-2">  
</div>
```

To place an element in the grid, call it as an argument of a layout function

```
fluidRow("In the row")
```

```
<div class="row">In the row</div>
```

```
column(2)
```

```
<div class="col-sm-2">  
</div>
```


To place an element in the grid, call it as an argument of a layout function

```
fluidRow("In the row")
```

```
<div class="row">In the row</div>
```

```
column(2, plotOutput("hist"))
```

```
<div class="col-sm-2">  
</div>
```

To place an element in the grid, call it as an argument of a layout function

```
fluidRow("In the row")
```



```
<div class="row">In the row</div>
```

```
column(2, plotOutput("hist"))
```

```
<div class="col-sm-2">  
  <div id="hist" class="shiny-plot-output"  
    style="width: 100% ; height: 400px"></div>  
</div>
```



To place an element in the grid, call it as an argument of a layout function

```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5)  
  ),  
  fluidRow(  
    column(4, offset = 8,)  
  )  
)
```




To place an element in the grid, call it as an argument of a layout function

```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5, sliderInput(...))  
  ),  
  fluidRow(  
    column(4, offset = 8)  
  )  
)
```




To place an element in the grid, call it as an argument of a layout function

```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5, sliderInput(...))  
  ),  
  fluidRow(  
    column(4, offset = 8)  
  )  
)
```





To place an element in the grid, call it as an argument of a layout function

```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5, sliderInput(...))  
  ),  
  fluidRow(  
    column(4, offset = 8,  
      plotOutput("hist")  
    )  
  )  
)
```




To place an element in the grid, call it as an argument of a layout function

```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5, sliderInput(...))  
  ),  
  fluidRow(  
    column(4, offset = 8,  
      plotOutput("hist")  
    )  
  )  
)
```




To place an element in the grid, call it as an argument of a layout function


```
fluidPage(  
  fluidRow(  
    column(3),  
    column(5, sliderInput(...))  
  ),  
  fluidRow(  
    column(4, offset = 8,  
      plotOutput("hist")  
    )  
  )  
)
```




Choose a number




Histogram of rnorm(input\$num)




Recap: Layout functions




Position elements in a grid, or stack them in layers.



Use **fluidRow()** to arrange elements in rows




Use **column()** to arrange elements in columns



Column takes **width** and **offset** arguments

Assemble
layers
of panels

Use layout functions to position elements
within your app



Panels

Panels to group multiple elements into a single unit with its own properties.

The diagram illustrates the concept of Shiny panels. On the left, a large panel titled "Action button" is shown. It contains an "Action" button and a "Current Value:" section displaying the following R output:

```
[1] 0
attr(,"class")
[1] "integer"
"shinyActionButtonValue"
```

Below the current value is a "See Code" button. On the right, a browser window titled "Shiny Widgets Gallery" is shown. It displays a grid of various Shiny widgets, including "Action button", "Single checkbox", "Checkbox group", "Date input", "Date range", and "File input". A blue arrow points from the "Action button" panel on the left to the "Action button" widget in the browser window, indicating that the panel is a component of the gallery.

<http://shiny.rstudio.com/gallery/widget-gallery.html>

wellPanel()



Groups elements into a grey "well"

```
# 04-well.R

ui <- fluidPage(

  sliderInput("num", "Choose a number",
    value = 25, min = 1, max = 100),
  textInput("title", value = "Histogram",
    label = "Write a title"),

  plotOutput("hist")
)
```





wellPanel()

Groups elements into a grey "well"

```
# 04-well.R

ui <- fluidPage(
  wellPanel(
    sliderInput("num", "Choose a number",
      value = 25, min = 1, max = 100),
    textInput("title", value = "Histogram",
      label = "Write a title"),
  ),
  plotOutput("hist")
)
```



absolutePanel()

Panel position set rigidly (absolutely), not fluidly

conditionalPanel()

A JavaScript expression determines whether panel is visible or not.

fixedPanel()

Panel is fixed to browser window and does not scroll with the page

headerPanel()

Panel for the app's title, used with `pageWithSidebar()`

inputPanel()

Panel with grey background, suitable for grouping inputs

mainPanel()

Panel for displaying output, used with `pageWithSidebar()`

navlistPanel()

Panel for displaying multiple stacked `tabPanels()`. Uses sidebar navigation

sidebarPanel()

Panel for displaying a sidebar of inputs, used with `pageWithSidebar()`

tabPanel()

Stackable panel. Used with `navlistPanel()` and `tabsetPanel()`

tabsetPanel()

Panel for displaying multiple stacked `tabPanels()`. Uses tab navigation

titlePanel()

Panel for the app's title, used with `pageWithSidebar()`

wellPanel()

Panel with grey background.

tabPanel()

`tabPanel()` creates a stackable layer of elements.
Each tab is like a small UI of its own.

```
tabPanel("Tab 1", ...)
```

A title
(for navigation)

elements to
appear in the tab



Combine `tabPanel()`'s with one of:

- `tabsetPanel()`
- `navlistPanel()`
- `navbarPage()`

tabsetPanel()


`tabsetPanel()` combines tabs into a single *panel*.
Use *tabs* to navigate between tabs.

```
fluidPage(  
  tabsetPanel(  
    tabPanel("tab 1", "contents"),  
    tabPanel("tab 2", "contents"),  
    tabPanel("tab 3", "contents")  
  )  
)
```



Navigation



Content



navlistPanel()

`navlistPanel()` combines tabs into a single *panel*.
Use *links* to navigate between tabs.



```
fluidPage(  
  navlistPanel(  
    tabPanel("tab 1", "contents"),  
    tabPanel("tab 2", "contents"),  
    tabPanel("tab 3", "contents")  
  )  
)
```



navlistPanel()


`navlistPanel()` combines tabs into a single *panel*.
Use *links* to navigate between tabs.

```
fluidPage(  
  navlistPanel(  
    tabPanel("tab 1", "contents"),  
    tabPanel("tab 2", "contents"),  
    tabPanel("tab 3", "contents")  
  )  
)
```




Examples in 05-tabs.R
and 06-navlist.R

Recap: Panels




Panels group elements into a single unit for aesthetic or functional reasons



Use **tabPanel()** to create a stackable panel



Use **tabsetPanel()** to arrange tab panels into a stack with tab navigation



Use **navlistPanel()** to arrange tab panels into a stack with sidebar navigation

The Shiny Layout Guide

<http://shiny.rstudio.com/articles/layout-guide.html>





You can build sophisticated, customized layouts with Shiny's grid system.

Use a
**prepackaged
layout**

sidebarLayout()

Use with `sidebarPanel()` and `mainPanel()` to divide app into two sections.

```
ui <- fluidPage(  
  sidebarLayout(  
    sidebarPanel(),  
    mainPanel()  
  )  
)
```



Example in
07-sidebar.R

`fixedPage()`

Creates a page that defaults to a width of 724, 940, or 1170 pixels (depending on browser window)

```
ui <- fixedPage(  
  fixedRow(  
    column(5, # etc.)  
  )  
)
```



Use with **fixedRow()**

Compare to `fluidPage()` and `fluidRow()` which adjust to browser window

navbarPage()


`navbarPage()` combines tabs into a single *page*.
navbarPage() replaces *fluidPage()*. Requires title.

```
navbarPage(title = "Title",  
  tabPanel("tab 1", "contents"),  
  tabPanel("tab 2", "contents"),  
  tabPanel("tab 3", "contents")  
)
```




Navigation

Content



tabPanel **tabPanel** **tabPanel** **tabPanel**




navbarPage

navbarMenu()

`navbarMenu()` combines tab links into a dropdown menu for `navbarPage()`



```
navbarPage(title = "Title",  
  tabPanel("tab 1", "contents"),  
  tabPanel("tab 2", "contents"),  
  navbarMenu(title = "More",  
    tabPanel("tab 3", "contents"),  
    tabPanel("tab 4", "contents"),  
    tabPanel("tab 5", "contents")  
  )  
)
```



dashboardPage()


`dashboardPage()` comes in the shinydashboard package

```
library(shinydashboard)
ui <- dashboardPage(
  dashboardHeader(),
  dashboardSidebar(),
  dashboardBody()
)
```



shinydashboard

<http://rstudio.github.io/shinydashboard/>




A package of layout functions for building administrative dashboards with Shiny

Dynamic Dashboards with Shiny Webinar:

www.rstudio.com/resources/webinars/


Recap: Prepackaged Layouts




Use **sidebarLayout()** with **sidebarPanel()** and **mainPanel()** to quickly create a sidebar design.



Use **fixedPanel()** with **fixedrow()** to create a fixed (non-fluid) design



Use **navbarPage()** with **navbarMenu()** to create "multipage" app






Use the **shinyDashboard** package to create dashboard layouts


Style with
CSS

What is CSS?

Cascading Style Sheets (CSS) are a framework for customizing the appearance of elements in a web page.



Style a web page in three ways:


- 
- 1** Link to an external CSS file
 - 2** Write global CSS in header
 - 3** Write individual CSS in a tag's style attribute
- Overrides

Match styling to:

- 
- 1** Tag
 - 2** Class
 - 3** id
- Overrides

Bootstrap

Shiny uses the Bootstrap 3 CSS framework, getbootstrap.com




Bootstrap

Shiny uses the Bootstrap 3 CSS framework, getbootstrap.com

```
fluidPage()
```

```
<div class="container-fluid"></div>
```



Style a **Shiny app** in three ways:

- 
- 1** Link to an external CSS file
 - 2** Write global CSS in header
 - 3** Write individual CSS in a tag's style attribute
- Overrides

*CSS designed to work with Bootstrap 3 will work best with Shiny.

1 Link to an external CSS file

Place .css files in the **www** folder of your app directory



Shiny will share a file with your user's browser if the file appears in **www**. Shiny will not share files that you do not place in **www**.

1 Link to an external CSS file


Set the theme argument of `fluidPage()` to the .css filename, or...

```
ui <- fluidPage(  
  theme = "bootswatch-cerulean.css",  
  sidebarLayout(  
    sidebarPanel(),  
    mainPanel()  
  )  
)
```

1 Link to an external CSS file

Or place a link in the app's header with to the file with **tags\$head()** and **tags\$link()**

```
ui <- fluidPage(  
  tags$head(  
  
  
  
  
  
  
  
  
  
  )  
)
```




```
<head>  
  
</head>  
<body>  
  <div class="container-fluid">  
    </div>  
</body>
```

1 Link to an external CSS file

Or place a link in the app's header with to the file with **tags\$head()** and **tags\$link()**

```
ui <- fluidPage(  
  tags$head(  
    tags$link(  
      rel = "stylesheet",  
      type = "text/css",  
      href = "file.css"  
    )  
  )  
)
```




```
<head>  
  <link type="text/css" rel="stylesheet" href="file.css"/>  
</head>  
<body>  
  <div class="container-fluid">  
    </div>  
</body>
```

2 Write global CSS in header

Write global CSS with **tags\$head()** and **tags\$style()** and **HTML()**

```
ui <- fluidPage(  
  tags$head(  
    tags$style(HTML("  
      p {  
        color:red;  
      }  
    "))  
  )  
)
```




```
<head>  
  <style>  
    p {  
      color:red;  
    }  
  </style>  
</head>  
<body>  
  <div class="container-fluid">  
    </div>  
</body>
```

2 Write global CSS in header

Or save the CSS as a file in your app directory and include it with **includeCSS()**

```
ui <- fluidPage(  
  includeCSS("file.css")  
)
```



```
<head>  
  <style>  
    p {  
      color:red;  
    }  
  </style>  
</head>  
  
<body>  
  <div class="container-fluid">  
  
  </div>  
</body>
```



3 Write individual CSS in a tag's style attribute

Set the style argument in Shiny's tag functions

```
ui <- fluidPage(  
  tags$h1("Title", style = "color:red;")  
)
```

To learn more about CSS & HTML


<http://www.codecademy.com/tracks/web>



I recommend the
free codecademy
tutorial

Customize your apps with HTML, CSS, and Javascript


<http://shiny.rstudio.com/articles/css.html>



You can pair any app with whatever web technologies you wish. The above guide explains how to style your app with CSS.


Add Google Analytics to a Shiny app

<http://shiny.rstudio.com/articles/google-analytics.html>




A case study in using jQuery to track visitor actions with Google Analytics

Recap: Style with CSS



Style Shiny apps like web pages: with CSS.



Shiny's general CSS classes come from the **bootstrap 3** framework

```
names(tags)
## [1] "a" "abbr" "address" "area"
## [5] "article" "aside" "audio" "b"
## [9] "base" "bdi" "bdo" "blockquote"
## [13] "body" "br" "button" "canvas"
## [17] "caption" "cite" "code" "col"
## [21] "colgroup" "command" "data" "datalist"
## [25] "del" "del" "details" "div"
## [29] "div" "div" "div" "div"
## [33] "embed" "eventsource" "fieldset" "figcaption"
## [37] "figure" "figure" "figure" "figure"
## [41] "h2" "h2" "h2" "h2"
## [45] "h2" "h2" "h2" "h2"
```

You can recreate HTML methods for including CSS with **tags\$head()**, **tags\$link()** and **tags\$style()**


You now how to

My Shiny App




See other apps in
the **Shiny Showcase**

Add static
elements




Lay out
elements




Style elements
with CSS


How to start with Shiny



Build and
share apps
(Part 1)



Control
reactions
(Part 2)



Customize
appearance
(Part 3)

**Where to go
from here**

Experiment and practice
build your own
apps

The Shiny Development Center

shiny.rstudio.com

