QuickShop's Use Cases

- UC1 - Browse Items
- UC2 - Compare Prices
- UC3 - Add Item to Cart
- UC4 - View Cart
- UC5 - Proceed to Checkout
- UC6 - Save Item for Later

Use Case: BrowseItems	
Identifier:	UC1
Description:	The BrowseItems case models a user exploring available grocery items across multiple retailers using Quick Shop.
Actors:	User
Preconditions:	The user has launched Quick Shop and has internet access.
Flow Of Events:	1. User enters a keyword (e.g., "orange juice") or selects a product category (e.g., beverages). 2. All listings for relevant products (e.g., "Tropicana 1L", "Store-brand OJ") from different stores are displayed. a. For each product found, the system displays product name, store, price, delivery info, and availability.
Postconditions:	A raw, unsorted list of items is shown to the user based on their query or category.

Use Case: Sort and Filter Items	
Identifier:	UC2
Description:	The Sort and Filter Items case models a user narrowing down the list of items using various sorting and filtering options.
Actors:	User
Preconditions:	The user has performed a search or selected a category and is viewing a product list.

Flow Of Events:	1. The user is presented with filter options (e.g., price range, store, dietary preference, brand). 2. The user selects one or more filters (price, relevance, etc…). 3. Quick Shop re-fetches or reorganizes the item list to reflect the selected filters and sort order.
Postconditions:	A refined and narrowed down item list is shown to the user based on applied filters and sorting.

Use Case: Add Item to Cart	
Identifier:	UC3
Description:	The Add Item To Cart case models a user adding a grocery item from a selected retailer to the Quick Shop universal cart.
Actors:	User
Preconditions:	The user has selected a product and chosen a group of preferred retailers.
Flow Of Events:	1. The user selects “Add to Cart” on the desired listing. 2. Quick Shop checks if the item already exists in the cart. 3. If new, the item is added to the cart with retailer data attached. or If duplicate, Quick Shop prompts the user to update or ignore. 4. A confirmation message appears (“Item added to cart”).
Postconditions:	The item appears in the Quick Shop cart, associated with the selected store.

Use Case: View Cart	
Identifier:	UC4
Description:	The ViewCart case models a user reviewing the contents of their Quick Shop cart.

Actors:	User
Preconditions:	The user has added at least one item to the cart.
Flow Of Events:	1. The user selects the cart. 2. Quick Shop displays all cart items, grouped by retailer. 3. The user may do any of the following: a. adjust quantities or remove items. b. sort the cart by price, store, or item name. c. filter by store or availability. 4. The cart updates dynamically to reflect these changes.
Postconditions:	The cart reflects the user's current selections and is ready for checkout.

Use Case: Proceed to Checkout	
Identifier:	UC5
Description:	This use case models a user choosing to purchase a specific item from a selected retailer, and Quick Shop redirecting them to the retailer's website to complete the transaction.
Actors:	User
Preconditions:	The user has added one or more specific product listings to the cart. Each product in the cart is tied to a unique retailer (e.g., "12-pack Coca-Cola from Amazon").
Flow Of Events:	1. The user navigates to the cart view. 2. The cart displays all added items, grouped by the retailer they were selected from. 3. A "Buy from [Retailer]" button is shown for each corresponding item or group. 4. The user selects "checkout" for an item (or group of items from the same store). 5. Quick Shop opens the selected retailer's product or cart page in a new tab

	or redirects the user there directly. 6. The user completes the purchase on the retailer’s site.
Postconditions:	The user is taken to the appropriate retailer's site to complete the purchase of each item individually.