

ORCA PED Analyzer

User and Method Manual

Sebastiano Romi

Version 2.10.1

Author: Sebastiano Romi

Affiliation: European Laboratory for non-Linear Spectroscopy (LENS), Università degli Studi di Firenze (UNIFI)

Contact: romi@lens.unifi.it

Purpose

ORCA PED Analyzer performs a molecule-agnostic analysis of ORCA normal modes using a selectable normalized diagonal potential-energy distribution (**PED**) or total-energy distribution (**TED**) in internal coordinates. It adds hierarchical/topological assignments, optional VPT2/GVPT2 post-processing, broadened IR spectra, CSV exports, and an Avogadro CJSON file containing all harmonic normal modes.

The program is designed around a conservative principle: **assignments are derived from the calculated atomic motion and the internal-coordinate energy decomposition, not from empirical frequency windows.**

Main input

```
molecule.hess      # always the CENTRAL ORCA Hessian
molecule.out       # optional VPT2/GVPT2 output; auto-detected for same basename
```

Never use displaced VPT2 Hessians such as:

```
molecule_D001.hess
molecule_D002.hess
...
```

as input to the analyzer.

Main output

By default, the script creates:

```
molecule_analysis/
  molecule_summary.csv
  molecule_families.csv
  molecule_ped.csv           # default PED run
  molecule_ted.csv          # TED run instead of molecule_ped.csv
  molecule_IR_fundamentals.dat
  molecule_IR_anharmonic.dat # if valid VPT2 is available
  molecule_IR_complete.dat  # if valid VPT2 is available
  molecule_avogadro_vibrations.cjson
  molecule_vpt2_bands.csv    # if valid VPT2 is available
  molecule_fermi.txt         # if a Fermi block is present
  molecule_manifest.txt
```

The PED/TED decomposition and Avogadro vectors describe **harmonic normal modes**. When a valid VPT2 calculation is available, VPT2 fundamental frequencies are used in the relevant tables and spectra, while overtone and combination bands are read directly from the ORCA VPT2 output.

1. Main features of version 2.10.1

- **Desktop applications.** Pre-built Linux AppImage, Windows executable and macOS DMG packages provide a graphical interface without requiring a local Python installation.
- **Interactive desktop workflow.** The GUI provides automatic VPT2 detection, configurable IR FWHM, generic/raw assignment controls, a live analysis log and the ability to stop a running analysis.
- **Interactive IR viewer.** After a successful analysis, generated IR spectra are displayed automatically when available; individual spectra can be shown/hidden and the embedded Matplotlib toolbar provides zoom, pan, navigation and save controls.
- **Single output directory.** All generated files are written to `BASENAME_analysis/` by default.
- **Three IR spectra.** Fundamentals; anharmonic-only overtone/combination bands; complete spectrum.
- **Automatic VPT2 preference.** If VPT2 is complete and numerically valid, fundamental spectra and tables use the VPT2 fundamental frequencies; otherwise harmonic frequencies are retained.
- **Numerical VPT2 validation.** A normally terminated ORCA job containing `inf` or `nan` in the VPT2 fundamentals is classified as complete but invalid, and its anharmonic data are ignored.
- **Avogadro CJSON.** One native CJSON file stores geometry, harmonic intensities, harmonic frequencies and all harmonic normal-mode vectors.
- **Consistent Avogadro numbering.** Translational/rotational entries preceding the true vibrations are retained in the CJSON so that Avogadro mode numbers match the ORCA/PED mode numbers. For a nonlinear molecule, the first true vibration is normally displayed as mode 6.
- **Manifest.** Each run records the script version, inputs, VPT2 state, IR broadening parameters and generated files.
- **Selectable PED/TED.** PED remains the backward-compatible default; TED adds the kinetic-energy contribution through the Wilson G matrix. Topological assignments, generic families and primitive internal coordinates with phase remain available.

2. Ways to run ORCA PED Analyzer

ORCA PED Analyzer can be used either as a **pre-built desktop application** or directly from the Python source code. For most users, the desktop application is the simplest option because it does not require a Python environment or terminal commands.

2.1 Pre-built desktop applications - recommended for most users

Ready-to-run applications are provided on the GitHub Releases page:

<https://github.com/SebRoLENS/orca-ped-analyzer/releases/latest>

The current release provides:

- **Linux x86_64:** `ORCA-PED-Analyzer-Linux-x86_64.AppImage` - portable AppImage.
- **Windows x86_64:** `ORCA-PED-Analyzer.exe` - standalone executable.
- **macOS Apple Silicon:** `ORCA-PED-Analyzer-macOS-arm64.dmg` - for Apple M-series Macs.
- **macOS Intel x86_64:** `ORCA-PED-Analyzer-macOS-x86_64.dmg` - for Intel-based Macs.

The packaged applications already contain Python and the required Python dependencies. Therefore, when using these builds, **Python, NumPy and a terminal are not required**.

Linux

1. Download `ORCA-PED-Analyzer-Linux-x86_64.AppImage` from the latest GitHub release.
2. Mark the file as executable. This can usually be done from the file manager under **Properties -> Permissions**, or from a terminal with:

```
chmod +x ORCA-PED-Analyzer-Linux-x86_64.AppImage
```

3. Double-click the AppImage to launch ORCA PED Analyzer.

The AppImage is portable and does not require a traditional installation. It can be kept in any convenient directory.

Windows

1. Download **ORCA-PED-Analyzer.exe** from the latest GitHub release.
2. Save it in a convenient directory.
3. Double-click the executable to launch the program.

No Python installation or separate installer is required.

macOS - Apple Silicon or Intel

1. Select the DMG matching the Mac architecture:
 - **ORCA-PED-Analyzer-macOS-arm64.dmg** for Apple Silicon (M-series);
 - **ORCA-PED-Analyzer-macOS-x86_64.dmg** for Intel Macs.
2. Open the downloaded DMG.
3. Copy **ORCA PED Analyzer.app** to the **Applications** folder or another preferred location.
4. Launch the application normally from Finder.

No Python installation is required.

2.2 Using the graphical application

The graphical launcher runs the same scientific analysis engine as the command-line program and exposes the options most commonly needed for interactive work.

Main controls

1. **Central Hessian (.hess).** Select the central ORCA Hessian. Displaced VPT2 Hessians such as `molecule_D001.hess` must not be used as the main input.
2. **VPT2/GVPT2 output (.out).** This is optional. A completed output can be selected explicitly, or **Auto-detect matching .out** can be left enabled so that the analyzer searches for the corresponding output automatically.
3. **Output directory.** Leave this empty to use the default `BASENAME_analysis/` directory, or select another location.
4. **Energy distribution.** Select **PED** (default) or **TED**. PED preserves the behaviour of previous versions; TED combines potential and kinetic contributions using the Wilson G matrix.
5. **Show generic groups.** Enables the same generic element/type assignment families provided by the command-line `--show-generic` option.
6. **Show raw ICs.** Includes primitive internal-coordinate contributions and phase information, corresponding to `--show-raw`.
7. **IR FWHM.** Sets the Gaussian broadening width used for generated IR spectra. The default is 10 cm^{-1} .
8. **Run analysis.** Starts the calculation in a separate process so that the graphical interface remains responsive.
9. **Stop analysis.** Terminates a running analysis. Partial output files may remain if the run is stopped before completion.

Live analysis log

The lower part of the main window contains a live log showing the output of the analysis process. Warnings and errors are also forwarded to this panel, making it possible to follow progress and diagnose problems without opening a terminal.

ORCA PED Analyzer

[User manual](#)[Check GitHub for updates](#)

Selectable normalized diagonal internal-coordinate PED or TED with optional ORCA VPT2/GVPT2 integration. The GUI uses the same analysis engine as the command-line program.
Contact: romi@lens.unifi.it

Central Hessian (.hess):

Browse...

VPT2/GVPT2 output (.out):

Browse...

Output directory:

Browse...

Options

Energy distribution:

PED

IR FWHM (cm⁻¹):

10

☒ Auto-detect matching .out

☐ Show generic groups

☐ Show raw ICs

Run analysis

Stop analysis

Select a central ORCA .hess file.

Analysis log:

Figure 1: ORCA PED Analyzer graphical interface

Automatic IR spectrum viewer

After a successful analysis, the GUI searches the selected output directory for generated `*_IR_*.dat` files. If one or more spectra are present, an **IR spectra** window opens automatically.

The viewer can display the fundamentals, anharmonic-only and complete spectra generated by the run. Each available curve has a checkbox and can be shown or hidden independently. The embedded Matplotlib navigation toolbar provides the usual zoom, pan, back/forward navigation and figure-saving controls.

The plotted data are exactly the same `.dat` files written by the analysis engine; the viewer is therefore a visualization layer and does not modify the scientific results.

Manual, updates and contact

The top of the GUI contains direct links to the user manual and the GitHub repository/release page. The author contact address is also shown in the graphical interface. If the operating system cannot open a link automatically, the application displays the explicit URL so that it can be copied into a browser.

The generated PED/TED tables, assignments, spectra, VPT2 information and Avogadro CJSON files are the same scientific outputs produced by the corresponding command-line analysis.

2.3 Security warnings and unsigned builds

The current desktop applications are **not digitally code-signed or notarized**. Consequently, operating-system security mechanisms may display a warning when the application is launched for the first time.

- **Windows:** Microsoft SmartScreen may report that the publisher is unknown or ask for confirmation before running the application.
- **macOS:** Gatekeeper may report that the developer cannot be verified and may require the user to explicitly allow or open the application.
- **Linux:** AppImage files are not normally affected by an equivalent publisher-signing warning, but the executable permission may need to be enabled before first use.

These warnings are expected for unsigned software downloaded from the Internet and indicate that the operating system cannot verify a code-signing identity for the publisher. They are separate from the scientific operation of the program.

For additional verification, each GitHub release includes `SHA256SUMS.txt`, containing SHA-256 checksums for the distributed application files. Users who require strict software provenance can compare the checksum of the downloaded file with the value published in the release.

The application source code and the GitHub Actions build workflow used to create the distributed packages are public in this repository.

2.4 Running from source / command line

The Python source version remains the preferred interface for advanced command-line options, scripting and reproducible automated workflows.

Requirements for the **source version only**:

- Python 3.9 or newer
- NumPy
- Matplotlib

Install the dependencies with:

```
python3 -m pip install -r requirements.txt
```

On Debian, NumPy can alternatively be installed with:

```
sudo apt install python3-numpy
```

Check the script version and available options with:

```
python3 orca_ped_analyzer.py --version
python3 orca_ped_analyzer.py --help
```

Expected public version:

```
orca_ped_analyzer.py 2.10.1
```

3. Which Hessian should be used?

3.1 Central Hessian

The PED always uses the central ORCA Hessian:

```
molecule.hess
```

The script reads or derives from this file:

- molecular geometry,
- Cartesian Hessian,
- harmonic frequencies,
- harmonic normal-mode eigenvectors,
- harmonic IR information.

The central Hessian is also the source of the vectors exported to Avogadro.

3.2 Displaced VPT2 Hessians

Files such as:

```
molecule_D001.hess
molecule_D002.hess
...
```

are intermediate ORCA files used to construct the anharmonic force field. They are **not** input files for the PED analyzer.

Practical rule: use one central `.hess` for the PED. Add VPT2 information by supplying the associated ORCA `.out`; do not switch to a displaced Hessian.

4. Command-line quick start

4.1 Minimum command

```
python3 orca_ped_analyzer.py molecule.hess
```

If `molecule.out` exists beside the Hessian, it is automatically inspected. A complete and numerically valid VPT2 analysis is incorporated.

4.2 VPT2 output with another name

Useful after a restarted calculation:

```
python3 orca_ped_analyzer.py molecule.hess \
    --vpt2-out molecule_restart.out
```

4.3 Select TED instead of PED

PED is the default for backward compatibility. To use total-energy distribution analysis:

```
python3 orca_ped_analyzer.py molecule.hess --energy-distribution ted
```

The shorter alias is equivalent:

```
python3 orca_ped_analyzer.py molecule.hess --distribution ted
```

4.4 Disable automatic VPT2 detection

```
python3 orca_ped_analyzer.py molecule.hess --no-auto-vpt2
```

4.5 Recommended detailed run

```
python3 orca_ped_analyzer.py molecule.hess \  
  --show-generic --show-raw \  
  --family-top 6 --family-min-percent 2 \  
  --top 10 --min-percent 1 \  
  --ir-fwhm 5
```

5. Output directory and manifest

By default the output directory is:

BASENAME_analysis/

For propanamine_VPT2.hess, for example:

```
propanamine_VPT2_analysis/  
  propanamine_VPT2_summary.csv  
  propanamine_VPT2_families.csv  
  propanamine_VPT2_ped.csv          # default PED; becomes *_ted.csv for TED  
  propanamine_VPT2_IR_fundamentals.dat  
  propanamine_VPT2_IR_anharmonic.dat  
  propanamine_VPT2_IR_complete.dat  
  propanamine_VPT2_avogadro_vibrations.cjson  
  propanamine_VPT2_vpt2_bands.csv  
  propanamine_VPT2_fermi.txt  
  propanamine_VPT2_manifest.txt
```

Conditional files appear only when the required information is available and valid.

Choose another output directory with:

```
python3 orca_ped_analyzer.py molecule.hess \  
  --output-dir vibrational_analysis
```

A relative path is interpreted relative to the Hessian directory.

The manifest records the script version, central Hessian, selected **PED/TED energy distribution**, selected VPT2 output, VPT2 status, IR FWHM and generated files. It is useful for reproducibility.

6. VPT2 detection and validation

The program distinguishes **program termination** from **numerical validity**. A VPT2 job can terminate normally but still contain non-finite anharmonic corrections.

State	Typical message	Analyzer behavior
Not available	no matching .out / no VPT2 section	PED/TED + harmonic fundamentals
Incomplete/running	INCOMPLETE/RUNNING	partial VPT2 data ignored
Complete but invalid	COMPLETE BUT NUMERICALLY INVALID	inf/nan ignored; harmonic data retained

State	Typical message	Analyzer behavior
Complete and valid	COMPLETE + VALID	VPT2 fundamentals, overtone/combination bands and Fermi information integrated

6.1 Complete but numerically invalid

Example diagnostic:

```
# VPT2: COMPLETE BUT NUMERICALLY INVALID in molecule.out
# fundamental rows=30/30; non-finite fundamentals=30; ...
```

The harmonic PED/TED analysis and CJSON remain usable. The fundamentals spectrum is produced using harmonic frequencies, while the anharmonic-only and complete spectra are not generated.

6.2 Mapping VPT2 fundamentals to Hessian modes

ORCA's VPT2 table numbers only vibrational modes, while the Hessian mode list normally also contains translational and rotational entries. The analyzer therefore maps VPT2 fundamentals to the central Hessian by comparing harmonic frequencies.

Default tolerance:

```
--vpt2-match-tol 10
```

that is, 10 cm⁻¹. If mapping fails, first verify that the `.hess` and `.out` belong to the same calculation.

7. How PED and TED are calculated

The analyzer creates primitive internal coordinates, numerically constructs the Wilson B matrix and selects an independent set spanning the vibrational space: 3N-6 coordinates for a nonlinear molecule or 3N-5 for a linear molecule.

For harmonic normal-mode vector (l_k), the internal-coordinate displacement is

$$D_k = B l_k.$$

The selected internal-coordinate force-constant representation is

$$F = (B^+)^T H B^+,$$

where (B^+) is the pseudoinverse of B and H is the Cartesian Hessian.

7.1 Potential-energy distribution (PED)

PED is the default and is identical to the decomposition used in earlier ORCA PED Analyzer versions:

$$PED_i^{(k)} = 100 \frac{F_{ii} D_{ik}^2}{\sum_j F_{jj} D_{jk}^2}.$$

It is a normalized diagonal potential-energy decomposition. Because the common modal factor cancels during normalization, this form is equivalent to using the diagonal potential contribution divided by the modal eigenvalue.

7.2 Total-energy distribution (TED)

TED additionally includes the kinetic-energy contribution. The Wilson kinetic matrix is

$$G = BM^{-1}B^T,$$

where M is the diagonal Cartesian mass matrix. The code uses $(G^{-1})_{ii}$ and first normalizes every displacement column so that

$$D_k^T G^{-1} D_k = 1.$$

The corresponding modal force-constant eigenvalue is then obtained as

$$\lambda_k = D_k^T F D_k.$$

The implemented normalized diagonal TED is

$$TED_i^{(k)} = 100 \frac{[F_{ii}/\lambda_k + (G^{-1})_{ii}] D_{ik}^2}{\sum_j [F_{jj}/\lambda_k + (G^{-1})_{jj}] D_{jk}^2}.$$

The factor of one half associated with averaging potential and kinetic contributions cancels in the normalization. The kinetic normalization also makes the result invariant to arbitrary scaling of a normal-mode eigenvector.

This implementation follows the **total energy distribution** concept introduced by E. Rytter and the corrected/modern formulation summarized by Oenen, Dinu and Liedl. The original 1974 definition has been discussed and refined in the later literature; the implementation therefore follows the modern formulation rather than reproducing the historical expression literally.

Important limitation: the percentages above use the **diagonal approximation**. Off-diagonal coupling terms are omitted to provide positive, easily interpretable per-coordinate percentages. For internal coordinates this approximation is formally better justified for PED than for KED/TED; consequently TED should be interpreted as a useful coordinate-decomposition metric, not as an exact partition of all coupling terms.

Both PED and TED describe the mechanical/energetic character of a **harmonic zero-order normal mode**. Neither is an IR-intensity percentage, and both depend on the chosen internal-coordinate representation.

8. Three assignment levels

8.1 Topological assignment - default

Primitive internal coordinates are grouped into conservative families that can be inferred from connectivity and graph topology, for example:

- cyclic C-C stretching,
- inter-ring C-C torsion,
- ring-site C-H in-plane bending,
- exocyclic C-N stretching.

The analyzer does not invent aromaticity or bond orders such as C=C or C=N from the Hessian alone.

8.2 Generic assignment - `--show-generic`

`--show-generic`

Displays chemistry-independent element/type families such as:

- C-C stretching,

- C-H bending,
- C-N stretching.

8.3 Primitive internal coordinates - `--show-raw`

`--show-raw`

Displays individual coordinates with percentage and relative phase, for example:

```
nu(C5-C6) 20.84%[+]
```

9. Pure, mixed and phase-qualified modes

The assignment does not simply choose the largest individual primitive coordinate. Primitive contributions from the selected PED or TED are first grouped by family; then the program evaluates whether one family dominates or whether the mode should be described as mixed.

Main defaults:

Parameter	Default	Meaning
<code>--pure-threshold</code>	70%	threshold for a non-mixed assignment
<code>--mixed-second</code>	20%	sufficiently large second family triggers a mixed assignment
<code>--family-top</code>	4	maximum number of grouped families printed
<code>--family-min-percent</code>	2%	grouped families below this threshold are not printed

For equivalent or closely related stretches, the relative sign of the internal-coordinate displacement can qualify a motion as `in-phase`, `opposite-phase`, or `mixed-phase` when the criterion is sufficiently robust.

10. Avogadro CJSON

Unless disabled with `--no-avogadro-cjson`, each run writes:

```
BASENAME_avogadro_vibrations.cjson
```

It contains:

- geometry,
- inferred connectivity,
- harmonic frequencies,
- harmonic IR intensities,
- all harmonic Cartesian normal-mode vectors.

Open it with Avogadro 2:

```
avogadro2 "/full/path/BASENAME_analysis/BASENAME_avogadro_vibrations.cjson"
```

10.1 Why are the CJSON frequencies harmonic?

VPT2 corrects state energies and transition frequencies but does not provide the analyzer with a replacement Cartesian normal-mode eigenvector set. The animated vectors therefore remain the harmonic normal modes.

10.2 Why does Avogadro start the first real vibration at mode 6?

Avogadro numbers vibration entries sequentially. Version 2.10.1 keeps the preceding translational/rotational entries in the CJSON so that the number displayed by Avogadro matches the ORCA/PED Hessian mode number. For a typical nonlinear molecule:

```
Avogadro mode 1-5  -> translational/rotational near-zero entries
Avogadro mode 6    -> first true vibration, ORCA/PED mode 6
Avogadro mode 7    -> ORCA/PED mode 7
...
```

This avoids the previous numbering offset.

11. Automatically generated IR spectra

The analyzer writes up to three .dat files. They are positive-going Gaussian-broadened curves represented as **relative absorbance**, with increasing wavenumber in the output grid.

File	When	Contents
*_IR_fundamentals.dat	whenever central Hessian IR data are available	fundamentals only; VPT2 frequencies if valid, otherwise harmonic
*_IR_anharmonic.dat	valid completed VPT2 only	VPT2 overtone + combination bands only
*_IR_complete.dat	valid completed VPT2 only	VPT2 fundamentals + overtone/combination bands

11.1 Frequency-source rule

```
complete + valid VPT2 -> VPT2 fundamental frequencies
missing/incomplete/invalid VPT2 -> harmonic Hessian frequencies
```

Fundamental intensities are taken from the IR information in the central harmonic Hessian. Overtone/combination frequencies and intensities come from the ORCA VPT2 output.

11.2 Relative absorbance

Each spectrum contains two columns:

```
wavenumber_cm-1    absorbance_relative
```

The absorbance is relative, not absolute Beer-Lambert absorbance. Concentration and optical path length are not known. Spectra generated in the same run share the same normalization convention, allowing relative visual comparison.

11.3 Bandwidth

```
python3 orca_ped_analyzer.py molecule.hess --ir-fwhm 5
```

--ir-fwhm is the Gaussian full width at half maximum in cm^{-1} . Default: 10 cm^{-1} .

11.4 Grid range and spacing

```
--ir-xmin 400 --ir-xmax 4000 --ir-step 0.5
```

If limits are omitted, the range is selected automatically from the available bands and FWHM.

12. Example FTIR workflow

For a 400-4000 cm^{-1} range, 5 cm^{-1} FWHM and 0.5 cm^{-1} grid spacing:

```
python3 orca_ped_analyzer.py molecule.hess \
  --ir-fwhm 5 \
  --ir-xmin 400 --ir-xmax 4000 --ir-step 0.5
```

With a complete and valid VPT2 output, all three spectra are produced. Otherwise only the fundamentals spectrum is written, using harmonic frequencies.

13. Overtones, combination bands and Fermi resonance

For valid VPT2 data, the analyzer reads ORCA overtone and combination-band frequencies and intensities. The textual assignment is derived from the **zero-order harmonic constituents**.

Conceptually:

State	Freq/ cm^{-1}	Int/ km mol^{-1}	Assignment
2nu0	...	...	overtone of ...
nu0+nu1	...	...	... + ...

If ORCA prints a Fermi-resonance analysis block, the script records its presence. With:

```
--show-fermi
```

it is also printed to the terminal and stored in `*_fermi.txt` when file output is enabled.

Interpretation: PED/TED and Avogadro animations describe harmonic zero-order modes. A strongly resonant observed state may be a mixture of zero-order states and should not be treated as a pure fundamental solely from its PED label.

14. CSV tables

CSV output is enabled by default.

File	When	Content
*_summary.csv	always	one row per mode: harmonic frequency, optional VPT2 fundamental, assignment, grouped PED/TED
*_families.csv	always	topological/generic families and percentages
*_ped.csv	PED selected (default)	primitive IC, PED percentage, phase, D_value, F_diagonal
*_ted.csv	TED selected	primitive IC, TED percentage, phase, D_value, F_diagonal, (G ⁻¹)_diagonal, and modal lambda
*_vpt2_bands.csv	valid VPT2	overtone/combination data, intensity and assignment
*_fermi.txt	Fermi block present	original ORCA Fermi-analysis block

Change the CSV prefix with:

```
--csv-prefix vib
```

Disable CSV output with:

`--no-csv`

15. Selected internal-coordinate set

The terminal output prints the independent internal-coordinate set actually used for the selected PED/TED analysis, for example:

```
# Selected internal-coordinate set:
#   1 nu(C1-C2)
#   2 delta(C1-C2-C3)
#   3 tau(C1-C2-C3-C4)
...
```

Inspect this especially for complex molecules, metal-containing systems, unusually long bonds, clusters, or unconventional topology.

16. Command-line reference

Option	Default	Function
<code>--vpt2-out FILE</code>	-	explicitly select VPT2 output
<code>--no-auto-vpt2</code>	off	do not search for same-basename .out
<code>--vpt2-match-tol</code>	10 cm ⁻¹	VPT2 -> Hessian mapping tolerance
<code>--bond-scale</code>	1.25	distance factor for bond detection
<code>--linear-cut</code>	175 deg	angles at/above threshold treated as linear bends
<code>--min-freq</code>	20 cm ⁻¹	ignore modes with absolute frequency below threshold
<code>--energy-distribution</code> <code>{ped,ted} / --distribution</code> <code>{ped,ted}</code>	ped	choose PED or TED decomposition
<code>--top</code>	5	number of primitive coordinates shown with <code>--show-raw</code>
<code>--min-percent</code>	1%	primitive-coordinate reporting threshold
<code>--family-top</code>	4	maximum grouped families displayed
<code>--family-min-percent</code>	2%	grouped-family reporting threshold
<code>--pure-threshold</code>	70%	non-mixed assignment threshold
<code>--mixed-second</code>	20%	second-family threshold for mixed assignment
<code>--show-generic</code>	off	show generic molecule-agnostic families
<code>--show-raw</code>	off	show primitive internal coordinates and phase
<code>--show-fermi</code>	off	print ORCA Fermi block
<code>--output-dir DIR</code>	BASENAME_analysis	directory for generated files
<code>--csv-prefix PREFIX</code>	Hessian basename	CSV prefix
<code>--no-csv</code>	off	disable CSV files
<code>--no-avogadro-cjson</code>	off	disable Avogadro CJSON
<code>--cjson-name FILE</code>	*_avogadro_vibrations.cjson	custom CJSON name
<code>--no-ir-spectra</code>	off	disable IR spectra

Option	Default	Function
<code>--ir-prefix PREFIX</code>	Hessian basename	IR file prefix
<code>--ir-fwhm</code>	10 cm ⁻¹	Gaussian FWHM
<code>--ir-xmin / --ir-xmax</code>	automatic	spectrum range
<code>--ir-step</code>	1 cm ⁻¹	IR grid spacing

17. Quality control and troubleshooting

17.1 Cartesian-Hessian reconstruction error

The program reports, for example:

```
# Cartesian-Hessian reconstruction relative error: 4.462e-06
```

A very small value indicates that the selected internal-coordinate representation reproduces the original Cartesian Hessian well. The script warns above approximately 1e-3.

Order of magnitude	Practical interpretation
1e-6 to 1e-4	very good
around 1e-3	inspect carefully
greater than 1e-3	possible connectivity/internal-coordinate problem

17.2 Degenerate and collective modes

Within an exactly or nearly degenerate subspace, individual eigenvectors can rotate without changing the physical subspace. Primitive-coordinate PED/TED percentages can therefore be basis-dependent. Grouped assignments and the degenerate set as a whole are usually more robust.

17.3 VPT2 containing `inf/nan`

This is not treated as a parsing error. It means the anharmonic result is numerically unusable. The analyzer classifies it as COMPLETE BUT NUMERICALLY INVALID and discards VPT2 frequencies/bands.

17.4 A `_Dxxx.hess` was supplied accidentally

The analyzer reports that the file looks like a displaced VPT2 Hessian and asks for the central Hessian instead.

17.5 Multiple fragments or unusual connectivity

Bond recognition uses distances and covalent radii. For clusters, noncovalent contacts, metal systems or multiple fragments, inspect `--bond-scale` and the selected internal-coordinate set carefully.

18. Recommended workflow

1. Optimize the geometry to a well-converged minimum.
2. Compute and inspect the central Hessian; check for imaginary frequencies.
3. Run `orca_ped_analyzer.py` on the central Hessian and select PED (default) or TED as appropriate.
4. Inspect the reconstruction error and selected internal-coordinate set.
5. For complex systems, use `--show-generic --show-raw`.
6. If VPT2 is still running, use the harmonic outputs safely; partial anharmonic data are ignored.
7. When VPT2 finishes, rerun the analyzer. If the result is valid, VPT2 fundamental frequencies automatically take priority in the relevant tables and spectra.
8. Open the CJSON in Avogadro to inspect all harmonic normal modes using the same mode numbering as the selected PED/TED output.

- Use the three IR spectra to separate fundamentals, anharmonic-only additional bands and the complete simulated spectrum.
- Archive the entire *_analysis directory with the calculation data.

19. Reporting results in a scientific publication

For a main-text assignment table, a useful minimal structure is:

Experimental / cm ⁻¹	VPT2 / cm ⁻¹	Assignment
...	...	cyclic C-C stretching
...	...	mixed C-N stretching / cyclic C-C stretching

For Supporting Information, retain more detail:

Mode	Harmonic / cm ⁻¹	VPT2 / cm ⁻¹	Anharmonic shift	Calculated IR intensity	Assignment	Grouped PED/TED
...	...	...	...	...	...	...

Recommended reporting principles:

- use VPT2 fundamentals when the VPT2 result is valid;
- keep harmonic frequencies in the Supporting Information because the PED belongs to the harmonic zero-order modes;
- report multiple grouped PED/TED contributions when no family dominates clearly;
- avoid reporting every primitive coordinate in the main paper;
- provide the complete primitive PED/TED table as machine-readable Supporting Data when useful;
- keep overtone/combination assignments separate from fundamentals;
- explicitly discuss Fermi mixing when it materially affects a spectral assignment.

20. Quick reference

Check version:

```
python3 orca_ped_analyzer.py --version
python3 orca_ped_analyzer.py --help
```

Standard PED analysis with automatic VPT2 detection:

```
python3 orca_ped_analyzer.py molecule.hess
```

TED analysis:

```
python3 orca_ped_analyzer.py molecule.hess --energy-distribution ted
```

Detailed analysis with 5 cm⁻¹ IR FWHM:

```
python3 orca_ped_analyzer.py molecule.hess \
  --show-generic --show-raw \
  --family-top 6 --family-min-percent 2 \
  --top 10 --min-percent 1 \
  --ir-fwhm 5
```

IR range 400-4000 cm⁻¹:

```
python3 orca_ped_analyzer.py molecule.hess \
  --ir-fwhm 5 --ir-xmin 400 --ir-xmax 4000 --ir-step 0.5
```

Custom output directory:

```
python3 orca_ped_analyzer.py molecule.hess \  
  --output-dir vibrational_analysis
```

Open vibrations in Avogadro:

```
avogadro2 "$(realpath molecule_analysis/molecule_avogadro_vibrations.cjson)"
```

Remember: **one central Hessian only**. PED is the default; TED is selected with `--energy-distribution ted` or from the GUI. VPT2 is added through the ORCA output file; animated vectors remain harmonic. When VPT2 is valid, VPT2 fundamentals take priority in the corresponding spectra and tables.

21. Method references

1. E. Rytter, "Total energy distribution method for classification of normal modes of vibration," *J. Chem. Phys.* **60**, 3882-3883 (1974). DOI: 10.1063/1.1680833.
2. K. Oenen, D. F. Dinu, and K. R. Liedl, "Determining internal coordinate sets for optimal representation of molecular vibration," *J. Chem. Phys.* **160**, 014104 (2024). DOI: 10.1063/5.0180657.

22. Development and validation disclaimer

I am primarily a **user of computational chemistry software and an amateur programmer**, rather than a professional software developer. The development of ORCA PED Analyzer made extensive use of **AI-assisted programming**. To reduce the risk of introducing unnoticed errors, I developed the program incrementally, testing individual components and successive versions against real computational outputs and checking the consistency of the results at each stage.

For the systems tested so far, the results and vibrational assignments produced by the program have been fully consistent with the expected behaviour. Nevertheless, users are strongly encouraged to validate the software on **well-understood computational test cases** before relying on it for new scientific problems. This is good practice for any scientific software, and is particularly valuable here because independent testing can reveal implementation bugs, problematic assignments, edge cases, or methodological mistakes that I may have overlooked.

If you find any such issue, please report it. Identifying and correcting errors will only make the software more reliable and useful to the wider community. Contributions, validation cases, criticism, and suggested improvements are therefore sincerely appreciated. **Thank you for helping improve this open-source project.**