

Nombre del estudiante: Sebastián Emilio Aguiñada Coto

Carné: AC232994

Asignatura: Diseño y programación de Software Multiplataforma

Numero de guía: Guía 1

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit
$ git config --global -l
core.editor="C:\Users\sebas\AppData\Local\Programs\Microsoft VS Code\bin\code" -
-wait
user.email=sebastiancrack20@outlook.com
user.name=Sebascode20

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit
$ git init
Initialized empty Git repository in C:/Users/sebas/OneDrive/Documentos/EjemploGit/.git/

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git add -A

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git commit -m "primera version"
[master (root-commit) 0b6f656] primera version
1 file changed, 8 insertions(+)
create mode 100644 holaMundo.html

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git log
commit 0b6f6568094ee5497630bb98b769dcc9bbb8fd10 (HEAD -> master)
Author: Sebascode20 <sebastiancrack20@outlook.com>
Date: Sat Jan 25 09:47:22 2025 -0600

    primera version

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git log --oneline --decorate --all --graph
* 0b6f656 (HEAD -> master) primera version

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote --v

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote add origin git@github.com:Sebascode20/EjemploGit.git

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote --v
origin git@github.com:Sebascode20/EjemploGit.git (fetch)
origin git@github.com:Sebascode20/EjemploGit.git (push)

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
The authenticity of host 'github.com (140.82.113.4)' can't be established.
ED25519 key fingerprint is SHA256:+DiY3wvvV6TuJJhbpZisF/zLDA0zPMSvHdkr4UvCOqU.
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
The authenticity of host 'github.com (140.82.113.4)' can't be established.
ED25519 key fingerprint is SHA256:+DiY3wvvV6TuJJhbpZisF/zLDA0zPMSvHdkr4UvCOqU.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added 'github.com' (ED25519) to the list of known hosts.
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ ssh -T git@github.com
git@github.com: Permission denied (publickey).
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ ssh-keyscan github.com >> ~/.ssh/known_hosts
# github.com:22 SSH-2.0-4dc3263f8
# github.com:22 SSH-2.0-4dc3263f8
# github.com:22 SSH-2.0-4dc3263f8
# github.com:22 SSH-2.0-4dc3263f8
# github.com:22 SSH-2.0-4dc3263f8
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ ssh -T GITHUB-Sebascode20@github.com
GITHUB-Sebascode20@github.com: Permission denied (publickey).
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote set-url origin git@github.com:Sebascode20/EjemploGit.git
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote -v
origin  git@github.com:Sebascode20/EjemploGit.git (fetch)
origin  git@github.com:Sebascode20/EjemploGit.git (push)
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote add origin git@github.com:Sebascode20/EjemploGit.git
error: remote origin already exists.
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote --v
origin  git@github.com:Sebascode20/EjemploGit.git (fetch)
origin  git@github.com:Sebascode20/EjemploGit.git (push)
```

```
sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
git@github.com: Permission denied (publickey).
fatal: Could not read from remote repository.
```

Please make sure you have the correct access rights
and the repository exists.

```

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote --remove origin
error: unknown option 'remove'
usage: git remote [-v | --verbose]
    or: git remote add [-t <branch>] [-m <master>] [-f] [--tags | --no-tags] [--m
error=<fetch|push>] <name> <url>
    or: git remote rename [--[no-]progress] <old> <new>
    or: git remote remove <name>
    or: git remote set-head <name> (-a | --auto | -d | --delete | <branch>)
    or: git remote [-v | --verbose] show [-n] <name>
    or: git remote prune [-n | --dry-run] <name>
    or: git remote [-v | --verbose] update [-p | --prune] [(<group> | <remote>)..
.]
    or: git remote set-branches [--add] <name> <branch>...
    or: git remote get-url [--push] [--all] <name>
    or: git remote set-url [--push] <name> <newurl> [<oldurl>]
    or: git remote set-url --add <name> <newurl>
    or: git remote set-url --delete <name> <url>

    -v, --[no-]verbose    be verbose; must be placed before a subcommand

```

```

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git -r origin
unknown option: -r
usage: git [-v | --version] [-h | --help] [-C <path>] [-c <name>=<value>]
    [--exec-path[=<path>]] [--html-path] [--man-path] [--info-path]
    [-p | --paginate | -P | --no-pager] [--no-replace-objects] [--bare]
    [--git-dir=<path>] [--work-tree=<path>] [--namespace=<name>]
    [--config-env=<name>=<envvar>] <command> [<args>]

```

```

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote -r origin
error: unknown switch 'r'
usage: git remote [-v | --verbose]
    or: git remote add [-t <branch>] [-m <master>] [-f] [--tags | --no-tags] [--m
error=<fetch|push>] <name> <url>
    or: git remote rename [--[no-]progress] <old> <new>
    or: git remote remove <name>
    or: git remote set-head <name> (-a | --auto | -d | --delete | <branch>)
    or: git remote [-v | --verbose] show [-n] <name>
    or: git remote prune [-n | --dry-run] <name>
    or: git remote [-v | --verbose] update [-p | --prune] [(<group> | <remote>)..
.]
    or: git remote set-branches [--add] <name> <branch>...
    or: git remote get-url [--push] [--all] <name>
    or: git remote set-url [--push] <name> <newurl> [<oldurl>]
    or: git remote set-url --add <name> <newurl>

```

```

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote remove origin

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git remote add origin https://github.com/Sebascode20/EjemploGit.git

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git push -u origin master
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Delta compression using up to 8 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 302 bytes | 100.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Sebascode20/EjemploGit.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git pull origin master
remote: Enumerating objects: 5, done.
remote: Counting objects: 100% (5/5), done.
remote: Compressing objects: 100% (2/2), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 1.01 KiB | 69.00 KiB/s, done.
From https://github.com/Sebascode20/EjemploGit
 * branch            master       -> FETCH_HEAD
   0b6f656..933b87b master       -> origin/master
Updating 0b6f656..933b87b
Fast-forward
 holaMundo.html | 3 ++-
 1 file changed, 2 insertions(+), 1 deletion(-)

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$ git log --oneline --decorate --all --graph
* 933b87b (HEAD -> master, origin/master) Update holaMundo.html
* 0b6f656 primera version

sebas@SEBASTIAN MINGW64 ~/OneDrive/Documentos/EjemploGit (master)
$

```

Link al repositorio GitHub

<https://github.com/Sebascode20/EjemploGit>