

🕒 Sunday, March 05, 2017



# LIKE GEEKS



LINUX

## How To Write Practical Shell Script

📅 February 25, 2017 👤 admin 💬 0 Comments

In the last post, we've talked about **regex** and we see how to use them in sed and awk for text processing and we discussed before **Linux sed** command and **awk command**. During the series, we write small shell **scripts** but we didn't mix things up, I think we should take a small step and write a shell script that can be some useful.

The main reason for learning to write a shell script is to be able to create your own Linux utilities. Understanding how to write useful and practical scripts is important.

However, sometimes it helps to do something fun to learn a concept or skill. The scripts in this post they can be lots of fun! And they help empower your script writing concepts.

Our main points are:

## Sending messages

### Write command

### Creating the send script

### Monitoring Disk Space

## Sending messages


You can send messages to someone by phone or e-mail but one method, not commonly used anymore, is sending a message directly to a fellow system user's terminal. Because this technique is largely unknown

The shell script helps you to quickly and easily send a message to someone who is logged onto your Linux system.

For this simple shell script, only a few functions are required. Several of the commands are common and have been covered in our series of shell scripting; you can review the posts to understand what we are talking about

The first command needed is the who command. The who command allows you to see all the users currently logged into the system.

```
$ who
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ who
likegeeks tty7      2017-02-25 09:26 (:0)
testuser pts/1     2017-02-25 09:27 (192.168.1.2)
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

To send a message, you only need the first two items. Both the username and the user's current terminal are necessary

Users can prevent anyone to send them messages via the `mesg` command. Therefore, before you start attempting to send messages, it's a good idea to check whether messages are allowed. For yourself, you can simply enter the `mesg` command like this

```
$ mesg
```

A terminal window titled 'likegeeks@likegeeks-VirtualBox ~/Desktop' with a menu bar (File, Edit, View, Search, Terminal, Help). The prompt is 'likegeeks@likegeeks-VirtualBox ~/Desktop \$'. The user enters 'mesg' and the output is 'is y'. The prompt returns to 'likegeeks@likegeeks-VirtualBox ~/Desktop \$'.

The `is n` result shows that messaging is turned off. If the result showed `is y`, messages would be allowed.


To check anyone else's message status, you can use the `who` command again. Keep in mind that this checks the message status only for those who are currently logged into the system. You use the `-T` option to check their message status

If you see dash (-) that means messages are turned off and if you see plus sign (+) that means messages are enabled

To allow messages to be sent to you, if it is turned off, you need to use the `message` command with the `y` option like this

```
$ mesg y
```

```
$ mesg
```

A terminal window titled 'likegeeks@likegeeks-VirtualBox ~/Desktop' with a menu bar (File, Edit, View, Search, Terminal, Help). The prompt is 'likegeeks@likegeeks-VirtualBox ~/Desktop \$'. The user enters 'mesg' and the output is 'is n'. The user then enters 'mesg y' and the output is 'is y'. The prompt returns to 'likegeeks@likegeeks-VirtualBox ~/Desktop \$'.

Sure enough, the command shows `is y`, which indicates messages are allowed to this user

Of course, we need another user to be able to communicate with him so in my case I'm going to connect to my PC using ssh and I'm already logged in with my user, so we have two users logged onto the system

Now we can send the message from one user to another.


## Write command

The primary tool for sending messages between logged in users is the write command. As long as messaging is allowed, the write command allows you to send a message to another logged-in user using his username and current terminal


Note: The write command only allows you to successfully send messages to users logged onto a virtual console terminal. A user logged into the graphical environment (KDE, Gnome, Cinnamon or any) will not be able to receive messages.

We will send a message to testuser user from my user likegeeks like this

```
$ write testuser pts/1
```

A screenshot of a terminal window titled 'likegeeks@likegeeks-VirtualBox ~/Desktop'. The window shows the output of the 'who -T' command, which lists two users: 'likegeeks' on 'tty7' and 'testuser' on 'pts/1'. Below this, the 'write testuser pts/1' command is executed, and the word 'welcome' is sent to the testuser terminal. The prompt returns to the user 'likegeeks'.

After the message is initiated by the write command, a blank line is shown for you to begin inputting the message text. It may be as many lines as you desire. When the Enter key is pressed, a new line is available for more message text. After you are finished entering message text, the whole message is sent by pressing the Ctrl+D key combination which is end of file signal I recommend you to review the post about [signals and jobs](#).



```
testuser@likegeeks-VirtualBox ~  
testuser@likegeeks-VirtualBox ~$  
Message from likegeeks@likegeeks-VirtualBox on pts/0 at 09:32 ...  
welcome  
EOF  
█
```

The receiver can see which user on which terminal sent the message. A timestamp is also included. Notice the EOF shown at the bottom. It indicates End Of File, which lets the message recipient know that this is the entire message.

I think now we have all part to build our shell script

## Creating the send script

before we create our shell script, we need to determine whether the user we want to send a message to is logged on the system and this can be done using who command to determine that

```
logged_on=$(who | grep -i -m 1 $1 | awk '{print $1}')
```


The results of the who command are piped into the grep command. The grep command uses the -i option to ignore case, so the username to be entered using uppercase or lowercase letters. The -m 1 option is included in the grep command, in case the user is logged into the system multiple times. The grep command produces either nothing, if the user is not logged on, or the username's first login information. This output is passed to the awk command. The awk command returns only the first item, either nothing or the username. This final output from the awk command is stored in the variable logged\_on

Then we need to check the variable logged on if it contains something or not

```
if [ -z $logged_on ]  
then  
echo "$1 is not logged on."  
echo "Exit"
```

```
exit  
fi
```

I recommend you to read the post about if statement and how to use it **Bash Script**

A screenshot of a terminal window titled 'likegeeks@likegeeks-VirtualBox ~/Desktop'. The window has a menu bar with 'File', 'Edit', 'View', 'Search', 'Terminal', and 'Help'. The terminal shows the following commands and output:  
likegeeks@likegeeks-VirtualBox ~/Desktop \$ ./senderscript testuser  
testuser is not logged on.  
Exit  
likegeeks@likegeeks-VirtualBox ~/Desktop \$ ./senderscript testuser  
likegeeks@likegeeks-VirtualBox ~/Desktop \$

The logged\_on variable is tested to determine if it is a zero-length variable.


If it is a zero-length variable, the script user is informed via echo commands that the user is not currently logged onto the system, and the script is exited via the exit command. If the user is logged onto the system, the logged\_on variable contains the user's username, and the script continues

## Checking if user accepts messages

The next step is to determine whether a logged on user accepts messages

```
allowed=$(who -T | grep -i -m 1 $1 | awk '{print $2}')  
if [ $allowed != "+" ]  
then  
echo "$1 does not allowing messaging."  
echo "Exit"  
exit  
fi
```





```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser
testuser does not allowing messaging.
Exit
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser
likegeeks@likegeeks-VirtualBox ~/Desktop $
```


```
testuser@likegeeks-VirtualBox ~
testuser@likegeeks-VirtualBox ~ $ mesg n
testuser@likegeeks-VirtualBox ~ $ mesg y
testuser@likegeeks-VirtualBox ~ $
```

Notice that we use the `who` command with `-T`. This displays a `(+)` next to the username if messaging is allowed. Otherwise, it displays a `(-)` next to the username, if messaging is not allowed. The results from the `who` command are then piped into `grep` and `awk` to pull out only the messaging indicator. The messaging indicator is stored in the `allowed` variable. Finally, an `if` statement is used to test for a messaging indicator not set to `+`. If the indicator is not set to `+`, the script user is informed and the script is exited. However, if the messaging indicator shows messaging is allowed, the script continues.

## Checking if message was included

To test for the message parameter, an `if` statement is used like this

```
if [ -z $2 ]
then
echo "No message parameter included."
echo "Exit"
exit
fi
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser
No message parameter included.
Exit
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser welcome
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

## Getting the current terminal

Before we send a message, we need to get the user current terminal and stored in a variable

```
terminal=$(who | grep -i -m 1 $1 | awk '{print $2}')
```


Then we can send the message

```
echo $2 | write $logged_on $terminal
```

Now we can test the whole shell script to see how it goes

```
$ ./senderscript likegeeks welcome
```

Let's see the other shell window




Good! You can now send simple one-word messages

## Sending a long message

Surely you want to send more than just a single word. If you try that with this shell script

```
$ ./senderscript likegeeks welcome to shell scripting
```





```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser welcome to shell scripting
likegeeks@likegeeks-VirtualBox ~/Desktop $

testuser@likegeeks-VirtualBox ~
testuser@likegeeks-VirtualBox ~ $
Message from likegeeks@likegeeks-VirtualBox on pts/0 at 09:43 ...
welcome
EOF
█
```

It didn't work. Only the first word of the message is sent. This is due to the script using parameters and each word is treated as a different parameter. To fix this problem we will use the shift command with the while loop you can review the shift command from our post [Bash Scripting](#)

```
shift
while [ -n "$1" ]
do
whole_message=$whole_message' '$1
shift
done
```

And now one thing need to be fixed the message parameter.

Instead of just sending parameter \$2 to the write utility, the script is modified to send the variable, whole\_message

```
echo $whole_message | write $logged_on $terminal
```


So now the whole script should be like this

```
#!/bin/bash
logged_on=$(who | grep -i -m 1 $1 | awk '{print $1}')
if [ -z $logged_on ]
then
```

```
echo "$1 is not logged on."
echo "Exit"
exit
fi
allowed=$(who -T | grep -i -m 1 $1 | awk '{print $2}')
if [ $allowed != "+" ]
then
echo "$1 does not allowing messaging."
echo "Exit"
exit
fi
if [ -z $2 ]
then
echo "No message parameter included."
echo "Exit"
exit
fi
terminal=$(who | grep -i -m 1 $1 | awk '{print $2}')
shift
while [ -n "$1" ]
do
whole_message=$whole_message' '$1
shift
done
echo $whole_message | write $logged_on $terminal
```

If you try now

```
$ ./senderscript likegeeks welcome to shell scripting
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./senderscript testuser welcome to shell scripting
likegeeks@likegeeks-VirtualBox ~/Desktop $

testuser@likegeeks-VirtualBox ~
testuser@likegeeks-VirtualBox ~ $
Message from likegeeks@likegeeks-VirtualBox on pts/0 at 09:51 ...
welcome to shell scripting
EOF
```

Awesome!! It worked. Again I'm not here to make a script to send the message to the user but the main reason to review our shell scripting knowledge and use all parts we've learned together and see how things work together.

## Monitoring Disk Space


We are going to build a shell script utility that will help you determine the top ten disk space consumers for designated directories

The `du` command displays the disk usage for individual files and directories. The `-s` option lets you summarize totals at the directory level I recommend you to review my post about `du` command and all other **Main Linux Commands**. This comes in handy when calculating the total disk space used by an individual user

```
$ du -s /var/log/
```

The listing quickly becomes too detailed. The `-S` (capital S) option works better for our purposes here, providing a total for each directory and subdirectory individually.


```
$ du -S /var/log/
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ du -s /var/log/
6228 /var/log/
likegeeks@likegeeks-VirtualBox ~/Desktop $ du -S /var/log/
12 /var/log/fsck
24 /var/log/mdm
4 /var/log/ntpstats
60 /var/log/apt
4 /var/log/upstart
4 /var/log/hp/tmp
4 /var/log/hp
68 /var/log/ConsoleKit
36 /var/log/cups
4 /var/log/samba
828 /var/log/installer
5180 /var/log/
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

Because we are interested in the directories consuming the biggest chunks of disk space, the sort command is used on the listing produced by du

```
$ du -S /var/log/ | sort -rn
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ du -S /var/log/ | sort -rn
5184 /var/log/
828 /var/log/installer
68 /var/log/ConsoleKit
60 /var/log/apt
36 /var/log/cups
24 /var/log/mdm
12 /var/log/fsck
4 /var/log/upstart
4 /var/log/samba
4 /var/log/ntpstats
4 /var/log/hp/tmp
4 /var/log/hp
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

The -n option allows you to sort numerically. The -r option lists the largest numbers first (reverse order). This is perfect for finding the largest disk consumers

The sed command brings more clarity to this listing. To focus on the top ten disk space consumers, when line 11 is reached, sed is set to delete the rest of the listing. The next step is to add a line number for each line in the listing. To get those line numbers on the same line as

the disk space text, combine the text lines using the N command. The sed commands will look like this

```
sed '{11,$D; =}' |  
sed 'N; s/\n/ /' |
```


you can review my post about [sed command](#)

Then we can clean the output using the awk command. The output from the sed command is piped into the awk command and printed using the printf function

```
awk '{printf $1 ":" "\t" $2 "\t" $3 "\n"}'
```

After the line number, a colon (:) is added, and tab (\t) characters are put between the individual fields for each text line's output row.

```
$ du -S /var/log/ |  
sort -rn |  
sed '{11,$D; =}' |  
sed 'N; s/\n/ /' |  
awk '{printf $1 ":" "\t" $2 "\t" $3 "\n"}'
```



The screenshot shows a terminal window titled 'likegeeks@likegeeks-VirtualBox ~/Desktop'. The user enters a series of commands to list disk space usage for the /var/log/ directory, sorted by size in descending order, and formatted with line numbers and tabs. The output shows 10 lines of data.

```
likegeeks@likegeeks-VirtualBox ~/Desktop $ du -S /var/log/ |  
> sort -rn |  
> sed '{11,$D; =}' |  
> sed 'N; s/\n/ /' |  
> awk '{printf $1 ":" "\t" $2 "\t" $3 "\n"}'  
1: 5184 /var/log/  
2: 828 /var/log/installer  
3: 68 /var/log/ConsoleKit  
4: 60 /var/log/apt  
5: 36 /var/log/cups  
6: 24 /var/log/mdm  
7: 12 /var/log/fsck  
8: 4 /var/log/upstart  
9: 4 /var/log/samba  
10: 4 /var/log/ntpstats  
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

Now we understand how the command work let's write the script

To be productive, the script creates a report for multiple directories. We will make a variable to accomplish this say MY\_DIRECTORIES. For our purposes here, the variable is set to just two directories

```
MY_DIRECTORIES="/home /var/log"
```

We will make a for loop to perform the du command on each directory listed in the variable. Each time the for loop iterates through the list of values in the variable MY\_DIRECTORIES

So the shell script will look like this

```
#!/bin/bash
MY_DIRECTORIES="/home /var/log"
echo "Top Ten Disk Space Usage"
for DIR in $MY_DIRECTORIES
do
echo "The $DIR Directory:"
du -S $DIR 2>/dev/null |
sort -rn |
sed '{11,$D; =}' |
sed 'N; s/\n/ /' |
awk '{printf $1 ":" "\t" $2 "\t" $3 "\n"}'
done
exit
```



```
likegeeks@likegeeks-VirtualBox ~/Desktop
File Edit View Search Terminal Help
likegeeks@likegeeks-VirtualBox ~/Desktop $ ./myscript
Top Ten Disk Space Usage
The /home Directory:
1:      28116   /home/likegeeks/.local/share/Trash/files
2:      20004   /home/likegeeks/.cache/mozilla/firefox/mwad0hks.default/cache2/entries
3:      16132   /home/likegeeks/.mozilla/firefox/mwad0hks.default
4:      10252   /home/testuser/.mozilla/firefox/mwad0hks.default
5:       2904   /home/likegeeks/.cache/mozilla/firefox/mwad0hks.default/safebrowsing
6:       2324   /home/likegeeks
7:       2224   /home/likegeeks/Downloads
8:       1392   /home/likegeeks/.cache/mozilla/firefox/mwad0hks.default/startupCache
9:       1352   /home/likegeeks/.mozilla/firefox/mwad0hks.default/gmp-gmpopenh264/1.6
10:       884   /home/testuser/.config/chromium/Default
The /var/log Directory:
1:       5184   /var/log
2:        828   /var/log/installer
3:        68    /var/log/ConsoleKit
4:        60    /var/log/apt
5:        36    /var/log/cups
6:        24    /var/log/mdm
7:        12    /var/log/fsck
8:         4    /var/log/upstart
9:         4    /var/log/samba
10:         4    /var/log/ntpstats
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

Good!! The report shows the disk consumption for both directories in a beautifully formatted report

You can filter files so instead of calculating the consumption of all files you can calculate specific extension \*.log or whatever, just change the file globbing

One thing I have to mention here in production systems you can't rely on disk space report instead, consider setting disk quotas. If the quota package is installed

Quota package is specialized for that but here we are learning how shell scripts work when things mix together.

I hope you understand how shell scripts work and how commands work together

Again the shell scripts we've introduced here is for showing how shell scripting work, there are a ton of ways to implement any task in Linux

My post is finished for now. I tried to reduce the code length and make everything simple as possible hope you like it

Thank you.

41

**Admin**

<https://likegeeks.com>

## RELATED ARTICLES




LINUX

### Regex tutorial for Linux

 February 23, 2017    admin

In order to successfully working with the Linux sed editor and the awk command in your shell scripts you has to understand regular expressions or in short regex and to be accurate in our case it is bash regex, since there are many engines for regex you can use and we here in this regex [...]



LINUX

### 31+ Examples for sed Linux command in text manipulation

 February 19, 2017    admin

On the previous post we've talked about bash functions and how to use it from the command line and we've seen some other cool stuff I recommend you to review it, Today we will talk about a very useful tool for string manipulation called sed, sed



LINUX

### Bash Script Step By Step, You will love it

 February 7, 2017    admin

Today we are going to talk about bash script or shell scripting actually, they are called shell scripts in general but we are going to call them bash scripts because we are going to use bash among the other Linux shells. There are zsh, tcsh , ksh and other shells, you can review the basic [...]