


Optocoupler, Phototransistor Output (Dual, Quad Channel)



DESCRIPTION

The ILD74, ILQ74 is an optically coupled pair with a GaAlAs infrared LED and a silicon NPN phototransistor. Signal information, including a DC level, can be transmitted by the device while maintaining a high degree of electrical isolation between input and output.

The ILD74, ILQ74 is especially for driving medium-speed logic, where it may be used to eliminate troublesome ground loop and noise problems. Also it can be used to replace relays and transformers in many digital interface applications, as well as analog applications such as CTR modulation.

The ILD74 has two isolated channels in a single DIP package; the ILQ74 has four isolated channels per package.

FEATURES

- ILD74, ILQ74 TTL compatible
- Transfer ratio, 35 % typical
- Coupling capacitance, 0.5 pF
- Single, dual, and quad channel
- Industry standard DIP packages
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC





RoHS
COMPLIANT

AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- CSA 93751
- BSI IEC 60950; IEC 60065
- DIN EN 60747-5-2 (VDE 0884)/DIN EN 60747-5-5 pending available with option 1
- FIMKO

ORDERING INFORMATION



| AGENCY CERTIFIED/PACKAGE | DUAL CHANNEL | QUAD CHANNEL |
|---------------------------------|----------------------------|----------------------------|
| | CTR (%) | |
| UL, CSA, BSI, FIMKO | ≥ 12.5 | ≥ 12.5 |
| DIP-8 | ILD74 | - |
| SMD-8, option 9 | ILD74-X009T ⁽¹⁾ | - |
| DIP-16 | - | ILQ74 |
| SMD-16, option 9 | - | ILQ74-X009T ⁽¹⁾ |
| VDE, UL, CSA, BSI, FIMKO | ≥ 12.5 | ≥ 12.5 |
| DIP-8 | ILD74-X001 | - |
| DIP-8, 400 mil, option 6 | ILD74-X016 | - |
| SMD-8, option 7 | ILD74-X017T | - |
| DIP-16 | - | ILQ74-X001 |

Notes

- Additional options may be possible, please contact sales office.
- ⁽¹⁾ Also available in tubes, do not put "T" on the end.

| ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | |
|--|---|-------|------------|----------------|------------------------|
| PARAMETER | TEST CONDITION | PART | SYMBOL | VALUE | UNIT |
| INPUT | | | | | |
| Peak reverse voltage | | | V_R | 3 | V |
| Forward continuous current | | | I_F | 60 | mA |
| Power dissipation | | | P_{diss} | 100 | mW |
| Derate linearly from 55 % | | | | 1.33 | mW/ $^{\circ}\text{C}$ |
| OUTPUT | | | | | |
| Collector emitter breakdown voltage | | | BV_{CEO} | 20 | V |
| Emitter collector breakdown voltage | | | BV_{ECO} | 5 | V |
| Collector base breakdown voltage | | | BV_{CBO} | 70 | V |
| Power dissipation | | | P_{diss} | 150 | mW |
| Derate linearly from 25 $^{\circ}\text{C}$ | | | | 2 | mW/ $^{\circ}\text{C}$ |
| COUPLER | | | | | |
| Isolation test voltage | $t = 1\text{ s}$ | | V_{ISO} | 5300 | V_{RMS} |
| Isolation resistance | $V_{IO} = 500\text{ V}$, $T_{amb} = 25\text{ }^{\circ}\text{C}$ | | R_{IO} | $\geq 10^{12}$ | Ω |
| | $V_{IO} = 500\text{ V}$, $T_{amb} = 100\text{ }^{\circ}\text{C}$ | | R_{IO} | $\geq 10^{11}$ | Ω |
| Total package dissipation | | ILD74 | P_{tot} | 400 | mW |
| | | ILQ74 | P_{tot} | 500 | mW |
| Derate linearly from 25 $^{\circ}\text{C}$ | | ILD74 | | 5.33 | mW/ $^{\circ}\text{C}$ |
| | | ILQ74 | | 6.67 | mW/ $^{\circ}\text{C}$ |
| Creepage distance | | | | ≥ 7 | mm |
| Clearance distance | | | | ≥ 7 | mm |
| Storage temperature | | | T_{stg} | - 55 to + 150 | $^{\circ}\text{C}$ |
| Operating temperature | | | T_{amb} | - 55 to + 100 | $^{\circ}\text{C}$ |
| Lead soldering time at 260 $^{\circ}\text{C}$ | | | | 10 | s |

Note

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

| ELECTRICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|-------------|------|------|------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| INPUT | | | | | | |
| Forward voltage | $I_F = 20\text{ mA}$ | V_F | | 1.3 | 1.5 | V |
| Reverse current | $V_R = 3\text{ V}$ | I_R | | 0.1 | 100 | μA |
| Capacitance | $V_R = 0\text{ V}$ | C_O | | 25 | | pF |
| OUTPUT | | | | | | |
| Collector emitter breakdown voltage | $I_C = 1\text{ mA}$ | BV_{CEO} | 20 | 50 | | V |
| Collector emitter leakage current | $V_{CE} = 5\text{ V}$, $I_F = 0\text{ A}$ | I_{CEO} | | 5 | 500 | nA |
| Capacitance collector emitter | $V_{CE} = 0\text{ V}$, $f = 1\text{ Hz}$ | C_{CE} | | 10 | | pF |
| COUPLER | | | | | | |
| Saturation voltage, collector emitter | $I_C = 2\text{ mA}$, $I_F = 16\text{ mA}$ | V_{CEsat} | | 0.3 | 0.5 | V |
| Resistance (input to output) | | R_{IO} | | 100 | | $\text{G}\Omega$ |
| Capacitance (input to output) | | C_{IO} | | 0.5 | | pF |

Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

**CURRENT TRANSFER RATIO** ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|---------------------------|--|------------|------|------|------|------|
| DC current transfer ratio | $I_F = 16\text{ mA}$, $V_{CE} = 5\text{ V}$ | CTR_{DC} | 12.5 | 35 | | % |

SWITCHING CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|-----------------|--|----------------------|------|------|------|---------------|
| Switching times | $R_L = 100\text{ }\Omega$, $V_{CE} = 10\text{ V}$, $I_C = 2\text{ mA}$ | t_{on} , t_{off} | | 3 | | μs |


TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

Fig. 1 - Forward Voltage vs. Forward Current




Fig. 3 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 2 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 4 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 5 - Normalized Non-Saturated and Saturated CTR vs. LED Current




Fig. 8 - Normalized CTR_{cb} vs. LED Current and Temperature




Fig. 6 - Collector Emitter Current vs. Temperature and LED Current




Fig. 9 - Collector Base Photocurrent vs. LED Current




Fig. 7 - Collector Emitter Leakage Current vs. Temperature




Fig. 10 - Normalized Photocurrent vs. I_F and Temperature






 Fig. 11 - Normalized Non-Saturated h_{FE} vs. Base Current and Temperature

 Fig. 12 - Normalized Saturated h_{FE} vs. Base Current and Temperature




Fig. 13 - Propagation Delay vs. Collector Load Resistor

PACKAGE DIMENSIONS in millimeters





PACKAGE MARKING



Notes

- Only options 1 and 7 reflected in the package marking
- The VDE logo is only marked on option 1 parts
- Tape and reel suffix (T) is not part of the package marking



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.