

1

2

3

4

5

6

7

8

9

PCB specification

A

B

C

D

E

F

G

H

Epoxyde glass farbic copper-clad laminated sheet of defined flammability according to EN 60249-2-5-FVO-IEC-EP-GC Cu. Insulating material group IIIa according to EN 60664-1. Nominal thickness 1.5mm (include copper foil on both sides). Double-sided, final thickness without solder mask < 1.64mm. Base copper clad 18um,final copper clad > 60um on on both sides. Surface HAL leadfree (SnCu- base alloy without Ag).

top copper

base material

bottom copper

hole

toleranced DIN				tolerance	change date	num- ber	modification		12.05.2016	S.Kulik	S.Kulik			
thread according to DIN				scale:				Date		editor	certifi- cated	Appr.	Index	
surface:				material type:				substitution for dimensions w/o tolerance:						
german projection		material:		DVT-PowerAMP-Stage										
				project version										
semi finished product				TDE		PN10043		1						
material consumption:								6						
weight:														
number of pieces per package:				Format: DIN A 3		Classing:								

Supporting regulations which apply

mailing:

V:

ZV:

For this drawing we reserve ourselves all rights
+ Pay attention to protection note according to DIN ISO 16016
+ Changes from the supplier need the previous approval by TDE

Handwritten
remarks
are not allowed