







Comment	Description	Designator	Footprint	LibRef	Quantity
Сар	Capacitor	C1, C2, C3, C4, C5	RAD-0.3	Сар	5
RJHSE-5080	CONN MOD JACK 8P8C R/A UNSHLD	J1	FP-RJHSE-5080-MFG	CMP-02366-000003-1	1
10mH	Radial Inductor, 10 uH, +/- 10%, 3 A, -55 to 105 degC, 2-Pin THD, RoHS, Bulk	L1	INDR62-500- 1100X850X1100	CMP-1747-00016-1	1
151033RS03000	THT LED round mono- color waterclear, WL- TMRW, Red	LED1, LED2, LED3, LED4, LED5	Type 3mm	CMP-1489-00004-1	5
691321100007	Serie 3211 - 3.50mm Vertical PCB Header WR-TBL, 7 pin	P1	691321100007	CMP-1502-01788-1	1
691321100005	WR-TBL, 5 pin	P2, P3	691321100005	CMP-1502-01786-1	2
691321100002	Serie 3211 - 3.50mm Vertical PCB Header WR-TBL, 2 pin	P4	691321100002	CMP-1502-01783-1	1
691321100004	Serie 3211 - 3.50mm Vertical PCB Header WR-TBL, 4 pin	P5	691321100004	CMP-1502-01785-1	1
P2N2222AG	Amplifier Transistor, NPN Silicon, 3-Pin TO- 92, Pb-Free, Bulk Box	Q1	ONSC-TO-92-3-29-11	CMP-1048-01402-1	1
Res1	Resistor	R1, R6, R7, R9, R10, R11, R12	AXIAL-0.4	Res1	7
Res3	Resistor	R2, R3, R4, R5, R8	AXIAL-0.4	Res3	5
ATmega328-PU	8-bit AVR Microcontroller, 32KB Flash, 1KB EEPROM, 2KB SRAM, 28-pin PDIP, Industrial Grade (-40°C to 85°C)	U1	28P3	CMP-0095-00015-2	1
FOXSLF/160-20	Resistance Weld Thru Hole Crystal, 16 MHz, 20 to 70 degC, 2-Pin THD, RoHS, Bulk		FOX-FOXSLF160-20	CMP-1749-00003-1	1