Mayao, Armhel G.
BSIS - 3A

GIT COMMANDS

```
admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO
$ git config --global user.name "Secret1243"

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO
$ git config --global user.email "mayaoarmhel@gmail.com"

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO
$ git config list
diff.astextplain.textconv=astextplain
filter.lfs.clean=git-lfs clean -- %f
filter.lfs.smudge=git-lfs smudge -- %f
filter.lfs.process=git-lfs filter-process
filter.lfs.required=true
http.sslbackend=schannel
core.autocrlf=true
core.fscache=true
core.symlinks=true
pull.rebase=false
credential.helper=manager
credential.https://dev.azure.com.usehttppath=true
init.defaultbranch=master
core.editor="C:\Users\admin\AppData\Local\Programs\Microsoft VS Code\bin\code" --wait
user.name=Secret1243
user.email=mayaoarmhel@gmail.com

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO
$ git init
Initialized empty Git repository in C:/Users/admin/OneDrive/Documents/BSIS-REPO/.git/

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ touch bsis-ns.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ cat bsis-ns.txt
Hello World!
admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git status
On branch master
```

```
No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        bsis-ns.txt

nothing added to commit but untracked files present (use "git add" to track)

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git add bsis-ns.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
        new file:   bsis-ns.txt


admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git commit -m "Added a new file"
[master (root-commit) e84acb2] Added a new file
 1 file changed, 1 insertion(+)
 create mode 100644 bsis-ns.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ touch sample.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ touch sample1.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ ls
bsis-ns.txt  sample.txt  sample1.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git add .

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git status
On branch master
```

```
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        new file:   sample.txt
        new file:   sample1.txt


admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git commit -m "Added two more files"
[master a3b103a] Added two more files
 2 files changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 sample.txt
 create mode 100644 sample1.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   bsis-ns.txt

no changes added to commit (use "git add" and/or "git commit -a")

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git add bsis-ns.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git commit -m "Modified bsis-ns file"
[master 7005159] Modified bsis-ns file
 1 file changed, 2 insertions(+), 1 deletion(-)

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git log --online
fatal: unrecognized argument: --online

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git log --oneline
7005159 (HEAD -> master) Modified bsis-ns file
a3b103a Added two more files
e84acb2 Added a new file

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git remote add origin https://github.com/Secret1243/Repository_Activity_1.git
```

```
admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git remote -v
origin  https://github.com/Secret1243/Repository_Activity_1.git (fetch)
origin  https://github.com/Secret1243/Repository_Activity_1.git (push)

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git branch
* master

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git push -u origin master
Enumerating objects: 9, done.
Counting objects: 100% (9/9), done.
Delta compression using up to 4 threads
Compressing objects: 100% (5/5), done.
Writing objects: 100% (9/9), 773 bytes | 257.00 KiB/s, done.
Total 9 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a pull request for 'master' on GitHub by visiting:
remote:      https://github.com/Secret1243/Repository_Activity_1/pull/new/master
remote:
To https://github.com/Secret1243/Repository_Activity_1.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git pull
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (3/3), 887 bytes | 63.00 KiB/s, done.
From https://github.com/Secret1243/Repository_Activity_1
 * [new branch]      main       -> origin/main
Already up to date.

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ cat bsis-ns.txt
Hello World!
Hello BSIS-NS-3A
admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git add bsis-ns.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git commit -m "Added another greeting"
```

```
[master bd608a7] Added another greeting
 1 file changed, 2 insertions(+), 1 deletion(-)

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git push
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 324 bytes | 324.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Secret1243/Repository_Activity_1.git
   7005159..bd608a7  master -> master

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git log
commit bd608a7a956a6b6c30d475387638e01a9cd397f9 (HEAD -> master, origin/master)
Author: Secret1243 <mayaoarmhel@gmail.com>
Date:   Sat Oct 24 10:32:58 2026 +0800

    Added another greeting

commit 7005159db71607ba8c81493c5b26deee3662b31e
Author: Secret1243 <mayaoarmhel@gmail.com>
Date:   Sat Oct 24 10:22:52 2026 +0800

    Modified bsis-ns file

commit a3b103aa25f86ea579f6af7f5059d976e12d2d86
Author: Secret1243 <mayaoarmhel@gmail.com>
Date:   Sat Oct 24 10:20:40 2026 +0800

    Added two more files

commit e84acb20629ffae5ae9c40f11aa98d4c58a55b1c
Author: Secret1243 <mayaoarmhel@gmail.com>
Date:   Sat Oct 24 10:19:04 2026 +0800

    Added a new file

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git status
On branch master
Your branch is up to date with 'origin/master'.
```

```
nothing to commit, working tree clean

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git branch
* master

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (master)
$ git switch main
branch 'main' set up to track 'origin/main'.
Switched to a new branch 'main'

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git pull origin main
From https://github.com/Secret1243/Repository_Activity_1
 * branch            main       -> FETCH_HEAD
Already up to date.

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git pull origin master
From https://github.com/Secret1243/Repository_Activity_1
 * branch            master     -> FETCH_HEAD
fatal: refusing to merge unrelated histories

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git branch
* main
  master

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git fetch origin

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git merge origin/master --allow-unrelated-histories
Merge made by the 'ort' strategy.
 bsis-ns.txt | 3 +++
 sample.txt  | 0
 sample1.txt | 0
 3 files changed, 3 insertions(+)
 create mode 100644 bsis-ns.txt
 create mode 100644 sample.txt
 create mode 100644 sample1.txt

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
```

```
$ git push origin main
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (2/2), 359 bytes | 359.00 KiB/s, done.
Total 2 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/Secret1243/Repository_Activity_1.git
   07d70bb..09dc6ab  main -> main

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$ git status
On branch main
Your branch is up to date with 'origin/main'.

nothing to commit, working tree clean

admin@CLIENT05 MINGW64 ~/OneDrive/Documents/BSIS-REPO (main)
$
```