

Report No.:18290KC40023301

Test Report

Client Name : Seeed Technology Co., Ltd**Client Address : 9F, G3 Building, TCL International E City,
Zhongshanyuan Road, Nanshan District,
Shenzhen, Guangdong Province, P.R.C****Product Name : recomputer Industrial****Report Date : 2024.3.5****Shenzhen Anbotek Compliance Laboratory Limited**

Marking

1. The test report is invalid without the official stamp of Shenzhen Anbotech Compliance Laboratory Limited.
2. Nobody is allowed to photocopy or partly photocopy this test report without written permission of Shenzhen Anbotech Compliance Laboratory Limited.
3. The test report is invalid without the signatures of approver.
4. The test report is invalid if altered.
5. Objections to the test report must be submitted to Shenzhen Anbotech Compliance Laboratory Limited within 15 days.
6. The test report is valid for the tested samples only.
7. As for test verdict, “—” means “no need for judgment” “N/A” means “not applicable”.



Report No.:18290KC40023301

TEST REPORT

Sample(s) Name	recomputer Industrial	Model	J4012
Applicant	Seeed Technology Co., Ltd	Trademark	Seeed Studio
Manufacturer	Seeed Technology Co., Ltd	Quantity	1pc
Applicant Address	9F, G3 Building, TCL International E City, Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong Province, P.R.C	Sample(s) received Date	2024.2.21
Factory	Seeed Technology Co., Ltd		
Test item	MTBF $\geq$ 55000 hours at operating temperature of 35 °C MTBF $\geq$ 30000 hours at operating temperature of 50 °C		
Test Method	Telcordia Technologies Special Report SR-332 Issue 4, March 2016		
Testing period	2024.2.21 - 2024.2.28		
Test Conclusion	According to the standards in the inspection, the tested sample inspection(test) project all conform to the requirements. Issue Date: 2024.3.5		
Remark	/		

Prepared by:

Jack Xie

Name: Jack Xie

Checked by:

Jimmy Zhou

Name: Jimmy Zhou

Approved by:

Jeff Zhu

Name: Jeff Zhu

Shenzhen Anbotek Compliance Laboratory Limited

Code:AB-AR-01-d

Page 3 of 40

Address: Zone South, 1/F., Building 2, Hengchangrong High-Tech Industrial Park,
Huangtian, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Report No.:18290KC40023301

1. Detection methods and instructions:

(1) The prediction method is used by Telecordia SR-332 component failure rate prediction.

$$MTBF=1/\lambda$$

 λ =Failure rate(FITs) , FITs means failures in 10⁹ hours.

The prediction of the steady-state failure rate for a device is based on a generic steady-state failure rate for the type of device. This generic value is then modified for quality, stress, and temperature.

$$\lambda_{ssi} = \lambda_{Gi} \pi_{Qi} \pi_{Si} \pi_{Ti}$$

Where λ_{Gi} : mean generic steady-state failure rate for device i π_{Qi} : Quality Factor for device i π_{Si} : Stress Factor for device i π_{Ti} : Temperature Factor for device i

$$\sigma_{ssi} = \sigma_{Gi} \pi_{Qi} \pi_{Si} \pi_{Ti}$$

Where σ_{ssi} : Quality Factor for device i

$$\lambda_{ss} = \pi \varepsilon \sum_{i=1}^n N_i \lambda_{ssi}$$

Where n: Numbers of different device types in the unit

N_i: Quality of ith device type $\pi \varepsilon$: Unit environmental factor

(2) Calculating parameter

Operating Temperature: 35℃、50℃

Environment: Ground、Benign

Calculation model: Telecordia SR-332



Report No.:18290KC40023301

2. Test result:

Test result, The details included in this report

Model	Operating	Failure rate (FITs)	MTBF(Hours)
J4012	35℃	18162.4734	55058.58029
J4012	50℃	32868.8496	30423.9428

Remark:

The above data represent the failure rate of the product and predicted MTBF is according to the Telecordia SR-332 standard, on the ground, benign operation environment.

Reliability prediction by using the data from the client.



Report No.:18290KC40023301

Operating temperature of 35 °C:

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
1	110110191, reComputer Industrial J4012, G.2 (Design)	/	1	0	0
2	202003757, PCBA;reComputer Industrial J201, H.2 (Design)	/	1	2	2
3	301010000, SMD RES 0R-5%-1/16W;0402, A.2 (Design)	RC0402JR-070RL	91	0.1458	13.2678
4	301010004, SMD RES 10K-5%-1/16W;0402, A.2 (Design)	RC0402JR-0710KL	54	0.1458	7.8732
5	301010006, SMD RES 1K-5%-1/16W;0402, A.2 (Design)	RC0402JR-071KL	19	0.1458	2.7702
6	301010027, SMD RES 51K-5%-1/16W;0402, A.1 (Design)	RC0402JR-0751KL	3	0.1458	0.4374
7	301010043, SMD RES 1M-1%-1/16W;0402, A.2 (Design)	RC0402FR-071ML	8	0.1458	1.1664
8	301010054, SMD RES 47K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0747K L	10	0.1458	1.458
9	301010063, SMD RES 22K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0722K L	2	0.1458	0.2916
10	301010081, SMD RES 200K-1%-1/16W;0402, A.1 (Design)	RC0402FR-07200 KL	2	0.1458	0.2916
11	301010185, SMD RES 10R-1%-1/10W;0603, A.2 (Design)	RC0603FR-0710R L	4	0.1458	0.5832
12	301010188, SMD RES 150R-1%-1/10W;0603, A.1 (Design)	RC0603FR-07150 RL	4	0.1458	0.5832
13	301010292, SMD RES 0R-5%-1/10W;0603, A.2 (Design)	RC0603JR-070RL	12	0.1458	1.7496
14	301010295, SMD RES 330R-5%-1/10W;0603, A.1 (Design)	RC0603JR-07330 RL	4	0.1458	0.5832
15	301010410, SMD RES 1M-1%-1/4W;1206, A.1 (Design)	RC1206FR-071ML	2	0.1458	0.2916
16	301010437, SMD RES 5.1R-5%-1/16W;0402, A.3 (Design)	RC0402JR-075R1 L	8	0.1458	1.1664
17	301010441, SMD RES 33K-1%-1/16W;0402, A.3 (Design)	RC0402FR-0733K L	1	0.1458	0.1458
18	301010456, SMD RES 100K-1%-1/16W;0402, A.2 (Design)	RC0402FR-07100 KL	54	0.1458	7.8732



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
19	301010481, SMD RES;200R-1%-1/16W-0402, A.1 (Design)	RC0402FR-07200 RL	3	0.1458	0.4374
20	301010495, SMD RES;5.1K-1%-1/16W;0402, A.1 (Design)	RC0402FR-075K1 L	5	0.1458	0.729
21	301010726, SMD RES 2.2K-5%-1/4W;1206, A.1 (Design)	RC1206JR-072K2L	8	0.1458	1.1664
22	301010736, SMD RES 12K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0712K L	1	0.1458	0.1458
23	301010738, SMD RES 15K-1/16W-1%;0402, A.2 (Design)	RC0402FR-0715K L	4	0.1458	0.5832
24	301010746, SMD RES 2.2K-1%-1/16W;0402, A.1 (Design)	RC0402FR-072K2 L	6	0.1458	0.8748
25	301011091, SMD RES 12.4K-1%-1/16W;0402, A.2 (Design)	RC0402FR-0712K 4L	3	0.1458	0.4374
26	301011315, SMD RES 66.5K-1%-1/16W;0402, A.2 (Design)	RC0402FR-0766K 5L	1	0.1458	0.1458
27	301011477, SMD RES 27R-1%-1/16W;0402, A.2 (Design)	RC0402FR-0727R L	6	0.1458	0.8748
28	301011878, SMD RES 120R-5%-1/4W;1206, A.2 (Design)	RC1206JR-07120 RL	1	0.1458	0.1458
29	301011894, SMD RES 150K-1%-1/16W;0402, A.1 (Design)	RC0402FR-07150 KL	1	0.1458	0.1458
30	301012385, SMD RES 2.2R-1%-1/16W;0402, A.2 (Design)	RC0402FR-072R2 L	2	0.1458	0.2916
31	301012386, SMD RES 499R-1%-1/16W;0402, A.2 (Design)	RC0402FR-07499 RL	14	0.1458	2.0412
32	301013048, SMD RES 6.04K-0.5%-1/16W;0402, A.1 (Design)	RT0402DRE076K0 4L	1	0.1458	0.1458
33	301013446, SMD RES 19.6K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0719K 6L	1	0.1458	0.1458
34	301013490, SMD RES 39.2K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0739K 2L	5	0.1458	0.729



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
35	301013559, SMD RES 7mR-1%-100ppm/°C-1W;1206, A.1 (Design)	PA1206FRF470R0 07L	5	0.1458	0.729
36	302010000, SMD CAP Ceramic 33pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N330	4	0.7156	2.8624
37	302010001, SMD CAP Ceramic 10pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N100	6	0.7156	4.2936
38	302010004, SMD CAP Ceramic 100nF-16V-10%-X7R;0402, A.1 (Design)	CC0402KRX7R7B B104	127	0.7156	90.8812
39	302010009, SMD CAP Ceramic 680pF-50V-10%-X7R;0402, A.1 (Design)	CC0402KRX7R9B B681	2	0.7156	1.4312
40	302010011, SMD CAP Ceramic 4.7pF-50V-0.25pF-NPO;0402, A.1 (Design)	CC0402CRNPO9B N4R7	2	0.7156	1.4312
41	302010012, SMD CAP Ceramic 100pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N101	4	0.7156	2.8624
42	302010013, SMD CAP Ceramic 220pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N221	2	0.7156	1.4312
43	302010015, SMD CAP Ceramic 150pF-50V-5%-NPO;0402, A.1 (Design)	CC0402JRNPO9B N151	2	0.7156	1.4312
44	302010016, SMD CAP Ceramic 18pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N180	4	0.7156	2.8624
45	302010018, SMD CAP Ceramic 22pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N220	1	0.7156	0.7156
46	302010038, SMD CAP Ceramic 10nF-50V-10%-X7R;0402, A.1 (Design)	GRM155R71H103 KA88D	9	0.7156	6.4404
47	302010049, SMD CAP Ceramic 12pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N120	2	0.7156	1.4312



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
48	302010051, SMD CAP Ceramic 220nF-16V-10%-X7R;0402, A.3 (Design)	CC0402KRX7R7B B224	8	0.7156	5.7248
49	302010103, SMD CAP Ceramic 10uF-10V-10%-X5R;0603, A.2 (Design)	CC0603KRX5R6B B106	11	0.7156	7.8716
50	302010111, SMD CAP Ceramic 4.7uF-10V-10%-X5R;0603, A.2 (Design)	CC0603KRX5R6B B475	13	0.7156	9.3028
51	302010138, SMD CAP Ceramic 100nF-50V-10%-X7R;0603, B.1 (Design)	CC0603KRX7R9B B104	11	0.7156	7.8716
52	302010139, SMD CAP Ceramic 1uF-25V-10%-X7R;0603, A.1 (Design)	CC0603KRX7R8B B105	2	0.7156	1.4312
53	302010235, SMD CAP Ceramic 22uF-25V-20%-X5R;0805, A.1 (Design)	CC0805MKX5R8B B226	14	0.7156	10.0184
54	302010394, SMD CAP Ceramic 1nF-50V-5%-X7R;0402, A.1 (Design)	CC0402JRX7R9B B102	4	0.7156	2.8624
55	302011962, SMD CAP Ceramic 1nF-2kV-10%-X7R;1206, A.3 (Design)	CC1206KKX7RDB B102	2	0.7156	1.4312
56	302012659, SMD CAP Ceramic 4.7uF-50V-10%-X7R;0805, A.1 (Design)	GRM21BZ71H475 KE15L	7	0.7156	5.0092
57	302012962, SMD CAP Ceramic 10nF-100V-10%-X7R;0603, A.2 (Design)	CC0603KRX7R0B B103	2	0.7156	1.4312
58	302013246, SMD CAP Ceramic 470nF-50V-10%-X5R;0603, A.1 (Design)	CC0603KRX5R9B B474	3	0.7156	2.1468
59	302013249, SMD CAP Ceramic 1uF-10V-10%-X5R;0402, A.1 (Design)	CL05A105KP5NN NC	12	0.7156	8.5872
60	302013268, SMD CAP Ceramic 22uF-35V-20%-X5R;1210, A.1 (Design)	GMK325BJ226MM -P	5	0.7156	3.578



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
61	302020569, SMD CAP Tantalum 330uF-6.3V-20%-0.08R;C-6032, A.2 (Design)	CA55-C6R3M337T E080	7	0.7156	5.0092
62	302031185, SMD CAP Aluminum 220uF-50V;SMD-D10*H10.5mm, A.2 (Design)	VD1H221MG1050 00CE0	2	0.7156	1.4312
63	303010925, SMD Inductor 1uH-20%;L2.0*W1.6*H1.0mm, A.3 (Design)	WPN201610H1R0 MT	1	0.8223	0.8223
64	303011145, SMD Inductor 1nH-0.3nH-300mA;0402, A.3 (Design)	LQG15HN1N0S02 D	1	0.8223	0.8223
65	303011409, SMD Inductor 6.8uH-20%-1.5A;L4.0xW4.0xH2.6m m, A.3 (Design)	SWPA4026S6R8M T	1	0.8223	0.8223
66	303011669, SMD Inductor 3.3uH-20%-3.3A;2P-L4.2*W4.4*H1. 8mm, A.2 (Design)	MWSA0402S-3R3 MT	4	0.8223	3.2892
67	303011722, SMD Inductor;4.0nH±0.1nH-0.4R-5.3GH z-350mA;0201, A.2 (Design)	LQP03TN4N0B02 D	8	0.8223	6.5784
68	303011796, SMD Inductor;4.7uH-20%-13.1mR-15A-1 4A;L8.8*W8.3*H4.8mm, A.2 (Design)	CSEB0850-4R7M	2	0.8223	1.6446
69	303030024, SMD Ferrite Bead;120R-2A;0603, A.4 (Design)	BLM18PG121SN1 D	13	0.0731	0.9503
70	303050063, SMD Common Mode Filter 90R-400mA;4P-L2.0*W1.2*H1.4m, A.2 (Design)	SRF2012-900YA	2	0.0731	0.1462
71	303050383, SMD Common Mode Filter;3200R-0.65A;4P-L8.7*W10*H 6.5mm, A.4 (Design)	CSTCB1060R-302	1	0.0731	0.0731
72	303050503, DIP Common Mode Chokes 2mH@1KHz-10% 6A 600V ;4P-D20*H18mm, A.2 (Design)	PDMCAT16128-20 2ML	1	0.1005	0.1005



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
73	303050504, SMD Common Mode Chokes 1.4k@100MHz 1.9A-50V;4P-L4.75*W4.5*H2mm, A.2 (Design)	PCAQ4520MB-142	3	1.5533	4.6599
74	304010714, SMD Diode 40V-2A; PowerDI™ 123, A.3 (Design)	DFLS240L-7	2	0.2891	0.5782
75	304020022, SMD Diode Schottky 30V-1A;SOD-323F, A.2 (Design)	PMEG3010CEJ,115	16	7.1269	114.0304
76	304030489, SMD Diode Zener 43V-500MW;SOD-123, A.2 (Design)	MMSZ5260BT1G	4	63.0732	252.2928
77	304030509, SMD Diode Zener 3.3V-500mW;SOD-123, A.2 (Design)	MMSZ3V3T1G	2	63.0732	126.1464
78	304030710, SMD Diode Zener 5.6V-500mW;SOD-123, A.3 (Design)	MMSZ5232BT1G	1	63.0732	63.0732
79	304030711, SMD Diode Zener;27V-26.46V to 27.54V-500mW;SOD-123, A.2 (Design)	MMSZ5254A_R1_00001	1	63.0732	63.0732
80	304040003, SMD Diode Switching 75V-150mA;SOD-323, A.3 (Design)	1N4148WS.	2	3.0135	6.027
81	304050009, SMD Diode TVS 16VWM 26V;SMB, A.2 (Design)	SMBJ16CA	6	0.5782	3.4692
82	304050312, SMD Diode ESD 5.5V-6V-12pF-30KV-30KV;X1SON(2), A.2 (Design)	TPD1E10B06DPYR	25	3.0135	75.3375
83	304050905, SMD Diode TVS 26V 1.5KW Bidirectional;SMC, A.2 (Design)	SMCJ26CA	1	0.5782	0.5782
84	304050907, SMD Gas Discharge Tube 90V 20KA 2 Electrodes;D8.3*L6.0mm, A.2 (Design)	2RP090M-8-S	1	315.366	315.366
85	304050978, SMD Diode TVS-58VWM-93.6V;DO-214AA(SMB), A.2 (Design)	SMBJ58CA	3	0.5782	1.7346



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
86	304051142, SMD Diode TVS 13V 1.5KW Bidirectional;SMC, A.2 (Design)	SMCJ13CA	2	0.5782	1.1564
87	304060074, SMD Diode ESD 0.05pF;0402, A.3 (Design)	ESDPSA0402V05	30	3.0135	90.405
88	304060294, SMD Diode Array ESD;4 Channel,6 Gbps,5.5V;USON-10, A.4 (Design)	TPD4E05U06DQAR	4	4.8762	19.5048
89	304060395, SMD Diode Array ESD;4 Channel,0.25pF,3.6V,10Gbps;USO N-10, A.2 (Design)	TPD4E02B04DQAR	7	4.8762	34.1334
90	304090043, SMD LED Clear-Green;LED-0603, C.2 (Design)	19-217/G7C-AN1P 2/6T	2	0.2891	0.5782
91	304091968, DIP LED;Yellow Green+Red;4P-2.54-11.5*9.65*4.3 mm, A.2 (Design)	A694B/SYGSUR/S 530-A3	1	0.2891	0.2891
92	305010564, SMD Transistor NPN 80V-1A;SOT-223, A.2 (Design)	BCP56-10T1G	4	1.5505	6.202
93	305010705, SMD Transistors NPN 40V-200mA-200mW;SOT-323, A.2 (Design)	MMST3904-7-F	2	1.5505	3.101
94	305020002, SMD Transistors PNP 40V-200mA;SOT-23, A.2 (Design)	MMBT3906LT3G	1	1.5505	1.5505
95	305020497, SMD MOSFET P-CH 60V-70A;PDFNWB5*6-8L, A.2 (Design)	CJAC70P06	2	3.0135	6.027
96	305030012, SMD MOSFET P-CH 50V-130mA;SOT-323, A.2 (Design)	BSS84W-7-F	1	3.0135	3.0135
97	305030799, SMD OptoMOS;4SOP, A.3 (Design)	CPC1017NTR	1	4.2860	4.286
98	305031179, SMD MOSFET P-CH 30V-12A;HSMT8, A.2 (Design)	RQ3E120ATTB	1	3.0135	3.0135
99	305031301, SMD MOSFET N-CH;30V-50A,11.8 mOhm;VSON 3.3*3.3mm, A.2 (Design)	CSD17308Q3	2	3.0135	6.027



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
100	305031302, SMD MOSFET N-CH;30V-60A,3.2 mOhm;VSON 3.3*3.3mm, A.3 (Design)	CSD17575Q3	2	3.0135	6.027
101	305031465, SMD MOSFET N-CH;built-in ESD,Vgs =20V,Vds=30V,100mA;SOT-323, A.3 (Design)	2SK3018	23	3.0135	69.3105
102	305031480, SMD MOSFET N-CH;built-in ESD,Vds=20V,Vgs =12V,Vgs(th)=0.35V-1.1V,0.75A;S OT-323, A.2 (Design)	CJ3134KW	3	3.0135	9.0405
103	306011268, SMD Crystal 25MHz-12pF-10ppm-30ppm-50R;4 P-SMD-L3.2*W2.5*H0.8mm, A.2 (Design)	5YAA25000121TF 50Q3	2	13	26
104	306011385, SMD Crystal 12MHz-10pF-10ppm-100R;4P-SMD -L3.2*W2.5*H0.8mm, A.2 (Design)	5YAA12000101TF A0Q3	1	13	13
105	306020781, SMD Oscillator;32.768KHz-3.3V-30ppm; SMD-3225-4P-L3.2*W2.5*H1.1mm, A.2 (Design)	1631-L3273-BTBQ YA	1	13	13
106	307010738, SMD PPTC 500mA-1A-60V;1812, A.2 (Design)	JK-MSMD050-60	4	0.4	1.6
107	307020350, SMD Fuseholder with Fuse-5A;2P-L9.73*W5.03*H3.81m m, A.5 (Design)	6125(H).24T15002 00J	1	0.4	0.4
108	310011401, SMD IC MCU;Dual Cortex M0+;133Mhz;QFN-56-2022 (含)年以后, A.4 (Design)	RP2040	1	242.165	242.165
109	310030161, SMD IC PMIC;DFN(2*2)-8, B.2 (Design)	ETA3410D2I-T	1	218.5463	218.5463
110	310030260, SMD IC PMIC;SOT23-5, A.1 (Design)	SY6280AAC	3	215.216	645.648
111	310031538, SMD IC PMIC;Reset Circuit;2.63V VTH RST;SOT143, A.2 (Design)	UM805RE	1	235.486	235.486



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
112	310032333, DIP Isolated DCDC;5V to 5V,1500VDC/min,0.75W,Regulator; 4P-2.54mm-L11.60*W6.00*H10.16 mm, A.2 (Design)	IB0505S-W75R3	1	282.516	282.516
113	310032514, SMD IC PMIC;Power Switch,Single Channel,2.5V to 5.5V,2.1A,Active High;SOT23-5, A.2 (Design)	SGM2588CYN5G/ TR	2	247.5683	495.1366
114	310032529, SMD IC PMIC;LDO-1.8V-500mA;SOT23-5, A.3 (Design)	LC1458CB5TR18	1	221.8564	221.8564
115	310032530, SMD IC PMIC;LDO-3.3V-500mA;SOT23-5, A.3 (Design)	LC1458CB5TR33	1	221.8564	221.8564
116	310032622, SMD IC DCDC;Synchronous Buck Controller,External Switch,4V to 60V Input;QFN-20 (3mmx4mm), A.2 (Design)	MP9928GL-Z	2	239.1649	478.3298
117	310050024, SMD IC Logic;TSSOP-20, A.3 (Design)	TXB0108PWR	1	218.135	218.135
118	310050025, SMD IC Logic;TSSOP-14, A.2 (Design)	TXB0104PWR	1	211.186	211.186
119	310050099, SMD IC Logic;TSSOP-14, A.2 (Design)	TXS0104EPWR	1	211.186	211.186
120	310050347, SMD IC Logic;SOT-6, A.2 (Design)	SN74LVC1T45DR LR	1	234.854	234.854
121	310050830, SMD IC Logic;TSSOP-5, A.2 (Design)	74LVC1G07GW	3	293.1986	879.5958
122	310051190, SMD IC Logic;Buffer, Non-Inverting 1 Element 1 Bit per Element 3-State Output SOT-23-5, A.2 (Design)	SN74LV1T125DBV R	4	218.5651	874.2604
123	310051411, SMD IC Logic;2-Bit Bidirectional Voltage-Level Translator;X2SON-8, A.2 (Design)	TXB0302DQMR	1	238.5613	238.5613



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
124	310051412, SMD IC Logic;Digital Isolators,2+2 Channels,1.71 V to 1.89 V and 2.25 V to 5.5 V;SOIC (16), A.2 (Design)	ISO6742DWR	1	249.563	249.563
125	310070986, SMD IC Interface;QFN-24, A.2 (Design)	CP2102N-A02-GQ FN24R	1	218.6739	218.6739
126	310071436, SMD IC Interface CAN Transceiver;SOIC-16, A.3 (Design)	TPT71044-SOBR	1	256.8974	256.8974
127	310071437, SMD IC Interface;4-port 5-Gbps SuperSpeed USB 3.0 Hub;VQFN-56, A.2 (Design)	USB5744T-I/2G	1	278.389	278.389
128	310071438, SMD IC Interface;PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC/PHY;48-SQFN, A.2 (Design)	LAN7430-I/Y9X	1	218.801	218.801
129	310071439, SMD IC Interface;Single 3.3V or 5V RS232/RS422/RS485 Multiprotocol Transceiver;TQFN40L 5*5, A.2 (Design)	F81439N	1	277.3861	277.3861
130	310071440, SMD IC Interface;16-bit 2.3V to 5.5V I2C I/O expander with interrupt & config registers;VQFN(24), A.2 (Design)	PCA9535RGER	1	294.8331	294.8331
131	310090011, SMD IC Memory;EEPROM Memory IC 256Kb (32768 x 8)-SOIC-8(3.9mm), A.2 (Design)	AT24C256C-SSHL -T	1	259.5646	259.5646
132	310091344, SMD IC NOR Flash;Dual and Quad SPI,4M-bit,2.7-3.6V;SOIC-8(150mil), A.2 (Design)	GD25Q40ETIGR	1	272.689	272.689
133	310100627, SMD IC Analog Switch;High Speed USB 2.0 (480Mbps) DPDT Analog Switch;WQFN-10, A.2 (Design)	SGM7222YWQ10/ TR	4	287.891	1151.564
134	310990465, SMD IC OPTOISOLATOR;4SOP, A.2 (Design)	SFH690BT3	8	203.347	1626.776



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
135	311021382, DIP Button Side 1.57N;4P-90D, A.2 (Design)	SKQJLBA010	2	1.0591	2.1182
136	311080506, SMD Top DIP Switches;2*4P-L6.66*W8.3*H2.35mm, A.2 (Design)	SP-04P	1	1.0591	1.0591
137	314130227, SMD Varistor DC30V-AC25V-30A-0.1J-72V;0805, A.2 (Design)	V30MLA0805LNT	4	0.732	2.928
138	314130267, DIP RES Varistor ,820K 18V-1800V;2P-7.5-L14*W2.1*H14.5 mm, A.2 (Design)	820KD14	2	0.732	1.464
139	317990927, DIP PoE module;PSE,Input 12V to 24V,Output 52V,30W,6P-2.54mm-L60*W20*H16.8mm, A.2 (Design)	WC-PSE12-52V	1	4.683	4.683
140	319015640, PCB;reComputer Industrial J201_V1.2-黑油白字-6 层, A.3 (Design)	/	1	2	2
141	320011178, DIP Female USB Type A; USB3.0 R-A ;9+2P, A.2 (Design)	UEA1112C-4HK1-4H	1	34.5883	34.5883
142	320011199, SMD USB Type-C;USB2.0 Only,12P+4P-8.94*8.3*3.26mm, A.2 (Design)	UBF31-0171L	2	34.5883	69.1766
143	320011342, DIP USB-A,Stacked USB 3.0-R/A;18+4P, A.3 (Design)	USB-2A-01-3.0	1	34.5883	34.5883
144	320020839, DIP Beige Male Header VERT;1*2P-1.25MM, A.4 (Design)	WY-3739	1	0.9434	0.9434
145	320021938, DIP Black Male Header VERT;2*10P-2.54-2.5-6.0-3.0mm-90D, A.2 (Design)	PST-PH-254-0100-2*10P	1	9.434	9.434
146	320021939, SMD Black Male Header VERT;With Positioning,Without Pin14;2*7P-1.27-5.5-4.0mm, A.2 (Design)	SF-PH-127-0030-2*7-K14-D	1	34.5883	34.5883



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
147	320060644, SMD FPC CONN;15P-1.0mm-90D, A.3 (Design)	YL002-009-015	2	7.0755	14.151
148	320100250, SMD Nano-SIM Holder;7P+4-L13.5*W13.1*H1.50m m(自弾), B.2 (Design)	ST-SIM-SP132	1	3.3019	3.3019
149	320111670, DIP Male DB9 Connector;DB9-90D;9+2P, A.2 (Design)	DT10621-H7809-4 H	1	34.5883	34.5883
150	320111775, DIP JST Male Connector Black;4P-1.25MM, A.2 (Design)	1.25-4A-black	1	34.5883	34.5883
151	320111776, SMD Connector Black M.2 Key-M,PCIe Gen4.0,H=2.0mm,10u Gold Plating;67P-0.5mm, A.2 (Design)	2E0BC26-F20BM- 7H	1	1.5722	1.5722
152	320111877, SMD+DIP HDMI Connector;HDMI 2.1,Type A,Gold Flash;19+4P-L12.15*W15.00*H6.18 mm-90D, A.2 (Design)	QJA5311-LF34S-7 F	1	34.5883	34.5883
153	320111888, DIP PCB Connector;Terminal Block,Green,2x8Pin;3.81mm-90D, A.2 (Design)	YL032-096-016	1	7.5472	7.5472
154	320112030, DIP Female Screw Terminal-Green;1*2P-5.08-90D, A.3 (Design)	STP2EDGRM-X-5. 08-2P	1	34.5883	34.5883
155	320140597, DIP RJ45;1000M,Integrated Magnetics+PoE,G/Y 2 LEDs,Right Angle;18+2P-21.25*15.93*13.30m m, A.2 (Design)	LPJG4926-7HENL	1	34.5883	34.5883
156	320140598, DIP RJ45;1000M,Integrated Magnetics,G/Y 2 LEDs,Right Angle,Voltage Type;16+2P-21.25*15.93*13.3mm, A.2 (Design)	LPJG4933-7HENL	1	34.5883	34.5883



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
157	320170000, SMD Battery Cell Holder Plastic;CR1220-15*13*H4mm, B.2 (Design)	MTBA20-1220A0-0 5133	1	2.0439	2.0439
158	320210481, SMD BTB CONN Black m.2 B-key;67P-0.5mm;L21.9*W2.9*H8.5 mm, A.2 (Design)	2E0BC21-S85BB-7 H	1	1.5722	1.5722
159	320210501, SMD BTB CONN;Gold Flash-2*130P+2P-0.5mm-H=9.2mm -S=6.9mm-SODD4 9.2 STD, A.2 (Design)	ASAA821-EASB0- 7H	1	1.5722	1.5722
160	320991107, SMD Mini PCI-E CONN;52P-0.8mm-L29.9*9.08*4.0 mm, A.3 (Design)	ST-PC-002	1	2.0439	2.0439
161	326051030, SMD Stud; M3 铜柱, D5.56*0.3mm, 黄铜, 表面电镀锡(编带包装,带麦拉), A.2 (Design)	SMTSO3003CTJ	1	0	0
162	326051131, SMD Stud; M2.5 铜柱, D5.56*L6.5+D4.09*1.53mm, 无铅铜, 表面电镀锡(编带包装), A.2 (Design)	SMTSO2565CTJ-U L	2	0	0
163	326051132, SMD Stud; M2 铜柱, D5.56*1.5mm, 无铅铜, 表面电镀锡(编带包装), A.2 (Design)	SMTSO2015CTJ-U L	4	0	0
164	327133101, 空白贴纸;80g 铜版不干胶纸-10*10mm 双排-2500pcs 卷, A.2 (Design)	/	1	0	0
165	401040291, 胶水,硅橡胶,型号:KD-8405MBW,白色膏状,100ml, A.2 (Design)	/	1	0	0
166	206001531, reComputer Industrial_左挡板-镭雕, A.2 (Design)	/	1	0	0
167	323011231, reComputer Industrial_左挡板;铝 6063-155.0*30.0*17.5mm-喷砂氧化-丝印-黑色-48H, A.2 (Design)	/	1	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
168	206001532, reComputer Industrial_右挡板-镭雕, A.2 (Design)	/	1	0	0
169	323011232, reComputer Industrial_右挡板;铝 6063-155.0*30.0*17.5mm-喷砂氧化-丝印-黑色-48H, A.2 (Design)	/	1	0	0
170	206001533, reComputer Industrial_底壳-镭雕, A.2 (Design)	/	1	0	0
171	323030948, reComputer Industrial_底壳;SPCC-155.0*155.0*31.0mm-喷涂-丝印-黑色-48H, A.2 (Design)	/	1	0	0
172	206001536, reComputer Industrial-Orin_散热器-镭雕, A.2 (Design)	/	1	0	0
173	323011238, reComputer Industrial-Orin_散热器;铝 6063-155.0*155.0*22.5mm-喷砂氧化-黑色-48H, A.2 (Design)	/	1	0	0
174	206001540, reComputer Industrial_带电源包装组件, D.2 (Design)	/	1	0	0
175	327040006, Plastic Bag Green;W50*H70*0.12mm (双层厚度)-自封口, A.1 (Design)	/	1	0	0
176	327040014, Plastic Bag Clear;W100*H150*0.05mm-自封口-红边, A.1 (Design)	/	2	0	0
177	327111702, reComputer Industrial_纸盒;259*189*80MM-300G 优质牛卡+K9 (H230 110) 过光油, A.2 (Design)	/	1	0	0
178	327111703, 配件盒;182*72*55MM-300G 优质牛卡+K9 (H230 110), A.2 (Design)	/	1	0	0
179	327111704, 纸箱;K=K-340*275*220MM, B.1 (Design)	/	1	0	0
180	327122437, 平卡;K6K-320*265*3MM, A.2 (Design)	/	2	0	0
181	327130462, Label;不可移透明圆形贴纸-D30mm-高粘, A.2 (Design)	/	1	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
182	327131816, 空白标签;5000pcs 卷-5 列-耐高温 300 度-7*14mm, C.1 (Design)	/	1	0	0
183	327132226, Label;空白标签-铜版纸 不干胶-90*140mm-250pcs/卷, A.3 (Design)	/	1	0	0
184	327132997, 空白贴纸;75#合成纸贴 纸-36.7*10.7mm 单排-2500pcs 卷, A.2 (Design)	/	1	0	0
185	327133101, 空白贴纸;80g 铜版不干 胶纸-10*10mm 双排-2500pcs 卷, A.2 (Design)	/	1	0	0
186	327133163, Label;空白标 签;1000pcs 卷-1 列-50# PI 耐高温贴 纸-76*30mm, A.2 (Design)	/	1	0	0
187	327142009, 内托(上 盖);185*185*30MM-IXPE30B, A.2 (Design)	/	1	0	0
188	327142010, 内托(下 盖);185*185*30MM-IXPE30B, A.2 (Design)	/	1	0	0
189	327172034, 安全说明书;80G 书纸- 折叠款-80*80mm, A.2 (Design)	/	1	0	0
190	206001545, M. 2 NVME 2280 SSD 128G-外发烧录 reComputer Industrial J4012, C.2 (Design)	/	1	1000	1000
191	317990969, M. 2 NVME 2280 SSD 128G, A.3 (Design)	NHESR128GTLE W-I3C-2	1	1000	1000
192	313010036, Lithium-ion Battery;3V-40mAh;CR1220, A.4 (Design)	CR1220	1	25	25
193	313080684, Power Adapter;3P-Black-19V-4.74A; 梅花 口(不带 AC 电源线), A.3 (Design)	PA-1900-32I2	1	210	210
194	317990915, NVIDIA Jetson Orin NX Module 16GB, A.2 (Design)	900-13767-0000-0 00	1	2800	2800



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
195	320111889, Pluggable Terminal Block, Green; 2x8Pin 3.81mm, A.2 (Design)	YL032-098-016	1	34.5883	34.5883
196	320112031, Male Screw Terminal-Green; 1*2P-5.08, A.3 (Design)	STP2EDGM-X-5.0 8-2P	1	34.5883	34.5883
197	321050726, DC Power Pigtail Cable; Female-18AWG-L230mm-55 25-剥锡 4mm-Red/Black, A.2 (Design)	5525 母头连接线	1	1.5722	1.5722
198	322100782, 天线孔塞; 硅胶 -D10*H7.0mm-磨砂-黑色-60度 -1mm 壁厚, A.2 (Design)	/	4	0	0
199	322100786, 导热硅胶片; 14*14*2mm, 6W/M.K, A.3 (Design)	/	1	0	0
200	322100787, 导热硅脂; 安众 SZTG-40 系列-灰色-导热系数 4W/mk-1KG/瓶, A.2 (Design)	/	1	0	0
201	322991191, reComputer Industrial_ 导电棉-左; 导电棉-75.0*25.0*3.0mm-单面背导电胶-黑色, A.2 (Design)	/	1	0	0
202	322991192, reComputer Industrial_ 导电棉-右; 海绵+导电布 -85.0*25.0*3.0mm-单面背导电胶-黑色, A.2 (Design)	/	1	0	0
203	322991193, 导电棉; 62.0*4.5*0.3mm-单面背导电胶-黑色, A.2 (Design)	/	2	0	0
204	322991196, 脚垫; 硅橡胶-带铁垫 -11*9*6mm-黑色, A.2 (Design)	/	4	0	0
205	323011237, 工业 DIN 导轨卡扣; 铝 -48.0x30.0x9.0mm-黑色, A.2 (Design)	/	1	0	0
206	323030949, reComputer Industrial_ 安装挂板; SPCC-130.0*43.8*3.4mm-喷粉-绿色-48H, B.1 (Design)	/	2	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
207	323030950, reComputer Industrial Jetson_标识牌;SPCC-21.0*20.0*23.3mm-喷粉-绿色-48H, A.2 (Design)	/	1	0	0
208	326010872, Screw;十字圆头机牙螺丝_M2.5x6mm;碳钢镀镍;本色, A.3 (Design)	/	2	0	0
209	326020017, Screw;十字沉头机牙螺丝-120°头型-KM3xH5mm-铁-三价铬黑锌-耐落-黑色-48H, A.2 (Design)	/	12	0	0
210	326020442, Screw;十字扁头机牙螺丝-CM2xH3mm-头径 4.0mm 厚 0.5mm-铁-黑色, A.3 (Design)	/	2	0	0
211	326020683, Screw,十字机牙平头-碳钢-CM3*4.0mm-镀黑镍-耐落-12H, A.2 (Design)	/	3	0	0
212	326020684, Screw;十字圆头机牙螺丝-PM4.0*4.0mm-铁-锌镍合金-耐落-本色-48H, A.2 (Design)	/	1	0	0
213	326020685, Screw;十字沉头机牙螺丝-KM3*H32mm-铁-三价铬黑锌-耐落-黑色-48H, A.2 (Design)	/	4	0	0
214	326051065, Stud,滚花螺栓-M3*+6.5mm+M2*2.0mm-铜镀镍-银色, A.2 (Design)	/	1	0	0
215	327133265, reComputer Industrial J4012_背部贴纸;80g 铜版不干胶贴纸+哑膜-160*110mm, A.2 (Design)	/	1	0	0



Report No.:18290KC40023301

Operating temperature of 50 °C:

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
1	110110191, reComputer Industrial J4012, G.2 (Design)	/	1	0	0
2	202003757, PCBA;reComputer Industrial J201, H.2 (Design)	/	1	3.68	3.68
3	301010000, SMD RES 0R-5%-1/16W;0402, A.2 (Design)	RC0402JR-070RL	91	0.269	24.479
4	301010004, SMD RES 10K-5%-1/16W;0402, A.2 (Design)	RC0402JR-0710KL	54	0.269	14.526
5	301010006, SMD RES 1K-5%-1/16W;0402, A.2 (Design)	RC0402JR-071KL	19	0.269	5.111
6	301010027, SMD RES 51K-5%-1/16W;0402, A.1 (Design)	RC0402JR-0751KL	3	0.269	0.807
7	301010043, SMD RES 1M-1%-1/16W;0402, A.2 (Design)	RC0402FR-071ML	8	0.269	2.152
8	301010054, SMD RES 47K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0747KL	10	0.269	2.69
9	301010063, SMD RES 22K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0722KL	2	0.269	0.538
10	301010081, SMD RES 200K-1%-1/16W;0402, A.1 (Design)	RC0402FR-07200KL	2	0.269	0.538
11	301010185, SMD RES 10R-1%-1/10W;0603, A.2 (Design)	RC0603FR-0710RL	4	0.269	1.076
12	301010188, SMD RES 150R-1%-1/10W;0603, A.1 (Design)	RC0603FR-07150RL	4	0.269	1.076
13	301010292, SMD RES 0R-5%-1/10W;0603, A.2 (Design)	RC0603JR-070RL	12	0.269	3.228
14	301010295, SMD RES 330R-5%-1/10W;0603, A.1 (Design)	RC0603JR-07330RL	4	0.269	1.076
15	301010410, SMD RES 1M-1%-1/4W;1206, A.1 (Design)	RC1206FR-071ML	2	0.269	0.538
16	301010437, SMD RES 5.1R-5%-1/16W;0402, A.3 (Design)	RC0402JR-075R1L	8	0.269	2.152
17	301010441, SMD RES 33K-1%-1/16W;0402, A.3 (Design)	RC0402FR-0733KL	1	0.269	0.269
18	301010456, SMD RES 100K-1%-1/16W;0402, A.2 (Design)	RC0402FR-07100KL	54	0.269	14.526



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
19	301010481, SMD RES;200R-1%-1/16W-0402, A.1 (Design)	RC0402FR-07200 RL	3	0.269	0.807
20	301010495, SMD RES;5.1K-1%-1/16W;0402, A.1 (Design)	RC0402FR-075K1 L	5	0.269	1.345
21	301010726, SMD RES 2.2K-5%-1/4W;1206, A.1 (Design)	RC1206JR-072K2L	8	0.269	2.152
22	301010736, SMD RES 12K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0712K L	1	0.269	0.269
23	301010738, SMD RES 15K-1/16W-1%;0402, A.2 (Design)	RC0402FR-0715K L	4	0.269	1.076
24	301010746, SMD RES 2.2K-1%-1/16W;0402, A.1 (Design)	RC0402FR-072K2 L	6	0.269	1.614
25	301011091, SMD RES 12.4K-1%-1/16W;0402, A.2 (Design)	RC0402FR-0712K 4L	3	0.269	0.807
26	301011315, SMD RES 66.5K-1%-1/16W;0402, A.2 (Design)	RC0402FR-0766K 5L	1	0.269	0.269
27	301011477, SMD RES 27R-1%-1/16W;0402, A.2 (Design)	RC0402FR-0727R L	6	0.269	1.614
28	301011878, SMD RES 120R-5%-1/4W;1206, A.2 (Design)	RC1206JR-07120 RL	1	0.269	0.269
29	301011894, SMD RES 150K-1%-1/16W;0402, A.1 (Design)	RC0402FR-07150 KL	1	0.269	0.269
30	301012385, SMD RES 2.2R-1%-1/16W;0402, A.2 (Design)	RC0402FR-072R2 L	2	0.269	0.538
31	301012386, SMD RES 499R-1%-1/16W;0402, A.2 (Design)	RC0402FR-07499 RL	14	0.269	3.766
32	301013048, SMD RES 6.04K-0.5%-1/16W;0402, A.1 (Design)	RT0402DRE076K0 4L	1	0.269	0.269
33	301013446, SMD RES 19.6K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0719K 6L	1	0.269	0.269
34	301013490, SMD RES 39.2K-1%-1/16W;0402, A.1 (Design)	RC0402FR-0739K 2L	5	0.269	1.345



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
35	301013559, SMD RES 7mR-1%-100ppm/°C-1W;1206, A.1 (Design)	PA1206FRF470R0 07L	5	0.269	1.345
36	302010000, SMD CAP Ceramic 33pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N330	4	0.8524	3.4096
37	302010001, SMD CAP Ceramic 10pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N100	6	0.8524	5.1144
38	302010004, SMD CAP Ceramic 100nF-16V-10%-X7R;0402, A.1 (Design)	CC0402KRX7R7B B104	127	0.8524	108.2548
39	302010009, SMD CAP Ceramic 680pF-50V-10%-X7R;0402, A.1 (Design)	CC0402KRX7R9B B681	2	0.8524	1.7048
40	302010011, SMD CAP Ceramic 4.7pF-50V-0.25pF-NPO;0402, A.1 (Design)	CC0402CRNPO9B N4R7	2	0.8524	1.7048
41	302010012, SMD CAP Ceramic 100pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N101	4	0.8524	3.4096
42	302010013, SMD CAP Ceramic 220pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N221	2	0.8524	1.7048
43	302010015, SMD CAP Ceramic 150pF-50V-5%-NPO;0402, A.1 (Design)	CC0402JRNPO9B N151	2	0.8524	1.7048
44	302010016, SMD CAP Ceramic 18pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N180	4	0.8524	3.4096
45	302010018, SMD CAP Ceramic 22pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N220	1	0.8524	0.8524
46	302010038, SMD CAP Ceramic 10nF-50V-10%-X7R;0402, A.1 (Design)	GRM155R71H103 KA88D	9	0.8524	7.6716
47	302010049, SMD CAP Ceramic 12pF-50V-5%-NPO;0402, A.2 (Design)	CC0402JRNPO9B N120	2	0.8524	1.7048



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
48	302010051, SMD CAP Ceramic 220nF-16V-10%-X7R;0402, A.3 (Design)	CC0402KRX7R7B B224	8	0.8524	6.8192
49	302010103, SMD CAP Ceramic 10uF-10V-10%-X5R;0603, A.2 (Design)	CC0603KRX5R6B B106	11	0.8524	9.3764
50	302010111, SMD CAP Ceramic 4.7uF-10V-10%-X5R;0603, A.2 (Design)	CC0603KRX5R6B B475	13	0.8524	11.0812
51	302010138, SMD CAP Ceramic 100nF-50V-10%-X7R;0603, B.1 (Design)	CC0603KRX7R9B B104	11	0.8524	9.3764
52	302010139, SMD CAP Ceramic 1uF-25V-10%-X7R;0603, A.1 (Design)	CC0603KRX7R8B B105	2	0.8524	1.7048
53	302010235, SMD CAP Ceramic 22uF-25V-20%-X5R;0805, A.1 (Design)	CC0805MKX5R8B B226	14	0.8524	11.9336
54	302010394, SMD CAP Ceramic 1nF-50V-5%-X7R;0402, A.1 (Design)	CC0402JRX7R9B B102	4	0.8524	3.4096
55	302011962, SMD CAP Ceramic 1nF-2kV-10%-X7R;1206, A.3 (Design)	CC1206KKX7RDB B102	2	0.8524	1.7048
56	302012659, SMD CAP Ceramic 4.7uF-50V-10%-X7R;0805, A.1 (Design)	GRM21BZ71H475 KE15L	7	0.8524	5.9668
57	302012962, SMD CAP Ceramic 10nF-100V-10%-X7R;0603, A.2 (Design)	CC0603KRX7R0B B103	2	0.8524	1.7048
58	302013246, SMD CAP Ceramic 470nF-50V-10%-X5R;0603, A.1 (Design)	CC0603KRX5R9B B474	3	0.8524	2.5572
59	302013249, SMD CAP Ceramic 1uF-10V-10%-X5R;0402, A.1 (Design)	CL05A105KP5NN NC	12	0.8524	10.2288
60	302013268, SMD CAP Ceramic 22uF-35V-20%-X5R;1210, A.1 (Design)	GMK325BJ226MM -P	5	0.8524	4.262



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
61	302020569, SMD CAP Tantalum 330uF-6.3V-20%-0.08R;C-6032, A.2 (Design)	CA55-C6R3M337T E080	7	0.8524	5.9668
62	302031185, SMD CAP Aluminum 220uF-50V;SMD-D10*H10.5mm, A.2 (Design)	VD1H221MG1050 00CE0	2	0.8524	1.7048
63	303010925, SMD Inductor 1uH-20%;L2.0*W1.6*H1.0mm, A.3 (Design)	WPN201610H1R0 MT	1	1.069	1.069
64	303011145, SMD Inductor 1nH-0.3nH-300mA;0402, A.3 (Design)	LQG15HN1N0S02 D	1	1.069	1.069
65	303011409, SMD Inductor 6.8uH-20%-1.5A;L4.0xW4.0xH2.6m m, A.3 (Design)	SWPA4026S6R8M T	1	1.069	1.069
66	303011669, SMD Inductor 3.3uH-20%-3.3A;2P-L4.2*W4.4*H1. 8mm, A.2 (Design)	MWSA0402S-3R3 MT	4	1.069	4.276
67	303011722, SMD Inductor;4.0nH±0.1nH-0.4R-5.3GH z-350mA;0201, A.2 (Design)	LQP03TN4N0B02 D	8	1.069	8.552
68	303011796, SMD Inductor;4.7uH-20%-13.1mR-15A-1 4A;L8.8*W8.3*H4.8mm, A.2 (Design)	CSEB0850-4R7M	2	1.069	2.138
69	303030024, SMD Ferrite Bead;120R-2A;0603, A.4 (Design)	BLM18PG121SN1 D	13	0.1345	1.7485
70	303050063, SMD Common Mode Filter 90R-400mA;4P-L2.0*W1.2*H1.4m, A.2 (Design)	SRF2012-900YA	2	0.1345	0.269
71	303050383, SMD Common Mode Filter;3200R-0.65A;4P-L8.7*W10*H 6.5mm, A.4 (Design)	CSTCB1060R-302	1	0.1345	0.1345
72	303050503, DIP Common Mode Chokes 2mH@1KHz-10% 6A 600V ;4P-D20*H18mm, A.2 (Design)	PDMCAT16128-20 2ML	1	0.1849	0.1849



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
73	303050504, SMD Common Mode Chokes 1.4k@100MHz 1.9A-50V;4P-L4.75*W4.5*H2mm, A.2 (Design)	PCAQ4520MB-142	3	2.858	8.574
74	304010714, SMD Diode 40V-2A; PowerDI™ 123, A.3 (Design)	DFLS240L-7	2	0.5319	1.0638
75	304020022, SMD Diode Schottky 30V-1A;SOD-323F, A.2 (Design)	PMEG3010CEJ,115	16	13.1134	209.8144
76	304030489, SMD Diode Zener 43V-500MW;SOD-123, A.2 (Design)	MMSZ5260BT1G	4	116.0546	464.2184
77	304030509, SMD Diode Zener 3.3V-500mW;SOD-123, A.2 (Design)	MMSZ3V3T1G	2	116.0546	232.1092
78	304030710, SMD Diode Zener 5.6V-500mW;SOD-123, A.3 (Design)	MMSZ5232BT1G	1	116.0546	116.0546
79	304030711, SMD Diode Zener;27V-26.46V to 27.54V-500mW;SOD-123, A.2 (Design)	MMSZ5254A_R1_00001	1	116.0546	116.0546
80	304040003, SMD Diode Switching 75V-150mA;SOD-323, A.3 (Design)	1N4148WS.	2	5.5448	11.0896
81	304050009, SMD Diode TVS 16VWM 26V;SMB, A.2 (Design)	SMBJ16CA	6	1.0638	6.3828
82	304050312, SMD Diode ESD 5.5V-6V-12pF-30KV-30KV;X1SON(2), A.2 (Design)	TPD1E10B06DPYR	25	5.5448	138.62
83	304050905, SMD Diode TVS 26V 1.5KW Bidirectional;SMC, A.2 (Design)	SMCJ26CA	1	1.0638	1.0638
84	304050907, SMD Gas Discharge Tube 90V 20KA 2 Electrodes;D8.3*L6.0mm, A.2 (Design)	2RP090M-8-S	1	580.2734	580.2734
85	304050978, SMD Diode TVS-58VWM-93.6V;DO-214AA(SMB), A.2 (Design)	SMBJ58CA	3	1.0638	3.1914



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
86	304051142, SMD Diode TVS 13V 1.5KW Bidirectional;SMC, A.2 (Design)	SMCJ13CA	2	1.0638	2.1276
87	304060074, SMD Diode ESD 0.05pF;0402, A.3 (Design)	ESDPSA0402V05	30	5.5448	166.344
88	304060294, SMD Diode Array ESD;4 Channel,6 Gbps,5.5V;USON-10, A.4 (Design)	TPD4E05U06DQAR	4	8.9722	35.8888
89	304060395, SMD Diode Array ESD;4 Channel,0.25pF,3.6V,10Gbps;USO N-10, A.2 (Design)	TPD4E02B04DQAR	7	8.9722	62.8054
90	304090043, SMD LED Clear-Green;LED-0603, C.2 (Design)	19-217/G7C-AN1P 2/6T	2	0.5319	1.0638
91	304091968, DIP LED;Yellow Green+Red;4P-2.54-11.5*9.65*4.3 mm, A.2 (Design)	A694B/SYGSUR/S 530-A3	1	0.5319	0.5319
92	305010564, SMD Transistor NPN 80V-1A;SOT-223, A.2 (Design)	BCP56-10T1G	4	2.8529	11.4116
93	305010705, SMD Transistors NPN 40V-200mA-200mW;SOT-323, A.2 (Design)	MMST3904-7-F	2	2.8529	5.7058
94	305020002, SMD Transistors PNP 40V-200mA;SOT-23, A.2 (Design)	MMBT3906LT3G	1	2.8529	2.8529
95	305020497, SMD MOSFET P-CH 60V-70A;PDFNWB5*6-8L, A.2 (Design)	CJAC70P06	2	5.5448	11.0896
96	305030012, SMD MOSFET P-CH 50V-130mA;SOT-323, A.2 (Design)	BSS84W-7-F	1	5.5448	5.5448
97	305030799, SMD OptoMOS;4SOP, A.3 (Design)	CPC1017NTR	1	7.8862	7.8862
98	305031179, SMD MOSFET P-CH 30V-12A;HSMT8, A.2 (Design)	RQ3E120ATTB	1	5.5448	5.5448
99	305031301, SMD MOSFET N-CH;30V-50A,11.8 mOhm;VSON 3.3*3.3mm, A.2 (Design)	CSD17308Q3	2	5.5448	11.0896



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
100	305031302, SMD MOSFET N-CH;30V-60A,3.2 mOhm;VSON 3.3*3.3mm, A.3 (Design)	CSD17575Q3	2	5.5448	11.0896
101	305031465, SMD MOSFET N-CH;built-in ESD,Vgs =20V,Vds=30V,100mA;SOT-323, A.3 (Design)	2SK3018	23	5.5448	127.5304
102	305031480, SMD MOSFET N-CH;built-in ESD,Vds=20V,Vgs =12V,Vgs(th)=0.35V-1.1V,0.75A;S OT-323, A.2 (Design)	CJ3134KW	3	5.5448	16.6344
103	306011268, SMD Crystal 25MHz-12pF-10ppm-30ppm-50R;4 P-SMD-L3.2*W2.5*H0.8mm, A.2 (Design)	5YAA25000121TF 50Q3	2	13	26
104	306011385, SMD Crystal 12MHz-10pF-10ppm-100R;4P-SMD -L3.2*W2.5*H0.8mm, A.2 (Design)	5YAA12000101TF A0Q3	1	13	13
105	306020781, SMD Oscillator;32.768KHz-3.3V-30ppm; SMD-3225-4P-L3.2*W2.5*H1.1mm, A.2 (Design)	1631-L3273-BTBQ YA	1	13	13
106	307010738, SMD PPTC 500mA-1A-60V;1812, A.2 (Design)	JK-MSMD050-60	4	0.4	1.6
107	307020350, SMD Fuseholder with Fuse-5A;2P-L9.73*W5.03*H3.81m m, A.5 (Design)	6125(H).24T15002 00J	1	0.4	0.4
108	310011401, SMD IC MCU;Dual Cortex M0+;133Mhz;QFN-56-2022 (含)年以后, A.4 (Design)	RP2040	1	425.5836	425.5836
109	310030161, SMD IC PMIC;DFN(2*2)-8, B.2 (Design)	ETA3410D2I-T	1	412.1251	412.1251
110	310030260, SMD IC PMIC;SOT23-5, A.1 (Design)	SY6280AAC	3	325.9974	977.9922
111	310031538, SMD IC PMIC;Reset Circuit;2.63V VTH RST;SOT143, A.2 (Design)	UM805RE	1	403.2942	403.2942



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
112	310032333, DIP Isolated DCDC;5V to 5V,1500VDC/min,0.75W,Regulator; 4P-2.54mm-L11.60*W6.00*H10.16 mm, A.2 (Design)	IB0505S-W75R3	1	519.8294	519.8294
113	310032514, SMD IC PMIC;Power Switch,Single Channel,2.5V to 5.5V,2.1A,Active High;SOT23-5, A.2 (Design)	SGM2588CYN5G/ TR	2	425.5256	851.0512
114	310032529, SMD IC PMIC;LDO-1.8V-500mA;SOT23-5, A.3 (Design)	LC1458CB5TR18	1	408.2157	408.2157
115	310032530, SMD IC PMIC;LDO-3.3V-500mA;SOT23-5, A.3 (Design)	LC1458CB5TR33	1	408.2157	408.2157
116	310032622, SMD IC DCDC;Synchronous Buck Controller,External Switch,4V to 60V Input;QFN-20 (3mmx4mm), A.2 (Design)	MP9928GL-Z	2	400.0634	800.1268
117	310050024, SMD IC Logic;TSSOP-20, A.3 (Design)	TXB0108PWR	1	401.3684	401.3684
118	310050025, SMD IC Logic;TSSOP-14, A.2 (Design)	TXB0104PWR	1	388.5822	388.5822
119	310050099, SMD IC Logic;TSSOP-14, A.2 (Design)	TXS0104EPWR	1	388.5822	388.5822
120	310050347, SMD IC Logic;SOT-6, A.2 (Design)	SN74LVC1T45DR LR	1	432.1313	432.1313
121	310050830, SMD IC Logic;TSSOP-5, A.2 (Design)	74LVC1G07GW	3	511.4854	1534.4562
122	310051190, SMD IC Logic;Buffer, Non-Inverting 1 Element 1 Bit per Element 3-State Output SOT-23-5, A.2 (Design)	SN74LV1T125DBV R	4	402.1597	1608.6388
123	310051411, SMD IC Logic;2-Bit Bidirectional Voltage-Level Translator;X2SON-8, A.2 (Design)	TXB0302DQMR	1	438.9527	438.9527



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
124	310051412, SMD IC Logic;Digital Isolators,2+2 Channels,1.71 V to 1.89 V and 2.25 V to 5.5 V;SOIC (16), A.2 (Design)	ISO6742DWR	1	459.1959	459.1959
125	310070986, SMD IC Interface;QFN-24, A.2 (Design)	CP2102N-A02-GQFN24R	1	402.3599	402.3599
126	310071436, SMD IC Interface CAN Transceiver;SOIC-16, A.3 (Design)	TPT71044-SOBR	1	402.6912	402.6912
127	310071437, SMD IC Interface;4-port 5-Gbps SuperSpeed USB 3.0 Hub;VQFN-56, A.2 (Design)	USB5744T-I/2G	1	512.2357	512.2357
128	310071438, SMD IC Interface;PCIe to Gigabit Ethernet Controller with Integrated Ethernet MAC/PHY;48-SQFN, A.2 (Design)	LAN7430-I/Y9X	1	402.5938	402.5938
129	310071439, SMD IC Interface;Single 3.3V or 5V RS232/RS422/RS485 Multiprotocol Transceiver;TQFN40L 5*5, A.2 (Design)	F81439N	1	510.3904	510.3904
130	310071440, SMD IC Interface;16-bit 2.3V to 5.5V I2C I/O expander with interrupt & config registers;VQFN(24), A.2 (Design)	PCA9535RGER	1	535.4924	535.4924
131	310090011, SMD IC Memory;EEPROM Memory IC 256Kb (32768 x 8)-SOIC-8(3.9mm), A.2 (Design)	AT24C256C-SSHL-T	1	407.5984	407.5984
132	310091344, SMD IC NOR Flash;Dual and Quad SPI,4M-bit,2.7-3.6V;SOIC-8(150mil), A.2 (Design)	GD25Q40ETIGR	1	501.7477	501.7477
133	310100627, SMD IC Analog Switch;High Speed USB 2.0 (480Mbps) DPDT Analog Switch;WQFN-10, A.2 (Design)	SGM7222YWQ10/TR	4	529.7194	2118.8776
134	310990465, SMD IC OPTOISOLATOR;4SOP, A.2 (Design)	SFH690BT3	8	324.1588	2593.2704



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
135	311021382, DIP Button Side 1.57N;4P-90D, A.2 (Design)	SKQJLBA010	2	1.9487	3.8974
136	311080506, SMD Top DIP Switches;2*4P-L6.66*W8.3*H2.35mm, A.2 (Design)	SP-04P	1	1.9487	1.9487
137	314130227, SMD Varistor DC30V-AC25V-30A-0.1J-72V;0805, A.2 (Design)	V30MLA0805LNT	4	1.3468	5.3872
138	314130267, DIP RES Varistor ,820K 18V-1800V;2P-7.5-L14*W2.1*H14.5 mm, A.2 (Design)	820KD14	2	1.3468	2.6936
139	317990927, DIP PoE module;PSE,Input 12V to 24V,Output 52V,30W,6P-2.54mm-L60*W20*H16.8mm, A.2 (Design)	WC-PSE12-52V	1	8.6167	8.6167
140	319015640, PCB;reComputer Industrial J201_V1.2-黑油白字-6 层, A.3 (Design)	/	1	3.68	3.68
141	320011178, DIP Female USB Type A; USB3.0 R-A ;9+2P, A.2 (Design)	UEA1112C-4HK1-4H	1	63.6424	63.6424
142	320011199, SMD USB Type-C;USB2.0 Only,12P+4P-8.94*8.3*3.26mm, A.2 (Design)	UBF31-0171L	2	63.6424	127.2848
143	320011342, DIP USB-A,Stacked USB 3.0-R/A;18+4P, A.3 (Design)	USB-2A-01-3.0	1	63.6424	63.6424
144	320020839, DIP Beige Male Header VERT;1*2P-1.25MM, A.4 (Design)	WY-3739	1	1.7358	1.7358
145	320021938, DIP Black Male Header VERT;2*10P-2.54-2.5-6.0-3.0mm-90D, A.2 (Design)	PST-PH-254-0100-2*10P	1	17.358	17.358
146	320021939, SMD Black Male Header VERT;With Positioning,Without Pin14;2*7P-1.27-5.5-4.0mm, A.2 (Design)	SF-PH-127-0030-2*7-K14-D	1	63.6424	63.6424



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
147	320060644, SMD FPC CONN;15P-1.0mm-90D, A.3 (Design)	YL002-009-015	2	13.0189	26.0378
148	320100250, SMD Nano-SIM Holder;7P+4-L13.5*W13.1*H1.50m m(自弾), B.2 (Design)	ST-SIM-SP132	1	6.0754	6.0754
149	320111670, DIP Male DB9 Connector;DB9-90D;9+2P, A.2 (Design)	DT10621-H7809-4 H	1	63.6424	63.6424
150	320111775, DIP JST Male Connector Black;4P-1.25MM, A.2 (Design)	1.25-4A-black	1	63.6424	63.6424
151	320111776, SMD Connector Black M.2 Key-M,PCIe Gen4.0,H=2.0mm,10u Gold Plating;67P-0.5mm, A.2 (Design)	2E0BC26-F20BM- 7H	1	2.8928	2.8928
152	320111877, SMD+DIP HDMI Connector;HDMI 2.1,Type A,Gold Flash;19+4P-L12.15*W15.00*H6.18 mm-90D, A.2 (Design)	QJA5311-LF34S-7 F	1	63.6424	63.6424
153	320111888, DIP PCB Connector;Terminal Block,Green,2x8Pin;3.81mm-90D, A.2 (Design)	YL032-096-016	1	13.8868	13.8868
154	320112030, DIP Female Screw Terminal-Green;1*2P-5.08-90D, A.3 (Design)	STP2EDGRM-X-5. 08-2P	1	63.6424	63.6424
155	320140597, DIP RJ45;1000M,Integrated Magnetics+PoE,G/Y 2 LEDs,Right Angle;18+2P-21.25*15.93*13.30m m, A.2 (Design)	LPJG4926-7HENL	1	63.6424	63.6424
156	320140598, DIP RJ45;1000M,Integrated Magnetics,G/Y 2 LEDs,Right Angle,Voltage Type;16+2P-21.25*15.93*13.3mm, A.2 (Design)	LPJG4933-7HENL	1	63.6424	63.6424



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
157	320170000, SMD Battery Cell Holder Plastic;CR1220-15*13*H4mm, B.2 (Design)	MTBA20-1220A0-0 5133	1	3.7607	3.7607
158	320210481, SMD BTB CONN Black m.2 B-key;67P-0.5mm;L21.9*W2.9*H8.5 mm, A.2 (Design)	2E0BC21-S85BB-7 H	1	2.8928	2.8928
159	320210501, SMD BTB CONN;Gold Flash-2*130P+2P-0.5mm-H=9.2mm -S=6.9mm-SODD4 9.2 STD, A.2 (Design)	ASAA821-EASB0- 7H	1	2.8928	2.8928
160	320991107, SMD Mini PCI-E CONN;52P-0.8mm-L29.9*9.08*4.0 mm, A.3 (Design)	ST-PC-002	1	3.7607	3.7607
161	326051030, SMD Stud; M3 铜柱, D5.56*0.3mm, 黄铜, 表面电镀锡(编带包装,带麦拉), A.2 (Design)	SMTSO3003CTJ	1	0	0
162	326051131, SMD Stud; M2.5 铜柱, D5.56*L6.5+D4.09*1.53mm, 无铅铜, 表面电镀锡(编带包装), A.2 (Design)	SMTSO2565CTJ-U L	2	0	0
163	326051132, SMD Stud; M2 铜柱, D5.56*1.5mm, 无铅铜, 表面电镀锡(编带包装), A.2 (Design)	SMTSO2015CTJ-U L	4	0	0
164	327133101, 空白贴纸;80g 铜版不干胶纸-10*10mm 双排-2500pcs 卷, A.2 (Design)	/	1	0	0
165	401040291, 胶水,硅橡胶,型号:KD-8405MBW,白色膏状,100ml, A.2 (Design)	/	1	0	0
166	206001531, reComputer Industrial_左挡板-镭雕, A.2 (Design)	/	1	0	0
167	323011231, reComputer Industrial_左挡板;铝 6063-155.0*30.0*17.5mm-喷砂氧化-丝印-黑色-48H, A.2 (Design)	/	1	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
168	206001532, reComputer Industrial_右挡板-镭雕, A.2 (Design)	/	1	0	0
169	323011232, reComputer Industrial_右挡板;铝 6063-155.0*30.0*17.5mm-喷砂氧化-丝印-黑色-48H, A.2 (Design)	/	1	0	0
170	206001533, reComputer Industrial_底壳-镭雕, A.2 (Design)	/	1	0	0
171	323030948, reComputer Industrial_底壳;SPCC-155.0*155.0*31.0mm-喷涂-丝印-黑色-48H, A.2 (Design)	/	1	0	0
172	206001536, reComputer Industrial-Orin_散热器-镭雕, A.2 (Design)	/	1	0	0
173	323011238, reComputer Industrial-Orin_散热器;铝 6063-155.0*155.0*22.5mm-喷砂氧化-黑色-48H, A.2 (Design)	/	1	0	0
174	206001540, reComputer Industrial_带电源包装组件, D.2 (Design)	/	1	0	0
175	327040006, Plastic Bag Green;W50*H70*0.12mm (双层厚度)-自封口, A.1 (Design)	/	1	0	0
176	327040014, Plastic Bag Clear;W100*H150*0.05mm-自封口-红边, A.1 (Design)	/	2	0	0
177	327111702, reComputer Industrial_纸盒;259*189*80MM-300G 优质牛卡+K9 (H230 110) 过光油, A.2 (Design)	/	1	0	0
178	327111703, 配件盒;182*72*55MM-300G 优质牛卡+K9 (H230 110), A.2 (Design)	/	1	0	0
179	327111704, 纸箱;K=K-340*275*220MM, B.1 (Design)	/	1	0	0
180	327122437, 平卡;K6K-320*265*3MM, A.2 (Design)	/	2	0	0
181	327130462, Label;不可移透明圆形贴纸-D30mm-高粘, A.2 (Design)	/	1	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
182	327131816, 空白标签;5000pcs 卷-5 列-耐高温 300 度-7*14mm, C.1 (Design)	/	1	0	0
183	327132226, Label;空白标签-铜版纸 不干胶-90*140mm-250pcs/卷, A.3 (Design)	/	1	0	0
184	327132997, 空白贴纸;75#合成纸贴 纸-36.7*10.7mm 单排-2500pcs 卷, A.2 (Design)	/	1	0	0
185	327133101, 空白贴纸;80g 铜版不干 胶纸-10*10mm 双排-2500pcs 卷, A.2 (Design)	/	1	0	0
186	327133163, Label;空白标 签;1000pcs 卷-1 列-50# PI 耐高温贴 纸-76*30mm, A.2 (Design)	/	1	0	0
187	327142009, 内托(上 盖);185*185*30MM-IXPE30B, A.2 (Design)	/	1	0	0
188	327142010, 内托(下 盖);185*185*30MM-IXPE30B, A.2 (Design)	/	1	0	0
189	327172034, 安全说明书;80G 书纸- 折叠款-80*80mm, A.2 (Design)	/	1	0	0
190	206001545, M. 2 NVME 2280 SSD 128G-外发烧录 reComputer Industrial J4012, C.2 (Design)	/	1	2140	2140
191	317990969, M. 2 NVME 2280 SSD 128G, A.3 (Design)	NHESR128GTLE W-I3C-2	1	2140	2140
192	313010036, Lithium-ion Battery;3V-40mAh;CR1220, A.4 (Design)	CR1220	1	46	46
193	313080684, Power Adapter;3P-Black-19V-4.74A; 梅花 口(不带 AC 电源线), A.3 (Design)	PA-1900-32I2	1	386.4	386.4
194	317990915, NVIDIA Jetson Orin NX Module 16GB, A.2 (Design)	900-13767-0000-0 00	1	5200	5200



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
195	320111889, Pluggable Terminal Block, Green; 2x8Pin 3.81mm, A.2 (Design)	YL032-098-016	1	63.6424	63.6424
196	320112031, Male Screw Terminal-Green; 1*2P-5.08, A.3 (Design)	STP2EDGM-X-5.0 8-2P	1	63.6424	63.6424
197	321050726, DC Power Pigtail Cable; Female-18AWG-L230mm-55 25-剥锡 4mm-Red/Black, A.2 (Design)	5525 母头连接线	1	2.8928	2.8928
198	322100782, 天线孔塞; 硅胶 -D10*H7.0mm-磨砂-黑色-60度 -1mm 壁厚, A.2 (Design)	/	4	0	0
199	322100786, 导热硅胶片; 14*14*2mm, 6W/M.K, A.3 (Design)	/	1	0	0
200	322100787, 导热硅脂; 安众 SZTG-40 系列-灰色-导热系数 4W/mk-1KG/瓶, A.2 (Design)	/	1	0	0
201	322991191, reComputer Industrial_ 导电棉-左; 导电棉-75.0*25.0*3.0mm-单面背导电胶-黑色, A.2 (Design)	/	1	0	0
202	322991192, reComputer Industrial_ 导电棉-右; 海绵+导电布 -85.0*25.0*3.0mm-单面背导电胶-黑色, A.2 (Design)	/	1	0	0
203	322991193, 导电棉; 62.0*4.5*0.3mm-单面背导电胶-黑色, A.2 (Design)	/	2	0	0
204	322991196, 脚垫; 硅橡胶-带铁垫 -11*9*6mm-黑色, A.2 (Design)	/	4	0	0
205	323011237, 工业 DIN 导轨卡扣; 铝 -48.0x30.0x9.0mm-黑色, A.2 (Design)	/	1	0	0
206	323030949, reComputer Industrial_ 安装挂板; SPCC-130.0*43.8*3.4mm-喷粉-绿色-48H, B.1 (Design)	/	2	0	0



Report No.:18290KC40023301

No.	Identifying	MPN code	Quantity	Failure rate	Total failure rate
207	323030950, reComputer Industrial Jetson_标识牌;SPCC-21.0*20.0*23.3mm-喷粉-绿色-48H, A.2 (Design)	/	1	0	0
208	326010872, Screw;十字圆头机牙螺丝_M2.5x6mm;碳钢镀镍;本色, A.3 (Design)	/	2	0	0
209	326020017, Screw;十字沉头机牙螺丝-120°头型-KM3xH5mm-铁-三价铬黑锌-耐落-黑色-48H, A.2 (Design)	/	12	0	0
210	326020442, Screw;十字扁头机牙螺丝-CM2xH3mm-头径 4.0mm 厚 0.5mm-铁-黑色, A.3 (Design)	/	2	0	0
211	326020683, Screw,十字机牙平头-碳钢-CM3*4.0mm-镀黑镍-耐落-12H, A.2 (Design)	/	3	0	0
212	326020684, Screw;十字圆头机牙螺丝-PM4.0*4.0mm-铁-锌镍合金-耐落-本色-48H, A.2 (Design)	/	1	0	0
213	326020685, Screw;十字沉头机牙螺丝-KM3*H32mm-铁-三价铬黑锌-耐落-黑色-48H, A.2 (Design)	/	4	0	0
214	326051065, Stud,滚花螺栓-M3*+6.5mm+M2*2.0mm-铜镀镍-银色, A.2 (Design)	/	1	0	0
215	327133265, reComputer Industrial J4012_背部贴纸;80g 铜版不干胶贴纸+哑膜-160*110mm, A.2 (Design)	/	1	0	0





End of Report