



## Enterprise Computing: Exercise 7 – Benchmarking II

Marco Peise, Stefan Tai

# Agenda

## Exercise 7 Benchmarking II – BenchFoundry

## Exercise 7

# Task 1

Name four relevant reasons why benchmarks such as TPC, OLTPBench, YCSB or YCSB++ are not optimal for benchmarking cloud database systems or cloud database services.

.

# Task 2 BenchFoundry

## BenchFoundry: A Benchmarking Framework for Cloud Database Services

David Bermbach and Jörn Kuhlenkamp  
*Information Systems Engineering Research Group*  
*TU Berlin*  
*Berlin, Germany*  
*Email: {db,jk}@ise.tu-berlin.de*

Akon Dey  
*Awake Networks Inc.*  
*Mountain View, California, USA*  
*Email: akon@awakenetworks.com*

**Abstract**—Understanding quality of cloud database systems and services is often crucial. However, current cloud database benchmarks either come without an implementation, have strong disadvantages, or can only be used with relational database systems and services.


In this paper, we present BenchFoundry which is not a benchmark itself but rather is a benchmarking framework that can execute arbitrary application-driven benchmark workloads in a distributed deployment while measuring multiple qualities at the same time. BenchFoundry can be used or extended for every kind of OLTP database system or service. Specifically, BenchFoundry is the first system where workload specifications become mere configuration files instead of code. In our design, we have put special emphasis on ease-of-use

actually implemented. Other approaches, e.g., YCSB [2] or YCSB++ [3] are essentially micro-benchmarks. While these are useful for understanding how tiny changes in workloads affect system quality or for testing isolated database features, they are not a good fit for use cases such as selecting or optimizing the configuration of a database system since micro-benchmarks rarely mimic application workloads realistically. Other criteria where existing approaches are lacking are aspects like extensibility in terms of workloads, multi-quality measurements, (geo-)distribution support of the benchmark out of the box, fine-grained result collection, or ease-of-use. We will discuss requirements for modern benchmarks in detail and give an overview of related work in section 2.

### References:

- <https://github.com/dbermbach/BenchFoundry>
- D. Bermbach, J. Kuhlenkamp, A. Dey "BenchFoundry: A Benchmarking Framework for Cloud Database Services ", to appear , 2017


# BenchFoundry



## References:


- <https://github.com/dbermbach/BenchFoundry>
- D. Bermbach, J. Kuhlenskamp, A. Dey "BenchFoundry: A Benchmarking Framework for Cloud Database Services ", to appear , 2017

# BenchFoundry



## References:

- <https://github.com/dbermbach/BenchFoundry>
- D. Bermbach, J. Kuhlenskamp, A. Dey "BenchFoundry: A Benchmarking Framework for Cloud Database Services ", to appear , 2017




## References:

- <https://github.com/dbermbach/BenchFoundry>
- D. Bermbach, J. Kühlenkamp, A. Dey "BenchFoundry: A Benchmarking Framework for Cloud Database Services ", to appear , 2017



## Setup BenchFoundry with MariaDB



## # install & configure 5 t2.micro instances

1. Create 5 t2.micro instances which are reachable from any TCP Port outside of AWS
2. Update the Operating System (sudo apt-get update, sudo apt-get upgrade)
3. OPTIONAL: Install Thrift compiler (sudo apt-get install thrift-compiler) if you want to build the original BF
4. OPTIONAL: Install Maven (sudo apt-get install maven) if you want to build the original BF
5. Install Java (sudo apt-get install default-jre, sudo apt-get install default-jdk)

## # download tar for current BenchFoundry on each micro instance

Original from: <https://github.com/dbermbach/BenchFoundry>

Already build: <https://github.com/marcopeise/BenchFoundry>

On Master instance edit:

1. benchfoundry.properties and slaves.properties

## # install & configure MariaDB for your t2.medium instance

1. <https://mariadb.com/> (sudo apt-get install mariadb-server)
2. Create User “benchfoundry” with password “benchfoundry” and grant privileges on the SQL command line:

```
CREATE USER 'benchfoundry'@'%' IDENTIFIED BY 'benchfoundry';  
GRANT ALL PRIVILEGES ON *.* TO 'benchfoundry'@'%' WITH GRANT OPTION;
```

```
[MariaDB [(none)]> CREATE USER 'benchfoundry'@'%' IDENTIFIED BY 'benchfoundry';  
Query OK, 0 rows affected (0.00 sec)  
  
[MariaDB [(none)]> GRANT ALL PRIVILEGES ON *.* TO 'benchfoundry'@'%' WITH GRANT OPTION;  
Query OK, 0 rows affected (0.00 sec)
```

3. Create a Database called “test” with the SQL command line
4. Make DB available to the clients (/etc/mysql/mariadb.conf.d/50-server.cnf -> comment out bind-address)

## # download Dbeaver for your local client

<http://dbeaver.jkiss.org/>

## # run Master & Slave instances

On **each Slave** start BenchFoundry:

```
java -jar target/BenchFoundry-1.0-SNAPSHOT-jar-with-dependencies.jar <port>
```

(should correlate with slaves.properties on Master Instance)

On the **Master** instance start BenchFoundry:

```
java -jar target/BenchFoundry-1.0-SNAPSHOT-jar-with-dependencies.jar benchfoundry.properties
```

## # analyse the outcome