

Machine Learning 1 Homework 07 Theory Part

15.12.2015

The object function is:

$$Q(\theta, \theta^{old}) = \sum_{z \in \{heads, tails\}^N} P(Z = z | \mathcal{X} = x, \theta^{old}) \log P(\mathcal{X} = x, Z = z | \theta)$$

$$= \sum_{z \in \{heads, tails\}^N} P(Z = z | \mathcal{X} = x, \theta^{old}) \sum_{i=1}^N \left(\log P(Z = z^{(i)} | \theta) + \sum_{j=1}^m \log P(X_j = x_j^{(i)} | Z = z^{(i)}, \theta) \right)$$

We also know that:

$$\sum_{i=1}^N \left(\log P(Z = z^{(i)} | \theta) + \sum_{j=1}^m \log P(X_j = x_j^{(i)} | Z = z^{(i)}, \theta) \right)$$

$$= \sum_{zishead} [\log \lambda + h(x_i) \log p_1 + t(x_i) \log(1 - p_1)] + \sum_{zishead} [\log(1 - \lambda) + h(x_i) \log p_2 + t(x_i) \log(1 - p_2)]$$

$h(x_i)$ is the number of heads when tossing coin M times, $t(x_i)$ is the number when tossing hcoin M times. Of course that $h(x_i) + t(x_i) = M$

maximize this, we get:

$$\hat{\lambda} = \frac{1}{N} \sum_{i=1}^N R_1(i)$$

$$\hat{p}_1^{new} = \frac{\sum_{i=1}^N R_1(i) h(x_i)}{M \sum_{i=1}^N R_1(i)}$$

$$\hat{p}_2^{new} = \frac{\sum_{i=1}^N R_2(i) h(x_i)}{M \sum_{i=1}^N R_2(i)}$$

where:

$$\theta^{old} = (\lambda, p_1, p_2)$$

$$R_1(i) = \frac{\lambda p_1^{h(x_i)} (1 - p_1)^{t(x_i)}}{\lambda p_1^{h(x_i)} (1 - p_1)^{t(x_i)} + (1 - \lambda) p_2^{h(x_i)} (1 - p_2)^{t(x_i)}}$$

$$R_2(i) = \frac{\lambda p_2^{h(x_i)} (1 - p_2)^{t(x_i)}}{\lambda p_1^{h(x_i)} (1 - p_1)^{t(x_i)} + (1 - \lambda) p_2^{h(x_i)} (1 - p_2)^{t(x_i)}}$$