TestLink

Requirements Specification Document

Test Project: UniShare

Printed by TestLink on 26/10/2026

2026 Group UniShare

Table Of Contents

1. SRS-P-CHAT : UC-S3-011/012/013/019/020 Chat with AI Assistant

REQ-P-CHAT-01 : Only approved, logged-in students use the AI assistant

REQ-P-CHAT-02 : Message validation

REQ-P-CHAT-03 : New conversation is created on first message

REQ-P-CHAT-04 : Streaming response and persistence

REQ-P-CHAT-05 : Continue a previous conversation

REQ-P-CHAT-06 : Conversation history sidebar

REQ-P-CHAT-07 : Delete a conversation

REQ-P-CHAT-08 : Conversation privacy

REQ-P-CHAT-09 : AI unavailable handling

1. Requirements Spec.: SRS-P-CHAT : UC-S3-011/012/013/019/020 Chat with AI Assistant	
revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (9/0)
Student chats with the AI tutor, keeps a conversation history, continues and deletes conversations. Source: UniShare_Iteration_3.md AI Learning Assistant Use Case, Sequence 2, Use Case 2 (UC-S3-012); src/app/(student)/ai/[[...id]]/page.tsx, src/components/ai/ai-chat-interface.tsx, conversation-history-sidebar.tsx, src/app/api/chat/route.ts, src/server/api/routers/ai.ts.	

Requirement: REQ-P-CHAT-01 : Only approved, logged-in students use the AI assistant	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The /ai page shall be available only to authenticated users with role APPROVED; a PENDING user is redirected to /waiting-approval. POST /api/chat without a session returns 401 'Unauthorized'.	
Related Test Cases	US-46 : Chat access without approval, session or conversation id [Version :1]

Requirement: REQ-P-CHAT-02 : Message validation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
A message shall not be empty (whitespace only counts as empty; the Send button stays disabled and nothing is sent) and shall be at most 5000 characters ('Message must be under 5000 characters', Iteration 3 A2). Implementation note: tRPC ai.sendMessage accepts 1-10000 characters.	
Related Test Cases	US-43 : Empty and whitespace-only message is not sent [Version :1]US-44 : Message length boundaries (4999, 5000, 5001 characters) [Version :1]

Requirement: REQ-P-CHAT-03 : New conversation is created on first message	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Sending the first message in a new chat creates an AiConversation owned by the user with the client-generated id, temperature 0-2 (default 0.7) and an AI-generated title of at most 6 words (fallback: first 50 characters of the message). The URL changes to /ai/<id> and the conversation appears at the top of the sidebar. A request without conversationId returns 400 'No conversation ID provided'.	
Related Test Cases	US-42 : Start a new AI conversation (main flow) [Version :1]US-46 : Chat access without approval, session or conversation id [Version :1]US-49 : New Chat and untitled conversation [Version :1]

Requirement: REQ-P-CHAT-04 : Streaming response and persistence	
Version :	1

revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The AI answer (model badge 'Gemini 2.5 Flash') streams into the chat while a loader is shown; input submission is disabled while status is submitted/streaming. When the stream finishes the user and assistant messages are saved (assistant message with tokensUsed) and the conversation updatedAt is set.	
Related Test Cases	US-42 : Start a new AI conversation (main flow) [Version :1]US-45 : Continue a previous conversation with context [Version :1]

Requirement: REQ-P-CHAT-05 : Continue a previous conversation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Opening /ai/<id> loads all messages of that conversation oldest first; a follow-up message is answered with the earlier messages as context and is appended to the same conversation.	
Related Test Cases	US-45 : Continue a previous conversation with context [Version :1]

Requirement: REQ-P-CHAT-06 : Conversation history sidebar	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The sidebar lists only the user's conversations, most recently updated first, 5 at a time; 'Load More' adds 10 more and the footer shows 'Showing <n> of <total>'. A conversation without title shows 'Untitled Chat'. 'New Chat' opens an empty chat at /ai. API page size 1-100.	
Related Test Cases	US-48 : Sidebar paging boundaries (5, 6 and 16 conversations) [Version :1]US-49 : New Chat and untitled conversation [Version :1]

Requirement: REQ-P-CHAT-07 : Delete a conversation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The delete icon asks 'Delete this conversation? This action cannot be undone.'; on OK the conversation and all its messages are deleted (cascade) and it disappears from the sidebar; on Cancel nothing changes.	
Related Test Cases	US-50 : Delete conversation - confirm and cancel [Version :1]

Requirement: REQ-P-CHAT-08 : Conversation privacy	
Version :	1
revision:	1
Author:	admin

Status	Valid
Type	Use Case
Coverage	100% (1/1)
A user can read, continue or delete only his own conversations. Another user's conversation id gives NOT_FOUND 'Conversation not found' (Iteration 3 A3: no access to other users' conversations).	
Related Test Cases	US-51 : User cannot read, continue or delete another user's conversation [Version :1]

Requirement: REQ-P-CHAT-09 : AI unavailable handling	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
If the AI server cannot be reached the chat shows 'Unable to connect to AI server. Please make sure Ollama is running.'; a server-side failure returns 500 'Failed to process AI request'. The user message is kept and the student can retry.	
Related Test Cases	US-47 : AI server unavailable [Version :1]

TestLink

Requirements Specification Document

Test Project: UniShare

2026 Group UniShare

Table Of Contents

1. SRS-P-QUIZ : UC-S3-014/015 Generate and Attempt AI Quiz

REQ-P-QUIZ-01 : Quiz generation form and limits

REQ-P-QUIZ-02 : At least one question type

REQ-P-QUIZ-03 : Course / note context access

REQ-P-QUIZ-04 : Successful generation is saved

REQ-P-QUIZ-05 : Taking a quiz

REQ-P-QUIZ-06 : Automatic grading and score

REQ-P-QUIZ-07 : Quiz list and repeated attempts

REQ-P-QUIZ-08 : Quiz ownership and delete

1. Requirements Spec.: SRS-P-QUIZ : UC-S3-014/015 Generate and Attempt AI Quiz

revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (8/0)

Student generates a practice quiz with AI for a course and attempts it with automatic grading. Source: UniShare_Iteration_3.md Sequence 3, Use Case 3 (UC-S3-014), UC-S3-015; src/server/api/routers/ai.ts (generateQuiz, getQuizzes, getQuiz, submitQuizAttempt, deleteQuiz); src/server/ai/quiz-generator.ts; src/components/ai/quiz-generator-form.tsx, quiz-taker.tsx, quiz-results.tsx, quiz-list.tsx; course page tab 'Quizzes'.

Requirement: REQ-P-QUIZ-01 : Quiz generation form and limits	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Course > Quizzes > Generate Quiz shows Topic * (required, trimmed; empty gives 'Please enter a topic'), Number of Questions slider 5-50 in steps of 5 (default 10), Difficulty Easy/Medium/Hard (default Medium) and Question Types Multiple Choice, True/False (checked by default) and Short Answer. The API accepts questionCount 1-50 and difficulty easy|medium|hard.	
Related Test Cases	US-52 : Generate a quiz for own course (main flow) [Version :1]US-53 : Topic is required [Version :1]US-55 : Question count boundaries [Version :1]US-56 : Difficulty and question type partitions [Version :1]

Requirement: REQ-P-QUIZ-02 : At least one question type	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Submitting with no question type checked shows 'Please select at least one question type' and no quiz is generated.	
Related Test Cases	US-54 : No question type selected [Version :1]

Requirement: REQ-P-QUIZ-03 : Course / note context access	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
A quiz may be generated for a course or note only by the course owner or an ACCEPTED collaborator. Unknown course: 'Course not found'; no access: 'You don't have access to this course'. Unknown note: 'Note not found'; no access: 'You don't have access to this note'.	
Related Test Cases	US-57 : Quiz generation access by course relation [Version :1]

Requirement: REQ-P-QUIZ-04 : Successful generation is saved	
Version :	1
revision:	1

Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
On success the quiz and its questions (in generated order) are stored for the user with the topic as prompt and token usage, toast 'Quiz generated successfully!' is shown and the quiz opens for taking. While generating, the form is disabled and the button shows 'Generating...'. If the AI answer is not valid quiz JSON the error 'Failed to generate quiz. The AI response was not in the expected format.' is shown and nothing is saved.	
Related Test Cases	US-52 : Generate a quiz for own course (main flow) [Version :1]US-58 : Invalid AI response is not saved [Version :1]

Requirement: REQ-P-QUIZ-05 : Taking a quiz	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The quiz taker shows '<answered> of <total> answered', '<p>% complete', one button per question, Previous (disabled on question 1), Next, and on the last question 'Submit Quiz', which stays disabled until every question is answered ('Please answer all questions before submitting'). Multiple choice shows the generated options, True/False shows True and False, Short Answer shows 'Type your answer here...'.	
Related Test Cases	US-56 : Difficulty and question type partitions [Version :1]US-59 : Submit is enabled only when all questions are answered [Version :1]

Requirement: REQ-P-QUIZ-06 : Automatic grading and score	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Multiple choice and True/False answers are correct only on exact match with the stored correct answer; Short Answer is compared trimmed and case-insensitive. Score = correct / total questions x 100. The attempt is saved with completedAt. Results show the score with message: >=90 'Excellent!', >=80 'Great job!', >=70 'Good work!', >=60 'Not bad!', otherwise 'Keep studying!'.	
Related Test Cases	US-60 : Score bands on the results page [Version :1]US-61 : Answer matching rules per question type [Version :1]US-62 : Attempt is saved, best score and retake [Version :1]

Requirement: REQ-P-QUIZ-07 : Quiz list and repeated attempts	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The Quizzes tab lists the user's quizzes for the course newest first with 'Best Score: <n>%'; with none it shows 'No quizzes yet'. A quiz can be attempted any number of times ('Retake Quiz'); every attempt is kept.	
Related Test Cases	US-62 : Attempt is saved, best score and retake [Version :1]US-64 : Delete own quiz [Version :1]

Requirement: REQ-P-QUIZ-08 : Quiz ownership and delete	
Version :	1

revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Only the creator can open, attempt or delete a quiz; otherwise 'Quiz not found'. Delete asks 'Are you sure you want to delete this quiz? This action cannot be undone.' and removes the quiz with its questions and attempts.	
Related Test Cases	US-63 : Another user's quiz cannot be opened, attempted or deleted [Version :1]US-64 : Delete own quiz [Version :1]

TestLink

Requirements Specification Document

Test Project: UniShare

Table Of Contents

1. SRS-P-PLAN : UC-S3-016/017 Generate and Track AI Study Plan

REQ-P-PLAN-01 : Study plan form and limits

REQ-P-PLAN-02 : Course access for study plans

REQ-P-PLAN-03 : Generated plan is saved with weeks and tasks

REQ-P-PLAN-04 : Track progress

REQ-P-PLAN-05 : Plan ownership and delete

REQ-P-PLAN-06 : Plan kept when the course is deleted

1. Requirements Spec.: SRS-P-PLAN : UC-S3-016/017 Generate and Track AI Study Plan

revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (6/0)

Student generates a weekly study plan for a course and tracks task completion. Source: UniShare_Iteration_3.md Sequence 4, UC-S3-016, UC-S3-017, Data Description 'Study Plan Generation'; src/server/api/routers/ai.ts (generateStudyPlan, getStudyPlans, updateStudyPlanTask, deleteStudyPlan); src/server/ai/study-plan-generator.ts; src/components/ai/study-plan-generator-form.tsx, study-plan-viewer.tsx, study-plan-list.tsx; prisma/schema.prisma (AiStudyPlan).

Requirement: REQ-P-PLAN-01 : Study plan form and limits	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Generate Study Plan requires a course ('Please select a course'); Number of Weeks 1-16 (default 4; Iteration 3 states 1-12), Hours Per Week 1-40 (default 5), Learning Goal (Optional) and Target Deadline (Optional, dates before today cannot be picked). Values outside the ranges are rejected by the API.	
Related Test Cases	US-65 : Generate a study plan (main flow) [Version :1]US-66 : Weeks and hours boundaries [Version :1]US-67 : Course is required and deadline cannot be in the past [Version :1]

Requirement: REQ-P-PLAN-02 : Course access for study plans	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Only the course owner or an ACCEPTED collaborator can generate a plan for a course. Unknown course: 'Course not found'; no access: 'You don't have access to this course'.	
Related Test Cases	US-68 : Study plan access by course relation [Version :1]

Requirement: REQ-P-PLAN-03 : Generated plan is saved with weeks and tasks	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
On success the plan is saved with its weeks (ordered by week number) and tasks (in order), toast 'Study plan generated successfully!' is shown. Without goal the stored prompt is 'Study plan for course'. With a deadline endDate = deadline and startDate = deadline - weeks x 7 days. Invalid AI JSON gives 'Failed to generate study plan. The AI response was not in the expected format.'	
Related Test Cases	US-65 : Generate a study plan (main flow) [Version :1]US-67 : Course is required and deadline cannot be in the past [Version :1]

Requirement: REQ-P-PLAN-04 : Track progress

Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Ticking a task marks it completed (completedAt set, toast 'Task updated'); unticking clears completedAt. Overall Progress = completed tasks / all tasks x 100 (rounded, 0% when there are no tasks) and every week shows its Week Progress; a week at 100% is shown as complete.	
Related Test Cases	US-69 : Track task completion and progress [Version :1]

Requirement: REQ-P-PLAN-05 : Plan ownership and delete	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Only the owner of a plan can update its tasks ('Task not found' otherwise) or delete it ('Study plan not found'). Delete asks 'Are you sure you want to delete this study plan? This action cannot be undone.'. With no plans the tab shows 'No study plans yet'.	
Related Test Cases	US-70 : Plan ownership and delete [Version :1]

Requirement: REQ-P-PLAN-06 : Plan kept when the course is deleted	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Study plans are linked to a course by an optional courseId with SET NULL on course delete, so plans are preserved (Iteration 3 Data Description).	
Related Test Cases	US-71 : Study plan survives course deletion [Version :1]

TestLink

Requirements Specification Document

Test Project: UniShare

Printed by TestLink on 26/10/2026

2026 Group UniShare

Table Of Contents

1. SRS-P-AIN : UC-S3-018 Enhance Notes with AI

REQ-P-AIN-01 : Enhancement request validation

REQ-P-AIN-02 : Only owner or contributor can enhance a note

REQ-P-AIN-03 : Enhancement result and history

1. Requirements Spec.: SRS-P-AIN : UC-S3-018 Enhance Notes with AI	
revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (3/0)
Student uses AI to generate, improve, summarize or expand a course note. Source: UniShare_Iteration_3.md UC-S3-018, Data Description 'Note Enhancement'; src/app/api/ai/generate-note/route.ts; src/server/api/routers/ai.ts (generateNote, getNoteGenerations).	

Requirement: REQ-P-AIN-01 : Enhancement request validation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Type must be one of GENERATE, IMPROVE, SUMMARIZE, EXPAND and prompt must be 1-5000 characters; otherwise 400 'Invalid request'. Temperature, if given, 0-2.	
Related Test Cases	US-72 : Each enhancement type returns content and is recorded [Version :1]US-73 : Invalid enhancement requests [Version :1]

Requirement: REQ-P-AIN-02 : Only owner or contributor can enhance a note	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The course owner and ACCEPTED CONTRIBUTORs can enhance a note. A VIEWER or unrelated user gets 403 'Forbidden: You don't have permission to edit this note'; unknown note 404 'Note not found'; no session 401 'Unauthorized'.	
Related Test Cases	US-74 : Enhancement permission by role [Version :1]

Requirement: REQ-P-AIN-03 : Enhancement result and history	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
A successful call returns success, generatedText (markdown) and tokensUsed and stores an AiGeneratedNote with prompt, type, content before and after. getNoteGenerations returns only the caller's generations for that note, newest first (page size 1-50, default 20). AI provider errors return 503.	
Related Test Cases	US-72 : Each enhancement type returns content and is recorded [Version :1]US-74 : Enhancement permission by role [Version :1]

Requirements Specification Document

Test Project: UniShare

Printed by TestLink on 26/10/2026

2026 Group UniShare

Table Of Contents

1. SRS-P-NOTE : UC-S4-002 Real-Time Collaborative Notes

REQ-P-NOTE-01 : Open course notes

REQ-P-NOTE-02 : Only course members can open notes

REQ-P-NOTE-03 : Role-based editing (OWNER / CONTRIBUTOR / VIEWER)

REQ-P-NOTE-04 : Real-time synchronisation and persistence

REQ-P-NOTE-05 : Presence of live collaborators

REQ-P-NOTE-06 : Create pages and nested sub-pages

REQ-P-NOTE-07 : Delete pages and server-side permission checks

REQ-P-NOTE-08 : Network interruption

1. Requirements Spec.: SRS-P-NOTE : UC-S4-002 Real-Time Collaborative Notes

revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (8/0)

Course owner and collaborators edit nested note pages together in real time (Liveblocks + BlockNote). Source: UniShare_Iteration_4.md Use Case Diagram 2 and Use Case 2 (UC-S4-002), Data Description 'Note Table'; src/app/(student)/courses/[id]/notes/[[...pageId]]/page.tsx, src/components/notes/*, src/components/resources/resource-card.tsx, src/app/api/notes/create, src/app/api/notes/[id], src/app/api/liveblocks-auth/route.ts.

Requirement: REQ-P-NOTE-01 : Open course notes	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
'Open Collaborative Notes' on the Notes card opens /courses/<id>/notes. If the course has no pages and the user can edit, a page 'Getting Started' is created and opened; a VIEWER sees 'No pages have been created yet. Ask a contributor or owner to create one.'. Without page id, or with an unknown / other course page id, the first page is opened.	
Related Test Cases	US-75 : Owner opens notes for the first time [Version :1]US-76 : Viewer opens a course without pages [Version :1]US-80 : Unknown or other course page id [Version :1]

Requirement: REQ-P-NOTE-02 : Only course members can open notes	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Only the owner and ACCEPTED collaborators can open the notes: others are redirected to /courses/<id>, logged-out users to /login, unknown course to /courses. Liveblocks auth: no session 401 'Unauthorized', missing room 400 'Bad Request - Room ID missing', unknown page 404 'Page not found', non-member 403 'Forbidden'.	
Related Test Cases	US-77 : Notes access by user relation [Version :1]US-79 : Liveblocks authentication endpoint [Version :1]

Requirement: REQ-P-NOTE-03 : Role-based editing (OWNER / CONTRIBUTOR / VIEWER)	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The header shows the role badge OWNER, CONTRIBUTOR or VIEWER. OWNER and CONTRIBUTOR can edit content, titles and pages. VIEWER sees 'Viewing in Read-Only Mode', cannot type in the editor or title and sees no add/delete page controls; the server must not accept a VIEWER's edits (Iteration 4: VIEWER read-only).	
Related Test Cases	US-75 : Owner opens notes for the first time [Version :1]US-78 : Viewer is read-only (UI and server) [Version :1]

Requirement: REQ-P-NOTE-04 : Real-time synchronisation and persistence	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Text typed by one member appears for the other members of the same page in real time; concurrent edits, also of the same block, merge without conflict and all editors converge (Yjs CRDT). Content is persisted by Liveblocks ('All changes saved') and is still there after reload.	
Related Test Cases	US-81 : Two students edit the same page in real time [Version :1]US-82 : Simultaneous edit of the same text converges [Version :1]US-86 : Offline edits sync after reconnect [Version :1]

Requirement: REQ-P-NOTE-05 : Presence of live collaborators	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The 'Active Collaborators' bar shows the current user ('<name> (You)') and up to 5 other online users as coloured initials, '+<n>' for more, and '<count> online'. When a user leaves, his avatar disappears.	
Related Test Cases	US-81 : Two students edit the same page in real time [Version :1]US-83 : Presence list boundaries and leaving [Version :1]

Requirement: REQ-P-NOTE-06 : Create pages and nested sub-pages	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
The '+' button in 'Pages' creates an 'Untitled' page placed after the last page and opens it; 'Add sub-page' creates a child page shown indented under its parent (expand/collapse). Each page has its own room. The title is edited inline and saved on Enter or leaving the field.	
Related Test Cases	US-84 : Create page and nested sub-page [Version :1]

Requirement: REQ-P-NOTE-07 : Delete pages and server-side permission checks	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Delete asks 'Are you sure you want to delete this page?'; deleting a page also deletes its sub-pages; if the open page is deleted the first remaining page opens. A VIEWER calling the API gets 403 'You don't have permission to create pages' / 'You don't have permission to edit this page' / 'You don't have permission to delete this page'.	
Related Test Cases	US-78 : Viewer is read-only (UI and server) [Version :1]US-85 : Delete a page with sub-pages [Version :1]

Requirement: REQ-P-NOTE-08 : Network interruption

Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
If a member loses connection, edits are kept locally and synchronised when the connection returns (Iteration 4 UC-S4-002 A1).	
Related Test Cases	US-86 : Offline edits sync after reconnect [Version :1]