TestLink

Requirements Specification Document

Test Project: UniShare

Printed by TestLink on 26/10/2026

2026 Group UniShare

Table Of Contents

1. SRS-A-REG : UC-S2-001 Student Registration (detailed Use Case 1)

REQ-A-REG-01 : Public registration form and required fields

REQ-A-REG-02 : University and faculty selection

REQ-A-REG-03 : Minimum name length

REQ-A-REG-04 : Maximum name length of 100 (document-only gap)

REQ-A-REG-05 : Email syntax

REQ-A-REG-06 : Unique registration email and error recovery

REQ-A-REG-07 : Password minimum length

REQ-A-REG-08 : Password character classes

REQ-A-REG-09 : Password confirmation

REQ-A-REG-10 : Required uploaded ID and URL validation

REQ-A-REG-11 : Required academic selections

REQ-A-REG-12 : Faculty must belong to selected university (document-only gap)

REQ-A-REG-13 : Public upload accepts one image

REQ-A-REG-14 : Student ID file size maximum

REQ-A-REG-15 : Upload removal and recovery

REQ-A-REG-16 : Persist pending applicant with bcrypt and success UI

REQ-A-REG-17 : Welcome email is best effort

1. Requirements Spec.: SRS-A-REG : UC-S2-001 Student Registration (detailed Use Case 1)

revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (17/0)

Unauthenticated applicant supplies identity, academic details, password and student ID. Source: assignment/UniShare Iteration 2.md, detailed Use Case 1 and diagram UC-S2-001..007. Current UI is /signup (the document says /register), then /login after 3000 ms; src/app/(auth)/signup/page.tsx, src/server/api/routers/user.ts, src/app/api/uploadthing/core.ts, src/lib/email.ts, prisma/schema.prisma. REG-04 and REG-12 preserve document requirements absent from current server validation.

Requirement: REQ-A-REG-01 : Public registration form and required fields	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 1-3, 23; src/app/(auth)/signup/page.tsx. /signup displays 'Join UNIShare', 'Full Name', 'University Email', 'Password', 'Confirm Password', 'University', 'Faculty', 'Student ID Photo' and 'Create Account'. The six text/select inputs are HTML required; missing input blocks form submission.	
Related Test Cases	US-42 : Public registration displays all mandatory controls [Version :1]US-45 : Each empty required registration input blocks submission [Version :1]

Requirement: REQ-A-REG-02 : University and faculty selection	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 6-13; user.ts getUniversities; signup/page.tsx. Universities and their faculties are sorted ascending by name. Faculty is disabled until a university is selected, contains only its faculties and resets to 'Select faculty' when university changes. Placeholders are 'Select university' and 'Select faculty'.	
Related Test Cases	US-43 : University list is alphabetical and faculties are scoped [Version :1]US-44 : Changing university clears the previously selected faculty [Version :1]

Requirement: REQ-A-REG-03 : Minimum name length	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23; user.ts register name schema. A name shorter than 2 characters is rejected with 'Name must be at least 2 characters'; 2 and 3 characters pass this constraint.	
Related Test Cases	US-47 : Name minimum boundaries at 1, 2 and 3 characters [Version :1]

Requirement: REQ-A-REG-04 : Maximum name length of 100 (document-only gap)

Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23 specifies 2-100 characters; user.ts register and signup/page.tsx have no maximum. Business expectation: 99 and 100 accepted, 101 rejected without creating a user. Current code will accept 101; no maximum-length message exists. Record this as a document/code discrepancy when executed.	
Related Test Cases	US-48 : Document maximum name boundary at 99, 100 and 101 characters [Version :1]

Requirement: REQ-A-REG-05 : Email syntax	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23; user.ts register email schema; signup/page.tsx. API rejects malformed/empty email with 'Invalid email address'. UI uses required type=email. No university-domain allowlist is implemented; syntactically valid example.com is accepted.	
Related Test Cases	US-49 : Email invalid partitions and valid nonuniversity domain [Version :1]

Requirement: REQ-A-REG-06 : Unique registration email and error recovery	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 27-28, A1; user.ts register; prisma/schema.prisma User.email. An existing exact email is rejected with 'User with this email already exists'; no extra record is created. UI displays server error, clears its loading state and allows correction.	
Related Test Cases	US-50 : Existing approved and pending email cannot register twice [Version :1]US-60 : SMTP welcome failure preserves a successful registration [Version :1]US-61 : Duplicate-email server error can be corrected without reuploading [Version :1]

Requirement: REQ-A-REG-07 : Password minimum length	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23; user.ts register; signup/page.tsx handleSubmit. Password minimum is 8 characters; failure text 'Password must be at least 8 characters'. There is no explicit application maximum; test 7, 8 and 9 characters with valid complexity.	
Related Test Cases	US-51 : Password length boundaries at 7, 8 and 9 characters [Version :1]

Requirement: REQ-A-REG-08 : Password character classes	
Version :	1

revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 secure-password description; user.ts register regex. New passwords require uppercase, lowercase and a digit. Missing any class returns 'Password must contain at least one uppercase letter, one lowercase letter, and one number'. Symbols are optional; seeded admin123 remains usable for login.	
Related Test Cases	US-52 : Password complexity decision table for all three classes [Version :1]

Requirement: REQ-A-REG-09 : Password confirmation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 client validation; signup/page.tsx handleSubmit. Unequal password and confirmation show 'Passwords do not match' before the mutation; the form becomes editable again. Confirmation is a UI check, not an API field.	
Related Test Cases	US-53 : Mismatched confirmation blocks then corrected value succeeds [Version :1]

Requirement: REQ-A-REG-10 : Required uploaded ID and URL validation	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 14-23; signup/page.tsx and user.ts register. Create Account is disabled without an uploaded URL. The handler guard says 'Please upload your student ID'. API studentIdUrl must be a URL or returns 'Invalid student ID URL'; the schema does not restrict the URL host.	
Related Test Cases	US-42 : Public registration displays all mandatory controls [Version :1]US-46 : Remove uploaded student ID then replace it [Version :1]US-54 : API rejects empty academic selections and invalid ID URLs [Version :1]

Requirement: REQ-A-REG-11 : Required academic selections	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23; user.ts register universityId/facultyId. Empty universityId and facultyId return 'University is required' and 'Faculty is required'. These are nonempty-string checks; existing seeded IDs are used for valid cases.	
Related Test Cases	US-44 : Changing university clears the previously selected faculty [Version :1]US-45 : Each empty required registration input blocks submission [Version :1]US-54 : API rejects empty academic selections and invalid ID URLs [Version :1]

Requirement: REQ-A-REG-12 : Faculty must belong to selected university (document-only gap)	
Version :	1

revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 23 and A5; user.ts register; prisma/schema.prisma User/Faculty relations. Business expectation: reject a tampered request pairing UTM with a Universiti Malaya faculty, documented text 'Invalid faculty selection'. Current router only validates nonempty IDs and independent foreign keys, so does not enforce this relation.	
Related Test Cases	US-55 : Tampered faculty from a different university must be rejected [Version :1]

Requirement: REQ-A-REG-13 : Public upload accepts one image	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 16-17, A4; api/uploadthing/core.ts studentIdUploader. Unauthenticated uploads accept image files, maximum file count 1; PDFs and a two-image batch are rejected. Completion returns uploadedBy='registration' and the file URL; UI shows 'Student ID uploaded'. Library-generated error wording is not fixed by app code.	
Related Test Cases	US-56 : Public image upload accepts JPG and PNG but rejects PDF [Version :1]US-58 : Two-file batch and failed upload do not enable registration [Version :1]

Requirement: REQ-A-REG-14 : Student ID file size maximum	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 step 17, A3; api/uploadthing/core.ts studentIdUploader. Image maxFileSize='4MB' (4194304 bytes); 4194303 and 4194304 are accepted, 4194305 rejected. The app formats uploader callback errors as 'Upload failed: <message>'.	
Related Test Cases	US-57 : ID image size boundaries at 4 MiB minus one, exact and plus one byte [Version :1]

Requirement: REQ-A-REG-15 : Upload removal and recovery	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 A2 and review step 21; signup/page.tsx upload callbacks. 'Remove' clears the selected URL, restores the uploader and disables Create Account. Upload failure displays 'Upload failed: <message>' and no successful ID state; retry can succeed.	
Related Test Cases	US-46 : Remove uploaded student ID then replace it [Version :1]US-58 : Two-file batch and failed upload do not enable registration [Version :1]

Requirement: REQ-A-REG-16 : Persist pending applicant with bcrypt and success UI	
Version :	1
revision:	1

Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 29-32, 37-38; user.ts register; signup/page.tsx; prisma/schema.prisma. Successful registration stores role PENDING, null approvedAt, selected IDs, ID URL and bcrypt hash using 12 rounds. Response success=true with userId and 'Registration successful! Please wait for admin approval. You'll receive an email once approved.'. UI shows 'Registration Successful!', 'Your account has been created and is pending admin approval.' and 'Redirecting to login...', then /login after 3000 ms (document instead says /waiting-approval).	
Related Test Cases	US-59 : Successful applicant is PENDING with hashed password and welcome email [Version :1]US-60 : SMTP welcome failure preserves a successful registration [Version :1]US-61 : Duplicate-email server error can be corrected without reuploading [Version :1]US-86 : Deleted applicant cannot login and may register again for review [Version :1]

Requirement: REQ-A-REG-17 : Welcome email is best effort	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 1 steps 33-36, A6; user.ts register; src/lib/email.ts sendWelcomeEmail. Attempt welcome email to the applicant with subject 'Welcome to UNIShare - Registration Received'. SMTP failure logs 'Failed to send welcome email:' but registration still returns success and leaves the applicant PENDING; retry must not create a duplicate.	
Related Test Cases	US-59 : Successful applicant is PENDING with hashed password and welcome email [Version :1]US-60 : SMTP welcome failure preserves a successful registration [Version :1]

TestLink

Requirements Specification Document

Test Project: UniShare

2026 Group UniShare

Table Of Contents

1. SRS-A-ADM : UC-S2-002 Admin Approval (detailed Use Case 2)

REQ-A-ADM-01 : Admin route and API authorization

REQ-A-ADM-02 : Pending list and safe user data

REQ-A-ADM-03 : Review identity details and full-size student ID

REQ-A-ADM-04 : Dashboard totals refresh after decisions

REQ-A-ADM-05 : Search/filter and sorting (document-only gap)

REQ-A-ADM-06 : Approval confirmation and valid transition

REQ-A-ADM-07 : Missing and nonpending targets rejected

REQ-A-ADM-08 : Approval email failure does not undo approval

REQ-A-ADM-09 : Rejection confirmation, optional reason and deletion

REQ-A-ADM-10 : Rejection email is best effort

1. Requirements Spec.: SRS-A-ADM : UC-S2-002 Admin Approval (detailed Use Case 2)

revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (10/0)

Admin reviews and approves/rejects applicants. Source: assignment/UniShare Iteration 2.md detailed Use Case 2 and diagram UC-S2-010..015; src/server/api/routers/admin.ts; src/app/(admin)/layout.tsx, admin/page.tsx, admin/approvals/page.tsx; src/lib/email.ts; prisma/schema.prisma. Search and interactive sorting are document-only gaps; bulk approval is future scope.

Requirement: REQ-A-ADM-01 : Admin route and API authorization	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 preconditions and steps 1-3; admin.ts adminProcedure; src/server/api/trpc.ts protectedProcedure; src/app/(admin)/layout.tsx; middleware.ts. Only ADMIN accesses admin procedures. Anonymous API requests return UNAUTHORIZED; authenticated APPROVED/PENDING users return FORBIDDEN 'Only administrators can perform this action'. Anonymous admin pages redirect /login; non-admins redirect through /courses (PENDING ends at /waiting-approval).	
Related Test Cases	US-64 : Admin login reaches approval dashboard [Version :1]US-70 : Anonymous and nonadmin users cannot access admin pages or procedures [Version :1]

Requirement: REQ-A-ADM-02 : Pending list and safe user data	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 steps 7-8; admin.ts getPendingUsers/getAllUsers. Pending list includes only role PENDING, newest createdAt first, with academic details and without password. getAllUsers also excludes password. Empty UI: 'All caught up!' and 'There are no pending approvals at the moment.'.	
Related Test Cases	US-71 : Pending list excludes approved/admin accounts, orders newest first and handles zero [Version :1]

Requirement: REQ-A-ADM-03 : Review identity details and full-size student ID	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 steps 10-15; admin/approvals/page.tsx. The current page uses cards with name, email, 'University:', 'Faculty:', 'Registered:', 'Student ID', 'View full size →', 'Approve' and 'Reject'. Clicking ID or full-size link opens the exact stored studentIdUrl in a new tab; no separate student-detail route is implemented.	
Related Test Cases	US-72 : Admin sees applicant identity and opens the stored student ID [Version :1]

Requirement: REQ-A-ADM-04 : Dashboard totals refresh after decisions

Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 steps 5, 23-25; admin.ts getDashboardStats; approvals/page.tsx. Cards 'Pending Approvals', 'Approved Users', 'Total Users', 'Administrators' reflect role counts. Approve decreases pending and increases approved, leaving total/admin unchanged; reject decreases pending and total. Successful mutations invalidate pending list and statistics.	
Related Test Cases	US-73 : Dashboard role counts refresh after approve and reject [Version :1]

Requirement: REQ-A-ADM-05 : Search/filter and sorting (document-only gap)	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 step 8, diagram UC-S2-015; admin/approvals/page.tsx and admin.ts getPendingUsers. Business expectation: filter pending applicants by name/email and sort by date/name/university. Current cards expose no search/filter/sort controls; preserve as a gap rather than inventing labels or claiming these controls work.	
Related Test Cases	US-74 : Documented pending-applicant search and sorting are available [Version :1]

Requirement: REQ-A-ADM-06 : Approval confirmation and valid transition	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 steps 16-17; admin.ts approveUser; approvals/page.tsx. 'Are you sure you want to approve this user?' must be confirmed; cancel sends no mutation. Only PENDING transitions to APPROVED, setting approvedAt. Response success=true and '<name> has been approved successfully'; card disappears. While a decision is pending both action buttons are disabled and selected approval says 'Approving...'. No success toast is implemented.	
Related Test Cases	US-69 : Pending session observes admin approval without signing in again [Version :1]US-75 : Cancel approval leaves applicant pending [Version :1]US-76 : Confirm approval updates role, timestamp and email [Version :1]US-79 : Approval remains effective when approval email fails [Version :1]US-80 : Sequential replay of approval preserves first approval timestamp [Version :1]

Requirement: REQ-A-ADM-07 : Missing and nonpending targets rejected	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 A2/A3 and rejection alternative; admin.ts approveUser/rejectUser. Unknown userId returns NOT_FOUND 'User not found'. APPROVED/ADMIN targets return BAD_REQUEST 'User is not pending approval' for either operation; record and approvedAt stay unchanged. Sequential replay of approval is rejected; atomic concurrent safety is not claimed.	
Related Test Cases	US-77 : Approve refuses already approved and admin targets [Version :1]US-78 : Approve rejects nonexistent or empty target ID [Version :1]US-80 : Sequential replay of approval preserves first approval timestamp [Version :1]US-84 : Reject refuses approved/admin targets and missing users [Version :1]

Requirement: REQ-A-ADM-08 : Approval email failure does not undo approval	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 steps 18-21, A1; admin.ts approveUser; email.ts sendApprovalEmail. Attempt subject 'Your UNIShare Account Has Been Approved!' preceded by U+1F389 (party popper) and a space to applicant with dashboard URL NEXT_PUBLIC_APP_URL + '/courses'. Failure logs 'Failed to send approval email:' but response still succeeds and applicant remains APPROVED; the document's warning toast is not implemented.	
Related Test Cases	US-76 : Confirm approval updates role, timestamp and email [Version :1]US-79 : Approval remains effective when approval email fails [Version :1]

Requirement: REQ-A-ADM-09 : Rejection confirmation, optional reason and deletion	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 rejection alternative; admin.ts rejectUser; approvals/page.tsx; schema.prisma Role. UI prompts 'Enter rejection reason (optional):', then 'Are you sure you want to reject this user?'. Final cancel makes no change. Confirm deletes a PENDING applicant; there is no REJECTED enum or retain-account option. Response success=true and 'Registration for <name> has been rejected'. While pending, buttons disable and selected rejection says 'Rejecting...'. Deleted applicant cannot login and may register again.	
Related Test Cases	US-81 : Reject with reason sends explanation and deletes pending applicant [Version :1]US-82 : Optional rejection reason accepts blank and canceled prompt [Version :1]US-83 : Cancel final rejection confirmation preserves applicant [Version :1]US-85 : Rejection still deletes applicant when mail fails [Version :1]US-86 : Deleted applicant cannot login and may register again for review [Version :1]

Requirement: REQ-A-ADM-10 : Rejection email is best effort	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 2 rejection alternative and email-failure principle; admin.ts rejectUser; email.ts sendRejectionEmail. Attempt email before deletion, subject 'UNIShare Registration Update'; nonempty reason appears under 'Reason:', omitted/empty reason omits that section. SMTP failure logs 'Failed to send rejection email:' and deletion still completes.	
Related Test Cases	US-81 : Reject with reason sends explanation and deletes pending applicant [Version :1]US-82 : Optional rejection reason accepts blank and canceled prompt [Version :1]US-85 : Rejection still deletes applicant when mail fails [Version :1]

Requirements Specification Document

Test Project: UniShare

Printed by TestLink on 26/10/2026

Table Of Contents

1. SRS-A-LOG : UC-S2-003 Student Login (detailed Use Case 3)

REQ-A-LOG-01 : Valid credentials route by current role

REQ-A-LOG-02 : Generic invalid-credentials errors

REQ-A-LOG-03 : Required login fields

REQ-A-LOG-04 : Session persistence and authenticated-page redirects

REQ-A-LOG-05 : Fresh approval status without a new login

REQ-A-LOG-06 : Pending access restrictions and sign out

1. Requirements Spec.: SRS-A-LOG : UC-S2-003 Student Login (detailed Use Case 3)	
revision	1
Author	admin
Type	User Requirement Specification
Total count of requirements (Coverage)	N/A (6/0)
Credential authentication, role routing and sessions, including Admin login. Source: assignment/UniShare Iteration 2.md detailed Use Case 3 and diagram UC-S2-007..010; src/server/auth/config.ts; src/app/(auth)/login/page.tsx, waiting-approval/page.tsx; middleware.ts; src/app/(student)/layout.tsx; src/app/(admin)/layout.tsx. Implementation uses JWT sessions, not inserted Session rows or a Remember me control.	

Requirement: REQ-A-LOG-01 : Valid credentials route by current role	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 steps 14-31; auth/config.ts authorize; login/page.tsx; middleware.ts; student/layout.tsx; admin/page.tsx. Password checked with bcrypt. APPROVED reaches /courses, PENDING /waiting-approval, ADMIN /admin/approvals via /courses. Successful UI shows 'Welcome Back!' and 'Taking you to your dashboard...'; PENDING page heading is 'Account Pending Approval'.	
Related Test Cases	US-62 : Approved student logs in with seeded credentials [Version :1]US-63 : Pending login cannot access student features and can sign out [Version :1]US-64 : Admin login reaches approval dashboard [Version :1]US-67 : Existing sessions bypass login and signup by role [Version :1]US-79 : Approval remains effective when approval email fails [Version :1]

Requirement: REQ-A-LOG-02 : Generic invalid-credentials errors	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 A1/A2; auth/config.ts authorize; login/page.tsx. Unknown email and wrong password show identical 'Invalid email or password', keep user on /login, and restore editable fields/'Sign In'. No authenticated session is issued.	
Related Test Cases	US-65 : Unknown email and wrong password have the same safe error [Version :1]US-86 : Deleted applicant cannot login and may register again for review [Version :1]

Requirement: REQ-A-LOG-03 : Required login fields	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 steps 7-8; login/page.tsx; auth/config.ts authorize. UI 'Email Address' is required type=email; 'Password' is required type=password. Missing values prevent browser submission. Direct authorize without credentials throws 'Missing email or password'; external UI errors are mapped to 'Invalid email or password'.	
Related Test Cases	US-66 : Missing and malformed login fields cannot authenticate [Version :1]

Requirement: REQ-A-LOG-04 : Session persistence and authenticated-page redirects	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 steps 21-27 and postconditions; auth/config.ts callbacks; middleware.ts; login/page.tsx; user.ts getCurrentSession. JWT-backed sessions persist across reload/new same-profile tabs, expose user id/role/universityId/facultyId without password, and existing-session /login or /signup returns to the role-appropriate destination.	
Related Test Cases	US-67 : Existing sessions bypass login and signup by role [Version :1]US-68 : JWT session survives reload and another tab without exposing password [Version :1]

Requirement: REQ-A-LOG-05 : Fresh approval status without a new login	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 role check/A3 and diagram UC-S2-009; auth/config.ts session callback; student/layout.tsx. Session reload reads current database role, so an Alice session issued while PENDING can reach /courses after admin approval without a new credentials submission.	
Related Test Cases	US-69 : Pending session observes admin approval without signing in again [Version :1]

Requirement: REQ-A-LOG-06 : Pending access restrictions and sign out	
Version :	1
revision:	1
Author:	admin
Status	Valid
Type	Use Case
Coverage	100% (1/1)
Source: Iteration 2 Use Case 3 A3; waiting-approval/page.tsx; student/layout.tsx; middleware.ts; user.ts getCurrentSession. PENDING is routed away from student features to 'Account Pending Approval'. 'Sign Out' clears the session and returns /login; subsequent /courses redirects /login and getCurrentSession returns null.	
Related Test Cases	US-63 : Pending login cannot access student features and can sign out [Version :1]