Установка и работа с MongoDB

1. Устанавливаю зависимость sudo apt install -y gnupg
2. Импортирую ключи GPG, обязательны нужны - curl -fsSL https://www.mongodb.org/static/pgp/server-8.0.asc | sudo gpg -o /usr/share/keyrings/mongodb-server-8.0.gpg –dearmor
3. Добавляю пакет репозитория в систему управления пакетами APT - echo "deb [arch=amd64,arm64 signed-by=/usr/share/keyrings/mongodb-server-8.0.gpg] https://repo.mongodb.org/apt/ubuntu noble/mongodb-org/8.0 multiverse" | sudo tee /etc/apt/sources.list.d/mongodb-org-8.0.list
4. Обновляем систему и устанавливаем mongodb - sudo apt install -y mongodb-org
5. Включаем службу
6. Для доступа и работы с MongoDB вводим mongosh

```
anastasia@DESKTOP-ADT12D6:~$ mongosh
Current Mongosh Log ID: 69d900cbd9a13aa1fe44ba88
Connecting to:          mongodb://127.0.0.1:27017/?directConnection=true&ser
verSelectionTimeoutMS=2000&appName=mongosh+2.8.2
Using MongoDB:          8.0.20
Using Mongosh:          2.8.2

For mongosh info see: https://www.mongodb.com/docs/mongodb-shell/


To help improve our products, anonymous usage data is collected and sent to
MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
You can opt-out by running the disableTelemetry() command.

------
   The server generated these startup warnings when booting
   2026-04-10T16:35:48.164+03:00: Using the XFS filesystem is strongly recom
mended with the WiredTiger storage engine. See http://dochub.mongodb.org/cor
e/prodnotes-filesystem
   2026-04-10T16:35:48.443+03:00: Access control is not enabled for the data
base. Read and write access to data and configuration is unrestricted
   2026-04-10T16:35:48.444+03:00: For customers running the current memory a
llocator, we suggest changing the contents of the following sysfsFile
   2026-04-10T16:35:48.444+03:00: For customers running the current memory a
llocator, we suggest changing the contents of the following sysfsFile
   2026-04-10T16:35:48.444+03:00: We suggest setting the contents of sysfsFi
le to 0.
   2026-04-10T16:35:48.444+03:00: We suggest setting swappiness to 0 or 1, a
s swapping can cause performance problems.
------

test> |
```

7. Создаю таблицу (коллекцию) с помощью команды db.createCollection(“data”), затем проверяем создалась ли

```
test>  db.createCollection("data")
{ ok: 1 }
test> show collections
data
```

8. Далее создаю пользователя manager с правами чтения с помощью команды db.createUser({user:”manager”, pwd:”TestPassw@”, roles: [{role: “read”, db: “data”}]})

```
data> db.createUser({user:"manager", pwd:"TestPasswd@", roles: [{role: "read
", db:"data"}]})
{ ok: 1 }
```

9. Итог создания пользователя, где указана роль

```
data> show users
[
  {
    _id: 'data.manager',
    userId: UUID('57224733-ec90-4597-9ec6-4f54cda65c40'),
    user: 'manager',
    db: 'data',
    roles: [ { role: 'read', db: 'data' } ],
    mechanisms: [ 'SCRAM-SHA-1', 'SCRAM-SHA-256' ]
  }
]
```