Alegre, Jhon Isaac S.

Last year work:

```
isaac@Workstation:~/ansible$ ansible all -m ping
192.168.56.104 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3"
    },
    "changed": false,
    "ping": "pong"
}
isaac@Workstation:~/ansible$
```

Right now, we configure the ansible playbook to install the mariadb using the package name: mariadb-server

playbook.yml

```yaml
- name: Web server setup (install + create user dirs)
 hosts: web_servers
 gather_facts: yes
 vars:
   target_user: "isaac"



 tasks:
 - name: Install mariadb-server (system-level)
   ansible.builtin.apt:
     name: mariadb-server
     state: present
   become: yes

 - name: Install mariadb-client
   ansible.builtin.apt:
     name: mariadb-client
     state: present
   become: yes

 - name: Create user directories inside target user's home
   ansible.builtin.file:
     path: "~/{{ item }}"
     state: directory
```

```
    mode: '0755'
  loop:
    - test_d1
    - test_d2
    - test_d3
  become: yes
  become_user: "{{ target_user }}"
```

inventory.ini

```
[web_servers]
#^is a metagrouup
192.168.56.104
```

ansible.cfg

```
[defaults]
inventory = inventory.ini
private_key_file = /home/isaac/.ssh/id_rsa
```

Result of ansible-playbook playbook.yml -K

```
isaac@Workstation:~/ansible$ ansible-playbook playbook.yml -K
BECOME password:

PLAY [Web server setup (install + create user dirs)] ***************************

TASK [Gathering Facts] *********************************************************
ok: [192.168.56.104]

TASK [Install mariadb-server (system-level)] ***********************************
changed: [192.168.56.104]

TASK [Install mariadb-client] **************************************************
changed: [192.168.56.104]

TASK [Create user directories inside target user's home] ***********************
ok: [192.168.56.104] => (item=test_d1)
ok: [192.168.56.104] => (item=test_d2)
ok: [192.168.56.104] => (item=test_d3)

PLAY RECAP *********************************************************************
192.168.56.104             : ok=4    changed=2    unreachable=0    failed=0    skipped=0    r
escued=0    ignored=0

isaac@Workstation:~/ansible$
```

```
isaac@ManagerNode:~$ systemctl status mariadb
● mariadb.service - MariaDB 10.6.22 database server
     Loaded: loaded (/lib/systemd/system/mariadb.service; enabled; vendor prese>
     Active: active (running) since Tue 2026-01-06 18:01:58 +08; 28s ago
       Docs: man:mariadbd(8)
             https://mariadb.com/kb/en/library/systemd/
    Process: 8027 ExecStartPre=/usr/bin/install -m 755 -o mysql -g root -d /var>
    Process: 8028 ExecStartPre=/bin/sh -c systemctl unset-environment _WSREP_ST>
    Process: 8031 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && >
    Process: 8078 ExecStartPost=/bin/sh -c systemctl unset-environment _WSREP_S>
    Process: 8080 ExecStartPost=/etc/mysql/debian-start (code=exited, status=0/>
   Main PID: 8064 (mariadbd)
     Status: "Taking your SQL requests now..."
      Tasks: 12 (limit: 62304)
     Memory: 61.4M
        CPU: 505ms
     CGroup: /system.slice/mariadb.service
             └─8064 /usr/sbin/mariadbd
lines 1-17/17 (END)
```