

# Pre-stimulus time dimension reduction by using t-SNE to predict conscious awareness about correct or incorrect response



**Sejik Park**

**Departments of Computer Science and Engineering  
Interdisciplinary Major in Brain and Cognitive Sciences  
Korea University College of Informatics**

We think the **Unthinkable**

# CONTENTS

## 1. Preprocessing

- Baseline correction
- Artifact rejection by EMD & Pearson correlation

## 2. Main

- t-SNE (dimension reduction)
- Circle regression

## 3. Result

- Variance ( $R^2$ )
- Perceptual accuracy

- **Baseline Correction**
  - Epoch data with given code (onset-500 to onset)
  - Baseline correction were performed using the 500-0 ms pre-stimulus interval
- **Further research**
  - Check all channels for finding bad channel to interpolation
  - Artifact rejection (limit maximum amplitude & maximal gradient voltage step): remove epoch
  - Offline filter (e.g. 0.5-30 Hz) & ICA noise reduction (Kawakatsu 2003)
  - Individual averaged data analysis & Grand averaged data analysis
  - Frequency analysis (e.g. wavelet → Beta) (Pfurtscheller, Woertz et al. 2002)
  - Change time range or short range repeat analysis

**Also, parallel coding with MATLAB would be better to overcome very slow computation speed**

- Artifact rejection by Empirical Mode Decomposition (EMD) & Pearson correlation
  - **Strong artifact rejection tool to remove blinking and small movement** (Rosas-Cholula, Ramirez-Cortes et al. 2013)
- Further research
  - **Change EMD parameter (resolution, residual energy)**
  - **Change correlation p-value**
  - **Check EMD artifact rejection removing noise not real signal by somatosensory meg simulation data**

- **t-Distributed Stochastic Neighbor Embedding (t-SNE; dimension reduction)**
  - **Dimension reduction is one way to control the complexity of electroencephalogram (Li and Lu 2009)**
  - **t-SNE is good to visualize difference among subject groups**
- **Further research**
  - **Change t-SNE parameter (dimensionality reduction number, perplexity)**
  - **Using different input (frequency information, connectivity information by grand causality)**
  - **Check EMD artifact rejection removing noise not real signal by somatosensory meg simulation data**
  - **t-SNE with deep recurrent neural network for analysis**

# Main & Result

- Main: Circle regression (non-linear regression)
  - Dimension reduction data plot looks like circular
- Further research
  - Relation between channels to get encoded information
- Result: Variance ( $R^2$ )
  - Wrong value (because of non-linear regression): all values are over 0.90
- Further research
  - Find way to use linear regression (way to find simple dimension reduction data)

Circle regression is not for R square value



- Perceptual accuracy
  - hits + correction rejection vs. false alarms + misses
  - Accuracy over 198 epochs: 0.6021 (Channel: 313)
  - t-SNE is good to visualize difference among subject groups
  - Result file: SejikPark\_BIOMAG2016.mat
- Further research
  - Find meaning of the 313 channel location
  - Test more data (epochs & subjects) with training & test analysis (e.g. 80% data for training analysis to get parameter and 20% data for test analysis to know the accuracy of method)
  - Find accuracy has meaning (coincidence or real meaningful result)

**Limitation: analysis of only 198 epochs of first subjects because of limit of time and computational power**



E-mail: [sejik4072@korea.ac.kr](mailto:sejik4072@korea.ac.kr)  
Thank you



- Kawakatsu, M. (2003). Application of ICA to MEG noise reduction. Fourth international symposium on independent component analysis and blind signal separation (ICA2003), Nara, Japan.
- Li, M. and B.-L. Lu (2009). Emotion classification based on gamma-band EEG. 2009 Annual International Conference of the IEEE Engineering in Medicine and Biology Society, IEEE.
- Pfurtscheller, G., et al. (2002). "Contrasting behavior of beta event-related synchronization and somatosensory evoked potential after median nerve stimulation during finger manipulation in man." Neuroscience letters **323**(2): 113-116.
- Rosas-Cholula, G., et al. (2013). Head movement artifact removal in EEG signals using Empirical Mode Decomposition and Pearson Correlation. Proceedings on the International Conference on Artificial Intelligence (ICAI), The Steering Committee of The World Congress in Computer Science, Computer Engineering and Applied Computing (WorldComp).

## **Code (open source) reference:**

**(EMD) Rato, R. T., Ortigueira, M. D., & Batista, A. G. (2008). On the HHT, its problems, and some solutions. Mechanical Systems and Signal Processing, 22(6), 1374-1394.**

**(t-SNE) Van Der Maaten, L. (2010). Fast Optimization for t-SNE. In In Neural Information Processing Systems (NIPS) 2010 Workshop on Challenges in Data Visualization (Vol. 100).**