

Integrator Guide

ABDM ABHA V3 APIs

Version 1.4

Version History:

Version	Release Date	Created By	Reviewed by	Approved by	Nature of changes
1.0	07-08-2024	Priyanka Varude	Prasad Vishwanath	Sachin Yadav	Document Approved
1.1	19-09-2024	Priyanka Varude	Prasad Vishwanath	Nitesh Jain	Updated document with QR code API details
1.2	04-10-2024	Priyanka Varude	Prasad Vishwanath	Nitesh Jain	Updated Password Uses Cases
1.3	16-12-2024	Nilam Barve	Priyanka Varude	Nitesh Jain	Biometric Login APIs and Forgot ABHA
1.4	28-01-2025	Kushal Pandita	Priyanka Varude	Nitesh Jain	Find ABHA via Biometric, ABHA address Verification via Biometric

Table Of Contents

ABHA APIs	7
1.0 Generate session token.....	7
2.0 Encrypt data (Aadhaar/Mobile/OTP/Password)	8
3.0 ABHA Creation via Aadhaar.....	9
 Step 1: Login via Aadhaar OTP.....	9
 Step 2: Resend Aadhaar OTP.....	11
 Step 3: Enrol ABHA	12
 Step 4: ABHA Mobile Verification	22

Step 5: Email Verification	25
Step 6: ABHA Suggestions and ABHA Address creation	27
4.0 ABHA Creation via Driving License.....	29
5.0 ABHA Creation via Demo Auth	34
6.0 ABHA Creation via Biometrics	36
6.2.1 Create ABHA via FingerPrint	36
6.2.2 Create ABHA via FaceAuth	43
6.2.3 Create ABHA via IrisAuth.....	51
7.0 ABHA verification	57
7.1 Login via Aadhaar OTP	57
7.2 Login via Aadhaar Number	61
7.3 Login via Abha OTP	66
7.4 Login via Mobile OTP.....	69
7.5 Login via Biometric	75
7.5.1 Login via FaceAuth	75
7.5.2 Login via FingerprintAuth	79
7.5.3 Login via IrisAuth	84
7.6 Find ABHA	89
7.6.1 Search ABHA using Mobile.....	89
7.6.1.1 Search ABHA.....	89
7.6.1.2 Generate OTP	90
7.6.1.3 Verify OTP.....	91
7.6.2 Search ABHA using Aadhaar	95
7.6.2.1 Search ABHA.....	96
7.6.2.2 Generate OTP	97
7.6.2.3 Verify OTP.....	99
7.6.3 Search ABHA using Biometrics	102
7.6.3.1 Search ABHA using Biometric (Face).....	102
7.6.3.1.1 Search ABHA	102

7.6.3.1.2 Generate OTP.....	103
7.6.3.1.3 Verify OTP.....	105
7.6.3.2 Search ABHA using Biometric (Fingerprint)	112
7.6.3.2.1 Search ABHA	112
7.6.3.2.2 Generate OTP.....	114
7.6.3.2.3 Verify OTP	115
7.6.3.3 Search ABHA using Biometric (IRIS)	120
7.6.3.3.1 Search ABHA	120
7.6.3.3.2 Generate OTP.....	122
7.6.3.3.3 Verify OTP	123
8.0 Update Profile	127
8.1 Update Mobile.....	127
8.2 Update Email	130
8.3 Delete/Deactivate ABHA Number	131
8.3.1 Delete ABHA Via Aadhaar	131
8.3.2 Delete ABHA Via ABHA OTP	134
8.3.3 Delete ABHA Via Password.....	137
8.4 Deactivate ABHA Number.....	139
8.4.1 Deactivate ABHA Via Aadhaar	139
8.4.2 Deactivate ABHA Via ABHA OTP	142
8.4.3 Deactivate ABHA Via Password.....	145
8.5 Re-activate ABHA Number	147
8.6 Re-KYC	150
9.0 Get Profile	153
10.0 Generate QR Code	164
11.0 Generate ABHA Card	164
12.0 Forgot ABHA number.....	165
12.1 Recover via Aadhaar OTP	165
12.2 Recover via Mobile OTP.....	169

13.0 Benefit API's	174
13.1 Create ABHA using Aadhaar	174
Step 2: Enrol ABHA	176
13.2 Create ABHA via Biometric	182
13.2.1 Create ABHA via FingerPrint	182
13.2.2 Create ABHA via FaceAuth.....	191
13.2.3 Create ABHA via IrisAuth.....	201
13.3 Link OR Delink ABHA With Benefit Name.....	207
13.3.1 Link ABHA With Benefit Name.....	207
13.3.2 De-link ABHA With Benefit Name	210
13.4 Update ABHA Profile Details	212
13.4.1 Update Mobile.....	212
13.4.2 Update Profile.....	214
13.4.3 Update Profile.....	215
13.5 Search Benefit Details	217
13.5.1 Search by Aadhaar	217
13.5.2 Search by Health Id Number	218
13.5.3 Search	219
13.6 Find ABHA (For Govt Entity).....	220
13.6.1 Search ABHA using Mobile.....	220
13.6.1.1 Search ABHA.....	220
13.6.1.2 Generate OTP.....	222
13.6.1.3 Verify OTP.....	223
13.6.2 Search ABHA using Aadhaar	226
13.6.2.1 Search ABHA.....	226
13.6.2.2 Generate OTP.....	228
13.6.2.3 Verify OTP.....	229
13.6.3 Search ABHA using Biometrics	235
13.6.3.1 Search ABHA using Biometric (Face)	235

13.6.3.1.1 Search ABHA	235
13.6.3.1.2 Generate OTP	236
13.6.3.1.3 Verify OTP	238
13.6.3.2 Search ABHA using Biometric (Fingerprint)	244
13.6.3.2.1 Search ABHA	244
13.6.3.2.2 Generate OTP	246
13.6.3.2.3 Verify OTP	247
13.6.3.3 Search ABHA using Biometric (IRIS).....	251
13.6.3.3.1 Search ABHA	251
13.6.3.3.2 Generate OTP	253
13.6.3.3.3 Verify OTP	254
13.7 Child ABHA (These APIs are intended for use only by specific Government	260
integrators, approved by NHA).....	260
13.7.1 Create ABHA	260
13.7.2 Get Child ABHA	262
13.7.3 Update Child ABHA	263
14.0 ABHA Address Verification	265
14.1 ABHA Address Verification via Mobile OTP	265
14.2 ABHA Address Verification via Aadhaar OTP	272
14.3 ABHA Address Verification via Biometric	278
14.3.1 ABHA Address Verification via Biometric (Face)	278
14.3.2 ABHA Address Verification via Biometric (Fingerprint)	284
14.3.3 ABHA Address Verification via Biometric (Iris)	290
14.4 Profile	297
14.4.1 Get ABHA address ABHA Profile	297
14.4.2 Get ABHA address ABHA card.....	299
14.4.3 Get QR Code.....	300

ABHA APIs

Environment URLs {{base_url}}:

SBX: <https://abhasbx.abdm.gov.in/abha/api>

Prod: <https://abha.abdm.gov.in/api/abha>

Note: Base URLs for ABHA Address verification (applicable to section 12 of this document only):

SBX: <https://abhasbx.abdm.gov.in/abha/api/v3/phr/web>

PROD: <https://phr.abdm.gov.in/api/phr/web/v3>

1.0 Generate session token

This API generates Session token using client_id and client_secret.

V3 Session:

Sandbox Session URL <https://dev.abdm.gov.in/api/hiecm/gateway/v3/sessions>

Production Session URL <https://apis.abdm.gov.in/api/hiecm/gateway/v3/sessions>

Method: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-CM-ID	{{X_CM_ID}}	Yes	This value depends on the environment where API is getting executed. Eg. SBX or PROD. For SBX- sbx and for PROD- abdm

Request Body:

```
{
  "clientId": "{{ClientId}}",
  "clientSecret": "{{ClientSecret}}",
  "grantType": "client_credentials"
}
```

```
Response
Code: 200 OK

{
  "accessToken":
"eyJhbGciOiJIUzI1NiIsInR5cCIgOiAiSldUiiwia2lkiiA6ICJBbFJlNVdDbThUbTIFI9JZk85ejA2aWVjQ3Y1MXBLS0ZrbkdXlRCdkswnO..hmJ4tmAbpRd8tPMmzTdQvzGhxE7rQcDJEow2MrL3W1MhSeZk_CeJGYyHh7NDgFzzfT39oQiUAYf06buXi1KWX8xptkrQk1uitgNecqw8Le15wufs2Z8dFawsYJtmVHPP_2rDqvUhSeTADGYBp-84tXkpslgp2tjkjsDOOkQsZtpJLaV_vHkkLi7QRncl2KG2IfHDS8yebcpqi-MMGYCdmyb42Po5xmQ9Lzw6lwGJzUsFxkbIQ22m3MaYqXYt4ZOPfxYcunr7ppMhNIdJVE55_CMuY-NfWrbaTk6iLA-yOPCQ-vyyu9l1pN2iwyJbtMotEtV065Uqek0oQ0py2Mw",
  "expiresIn": 1200,
  "refreshExpiresIn": 1800,
  "refreshToken":
"eyJhbGciOiJIUzI1NiIsInR5cCIgOiAiSldUiiwia2lkiiA6IClyMWU5NzA4OS00ZTcxLTQyNGEOTAzYS1jOTAyMWM1NmFINWYifQ.eyJleHAiOiEje3MTA0MDM1NjlsImhdCl6MTcxMDQwMTc2MiwiianRpIjoizTQONDgzYzctZDFmYy00ZDg5LTkyNzctOTUxYzIOMDNhYzUwliwiaXNzljoiHR0cHM6Ly9kZXRYubmRobS5nb3YuaW4vYXV0OAc9yZWFSbxMVY2VudHJhbC1yZWdpY2R3Y2RpeSIsImF1ZCI6Imh0dHBzOi8vZGV2Lm5kaG0uZ292LmluL2F1dGdvcmVhbG1zL2NlbnRyYWwtcmVnaXN0cnkiLCJzdWIiOiIwNmJkNGZlNy04NjEyLTRiZmEtYTlNS1iMDdiZmFjZmU1M2QiLCJ0eXAiOiJSZWZyZXNoliwiYXpwIjoiaGVhbHRoaWQtYXBpliwic2Vzc2lvbl9zdGF0ZSI6IjBlNDIjZDBjLWQ0OWQtNDA0Yi1hZWY3LWRIZGY3NDRINTA1ZCIsluNjb3Blljoib3BlbmklIGVtYWIsIHBvb2ZpbGUifQ.NAMWFGblqmGHaWa__9WnJPvglyZdCAE9AwxyUZ5UrM",
  "tokenType": "bearer"
}
```

Step 1 : To encrypt any data(Aadhaar/Mobile/OTP/Password etc) public key can be generated using below API

Request: GET

GET

https://abhasbx.abdm.gov.in/abha/api/v3/profile/public/certificate

Send

Params

Auth

Headers (10)

Body

Scripts

Settings

Cookies

none

This request does not have a body

Response

```

{
  "publicKey":
    "MIICljANBgqhkiG9w0BAQEFAAOCAg8AMIICGgKCAgEASTWB95C5pHLXiYW59qyO4Xb+59KYVm9Hywbo77qETZVAyc6VlsxU+UWhd/k/YtjZibCznB+HaXWX9TVTFs9Nwgv7LRGq5uLczpZQDrU7dnGkl/urRA8p0Jv/f8T0MZdFWQgks91uFffeBmJOb58u68ZRxSYGMPe4hb9XXKDVsgoSJaRNYviH7RgAl2QhTCwLEiMqlaUX3p1SAc178ZIN8qHXSSGXvhDR1GKM+y2DlyJqlzfik7ID14mDY/I4lcbftib8cv7llkybtjX1AayfZp4XpmIXKWv8nRM488/jOAF81Bi13paKgpjQUUuwq9tb5Qd/DChytYgBTBTJFe7irDFCmTlCqPr8+IMB7tXA3YXp3z605Z6cGoYxezUm2Nz2o6oUmarDUntDhq/PnkNergmSeSvS8gD9DHBuJkZWZweG3xOPXiKQAUBr92mdFhJGm6fitO5jsBxgpmulxpG0oKDy9IAOLWSqK92JMcbMNHn4wRikdl9HSiXrrl7fLhJYTbyU3I4v5ESdEsayHXuiwO/1C8y56egzKSw44GAtEpbAKTNEEFK5H5R0QnVBIXOvfeF4tzGvmkfOO6nNXU3o/WAdOyV3xSQ9dqLY5MEL4sJCGY1iJBIAQ452s8v0ynJG5Yq+8hNhsCVnklCzAlsIzQpnSVDUVEzv17grVAw078CAwEAAQ==",
  "encryptionAlgorithm": "RSA/ECB/OAEPWithSHA-1AndMGF1Padding"
}

```

Step 2 : once public key is generated data can be encrypted using below third party API
[“https://www.devglan.com/online-tools/rsa-encrypt”](https://www.devglan.com/online-tools/rsa-encrypt)

Step 3: Select Cipher type as **RSA/ECB/OAEPWithSHA-1AndMGF1Padding**

3.0 ABHA Creation via Aadhaar

Create via Aadhaar OTP

Step 1: Login via Aadhaar OTP

This API accepts encrypted Aadhaar Number and then Generates OTP for Aadhaar linked mobile number.

V3 URL: {{base_url}}/v3/enrollment/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	Empty	No	Transaction Id is Mandatory to identify the unique transaction for ABHA enrolment. This chains all the steps to enrol in ABHA. Transaction Id will be returned after a successful OTP transaction.
Scope	abha-enrol	Yes	Defines the scope of the current action of the API, following are the values that can be used. ABHA_ENROL("abha-enrol"), DL_FLOW("dl-flow"), MOBILE_VERIFY("mobile-verify"), EMAIL_VERIFY("email-verify"),
loginHint	aadhaar	Yes	Type of login
loginId	Encrypted Aadhaar number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	aadhaar	Yes	OTP system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "txnId": "", "scope": ["abha-enrol"], "loginHint": "aadhaar", "loginId": "{{Aadhaar_encrypted_Output}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "1234567890:20211216223812", "message": "OTP is sent to Aadhaar registered mobile ending xxx001" }</pre>

Step 2: Resend Aadhaar OTP

This API resends Aadhaar OTP

V3 URL: {{base_url}}/v3/enrollment/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	Empty	No	Transaction Id is Mandatory to identify the unique transaction for ABHA enrolment. This chains all the steps to enrol in ABHA. Transaction Id will be returned after a successful OTP transaction.
Scope	abha-enrol	Yes	Defines the scope of the current action of the API, following are the values that can be used. ABHA_ENROL("abha-enrol"), DL_FLOW("dl-flow"), MOBILE_VERIFY("mobile-verify"), EMAIL_VERIFY("email-verify"),

loginHint	aadhaar	Yes	Type of login
loginId	Encrypted Aadhaar number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	aadhaar	Yes	OTP system to verify hlu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-enrol"], "loginHint": "aadhaar", "loginId": "{{AadhaarencryptedOutput}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "0658241c-1ad1-4703-8fc2-512a5fb8754b", "message": "OTP sent to Aadhaar registered mobile number ending with *****5852" }</pre>

Step 3: Enrol ABHA

API accepts transaction ID (previous step response) and encrypted OTP along with a primary mobile number for ABHA.

V3 URL: http://{{base_url}}/v3/enrollment/enrol/byAadhaar

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
authData	Empty	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrolment. This chains all the steps to enrol in ABHA. Transaction Id will be returned after a successful OTP transaction.
authMethods	Otp	Yes	Defines the authentication method used for enrolment, following are the values that can be used. OTP("otp"), PI("pi"),
timeStamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
txnId	Actual Transaction Id	Yes	Transaction Id received as a response to request/mobileOrEmailOTP API
otpValue	Encrypted OTP value	Yes	
Mobile	Primary Mobile number	Yes	If the user wants to use a mobile number which is other than the mobile number which is linked with the Aadhaar number
Consent	-	Yes	
Code	abha-enrollment	Yes	Consent code for creating AHBA number
Version	1.4	Yes	Consent version for creating ABHA number

Note: mobile parameter in the below request is referred to as the primary mobile number **V3 Request**

Body:

Request Body

```
{
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "txnId": "{{lastResponseTxnId}}",
      "otpValue": "{{OTP_encryption}}",
      "mobile": "{{mobile_number}}"
    }
  },
  "consent": {
    "code": "abha-enrollment",
    "version": "1.4"
  }
}
```

V3 Response

a) If the primary mobile number matches with Aadhaar linked mobile number.

Response
Code: 200 OK

[illegible]

b) If the primary mobile number is different from Aadhaar linked mobile number.

Response
Code : 200 OK
<pre>{ "message": "Account created successfully", "txnid": "2ec82835-9314-4296-acc0-5d526371998d", "tokens": { "token": "eyJhbGciOiJIUzUxMiJ9.eyJpc0t5Y1ZlcmImaWVklp0cnVlCjZdWiiOiw5MS0xNjAxLTQ1NDgtMTM4MCIslmNsaWVudElkloiYWJ oYS1wcm9maWxlfWwcC1hcGkiLCJzeXNOZW0iOiBQkhlBU4iLCJhY2NvdW50VHlwZSI6InN0YV5kYXJkIiwibW9iaWxlfjpuZDxlcjYmhhTnV tYmVmljoiOTETMTYwMS00NTQ4LTEzeODAiLCJwcmVmZXYjZWRBYmhhQWRkcmVzcyl6ljxkMTYwMTQ1NDgxMzgwQHNieCIsInR5cCI6IiRyYW5z YWN0aW5uIiwiaXhwljoxNzE0ODUwNDY2LCJpYXQioEjE3MTU4NDg2NjYsInR4bklkloiMmVjODI4MzUtOTMxNC00Mjk2LWJFjYzAtNWQ1MjYzN ze50THkin0.NXTXyZvRmGVTAeByvPW9rLFhYPASOveshK9fvMFY1X00u0LBjNQ5ZzS50lIOWBCOU6yW5wDCA9a03W59UUGEOjXs9QXQG0C5 eyVWQMSLsuYwxjhMXN0yNhQxFtMiXjZfGfXJEUcsHznT5f0UHZIND82dw- bljZpwFoY_y66tmxpHme7Z5kvGKmiheUKpQBcSw6pj6WzZuA2AVB0w15yLW3LAdsxMZqFTESaCxCIQSjc2HOCgduWQu4L9i5rJLEn8Rn4yx_DDj gtxAtP6Ggem5jy-82qQausJUyC30kvuExY5BFpvpnXHarJoAtmkCRwnci_mJf4TLjI8ygfAncXmElZhhwV3TXfhC6glgnbg- YXN6668aOaOGCg8G5tIjjim65yEKJH4bgArhsYJ_0djLKK_UqFjXRPY6CoJ6S_qgNBUVtA1Mw9LOc2Tfj3_P_gKxoBrPz5AA_aYOIQYsnB5TISI4dzN2HaTrV geosYDhphVXNPnHoe_XvoBQwhZ_A-oOpY-j9j2qeRRXOdWiRgl47juFDPO_ze_iBBcGyXZqdfdmf35Hk3JXbe1_Y3Qs12PG8dXB9vgh- h3fLkxH_swTMR13JJYWNcU9CAFXbcirTEDTWngdh2JZNDOb0z7_Q68_L8rxGM49kZCQcaVWr5jPlPsGvJ7Ban3Ur8kk", "expiresIn": 1800. } }</pre>

"refreshToken": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI5MS0xNjAxLTQ1NDgtMTM4MCIslmNsaVVudElkljoiYWJoYS1wcm9maWxlLWFwcC1hcGkiLCJzeXN0ZW0iOiJBQkhBLU4iLCJ0eXAiOiJZSWZyZXNoliwiZXhwIjoxNzE3MTQ0NjY2LCJpYXQiOiE3MTU4NDg2NjZ9.feDbP3ZZ5rjyVHVNTjt2MkecmaRMoorscip-812w899srCCKvdqawh2dwyDsJLOJS6O7tw1g5Bu7qQJdr3GxfQDFzGV3rejfVDNyuq8ZRzyUrrWR3x3P54JbZ51msY0W166arm0SSypaKKitaXsc

[illegible]


```
"email": null,  
"phrAddress": [
```

```
    "91160145481380@sbx"
  ],
  "address": "165/2 Plot no-25 Mangalai Colony Shahunagar, Godoli, Satara, Maharashtra",
  "stateCode": "27",
  "pinCode": "415001",
  "abhaType": "STANDARD",
  "stateName": "MAHARASHTRA",
  "districtName": "SATARA",
  "ABHANumber": "91-1601-4548-XXXX",
  "abhaStatus": "ACTIVE"
},
"isNew": true
}
```

Note: If the primary mobile number matches with Aadhaar linked mobile number then mobile is saved in DB and if the primary mobile number is different from Aadhaar linked mobile number then mobile is not saved and its value is null.

Step 4: ABHA Mobile Verification

a. Send OTP

This API generates OTP for mobile verification (Mobile number not linked with Aadhaar).

V3 URL: {{base_url}}/v3/enrollment/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session api

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	Actual Transaction Id	Yes	Transaction Id received as a response to /enrollment/enrol/byAadhaarAPI

Scope	abha- enrol mobile- verify	Yes	Defines the scope of the current action of the API, following are the values that can be used. ABHA_ENROL("abha-enrol"), DL_FLOW("dl-flow"), MOBILE_VERIFY("mobile-verify"), EMAIL_VERIFY("email-verify"),
loginHint	mobile	Yes	
loginId	Encrypted Mobile number	Yes	
otpSystem	abdm	Yes	OTP system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "txnId": "{{txnId}}", "scope": ["abha-enrol", "mobile-verify"], "loginHint": "mobile", "loginId": "oEIWeeEnSg4tzWQQ8iPedMACyd/+6pfmdPsnwADBwaj26wWM0emiAHZRVMV0lr8W21oa6ai22CxY2XatoT8DhWnQEIU/ g86QaPsqlr/ksMaSBsKSe0TIPwPasB1RwCmfstelj+Zg0yNplvD/sYqyBFvSLHka7FSqk4/Djp4PK3PCji6He8y3mZXy7rNYBBbo7 9VsZQkgpoiQCzaynZzzW2iEwEmpGmZ0yJz0L9ynjQH/sVvzpljPz5BUIcnn5Qw5nrPlzR764VcBP15MGjdFleNrDn/m1WGaYlQg 7c+AGelcI/3XRjoJvQr722xB0aicJa631Qy3CIQyoX4hJgMv1vgLfdRHB4AsvnbobfZmHngnCuYnBah44tclSZTOyET3nqP6Y/zPHh mPh4CoMu0DAli3dBKKj96SHWVd44JostStCq6hUDKDrNuzNPzdeQPGFcu+B24LuvfKglQR4DGyhwCH6Jr17Atvk/vAi7fxCPpX PLxPoXj9JRJmsp3Gfe3MjtSddpZbGNG24ds47ijhcysdchwuXzRq6nW/ij4k09qj8WQO1KG7a4b7SLx7OCPoQqiZQFzV+wGf FrNbqZtZ1toAKGKNu7HS5iY5RACYwUffhZvbpu/hUNblsda+zxKzJ3O3zOAJYMie4SBD0W+ZaNem8hQao3brsE5WqxqeyHGxE iDPpA=", "otpSystem": "abdm" }</pre>

V3 Response:

Response
<pre>{ "txnId": "3ec0e997-fd1b-47cd-b0f5-60199d334e73", "message": "OTP sent to mobile number ending with *****3372" }</pre>

b. Verify OTP

This API verifies via Mobile OTP.

V3 URL: {{base_url}}/v3/enrollment/auth/byAbdm **V3 Request:** POST **V3**

Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endto-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session api

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
authData	Empty	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrolment. This chains all the steps to enrol in ABHA. Transaction Id will be returned after a successful OTP transaction.
authMethods	Otp	Yes	Defines the authentication method used for enrolment, following are the values that can be used. OTP("otp"), PI("pi"),
timeStamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
txnId	Actual Transaction Id	Yes	Transaction Id received as a response to request/mobileOrEmailOTP API
otpValue	Encrypted OTP value	Yes	

V3 Request Body:

Request Body

```

{
  "scope": [
    "abha-enrol",
    "mobile-verify"
  ],
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "timeStamp": "{{current_timestamp}}",
      "txnId": "{{txnId}}",
      "otpValue":
        "WyJtOAFEE5shyS5gizaNxl3rGNahQe6cO8Ada+gFBKm0PjWLeVpElh1hsd8GzP2GlvYB6flEstF1aUjqYi9B275EWdpqqTchVn13
        X0zI94SBnEFR6VcdJ35OQaey1JAdldcVAvaAQbbb7M2ih+mLuQ3Y3UsHynt4cUcH5L76Wilk4s2zfB9GZ7PpRPWFJWGJat9LdAs
        wX1H41Ce7PP3Fqp/hs3yhZkEYF25VeESBZYQnuCNtdoy+S+D+dPcYBJKB7Ehwe+o+18F7tcS+Cqj20LQRHGnLWE39A1nXNxc
        kEVdUcoZJA8+otLNFvjINrSS0YHu0uud2UxsCkj1HfM6SLkQzu4QEdllkKB10AtpGFaAbAk4NiKyAJSQsneLRsV66fDE7D7RZjJVlrs
        awxJeqfrTr4xryR+NCEl+90o74T2Im3K/IFxYuMLnUza66pIM0/9NRkk772p9142/F43pY/ntWle8UoZGODUNQySRJuhOhK8JW
        ExZxdocwgwJI7fo9d3SFQ3gIHfsDswtkyDxWLikrVSWvAnaqoBCKa+WlrXx+Ey76ZtPxGjURZ0OtIdMUfhK31X6SzfWlkzOIQUm
        3cAaLeJaLYd0hg+QewbDP6k1nWzZiAap2jpkfUnLunJVRfeSyzRE6tEgvdqT/jUI62S3ApJUrLQQgFAPp3VjUU84="
    }
  }
}

```

V3 Response:

Response
<pre> { "txnId": "366c8f41-4ef8-49ee-b73a-2e3e44613086", "authResult": "success", "message": "OTP verified successfully" } </pre>

Step 5: Email Verification

V3 URL: {{base_url}}/v3/profile/account/request/emailVerificationLink

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile emaillinkverify	Yes	Defines the scope of the current action of the API, following are the values that can be used. abha-profile email-linkverify
loginHint	email	Yes	Type of login
loginId	Encrypted email idr	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "email-link-verify"], "loginHint": "email", "loginId": "pb2Rf4GQ3zq5rlxXWgpn8Td9HMH0sJlb/SbN+6CHpylD422FxcJPHgo9Zyc3SESSetu60JFga4729tdi4BPU0mW053M6d2kC3E W8cd917VNP0hett79+S80JG6VdWYsb3pzF3G7GoGaCEqcmr6pt5ZX2NNkN9YT5f9QXqSUkrNA9/RJVUzUy+KuXo0MbV35 nOU6IO5Bs8Bly+Ggs96kogiTf8iajlxheo002nVU1Ln6Q9rjgLF11ibyEJ5/wvOp8FvSA3Ed8+CodQpkWeiJbRFokZCMHx9ONII08 Zbr0brbCGQsZkfQOjRZswgS8vV3lJded1Vx7qY3bqb/QWZSYLWgXN61TFU4EZ/vq1jix0YasluuxjijWUzTV43qDL/AJPKLnsOhGis 1G+quo7WKzTCAAekjEEApZNrZL5RYcn3gykXfbNJaSu82tHO4Bke9uXc6ON91QcAhNHeOJFc3zPvftCQu59YYunuiaM3YmX MCEvtaOYyaO1mLd+OEDCrWTeEyPZCKRf32W0TXjhoTN7UcC+t94hWWv2dAahbVzpMiS+NXVoAMj66/l/7wbUqsem/aK+3j /tveftXJTyREg7/wjHwBrjUdt8hMFsbinsYs+S7Bpus65Oafqrost5MDdxlu+0g8C3ce0EUDF76sklA1S885gN3KMsqk5cC9hY=", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200
No Response

Step 6: ABHA Suggestions and ABHA Address creation**a) Get ABHA Address Suggestion**

This API returns ABHA address suggestion.

V3 URL: {{base_url}}/v3/enrollment/enrol/suggestion

V3 Request: GET

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
Transaction_Id	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA.
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters: NA

V3 Request body: NA

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "daa3ec62-60b2-4d06-8dc0-16e38c38d102", "abhaAddressList": ["anchalsing1", "anchal1995", "anchal.singh", "anchal299", "singh299"] }</pre>

b) Create Custom ABHA Address.

API is used to create Custom ABHA Address against that transaction ID.

V3 URL: {{base_url}}/v3/enrollment/enrol/abha-address

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA. Transaction Id will be returned after successful ABHA Address creation

abhaAddress	String	Yes	Custom ABHA Address that the user wants to create
Preferred	Number	Yes	The accepted value is "1" which is used for setting the ABHA Address as the Preferred one.

V3 Request Body:

Request Body
<pre>{ "txnId": "e4a7ebfa-18c5-481f-acd2-a6dc1165ae46", "abhaAddress": "gaurav_22101991", "preferred": 1 } </pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "e4a7ebfa-18c5-481f-acd2-a6dc1165ae46", "healthIdNumber": "91-6285-4575-XXXX", "preferredAbhaAddress": "gaurav_22101991" }</pre>

4.0 ABHA Creation via Driving License

Step 1: Generate OTP

This is an API that will be invoked to send OTP to a given encrypted mobile number and create transaction id.

V3 URL: {{base_url}}/v3/enrollment/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds

Authorization Token	{{accesstoken}}	Yes	Token generated from session api
---------------------	-----------------	-----	----------------------------------

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
scope	abha-enrol mobileverify dl-flow	Yes	Defines the scope of the current action of the API
loginHint	"mobile"	Yes	Type of login
loginId	Encrypted mobile number	Yes	Actual value of login type. This needs to be RSA encrypted using a Public key
otpSystem	"abdm"	Yes	OTP system to verify hiu/hip/phr login

V3 Request Body:

Request body
<pre>{ "scope": ["abha-enrol", "mobile-verify", "dl-flow"], "loginHint": "mobile", "loginId": "{{Mobile_Encryption}}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "34935c59-f57e-4304-a318-3aa0b146c426", "message": "OTP is sent to Aadhaar registered mobile ending *****3603" }</pre>

Step 2: Verify Mobile OTP

This API will verify mobile OTP and update details in the transaction table.

V3 URL: {{base_url}}/v3/enrollment/auth/byAbdm

V3 Request: POST

V3 Request Headers: