

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
scope	search-abha	Yes	Search scope
Mobile	Mobile number	Yes	User mobile number

V3 Request Body:

Request Body
<pre>{ "scope": ["search-abha"], "mobile": "{{Mobile_Encryption}}" }</pre>

V3 Response:

```
[
  {
    "txnId": "d0660ae0-1798-4e42-8e07-33eea4a3824d",
    "ABHA": [
      {
        "index": 1,
        "ABHANumber": "91-5259-8743-XXXX",
        "name": "Narayanan Madaswamy",
        "gender": "M"
        "kycVerified": "true",
        "authMethods":
          [
            "AADHAAR_OTP",
            "MOBILE_OTP",
            "AADHAAR_BIO",
            "DEMOGRAPHICS"
          ]
      }
    ]
  }
]
```

7.6.3.3.2 Generate OTP

V3 URL: {{base_url}}/v3/profile/login/request/otp **V3 Request:** POST **V3 Request Headers:**

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-iris-verify search-abha	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), AADHAAR-BIO-VERIFY("aadhaar-bio-verify") AADHAAR-FACE-VERIFY("aadhaar-face-verify") AADHAAR-IRIS-VERIFY("aadhaar-iris-verify") EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
loginHint	index	Yes	Index of ABHA number given in search API response.
loginId	Index_Encryption	Yes	Actual value index generated in search API. This needs to be RSA encrypted using public key
otpSystem	aadhaar	Yes	Otp system to verify hiu/hip/phr login, following are the values can be used. AADHAAR("aadhaar"), ABDM("abdm"),
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-login", "search-abha", "aadhaar-iris-verify"], }</pre>

```
"loginHint": "index",
"loginId": "{{Index_Encryption}}",
"otpSystem": "aadhaar",
"txnId": "{{txnId}}"
}
```

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "775b6a11-ea05-49e2-8661-f9aa855cad34", "message": "IRIS authentication request successfully sent. " }</pre>

7.6.3.3.3 Verify OTP

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
scope	abha-login aadhaar-iris-verify	Yes	Defines the scope of the current action of the API

authMethods	"iris"	Yes	Defines the authentication method used for enrolment, following are the values that can be used OTP("otp"), PI("pi"), FACE("face") BIO("bio") IRIS("iris")
txnId	"3585baee-eab3-4651-b2cb215ee4f4d181"	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll ABHA. Transaction Id will be returned after a successful OTP transaction.
irisAuthPid	Generated Iris AuthPid Value	Yes	Iris auth pid can be generated from the Biometric systems

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-login", "aadhaar-iris-verify"], "authData": {"authMethods": ["iris"], "iris": { "txnId": "{{otpTxnId}}", "irisAuthPid": "{{irisAuthPid}}" } } }</pre>

V3 Response:

Response
200 OK

[illegible]

1VmI9QWnba5+28U2Eip++Xnvn61sW+oW04QxzI28/Kdw5oQFoLinbfalyAcE07rQA0LRin4pwWgBmKXFPC0uKYEeKMJVJto
20Aef3TZc1VqecguahpDAUTFLSAKM460Vh6/qbWkQjJdnuD/n3oSuBX1nXGgIkghkKbMcpG5Nctc6jd3P8ArZ3ftyaqvlXkZjyS
c1GTgHmtVGwD+nJjZThkd+1M5UBsU0SfNkimBp22p3EBUhz8vTNXIdYUix3xSuhGSdrEdaxUbeuOmKcvJ+9zRYDsbHxrqsFx
Gz3jSoTtkV29+lehaL4nTUMJIMEgfMRjB759vf3rxNZACDjmtSx1a4snDRu20NuKk0nED32Mh1BU5GM5qXGK5Twh4pg1mP
7K6mO7ReV5wwHGRn+VdeF4rN6CI8e1AqXbmkK47UANC0bakC0u2i4HmMn3jUdPmyJDxTBSGLS0lGaAlrq4S2geWRgqK
MkmvPNW1P7fdM6AilcKD1rd8Xagu1bJHOeGfB/IVx7cn5fxqorqAE/NmlwD3ojjaRtqjn1rQi01m6559Ku41FsoBSTtBOB60w
xsPcV0cGkqpUsefpVoaZGw5QAdqTKi1TZy0YkXkA4pxXkHOCv1Uelx7vmUY+ITDRosHCcH2p3D2bOVUjB7U4S4PA5rTu9HaB
iyDI9Ky8MmVlwfUyGmtzV0/UpbW5SRZHjbPLISDjvzXsPhrxZYajCYTOyyq2AJW5Yex714TuKnJzVy3lyC245FS1cR9LDDDJmlx
XJ/D7Vm1HQfJlLz2zbG3HJ2nkH+Y/CuurMQm2lxSqOaftoA8suhiSq9X79Nrk1n0MYti7bVJoprjK4oA821NzPdyuzZYsTms9AX
clOpOK2NcjSG+dBnb165qnpNv5lxvl4FaLYaVzTtLJYkHc9zWnFEBiokGOMVct4yT0qZHRBFiKIHGRVvyl2AYpl1KKBU689qzNBi
QAHmrJiUR8Dmmqpl4F5mM7a0iSzNnjGTms65tl5hyozWxNGTkvUMMRNAnqchc27W+4HkZ4plFIA4wvrW5qlurxkEYPUVkr
s20lvKA9PWTEc8lZne/DiaWDW1SNvkmRg6no2ASK9fAyK8v8AAMa3t5A8ccUP2RckA5Lkjb9TqXqK5xzWUtyBQKWilqQPMt
RYFjWYTV/UM+ZWfjFNjDNLSGjOOKAOE8TWGG/bIO1yWU/WnaVElrMzNgA1seKrdZrHzgw3RdvYkVl2kfnaXbpnA5z+Zq09C
o7if2EhJHmrrrGXAERwO+aldDhkOGUc9wa0YtF0j4mU47bqdl1NfeLtnclD9FwavrF6DNYsNxFYyBAygHoQa1r08jeXazZX2
qHY0V+pDdPNbnclZz61mnXLpGktCp5xgZro7ualpwAynoKw5760VsMglB5G3NWMiJKQwasZT/Akps+wqOO/YPiRCVJ4Irvs9
S0x4cK6qc4C7lB/L0ac6W8xyu049etEmrCSfco3NulxavgckcGuRIMdwQO1d0sWxcDp9a5PUbfy72VOh3ZHHY0oEVEdrM4
3k1x5Qfl+zsSFPgdyj/wCv+FetjpXNeB9Jj03w3aMi/PPGsrN655H866cCpk9TIAKXFKBTtSB5hqqhCSeKwpLyJScsK3dXlQxNc
bOpVyDRJ2KSUXZNSjX7oJNU5r+WTgfKPaqxpuOam7KsMnBmiZWJORikgt2jsUCj7o7/WnnpTpEeSJFOXCKuBcUVoA89wVu2
kWHB5UEgHsTjmodMRtPvTc3O2WGMk43Fd/UDryOuemeO1aEMUqrtK8VDqMH7pWlwo61opW2Kcl7mPJ59/qJlLMQtkZ
JO0dhmuq0yNo9u6RSe4FZmnWT3GBEmc9cCuq03SS4AJ2jual6mklkU8UkiZifBqhb289tJKhWOQsQulKXsforW5NaPbk7QS
BTliW5IEJ8aluw3G5hWHh6OynF0dk5wcRyDK56cj6VJHbNBM0hP3jnyOFH0HatXyG3bQ3FSjTlxktk05SuSoWKQbcOBisUrN
p9TiEY5KBmPpzXRG2VB0pptwXmMdm36c1EXZkyjfQ9L0SS3m0e0Nsu2ERhVXGMY4x+laYFc94Mt3h0MF+kkhZee2AP5g
10YFI5pKzsJilXsJr4oJPOD72HfEa4rUoCkrCv6C6bgRiua1mxJbYcm0WmcefskPFTTRlGOahrMsbV61ddi+wqjUkTYwKuG5Udz
UK+Y3HSi4tVulGhY4DDt2ptvJkYzUdxc+WDydx9K0aNkyGz2WNo0Uk0cciE4Ynhhmt7R9ak+zhIDxSlcMmfUcjNcm0Us8gcrkf
yrXtS8UW1InLEY+WnYnmfQ0hqmoX3rCYW7Wp5GAd1WoJ1IDEDck5qoltcNEDJEB7ZGRTo0mibpxQ0NsfU00iB5lpZFKimRT
cDdwfens4bipehaaZASSuDTJLnyk8v+8P5U6RhuwKjdCyZP3c4qTNvXQ9VsLYWljBbjB8tAplGMnuatAVHbv5tvfj/eQH9KnAp
HlxoFPAAp1AjhhUFzbrNGQRU4p1UxnD6rphRiwFc/LGUy8V6fc2aTocjmuN1rThbsSBUNFJnOkUD07inEYpKluzLRYtpsNhqS
SRAXeToOnrVUPtfl61lrKzbmPFbmlwgupJ/kiT2+Y4rVgt7hVDs6K3bFzQ53AgjFWVklJlEmMegp3KTsa4juzGP3qBR371E813E
+I8SGkt/tGcG4GPRhV7awPzEH3FDC6YyGeZ12zRhX9Qc1Nu/OmuV2e4qJXPTNTJCTsWO4NddoHh21u9Phu52kjdjdGAAQDj
B/KuShja4mjhjGXdgq/U8V6taW62tpDbqSVjQICe+B1rN6GU5W2LCrgADoKeBSAU6pMgoopaAOEFOpgNI80cYyzAfU1QEw
PFc14kTMRNXrrX7S3BG8MR2FcqxutG+yqrhaTY0jDbrTCvIRSbagOK8i4OaargHB6VZZPIOapkZYg9a3pu6GWkcFavWSq+SB2r
JUITg8VetplVD8+CRxVjUjatXjce1TMwRetYsMxQevvU4uSx6En9KdhXL7SHfirZOarhmOMkY96fHl2wPu+tSwua+jP8A8TizY9
BOn/oQr1leleRWEgt762kp3Y5FY/QGvU7LUbe7jV43Bz+tZMialWp1NHNOqSApaBS0AeLXXic8iEGsa41O5uSd8hA9BVOIFDZ
oogSseaaMU9I2dsKpJ9q0bfS3fBfnPYf1NEyt7DuZqRs5woJPtVhLF8bnlUAZPeugj0xUXcOT0VR1q39iAVo9q5ZeeOa2VDuLm
OI1Z3spS3jjKmf5mdhztz0HpURi39ua6TxPp5ks7S8CnNvJhvKQ2Bn8wo/GsQJhs461Tjy7F7x1KhR14bketPjChuhBhtV3yQw6
U5LbPbn2pXHykUeMcAn8KsBJGwcY+tWILcDopq9FCvcUXHyLOGOeVstzV8QrEOmTVkAKnygCoipY+UjrlsV2PBjY8lzSvzc2D
uWh2B4lz9w55A9ulZkkZl6V1ngvSXVjtQkBAIAWMEdVHf8f6VVKN3YzqGvaajPbny5T5gBwcjK+tbdvxc3C5Rvw71h3K5bKB
QXO4+4HA/PPFVQp3BijCqlQXQxOhFLWVb6kyELOMjswrTjLSRQyMCK55QcdxHzxDbyztjzjZ7CtW30Rzhp2x/siukgtRGgVFCr
6AYqwl+duK6Y4dbsrmMq2soocCOlFvhn9K0UhwGPzH7dM1ejsGE34xVCctPcbBnaOK2UFFCtYwmlMzD6D0FTbR9oYcZ+m
auwx+XBhfSmW1oDImPzE55quUCCeyiuYZLeQZilXacjpn+tcLdWM1hdPbzKdy/dbGA47Ef59q9MEYxgkZHpvLUdHh1a3Cuds
i/6uTHKn/D2qZ07rQqMrM4CNTirMSgEZFXrvQL/TnPmRGSLtJGMjHuO1QRrXJJNaM3TTJolt0qwCo6CokWp1UAZPAHepLG
8scVKkdW7TTbu75t7d2Xj5iML+Z4rqNN8KRR7ZL9llbr5Q+4Pr6/y9q0jTllmU0jG0Xw82ps8oltOvvJ9Pb3rsZQkaC3QAKo+Y9
Ao9P8/4VO8gQblgMDq/YVklYlDOsCEhfvMe5NdkIKCOeUm2RtSrXgOMDHAq0FyMjtVSdN06SDpV6LbjqR+NO2pjVdTuHH
65pY5TC4ZC0Z79wamlTB6k1CyAjdauOp7iOckilcnH0zVuxtDlFmZeD0yKjtoHvLjp8inGfWtSWYQRiNQOPQVcV1ArahOIISi4
BPA4qjZQ7sHGSe9Q3swe4WMElm7Zrd0y08tQZOCR3oerGMktX5YwcDONUzG4k8uNyMntWreSlgPTGOoNYn2l3kKWq5bP
LdhQ0glCgggAqLl5W6kmr8BWQD5dpA/OotP0whvMmyzHqTWtKkccOxdqg9eOaaQEliBPknJ6HFRyaZYXR/fwQQw6EoCarx
XLpCyKhyj/lmrCXT7yBjavXC9TQ0mAv8AYemKeLG3+mwVbgs7G0UCO2t4sn+BAM0sTulvNkjTn7oxUlxdfzrYysAvoAOp7Clyrs
F2TLtYjYrE/TaphZS2GfJHVU7fU1UnnlitB5jEyP1GensKZHuhtS5PzNzzTslY87XF5sRiscfAUUVuEjvVY4xjHHFpscti7Z5zUt0mAj
8Ek+tIZJ5KlAcA4FMQnGcYI96sRnlccH6VExEc5XC880WAVtxPA69yKhaNgcNBFWIBK5zg+1RMhJIOOe9OwjNSOKtVCR85FZt
9epBCZnGccAdyfiinLRAGh6XJK7XlyMSSHIBHQdq3ry5js4c030oooStG4GEBcapKBhkh6AdzW5YaVHbqG2nPvRRSir6sZpO6
xx9s9qybi4YozPxRRVMRTtBiNifvMeprVsLU8MwBFFFSgNN/LVdzkALWFdXJu9UHQAmNDuwaKKHsBamUyzpvDECn3JlVjzO
AOM0UVQEwJnzjIOCasXgymMA0UVlx1p80W7JqO8TztcHJB5zRRTAkifi4PW05AwOQwx6ZoooEf/2Q=="
}
}
}

8.0 Update Profile

8.1_Update Mobile

Step 1: Generate OTP

This API will generate OTP on provided encrypted mobile number.

V3 URL: {{base_url}}/v3 /profile/account/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile mobile-verify	Yes	Defines the scope of the current action of the API
loginHint	mobile	Yes	Type of login
loginId	Mobile	Yes	Actual value of login type. This needs to be RSA encrypted using a Public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-profile",
    "mobile-verify"
  ],
  "loginHint": "mobile",
  "loginId": "{{Mobile_encryption}}",
  "otpSystem": "abdm"
}
```

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "1234567890:20211216223812", "message": "OTP sent to mobile number ending with *****2418" }</pre>

Step 2: Verify Mobile OTP

V3 URL: {{base_url}}/v3/profile/account/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
---------------	-------	-----------	-------------

Scope	abha-profile mobile-verify	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
timestamp	Actual time, format: "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrolment. This chains all the steps to enrol in ABHA. Transaction Id will be returned after a successful OTP transaction.
otpValue	Encrypted otpValue	Yes	Otp system to verify hiu/hip/phr login

V3 Request Body:

Response
Code: 200 OK
<pre>{ "scope": ["abha-profile", "mobile-verify"], "authData": { "authMethods": ["otp"], "otp": { "txnId": "{{txnId}}", "otpValue": "{{OTP_encryption}}" } } }</pre>

V3 Response:

Response
Code: 200 OK

```
{
  "txnId": "01bb3a4c-4588-4734-aff4-23d3978e50be",
  "authResult": "success",
  "message": "Mobile Number linked successfully",
  "accounts": [
    {
      "ABHANumber": "91-4173-3253-XXXX"
    }
  ]
}
```

8.2 Update Email

V3 URL: {{base_url}} /abha/api/v3/profile/account/request/emailVerificationLink

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA. Transaction Id will be returned after a successful OTP transaction.
Scope	abha-profile email-link-verify	Yes	Defines the scope of the current action of the API
loginHint	email	Yes	Type of login

loginId	Encrypted Email	Yes	Actual value of login type. This needs to be RSA encrypted using a Public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "email-link-verify"], "loginHint": "email", "loginId": "pb2Rf4GQ3zq5rlxXWgpn8Td9HMh0sJlb/SbN+6CHpylD422FxcJPHgo9Zyc3SESSetu60JFga4729tdi4BPU0mW053M6d2kC3E W8cd917VNP0hett79+S80JG6VdWYsb3pzF3G7GoGaCEqcmr6pt5ZX2NNkN9YT5f9QXqSUkrNA9/RJVUzUy+KuXo0MbV35 nOU6IO5Bs8Bly+Ggs96kogiTf8iajlxheo002nVU1Ln6Q9rjgLF11ibyEJ5/wvOp8FvSA3Ed8+CodQpkWeijbRFokZCMHx9ONII08 Zbr0brbCGQsZkfQOjRZswgS8vV3IJded1Vx7qY3bqb/QWZSYLWgXN61TFU4EZ/vq1jix0YasluuxjijWUzTV43qDL/AJPKLnsOhGis 1G+quo7WKzTCAAekjbEEApZNrZL5RYcn3gykXfbNJaSu82tHO4Bke9uXc6ON91QcAhNHeOJFc3zPvftCQu59YYunuiaM3YmX MCeVtaOYyaO1mLd+OEDCrWTeEyPZCkRf32W0TXjhoTN7UcC+t94hWWv2dAahbVzpMiS+NXVoAMj66/l/7wbUqsem/aK+3j /tveftXJTyREg7/wjHWBBrjUdt8hMFsbinsYs+S7Bpus65Oafqrost5MDdxlu+0g8C3ce0EUDF76sklA1S885gN3KMsqk5cC9hY=", "otpSystem": "abdm" }</pre>

V3 Response:

Code: 200 OK
No response

8.3 Delete/Deactivate ABHA Number

8.3.1 Delete ABHA Via Aadhaar

Step 1: Send OTP

V3 URL: {{base_url}}/v3 /profile/account/request/otp

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile, delete	Yes	Defines the scope of the current action of the API. de-activate/delete
loginHint	abha-number	Yes	Type of login
loginId	Encrypted abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	aadhaar	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "delete"], "loginHint": "abha-number", "loginId": "{{AbhaNumber_encryption}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "3917ca6b-1b3a-46a1-b99a-248e925929ff", "message": "OTP sent to mobile number ending with *****4723" }</pre>

Step 2: Verify OTP

V3 URL: {{base_url}}/v3/profile/account/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	Abha-profile delete	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
Timestamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA. Transaction Id will be returned after a successful OTP transaction.

otpValue	Encrypted OTP Value	Yes	Otp system to verify hiu/hip/phr login
----------	---------------------	-----	--

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "delete"], "authData": { "authMethods": ["otp"], "otp": { "txnId": "{{txnId}}", "otpValue": "{{OTP_encryption}}" } } }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "890f35c9-a9d5-4db5-861c-d27c17bd37f5", "authResult": "success", "message": "Your account has been deleted", "accounts": [{ "ABHANumber": "91-8434-1243-XXXX" }] }</pre>

8.3.2 Delete ABHA Via ABHA OTP

Step 1: Send OTP.

V3 URL: {{base_url}}/v3 /profile/account/request/otp

V3 Request: POST **V3**

Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile, delete	Yes	Defines the scope of the current action of the API. de-activate/delete
loginHint	abha-number	Yes	Type of login
loginId	Encrypted abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "delete"], "loginHint": "abha-number", "loginId": "{{AbhaNumber_encryption}}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "3917ca6b-1b3a-46a1-b99a-248e925929ff", "message": "OTP sent to mobile number ending with *****4723" }</pre>

Step 2: Verify OTP

V3 URL: {{base_url}}/v3/profile/account/verify **V3**

Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile delete	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
Timestamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA profile.

otpValue	Encrypted OTP Value	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),
----------	---------------------	-----	--

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "delete"], "authData": { "authMethods": ["otp"], "otp": { "txnId": "{{txnId}}", "otpValue": "{{OTP_encryption}}" } } }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "890f35c9-a9d5-4db5-861c-d27c17bd37f5", "authResult": "success", "message": "Your account has been deleted", "accounts": [{ "ABHANumber": "91-8434-1243-XXXX" }] }</pre>

8.3.3 Delete ABHA Via Password

Step 1: Verify Password.

V3 URL: {{base_url}}/v3/profile/account/verify

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile, delete	Yes	Defines the scope of the current action of the API. delete
authData	authmethods	Yes	Type of authentication method password
reasons		yes	

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-profile",
    "delete"
  ],
  "authData": {
    "authMethods": [
      "password"
    ],
    "password": {
      "password": "aEfgH6qnADmgcJHbxPvbnJuPsiocA5XHvg4uYWFOF6g/6ga+yQAKzVMQZoY31vdr367g3aXu9nbCiYITH9kLYuU3JrnYb29jV7aGEa6ek4luXG9jakddYDIhkqOdrGx4taTCWP+bv2smYtbWW0N5d5SulOtO41ZEhVQlJtYp6008TE5DE/Hcr25MI4p49mzG9oNUQC7ONwDfyhI9sRjRZ1M4ohp7M4+tZAKiS8qSYGVG2bUuraH9+3VMRWXerumyObI3q9vIcbhF0oXMkselJaOTDkVGrRbBYL8LaBeJ48p+XYX6wDds83i2O/C4pL4TFE+XCukmjTfrPXuaWi8qs80kFfL6Gmikp+MJm6HXy9pzfb1pAnGn+qPumqdiVAhedn2vdPjsLDRM6jn+l34RCri/0ePNNbhmQQRVVGXKuDTZUWmAqOSxcUb+Wnc0qMglUrSjVREaag2EcllqWfXV77ZkQgTVgQblTdSbdKXFcIRq9/3AE6lqwIwFe1/6x6t3bVIWL575VeqyazUfkOCu5R44CBsKE8LNXtaZYac5zxc2w5Ee6UlcG2726RaY6XWNiSJ+CZacMM8/8zlcYEZMTZfRmxnbNkgm6BcQ+j7HH9pUpmxK/57glFnVbgGsFG1nbcuz+5Fazd1B96O8ws9qfdwgrmr8RgADY64ROfElZ0M="
    }
  },
  "reasons": [
    "aaaaa",
    "bbbb"
  ]
}
```

```
}
```

V3 Response:

Response	
Code: 200 OK	
<pre>{ "authResult": "success", "message": "Your account has been deleted.", "accounts": [{ "ABHANumber": "91-5555-0357-XXXX" }] }</pre>	

8.4 Deactivate ABHA Number

8.4.1 Deactivate ABHA Via Aadhaar

Step 1: Send OTP.

V3 URL: {{base_url}}/v3 /profile/account/request/otp

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
---------------	-------	-----------	-------------

txnId	Empty	No	Transaction Id is Mandatory to identify the unique transaction for ABHA de-activate.
Scope	abha-profile, de-activate	Yes	Defines the scope of the current action of the API. de-activate/delete
loginHint	abha-number	Yes	Type of login
loginId	Encrypted abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	aadhaar	Yes	Otp system to verify hlu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "de-activate"], "loginHint": "abha-number", "loginId": "{{AbhaNumber_encryption}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "3917ca6b-1b3a-46a1-b99a-248e925929ff", "message": "OTP sent to mobile number ending with *****4723" }</pre>

Step 2: Verify OTP

V3 URL: {{base_url}}/v3/profile/account/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile, de-activate	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
Timestamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA. Transaction Id will be returned after a successful OTP transaction.
otpValue	Encrypted OTP Value	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),
reasons		Yes	

V3 Request Body:

Request Body

```

{
  "scope": [
    "abha-profile",
    "de-activate"
  ],
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "txnId": "{{txnId}}",
      "otpValue": "{{OTP_encryption}}"
    }
  },
  "reasons": ["aaaaa", "bbbb"]
}

```

V3 Response:

Response
Code: 200 OK
<pre> { "txnId": "890f35c9-a9d5-4db5-861c-d27c17bd37f5", "authResult": "success", "message": "Your account has been de-activated", "accounts": [{ "ABHANumber": "91-8434-1243-XXXX" }] } </pre>

8.4.2 Deactivate ABHA Via ABHA OTP

Step 1: Send OTP.

V3 URL: {{base_url}}/v3/profile/account/request/otp

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds

X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	Empty	No	Transaction Id is Mandatory to identify the unique transaction for ABHA deactivation.
Scope	abha-profile, deactivate	Yes	Defines the scope of the current action of the API. de-activate/delete
loginHint	Abha-number	Yes	Type of login
loginId	Encrypted abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "de-activate"], "loginHint": "abha-number", "loginId": "{{AbhaNumber_encryption}}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK

```
{
  "txnId": "3917ca6b-1b3a-46a1-b99a-248e925929ff",
  "message": "OTP sent to mobile number ending with *****4723"
}
```

Step 2: Verify OTP

V3 URL: {{base_url}}/v3/profile/account/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	Abha-profile de-activate	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
Timestamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA enrollment. This chains all the steps to enroll in ABHA. Transaction Id will be returned after a successful OTP transaction.

otpValue	Encrypted OTP Value	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm")
reasons		Yes	

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-profile", "de-activate"], "authData": { "authMethods": ["otp"], "otp": { "txnId": "{{txnId}}", "otpValue": "{{OTP_encryption}}" } }, "reasons":["aaaaa","bbbb"] }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "890f35c9-a9d5-4db5-861c-d27c17bd37f5", "authResult": "success", "message": "Your account has been de-activated", "accounts": [{ "ABHANumber": "91-8434-1243-XXXX" }] }</pre>

8.4.3 Deactivate ABHA Via Password

Verify Password.

V3 URL: {{base_url}}/profile/account/verify

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
X-token	Bearer X-token	Yes	X-token of user, user can get X-token after login to the system
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-profile, de-activate	Yes	Defines the scope of the current action of the API. de-activate/delete
authData	authmethods	Yes	Type of authentication method password
reasons		yes	

V3 Request Body:

```
{
  "scope": [
    "abha-profile",
    "de-activate"
  ],
  "authData": {
    "authMethods": [
      "password"
    ],
    "password": {
      "password": "aEfgH6qnADmgcJHbxPvbnJuPsiocA5XHvg4uYWFOF6g/6ga+yQAKzVMQZoY31vdr367g3aXu9nbCiYITH9kLYuU3JrnYb29jv7aGEa6ek4luXG9jakddYDIhkqOdrqX4taTCWP+bv2smyTbWW0N5d5SulOtO41ZEhvQLjtYp6008TE5DE/Hcr25MI4p49mzG9oNUQC7ONwDfyhI9sRjRZ1M4ohp7M4+tZAKIS8qSYGVG2bUuraH9+3VMRWXerumyObI3q9vIcbhF0oXMkseIJaOTDkVGrRbBYL8LaBeI48p+XYX6wDds83i2O/C4pL4TFE+XCukmjTfrPXuaWi8qs80kFfL6Gmikip+MJjm6HXy9pzfb1pAnGn+qPUmqdiVAhedn2vdPjsLDRM6jn+I34RCri/0ePNNbhMQRVVGXKuDTZUWmAqQ5xcUb+Wnc0qMgIUrsjVREaag2EcllqWfXV77ZkQgTVgQblTdSbdKXFclRq9/3AE6lqwlwFe1/6x6t3bVIWL575VeQyazUfkOCu5R44CBsKE8LNXtaZYac5zxc2w5Ee6UlcG2726RaY6XWNI SJ+CZacMM8/8zlcYEZMTZfRmxbnKgm6BcQ+j7HH9pUpmxK/57glFnVbgGsFG1nbcuz+5Fazd1B96O8ws9qfdwgrmr8RgADY64ROfElZ0M="
    }
  },
  "reasons": [
    "aaaaa",
    "bbbb"
  ]
}
```

```
}  
}
```

V3 Response:

Response
Code: 200 OK
<pre>{ "authResult": "success", "message": " Your account has been de-activate" "accounts": [{ "ABHANumber": "91-5555-0357-XXXX" }] }</pre>

8.5 Re-activate ABHA Number

Step 1: Send OTP.

V3 URL: {{base_url}}/v3 /profile/account/request/otp

V3 Request: POST

V3 Header Parameters:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
txnId	Empty	No	Transaction Id is Mandatory to identify the unique transaction for ABHA reactivation.

Scope	abha-login mobile-verify, re-activate	Yes	Defines the scope of the current action of the API.
loginHint	abha-number	Yes	Type of login
loginId	Encrypted abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	abdm	Yes	Otp system to verify hlu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-login", "mobile-verify", "re-activate"], "loginHint": "abha-number", "loginId": "{{AbhaNumber_encryption}}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "3917ca6b-1b3a-46a1-b99a-248e925929ff", "message": "OTP sent to mobile number ending with *****4723" }</pre>

Step 2: Verify OTP

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login mobile-verify, re-activate	Yes	Defines the scope of the current action of the API
authMethod	otp		Method of verification
Timestamp	Actual time, format : "YYYY-MM-DD HH:mm:ss"	Yes	
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA re-activation.
otpValue	Encrypted OTP Value	Yes	Otp system to verify hiu/hip/phr login

V3 Request Body:

```
{
  "scope": [
    "abha-login",
    "mobile-verify",
    "re-activate"
  ],
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "txnId": "{{txnId}}",
      "otpValue": "{{OTP_encryption}}"
    }
  }
}
```

V3 Response:

[illegible]

8.6 Re-KYC

This API used to provide Re-KYC Facility.

Step 1: Generate OTP

V3 URL: {{base url}}/v3/profile/account/request/otp

V3 Request: POST V3

Request Headers:

Property Name	Example Value	Mandatory	Description
---------------	---------------	-----------	-------------