

V3 Response:

[illegible]

7.2 Login via Aadhaar Number

Step 1: Generate OTP

This API accepts the encrypted Aadhaar Number and then generates OTP for Aadhaar linked ABHA number.

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar- verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
loginHint	aadhaar	Yes	Type of login, following are the values that can be used. ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),
loginId	Encrypted aadhaar number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	aadhaar	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body

```

{
  "scope": [
    "abha-login",
    "aadhaar-verify"
  ],
  "loginHint": "aadhaar",
  "loginId":
  "eP7sVhb5mxtlleG1xKUUTYDvcUoVBFDewpYFcA+pwFAOTsvZ/yTEOgyCfRKXcUKG0fTvAjtU73OIR9aJAu2llr6FWM8pwcDWlvZgP8YR6+X/8
rxvcuYYyGkBuWB6zoXeHE7ZwTDHNCUwEFyWLwBpNkbYJ+vbtYLLyB7y3fRk+cJtB+iJq/IOQaLYZQoYqR4aTMutqQaopWukaBRz1h/0LSFh2PI
fOxfSMKymOFvS33OqVVmqQ6p9aajm5zuFW/dG86oeN5qFZHaPjN/dx2Rv0VWILlvAm8J+ZQGuJovm0OuPmfal+FZgbjJDLPMAmhUYm+
WBv9GPqWbxt3sjYtQy2Th6y4j12Nw+O++9eKuwBmZ28Vdo6w/ulp1kmKzZvMdVUGp1piF6h/ru6r5k4nNT+C6ib6BB8rH8qcBs00nrX4WjzJ
iVG0AuvvZxAsCMzAXf+cep6RXZgeg68ORouvoA9mCv2xyOWKAkc+eJ7Y6GcdT3Vvl0Kqa/awqUpY/Tsppk7RVGAN2w2RL+SX7/V6Sa7o2Gw
JJJFgGhihUWIHkX3yaCyS7wCIMFzeLHIC4bTPb0lyoyYnM3MxvPtWl6Rlq08eyZFSUeEhpa+nTfVPjok6j7p2WjBXRln4ynxwr4yYpiiONIgnHta
ziUPvcW47B+sb28ZLqU1Gpldfcw8bXJrcHqc=",
  "otpSystem": "aadhaar"
}

```

V3 Response:

Response
Code: 200 OK
<pre> { "txnId": "01a71f23-b26f-463a-b54b-ea50446eae9", "message": "OTP is sent to Aadhaar registered mobile number ending with *****0161" } </pre>

Step 2: Verify OTP

This API accepts OTP from the user, once the OTP is successfully validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar- verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
otpValue	Encrypted OTP value	Yes	
authMethods	otp	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"),

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-login",
    "aadhaar-verify"
  ],
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "txnId": "{{txnId}}",
      "otpValue": "{{OTP_encryption}}"
    }
  }
}
```

V3 Response:

```
Response

Code: 200 OK

{
  "txnId": "15fbec8b-0168-471d-8691-003c183a24fb",
  "authResult": "success",
  "message": "OTP verified successfully",   "token":
"eyJhbGciOiJIUzUxMiJ9.eyJpc0t5Y1ZlcmImaWVklp0cnVlCjZdWliOiI5MS0yNTY4LTcwNzMtNDgxOSIsImNsaWVudEI
kljoiYWJ0YS1wcm9maWxlfWFwcC1hcGkiLCJzeXN0ZW0iOiJlCjZdWliOiI5MS0yNTY4LTcwNzMtNDgxOSIsImNsaWVudEI
51bWJlci6ljxlTI1NjgtNzA3My00ODE5liwicHJlZmVycmVkJWJ0YUkZlCjZdWliOiI5MS0yNTY4LTcwNzMtNDgxOSIsImNsaWVudEI
9uliwiZXhwIjoxNzA3MTI0MDI4LCJpYXQiOiE3MDcxMjlyMjgsInR4bklkIjoiaMTVmYmVmVjOGltMDE2OC00NzFkLTg2OTEtMDA
zYzE4M2EyNGZiIn0.OqM17elgWWTYizhn6Rlw3VlepK1ClcXdbw6ry8dDjPZepzbngRGQVUn0Na4uT7bMjgRXC3mNTaUZZWvJGLLCYnEXijtqlmzyQ
ATTHI_4KITIAd4PSEyZlmPjdFRiSoaz_etNt
6RPDt9q5 tze64YludufxsiCfDkfr0J6w6yK3crWYkobClKMokVzVdnGM9X1ysEduK-bozTIPvsyXwdfa3dc9km5nFClcFWaXQajPk",
  "expiresIn": 1800,
  "refreshToken": "eyJhbGciOiJIUzUxMiJ9. wEvha4yvYo4WNYMxigG7ObhAKL6ICUJGQ9hiGCglPwc2e1FrFXmw5W ",
  "refreshExpiresIn": 1296000,
  "accounts": [
    {
      "ABHANumber": "91-4819-7073-XXXX",
      "preferredAbhaAddress": "guneetarora@sbx",
      "name": "Guneet Singh Arora",
      "status": "ACTIVE",           "profilePhoto":
"/9j/4AAQSkZJRgABAgAAAQABAAD/2wBDAAGGBgcGBQgHBWcJCQgKDBQNDAsLDBkSEw8UHRofHh0aHBwgJC4nIC
IsxwckDcpLDAxNDQ0Hyc5PTgyPC4zNDL/2wBDAQkJCQwLDBGNDRgylRwhMjlyMjlyMjlyMjlyMjlyMjlyMjlyMjlyMjlyMjly
MjlyMjlyMjlyMjlyMjlyMjlyMjL/wAARCAIAKADASIAAhEBAxEB9QE80yB+ar6jDFd6dNazczxq0bgHBKkEHH4VJnimzH9x9
TTA+bdQtXs7+4tpCpkhlaNyvTcpcwfkPnrXW+P7E2niy4YKqpclsyhfcYJPuWVjXJHpVoBvU4FdVoN5aafFtyCzcs2OSa
w9KHgeZpbj/Vp0Hqat3Mfk7BoJjGeoDMMfzrOpZ+6zWCa1R6Bp+qWc0qASAbuma3WeMBMMmGmBh1+leTWcjRnBb
cvsa7bQ7uRrcIJA+6PQVvygom6k5bm9PNdAMysqj3rGuPENhCflkDHOMYrG1y/kaR4t/U8CuXkt5riY/vD15JojTi9WNy
a2L/iOAt21CYXMACzdGA/ ACP+BV65bda4rwLYf2d4ct1Yyef9+/OR8wGPp8oXj1zXb2i/ ="
    }
  ]
}
```

7.3 Login via Abha OTP

Step 1: Generate OTP

This API accepts the encrypted ABHA number and then generates OTP for Abha linked mobile number.

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, mobile-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
loginHint	abha-number	Yes	Type of login, following are the values that can be used. ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),

loginId	Encrypted Abha number	Yes	Actual value of login type. This needs to be RSA encrypted using a public key
otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login, following are the values that can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-login", "mobile-verify"], "loginHint": "abha-number", "loginId": "{{Abha_encryptedOutput}}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "cef6460d-a068-4c84-ae78-407fe6ad13d4", "message": "OTP sent to mobile number ending with *****4723" }</pre>

Step 2: Verify OTP

This API accepts encrypted OTP from the user, once the OTP is successfully validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction

TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, mobile-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
otpValue	Encrypted OTP value	Yes	
authMethods	otp	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"),

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-login",
    "mobile-verify"
  ],
  "authData": {
    "authMethods": [
      "otp"
    ],
    "otp": {
      "txnId": "{{txnId}}",
      "otpValue": "{{OTP_encryption}}"
    }
  }
}
```

V3 Response:

[illegible]

7.4 Login via Mobile OTP

Step 1: Generate OTP

API accepts mobile numbers and then generates OTP for the entered mobile number.

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, mobile-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
loginHint	mobile	Yes	Type of login, following are the values that can be used ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),
loginId	Encrypted Mobile number	Yes	Actual value of login type. This needs to be RSA encrypted using public key

otpSystem	abdm	Yes	Otp system to verify hiu/hip/phr login, following are the values can be used. AADHAAR("aadhaar"), ABDM("abdm"),
-----------	------	-----	---

V3 Request body:

Request Body
<pre>{ "scope": ["abha-login", "mobile-verify"], "loginHint": "mobile", "loginId": "{{[Mobile_Encryption]}", "otpSystem": "abdm" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "67f12929-22fd-4826-a8f3-a6fef3e11244", "message": "OTP sent to mobile number ending with *****9260" }</pre>

Step 2: Verify OTP

This API accepts encrypted OTP from the user, once the OTP is successfully validated a session token is generated along with the list of ABHA numbers (ACTIVE and DEACTIVATED) linked with the mobile number.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction

TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, mobile-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
authMethods	otp	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"),
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
otpValue	Encrypted OTP value	Yes	

V3 Request Body:

Request Body

V3 Response:

Step 3: Verify User.

This API accepts the ABHA number and transaction id, once both are validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify/user

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{IsoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API
T-token	Bearer {{token}}	Yes	Token received in login/verify API. Its' valid for 5mins.

V3 Body parameters:

Property Name	Value	Mandatory	Description
ABHANumber	AbhaNumber	Yes	14-digit ABHA number
txnId	9b4ce0f9-3a27-4598a02ab889479f4fb0	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login generated from Verify OTP step.

V3 Request Body:

Request Body
<pre>{ "ABHANumber": "{{AbhaNumber}}", "txnId": "{{txnId}}" }</pre>

V3 Response:

Response

[illegible]

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction

TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{{accesstoken}}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-face-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify"),
loginHint	ABHA number	Yes	Type of login, following are the values that can be used ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),
loginId	Encrypted ABHA number	Yes	Actual value of login type. This needs to be RSA encrypted using public key
otpSystem	aadhaar	Yes	Otp system to verify hlu/hip/phr login, following are the values can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request body:

Request Body

```

{
  "scope": [
    "abha-login",
    "aadhaar-face-verify"
  ],
  "loginHint": "abha-number",
  "loginId": "{{Abha_Number Encrypted}}",
  "otpSystem": "aadhaar"
}

```

V3 Response:

Response
Code: 200 OK
<pre> { "txnId": "67f12929-22fd-4826-a8f3-a6fef3e11244", "message": "FACE authentication request successfully sent." } </pre>

Step 2: Verify Face

This API accepts base-64 encoded face auth PID for the user which is generated by the Aadhaar RD service application. once the PID value is successfully validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-face-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify")
authMethods	face	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"), FACE("face"), BIO("bio"), IRIS("iris")
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
faceAuthPid	Base 64 encoded face auth Pid	Yes	PID value is base 64 encoded which is generated by the Aadhaar RD service application

V3 Request Body:

Request Body
<pre>{ "scope": ["abha-login", "aadhaar-face-verify"], "authData": { "authMethods": ["face"], "face": { "txnId": "{{txnId}}", "faceAuthPid": "{{Base-64-encoded_faceAuthPid}}" } } }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "ec5d10f4-41c9-4d7e-b857-4a77b04a35b7", "authResult": "success", "message": "Face verified successfully", "token": "eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiI5ODcyNjk5MjYwIiwiaXNjaW50SWQyOiIhYmhhLXB5b2ZpbGUtYXBwLWFWaSlzLnN5c3RlbnSI6IjFCSEEtTilslm1vYmIsZSI6Ijlk4NzI2OTkyNjAiLCJ0eXAiOiJ1cmFuc2ZlciIsImV4cCI6MTcwNzEyMzM2MywiaWF0IjoxNzA3MTIzMDYzZfQ.Jn9Xt0UuiVJ61-9paqnr0KWoy9T6pdc2QKQRv5qH6NlCujcoYq-ch8JVM7xHa6CkgDvT4PZj_ ", "expiresIn": 300, "accounts": [{ "ABHANumber": "91-5568-7073-XXXX", "preferredAbhaAddress": "nilam11@sbx", "name": "Nilam Pratik Jadhav", "gender": "M", "dob": "07-03-1997", "status": "ACTIVE", "profilePhoto": "/9j/zVr7GGNefc7jIEYzjFLKmwZNaotkU4A5qveRoootpXGY3lGe4RNU4kgBSM7j2Fen2MC29vHChJCKFyep964rSYkWCXUzKiqQF8xwgB/vc9QCVHHfHvXbWs8dxAs0EkcsbdHjcMDjgjrXo0YcsTgrT5pBMWWynkX7yxtjnHIFVwvlbY5BuUj589iRzj061dj+YICM5JqNh56uO+CcsxBPpk4rUyZFKJ13zQHZE2fKg9Qp7e5x09acl6pco4IOSAQMJg4/MnPHTUdrJ5c/IE8HpVuSBJTuK/OMfOOCMDoOaVgRlFKrqGRgynuDmpw3FY32Sa3Km3fI3AHHB2/ /Nzz+WfnfLI/7pJbuXkbY2GxfYtyM9QcZyDRRQtQZWn03U70lprt7WLGPKt2lzxj5j/EcADnPTtWzpOnzRafJJYhZJ0lwVbM anoQAccgBsZx1zRRTa0EpNGfFcRyXE8SRoojYkBGbg3dgY/Nf++gOatDGOKKK82vFRloelSk3HUgcYYnNRR239o38Vpn G/ILegHU/0+poopUopyVx1JNRbQmr+bpV/aRWLRSzRAxmJskAHAQTg5BAUdcZD5ycVJBrUqS+ZqViBJtCm4tC2SA2 4Bh98KPKQFs/3T0oorOkjeZnU2ModAwmWbnKsuPmX+E8d8DH1B6dKbp7Smwg81NknLvTH3WlyR+tFFMorz5Vgw6g1 owS70Vs+xoopsMS3Eb5W9qbJFHcgFwcjIDDqAQQf59DRRSgf/9k=", "kycVerified": true }] }</pre>

7.5.2 Login via FingerprintAuth

Note : List of UIDAI-approved biometric devices

- <https://uidai.gov.in/en/ecosystem/authentication-devices-documents/biometric>
<https://ind01.safelinks.protection.outlook.com/?url=https://uidai.gov.in/en/ecosystem/authentication-devices-documents/biometric-devices.html&data=05|02|Kushal.Pandita@ltimindtree.com|022d6e5cc5ca4c50ddc708dd93aaf31c|ff355289721e4dd7a663afec62ab9d54|0|0|638829084605444457|Unknown|TWfPbGZsb3d8eyJFbXB0eU1hcGkiOnRydWUsIlYiOiIwLjAuMDAwMCIslIAiOiJXaW4zMlslSkFOljoiTWFpbiClldUIjoyfQ==|0||&sdata=l/nQjzqQwmHwJj++2ueol9Tlnbz1iunxdtKxwPjPLQ=&reserved=0>[devices.html](#). (Kindly note that the list is updated by UIDAI periodically.)

Step 1: Send Biometric Verification Request

API accepts ABHA number and then by verifying the account will send the fingerprint verification request to the application.

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accessToken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-bio-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify"),

loginHint	ABHA number	Yes	Type of login, following are the values that can be used ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),
loginId	Encrypted ABHA number	Yes	Actual value of login type. This needs to be RSA encrypted using public key
otpSystem	aadhaar	Yes	Otp system to verify login, following are the values can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request body:

Request Body
<pre>{ "scope": ["abha-login", "aadhaar-bio-verify"], "loginHint": "abha-number", "loginId": "{{ABHA_Number Encrypted}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "67f12929-22fd-4826-a8f3-a6fef3e11244", "message": "Fingerprint authentication request successfully sent." }</pre>

Step 2: Verify Fingerprint

This API accepts base-64 encoded Fingerprint auth pid for the user which is generated by the biometric device. Once the pid value is successfully validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-bio-verify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("emailverify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify")
authMethods	bio	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"), FACE("face"), BIO("bio"), IRIS("iris")
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
fingerprintAuthPid	Base 64 encoded bio auth PID	Yes	PID value is base 64 encoded which is generated by biometric device

Note: Checkpoints to generate fingerprintAuthPid:- Ir = 'Y'; (This Attribute should be passed as 'Y' otherwise it will give K-547 error) ra = deviceType; rc = 'Y'; de = 'N'; pfr = 'N'; text = '2.5' + ra + rc + Ir + de + pfr; wadh = Base64.stringify(sha256(text)) or Convert to SHA-256 and then to base64.

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-login",
    "aadhaar-bio-verify"
  ],
  "authData": {
    "authMethods": [
      "bio"
    ],
    "bio": {
      "txnId": "{{txnId}}",
      "fingerprintAuthPid": "{{Base-64-encoded_fingerprintAuthPid}}"
    }
  }
}
```

V3 Response:

Response

Code: 200 OK

```
{
  "txnId": "ec5d10f4-41c9-4d7e-b857-4a77b04a35b7",
  "authResult": "success",
  "message": "Bio verified successfully",   "token":
"eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiI5ODcyNjk5MjYwIiwia2xpZW50SWQqOiIhYmhhLXB5b2ZpbGUtYXBwLWFWaSIsIn
N5c3RlbiSI6IkcSEEtIiIsIm1vYmIsZSI6IjYk4NzI2OTkyNjAiLCJ0eXAiOiJ1cmFuc2ZlcnIsImV4cCI6MTcwNzEyMzY2MzMywW
F0IjoxNzA3MTIzMDYzZfQ.Jn9Xt0UuiVJ61-9paqnr0KWoy9T6pdc2QKQrv5qH6NICulcoYq-ch8JVM7xHa6CkgDvT4PZj_
",
  "expiresIn": 300,
  "accounts": [
    {
      "ABHANumber": "91-5568-7073-XXXX",
      "preferredAbhaAddress": "nilam33@sbx",
      "name": "Nilam Pratik Jadhav",
      "gender": "M",
      "dob": "19-03-1997",
      "status": "ACTIVE",   "profilePhoto":
"/9j/zVr7GGNefc7jIEYzjFLKmwZNaotkU4A5qveRooztpXGY3lGe4Rnu4kgBSM7j2Fen2MC29vHChJCKFyep964rSYkWc
XUzKiqQF8xwgB/vc9QCVHHfHvXbpyWs8dxAs0EkcsbdHjcMDjgjrXo0YcsTgrT5pBMWWynkX7yxtjnHIFVwvlbY5BuUj589i
Rzj061dj+YICM5JqNh56O+CcsxBPpk4rUyZFKJ13zQHZE2fKg9Qp7e5x09acl6pco4IOSAQMJg4/MnPHtUdrJ5c/IE8HpVu
SBJTuK/OMfOOCMDoOaVgRLFKrQGRgynuDmpw3FY32Sa3Km3fl3AHHB2/
/Nzz+WfNfLI/7pJbuXkbY2GxfYtyM9QcZyDRRQtQZWn03U70lprt7WLGPKt2IzXj5j/EcAdnPTtWzpOnzRafJJYhZJ0lwVbM
anoQAccgBsZx1zRRTa0EpNGfFcRyXE8SRoojYkBGbg3dgY/Nf++gOatDGOKKK82vFRloelSk3HUgcYYnNRR239o38Vpn
G/JLegHU/0+poopUopyVx1JNRbQmr+bpV/aRWLRSzRAxmJskAHAQTg5BAUdcZD5ycVJBrUqS+ZqViBjtCm4tC2SA2
4Bh98KPQFs/3T0oor0kizeZnU2ModAwmWbnKsuPmX+E8d8DH1B6dKbp7Smwg81NknLvTH3WlyR+tFFMorz5Vgw6g1
owS70Vs+xoopMS3Eb5W9qbJFHcgFwcjIDDqAAQqf59DRRSgf/9k=",
      "kycVerified": true
    }
  ]
}
```

7.5.3 Login via IrisAuth

Step 1: Send Iris verification Request

API accepts ABHA number and then by verifying the account will send the Iris verification request to the application.

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{\${isoTimestamp}}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds

Authorization Token	{{accesstoken}}	Yes	Token generated from session API
---------------------	-----------------	-----	----------------------------------

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, aadhaar-irisverify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify"),
loginHint	ABHA number	Yes	Type of login, following are the values that can be used ABHA_NUMBER("abha-number"), MOBILE("mobile"), EMAIL("email"), AADHAAR("aadhaar"), PASSWORD("password"),
loginId	Encrypted ABHA number	Yes	Actual value of login type. This needs to be RSA encrypted using public key
otpSystem	aadhaar	Yes	Otp system to verify login, following are the values can be used. AADHAAR("aadhaar"), ABDM("abdm"),

V3 Request body:

Request Body
<pre>{ "scope": ["abha-login", "aadhaar-iris-verify"], "loginHint": "abha-number", "loginId": "{{Abha_Number Encrypted}}", "otpSystem": "aadhaar" }</pre>

V3 Response:

Response
Code: 200 OK
<pre>{ "txnId": "67f12929-22fd-4826-a8f3-a6fef3e11244", "message": "Iris authentication request successfully sent." }</pre>

Step 2: Verify Iris

This API accepts base-64 encoded Iris auth PID for the user which is generated by the Iris device. Once the PID value is successfully validated a session token is generated.

V3 URL: {{base_url}}/v3/profile/login/verify

V3 Request: POST

V3 Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the endtoend request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
---------------	-------	-----------	-------------

Scope	abha-login, aadhaar-irisverify	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), EMAIL_VERIFY("emailverify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"), AADHAAR_FACE_VERIFY("aadhaar-face-verify"), AADHAAR_BIO_VERIFY("aadhaar-bio-verify"), AADHAAR_IRIS_VERIFY("aadhaar-iris-verify")
authMethods	iris	Yes	Type of login, following are the values that can be used OTP("otp"), PASSWORD("password"), FACE("face"), BIO("bio"), IRIS("iris")
txnId	txnId	Yes	Transaction Id is Mandatory to identify the unique transaction for ABHA login.
irisAuthPid	Base 64 encoded iris auth PID	Yes	PID value is base 64 encoded which is generated by Iris Device

V3 Request Body:

Request Body

```
{
  "scope": [
    "abha-login",
    "aadhaar-iris-verify"
  ],
  "authData": {
    "authMethods": [
      "iris"
    ],
    "iris": {
      "txnId": "{{txnId}}",
      "irisAuthPid": "{{Base-64-encoded_irisAuthPid}}"
    }
  }
}
```

V3 Response:

Response

```

Code: 200 OK
{
  "txnId": "ec5d10f4-41c9-4d7e-b857-4a77b04a35b7",
  "authResult": "success",
  "message": "Iris verified successfully",   "token":
"eyJhbGciOiJSUzUxMiJ9.eyJzdWUiOiI5ODcyNjk1MjYwIiwiaXNpZW50SWQiOiIhYmhhLXB5b2ZpbGUtYXBwLWFWaSlzIn
N5c3RlbSI6IklkFCSEEtTilslm1vYmlsZSI6IjE4NzI2OTkyNjAiLCJ0eXAiOiJ1UcmFuc2ZlciIsImV4cCI6MTcwNzEyMzY2MywiaW
FOljoXNzA3MTIzMDYzfQ.Jn9Xt0UuiVJ61-9paqnr0KWoy9T6pdc2QKQRv5qH6NICuJcoYq-ch8JVM7xHa6CkgDvT4PZj_
",
  "expiresIn": 300,
  "accounts": [
    {
      "ABHANumber": "91-5568-7073-XXXX",
      "preferredAbhaAddress": "nilam11@sbx",
      "name": "Nilam Pratik Jadhav",
      "gender": "M",
      "dob": "27-03-1997",
      "status": "ACTIVE",      "profilePhoto":
"/9j/zVr7GGNefc7jIEYzjFLKmwZNaotkU4A5qveRoootpXGY3lGe4RNU4kgBSM7j2Fen2MC29vHChJCKFyep964rSYkWc
XUzKiqQF8xwgB/vc9QCvHHfHvXbWs8dxAs0EkcsbdHjcMDjigjrXo0YcsTgrT5pBMWWynkX7yxtjnHIFVwvlbY5BuUj589i
Rzj061dj+YICM5JqNh56O+CcsxBPpk4rUyZFKJ13zQHZE2fKg9Qp7e5x09acl6pco4IOSAQMjg4/MnPHtUdrJ5c/IE8HpVu
SBjTuK/OMfOOCMdOaVgRLFKrqGRgynuDmpw3FY32Sa3Km3fl3AHHB2/
/Nzz+WfNfLI/7pJbuXkbY2GxfYtyM9QcZyDRRQQtQZWn03U70lprt7WLGPKt2Izxj5j/EcADnPTtWzpOnzRafJJYhZl0lwVbM
anoQAccgBsZx1zRRTa0EpNGfFcRyXE8SRoojYkBGBG3dgY/Nf++gOatDGOKKK82vFRloelSk3HUgcYYnNRR239o38Vpn
G/JLegHU/0+poopUopyVx1JNRbQmr+bpV/aRWLRSzRAXmJskAHaQTg5BAUdcZD5ycVJBrUqS+ZqViBJtCm4tC2SA2
4Bh98KPQFs/3TOoor0kjeZnU2ModAwmWbnKsuPmX+E8d8DH1B6dKbp7Smwg81NknLvTH3WlyR+tFFMorz5Vgw6g1
owS70Vs+xoopsMS3Eb5W9qbJFHcgFwcjIDDqAQQf59DRRSGf/9k=",
      "kycVerified": true
    }
  ]
}

```

7.6 Find ABHA

7.6.1 Search ABHA using Mobile

7.6.1.1 Search ABHA

V3 URL: {{base_url}}/v3/profile/account/abha/search

V3 Request: POST **V3**

Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body Parameters:

Property Name	Example Value	Mandatory	Description
scope	search-abha	Yes	Search scope
Mobile	Mobile number	Yes	User mobile number

V3 Request Body:

Request Body
<pre>{ "scope": ["search-abha"], "mobile": "{{Mobile_Encryption}}" }</pre>

V3 Response:

```
[
  {
    "txnId": "d0660ae0-1798-4e42-8e07-33eea4a3824d",
    "ABHA": [
      {
        "index": 1,
        "ABHANumber": "91-5259-8743-XXXX",
        "name": "Narayanan Madaswamy",
        "gender": "M"
      }
    ]
  }
]
```

```

"kycVerified": "true",
"authMethods": [
  "AADHAAR_OTP",
  "MOBILE_OTP",
  "AADHAAR_BIO",
  "DEMOGRAPHICS"
]
}
]

```

7.6.1.2 Generate OTP

V3 URL: {{base_url}}/v3/profile/login/request/otp

V3 Request: POST **V3**

Request Headers:

Property Name	Example Value	Mandatory	Description
REQUEST-ID	18235d89-cb13-479d-ad71-7a57d5f669a8	Yes	Unique UUID for tracking the end-to-end request transaction
TIMESTAMP	{{isoTimestamp}}	Yes	The actual time when the request was initiated, ISO 8601 represents the date and time by starting with the year, followed by the month, the day, the hour, the minutes, seconds, and milliseconds
Authorization Token	{{accesstoken}}	Yes	Token generated from session API

V3 Body parameters:

Property Name	Value	Mandatory	Description
Scope	abha-login, mobile-verify search-abha	Yes	Defines the scope of the current action of the API, following are the values that can be used ABHA_LOGIN("abha-login"), ABHA_PROFILE("abha-profile"), AADHAAR_VERIFY("aadhaar-verify"), AADHAAR-BIO-VERIFY("aadhaar-bio-verify") AADHAAR-FACE-VERIFY("aadhaar-face-verify") AADHAAR-IRIS-VERIFY("aadhaar-iris-verify") EMAIL_VERIFY("email-verify"), MOBILE_VERIFY("mobile-verify"), PASSWORD_VERIFY("password-verify"), CHANGE_PASSWORD("change-password"), RE_KYC("re-kyc"),
loginHint	index	Yes	Index of ABHA number given in search API response.