

Linux Kernel Memory Management

Page Cache (Introduction), Watermarks, OOM, VMAs Part 4 of 4

Linux Kernel: Memory Management series by kaiwanTECH

Part 1: Introduction to Virtual Memory, Paging

Part 2: Kernel and Process Segments

Part 3: Memory Organization, Kernel Segment

Part 4: Page Cache (Intro), Watermarks, OOM, Page Fault, VMAs

Important Notice: Courseware - Legal

This courseware is both the product of the author and of freely available opensource and/or public domain materials. Wherever external material has been shown, it's source and ownership have been clearly attributed. We acknowledge all copyrights and trademarks of the respective owners.

The contents of the **courseware PDFs are considered proprietary** and thus cannot be copied or reproduced in any form whatsoever without the explicit written consent of the author.

Only the programs - **source code** and binaries (where applicable) - that form part of this courseware, and that are made available to the participant, are released under the terms of the <u>permissive MIT license</u>. Under the terms of the MIT License, you can certainly use the source code provided here; you must just attribute the original source (author of this courseware and/or other copyright/trademark holders).

VERY IMPORTANT :: Before using this source(s) in your project(s), you *MUST* check with your organization's legal staff that it is appropriate to do so.

The courseware PDFs are *not* under the MIT License, they are to be kept confidential, non-distributable without consent, for your private internal use only.

The duration, contents, content matter, programs, etc. contained in this courseware and companion participant VM are subject to change at any point in time without prior notice to individual participants.

Care has been taken in the preparation of this material, but there is no warranty, expressed or implied of any kind, and we can assume no responsibility for any errors or omisions. No liability is assumed for incidental or consequential damages in connection with or arising out of the use of the information or programs contained herein.

2000-2023 Kaiwan N Billimoria kaiwanTECH, Bangalore, India.

kaiwanTECH Linux OS Corporate Training Programs


Please do check out our current offering of world-class, seriously-valuable, high on returns, technical Linux OS corporate training programs here: http://bit.ly/ktcorp

Table of Contents

The Page Cache – an Introduction	5
Watermarks	16
	19
OOM Killer	
FAQ :: Disabling OOM on a Particular Process	24
snip	25
An experiment : Invoking the kernel OOM-Killer	26
Demand paging	28
Linux Memory Overcommit	40
Page Faults	46
Linux glibc malloc() Behaviour	59
Note on Optimizations	72

The Page Cache – an Introduction

- Pretty much every page of user process RAM is kept in either the page cache or the swap cache (the swap cache is just the part of the page cache associated with swap devices).
- The purpose of the cache is simply to keep as much **useful (in use)** data in memory as possible, so that page faults may be serviced **quickly**.
- The cache is a layer between the kernel memory management code and the disk I/O code. Also, when the kernel *swaps pages out* of a task, they *do not get written immediately* to disk, but rather are added to the (swap) cache. The kernel then writes the cache pages out to disk as necessary in order to create free memory.



Basic Definitions:

- **Dirty page**: a page that has been written to and contents are not flushed to disk
- **Clean page**: updated page, i.e., contents are up-to-date on disk; thus, a clean page can be freed when deemed necessary;

Recall that the page structure holds the dirty "bit" for a page, as the flag PG_dirty.

• **Anonymous page**: a page that has no file-mapping is termed an anonymous page (or zero-mapped page); for example, a page that has been malloc'ed. Anonymous pages require some form of backing storage (like swap) to hold them when they are not in main memory.

A typical example of (heavy) page caching taking place is when we use tar to create an archive.

SIDEBAR :: See Linux page caching in action

Test Case 1 : Tar'ring a (large-ish) folder)

We'll select a large folder (over 500 Mb) and tar it's contents. While 'tar' is running, we'll in parallel (on another terminal window) keep an eye on the output of 'free -m' particularly the last column ("cached" memory in MB).

```
$ time tar cvf doc.tar doc/
```

```
...
real 1m10.655s
user 0m0.392s
sys 0m4.336s
$
```

¢ while [true]; do	froo -mlboad	-02 +5i1	-n1. cloop	1. dono	
<<	total	used	free	shared	buffers	cached >>
Mem:	2011	672	1339	0	67	335
Mem:	2011	672	1339	0	67	335
Mem:	2011	682	1329	0	67	344
Mem:	2011	736	1274	0	67	398
Mem:	2011	751	1259	0	67	413
snip						
Mem:	2011	850	1161	0	67	508
Mem:	2011	856	1154	0	67	516
Mem:	2011	870	1141	0	67	529
snip						
Mem:	2011	1069	942	0	67	725
Mem:	2011	1090	920	0	67	747
Mem:	2011	1098	912	0	67	754
snip						
Mem:	2011	1201	810	0	67	855
Mem:	2011	1204	806	0	67	859
Mem:	2011	1232	779	0	67	886
snip						
Mem:	2011	1528	483	0	68	1175
Mem:	2011	1536	475	Θ	68	1183
Mem:	2011	1544	466	0	68	1192
snip						
Mem:	2011	1782	229	Θ	68	1425
Mem:	2011	1789	221	Ö	68	1433

Mem: 2011 1789 222 0 68 1433 ^C \$

(From the System Monitor applet, we can also see that, as of now on the test system, memory (RAM) usage is: "16% in use by programs, 77% in use as cache").

Now for the interesting part: soon afterward (and without rebooting of course), we run the same 'tar' a second time:

```
$ time tar cvf doc.tar doc/
...
real    0m20.152s
user    0m0.184s
sys    0m2.264s
```

It's taken only about 20 seconds this time, as opposed to about 70 seconds the first time! This is primarily due to the performance effect of page caching.

http://www.linuxatemyram.com/

Linux ate my ram!

Please read: Linux Page Cache Basics and,

Experiments and fun with the Linux disk (page) cache

--snip--





How do I see how much free ram I really have?

To see how much ram is free to use for your applications, run free -m and look at the row that says "-/+ buffers/cache" in the column that says "free". That is your answer in megabytes:

\$ free -m buffers cached total used free shared 1504 1491 13 0 91 764 -/+ buffers/cache: 635 869 Swap: 2047 6 2041

If you don't know how to read the numbers, you'll think the ram is 99% full when it's really just 42%.

--snip--

SIDEBAR - Resource

A must-read: "Page Cache, the Affair Between Memory and Files".

--snip--

First, even though this program uses regular read calls, three 4KB page frames are now in the page cache storing part of scene.dat. People are sometimes surprised by this, but all regular file I/O happens through the page cache. In x86 Linux, the kernel thinks of a file as a sequence of 4KB chunks. If you read a single byte from a file, the whole 4KB chunk containing the byte you asked for is read from disk and placed into the page cache. This makes sense because sustained disk throughput is pretty good and programs normally read more than just a few bytes from a file region. The page cache knows the position of each 4KB chunk within the file, depicted above as #0, #1, etc. Windows uses 256KB views analogous to pages in the Linux page cache.

Sadly, in a regular file read the kernel must copy the contents of the page cache into a user buffer, which not only takes cpu time and hurts the <u>cpu caches</u>, but also wastes physical memory with duplicate data. As per the diagram above, the scene.dat contents are stored twice, and each instance of the program would store the contents an additional time. We've mitigated the disk latency problem but failed miserably at everything else. Memory-mapped files are the way out of this madness:

When you use file mapping, the kernel maps your program's virtual pages directly onto the page cache. This can deliver a significant performance boost: Windows System Programming reports run time improvements of 30% and up relative to regular file reads, while similar figures are reported for Linux and Solaris in Advanced Programming in the Unix Environment. You might also save large amounts of physical memory, depending on the nature of your application.

--snip--

In Linux, if you request a large block of memory via malloc(), the C library will create an anonymous mapping (using mmap()) instead of using heap memory. 'Large' means larger than MMAP_THRESHOLD bytes, 128 kB by default and adjustable via mallopt().

--snip--

SIDEBAR :: Using the mmap(2) in applications

The above article "<u>Page Cache</u>, the Affair Between Memory and Files", clearly demonstrates why using memory-mapped IO is far superior to the "usual" approach – using the read/write system calls (or library equivalents) in a loop – especially for the use-case where the amount of IO to be performed is quite large.

But how exactly does one perform memory-mapped IO?

Ah. Do read this excellent tutorial: <u>"Beej's Guide to UNIX IPC"</u>, (and for covering the mmap(2)) see the section "10. Memory Mapped Files".

The 'free' command summarizes free and used memory, including the memory usage for buffers and (page) cache:

```
Eg.
$ free --help
Usage:
  free [options]
 Options:

-b, --bytes show output in bytes
-k, --kilo show output in kilobytes
-m, --mega show output in megabytes
-g, --giga show output in gigabytes
--tera show output in terabytes
-h, --human show human-readable output
--si use powers of 1000 not 1024
-l, --lohi show detailed low and high memory statistics
-o, --old use old format (without -/+buffers/cache line)
-t, --total show total for RAM + swap
-s N, --seconds N repeat printing every N seconds
-c N, --count N repeat printing N times, then exit
Options:
   -c N, --count N repeat printing N times, then exit
          --help display this help and exit
   -V, --version output version information and exit
For more details see free(1).
 $ free -ht
total used free
Mem: 2.8G 2.6G 130M
-/+ buffers/cache: 2.1G 657M
Swap: 5.7G 1.1G 4.6G
Total: 8.5G 3.7G 4.8G
                                                                                               nared buffers
200M 17M
                                                                                           shared
                                                                                                                                        cached
                                                                                                                                            509M
 << 657MB \sim = free(130M) + buffers(17M) + cached(509M).
 It is the totally available memory on the system, including buffers and cache. >>
```

nared buffers cached 647M 233M 1.8G

BTW, looking up free memory, as separate 'low' and 'high' memory, basis can be done with the '-l' option to free (-h = human readable):

shared

free

\$ free -lh total used

Mem:	7.5G	6.9G	5/1M
Low:	7.5G	6.9G	571M
High:	0B	0B	0B
-/+ buffer	rs/cache:	4.9G	2.6G
Swap:	. 15G	192M	15G

Interestingly, on a 32-bit x86 (IA-32) system with *more than* 896 MB RAM, you will notice that this makes a difference:

\$ free - h

4						
	total	used	free	shared	buffers	cached
Mem:	2.8G	2.0G	846M	180M	18M	707M
Low:	838M	625M	213M			
High:	2.0G	1.4G	633M			
-/+ buffer	rs/cache:	1.3G	1.5G			
Swap:	5.7G	597M	5.1G			
\$						

How to clean caches used by the Linux kernel

Short answer:

sync && echo 1 > /proc/sys/vm/drop_caches

total used

From *Documentation/sysctl/vm.txt*

--snip--

drop_caches

Writing to this will cause the kernel to drop clean caches, dentries and inodes from memory, causing that memory to become free.

Eg.

free -h

1	COCAL	acca		onan oa	barry babrio	a var cas co
Mem:	15G	9.1G	290M	975M	6.2G	5.3G
Swap:	7.6G	0B	7.6G			
Total:	23G	9.1G	7.9G			
# sync						
# echo 1 :	<pre>> /proc/sys/</pre>	vm/drop_	caches			
# free -h		•				
	total	used	free	shared	buff/cache	available
Mem:	15G	9.1G	4.8G	975M	1.7G	5.3G
Swap:	7.6G	0B	7.6G			
Total:	23G	9.1G	12G			

free

shared buff/cache available

#

To free pagecache:

echo 1 > /proc/sys/vm/drop_caches

To free dentries and inodes (cache):

echo 2 > /proc/sys/vm/drop_caches

To free pagecache, dentries (cache) and inodes (cache):

echo 3 > /proc/sys/vm/drop_caches

As this is a non-destructive operation and dirty objects are not freeable, the user should run `sync' first.

--snip--

Application File IO Sync

- The sync(1) command calls sync(2)
 - \circ void sync(void) : causes all buffered modifications to file metadata and data to be written to the underlying filesystems.
- fsync(2): int fsync(int fd);
- open(2)
 - O_DIRECT (Since Linux 2.4.10)

Try to minimize cache effects of the I/O to and from this file. In general this will degrade performance, but it is useful in special situations, such as when applications do their own caching. File I/O is done directly to/from user-space buffers. The O_DIRECT flag on its own makes an effort to transfer data synchronously, but does not give the guarantees of the O_SYNC flag that data and necessary metadata are transferred. To guarantee synchronous I/O, O_SYNC must be used in addition to O_DIRECT. **See NOTES** below for further discussion.

• O_SYNC The file is opened for synchronous I/O. Any write(2)s on the resulting file descriptor will block the calling process until the data has been physically written to the underlying hardware. But see NOTES below.

• • •

NOTES

. . .

POSIX provides for three different variants of synchronized I/O, corresponding to the flags O_SYNC, O_DSYNC, and O_RSYNC. Currently

(2.6.31), Linux implements only O_SYNC, but glibc maps O_DSYNC and O_RSYNC to the same numerical value as O_SYNC. Most Linux filesystems

don't actually implement the POSIX O SYNC semantics, which require

all metadata updates of a write to be on disk on returning to user space, but only the O_DSYNC semantics, which require only actual file data and metadata necessary to retrieve it to be on disk by the time the system call returns.

• • •

<< ... lots of Notes on using O_DIRECT ... >

"ZFS is the only modern filesystem we know of which uses its own read cache mechanism, rather than relying on its operating system's page cache to keep copies of recently-read blocks in RAM for it."

Src- ZFS 101—Understanding ZFS storage and performance, May 2020.

Watermarks

- 1. Another specific set of "trigger points" are available to the kernel, telling it when to initiate page reclamation. This is the per-node, and within that, per-zone basis triggers called "min", "low" and "high". They represent (in pages) the watermarks or threshold limits:
- When the amount of free RAM in a node:zone drops below high, the kernel starts swapping "gently" hoping to free sufficient pages to bring the level back above high.
- If it drops below the low watermark, the kernel starts swapping aggressively.
- If (rare case), this does not help and free pages go below the min watermark, the kernel now will swap aggressively and not allocate any RAM to userspace applications.

Incidentally, the "min" watermark (pages_min) is the amount of RAM kept reserved by the kernel for critical allocations, expressed in pages. [So, in the example below, in the 'normal' zone, min=936 => 936 * 4Kb = 3744 Kb.]

<<


Source

"Free memory in zones is controlled by various thresholds.

1)pages_min: If free memory falls below pages_min threshold, application demanding memory will also have to do the hard work of first reclaiming memory (synchronously). Once enough memory is reclaimed, request for memory is granted. This could turn out to be a very expensive call on application and you are likely to see performance impact.

2)pages_low: If free memory falls below pages_low threshold, kernel invokes kswapd demon to asynchronously work on reclaiming memory.

3)pages_high: Once enough memory is reclaimed by kswapd daemon, and free pages goes beyond pages high limit, kswapd will go into sleep state."



>>

2. These settings can be viewed using proc (seen later):

<< Output below from an Ubuntu system, running the 2.6.24-16-generic kernel. Note that the output you see could vary with the kernel version; on some versions a particular proc entry may not even be present >>

```
$ cat /proc/zoneinfo
Node 0, zone
 pages free
                 3066
        min
                 17
        low
                 21
        high
                 25
        scanned 0 (a: 8 i: 8)
        spanned 4096
        present 4064
--snip--
 all_unreclaimable: 0
 prev_priority:
                     12
 start_pfn:
                     0
Node 0, zone
             Normal
 pages free
                 87722
        min
                 936
        low
                 1170
        high
                1404
        scanned 0 (a: 0 i: 0)
       spanned 225280 present 223520
   nr_free_pages 87722
   nr_inactive 60749
   nr_active
                26942
--snip--
```

Another way to see the above – including a wealth of memory information, is to trigger the Magic-SysRq key combo '<Alt><SysRq> <m>' as follows as root user (this of course assumes that the Magic-SysRq feature is built in and enabled in the running kernel): (Also, fyi, don't get confused :-) . The output below was captured at a later date and on a different system from the one above; therefore the numbers don't match).

```
# echo m > /proc/sysrq-trigger
# dmesg
--snip--
[26038.210508] Mem-info:
...
[26038.210560] Active:286794 inactive:98690 dirty:0 writeback:0 unstable:0
[26038.210562] free:68642 slab:36081 mapped:39657 pagetables:1246 bounce:0
[26038.210569] DMA free:10064kB min:68kB low:84kB high:100kB active:2144kB inactive:56kB present:16256kB pages_scanned:0 all_unreclaimable? no
[26038.210575] lowmem_reserve[]: 0 873 2014 2014
[26038.210585] Normal free:247032kB min:3744kB low:4680kB high:5616kB active:226992kB inactive:164276kB present:894080kB pages_scanned:0 all_unreclaimable? no
[26038.210591] lowmem_reserve[]: 0 0 9134 9134
```

```
[26038.210601] HighMem free:17472kB min:512kB low:1736kB high:2960kB active:918040kB inactive:230428kB present:1169228kB pages_scanned:0 all_unreclaimable? no [26038.210607] lowmem_reserve[]: 0 0 0 0 [26038.210614] DMA: 122*4kB 63*8kB 45*16kB 9*32kB 2*64kB 0*128kB 1*256kB 1*512kB 1*1024kB 1*2048kB 1*4096kB = 10064kB [26038.210632] Normal: 6196*4kB 4435*8kB 3053*16kB 1624*32kB 663*64kB 202*128kB 41*256kB 6*512kB 0*1024kB 0*2048kB 1*4096kB = 247032kB [26038.210650] HighMem: 280*4kB 230*8kB 55*16kB 28*32kB 13*64kB 47*128kB 17*256kB 1*512kB 1*1024kB 0*2048kB 0*4096kB = 17472kB ...
```

Using the "Magic" SysRq is interesting right? See *Documentation/sysrq.txt* for details.

```
In terms of code:
```

A related question: what exactly determines the number of pages assigned to a zone watermark (min, low, high) level?

```
The answer is encoded in the function: 
<code>mm/page_alloc.c:setup_per_zone_wmarks</code>

which in turn is dependent on (the value of <code>min_free_kbytes</code>) and invoked by: 
<code>init_per_zone_wmark_min()</code>

The comment above the function <code>init_per_zone_wmark_min()</code> explains this: 
...

/*
```

```
* Initialise min_free_kbytes.
* For small machines we want it small (128k min). For large machines
* we want it large (64MB max). But it is not linear, because network
* bandwidth does not increase linearly with machine size. We use
   min_free_kbytes = 4 * sqrt(lowmem_kbytes), for better accuracy:
   min free kbytes = sqrt(lowmem kbytes * 16)
* which yields
* 16MB:
           512k
* 32MB:
           724k
* 64MB:
           1024k
* 128MB:
           1448k
* 256MB:
           2048k
* 512MB:
           2896k
* 1024MB: 4096k
* 2048MB: 5792k
* 4096MB: 8192k
* 8192MB: 11584k
* 16384MB: 16384k
int __meminit init_per_zone_wmark_min(void)
--snip--
```

From Documentation/sysctl/vm.txt

min_free_kbytes:

This is used to force the Linux VM to keep a minimum number of kilobytes free. The VM uses this number to compute a watermark[WMARK_MIN] value for each lowmem zone in the system. Each lowmem zone gets a number of reserved free pages based proportionally on its size.

Some minimal amount of memory is needed to satisfy PF_MEMALLOC allocations; if you set this to lower than 1024KB, your system will become subtly broken, and prone to deadlock under high loads.

Setting this too high will OOM your machine instantly.

Sysctl – some useful VM Tunables

Source: Kernel documentation on /proc/sys entries: Documentation/sysctl/vm.txt

Also very useful: http://balodeamit.blogspot.com/2015/11/deep-dive-into-linux-memory-management.html

[...]

dirty_background_ratio

Contains, as a percentage of total available memory that contains free pages and reclaimable pages, the number of pages at which the background kernel flusher threads will start writing out dirty data.

The total available memory is not equal to total system memory.

```
# cat /proc/sys/vm/dirty_background_ratio
10
#
```

So, by default, the kernel will start background writing memory pages to disk when 10% of them are dirtied.

$[\ldots]$

dirty ratio

Contains, as a percentage of total available memory that contains free pages and reclaimable pages, the number of pages at which a process which is generating disk writes will itself start writing out dirty data.

The total available memory is not equal to total system memory.

```
# cat /proc/sys/vm/dirty_ratio
20
#

Default: 20
[...]
page-cluster
```

page-cluster controls the number of pages up to which consecutive pages are read in from swap in a single attempt. This is the swap counterpart to page cache readahead.

The mentioned consecutivity is not in terms of virtual/physical addresses, but consecutive on swap space - that means they were swapped out together.

It is a logarithmic value - setting it to zero means "1 page", setting it to 1 means "2 pages", setting it to 2 means "4 pages", etc. Zero disables swap readahead completely.

The default value is three (eight pages at a time). There may be some small benefits in tuning this to a different value if your workload is swap-intensive.

Lower values mean lower latencies for initial faults, but at the same time extra faults and I/O delays for following faults if they would have been part of that consecutive pages readahead would have brought in.

```
# cat /proc/sys/vm/page-cluster
3
#
```

swappiness

This control is used to define how aggressive(ly) the kernel will swap memory pages. Higher values will increase agressiveness, lower values decrease the amount of swap. A value of 0 instructs the kernel not to initiate swap until the amount of free and file-backed pages is less than the high water mark in a zone.

The default value is 60.

This percentage value controls the tendency of the kernel to reclaim the memory which is used for caching of directory and inode objects.

At the default value of vfs_cache_pressure=100 the kernel will attempt to reclaim dentries and inodes at a "fair" rate with respect to pagecache and swapcache reclaim. Decreasing vfs_cache_pressure causes the kernel to prefer to retain dentry and inode caches. When vfs_cache_pressure=0, the kernel will

never reclaim dentries and inodes due to memory pressure and this can easily lead to out-of-memory conditions. Increasing vfs_cache_pressure beyond 100 causes the kernel to prefer to reclaim dentries and inodes.

Increasing vfs_cache_pressure significantly beyond 100 may have negative performance impact. Reclaim code needs to take various locks to find freeable directory and inode objects. With vfs_cache_pressure=1000, it will look for ten times more freeable objects than there are.

Tuning these values appropriate to your particular workload could yield possible benefits. It's a painstaking job and delicate balance though; wrong tuning could result in performance loss. See this article for an example: *My Journey to Improve Disk Performance on the Raspberry Pi*.

OOM Killer

<< Notes below extracted from ULK3, pg 710. >>

Despite the PFRA (Page Frame Reclamation Algorithm) effort to keep a reserve of free page frames << calls <code>shrink_all_memory(nr_to_reclaim)</code>, which is a wrapper over <code>do_try_to_free_pages()</code>, when caches (and other reclaimable pages) must be freed up >>, it is possible for the pressure on the virtual memory subsystem to become so high that all available memory becomes exhausted. This situation could quickly induce a freeze of every activity in the system: the kernel keeps trying to free memory in order to satisfy some urgent request, but it does not succeed because the swap areas are full and all disk caches have already been shrunken. As a consequence, no process can proceed with its execution, thus no process will eventually free up the page frames that it owns.

<<

So, the important thing here is:

When the system runs out of *all* memory, i.e., when RAM *and* swap are (almost) completely full, the OOM killer pays a visit!

Also note that on typical *embedded* systems, there is no swap space!

Good Resources:

- When Linux Runs Out of Memory.
- Surviving the Linux OOM Killer, Oct 2018

>>

<< <u>Src</u>

Script to display OOM Score and Oom Adj value of all processes alive

To cope with this dramatic situation, the PFRA makes use of a so-called **out of memory (OOM) killer**, which selects a process in the system and abruptly kills it to free its page frames. The OOM killer is like a surgeon that amputates the limb of a man to save his life: losing a limb is not a nice thing, but sometimes there is nothing better to do.

The <code>out_of_memory()</code> function is invoked by <code>__alloc_pages()</code> when the free memory is very low and the PFRA has not succeeded in reclaiming any page frames (see the section "The Zone Allocator" in Chapter 8). The function invokes <code>select_bad_process()</code> to select a victim among the existing processes, then invokes <code>oom_kill_process()</code> to perform the sacrifice.

<<

<u>Source – Memory FAQ</u>

Strict overcommit encourages the addition of gigabytes (even terabytes) of swap space, which leads to swap thrasing if it is ever used. Systems with large amounts of swap space can literally thrash for days, during which they perform less computation than they could perform in a single minute during non-thrashing operation (such as if the OOM killer triggered a reboot).

··· >>

Of course, *select_bad_process()* does not simply pick a process at random. The *selected* process should satisfy several requisites:

- The victim should own a large number of page frames, so that the amount of memory that can be freed is significant. (As a countermeasure against the "fork-bomb" processes, the function considers the amount of memory eaten by all children owned by the parent, too.)
- Killing the victim should lose a small amount of work it is not a good idea to kill a batch process that has been working for hours or days.
- The victim should be a low static priority (nice value) process the users tend to assign lower priorities to less important processes.
- The victim should **not** be a process with **root** privileges they usually perform important tasks.
- The victim should not directly access hardware devices (such as the X Window server), because the hardware could be left in an unpredictable state.
- The victim cannot be swapper (process 0), init (process 1), or any other kernel thread.

The <code>select_bad_process()</code> function scans every process in the system, uses an empirical formula to compute from the above rules a value that denotes how good selecting that process is, and returns the process descriptor address of the "best" candidate for eviction. Then, the <code>out_of_memory()</code> function invokes <code>oom_kill_process()</code> to send a deadly signal (usually SIGKILL; see Chapter 11) either to a child of that process or, if this is not possible, to the process itself. The <code>oom_kill_process()</code> function also kills all clones that share the same memory descriptor with the selected victim (basically, threads of the process).

*See*Introducing the OOM Killer [comic], Dzone :-)

Linux 2.6.36: "Recommended LWN article: Another OOM killer rewrite

The Out of Memory Killer is the part of the VM that kills a process when there's no memory (both RAM and swap) left. The algorithm that decides what is the better process to be killed has been rewritten in this release and should make better decisions.

Code: (commit), (commit)"



Daniel Stori (turnoff.us)

Here's a screenshot of *htop* output on a laptop sorted by "OOM score": ('chrome' (and/or 'brave' if alive) has the highest OOM scores; <eye-roll>:-))

```
10.7%]
                                                                                                    Hostname: kaiwan-T460
                     28.0%]
                                                                                                    Time: 12:36:33
                                                                                            7.4%]
                                                                                                    Uptime: 2 days, 80:55:34
                                                                                           25.7%]
                                                                                                    Tasks: 192; 2 running
                                                                                                    Load average: 0.72 0.96 1.16
                                                                                     1.07G/7.63G]
                                                                                                    Mem: 7.56G used: 5.85G buffers: 36.0M cache: 1.50G
      3481 12:21
                    13 kaiwan
                                        0 232M S
                                                      0.00 B/s
                                                                     3.0 0:10.94
                                                                                      315 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
                                                                0.0
                                         0 87440 S
       3481 Jan19
                                                      0.00 B/s
                                                                           0:42.38
                                                                                      313 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
                     9 kaiwan
                                                                                      307 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
       3481 Jan19
                                            99M S
                                                      0.00 B/s
                                                                0.0
                                                                     1.3
                                                                           0:28.38
26734
       3481 11:52
                    13 kaiwan
                                   20
                                        0
                                           215M S
                                                      0.00 B/s
                                                                0.0 2.8
                                                                           0:31.11
                                                                                      314 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
                                   20
                                           250M S
                                                      0.00 B/s
                                                                0.0
                                                                     3.2
                                                                                      320 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
25401
       3481 Jan19
                    13 kaiwan
                                        0
                                                                           1:11.12
                                                                                     317 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
319 B4 /opt/google/chrome/chrome --type=renderer --enable-feature
25294
       3481 Jan19
                                   20
                                        0 257M S
                                                      0.00 B/s
                                                                0.0 3.3 1:12.87
                    17 kaiwan
      3481 06:47
                                   20
                                           301M S
                                                                     3.9
                    12 kaiwan
                                        0
                                                      0.00 B/s
                                                                0.0
                                                                           0:22.11
23500
                                        0 212M S
                                                      0.00 B/s 0.0 2.7 15:05.45
                                                                                      14 B4 /usr/lib/libreoffice/program/soffice.bin --writer file://,
4919 4901 Jan19
                    12 kaiwan
```

From Documentation/sysctl/vm.txt:

...

oom_kill_allocating_task

This enables or disables killing the OOM-triggering task in out-of-memory situations.

If this is set to zero, the OOM killer will scan through the entire tasklist and select a task based on heuristics to kill. This normally selects a rogue memory-hogging task that frees up a large amount of memory when killed.

If this is set to non-zero, the OOM killer simply kills the task that triggered the out-of-memory condition. This avoids the expensive tasklist scan.

If panic_on_oom is selected, it takes precedence over whatever value is used in oom_kill_allocating_task.

The default value is 0.

•••

FAQ :: Disabling OOM on a Particular Process

Source: http://unix.stackexchange.com/questions/153585/how-oom-killer-decides-which-process-to-kill-first

. . .

Higher the value of oom_score of any process the higher is its likelihood of getting killed by the OOM Killer in an out-of-memory situation.

But how is the **00M_Score** calculated?

In David's patch set, the old badness() heuristics are almost entirely gone. Instead, the calculation turns into a simple question of what percentage of the available memory is being used by the process. If the system as a whole is short of memory, then "available memory" is the sum of all RAM and swap space available to the system. If, instead, the OOM situation is caused by exhausting the memory allowed to a given cpuset/control group, then "available memory" is the total amount allocated to that control group. A similar calculation is made if limits imposed by a memory policy have been exceeded. In each case, the memory use of the process is deemed to be the sum of its resident set (the number of RAM pages it is using) and its swap usage.

This calculation produces a percent-times-ten number as a result; a process which is using every byte of the memory available to it will have a score of 1000, while a process using no memory at all will get a score of zero. There are very few heuristic tweaks to this score, but the code does still subtract a small amount (30) from the score of root-owned processes on the notion that they are slightly more valuable than user-owned processes.

One other tweak which is applied is to add the value stored in each process's oom_score_adj variable, which can be adjusted via /proc. This knob allows the adjustment of each process's attractiveness to the OOM killer in user space; setting it to -1000 will disable OOM kills entirely, while setting to +1000 is the equivalent of painting a large target on the associated process.

snip			

Resource-

How to Configure the Linux Out-of-Memory Killer, by Robert Chase, Oracle

An experiment: Invoking the kernel OOM-Killer

One way to invoke the kernel's OOM killer is using the program shown below - a very simple "crazy allocator".

An alternate (easy) way to invoke it is by using the 'Magic-SysRq' facility, specifically command key 'f' will call *oom_kill* to kill a memory hog process (i.e. doing):

echo f > /proc/sysrq-trigger

!CAREFUL! Save your work first; some process(es) will die!

For details on SysRq usage, see *Documentation/sysrq.txt*).

```
$ cat oom_killer_try.c
 * oom-killer-try.c
 * Demo the kernel OOM killer by having this process call malloc()
 * repetedly without freeing.
 * Ultimately, the kernel will kill it via OOM.

* For a more "sure" kill, set the "force-page-fault" flag.
 ** WARNING **
 * Be warned that running this intensively can/will cause
 * heavy swapping on your system and will probably necessitate a
 * reboot.
 * Author: Kaiwan N Billimoria <kaiwan@designergraphix.com>
 * License: MIT
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#define BLK
                                   8192 // 2 pages
#define SEE MAPS FLAG
int force_page_fault=0;
 * This code (the cat,awk,.. commands) will actually stop working when
   memory ressure becomes high - as userspace app requests for memory will
   be ignored by the kernel.
static void see maps(void)
#if (SEE_MAPS_FLAG==1)
       int s:
       char cmd[128];
```

```
sprintf(cmd, "cat /proc/%d/maps |awk '$6==\"[heap]\" {print $0}' ;
      usleep 250000", getpid());
//printf("cmd: %s\n", cmd);
      s = system(cmd);
      if (s == -1) {
             perror("system");
       fflush(stdout);
#endif
int main( int argc, char **argv )
      char * p;
      int i=0, stepval=5000, verbose=0;
      if( argc < 3 ) {
             fprintf(stderr, "Usage: %s alloc-loop-count force-page-fault[0|1]
[verbose flag[0|1]]\n",argv[0]);
             exit(1);
      }
      printf("%s: PID %d\n", argv[0], getpid());
      if( atoi(argv[2])==1)
             force page fault=1;
      if (argc>=4) {
             if (atoi(argv[3])==1)
                   verbose=1;
      }
      do {
             p=(char *)malloc(BLK); << only "virtual" memory has been</pre>
               successfully allocated as of just now, not physical! >>
             if (verbose)
                    printf("%06d\taddr p = %x break = %x\n", ++i, (unsigned)p,
(unsigned)sbrk(0) );
             if(!p) {
                    fprintf (stderr, "%s: loop #%d: malloc failure.\n",
                      argv[0], i);
                    break;
             }
/* Force the MMU to raise page fault exception by writing into the page; (reading
or) writing a single byte, any byte, will
                                                            do the trick!
This is as the virtual address referenced will have no PTE entry, causing the MMU to
raise a page fault. The OS fault handler, being intelligent, figures out it's a "good
fault" and allocates a page frame. Only now do we have physical memory!
             if( force_page_fault ) {
                    p[4000] &= 0x14;
                    p[8000] |= 'a';
             if(!(i%stepval)) {
                                              // every 'stepval' iterations..
                    printf("%d...\n",i);
                    see maps();
```

```
usleep(250000); // to have time for sampling free mem..
}
i++;
} while( p && (i<atoi(argv[1])) );
see_maps();
return 0;
}
$</pre>
```

Source

• • •

Demand paging

The next question we need to address is how the page tables get created. Linux could create appropriate page-table entries whenever a range of virtual memory is allocated.

However, this would be wasteful because most programs allocate much more virtual memory than they ever use at any given time. For example, the text segment of a program often includes large amounts of error handling code that is seldom executed.

To avoid wasting memory on virtual pages that are never accessed, Linux uses a method called *demand paging*. With this method, the virtual address space starts out empty << we have only *virtual* pages, not physical >>. This means that, logically, all virtual pages are marked in the page table as **not present**.


When accessing a virtual page that is not present, the CPU (MMU, really) generates a *page fault*. This fault is intercepted by the Linux kernel and causes the page fault handler to be activated.

There, the kernel can allocate a new page frame, determine what the content of the accessed page should be (e.g., a new, zeroed page, a page loaded from the data section of a program, or a page loaded from the text segment of a program), load the page, and then update the page table to mark the page as present. Execution then resumes in the process with the instruction that caused the fault. Since the required page is now present, the instruction can now execute without causing a page fault.

• • •

Lets try out invoking the "OOM Killer" on an ARM-Linux system, a "Raspberry Pi" R2 Mode B board.

RASPBERRY PI MODEL B



The system is based on a Broadcom BCM2835 SoC, has 464 MB RAM (actually 512MB but some is shared with a VideoCore GPU). Thus, total RAM expressed in page frames = 464*1024/4 = 118,784.

Thus, if we allocate 2 pages in each malloc(), we can allocate a *theoretical* maximum of (118784 / 2) times = 59,392 times before we *completely* run out of memory! That too:

- we're ignoring the fact that some RAM is already in use
- embedded Linux systems that use flash chips as their secondary storage medium (the usual case), typically do not enable a swap partition. So, once we're out of RAM, we're out of virtual memory! (The R Pi running "Raspbian" Linux is an exception, though: it does have a default 100MB swap partition!).

RPi \$ cat /etc/issue
Debian GNU/Linux 7.0 \n \l

<< Raspbian >>

RPi \$ cat /proc/version

```
Linux version 3.6.11+ (kaiwan@asus-N53) (gcc version 4.4.1 (Sourcery G++ Lite 2010q1-
202) ) #1 PREEMPT Thu Feb 21 18:14:17 IST 2013
RPi $

RPi $ cat /proc/sys/vm/oom_kill_allocating_task
0
RPi $ cat /proc/sys/vm/oom_dump_tasks
1
RPi $
```

Experiment 1:

Worst case: (attempt to) loop 118,784 times, allocating 2 page frames per loop iteration to eat all memory. We say "page frames" as we shall turn On the "force-page-fault" flag, thus truly allocating two physical page frames per loop iteration!

(Think of this as having the OS instantiate page frames "on the fly" or "only when required" or "on demand"! More on this "memory overcommit feature" later...).

```
RPi $ free -m
             total
                         used
                                    free
                                                        buffers
                                                                    cached
                                              shared
Mem:
               464
                           98
                                     366
                                                         12
-/+ buffers/cache:
                           40
                                      424
                                      99
Swap:
                99
                            0
RPi$
RPi $ ./oom-killer-try
Usage: ./oom-killer-try alloc-loop-count force-page-fault[0|1] [verbose flag[0|1]]
RPi $
RPi $ ./oom-killer-try 118784 1
./oom-killer-try: PID 2148
0...
01512000-01535000 rw-p 00000000 00:00 0
                                                  [heap]
                                                             ← loop iteration count
01512000-03c3c000 rw-p 00000000 00:00 0
                                                  [heap]
10000...
01512000-06364000 rw-p 00000000 00:00 0
                                                  [heap]
01512000-08a68000 rw-p 00000000 00:00 0
                                                  [heap]
20000...
                                                  [heap]
01512000-0b190000 rw-p 00000000 00:00 0
01512000-0d895000 rw-p 00000000 00:00 0
                                                  [heap]
30000...
01512000-0ffbd000 rw-p 00000000 00:00 0
                                                  [heap]
35000...
system: Cannot allocate memory
                                    << perror output from the system(3) function >>
40000...
system: Cannot allocate memory
45000...
system: Cannot allocate memory
50000...
system: Cannot allocate memory
55000...
system: Cannot allocate memory
Killed
RPi $
```

```
<< Kernel Log >>
$ dmesq
[ 1316.727656] oom-killer-try invoked oom-killer: gfp mask=0x200da, order=0, oom adj=0,
oom score adi=0
<< Kernel-mode stack >>
[ 1316.727740] [<c001563c>] (unwind_backtrace+0x0/0xf4) from [<c00a36c0>]
  (dump_header+0x6c/0x200)
[ 1316.727777] [<c00a36c0>] (dump_header+0x6c/0x200) from [<c00a3e48>]
  (oom_kill_process+0x29c/0x3e4)
[ 1316.727811] [<c00a3e48>] (oom_kill_process+0x29c/0x3e4) from [<c00a42fc>]
  (out_of_memory+0x2d0/0x354)
[ 1316.727848] [<c00a42fc>] (out_of_memory+0x2d0/0x354) from [<c00a92b8>]
  (__alloc_pages_nodemask+0x5e4/0x61c) << The __alloc_pages_nodemask() function's, i.e.,</pre>
the buddy system's, failure to allocate memory causes it to invoke the out_of_memory()
function ! >>
[ 1316.727893] [<c00a92b8>] (__alloc_pages_nodemask+0x5e4/0x61c) from [<c00be5ec>]
                                          << the OS page fault handler 'understands' that this
  (handle_pte_fault+0x550/0x738)
is a legal request- thus it invokes __alloc_pages_nodemask() (the heart of the buddy systemallocator) to allocate a page frame. Until right now the allocation has succeeded, but now
                                       _alloc_pages_nodemask() (the heart of the buddy system
fails as the system hits OOM !!! >>
[ 1316.727928] [<c00be5ec>] (handle_pte_fault+0x550/0x738) from [<c00bec98>]
  (handle_mm_fault+0x98/0xcc)
[ 1316.727969] [<c00bec98>] (handle_mm_fault+0x98/0xcc) from [<c03f3c84>]
  (do page fault+0x2dc/0x414)
[ 1316.728006] [<c03f3c84>] (do_page_fault+0x2dc/0x414) from [<c00083d0>]
  (do_DataAbort+0x34/0x98)
[ 1316.728037] [<c00083d0>] (do_DataAbort+0x34/0x98) from [<c03f255c>]
  (__dabt_usr+0x3c/0x40)
                           << the write into the (as-of-now-invalid page frame triggers the
MMU to raise a Data Abort exception (on ARM), which in turn is hooked into the OS's page
fault handling code! >>
[ 1316.728057] Exception stack(0xdc841fb0 to 0xdc841ff8)
[ 1316.728079] 1fa0:
                                                           00002009 00016449 1e874bb8
  0000000
[ 1316.728104] 1fc0: 1e872bb8 00002009 b6f79288 1e872bb0 00018450 00000000 00002018
  00002710
 1316.728126] 1fe0: 00000004 bef2a618 b6ec072c b6ebe29c 60000010 ffffffff
 1316.728139] Mem-info:
[ 1316.728152] Normal per-cpu:
[ 1316.728167] CPU
                      0: hi: 186, btch: 31 usd:
[ 1316.728198] active_file:27 inactive_file:42 isolated_file:0
 1316.728198] unevictable:0 dirty:0 writeback:9716 unstable:0
[ 1316.728198] free:2048 slab_reclaimable:594 slab_unreclaimable:1571
  [\ldots]
[ 1316.754426] 2165 slab pages
[ 1316.754437] 370 pages shared
[ 1316.754447] 11998 pages swap cached
<< Table showing all processes with their memory usage and "oom score"; thus the kernel makes
a decision >>
                          << rss: resident-set-size: actual RAM usage (Kb) >>
 1316.754461] [ pid ]
                                                   rss nr_ptes swapents oom_score_adj name
                          uid tgid total_vm
 1316.754507
                  142]
                               142
                                         720
                                                     0
                                                                    133
                                                                                 -1000 udevd
                            0
                                                             5
[ 1316.754532] [
                  2561
                            0
                                256
                                         719
                                                     0
                                                             5
                                                                    137
                                                                                 -1000 udevd
[ 1316.754560] [
                                                                                 -1000 udevd
                  263]
                            0
                               263
                                         719
                                                                    135
[ 1316.754585] [ 1362]
                                                                                 -1000 ifplugd
                            0 1362
                                         436
                                                     7
                                                                    18
                            0 1383
                                                    7
                                                             4
                                                                                 -1000 ifplugd
[ 1316.754609] [ 1383]
                                         436
                                                                    16
[ 1316.754635] [ 1632] 0 1632
[ 1316.754659] [ 1692] 0 1692
[ 1316.754685] [ 1711] 65534 1711
                                                    0
                                                             5
                                                                    429
                                                                                 -1000 dhclient
                                        1223
                                        6992
                                                    1
                                                             7
                                                                    110
                                                                                    0 rsyslogd
                                                             5
                                         503
                                                     4
                                                                     26
                                                                                     0 thd
```

[1316.754709]	[1749]	0	1749	948	0	5	41	0 cron
snip								
[1316.755475]	[2060]	Θ	2060	2450	5	7	151	0 sshd
[1316.755500]	[2074]	1000	2074	2450	23	6	134	0 sshd
[1316.755525]	[2075]	1000	2075	1361	0	5	267	0 bash
[1316.755551]	[2148]	1000	2148	120097	99945	238	19731	0 oom-
killer-try								
[1316.755573]	Out of	memory:	Kill	process 214	48 (oom-	killer-tr	y) score	829 or sacrifice child
[1316.755596]	Killed	process	2148	(oom-kille	r-try) t	otal-vm:4	80388kB,	anon-rss:399736kB,
file-rss:44kB								
RPi\$								

<<

What exactly do the oom_score_adj and the "oom score" values mean?

Please look up documentation here:

https://www.kernel.org/doc/Documentation/filesystems/proc.txt section
"/proc/<pid>/oom_adj & /proc/<pid>/oom_score_adj - Adjust the oom-killer score"
for all details.

>>

RPi \$ fre	e-m					
	total	used	free	shared	buffers	cached
Mem:	464	76	388	0	1	14
-/+ buffers/cache:		60	404			
Swap:	99	59	40			
RPi \$						

Experiment 2:

(Attempt to) loop 118,784 times, allocating 2 virtual pages per loop iteration. We say "virtual pages" as we set the "force-page-fault" flag to zero; thus malloc() "succeeds" but only in a virtual sense- the virtual regions are successfully allocated but *no physical page frames* have been allocated (yet). This will happen only on a subsequent (future) access to the page(s).

```
RPi $ ./oom-killer-try
```

Usage: ./oom-killer-try alloc-loop-count force-page-fault[0|1] [verbose_flag[0|1]]

```
35000...
addr p = 0x1219f5c8 break = 0x121be000
40000...
addr p = 0x148b9208 break = 0x148c2000
45000...
addr p = 0x16fd2e48 break = 0x16feb000
50000...
addr p = 0x196eca88 break = 0x196f1000
55000...
addr p = 0x1be066c8 break = 0x1be17000
60000...
addr p = 0x1e520308 break = 0x1e53f000
65000...
addr p = 0x20c39f48 break = 0x20c44000
70000...
addr p = 0x23353b88 break = 0x2336c000
75000...
addr p = 0x25a6d7c8 break = 0x25a72000
80000...
addr p = 0x28187408 break = 0x28198000
85000...
addr p = 0x2a8a1048 break = 0x2a8c0000
90000...
addr p = 0x2cfbac88 break = 0x2cfc7000
95000...
addr p = 0x2f6d48c8 break = 0x2f6ed000
100000...
addr p = 0x31dee508 break = 0x31df3000
105000...
addr p = 0x34508148 break = 0x3451b000
110000...
addr p = 0x36c21d88 break = 0x36c42000
115000...
addr p = 0x3933b9c8 break = 0x39348000
RPi $
```

Experiment 3:

READ-ONLY Worst case: (attempt to) loop 118,784 times, allocating 2 page frames per loop iteration to eat all memory. We say "page frames" as we shall turn On the "force-page-fault" flag, thus truly allocating two physical page frames per loop iteration!

However, this time we don't write to two bytes of the two pages (as we did in *Experiment 1*); instead, we just read 2 bytes from the 2 pages.

What do we find?

It *still* causes the OOM-killer to be invoked, as even a read operation on the malloc'ed page triggers a page fault!

```
y = p[8000];
#endif
<< On an x86_64 >>
$ ./rdpg_oom_try 9000000 1
./rdpg_oom_try: PID 3084
0...
5000...
10000...
15000...
20000...
25000...
30000...
--snip--
780000...
785000...
790000...
Killed
$
```

An actual case of the OOM-killer being invoked; on an x86_64 Ubuntu 16.04 desktop. What was running? A <u>Yocto</u> build! Heavyweight, indeed!

\$ bitbake core-image-minimal

```
[...]
```

```
Initialising tasks: 100% |
#| Time: 0:00:04
NOTE: Executing SetScene Tasks
NOTE: Executing RunQueue Tasks
WARNING: zlib-native-1.2.8-r0 do fetch: Failed to fetch URL
http://downloads.sourceforge.net/libpng/zlib/1.2.8/zlib-1.2.8.tar.xz, attempting MIRRORS if
available
ERROR: Worker process (12167) exited unexpectedly (-9), shutting down...
ERROR: Worker process (12167) exited unexpectedly (-9), shutting down...
ERROR: Worker process (12167) exited unexpectedly (-9), shutting down...
ERROR: Worker process (12167) exited unexpectedly (-9), shutting down...
$ cat /proc/sys/vm/oom_dump_tasks /proc/sys/vm/oom_kill_allocating_task
1
$ cat /proc/sys/vm/overcommit_kbytes /proc/sys/vm/overcommit_memory
/proc/sys/vm/overcommit_ratio
```

```
0
50
$
$ dmesq
[\ldots]
Out of memory: Kill process 9742 (chrome) score 304 or sacrifice child
Killed process 9742 (chrome) total-vm:886128kB, anon-rss:25372kB, file-rss:50412kB
Purging GPU memory, 59195392 bytes freed, 135168 bytes still pinned.
38998016 and 0 bytes still available in the bound and unbound GPU page lists.
Purging GPU memory, 26406912 bytes freed, 135168 bytes still pinned.
35725312 and 0 bytes still available in the bound and unbound GPU page lists.
[...]
CPU: 2 PID: 2758 Comm: compiz Tainted: G
                                                   OE 4.4.0-62-generic #83-Ubuntu
Hardware name: LENOVO 20FMA089IG/20FMA089IG, BIOS R06ET39W (1.13 ) 07/11/2016
  000000000000286 0000000013e88cca ffff8802195a7510 ffffffff813f7c63
  ffff8802195a76e8 ffff880213dc5a00 ffff8802195a7580 ffffffff8120ad4e
  000000000000015 00000000000000 ffff880237061e40 ffff8801b00f3f08
 Call Trace:
  [<fffffff813f7c63>] dump_stack+0x63/0x90
  [<fffffff8120ad4e>] dump header+0x5a/0x1c5
  [<fffffff811926c2>] oom_kill_process+0x202/0x3c0
  [<fffffff81192ae9>] out of memory+0x219/0x460
  [<fffffff81198a5d>] __alloc_pages_slowpath.constprop.88+0x8fd/0xa70
  [<fffffff81198e56>] __alloc_pages_nodemask+0x286/0x2a0
  [<fffffff811e270c>] alloc pages current+0x8c/0x110
  [<fffffff81196ae9>] alloc kmem pages+0x19/0x90
  [<fffffff811b448e>] kmalloc_order_trace+0x2e/0xe0
  [<ffffffff811ee48e>] __kmalloc+0x22e/0x250
  [<fffffffc03bdc7f>] ? alloc_gen8_temp_bitmaps+0x2f/0x80 [i915 bpo]
  [<fffffffc03bdc98>] alloc_gen8_temp_bitmaps+0x48/0x80 [i915_bpo]
  [<fffffffc03c1230>] gen8 alloc va range 3lvl+0xa0/0x9d0 [i915 bpo]
  [<fffffff811aad1a>] ? shmem_getpage_gfp+0xca/0x830
  [<fffffff811e270c>] ? alloc_pages_current+0x8c/0x110
  [<fffffff8140892a>] ? sg init table+0x1a/0x40
  [<fffffff8142160d>] ? swiotlb_map_sg_attrs+0x6d/0x130
  [<fffffffc03c1d9f>] gen8_alloc_va_range+0x23f/0x4a0 [i915_bpo]
  [<fffffffc03c3e8b>] i915 vma bind+0x9b/0x180 [i915 bpo]
  [<fffffffc03cb4e3>] i915_gem_object_do_pin+0x873/0xae0 [i915_bpo]
  [<fffffffc03cb77d>] i915_gem_object_pin+0x2d/0x30 [i915_bpo]
  [<fffffffc03b8d89>] i915_gem_execbuffer_reserve_vma.isra.18+0x99/0x160 [i915_bpo]
  [<fffffffc03b91d5>] i915_gem_execbuffer_reserve.isra.19+0x385/0x3c0 [i915_bpo]
  [<fffffffc03ba65f>] i915_gem_do_execbuffer.isra.22+0x6bf/0x11e0 [i915_bpo]
  [<fffffffc03c4e2d>] ? i915_gem_object_get_pages_gtt+0x23d/0x3f0 [i915_bpo]
  [<ffffffffc03a9134>] ? intel_runtime_pm_put+0x64/0xc0 [i915_bpo]
  [<fffffffc03cce0d>] ? i915_gem_pwrite_ioctl+0xdd/0x910 [i915_bpo]
  [<fffffffc03bbe02>] i915_gem_execbuffer2+0xc2/0x1e0 [i915_bpo]
  [<fffffffc0054752>] drm_ioctl+0x152/0x540 [drm]
  [<fffffffc03bbd40>] ? i915 gem execbuffer+0x330/0x330 [i915 bpo]
  [<fffffff812260ae>] ? dput+0x1ee/0x220
  [<fffffff8122f7a4>] ? mntput+0x24/0x40
  [<fffffff812107f0>] ? __fput+0x190/0x220
  [<fffffff812227af>] do_vfs_ioctl+0x29f/0x490
  [<fffffff812108be>] ? ____fput+0xe/0x10
```

```
[<fffffff8109efc6>] ? task_work_run+0x86/0xa0
   [<fffffff81222a19>] SyS_ioctl+0x79/0x90
   [<fffffff818385f2>] entry_SYSCALL_64_fastpath+0x16/0x71
Mem-Info:
   active_anon:271031 inactive_anon:208811 isolated_anon:0
437391 isolated_file:0
52794 writeback:0 unstable:0
[...]
```

Recent Update: kernel ver 4.6 released on 15 May 2016 Source

...

1.2. Improve the reliability of the Out Of Memory task killer

In previous releases, the OOM killer (which tries to kill a task to free memory) tries to kill a single task in a good hope that the task will terminate in a reasonable time and frees up its memory. In practice, it has been shown that it's easy to find workloads which break that assumption, and the OOM victim might take unbounded amount of time to exit because it might be blocked in the uninterruptible state waiting for an event which is blocked by another task looping in the page allocator. This release adds a specialized kernel thread oom_reaper that tries to reclaim memory by preemptively reaping the anonymous or swapped out memory owned by the OOM victim, under an assumption that such a memory won't be needed when its owner is killed anyway.

Recommended LWN article: <u>Toward more predictable and reliable out-of-memory handling</u>

...

SIDEBAR [OPTIONAL]

Q. What are the possible ways malloc might fail?

A. (By Robert Love)

malloc signifies failure by returning NULL. There are several failure cases:

Input validation. For example, you've asked for many gigabytes of memory in a single allocation. The exact limit (if any) differs by malloc implementation; POSIX says nothing about a maximum value, short of its type being a size_t.

Allocation failures. With a data segment-based malloc, this means brk failed. This occurs when the new data segment is invalid, the system is low on memory, or the process has exceeded its maximum data segment size (as specified by RLIMIT_DATA). With a mapping-based malloc,

this means mmap failed. This occurs when the process is out of virtual memory (specified by RLIMIT_AS), has exceeded its limit on mappings, or has requested too large a mapping. Note most modern Unix systems use a combination of brk and mmap to implement malloc, choosing between the two based on the size of the requested allocation.

You asked for a zero-sized allocation. Per POSIX, malloc may return NULL if you call malloc with a parameter of zero.

Most modern Unix systems allocate memory opportunistically. This means that memory is committed to during malloc, but is in fact not actually allocated until first access. In such systems, which include Linux, malloc itself will rarely fail, as it does not actually allocate any memory. Instead, the failure is pushed forward to first access. That is, malloc will return a valid pointer but a subsequent dereference of that pointer will result in SEGV or an out-of-memory (OOM) condition and process termination. This is called overcommit and is an intentional design choice. Many systems, such as Linux, let you turn off overcommit for the rare workload that desires strict committing.

Note also that malloc may legitimately crash (i.e. it is by design and thus not a bug in malloc) if there is heap corruption. For example, in many malloc implementations, double freeing a pointer results in heap corruption that may not be realized until a subsequent malloc.

SIDEBAR

Found an interesting Android application that seems to make direct use of (a variation of) the kernel OOM Killer – it's called the "Free Memory Cleaner" application. It (in it's creator's own words): "frees up memory space using the feature that system kills running apps by low memory killer when available memory is low..."!

Variation on OOM? Yup, Android kernels have a Google-enhancement called the Android "low-memory killer". It's not the same as the classic OOM-killer; the low-memory killer classifies processes into "groups" and kills those processes in the lowest (lower) priority groups. <u>Link</u>.

Linux Memory Overcommit

Important: malloc()'s Behaviour

As you can see from the above "oom-killer-try" program, malloc() (via the kernel) **really does not allocate physical RAM at the time of the call**; it merely marks a VM page(s) as reserved by you and applies COW semantics to share it with others (tasks) like you, as long as all of you treat it as read-only! It's only when you actually write data to the page, is the physical memory actually allocated and the page(s) become truly yours (COW on private pages).

From man malloc (on Linux):

NOTES

By default, Linux follows an optimistic memory allocation strategy. This means that when malloc() returns non-NULL there is no guarantee that the memory really is available. In case it turns out that the system is out of memory, one or more processes will be killed by the OOM killer. For more information, see the description of /proc/sys/vm/overcommit_memory and /proc/sys/vm/oom_adj in proc(5), and the Linux kernel source file Documentation/vm/overcommit-accounting.

Normally, malloc() allocates memory from the heap, and adjusts the size of the heap as required, using sbrk(2). When allocating blocks of memory larger than MMAP_THRESHOLD bytes, the glibc malloc() implementation allocates the memory as a private anonymous mapping using mmap(2). MMAP_THRESHOLD is 128 kB by default, but is adjustable using mallopt(3). Allocations performed using mmap(2) are unaffected by the RLIMIT_DATA resource limit (see getrlimit(2)).

[...]

Crashes in malloc(), calloc(), realloc(), or free() are almost always related to heap corruption, such as overflowing an allocated chunk or freeing the same pointer twice.

The malloc() implementation is tunable via environment variables; see mallopt(3) for details.

One can switch off this overcommitting behavior using a command like

echo 2 > /proc/sys/vm/overcommit memory


See also the kernel Documentation directory, files vm/overcommit-accounting and sysctl/vm.txt .

From one of Gustav Duarte's excellent blog articles:

--snip--

A VMA is like a contract between your program and the kernel. You ask for something to be done (memory allocated, a file mapped, etc.), the kernel says "sure", and it creates or updates the appropriate VMA. But it does not actually honor the request right away, it waits until a page fault happens to do real work. The kernel is a lazy, deceitful sack of scum; this is the fundamental principle of virtual memory. It applies in most situations, some familiar and some surprising, but the rule is that VMAs record what has been agreed upon, while PTEs reflect what has actually been done by the lazy kernel. These two data structures together manage a

program's memory; both play a role in resolving page faults, freeing memory, swapping memory out, and so on.



--snip--

Resources:

http://linuxtoolkit.blogspot.in/2011/08/tweaking-linux-kernel-overcommit.html When Linux runs out of memory

Source: Professional Linux Kernel Architecture by Wolfgang Mauerer, Wrox Press.

. . .

sysctl_overcommit_memory can be set with the help of the /proc/sys/vm/overcommit_memory .

```
# cat /etc/issue
Linux Mint 17 Qiana \n \l
# uname -r
3.13.0-24-generic
# cat /proc/sys/vm/overcommit_memory
0
# cat /proc/sys/vm/overcommit_ratio
50
```

Currently there are three overcommit options:

- 1 : allows an application to allocate as much memory as it wants, even more than is permitted by the address space of the system.
- 0 : << the default >> means that heuristic overcommitting is applied with the result that the number of usable pages is determined by adding together the pages in the page cache, the pages in the swap area, and the unused page frames; requests for allocation of a smaller number of pages are permitted.
- 2 : stands for the strictest mode, known as strict overcommitting, in which the permitted number of pages that can be allocated is calculated as follows:

```
allowed = (totalram_pages - hugetlb) * sysctl_overcommit_ratio / 100;
allowed += total_swap_pages;
```

Here sysctl_overcommit_ratio is a configurable kernel parameter that is usually set to 50. If the total number of pages used exceeds this value, the kernel refuses to perform further allocations.

Why does it make sense to allow an application to allocate more pages than can ever be handled in principle? This is sometimes required for scientific applications. Some tend to allocate huge amounts of memory without actually requiring it — but, in the opinion of the application authors, it seems good to have it just in case. If the memory will, indeed, never be used, no physical page frames will ever be allocated, and no problem arises.

Such a programming style is clearly bad practice, but unfortunately this is often no criterion for the value of software. Writing clean code is usually not rewarding in the scientific community outside computer science. There is only immediate interest that a program works for a given configuration, while efforts to make programs future-proof or portable do not seem to provide immediate benefits and are therefore often not valued at all.

...

From *Documentation/sysctl/vm.txt*:

•••

overcommit memory:

This value contains a flag that enables memory overcommitment.

When this flag is 0, the kernel attempts to estimate the amount of free memory left when userspace requests more memory.

When this flag is 1, the kernel pretends there is always enough memory until it actually runs out.

When this flag is 2, the kernel uses a "never overcommit" policy that attempts to prevent any overcommit of memory.

This feature can be very useful because there are a lot of programs that malloc() huge amounts of memory "just-in-case" and don't use much of it.

The default value is 0.

See *Documentation/vm/overcommit-accounting* and *smm/mmap.c::__vm_enough_memory()* for more information.

overcommit_ratio:

When overcommit_memory is set to 2, the committed address space is not permitted to exceed swap plus this percentage of physical RAM. See above.

• • •

Useful Reference on the linux-mm wiki site:

OverCommit Accounting

Interesting, see:

Quora: What are the disadvantages of disabling memory overcommit in Linux?

Snippets:

• • •

<u>Nelson Elhage</u>, Kernel hacker and security guy. <u>Written Jan 25, 2012</u>

As I understand it, one of the biggest issues that, without memory overcommit, fork() must be accounted for as though it was *not* copy-on-write, since in theory the child could scribble over every writable page in its address space, and the kernel would have to allocate fresh pages for all of them.

Thus, a fork()ing server that spawns a new child for every request, or even has a request pool of N children, will effectively reserve N times as much memory (now unusable by anyone else), even though in practice the workers will never un-CoW most of those pages.

Similarly, as User mentioned, a process with a 10GB heap on a machine with 15G of RAM can't fork() and exec() children at all, since the kernel has no way of knowing that the child after the fork() won't go ahead and touch all 10G of that heap, and so the kernel must refuse the fork().

. . .

As an anecdote, I had coworker once who did make a point of turning off

overcommit on his laptop. Almost everything worked fine, but he was unable to run **gitk** on linux-2.6.git, even though it worked fine under near-identical conditions with overcommit turned on. The problem, of course, is exactly the one I just described: gitk would consume around 2GB of his 4GB of RAM, and when it tried to fork() and exec() **git** to read information about the repository, the kernel would not allow it, because it had to account for the possibility of the **gitk** child consuming another 2GB.

As far as I can tell, many people who claim "malloc() should just return NULL" have not thought about the problem very hard, yet. The real issue is not just related to malloc(), but to the subtler issues of CoW mappings and other lazily-allocated mappings (including the anonymous mmap()s that often back malloc()).

. . .

This is not to say that overcommit is always the right answer -- in e.g. embedded environments, or tightly controlled and carefully provisioned server environments, where you can enforce rules about which primitives and workloads actually happen in practice, you have more options, and/or it may be more important to make sure that the OOM killer never strikes.

```
Mark Hahn, computer guy
Written Jan 26, 2012
```

first, fork does not cause a giant copy as described.

the default vm.overcommit_memory mode works well, because it's very normal for processes to have only a fraction of their virtual address space resident. do this:

```
|ps -A --no-headers -o rss,vsz|awk '{r+=$1;v+=$2}END{print r,v,r/v}' on my desktop, rss is 12% of vsz (in total). setting vm.overcommit=2 is the conservative approach, which lets you guarantee never to OOM. instead, an allocation too far will indeed return an error, which the program can handle.
```

• • •

On my Ubuntu 16.04 LTS desktop with 8GB RAM:

```
$ ps -A --no-headers -o rss,vsz|awk '{r+=$1;v+=$2}END{print r,v,r/v}'
6493128 79326172 0.0818535
$
```

Implying that the ratio of RSS:VSZ at this point in time is just about 8%!

1

Page Faults

Source: "Linux Kernel's Memory Management Unit API" by Bill Gatliff.

When a process tries to access memory in a page that is not known to the MMU, the MMU generates a page fault exception. The page fault exception handler examines the state of the MMU hardware and the currently running process's memory information, and determines whether the fault is a "good" one, or a "bad" one. Good page faults cause the handler to give more memory to the process; bad faults cause the handler to terminate the process.

Good page faults are expected behavior, and occur whenever a program allocates dynamic memory, runs a section of code or writes a section of data for the first time, or increases its stack size. When the *process attempts to access* this new memory, the MMU declares a page fault, and the OS adds a fresh page of memory to the process's page table. The interrupted process is then resumed.

Bad faults occur when a process follows a NULL pointer, or tries to access memory that it doesn't own. Bad faults can also occur due to programming bugs in the kernel, in which case the handler will print an "oops" message before terminating the process.


<<

The <u>SAR (System Activity Report)</u> project is useful to get a birds-eye view of system activity (usually for servers). Your author setup sar and captured the day's stats; then viewed them via a useful GUI tool - kSar.

We take a peek at the 'Paging Activity' column and it's graphing: the interesting thing to notice now:

- the high number of *minor* faults / sec (bottom graph red colour) occurring pretty often) –
 it's "normal behavior"!
- The low number of *major* faults / sec (bottom graph black colour it's almost non-exitstant in fact); major faults imply a disk access and thus a major slowdown.

See the screenshot below:



The Page Fault Exception Handler - In Brief


Source: ULK3

--snip--

>>

The Linux Page Fault exception handler must distinguish exceptions caused by programming errors from those caused by a reference to a page that legitimately belongs to the process address space but simply hasn't been allocated yet.

The memory region descriptors allow the exception handler to perform its job quite efficiently. The do_page_fault() function, which is the Page Fault interrupt service routine for the 80 x 86 architecture, compares the linear address that caused the Page Fault against the memory regions of the current process; it can thus determine the proper way to handle the exception according to the scheme that is illustrated in the figure below.



Overall Scheme for the Page Fault handler

In practice, things are a lot more complex because the Page Fault handler must recognize several particular subcases that fit awkwardly into the overall scheme, and it must distinguish several kinds of legal access.

--snip--

Source - Memory FAQ

. . .

What is a page fault handler?

A page fault handler is an interrupt routine, called by the Memory Management Unit in response an attempt to access virtual memory which did not immediately succeed.

When a program attempts to read, write, or execute memory in a page that

hasn't got the appropriate permission bits set in its page table entry to allow that type of access, the instruction generates an interrupt. This calls the page fault handler to examines the registers and page tables of the interrupted process and determine what action to take to handle the fault.

The page fault handler may respond to a page fault in three ways:

- 1) The page fault handler can resolve the fault by immediately attaching a page of physical memory to the appropriate page table entry, adjusting the entry, and resuming the interrupted instruction. This is called a "soft fault".
- 2) When the fault handler can't immediately resolve the fault, it may suspend the interrupted process and switch to another while the system works to resolve the issue. This is called a "hard fault", and results when an I/O operation most be performed to prepare the physical page needed to resolve the fault.
- 3) If the page fault handler can't resolve the fault, it sends a signal (SIGSEGV) to the process, informing it of the failure. Although a process can install a SIGSEGV handler (debuggers and emulators tend to do this), the default behavior of an unhandled SIGSEGV is to kill the process with the message "bus error".

A page fault that occurs in an interrupt handler is called a "double fault", and usually panics the kernel. The double fault handler calls the kernel's panic() function to print error messages to help diagnose the problem. The process to be killed for accessing memory it shouldn't is the kernel itself, and thus the system is too confused to continue.

http://en.wikipedia.org/wiki/Double_fault

A triple fault cannot be handled in software. If a page fault occurrs in the double fault handler, the machine immediately reboots.

http://en.wikipedia.org/wiki/Triple_fault

How does the page fault handler allocate physical memory?

The Linux kernel uses lazy (on-demand) allocation of physical pages, deferring the allocation until necessary and avoiding allocating physical pages which will never actually be used.

Memory mappings generally start out with no physical pages attached. They define virtual address ranges without any associated physical memory. So malloc() and similar allocate space, but the actual memory is allocated later by the page fault handler.

Virtual pages with no associated physical page will have the read, write, and execute bits disabled in their page table entries. This causes any access to that address to generate a page fault, interrupting the program and calling the page fault handler.

When the page fault handler needs to allocate physical memory to handle a page fault, it zeroes a free physical page (or grabs a page from a pool of prezeroed pages), attaches that page of memory to the Page Table Entry associated with the fault, updates that PTE to allow the appropriate access, and resumes the faulting instruction.

Note that implementing this requires two sets of page table flags for read, write, execute, and share. The VM_READ, VM_WRITE, VM_EXEC, and VM_SHARED flags (in linux/mm.h) are used by the MMU to generate faults. The VM_MAYREAD, VM_MAYWRITE, VM_MAYEXEC, and VM_MAYSHARE flags are used by the page fault handler to determine whether the attempted access was legal and thus the fault handler should adjust the PTE to resolve the fault and allow the process to continue.

How does fork work?

The fork() system call creates a new process by copying an existing process. A new process is created with a copy of the page tables that calls fork(). These page tables are all copy on write mappings sharing the existing physical pages between parent and child.

How	does	exec	work?

...

Minimally Testing the MMU and Linux OS page fault handling

The user-mode C program below will attempt various illegal memory accesses.

The MMU will thus trigger an appropriate exception condition and invoke the OS's page fault handler. The OS page fault handler will go through a very detailed algorithm (short flowchart version shown above), in order to determine the actual fault (minor or major, good or bad) and, in these cases, being a usermode 'bad' fault, will send SIGSEGV to 'current'!

```
$ cat segv_pgfault.c
* segv_pgfault.c
* Make a usermode process segfault by accessing invalid user/kernel-space addresses..
* This in turn will have the MMU trigger an exception condition (Data Abort on
* ARM), which will lead to the OS's page fault handler being invoked. *It* will
* determine the actual fault (minor or major, good or bad) and, in this case, being
* a usermode 'bad' fault, will send SIGSEGV to 'current'!
* Author(s) : Kaiwan NB
* License(s): MIT
*/
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <signal.h>
#include <string.h>
#include <ctype.h>
/*-----*/
typedef unsigned int u32;
typedef long unsigned int u64;
/*----*/
#if __x86_64__ /* 64-bit; __x86_64__ works for gcc */
#define ADDR_TYPE u64
#define ADDR_FMT "%016lx"
static u64 rubbish_uaddr = 0x100000L;
static u64 rubbish kaddr = 0xffff0a8700100000L;
#else
#define ADDR_TYPE u32
#define ADDR_FMT "%08lx"
static u32 rubbish_uaddr = 0x100000L;
static u32 rubbish_kaddr = 0xd0100000L;
#endif
/*-----Functions -----*/
static void myfault(int signum, siginfo_t * siginfo, void *rest)
```

```
static int c = 0;
       printf("*** %s: [%d] received signal %d. errno=%d\n"
              " Cause/Origin: (si_code=%d): ",
              __func__, ++c, signum, siginfo->si_errno, siginfo->si_code);
       switch (siginfo->si_code) {
      case SI_USER:
             printf("user\n");
             break;
      case SI_KERNEL:
             printf("kernel\n");
             break;
      case SI_QUEUE:
             printf("queue\n");
             break;
       case SI_TIMER:
             printf("timer\n");
             break;
      case SI_MESGQ:
             printf("mesgq\n");
             break;
      case SI_ASYNCIO:
             printf("async io\n");
             break;
       case SI_SIGIO:
             printf("sigio\n");
             break;
       case SI_TKILL:
             printf("t[g]kill\n");
             break;
             // other poss values si_code can have for SIGSEGV
       case SEGV_MAPERR:
             printf("SEGV_MAPERR: address not mapped to object\n");
             break;
       case SEGV_ACCERR:
             printf("SEGV_ACCERR: invalid permissions for mapped object\n");
             break;
       default:
             printf("-none-\n");
      printf(" Faulting addr=0x" ADDR_FMT "\n", (ADDR_TYPE) siginfo->si_addr);
#if 1
      exit (1);
#else
      abort();
#endif
static void usage(char *nm)
       fprintf(stderr, "Usage: %s u|k r|w\n"
             "u => user mode\n"
             "k => kernel mode\n"
             " r => read attempt\n" " w => write attempt\n", nm);
}
```

```
int main(int argc, char **argv)
      struct sigaction act;
      if (argc != 3) {
             usage(argv[0]);
             exit(1);
      act.sa_sigaction = myfault;
      act.sa_flags = SA_RESTART | SA_SIGINFO;
      sigemptyset(&act.sa_mask);
      if (sigaction(SIGSEGV, &act, 0) == -1) {
             perror("sigaction");
             exit(1);
      }
      if ((tolower(argv[1][0]) == 'u') \&\& tolower(argv[2][0] == 'r')) {
             ADDR_TYPE *uptr = (ADDR_TYPE *) rubbish_uaddr;
                                               // an arbitrary userspace virtual addr
             printf
                 ("Attempting to read contents of arbitrary usermode"
                  "va uptr = 0x" ADDR_FMT ":\n",
                  (ADDR_TYPE) uptr);
             printf("*uptr = 0x" ADDR_FMT "\n", *uptr);
                                                           // just reading
      } else if ((tolower(argv[1][0]) == 'u') \&\& tolower(argv[2][0] == 'w')) {
             ADDR_TYPE *uptr = (ADDR_TYPE *) & main;
             printf
                  ("Attempting to write into arbitrary usermode"
                  "va uptr (&main actually) = 0x" ADDR_FMT ":\n",
                  (ADDR_TYPE) uptr);
             *uptr = 40; // writing
      } else if ((tolower(argv[1][0]) == 'k') \&\& tolower(argv[2][0] == 'r'))  {
             ADDR_TYPE *kptr = (ADDR_TYPE *) rubbish_kaddr;
                                               // arbitrary kernel virtual addr
             printf
                  ("Attempting to read contents of arbitrary"
                  "kernel va kptr = 0x" ADDR_FMT ":\n",
                  (ADDR TYPE) kptr);
             printf("*kptr = 0x" ADDR_FMT "\n", *kptr);  // just reading
      } else if ((tolower(argv[1][0]) == 'k') \&\& tolower(argv[2][0] == 'w')) {
             ADDR_TYPE *kptr = (ADDR_TYPE *) rubbish_kaddr;
                                               // arbitrary kernel virtual addr
             printf
                 ("Attempting to write into arbitrary kernel va kptr = 0x"
                    ADDR_FMT ":\n",
                  (ADDR_TYPE) kptr);
             *kptr = 0x62;// writing
      } else
             usage(argv[0]);
      exit(0);
}
/* vi: ts=4 */
$ ./segv_pgfault
Usage: ./segv_pgfault u|k r|w
```

```
u => user mode
k => kernel mode
r => read attempt
w => write attempt
0n an x86_64
$ ./seqv pqfault u r
Attempting to read contents of arbitrary usermode va uptr = 0x0000000000100000:
*** myfault: [1] received signal 11. errno=0
Cause/Origin: (si_code=1): SEGV_MAPERR: address not mapped to object
Faulting addr=0x0000000000100000
$ ./segv_pgfault u w
Attempting to write into arbitrary usermode va uptr (&main actually) =
0x0000000000400904:
*** myfault: [1] received signal 11. errno=0
Cause/Origin: (si code=2): SEGV ACCERR: invalid permissions for mapped object
Faulting addr=0x00000000000400904
$ ./segv_pgfault k r
Attempting to read contents of arbitrary kernel va kptr = 0xffff0a8700100000:
*** myfault: [1] received signal 11. errno=0
Cause/Origin: (si_code=128): kernel
<< security: the kernel va is not revealed >>
$
$ ./segv_pgfault k w
Attempting to write into arbitrary kernel va kptr = 0xffff0a8700100000:
*** myfault: [1] received signal 11. errno=0
Cause/Origin: (si_code=128): kernel
```

SIDEBAR :: KSM (Kernel Samepage Merging) Source

Kernel SamePage Merging (KSM) (also: Kernel Shared Memory, Memory Merging) lets the hypervisor system share identical memory pages amongst different processes or virtualized guests. This is done by scanning through the memory finding duplicate pages. The duplicate pair is then merged into a single page, and mapped into both original locations. The page is also marked as "copy-on-write", so the kernel will automatically separate them again should one process modify its data.[1]

KSM was originally intended to run more <u>virtual machines</u> on one host by <u>sharing</u> <u>memory</u> between <u>processes</u> as well as virtual machines. Upon <u>implementation</u>, it was found to be useful for non-virtualized environments as well where memory is at a premium.[2][3] An experimental implementation of KSM by Red Hat found that 52 virtual instances of Windows XP with 1GB of memory, could run on a host computer that had only 16GB of RAM.[4]

•••

Mainlined in 2.6.32.

KSM merges private anonymous pages, not pagecache ones. It's very useful to any application which generates many instances of the same data – QEMU running guest VMs and using *kvm* for acceleration – is a great example.

Source

Enabling KSM

KSM only operates on those areas of address space which an application has advised to be likely candidates for merging, by using the madvise(2) system call:

int madvise(addr, length, MADV MERGEABLE).

The app may call int madvise(addr, length, MADV_UNMERGEABLE) to cancel that advice and restore unshared pages: whereupon KSM unmerges whatever it merged in that range. Note: this unmerging call may suddenly require more memory than is available - possibly failing with EAGAIN, but more probably arousing the Out-Of-Memory killer.

More regarding KSM:

\$ man madvise

NAME

madvise - give advice about use of memory

SYNOPSIS

```
#include <sys/mman.h>
int madvise(void *addr, size_t length, int advice);
```

. . .

MADV_MERGEABLE (since Linux 2.6.32)

Enable Kernel Samepage Merging (KSM) for the pages in the range specified by addr and length. The kernel regularly scans those areas of user memory that have been marked as mergeable, looking for pages with identical content. These are replaced by a single write-protected page (which is automatically copied if a process later wants to update the content of the page).

KSM merges only private anonymous pages (see mmap(2)). The KSM feature is intended for applications that generate many instances of the same data (e.g., virtualization systems such as KVM).

It can consume a lot of processing power; use with care. See the Linux kernel source file Documentation/vm/ksm.txt for more details.

The MADV_MERGEABLE and MADV_UNMERGEABLE operations are available only if the kernel was configured with CONFIG_KSM.

```
MADV_UNMERGEABLE (since Linux 2.6.32)
```

Undo the effect of an earlier MADV_MERGEABLE operation on the specified address range; KSM unmerges whatever pages it had merged in the address range specified by addr and length.

•••

Useful!

Excellent: "Best Practices for KVM", IBM whitepaper. [PDF]

Relevant section: "Best practice: Over-commit memory resources by using page sharing or ballooning" pg 11-17 (covers using KSM for VMs best practices).

You can verify KSM is in action, by checking for the existence of some of its /sys files, under /sys/kernel/mm/ksm/

They are:

pages_shared pages are being used how many shared pages are being used how many more sites are sharing them i.e. how much saved how many pages unique but repeatedly checked for merging how many pages changing too fast to be placed in a tree full_scans how many times all mergeable areas have been scanned

[FYI / OPTIONAL]

Linux glibc malloc() Behaviour

The *first time* a process does an

malloc(8);

- the heap memory is not *physically* allocated yet, only *virtually* (remember, the kernel is a lazy guy!). (Technically, the kernel assigns or updates a VMA for this virtual region, marking it read-write, but *the PTE entry as read-only*. This is deliberate: it allows the kernel to catch the fault that will occur).
- Then, later, when the process attempts to write any address in this region, the MMU receives the virtual address. Now, the MMU will lookup the page tables to translate the virtual to a physical address; at this point, it will find the PTE is marked as read-only but a write is being attempted. Thus, the MMU raises a fault. Control goes to the the kernel's fault handler code; it "realizes" this is a good fault and allocates a page farme from the slab cache (possibly via the buddy allocator).

This is mapped into the faulting process's heap...

- Another request is made by the process, say: malloc(32);
- Now, since the glibc memory manager (what we call malloc) now knows that a full page is available in the heap and only 8 bytes are actually used up, this request will not cause a brk() syscall to the kernel. This can be verified by checking the current break (using sbrk(0)).

Also, seeking to within a page of the first request will – possibly, even probably - not cause a segfault even if the memory has not been programatically allocated! In fact, one finds that:

- a) glibc allocates a lot more than a page in the heap; it's often in the region of 130 Kb or so
- recent glibc does *not* grow the heap (and thus the data segment) when servicing malloc/calloc requests of more than MMAP_THRESHOLD (default: 128 kB). Instead, it uses the mmap(2) system call to setup a virtual region of the requested size. This is considered more efficient.

See below a program that helps us study how the system allocates memory dynamically to user-space applications via the usual malloc / calloc API.

```
$ cat malloc_brk_test.c
* malloc_brk_test.c
 * (c) Kaiwan NB.
 * License: MIT
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <malloc.h>
//#define USE_CALLOC
#undef USE_CALLOC
#define TRIES 5
void *heap_ptr[TRIES];
void *init_brk;
static void alloctest(int index, size_t num)
{
      void *p;
#ifndef USE_CALLOC
      p = malloc(num);
#else
      p = calloc(num, sizeof(char));
#endif
      if (!p) { printf("out of memory!\n"); exit(1); }
      heap_ptr[index] = p; // save ptr in order to free later..
#ifndef USE CALLOC
      printf("\n%d: malloc", index);
#else
      printf("\n%d: calloc", index);
#endif
      printf("(%6u) successful. Heap pointer: %8p\n", num, p);
      printf("Current break: %8p [delta: %d]\n", sbrk(0), (sbrk(0)-init_brk));
      malloc_stats();
}
int main (int argc, char **argv)
{
      int i;
      char *q;
      init_brk = sbrk(0);
      printf("Current break: %8p\n", init_brk);
      alloctest(0, 8);
      q=heap_ptr[0];
      *(q+3000) = 'a'; /* "should" segfault but (probably) does not
```

```
bcoz a *page* (or more) is allocated
                           by the previous alloc, not just 8 bytes!
                          See value of prg break compared to this
                          pointer.
                           */
      printf("(q+3000) is the mem loc 0x\%x. Mem here is: 0x\%08x\n",
             (unsigned int)(q+3000), *(q+3000));
      alloctest(1, (getpagesize()-8-5));
      alloctest(2, 3);
      alloctest(3, (sbrk(0)-init_brk+1000));
      alloctest(4, 200000);
      for (i=0; i<TRIES; i++)</pre>
             free(heap_ptr[i]);
      exit (0);
/* vi: ts=4 */
$ ./malloc_brk_test
Current break: 0x8e3e000
0: malloc( 8) successful. Heap pointer: 0x8e3e008
Current break: 0x8e5f000 [delta: 135168]
Arena 0:
system bytes
                     135168
                =
in use bytes =
                           16
Total (incl. mmap):
system bytes = 135168
in use bytes = 16
max mmap regions =
max mmap bytes =
                           0
                            0
(q+3000) is the mem loc 0x8e3ebc0. Mem here is: 0x00000061 << the
                                          'a' that we wrote in >>
1: malloc( 4083) successful. Heap pointer: 0x8e3e018
Current break: 0x8e5f000 [delta: 135168]
Arena 0:
system bytes =
in use bytes =
                       135168
                        4104
Total (incl. mmap):
system bytes = 135168
in use bytes = 4104
                       0
max mmap regions =
max mmap bytes =
                            0
2: malloc( 3) successful. Heap pointer: 0x8e3f010
Current break: 0x8e5f000 [delta: 135168]
Arena 0:
system bytes
                       135168
               =
in use bytes =
                       4120
Total (incl. mmap):
system bytes = 135168
in use bytes = 4120
max mmap regions =
                            0
                            0
max mmap bytes =
<< The 2^{nd} and 3^{rd} allocation above do not cause the brk syscall to be invoked, as
there is sufficient memory on the heap to service the requests >>
```

```
3: malloc(136168) successful. Heap pointer: 0xb77f5008
Current break: 0x8e5f000 [delta: 135168]
Arena 0:
system bytes = 135168
in use bytes = 4120
Total (incl. mmap):
system bytes = 274432
in use bytes = 143384
max mmap regions = 1
max mmap bytes = 139264
<< This (above) allocation request is a large one: ~132Kb. The 'mmap threshold' is
(default) 128Kb; thus, this causes an mmap() to the process virtual address space,
mapping in the virtually allocated region (which will later be mapped to physical
page frames via the MMU page-faulting on application access to these memory regions!
4: malloc(200000) successful. Heap pointer: 0xb77c4008
Current break: 0x8e5f000 [delta: 135168]
Arena 0:
system bytes = 135168
in use bytes = 4120
                         4120
Total (incl. mmap):
system bytes = 475136
in use bytes = 344088
max mmap regions = 2
max mmap bytes = 339968
<< Similarly, the large alloc above causes another mmap to occour >>
```

See the man page on mallopt(3) for details.

When malloc runs out of heap space it has to resort to invoking the system call sbrk(). In reality, sbrk is a wrapper: it invokes the actual system call brk(2):

```
malloc() \rightarrow sbrk() \rightarrow brk() \rightarrow sys\_brk() \rightarrow do\_brk()
\--- User Mode ---/ \--- Kernel Mode ---/
```

do_brk then either grows the existing VMA, or if it cannot, sets up a new VMA to mark the region as allocated.

If the requested allocation is \geq = MMAP_THRESHOLD (128Kb default), malloc internally uses the mmap(2) to setup a new VMA representing the (allocated) virtual address region.

For a (much) deeper understanding of the Linux heap, pl see: <u>Understanding the Heap & Exploiting Heap Overflows</u>, Mathy Vanhoef (good explanation, though the technique described is now a bit outdated by modern glibc).

<u>Source – Memory FAQ</u>

. . .

What are memory mappings?

A memory mapping is a set of page table entries describing the properties of a consecutive virtual address range. Each memory mapping has a start address and length, permissions (such as whether the program can read, write, or execute from that memory), and associated resources (such as physical pages, swap pages, file contents, and so on).

Creating new memory mappings allocates virtual memory, but not physical memory (except for a small amount of physical memory needed to store the page table itself). Physical pages are attached to memory mappings later, in response to page faults. Physical memory is allocated on-demand by the page fault handler as necessary to resolve page faults.

A page table can be thought of as a description of a set of memory mappings. Each memory mapping can be anonymous, file backed, device backed, shared, or copy on write.

The mmap() system call adds a new memory mapping to the current process's page tables. The munmap() system call discards an existing mapping.

Memory mappings cannot overlap << they are "tiled" >>. The mmap() call returns an error if asked to create overlapping memory mappings.

Virtual address ranges for which there is no current memory mapping are said to be "unmapped", and attempts to access them generate a page fault which cannot be handled. The page fault handler sends a Segmentation Violation signal (SIGSEGV) to the program on any access to unmapped addresses. This is generally the result of following a "wild pointer".

Note that by default, Linux intentionally leaves the first few kilobytes (or even megabytes) of each process's virtual address space unmapped, so that attempts to dereference null pointers generate an unhandled page fault resulting in an immediate SIGSEGV, killing the process.

...

What is an anonymous mapping?

Anonymous memory is a memory mapping with no file or device backing it. This is how programs allocate memory from the operating system for use by things like the stack and heap.

Initially, an anonymous mapping only allocates virtual memory. The new

mapping starts with a redundant copy on write mapping of the zero page. (The zero page is a single page of physical memory filled with zeroes, maintained by the operating system.) Every virtual page of the anonymous mapping is attached to this existing prezeroed page, so attempts to read from anywhere in the mapping return zeroed memory even though no new physical memory has been allocated to it yet.

Attempts to write to the page trigger the normal copy-on-write mechanism in the page fault handler, allocating fresh memory only when needed to allow the write to proceed. (Note, prezeroing optimizations change the implementation details here, but the theory's the same.) Thus "dirtying" anonymous pages allocates physical memory, the actual allocation call only allocates virtual memory.

Dirty anonymous pages can be written to swap space, but in the absence of swap they remain "pinned" in physical memory.

Anonymous mappings may be created by passing the MAP_ANONYMOUS flag to mmap().

What is a file backed mapping?

File backed mappings mirror the contents of an existing file. The mapping has some administrative data noting which file to map from, and at which offset, as well as permission bits indicating whether the pages may be read, written, or executed.

When page faults attach new physical pages to such a mapping, the contents of those pages is <u>initialized</u> by <u>reading</u> the contents of the file being mapped, at the appropriate offset for that page.

These physical pages are usually shared with the page cache, the kernel's disk cache of file contents. The kernel caches the contents of files when the page is read, so sharing those cache pages with the process reduces the total number of physical pages required by the system.

<< The "promise" of the page cache: exactly one physical page frame will be used at any point in time to map a page of a file. >>


Writes to file mappings created with the MAP_SHARED flag update the page cache pages, making the updated file contents immediately visible to other processes using the file, and eventually the cache pages will be flushed to disk updating the on-disk copy of the file.

Writes to file mappings created with the MAP_PRIVATE flag perform a copy on write, allocating a new local copy of the page to store the changes. These changes are not made visible to other processes, and do not update the on-disk copy of the file.

Note that this means writes to MAP_SHARED pages do not allocate additional physical pages (the page was already faulted into the page cache by the read, and the data can be flushed back to the file if the physical page is needed elsewhere), but writes to MAP_PRIVATE pages do (the copy in the page cache and the local copy the program needs diverge, so two pages are needed to store them, and flushing the page cache copy back to disk won't free up the local copy of the changed contents).

. . .

Process Virtual Memory Mapping



Source (above)

Very useful resource: <u>How The Kernel Manages Your Memory</u>, by Gustav Duarte.

- All processes share the kernel page tables starting at PAGE_OFFSET (value 0xc0000000), and have their own *process-specific* page tables for the range 0...PAGE_OFFSET-1. Thus, the process page tables are valid in kernel mode, which simplifies user-->kernel transitions.
- For each user process, the kernel *maintains an* **mm_struct** *describing the process's address space* this is in fact called the processes' *memory descriptor*. It is referred to by the *mm* field of the process descriptor.

Shown below are some relevant members of the process **memory descriptor** - the **mm struct** structure (**include/linux/sched.h**):

```
<< Page Directory - (re)stored
      pgd_t * pgd;
               into the CR3 register at context switch time >>
      atomic_t mm_users;
                            /* How many users with user space? */
       << mm users: in effect, this is the number of threads in
          this process ! >>
                           /* How many references to "struct
    atomic_t mm_count;
                               mm struct" (users count as 1) */
<< Related O&A: Linux Kernel: Why are we using two variables mm users and mm count in
mm struct?>>
                                  /* Page table pages */
   atomic_long_t nr_ptes;
                                  /* number of VMAs */
  int map_count;
  struct rw semaphore mmap sem;
  spinlock_t page_table_lock; /* Protects page tables and some counters */
      unsigned long start_code, end_code, start_data, end_data;
                                    << Code and Data segments >>
      unsigned long start_brk, << Initial process heap address>>
                   brk,
                           <<Current final address of heap>>
       start_stack; << Initial User Mode stack start address >>
      unsigned long arg_start, arg_end, << Cmd-line arguments >>
               env_start, env_end; << Environment variables >>
```

Note / Tips

1. Process (approximate) physical memory usage

Try ps aux and see for all the processes the total VM size (VSZ field) and RSS*. Sort processes by (approx) physical memory usage with:

ps aux | head -n1; ps aux | sort -k6n

*RSS – Resident Set Size:

- RSS is resident set size, the non-swapped physical memory that a task has used (in kiloBytes).
- The SIZE and RSS fields don't count some parts of a process including the page tables, kernel stack, struct thread_info, and struct task_struct. This is usually at least 20 KiB of memory that is always resident. SIZE is the virtual size of the process (code+data+stack).
- One can get detailed memory usage of a particular process (or indeed, thread) by : grep "^Vm" /proc/<pid>/status

```
Eg.
# grep "^Vm" /proc/1/status
```

VmPeak: 248200 kB VmSize: 182664 kB 0 kB VmLck: VmPin: 0 kB 5444 kB VmHWM: VmRSS: 2544 kB VmData: 148896 kB VmStk: 136 kB VmExe: 1260 kB VmLib: 3448 kB VmPTE: 96 kB

VmSwap: 1096 kB

<< Misc tip: quickly see the process hierarchy with PIDs using pstree -p. Note: this may not work on a busybox-based (or similar) Linux >>

mm->map_count is current # of VMAs (memory regions) that the process currently has.
 Maximum possible number of VMAs is tunable via:
 \$ cat /proc/sys/vm/max_map_count
 65530
 \$

Virtual Memory Areas (VMAs)


Simply put, VMAs are the metadata structures the kernel uses to manage the "segments", or more accurately, the "regions" that make up the VAS (virtual address space) of a process. Each VMA manages a homegeneous regipon of VAS.

<<

How The Kernel Manages Your Memory by Gustav Duarte.

. . .

Let's put together virtual memory areas, page table entries and page frames to understand how this all works. Below is an example of a user heap:



Blue rectangles represent pages in the VMA range, while arrows represent page table entries mapping pages onto page frames. Some virtual pages lack arrows; this means their corresponding PTEs have the **Present** flag clear.

This could be because the pages have never been touched or because their contents have been swapped out. In either case access to these pages will lead to page faults, even though they are within the VMA. It may seem strange for the VMA and the page tables to disagree, yet this often happens.

. . .

>>

Ref: Optimizing VMA caching << advanced; patch set merged into ver 3.15 (see http://kernelnewbies.org/Linux_3.15) >>

Vuln

<u>StackRot (CVE-2023-3269): Linux kernel privilege escalation vulnerability</u> Ruihan Li, July 2023

... Previously, the VMAs were managed using red-black trees. However, starting from Linux kernel version 6.1, the migration **to maple trees** took place. Maple trees are RCU-safe B-tree data structures optimized for storing non-overlapping ranges. Nonetheless, their intricate nature adds complexity to the codebase and introduces the StackRot vulnerability. ...

Linus:

Merge branch 'expand-stack' patch series (applied on 6.5, and subsequently backported to stable kernels (6.1.37, 6.3.11, and 6.4.1), effectively resolving the "Stack Rot" bug on July 1st.

Examining Memory Regions via the proc interface

Can we actually *see* for ourselves the memory regions of a Linux process? Yes, the **proc filesystem** (seen later) has a (pseudo) file that allows us to look up in detail the memory regions (VMAs) of any live process on the system.

The memory areas of a process can be seen by looking in /proc/<pid>/maps . As an example, here is the memory map of the init process (comments after a sharp sign): << Note: output below is from an IA-32 Linux box >>

```
start
        end
                  perm
                                mj:mn inode
# sudo cat /proc/1/maps
                                           # lets look at init's memory regions
08048000-0804f000 r-xp 00000000 16:0b 193988
                                                 /sbin/init # text
0804f000-08050000 rw-p 00006000 16:0b 193988
                                                 /sbin/init # data
08050000-08071000 rw-p 08050000 00:00 0
                                                 [heap]
                                                          # heap
b7e21000-b7e22000 rw-p b7e21000 00:00 0
                                          # zero-mapped bss for init*
                                                 /lib/tls/libc-2.3.4.so
b7e22000-b7f45000 r-xp 00000000 16:0b 294456
b7f45000-b7f46000 ---p 00123000 16:0b 294456
                                                 /lib/tls/libc-2.3.4.so
b7f46000-b7f47000 r--p 00123000 16:0b 294456
                                                 /lib/tls/libc-2.3.4.so
                                                 /lib/tls/libc-2.3.4.so
b7f47000-b7f4a000 rw-p 00124000 16:0b 294456
b7f4a000-b7f4c000 rw-p b7f4a000 00:00 0
b7f5c000-b7f5d000 rw-p b7f5c000 00:00 0
b7f5d000-b7f71000 r-xp 00000000 16:0b 290884
                                                 /lib/ld-2.3.4.so
b7f71000-b7f72000 r--p 00013000 16:0b 290884
                                                 /lib/ld-2.3.4.so
b7f72000-b7f73000 rw-p 00014000 16:0b 290884
                                                 /lib/ld-2.3.4.so
bff5b000-bff71000 rw-p bff5b000 00:00 0
                                                 [stack]
ffffe000-fffff000 ---p 00000000 00:00 0
                                                 [vdso]
start - end
                  perm
                          off
                                mj:mn inode
                                                   image
```

Each field in /proc/*/maps (except the image name) corresponds to a field in struct vm_area_struct.

<< Similar facilities are available in most modern OS's:

"... On OpenSolaris you would use the pmap command— for example, pmap -x < pid>—whereas on Mac OS X you would execute the vmmap command - for instance, vmmap < pid> or vmmap < procname>, where < procname> is a string that will be matched against all the processes running on the system. If you are working on Windows, we suggest that you download the Sysinternals Suite by Mark Russinovich (http://technet.microsoft.com/en-us/sysinternals/bb842062.aspx), which provides a lot of very useful system and process analysis tools in addition to vmmap." - "A Guide to Kernel Exploitation", Perla, Oldani

>>

Do use my <u>procmap</u> script (+ kernel module) to visualize the full virtual address space of any process!

<<

SIDEBAR :: /proc/iomem : physical address space

See this script for a CLI-based scaled view of the physical address space:

```
$ ./phymap_iomem.sh

/proc/iomem :: PHYSICAL ADDRESS SPACE [embedded ver]

Region Phy Addr [hex] Size


start - end : KB MB GB
```

7 4	~~~~	40074
I DN-1	ソマフいノ	19871
rener	03201	T301T

+	+
Reserved	[3 KB]
System RAM	[347 KB]
Reserved	[3 KB]
System RAM	[203 KB]
Reserved	[463 KB]
PCI Bus 0000	[127 KB]
Video ROM	[63 KB]
System ROM	[63 KB]
•	

--snip--

++					
Local APIC +	[3 KB] +				
System RAM	[13672447 KB]				
~	~				
Kernel code 	[12300 KB]				
Kernel data	[7677 KB] 				



\$ man 5 proc

--snip--

/proc/[pid]/maps

A file containing the currently mapped memory regions and their access permissions. See mmap(2) for some further information about memory mappings.

. . .

The address field is the address space in the process that the mapping occupies. The perms field is a set of permissions:

```
r = read
w = write
x = execute
s = shared
p = private (copy on write)
```

The offset field is the offset into the file/whatever; dev is the device (major:minor); inode is the inode on that device. O indicates that no inode is associated with the memory region, as would be the case with BSS (uninitialized data).

The pathname field will usually be the file that is backing the mapping. For ELF files, you can easily coordinate with the offset field by looking at the Offset field in the ELF program headers (readelf -l).

There are additional helpful pseudo-paths:

[stack] The initial process's (also known as the main thread's) stack.

[stack:<tid>] (since Linux 3.4)

A thread's stack (where the <tid> is a thread ID). It corresponds to the $\proc/[pid]/task/[tid]/\path$.

[vdso] The virtual dynamically linked shared object.

[heap] The process's heap.

If the pathname field is blank, this is an anonymous mapping as obtained via the mmap(2) function. There is no easy way to coordinate this back to a process's source, short of running it through gdb(1), strace(1), or similar.

Under Linux 2.0 there is no field giving pathname.

. . .

- * The name BSS is a historical relic, from an old assembly operator meaning "Block started by symbol." The BSS segment basically the uninitialized data segment of executable files isn't stored on disk, and the kernel maps the zero page (anonymous pages, typically filled by an malloc() request) to the BSS address range.
- Use *ldd(1)* to see what shared objects an executable links into
- The relevant code to look up and display information on the VMAs of a given PID is here: fs/proc/task_mmu.c : show_map_vma() .
- For security reasons, Linux supports a feature called **ASLR** (Address Space Layout Randomization). Tunable is: /proc/sys/kernel/randomize va space

The following values are supported:

- 0 No randomization. Everything is static.
- 1 Conservative randomization. Shared libraries, stack, mmap(), VDSO and heap are randomized.
- 2 Full randomization. In addition to elements listed in the previous point, memory managed through brk() is also randomized. **[default]**

Note on Optimizations

1. KSM candidates are aplenty: all the private anonymous regions (VMAs) of the VAS! Eg. (seeing VMAs of Qemu via /proc/<pid>/maps):

```
...
7f981c000000-7f981e592000 rw-p 00000000 00:00 0
7f981e592000-7f9820000000 ---p 00000000 00:00 0
7f9828000000-7f9828021000 rw-p 00000000 00:00 0
7f9828021000-7f982c000000 ---p 00000000 00:00 0
7f982c000000-7f982c021000 rw-p 00000000 00:00 0
...
7f98fdc00000-7f98fdc20000 rw-p 00000000 00:00 0
7f98fde00000-7f98fde10000 rw-p 00000000 00:00 0
...
7f9915205000-7f9915268000 rw-p 00000000 00:00 0
7f99152a9000-7f99153db000 rw-p 00000000 00:00 0
```

2. The file-mapped pages in the page cache are already highly optimized; when a process uses a library (text/data), it is actually mmap'ed from the page cache into the VAS of the process. The page cache thus guarantees that exactly one copy of a file page is kept at any point in time (in effect, a de-dup kind of similar to that of KSM)!

Utilities to see aspects of process memory (based on procfs) pmap(1)

pmap is part of the *procps* package – the one that provides ps(1). The pmap command reports the memory map of a process or processes.

```
# pmap -x 1
1: /sbin/init splash
                             Dirty Mode Mapping
Address
               Kbytes
00007fbd54000000
                164
                                 0 rw---
                                0 ----
00007fbd54029000
              65372
                        0
                                           anon
             164
                        0
                                0 rw---
00007fbd5c000000
                                         [ anon
00007fbd5c029000
00007fbd61498000
00007fbd61499000
00007fbd61c99000
00007fbd61c9a000
00007fbd6249a000
00007fbd6249e000
00007fbd6269d000
00007fbd6269e000
00007fbd6269f000
--snip--
00007fbd6462a000
                   4
                                 0 rw--- ld-2.21.so
                                 0 rw--- [ anon ]
00007fbd6462b000
                         0
                              0 r-x-- systemd
00007fbd6462c000
               1260
                              4 rw--- [ anon ]
00007fbd6493b000
               36 4
                 12 0
128 28
                        0
00007fbd64964000
                                0 rw---
                                         [ anon ]
                                0 r---- systemd
00007fbd64967000
                1276 524
132 24
8 0
8 8
00007fbd64987000
                                4 rw--- systemd
00007fbd64f0e000
                               468 rw---
                                         [ anon ]
00007ffc80623000
                                24 rw---
                                           stack ]
                                         [ anon ]
[ anon ]
                                0 r----
00007ffc806a5000
                               0 г-х--
00007ffc806a7000
fffffffff600000
                              0 г-х--
                                         [ anon ]
-----
total kB
          182664
                       2544
                               516
```

In addition, *pmap* can be used to display *very verbose output* with the -X and -XX switches:

```
$ pmap -X $$
2982: bash
        Address Perm Offset Device Inode Size Rss Pss Referenced Anonymous LazyFree ShmemPmdMapped Shared Hugetlb
Private Hugetlb Swap SwapPss Locked Mapping
   55cbe67d7000 r-xp 00000000 08:06 1844860 1040 928 193
                                                                                                           0
           0 193 bash
   55cbe6ada000 r--p 00103000 08:06 1844860 16 16 16
                                                              16
                                                                        16
                                                                                0
                                                                                              0
                                                                                                           0
0
           0
                16 bash
```

```
55cbe6ade000 rw-p 00107000 08:06 1844860 36 36 36 36 36 0 0 0 0 0 0 0 36 bash
```

[...]

```
$ pmap -XX $$2982: bash
```

Address Perm Offset Device Inode Size KernelPageSize MMLPageSize Rss Pss Shared_Clean Shared_Dirty Private_Clean Private_Dirty Referenced Anonymous LazyFree AnonHugePages ShmemPmdMapped Shared_Hugetlb Private_Hugetlb Swap SwapPss Locked VmFlagsMapping

```
55cbe67d7000 r-xp 00000000 08:06 1844860
                                                                        4 928 193
                                                                                                         0
                                                                                                                     0
0
        928
                   0
                           0
                                        0
                                                      0
                                                                    0
                                                                                  0
                                                                                       0
                                                                                              0
                                                                                                   193
                                                                                                         rd ex mr mw me dw sd
bash
    55cbe6ada000 r--p 00103000 08:06 1844860
                                                                                                                     0
                                              16
                                                            4
                                                                           16 16
                                                                                                         0
16
                   16
                            0
                                                       0
                                                                                   0
                                                                                        0
                                                                                               0
                                                                                                     16
                                                                                                          rd mr mw me dw ac sd
bash
```

[...]

Ref: Cheat sheet: understanding the pmap(1) output

In kernels since 2.6.14, there is an additional verbose 'smaps' entry under /proc/<pid>; this gives more detail on each segment (VMA).

To help interpret the various fields displayed, please take a look at the documentation: https://www.kernel.org/doc/Documentation/filesystems/proc.txt

Eg.:

```
# cat /proc/2012/smaps
00110000-00113000 r-xp 00000000 08:0a 9860
                                                  /usr/lib/libgthread-2.0.so.0.2600.1
Size:
                      12 kB
Rss:
                      12 kB
                       0 kB
Pss:
Shared_Clean:
                      12 kB
Shared_Dirty:
                       0 kB
Private_Clean:
                       0 kB
Private_Dirty:
                       0 kB
                      12 kB
Referenced:
                       0 kB
Swap:
KernelPageSize:
                       4 kB
                       4 kB
MMUPageSize:
00113000-00114000 r--p 00003000 08:0a 9860
                                                  /usr/lib/libgthread-2.0.so.0.2600.1
Size:
                       4 kB
                       4 kB
Rss:
```

```
Pss:
                         4 kB
Shared Clean:
                         0 kB
Shared_Dirty:
                         0 kB
Private_Clean:
Private_Dirty:
                         0 kB
                         4 kB
Referenced:
                         0 kB
                         0 kB
Swap:
KernelPageSize:
                         4 kB
MMUPageSize:
                         4 kB
--snip--
bf8bd000-bf8e0000 rw-p 00000000 00:00 0
                                                       [stack]
            144 kB
Size:
Rss:
                       140 kB
                       140 kB
Pss:
Shared_Clean: 0 kB
Shared_Dirty: 0 kB
Private_Clean: 0 kB
Private_Dirty: 140 kB
Referenced: 20 kB
                     20 kB
                       0 kB
Swap:
KernelPageSize: 4 kB
MMUPageSize:
                         4 kB
```

Source: https://www.kernel.org/doc/Documentation/filesystems/proc.txt

"…

The /proc/PID/smaps is an extension based on maps, showing the memory consumption for each of the process's mappings. For each of mappings there is a series of lines such as the following:

```
08048000-080bc000 r-xp 00000000 03:02 13130
                                                   /bin/bash
       1084 kB
Size:
Rss:
                      892 kB
                      374 kB
Pss:
Shared_Clean:
Shared_Dirty:
                     892 kB
                     0 kB
0 kB
0 kB
Private_Clean:
Private_Dirty:
Referenced:
Anonymous:
                     892 kB
                    0 kB
Anonymous:
Swap:
                       0 kB
KernelPageSize: 4 kB
MMUPageSize:
                       4 kB
Locked:
                      374 kB
VmFlags: rd ex mr mw me de
```

the first of these lines shows the same information as is displayed for the mapping in /proc/PID/maps. The remaining lines show the :

- << formatted for readability >>
- size of the mapping (size),
- the amount of the mapping that is currently resident in RAM (RSS),
- the process' proportional share of this mapping (PSS), the number of clean and dirty private pages in the mapping. Note that even a page which is part of a MAP_SHARED mapping, but has only a single pte mapped, i.e. is currently used by only one process, is accounted as private and not as shared.

- "Referenced" indicates the amount of memory currently marked as referenced or accessed.
- "Anonymous" shows the amount of memory that does not belong to any file. Even a mapping associated with a file may contain anonymous pages: when MAP_PRIVATE and a page is modified, the file page is replaced by a private anonymous copy.
- "Swap" shows how much would-be-anonymous memory is also used, but out on swap.

"VmFlags" field deserves a separate description. This member represents the kernel flags associated with the particular virtual memory area in two letter encoded manner. The codes are the following:

rd - readable

wr - writeable

ex - executable

sh - shared

mr - may read

mw - may write

me - may execute

ms - may share

gd - stack segment growns down

pf - pure PFN range

dw - disabled write to the mapped file

lo - pages are locked in memory

io - memory mapped I/O area

sr - sequential read advise provided

rr - random read advise provided

dc - do not copy area on fork

de - do not expand area on remapping

ac - area is accountable

nr - swap space is not reserved for the area

ht - area uses huge tlb pages

nl - non-linear mapping

ar - architecture specific flag

dd - do not include area into core dump

sd - soft-dirty flag

mm - mixed map area

hg - huge page advise flag

nh - no-huge page advise flag

mg - mergable advise flag

Note that there is no guarantee that every flag and associated mnemonic will be present in all further kernel releases. Things get changed, the flags may be vanished or the reverse -- new added.

This file is only present if the CONFIG_MMU kernel configuration option is enabled.

The /proc/PID/clear_refs is used to reset the PG_Referenced and ACCESSED/YOUNG bits on both physical and virtual pages associated with a process, and the

soft-dirty bit on pte (see Documentation/vm/soft-dirty.txt for details). To clear the bits for all the pages associated with the process > echo 1 > /proc/PID/clear refs

To clear the bits for the anonymous pages associated with the process > echo 2 > /proc/PID/clear_refs

To clear the bits for the file mapped pages associated with the process > echo 3 > /proc/PID/clear_refs

To clear the soft-dirty bit > echo 4 > /proc/PID/clear_refs

Any other value written to /proc/PID/clear_refs will have no effect.

The /proc/pid/pagemap gives the PFN, which can be used to find the pageflags using /proc/kpageflags and number of times a page is mapped using /proc/kpagecount. For detailed explanation, see Documentation/vm/pagemap.txt.

2. smem

From the smem(1) man page:

. . .

smem reports physical memory usage, taking shared memory pages into account. Unshared memory is reported as the USS (Unique Set Size). Shared memory is divided evenly among the processes sharing that memory. The unshared memory (USS) plus a process's proportion of shared memory is reported as the PSS (Proportional Set Size). The USS and PSS only include physical memory usage. They do not include memory that has been swapped out to disk.

<< RSS = Resident Set Size ; an (older) measure of physical memory usage by the process/mapping >>

<<

Source

One interesting metric is the **PSS value**, also known as "Proportional Share Size". This is the amount of memory which is private to the mapping, plus the partial amount of shared mappings of this process. For example, if the process has mapped 100 KiB of private memory, another 200 KiB of shared memory which is shared between two processes and another 150 KiB which is shared between three processes, the PSS is calculated like 100 KiB + 200 KiB / 2 + 150 KiB / 3 = 250 KiB. [...]

>>

Memory can be reported by process, by user, by mapping, or systemwide. Both text mode and graphical output are available.

. . .

REQUIREMENTS

smem requires:

- · Linux kernel providing 'Pss' metric in /proc/<pid>/smaps (generally 2.6.27 or newer).
- · Python 2.x (at least 2.4 or so).
- The matplotlib library (only if you want to generate graphical charts).

A few examples follow below [run on the Seawolf Minimal for Developer's VM]

```
ttv0 $ smem
 PID User
             Command
                                                    USS
                                                            PSS
                                                                     RSS
                                           Swap
 780 seawolf /lib/systemd/systemd --user
783 seawolf -bash
                                             0
                                                    956
                                                            2001
                                                                    6400
                                             0
                                                   2032
                                                           2770
                                                                    5392
1167 seawolf -bash
                                             0
                                                   2024
                                                           2773
                                                                    5372
1348 seawolf /usr/bin/python /usr/bin/sm
                                             0
                                                   6732
                                                            6969
                                                                    8948
tty0 $ smem -k
                << -k: Show unit suffixes (human-readable) >>
                                                  USS
                                                            PSS
 PID User Command
                                           Swap
                                                                    RSS
 780 seawolf /lib/systemd/systemd --user
                                            0
                                                956.0K
                                                                    6.2M
                                                            2.0M
783 seawolf -bash
1167 seawolf -bash
                                             0
                                                 2.0M
                                                           2.7M
                                                                    5.3M
                                                                    5.2M
                                                   2.0M
                                                            2.7M
                                             0
1361 seawolf /usr/bin/python /usr/bin/sm
                                                   6.5M
                                                            6.8M
                                                                    8.7M
tty0 $ smem -k -w << -w/--system : Report systemwide memory usage summary. >>
Area
                            Used Cache Noncache
                                     0 0
firmware/hardware
                             0
                              0
                                        0
kernel image
                                                   0
                        380.8M 356.5M
kernel dynamic memory
                                               24.3M
userspace memory
                          41.7M
                                    20.5M
                                               21.2M
free memory
                          569.4M
                                    569.4M
```

tty0 \$ smem -k -w --realmem=1G << --realmem: Amount of physical RAM. This lets smem detect the amount of memory used by firmware/hardware in the systemwide -w) output. If provided, it will also be used as the total memory size to base percentages on. >>

Area	Used	Cache	Noncache
firmware/hardware	32.1M	0	32.1M
kernel image	0	0	0
kernel dynamic memory	380.8M	356.6M	24.3M
userspace memory	41.7M	20.5M	21.2M
free memory	569.4M	569.4M	0
tty0 \$			

REPORT BY

If none of the following options are included, smem reports memory usage by process.

```
-m, --mappings
    Report memory usage by mapping.
-u, --users
    Report memory usage by user.
-w, --system
    Report systemwide memory usage summary.
```

tty0 \$ smem --users

User seawolf tty0 \$	Coun	t 4	Swap 0	USS 11984	PSS 14773	26	RSS 5344	
tty0 \$ so User seawolf tty0 \$	Coun	t	s -p Swap 0.00%	USS 1.18%	< PSS 1.45%		percentage RSS .60%	?s. >>
tty0 \$ s	mem -	-mann	i nas					
Map		порр	ciigs			PIDs	AVGPSS	PSS
[vdso]						4	0	0
[vsyscal	l]					4	Θ	0
[vvar]						4	0	0
				cap.so.2		1	9	9
/lib/x86						1	10	10
/lib/x86						1	10	10
/lib/x86						1 1	10 10	10 10
/lib/x86				util-2.2		1	10	11
/lib/x86						1	11	11
snip	_04-0	CHUX-	giid/ ccb	dd (d. 30.	1.5.0	1	11	11
/lib/x86	61 1	inuv	anu/lib	c 2 24 s	•	4	103	415
/lib/sys				C-2.24.50	J	1	520	520
/bin/bas		3y3tc	טויונ			2	488	976
/usr/bin		on2.7	,			1	2308	2308
<anonymo< td=""><td></td><td></td><td></td><td></td><td></td><td>4</td><td>786</td><td>3144</td></anonymo<>						4	786	3144
[heap]						4	1387	5548
tty0 \$								
tty0 \$ s	mem -	-mapp	ings -p			PIDs	AVGPSS	PSS
[vdso]						4	0.00%	0.00%
[vsyscal	11					4	0.00%	0.00%
[vvar]	- ,					4	0.00%	0.00%
/lib/x86	_64-l	inux-	gnu/lib	cap.so.2	.25	1	0.00%	0.00%
/lib/x86						1	0.00%	0.00%
/lib/x86						1	0.00%	0.00%
/lib/x86						1	0.00%	0.00%
/lib/x86	_64 - L	inux-	gnu/lib	util-2.2	4.so	1	0.00%	0.00%
/lib/x86						1	0.00%	0.00%
/lib/x86	_64-1	tiiux-	gnu/ ctb	uu ta.so.	1.3.0	1	0.00%	0.00%
snip								
/lib/x86	64-l	inux-	gnu/lib	c-2.24.s	0	4	0.01%	0.04%
/lib/sys	temd/					1	0.05%	0.05%
/bin/bas						2	0.05%	0.10%
/usr/bin		on2.7	•			1	0.23%	0.23%
<anonymo< td=""><td>us></td><td></td><td></td><td></td><td></td><td>4</td><td>0.08%</td><td>0.31%</td></anonymo<>	us>					4	0.08%	0.31%
[heap]						4	0.14%	0.55%
tty0 \$								

3. smemcap

\$ man smem

EMBEDDED USAGE

To capture memory statistics on resource-constrained systems, the the smemcap package includes a utility named smemcap. smemcap captures all /proc entries required by smem and outputs them as an uncompressed .tar file to STDOUT. smem can analyze the output using the --source option. smemcap is small and does not require Python.

To use smemcap:

- 1. Install package smemcap on target system.
- 2. Run smemcap on the target system and save the output: smemcap > memorycapture.tar
- 3. Copy the output to another machine and run smem on it: smem -S memorycapture.tar

The End?

You wish. :-)

Ponder and think, with these articles as food for thought:

- Transcendent Memory
 - Resource: Slide Presentation on Transcendent Memory, Oracle Linux.
 - LWN article Transcendent memory in a nutshell, by Dan Magenheimer, Aug 2011.
- Linux MM: rmap (reverse mapping); article <u>"The case of the overly anonymous anon vma" [LWN]</u>
- Virtualization technology brings up interesting usage of Linux MM; take a look at this article on how KVM (qemu-kvm) internally uses memory (it's old-ish; as of qemu v0.12)
- Source: "There are some cases where a desktop system could be really unresponsive
 while doing things such as writing to a very slow USB storage device and some memory
 pressure. This release includes a small patch that improves the VM heuristics to solve
 this problem.

Code: (commit)"

- Memory Management Notifiers, LWN, Jon Corbet, June 2008
- ... and lots more! A <u>Google search on "Linux memory management articles"</u> does indeed throw up a lot! :-)

Also, some <u>FAQs on Memory Management</u> .						
<<						

The APPENDICES are in a separate document: "Appendices | Linux VM".

>>




Linux Operating System

The highest quality Training on:

kaiwanTECH

Linux Fundamentals, CLI and Scripting
Linux Systems Programming
Linux Kernel Internals
Linux Device Drivers
Embedded Linux
Linux Debugging Techniques
New! Linux OS for Technical Managers

Please do visit our website for details: http://kaiwantech.in



http://kaiwantech.in

<< End of Linux Memory Management, Part 4 >>

kaiwanTECH Linux OS Corporate Training Programs

Please do check out our current offering of world-class, seriously-valuable, high on returns, technical Linux OS corporate training programs here: http://bit.ly/ktcorp