

Linux Basics

1. Introduction to Shell

1.1. What is a command shell?

- A program that interprets commands
- Allows a user to execute commands by typing them manually at a terminal, or automatically in programs called *shell scripts*.
- A shell is *not* an operating system. It is a way to interface with the operating system and run commands.

1.2. What is BASH?

- BASH = **B**ourne **A**gain **S**hell
- Bash is a shell written as a free replacement to the standard Bourne Shell (/bin/sh) originally written by Steve Bourne for UNIX systems.
- It has all of the features of the original Bourne Shell, plus additions that make it easier to program with and use from the command line.
- since it is Free Software, it has been adopted as the default shell on most Linux systems.

1.3. How is BASH different from the DOS command prompt?

- **Case Sensitivity:** In Linux/UNIX, commands and filenames are case sensitive, meaning that typing "EXIT" instead of the proper "exit" is a mistake.
- **"\" vs. "/"**: In DOS, the forward-slash "/" is the command argument delimiter, while the backslash "\" is a directory separator. In Linux/UNIX, the "/" is the directory separator, and the "\" is an escape character. More about these special characters in a minute!
- **Filenames:** The DOS world uses the "eight dot three" filename convention, meaning that all files followed a format that allowed up to 8 characters in the filename, followed by a period ("dot"), followed by an option extension, up to 3 characters long (e.g. FILENAME.TXT). In UNIX/Linux, there is no such thing as a file extension. Periods can be placed at any part of the filename, and "extensions" may be interpreted differently by all programs, or not at all.

1.4. Special Characters

Before we continue to learn about Linux shell commands, it is important to know that there are many symbols and characters that the shell interprets in special ways. This means that certain typed characters: a) cannot be used in certain situations, b) may be used to perform special operations, or, c) must be "escaped" if you want to use them in a normal way.

Character	Description
\	Escape character. If you want to reference a special character, you must "escape" it with a backslash first. Example: <code>touch /tmp/filename*</code>
/	Directory separator, used to separate a string of directory names. Example: <code>/usr/src/linux</code>

.	Current directory. Can also “hide” files when it is the first character in a filename.
..	Parent directory
~	User's home directory
*	Represents 0 or more characters in a filename, or by itself, all files in a directory. Example: <i>pic*2002 can represent the files pic2002, picJanuary2002, picFeb292002, etc</i>
?	Represents a single character in a filename. Example: <i>hello?.txt can represent hello1.txt, helloz.txt, but not hello22.txt</i>
[]	Can be used to represent a range of values, e.g. [0-9], [A-Z], etc. Example: <i>hello[0-2].txt represents the names hello0.txt, hello1.txt, and hello2.txt</i>
	“Pipe”. Redirect the output of one command into another command. Example: <i>ls more</i>
>	Redirect output of a command into a new file. If the file already exists, overwrite it. Example: <i>ls > myfiles.txt</i>
>>	Redirect the output of a command onto the end of an existing file. Example: <i>echo .Mary 555-1234. >> phonenumbers.txt</i>
<	Redirect a file as input to a program. Example: <i>more < phonenumbers.txt</i>
;	Command separator. Allows you to execute multiple commands on a single line. Example: <i>cd /var/log ; less messages</i>
&&	Command separator as above, but only runs the second command if the first one finished without errors. Example: <i>cd /var/logs && less messages</i>
&	Execute a command in the background, and immediately get your shell back. Example: <i>find / -name core > /tmp/corefiles.txt &</i>

1.5. Executing Commands

Command Syntax

Commands can be run by themselves, or you can pass in additional arguments to make them do different things. Typical command syntax can look something like this:

command [Options] <argument> [argument]

- angle brackets for required parameters: Example: *ping <hostname>*
- square brackets for optional parameters: Example: *mkdir [-p] <dirname>*
- ellipses for repeated items: *cp <source1> [source2...] <dest>*
- vertical bars for choice of items: *netstat {-t|-u}*

The Command PATH:

- Most common commands are located in your shell's "PATH", meaning that you can just type the name of the program to execute it.
Example: Typing "*ls*" will execute the "*ls*" command.
- Your shell's "PATH" variable includes the most common program locations, such as /bin, /usr/bin, /usr/X11R6/bin, and others.
- To execute commands that are not in your current PATH, you have to give the complete location of the command.

Examples: */home/bob/myprogram*

./program (Execute a program in the current directory)

~/bin/program (Execute program from a personal bin directory)

2.0. Getting Help

When you're stuck and need help with a Linux command, help is usually only a few keystrokes away! Help on most Linux commands is typically built right into the commands themselves, available through online help programs ("man pages" and "info pages"), and of course online.

2.1 Using a Built-In Help Command's

Many commands have simple "help" screens that can be invoked with special command flags.

These flags usually look like "-h" or "--help".

Example: *grep --help*

2.2 Online Manuals: "Man Pages"

The best source of information for most commands can be found in the online manual pages, known as "man pages" for short. To read a command's man page, type "man command".

Examples: *man ls* Get help on the "ls" command.

man man A manual about how to use the manual!

To search for a particular word within a man page, type "/word". To quit from a man page, just type the "Q" key. Sometimes, you might not remember the name of Linux command and you need to search for it.

For example, if you want to know how to change a file's permissions, you can search the man page descriptions for the word "permission" like this:

man -k permission

If you look at the output of this command, you will find a line that looks something like:

chmod (1) - change file access permissions

Now you know that "chmod" is the command you were looking for. Typing "man chmod" will show you the chmod command's manual page!

2.3 Info Pages

Some programs, particularly those released by the Free Software Foundation, use info pages as their main source of online documentation. Info pages are similar to man page, but instead of being displayed on one long scrolling screen, they are presented in shorter segments with links to other pieces of information.

For example: *info df* Loads the "df" info page.

3.0 Navigating the Linux File system

The Linux file system is a tree-like hierarchy of directories and files. At the base of the file system is the “/” directory, otherwise known as the “root” (not to be confused with the root user). Unlike DOS or Windows file systems that have multiple “roots”, one for each disk drive, the Linux file system mounts all disks somewhere underneath the / file system. The following table describes many of the most common Linux directories.

3.1 The Linux Directory Layout

Directory	Description
/	The nameless base of the filesystem. All other directories, files, drives, and devices are attached to this root. Commonly (but incorrectly) referred to as the “slash” or “/” directory. The “/” is just a directory separator, not a directory itself.
/bin	Essential command binaries (programs) are stored here (bash, ls, mount, tar, etc.)
/boot	Static files of the boot loader.
/dev	Device files. In Linux, hardware devices are accessed just like other files, and they are kept under this directory.
/etc	Host-specific system configuration files.
/home	Location of users' personal home directories (e.g. /home/susan).
/lib	Essential shared libraries and kernel modules.
/proc	Process information pseudo-filesystem. An interface to kernel data structures.
/root	The root (super user) home directory.
/sbin	Essential system binaries (fdisk, fsck, init, etc).
/tmp	Temporary files. All users have permission to place temporary files here.
/usr	The base directory for most shareable, read-only data (programs, libraries, documentation, and much more).
/usr/bin	Most user programs are kept here (cc, find, du, etc.).
/usr/include	Header files for compiling C programs.
/usr/lib	Libraries for most binary programs.
/usr/local	“Locally” installed files. This directory only really matters in environments where files are stored on the network. Locally-installed files go in /usr/local/bin, /usr/local/lib, etc.). Also often used for software packages installed from source, or software not officially shipped with the distribution.
/usr/sbin	Non-vital system binaries (lpd, useradd, etc.)
/usr/share	Architecture-independent data (icons, backgrounds, documentation, terminfo, man pages, etc.).
/usr/src	Program source code. E.g. The Linux Kernel, source RPMs, etc.
/usr/X11R6	The X Window System.
/var	Variable data: mail and printer spools, log files, lock files, etc.

3.2. Commands for Navigating the Linux File systems

The first thing you usually want to do when learning about the Linux filesystem is take some time to look around and see what's there! These next few commands will: a) Tell you where you are, b) take you somewhere else, and c) show you what's there. The following table describes the basic operation of the pwd, cd, and ls commands, and compares them to certain DOS commands that you might already be familiar with.

Linux Command	Description
pwd	"Print Working Directory" . Shows the current location in the directory tree.
cd	"Change Directory" . When typed all by itself, it returns you to your home directory.
cd directory	Change in to specified directory name. Example: cd /usr/src/linux
cd ~	"~" is an alias for your home directory. It can be used to a shortcut to your "home" or other directories relatives to your home.
cd ..	Move up one directory. For example, if you are in /home/vic and you type "cd ..", you will end up in /home
cd -	Return to Previous directory. An easy way to get back to your previous location!
ls	List files in the current directory, in column format.
ls -l	List files in long format.one file per line. This also shows additional info about the file, such as ownership, permissions, date and size.
ls -a	List all files, including "hidden" files. Hidden files are those files that begins with a ".". e.g: The .bashrc file in your home directory.
ls /usr/bin/d*	List all files whose names begin with the letter "d" in the /usr/bin directory.

4.0 Piping and Re-Direction

Before we move on to learning even more commands, let's side-track to the topics of piping and re-direction. The basic UNIX philosophy, therefore by extension the Linux philosophy, is to have many small programs and utilities that do a particular job very well. It is the responsibility of the programmer or user to combine these utilities to make more useful command sequences.

4.1 Piping Commands Together

The pipe character, "|", is used to chain two or more commands together. The output of the first command is "piped" into the next program, and if there is a second pipe, the output is sent to the third program, etc. For example:

```
ls -la /usr/bin | less
```

In this example, we run the command "ls -la /usr/bin", which gives us a long listing of all of the files in /usr/bin. Because the output of this command is typically very long, we pipe the output to a program called "less", which displays the output for us one screen at a time.

4.2 Redirecting Program Output to Files

There are times when it is useful to save the output of a command to a file, instead of displaying it to the screen. For example, if we want to create a file that lists all of the MP3 files in a directory, we can do something like this, using the ">" redirection character:

```
ls -l /home/vic/MP3/*.mp3 > mp3files.txt
```

A similar command can be written so that instead of creating a new file called mp3files.txt, we can append to the end of the original file:

```
ls -l /home/vic/extraMP3s/*.mp3 >> mp3files.txt
```

5.0 Other Linux Commands

The following sections describe many other commands that you will find on most Linux systems.

I can't possibly cover the details of all of these commands in this document, so don't forget that you can check the "man pages" for additional information. Not all of the listed commands will be available on all Linux or UNIX distributions.

5.1 Working with Files and Directories

These commands can be used to: find out information about files, display files, and manipulate them in other ways (copy, move, delete).

Linux Command	Description
file	Find out what kind of file it is. <i>For example, "file /bin/ls" tells us that it is a Linux executable file.</i>
cat	Display the contents of a text file on the screen. <i>For example: cat mp3files.txt would display the file we Created in the previous section.</i>
head	Display the first few lines of a text file. <i>Example: head /etc/services</i>
tail	Display the last few lines of a text file. <i>Example: tail /etc/services</i>
tail -f	Display the last few lines of a text file, and then output appended data as the file grows (very useful for following log files!). <i>Example: tail -f /var/log/messages</i>
cp	Copies a file from one location to another. <i>Example: cp mp3files.txt /tmp</i> <i>(copies the mp3files.txt file to the /tmp directory)</i>
mv	Moves a file to a new location, or renames it. <i>For example: mv mp3files.txt /tmp</i> <i>(copy the file to /tmp, and delete it from the original location)</i>
rm	Delete a file. <i>Example: rm /tmp/mp3files.txt</i>
mkdir	Make Directory. <i>Example: mkdir /tmp/myfiles/</i>
rmdir	Remove Directory. <i>Example: rmdir /tmp/myfiles/</i>

5.2 Finding Things

The following commands are used to find files. "ls" is good for finding files if you already know approximately where they are, but sometimes you need more powerful tools such as these:

Linux Command	Description
which	Shows the full path of shell commands found in your path. <i>For example, if you want to know exactly where the "grep" command is located on the filesystem, you can type "which grep". The output should be something like: /bin/grep.</i>
whereis	Locates the program, source code, and manual page for a command (if all information is available). <i>For example, to find out where "ls" and its man page are, type: "whereis ls". The output will look something like: ls: /bin/ls /usr/share/man/man1/ls.1gz</i>
locate	A quick way to search for files anywhere on the filesystem. <i>For example. You can find all files and directories that contain the name "mozilla" by typing: locate mozilla</i>
Find	A very powerful command, but sometimes tricky to use. It can be used to search for files matching certain patterns, as well as many other types of searches. <i>A simple example is: find . -name *mp3</i>

5.3. Informational Commands

The following commands are used to find out some information about the user or the system.

Linux Command	Description
ps	Lists Currently Running Process (Programs).
w	Show who is logged on and what they are doing.
id	Print your user id and group id's
df	Report file system disk space usage. ("Disk Free" is how I remember it)
du	"Disk Usage" in a particular directory. "du -s" provides a summary for the current directory.
top	Displays CPU processes in a full-screen GUI. A great way to see the activity on your computer in real-time. Type "Q" to quit.
free	Displays amount of free and used memory in the system.
cat /proc/cpuinfo	Displays lots of information about current memory usage.
uname -a	Prints system information to the screen (kernel version, machine type, etc)

5.4 Other Utilities

Here are some other commands that are useful to know:

Linux Command	Description
clear	Clear the screen.
echo	Display text on the screen. Mostly useful when writing shell scripts. <i>For example: echo "hello World"</i>
more	Display a file, or a program output one page at a time. <i>examples: more mp3files.txt</i> <i>ls -la more</i>
less	An improved replacement for the "more" command. Allows you to scroll backwards as well as forwards.
grep	Search for a pattern in a file or program output.
sort	Sort a file or program output. <i>Example: sort mp3files.txt</i>
su	"Switch User" . Allows you to switch to another user's account temporarily. The default account to switch to is the root/superuser account. Examples: su - Switch the root account. su - Switch to root, and log in with root's environment. su kernel - Switch to kernel account.

5.5 Shortcuts to Make it all Easier!

When you start using the Bash shell more often, you will appreciate these shortcuts that can save you very much typing time.

Linux Command	Description
Up/Down Arrow Keys	Scroll through your most recent commands. You can scroll back to an old command, hit Enter, and execute the command without having to re-type it.
history	Show your complete command history.
TAB Completion	If you type a particular command or file name that the shell recognizes, you can have it automatically completed for you if you press the TAB key. Try typing the first few characters of your favorite Linux command, then hit TAB a couple of times to see what happens.
Complete recent commands with "!"	Try this. Type "!" followed by the first couple of letters of a recent command and press ENTER! <i>For example, type:</i> <i>find /usr/bin -type f -name m* ..and now type : !fi</i>
history with Ctrl+R	Press CTRL-R and then type and portion of a recent command. It will search the commands for you, and once you find the command you want, just press ENTER.
Shift+PgUp Shift+pgDn	Scroll back and forward through your terminal.