Linux: System Info

Connecting through SSH:

To start this exercise we need to first start our own pwnbox and the victim machine. Once started the first challenge of this exercise is to connect to the victim machine through the ssh port 22. This is completed through the commands; 'ssh htb-student@{IP}' and entering the password 'HTB_@cademy_stdnt!'

```
└─▪ [★]$ ssh htb-student@10.129.23.0
```

```
└─▪ [★]$ ssh htb-student@10.129.23.0
htb-student@10.129.23.0's password:
```

Q1. Find out the machine hardware name.
Here we will collect info on the machine - in this case the machine hardware name. This is done through the use of the command 'nmap -a'.

```
htb-student@nixfund:~$ uname -a
Linux nixfund 4.15.0-123-generic #126-Ubuntu SMP Wed Oct 2
1 09:40:11 UTC 2020 x86_64 x86_64 x86_64 GNU/Linux
```

Answer: x86_64

Q2. What is the path to htb-student's home directory?
Upon successful connection to the victim machine through ssh we are logged in as the htb-student. Which we are also, usually, already in the home directory, so the command we need to use is 'PWD'

```
File  Edit  View  Search  Terminal  Help
htb-student@nixfund:~$ pwd
/home/htb-student
```

Answer: /home/htb-student

Q3. What is the path to the htb-student's mail?
While searching using various commands like ls and find we cannot locate a folder or file named 'mail', it can be found by getting the machine to tell us where it is! Using the command 'echo $MAIL' We get the results of the directory of where it is.

```
htb-student@nixfund: ~
File  Edit  View  Search  Terminal  Help
htb-student@nixfund:~$ echo $MAIL
/var/mail/htb-student
```

Answer: /var/mail/htb-student

Q4. Which shell is specified for the htb-student user?
Similarly to the previous question in order to find the answer we get the machine to print it out through using the 'echo' command as such; echo $SHELL'.

```
htb-student@nixfund:~$ echo $SHELL
/bin/bash
htb-student@nixfund:~$
```

Answer: /bin/bash

Q5. Which kernel release is installed on the system? (format: 1.22.3)
Just like the first question, this can be found through the use of the 'uname' command. Using 'uname -r' provides us exactly with the kernel release information.

```
htb-student@nixfund:~$ uname -r
4.15.0-123-generic
htb-student@nixfund:~$
```

Answer: 4.15.0

Q6. What is the name of the network interface that MTU is set to 1500?
Since it is a question about networking - we turn to use the tool that handles the Linux networking utility 'ifconfig'. When used in the terminal it will return the information regarding the machine network. In this particular case it shows us which interface has MTU set to 1500.

```
htb-student@nixfund:~$ ifconfig
ens192: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 15
00
        inet 10.129.23.0  netmask 255.255.0.0  broadcast 1
0.129.255.255
        inet6 dead:beef::250:56ff:fe8a:c8af  prefixlen 64
 scopeid 0x0<global>
        inet6 fe80::250:56ff:fe8a:c8af  prefixlen 64  scop
eid 0x20<link>
        ether 00:50:56:8a:c8:af  txqueuelen 1000  (Etherne
```

Answer: ens192