

All Classes

SMAplication
SMCallback
SMClearCache
SMContentType
SMEEvent
SMEEventUserLogin
SMEEventUserLogout
SMEEventUserRegister
SMEEventUserUnregister
SMForegroundGcmBroadcastReceiver
SMInAppContent
SMInAppContent.DisplayMessage
SMInAppContent.HtmlFragment
SMInAppContent.ImageFragment
SMInAppContent.UrlFragment
SMInAppMessage
SMInAppRefreshType
SMLink
SMManager
SMNotificationButton
SMNotificationCallback
SMRemoteMessageDisplay
SMSettings
SMThemeCategories

Package com.selligent.sdk

Interface Summary

Interface	Description
SMCallback	This allows to write codes that will be executed after an event is sent to the Selligent platform
SMNotificationCallback	Deprecated <i>Since 1.3, a broadcast is performed at the click on a button (cf.</i>

Class Summary

Class	Description
SMAplication	The Application class of the SDK from which the app custom Application should be extended.
SMEEvent	Object used to send a custom event to the Selligent platform with SMManager.sendEvent.
SMEEventUserLogin	Object used to send a "login" event to the Selligent platform with SMManager.sendEvent.
SMEEventUserLogout	Object used to send a "logout" event to the Selligent platform with SMManager.sendEvent.
SMEEventUserRegister	Object used to send a "register" event to the Selligent platform with SMManager.sendEvent.
SMEEventUserUnregister	Object used to send an "unregister" event to the Selligent platform with SMManager.sendEvent.
SMForegroundGcmBroadcastReceiver	Class implementing the receiver that will listen in the foreground for the push from the Selligent Mobile Platform.
SMInAppContent	An In App content
SMInAppContentHtmlFragment	This class implements a fragment that will display one or several HTML contents.
SMInAppContentImageFragment	This class implements a fragment that will display In App Content containing an image.
SMInAppContentUrlFragment	This class implements a fragment that will display In App Content containing an url.
SMInAppMessage	An In App message

SMLink	A link of an SMInAppContent .
SMManager	Singleton object used to interact with the Selligent Mobile SDK.
SMNotificationButton	Object containing all the data used to implement a button in a notification/message.
SMSettings	Configuration object passed to the 'start' method of SMManager.

Enum Summary

Enum	Description
SMClearCache	
SMContentType	Enum listing the different types of In App Content
SMInAppContent.DisplayMode	Enum listing the different display mode.
SMInAppRefreshType	Enum with the different values for the refresh of the In App messages and In Ap contents.
SMRemoteMessageDisplayType	List the different possibilities to display a remote message received while the app is in foreground - Automatic: the message is automatically displayed - Notification: a notification is created, the user needs to click on it to display the message - None: nothing is done, the message is not displayed, it is up to the app to display it (cf.
SMThemeCategories	Deprecated



com.sellgent.sdk

Class SMAapplication

```
java.lang.Object
    android.content.Context
        android.content.ContextWrapper
            android.app.Application
                com.sellgent.sdk.SMAapplication
```

All Implemented Interfaces:

```
android.content.ComponentCallbacks, android.content.ComponentCallbacks2
```

```
public class SMAapplication
extends android.app.Application
```

The Application class of the SDK from which the app custom Application should be extended.

Since:

1.0

Version:

2.1

Nested Class Summary

Nested classes/interfaces inherited from class android.app.Application

```
android.app.Application.ActivityLifecycleCallbacks,
android.app.Application.OnProvideAssistDataListener
```

Field Summary

Fields inherited from class android.content.Context

```
ACCESSIBILITY_SERVICE, ACCOUNT_SERVICE, ACTIVITY_SERVICE, ALARM_SERVICE,
APP_OPS_SERVICE, APPWIDGET_SERVICE, AUDIO_SERVICE, BATTERY_SERVICE,
BIND_ABOVE_CLIENT, BIND_ADJUST_WITH_ACTIVITY, BIND_ALLOW_OOM_MANAGEMENT,
BIND_AUTO_CREATE, BIND_DEBUG_UNBIND, BIND_EXTERNAL_SERVICE, BIND_IMPORTANT,
BIND_NOT_FOREGROUND, BIND_WAIVE_PRIORITY, BLUETOOTH_SERVICE, CAMERA_SERVICE,
CAPTIONING_SERVICE, CARRIER_CONFIG_SERVICE, CLIPBOARD_SERVICE,
COMPANION_DEVICE_SERVICE, CONNECTIVITY_SERVICE, CONSUMER_IR_SERVICE,
CONTEXT_IGNORE_SECURITY, CONTEXT_INCLUDE_CODE, CONTEXT_RESTRICTED,
CROSS_PROFILE_APPS_SERVICE, DEVICE_POLICY_SERVICE, DISPLAY_SERVICE,
DOWNLOAD_SERVICE, DROPBOX_SERVICE, EUICC_SERVICE, FINGERPRINT_SERVICE,
HARDWARE_PROPERTIES_SERVICE, INPUT_METHOD_SERVICE, INPUT_SERVICE, IPSEC_SERVICE,
JOB_SCHEDULER_SERVICE, KEYGUARD_SERVICE, LAUNCHER_APPS_SERVICE,
LAYOUT_INFLATER_SERVICE, LOCATION_SERVICE, MEDIA_PROJECTION_SERVICE,
```

```
MEDIA_ROUTER_SERVICE, MEDIA_SESSION_SERVICE, MIDI_SERVICE, MODE_APPEND,
MODE_ENABLE_WRITE_AHEAD_LOGGING, MODE_MULTI_PROCESS, MODE_NO_LOCALIZED_COLLATORS,
MODE_PRIVATE, MODE_WORLD_READABLE, MODE_WORLD_WRITEABLE, NETWORK_STATS_SERVICE,
NFC_SERVICE, NOTIFICATION_SERVICE, NSD_SERVICE, POWER_SERVICE, PRINT_SERVICE,
RECEIVER_VISIBLE_TO_INSTANT_APPS, RESTRICTIONS_SERVICE, SEARCH_SERVICE,
SENSOR_SERVICE, SHORTCUT_SERVICE, STORAGE_SERVICE, STORAGE_STATS_SERVICE,
SYSTEM_HEALTH_SERVICE, TELECOM_SERVICE, TELEPHONY_SERVICE,
TELEPHONY_SUBSCRIPTION_SERVICE, TEXT_CLASSIFICATION_SERVICE,
TEXT_SERVICES_MANAGER_SERVICE, TV_INPUT_SERVICE, UI_MODE_SERVICE,
USAGE_STATS_SERVICE, USB_SERVICE, USER_SERVICE, VIBRATOR_SERVICE, WALLPAPER_SERVICE,
WIFI_AWARE_SERVICE, WIFI_P2P_SERVICE, WIFI_RTT_RANGING_SERVICE, WIFI_SERVICE,
WINDOW_SERVICE
```

Fields inherited from interface android.content.ComponentCallbacks2

```
TRIM_MEMORY_BACKGROUND, TRIM_MEMORY_COMPLETE, TRIM_MEMORY_MODERATE,
TRIM_MEMORY_RUNNING_CRITICAL, TRIM_MEMORY_RUNNING_LOW, TRIM_MEMORY_RUNNING_MODERATE,
TRIM_MEMORY_UI_HIDDEN
```

Constructor Summary

Constructors

Constructor and Description

`SMAApplication()`

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method and Description

`void`

`onCreate()`

Methods inherited from class android.app.Application

```
getProcessName, onConfigurationChanged, onLowMemory, onTerminate, onTrimMemory,
registerActivityLifecycleCallbacks, registerComponentCallbacks,
registerOnProvideAssistDataListener, unregisterActivityLifecycleCallbacks,
unregisterComponentCallbacks, unregisterOnProvideAssistDataListener
```

Methods inherited from class android.content.ContextWrapper

```
bindService, checkCallingOrSelfPermission, checkCallingOrSelfUriPermission,
checkCallingPermission, checkCallingUriPermission, checkPermission,
checkSelfPermission, checkUriPermission, checkUriPermission, clearWallpaper,
```

```
createConfigurationContext, createContextForSplit,
createDeviceProtectedStorageContext, createDisplayContext, createPackageContext,
databaseList, deleteDatabase, deleteFile, deleteSharedPreferences,
enforceCallingOrSelfPermission, enforceCallingOrSelfUriPermission,
enforceCallingPermission, enforceCallingUriPermission, enforcePermission,
enforceUriPermission, enforceUriPermission, fileList, getApplicationContext,
getApplicationInfo, getAssets, getBaseContext, getCacheDir, getClassLoader,
getCodeCacheDir, getContentResolver, getDatabasePath, getDataDir, getDir,
getExternalCacheDir, getExternalCacheDirs, getExternalFilesDir,
getExternalFilesDirs, getExternalMediaDirs, getFilesDir, getFileStreamPath,
getMainExecutor, getMainLooper, getNoBackupFilesDir, getObbDir, getObbDirs,
getPackageCodePath, getPackageManager, getPackageName, getPackageResourcePath,
getResources, getSharedPreferences, getSystemService, getSystemServiceName,
getTheme, getWallpaper, getWallpaperDesiredMinimumHeight,
getWallpaperDesiredMinimumWidth, grantUriPermission, isDeviceProtectedStorage,
isRestricted, moveDatabaseFrom, moveSharedPreferencesFrom, openFileInput,
openFileOutput, openOrCreateDatabase, openOrCreateDatabase, peekWallpaper,
registerReceiver, registerReceiver, registerReceiver, registerReceiver,
removeStickyBroadcast, removeStickyBroadcastAsUser, revokeUriPermission,
revokeUriPermission, sendBroadcast, sendBroadcast, sendBroadcastAsUser,
sendBroadcastAsUser, sendOrderedBroadcast, sendOrderedBroadcast,
sendOrderedBroadcastAsUser, sendStickyBroadcast, sendStickyBroadcastAsUser,
sendStickyOrderedBroadcast, sendStickyOrderedBroadcastAsUser, setTheme,
setWallpaper, setWallpaper, startActivities, startActivities, startActivity,
startActivity, startForegroundService, startInstrumentation, startIntentSender,
startIntentSender, startService, stopService, unbindService, unregisterReceiver
```

Methods inherited from class android.content.Context

```
getColor, getColorStateList, getDrawable, getString, getString, getSystemService,
getText, obtainStyledAttributes, obtainStyledAttributes, obtainStyledAttributes,
obtainStyledAttributes
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail

SMAplication

```
public SMAplication()
```

Method Detail

onCreate

```
public void onCreate()
```

Overrides:

```
onCreate in class android.app.Application
```

com.selligent.sdk

Interface SMCallback

```
public interface SMCallback
```

This allows to write codes that will be executed after an event is sent to the Selligent platform

Since:

1.0

Version:

2.1

See Also:[SMEvent](#), [SManager.sendEvent\(SMEvent\)](#)

Method Summary

All Methods	Instance Methods	Abstract Methods
Modifier and Type	Method and Description	
void	onError (int httpResponseCode, java.lang.Exception exception) Event triggered when an error occured while sending the SMEvent	
void	onSuccess (java.lang.String result) Event triggered when the SMEvent was sent successfully.	

Method Detail

onSuccess

```
void onSuccess(java.lang.String result)
```

Event triggered when the SMEvent was sent successfully.

Parameters:

result - the String returned by the web service.

onError

```
void onError(int httpResponseCode,  
            java.lang.Exception exception)
```

Event triggered when an error occured while sending the SMEvent

Parameters:

httpResponseCode - the code of the error (404, 500, etc.)

exception - the Exception thrown by the web service call

com.selligent.sdk

Enum SMClearCache

```
java.lang.Object
  java.lang.Enum<SMClearCache>
    com.selligent.sdk.SMClearCache
```

All Implemented Interfaces:

java.io.Serializable, java.lang.Comparable<SMClearCache>

```
public enum SMClearCache
extends java.lang.Enum<SMClearCache>
```

Since:

1.3 The lifespan of the items in the cache

Version:

2.1

Enum Constant Summary

Enum Constants**Enum Constant and Description****Auto**

Default value, Selligent Mobile SDK manages the lifespan automatically.

Day

To clear the items that are one day old

Month

To clear the items that are one month old

None

To disable the cache mechanism.

Quarter

To clear the items that are one three months old

Week

To clear the items that are one week old

Method Summary

All Methods**Static Methods****Concrete Methods****Modifier and Type****Method and Description**

```
static SMClearCache valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name.

```
static SMClearCache[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

```
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf
```

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, wait, wait, wait
```

Enum Constant Detail

Auto

```
public static final SMClearCache Auto
```

Default value, Selligent Mobile SDK manages the lifespan automatically.

None

```
public static final SMClearCache None
```

To disable the cache mechanism.

Day

```
public static final SMClearCache Day
```

To clear the items that are one day old

Week

```
public static final SMClearCache Week
```

To clear the items that are one week old

Month

```
public static final SMClearCache Month
```

To clear the items that are one month old

Quarter

```
public static final SMClearCache Quarter
```

To clear the items that are one three months old

Method Detail**values**

```
public static SMClearCache[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMClearCache c : SMClearCache.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static SMClearCache valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

java.lang.IllegalArgumentException - if this enum type has no constant with the specified name

java.lang.NullPointerException - if the argument is null

com.selligent.sdk

Enum SMContentType

```
java.lang.Object
  java.lang.Enum<SMContentType>
    com.selligent.sdk.SMContentType
```

All Implemented Interfaces:

java.io.Serializable, java.lang.Comparable<SMContentType>

```
public enum SMContentType
extends java.lang.Enum<SMContentType>
```

Enum listing the different types of In App Content

Since:

1.4

Version:

2.1

Enum Constant Summary

Enum Constants**Enum Constant and Description**[Html](#)[Image](#)[Url](#)

Method Summary

All Methods**Static Methods****Instance Methods****Concrete Methods****Modifier and Type****Method and Description**static [SMContentType](#) [fromInteger](#)(int x)int [getValue](#)()static [SMContentType](#) [valueOf](#)(java.lang.String name)

Returns the enum constant of this type with the specified name.

static [SMContentType](#)[] [values](#)()

Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

```
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf
```

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, wait, wait, wait
```

Enum Constant Detail**Html**

```
public static final SMContentType Html
```

Url

```
public static final SMContentType Url
```

Image

```
public static final SMContentType Image
```

Method Detail**values**

```
public static SMContentType[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMContentType c : SMContentType.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static SMContentType valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used

to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`java.lang.IllegalArgumentException` - if this enum type has no constant with the specified name

`java.lang.NullPointerException` - if the argument is null

getValue

```
public int getValue()
```

fromInteger

```
public static SMContentType fromInteger(int x)
```

com.selligent.sdk

Class SMEVENT

`java.lang.Object`
`com.selligent.sdk.SMEVENT`

All Implemented Interfaces:`java.io.Externalizable, java.io.Serializable`**Direct Known Subclasses:**`SMEVENTUserLogin, SMEVENTUserLogout, SMEVENTUserRegister, SMEVENTUserUnregister`

```
public class SMEVENT
extends java.lang.Object
implements java.io.Externalizable
```

Object used to send a custom event to the Selligent platform with SMManager.sendEvent.

Since:

1.0

Version:

2.1

See Also:`SMManager.sendSMEVENT(SMEVENT), Serialized Form`

Field Summary

Fields

Modifier and Type	Field and Description
<code>SMCallback</code>	Callback A SMCallback object containing code to execute after the message is sent
<code>java.util.Hashtable<java.lang.String,java.lang.String></code>	Data Custom data

Constructor Summary

Constructors**Constructor and Description**`SMEVENT()`

Constructs an SMEVENT object without data and callback

```
SMEvent(java.util.Hashtable<java.lang.String,java.lang.String> data,
SMCallback callback)
```

Constructs an SMEvent object with the following:

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
boolean	equals (java.lang.Object o)	
	Compares this instance with the specified object and indicates if they are equal.	
int	hashCode ()	
	Returns an integer hash code for this object.	
void	readExternal (java.io.ObjectInput serializedObject)	
	This method is called when deserializing the object.	
void	writeExternal (java.io.ObjectOutput serializedObject)	
	This method is called when serializing the object.	

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, toString, wait, wait, wait
```

Field Detail

Data

```
public java.util.Hashtable<java.lang.String,java.lang.String> Data
```

Custom data

Callback

```
public SMCallback Callback
```

A SMCallback object containing code to execute after the message is sent

Constructor Detail

SMEvent

```
public SMEvent()
```

Constructs an SMEvent object without data and callback

SMEvent

```
public SMEvent(java.util.Hashtable<java.lang.String,java.lang.String> data,  
              SMCallback callback)
```

Constructs an SMEvent object with the following:

Parameters:

data - a Hashtable<String, String> containing the custom data

callback - a SMCallback object containing code to execute after the message is sent

See Also:

[SMCallback](#)

Method Detail

equals

```
public boolean equals(java.lang.Object o)
```

Compares this instance with the specified object and indicates if they are equal.

Overrides:

equals in class java.lang.Object

Parameters:

o - the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Returns an integer hash code for this object. By contract, any two objects for which [equals \(Object\)](#) returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

hashCode in class java.lang.Object

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMEvent object to recreate.

Throws:

java.io.IOException

java.lang.ClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMEvent object

Throws:

java.io.IOException

com.selligent.sdk

Class SMEEventUserLogin

```
java.lang.Object
  com.selligent.sdk.SMEvent
    com.selligent.sdk.SMEEventUserLogin
```

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMEEventUserLogin
extends SMEvent
```

Object used to send a "login" event to the Selligent platform with SMManager.sendEvent.

Since:

1.0

Version:

2.1

See Also:

SMManager.sendSMEvent(SMEvent), Serialized Form

Field Summary

Fields

Modifier and Type	Field and Description
java.lang.String	Email

Fields inherited from class com.selligent.sdk.SMEvent

[Callback](#), [Data](#)

Constructor Summary

Constructors

Constructor and Description

[SMEEventUserLogin\(\)](#)

[SMEEventUserLogin\(java.lang.String email, java.util.Hashtable<java.lang.String,java.lang.String> data, \[SMCallback\]\(#\) callback\)](#)
Constructs a new SMEEventUserLogin

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
boolean	equals (java.lang.Object o)	
	Compares this instance with the specified object and indicates if they are equal.	
int	hashCode ()	
	Returns an integer hash code for this object.	
void	readExternal (java.io.ObjectInput serializedObject)	
	This method is called when deserializing the object.	
void	writeExternal (java.io.ObjectOutput serializedObject)	
	This method is called when serializing the object.	

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

Email

public java.lang.String Email

Constructor Detail

SMEEventUserLogin

public SMEEventUserLogin()

SMEEventUserLogin

public SMEEventUserLogin(java.lang.String email,
 java.util.Hashtable<java.lang.String,java.lang.String> data,
 SMCallback callback)

Constructs a new SMEEventUserLogin

Parameters:

email - a String containing the e-mail address of the user.
 data - a Hashtable<String, String> containing custom data, can be null.
 callback - an SMCallback containing code to perform after the message is sent

See Also:

[SMCallback](#)

Method Detail**equals**

```
public boolean equals(java.lang.Object o)
```

Description copied from class: SMEEvent

Compares this instance with the specified object and indicates if they are equal.

Overrides:

[equals](#) in class [SMEEvent](#)

Parameters:

o - the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Description copied from class: SMEEvent

Returns an integer hash code for this object. By contract, any two objects for which [SMEEvent.equals\(Object\)](#) returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

[hashCode](#) in class [SMEEvent](#)

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Description copied from class: SMEEvent

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Overrides:

readExternal in class SMEEvent

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMEEvent object to recreate.

Throws:

java.io.IOException

java.langClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

Description copied from class: SMEEvent

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Overrides:

writeExternal in class SMEEvent

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMEEvent object

Throws:

java.io.IOException

com.selligent.sdk

Class SMEEventUserLogout

```
java.lang.Object
  com.selligent.sdk.SMEvent
    com.selligent.sdk.SMEEventUserLogout
```

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMEEventUserLogout
extends SMEvent
```

Object used to send a "logout" event to the Selligent platform with SMManager.sendEvent.

Since:

1.0

Version:

2.1

See Also:

SMManager.sendSMEvent(SMEvent), Serialized Form

Field Summary

Fields

Modifier and Type	Field and Description
java.lang.String	Email

Fields inherited from class com.selligent.sdk.SMEvent

[Callback](#), [Data](#)

Constructor Summary

Constructors

Constructor and Description

[SMEEventUserLogout\(\)](#)

[SMEEventUserLogout\(java.lang.String email, java.util.Hashtable<java.lang.String,java.lang.String> data, **SMCallback** callback\)](#)
Constructs a new SMEEventUserLogout

Method Summary

All Methods	Instance Methods	Concrete Methods	
Modifier and Type	Method and Description		
boolean	<code>equals (java.lang.Object o)</code>	Compares this instance with the specified object and indicates if they are equal.	
int	<code>hashCode ()</code>	Returns an integer hash code for this object.	
void	<code>readExternal (java.io.ObjectInput serializedObject)</code>	This method is called when deserializing the object.	
void	<code>writeExternal (java.io.ObjectOutput serializedObject)</code>	This method is called when serializing the object.	

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

Email

public java.lang.String Email

Constructor Detail

SMEEventUserLogout

public SMEEventUserLogout()

SMEEventUserLogout

```
public SMEEventUserLogout(java.lang.String email,
    java.util.Hashtable<java.lang.String,java.lang.String> data,
    SMCallback callback)
```

Constructs a new SMEEventUserLogout

Parameters:

email - a String containing the e-mail address of the user.
 data - a Hashtable<String, String> containing custom data, can be null.
 callback - an SMCallback containing code to perform after the message is sent

See Also:

[SMCallback](#)

Method Detail**equals**

```
public boolean equals(java.lang.Object o)
```

Description copied from class: SMEEvent

Compares this instance with the specified object and indicates if they are equal.

Overrides:

[equals](#) in class [SMEEvent](#)

Parameters:

`o` – the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Description copied from class: SMEEvent

Returns an integer hash code for this object. By contract, any two objects for which [SMEEvent.equals\(Object\)](#) returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

[hashCode](#) in class [SMEEvent](#)

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Description copied from class: SMEEvent

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Overrides:

readExternal in class SMEEvent

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMEEvent object to recreate.

Throws:

java.io.IOException

java.langClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

Description copied from class: SMEEvent

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Overrides:

writeExternal in class SMEEvent

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMEEvent object

Throws:

java.io.IOException

com.selligent.sdk

Class SMEEventUserRegister

```
java.lang.Object
  com.selligent.sdk.SMEvent
    com.selligent.sdk.SMEEventUserRegister
```

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMEEventUserRegister
extends SMEvent
```

Object used to send a "register" event to the Selligent platform with SMManager.sendEvent.

Since:

1.0

Version:

2.1

See Also:

SMManager.sendSMEvent(SMEvent), Serialized Form

Field Summary

Fields

Modifier and Type	Field and Description
java.lang.String	Email

Fields inherited from class com.selligent.sdk.SMEvent

[Callback](#), [Data](#)

Constructor Summary

Constructors

Constructor and Description

[SMEEventUserRegister\(\)](#)

[SMEEventUserRegister\(java.lang.String email, java.util.Hashtable<java.lang.String,java.lang.String> data, \[SMCallback\]\(#\) callback\)](#)
Constructs a new SMEEventUserRegister

Method Summary

All Methods	Instance Methods	Concrete Methods	
Modifier and Type	Method and Description		
boolean	equals (java.lang.Object o)	Compares this instance with the specified object and indicates if they are equal.	
int	hashCode ()	Returns an integer hash code for this object.	
void	readExternal (java.io.ObjectInput serializedObject)	This method is called when deserializing the object.	
void	writeExternal (java.io.ObjectOutput serializedObject)	This method is called when serializing the object.	

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

Email

public java.lang.String Email

Constructor Detail

SMEEventUserRegister

public SMEEventUserRegister()

SMEEventUserRegister

```
public SMEEventUserRegister(java.lang.String email,
                           java.util.Hashtable<java.lang.String,java.lang.String> data,
                           SMCallback callback)
```

Constructs a new SMEEventUserRegister

Parameters:

email - a String containing the e-mail address of the user.
 data - a Hashtable<String, String> containing custom data, can be null.
 callback - an SMCallback containing code to perform after the message is sent

See Also:

[SMCallback](#)

Method Detail**equals**

```
public boolean equals(java.lang.Object o)
```

Description copied from class: SMEEvent

Compares this instance with the specified object and indicates if they are equal.

Overrides:

[equals](#) in class [SMEEvent](#)

Parameters:

`o` - the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Description copied from class: SMEEvent

Returns an integer hash code for this object. By contract, any two objects for which [SMEEvent.equals\(Object\)](#) returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

[hashCode](#) in class [SMEEvent](#)

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Description copied from class: SMEEvent

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Overrides:

readExternal in class SMEEvent

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMEEvent object to recreate.

Throws:

java.io.IOException

java.langClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

Description copied from class: SMEEvent

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Overrides:

writeExternal in class SMEEvent

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMEEvent object

Throws:

java.io.IOException

com.selligent.sdk

Class SMEEventUserUnregister

```
java.lang.Object
  com.selligent.sdk.SMEvent
    com.selligent.sdk.SMEEventUserUnregister
```

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMEEventUserUnregister
extends SMEvent
```

Object used to send an "unregister" event to the Selligent platform with SMManager.sendEvent.

Since:

1.0

Version:

2.1

See Also:

SMManager.sendSMEvent(SMEvent), Serialized Form

Field Summary

Fields

Modifier and Type	Field and Description
java.lang.String	Email

Fields inherited from class com.selligent.sdk.SMEvent

[Callback](#), [Data](#)

Constructor Summary

Constructors

Constructor and Description

SMEEventUserUnregister()
SMEEventUserUnregister(java.lang.String email, java.util.Hashtable<java.lang.String,java.lang.String> data, SMCallback callback)
Constructs a new SMEEventUserUnregister

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type	Method and Description	
boolean	equals (java.lang.Object o)	
	Compares this instance with the specified object and indicates if they are equal.	
int	hashCode ()	
	Returns an integer hash code for this object.	
void	readExternal (java.io.ObjectInput serializedObject)	
	This method is called when deserializing the object.	
void	writeExternal (java.io.ObjectOutput serializedObject)	
	This method is called when serializing the object.	

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

Email

public java.lang.String Email

Constructor Detail

SMEEventUserUnregister

public SMEEventUserUnregister()

SMEEventUserUnregister

public SMEEventUserUnregister(java.lang.String email,
java.util.Hashtable<java.lang.String,java.lang.String> data,
SMCallback callback)

Constructs a new SMEEventUserUnregister

Parameters:

email - a String containing the e-mail address of the user.
 data - a Hashtable<String, String> containing custom data, can be null.
 callback - an SMCallback containing code to perform after the message is sent

See Also:

[SMCallback](#)

Method Detail**equals**

```
public boolean equals(java.lang.Object o)
```

Description copied from class: SMEEvent

Compares this instance with the specified object and indicates if they are equal.

Overrides:

[equals](#) in class [SMEEvent](#)

Parameters:

`o` - the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Description copied from class: SMEEvent

Returns an integer hash code for this object. By contract, any two objects for which [SMEEvent.equals\(Object\)](#) returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

[hashCode](#) in class [SMEEvent](#)

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Description copied from class: SMEEvent

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Overrides:

readExternal in class SMEEvent

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMEEvent object to recreate.

Throws:

java.io.IOException

java.langClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

Description copied from class: SMEEvent

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Overrides:

writeExternal in class SMEEvent

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMEEvent object

Throws:

java.io.IOException

com.selligent.sdk

Class SMForegroundGcmBroadcastReceiver

```
java.lang.Object
    android.content.BroadcastReceiver
        com.selligent.sdk.SMForegroundGcmBroadcastReceiver
```

```
public class SMForegroundGcmBroadcastReceiver
extends android.content.BroadcastReceiver
```

Class implementing the receiver that will listen in the foreground for the push from the Selligent Mobile Platform. If you do not extend `SMB BaseActivity`, you have to register and unregister this receiver respectively on the `onStart` and `onStop` events of your activities.

Since:

1.0

Version:

2.1

Nested Class Summary

Nested classes/interfaces inherited from class android.content.BroadcastReceiver

```
android.content.BroadcastReceiver.PendingResult
```

Constructor Summary

Constructors

Constructor and Description

`SMForegroundGcmBroadcastReceiver(android.content.Context context)`

Constructor of the class.

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type

Method and Description

android.content.IntentFilter	<code>getIntentFilter()</code>
------------------------------	--------------------------------

It creates the IntentFilter that must be used when registering the receiver.

void	<code>onReceive(android.content.Context context,</code>
------	---

```
    android.content.Intent intent)
```

This method is called when the BroadcastReceiver is receiving an Intent broadcast.

Methods inherited from class android.content.BroadcastReceiver

abortBroadcast, clearAbortBroadcast, getAbortBroadcast, getDebugUnregister, getResultCode, getResultData, getResultExtras, goAsync, isInitialStickyBroadcast, isOrderedBroadcast, peekService, setDebugUnregister, setOrderedHint, setResult, setResultCode, setResultData, setResultExtras

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

SMForegroundGcmBroadcastReceiver

```
public SMForegroundGcmBroadcastReceiver(android.content.Context context)
```

Constructor of the class.

Parameters:

context - the activity in which the receiver is instantiated.

Method Detail

getIntentFilter

```
public android.content.IntentFilter getIntentFilter()
```

It creates the IntentFilter that must be used when registering the receiver.

Returns:

the intent filter needed at registration.

onReceive

```
public void onReceive(android.content.Context context,
                     android.content.Intent intent)
```

This method is called when the BroadcastReceiver is receiving an Intent broadcast.

Specified by:

onReceive in class android.content.BroadcastReceiver

Parameters:

context - The Context in which the receiver is running

intent - The Intent being received

com.selligent.sdk

Class SMInAppContent

java.lang.Object
com.selligent.sdk.SMInAppContent

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMInAppContent
extends java.lang.Object
implements java.io.Externalizable
```

An In App content

Since:

1.4

Version:

2.1

See Also:

Serialized Form

Nested Class Summary

Nested Classes

Modifier and Type	Class and Description
static class	SMInAppContent.DisplayMode Enum listing the different display mode.

Constructor Summary

Constructors

Constructor and Description

[SMInAppContent\(\)](#)

Empty constructor of an In App Content

[SMInAppContent\(java.lang.String json\)](#)

Constructor that fills in the In App Content based on the given json

Method Summary

All Methods**Instance Methods****Concrete Methods**

Modifier and Type	Method and Description
boolean	equals (java.lang.Object o) Compares this instance with the specified object and indicates if they are equal.
java.lang.String	getBody () Gets the body of the SMInAppContent
java.lang.String	getCategory () Gets the category of the SMInAppContent
long	getCreationDate () Gets the creation date of the SMInAppContent
SMInAppContent.DisplayMode	getDisplayMode () Gets the display mode of the SMInAppContent
long	getExpirationDate () Gets the expiration date of the SMInAppContent
java.lang.String	getId () Gets the id of the SMInAppContent
android.graphics.Bitmap	getImage () Gets the bitmap of the image if the In App Content is of type Image and marked for its content to be downloaded.
SMLink []	getLinks () Gets the links of the SMInAppContent
java.lang.String	getTitle () Gets the title of the SMInAppContent
SMContentType	getType () Gets the type of the SMInAppContent
boolean	hasBeenFirstSeenInCurrentSession () Tells if the SMInAppContent has already been seen or not in the current session.
boolean	hasBeenSeen () Tells if the SMInAppContent has already been seen or not.
int	hashCode () Returns an integer hash code for this object.
void	readExternal (java.io.ObjectInput serializedObject) This method is called when deserializing the object.
void	writeExternal (java.io.ObjectOutput serializedObject)

This method is called when serializing the object.

Methods inherited from class java.lang.Object

`getClass, notify, notifyAll, toString, wait, wait, wait`

Constructor Detail

SMInAppContent

```
public SMInAppContent()
```

Empty constructor of an In App Content

SMInAppContent

```
public SMInAppContent(java.lang.String json)
```

Constructor that fills in the In App Content based on the given json

Parameters:

`json` - The json String representing an In-App content

Method Detail

equals

```
public boolean equals(java.lang.Object o)
```

Compares this instance with the specified object and indicates if they are equal.

Overrides:

`equals` in class `java.lang.Object`

Parameters:

`o` - the object to compare this instance with.

Returns:

`true` if the specified object is equal to this Object; `false` otherwise.

hashCode

```
public int hashCode()
```

Returns an integer hash code for this object. By contract, any two objects for which `equals (Object)` returns

true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

hashCode in class java.lang.Object

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMInAppContent object to recreate.

Throws:

java.io.IOException

java.lang.ClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMInAppContent object

Throws:

java.io.IOException

getId

```
public java.lang.String getId()
```

Gets the id of the SMInAppContent

Returns:

the String representing the id

Since:

1.4

getTitle

```
public java.lang.String getTitle()
```

Gets the title of the SMInAppContent

Returns:

the String representing the title

Since:

1.4

getBody

```
public java.lang.String getBody()
```

Gets the body of the SMInAppContent

Returns:

the String representing the body

Since:

1.4

getLinks

```
public SMLink[] getLinks()
```

Gets the links of the SMInAppContent

Returns:

an array of SMLink

Since:

1.4

getType

```
public SMContentType getType()
```

Gets the type of the SMInAppContent

Returns:

the `SMContentType`

Since:

1.4

getCategory

```
public java.lang.String getCategory()
```

Gets the category of the SMInAppContent

Returns:

the String representing the category

Since:

1.4

getDisplayMode

```
public SMInAppContent.DisplayMode getDisplayMode()
```

Gets the display mode of the SMInAppContent

Returns:

the `SMInAppContent.DisplayMode`

Since:

1.4

getCreationDate

```
public long getCreationDate()
```

Gets the creation date of the SMInAppContent

Returns:

the long representing the creation date in milliseconds since 01/01/1970

Since:

1.4

getExpirationDate

```
public long getExpirationDate()
```

Gets the expiration date of the SMInAppContent

Returns:

the long representing the expiration date in milliseconds since 01/01/1970

Since:

1.4

hasBeenSeen

```
public boolean hasBeenSeen()
```

Tells if the SMInAppContent has already been seen or not.

Returns:

true if it was seen, false otherwise.

Since:

1.4

hasBeenFirstSeenInCurrentSession

```
public boolean hasBeenFirstSeenInCurrentSession()
```

Tells if the SMInAppContent has already been seen or not in the current session.

Returns:

true if it was seen, false otherwise.

Since:

1.5

getImage

```
@Nullable  
public android.graphics.Bitmap getImage()
```

Gets the bitmap of the image if the In App Content is of type Image and marked for its content to be downloaded.

Returns:

the bitmap of the image if it exists, null otherwise

com.selligent.sdk

Enum SMInAppContent.DisplayMode

```
java.lang.Object
  java.lang.Enum<SMInAppContent.DisplayMode>
    com.selligent.sdk.SMInAppContent.DisplayMode
```

All Implemented Interfaces:

```
java.io.Serializable, java.lang.Comparable<SMInAppContent.DisplayMode>
```

Enclosing class:

[SMInAppContent](#)

```
public static enum SMInAppContent.DisplayMode
extends java.lang.Enum<SMInAppContent.DisplayMode>
```

Enum listing the different display mode. OnlyOnce means the SMInAppContent will only be displayed once. UntilReplaced means the SMInAppContent will stay visible until a new one replaces it (or it expires).

Enum Constant Summary

Enum Constants

Enum Constant and Description

[OnlyOnce](#)

[UntilReplaced](#)

Method Summary

All Methods

Static Methods

Concrete Methods

Modifier and Type

Method and Description

static [SMInAppContent.DisplayMode](#)

[valueOf](#)(java.lang.String name)

Returns the enum constant of this type with the specified name.

static [SMInAppContent.DisplayMode](#)[]

[values](#)()

Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

[compareTo](#), [equals](#), [getDeclaringClass](#), [hashCode](#), [name](#), [ordinal](#), [toString](#), [valueOf](#)

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, wait, wait, wait
```

Enum Constant Detail**OnlyOnce**

```
public static final SMInAppContent.DisplayMode OnlyOnce
```

UntilReplaced

```
public static final SMInAppContent.DisplayMode UntilReplaced
```

Method Detail**values**

```
public static SMInAppContent.DisplayMode[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMInAppContent.DisplayMode c : SMInAppContent.DisplayMode.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static SMInAppContent.DisplayMode valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`java.lang.IllegalArgumentException` - if this enum type has no constant with the specified name

java.lang.NullPointerException - if the argument is null

com.selligent.sdk

Class SMInAppContentHtmlFragment

java.lang.Object
 android.app.Fragment
 android.app.DialogFragment
 com.selligent.sdk.SMInAppContentHtmlFragment

All Implemented Interfaces:

android.content.ComponentCallbacks, android.content.ComponentCallbacks2,
android.content.DialogInterface.OnCancelListener,
android.content.DialogInterface.OnDismissListener,
android.view.View.OnCreateContextMenuListener

```
public class SMInAppContentHtmlFragment  
extends android.app.DialogFragment
```

This class implements a fragment that will display one or several HTML contents. It can either be used as a standard fragment or as a full screen dialog fragment

Since:

1.4

Version:

2.1

Nested Class Summary

Nested classes/interfaces inherited from class android.app.Fragment

```
android.app.Fragment.InstantiationException, android.app.Fragment.SavedState
```

Field Summary

Fields inherited from class android.app.DialogFragment

```
STYLE_NO_FRAME, STYLE_NO_INPUT, STYLE_NO_TITLE, STYLE_NORMAL
```

Fields inherited from interface android.content.ComponentCallbacks2

```
TRIM_MEMORY_BACKGROUND, TRIM_MEMORY_COMPLETE, TRIM_MEMORY_MODERATE,  
TRIM_MEMORY_RUNNING_CRITICAL, TRIM_MEMORY_RUNNING_LOW, TRIM_MEMORY_RUNNING_MODERATE,  
TRIM_MEMORY_UI_HIDDEN
```

Constructor Summary

Constructors**Constructor and Description**

SMInAppContentHtmlFragment()

Method Summary**All Methods****Static Methods****Instance Methods****Concrete Methods**

Modifier and Type	Method and Description
java.lang.String	getContentCategory()
	<p>This method returns the category given at the creation of the instance of SMInAppContentFragment</p>
int	getContentCount()
	<p>This method returns the number of contents in the fragment</p>
SMContentType	getContentType()
	<p>This method returns the type given at the creation of the instance of SMInAppContentFragment</p>
boolean	hasContent()
	<p>Tells if the fragment has content or not.</p>
static SMInAppContentHtmlFragment	newInstance(java.lang.String category)
	<p>Method used to create a new instance of SMInAppContentHtmlFragment that will display all the HTML In App Contents available</p>
static SMInAppContentHtmlFragment	newInstance(java.lang.String category, int count)
	<p>Method used to create a new instance of SMInAppContentHtmlFragment</p>
android.view.View	onCreateView(android.view.LayoutInflater inflater, android.view.ViewGroup container, android.os.Bundle savedInstanceState)
void	onSaveInstanceState(android.os.Bundle savedInstanceState)
void	onViewCreated(android.view.View view, android.os.Bundle savedInstanceState)
void	refresh()
	<p>This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.</p>
void	show(android.app.FragmentManager fragmentManager, java.lang.String tag)
	<p>Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager.</p>
int	show(android.app.FragmentTransaction fragmentTransaction, java.lang.String tag)
	<p>Display the fragment as a full screen dialog, adding the fragment using an</p>

existing transaction and then committing the transaction.

Methods inherited from class android.app.DialogFragment

dismiss, dismissAllowingStateLoss, dump, getDialog, getShowsDialog, getTheme, isCancelable, onActivityCreated, onAttach, onCancel, onCreate, onCreateDialog, onDestroyView, onDetach, onDismiss, onGetLayoutInflater, onStart, onStop, setCancelable, setShowsDialog, setStyle

Methods inherited from class android.app.Fragment

equals, getActivity, getAllowEnterTransitionOverlap, getAllowReturnTransitionOverlap, getArguments, getChildFragmentManager, getContext, getEnterTransition, getExitTransition, getFragmentManager, getHost, getId, getLayoutInflater, getLoaderManager, getParentFragment, getReenterTransition, getResources, getRetainInstance, getReturnTransition, getSharedElementEnterTransition, getSharedElementReturnTransition, getString, getString, getTag, getTargetFragment, getTargetRequestCode, getText, getUserVisibleHint, getView, hashCode, instantiate, instantiate, isAdded, isDetached, isHidden, isInLayout, isRemoving, isResumed, isStateSaved, isVisible, onActivityResult, onAttach, onAttachFragment, onConfigurationChanged, onContextItemSelected, onCreateAnimator, onCreateOptionsMenu, onCreateOptionsMenu, onDestroy, onDestroyOptionsMenu, onHiddenChanged, onInflate, onInflate, onLowMemory, onMultiWindowModeChanged, onMultiWindowModeChanged, onOptionsItemSelected, onOptionsMenuClosed, onPause, onPictureInPictureModeChanged, onPictureInPictureModeChanged, onPrepareOptionsMenu, onRequestPermissionsResult, onResume, onTrimMemory, onViewStateRestored, postponeEnterTransition, registerForContextMenu, requestPermissions, setAllowEnterTransitionOverlap, setAllowReturnTransitionOverlap, setArguments, setEnterSharedElementCallback, setEnterTransition, setExitSharedElementCallback, setExitTransition, setHasOptionsMenu, setInitialSavedState, setMenuVisibility, setReenterTransition, setRetainInstance, setReturnTransition, setSharedElementEnterTransition, setSharedElementReturnTransition, setTargetFragment, setUserVisibleHint, shouldShowRequestPermissionRationale, startActivity, startActivity, startActivityForResult, startActivityForResult, startIntentSenderForResult, startPostponedEnterTransition, toString, unregisterForContextMenu

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

SMInAppContentHtmlFragment

```
public SMInAppContentHtmlFragment()
```

Method Detail

newInstance

```
public static SMInAppContentHtmlFragment newInstance(java.lang.String category)
```

Method used to create a new instance of SMInAppContentHtmlFragment that will display all the HTML In App Contents available

Parameters:

category - String specifying the category of the content

Returns:

the new instance of SMInAppContentImageFragment or null if one of the parameters is null.

Since:

1.4

newInstance

```
public static SMInAppContentHtmlFragment newInstance(java.lang.String category,  
int count)
```

Method used to create a new instance of SMInAppContentHtmlFragment

Parameters:

category - String specifying the category of the content

count - number of In App contents to display. A value of -1 will display all contents available. Values 0 and inferior to -1 are invalid.

Returns:

the new instance of SMInAppContentImageFragment or null if one of the parameters is null.

Since:

1.4

onCreateView

```
public android.view.View onCreateView(android.view.LayoutInflater inflater,  
android.view.ViewGroup container,  
android.os.Bundle savedInstanceState)
```

Overrides:

onCreateView in class android.app.Fragment

onViewCreated

```
public void onViewCreated(android.view.View view,
```

```
        android.os.Bundle savedInstanceState)
```

Overrides:

onViewCreated in class android.app.Fragment

onSaveInstanceState

```
public void onSaveInstanceState(android.os.Bundle savedInstanceState)
```

Overrides:

onSaveInstanceState in class android.app.DialogFragment

show

```
public void show(android.app.FragmentManager fragmentManager,
                 java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager. This is a convenience for explicitly creating a transaction, adding the fragment to it with the given tag, and committing it. This does not add the transaction to the back stack. When the fragment is dismissed, a new transaction will be executed to remove it from the activity. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentManager - The FragmentManager this fragment will be added to.

tag - String to identify the fragment

Since:

1.4

show

```
public int show(android.app.FragmentTransaction fragmentTransaction,
                java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment using an existing transaction and then committing the transaction. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentTransaction - An existing transaction in which to add the fragment.

tag - String to identify the fragment

Returns:

the identifier of the committed transaction, -1 if there is no content.

Since:

1.4 WARNING: If you set `SMSettings.LoadCacheAsynchronously` to true, there might not be any content yet when this is executed. Prefer the method `show(FragmentManager, String)` which makes sure the content is retrieved before showing the dialog.

hasContent

```
public boolean hasContent()
```

Tells if the fragment has content or not. This is useful to know if the fragment can be displayed or not.

Returns:

true if there is content, false otherwise

Since:

1.4 WARNING: If you set `SMSettings.LoadCacheAsynchronously` to true, there might not be any content yet when this is executed.

getContentCategory

```
public java.lang.String getContentCategory()
```

This method returns the category given at the creation of the instance of `SMInAppContentFragment`

Returns:

a String representing the category

Since:

1.4

getContentType

```
public SMContentType getContentType()
```

This method returns the type given at the creation of the instance of `SMInAppContentFragment`

Returns:

the `SMContentType`

getContentCount

```
public int getContentCount()
```

This method returns the number of contents in the fragment

Returns:

an int corresponding to the number of contents in the fragment

Since:

1.4

refresh

```
public void refresh()
```

This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.

com.selligent.sdk

Class SMInAppContentImageFragment

```
java.lang.Object
    android.app.Fragment
        android.app.DialogFragment
            com.selligent.sdk.SMInAppContentImageFragment
```

All Implemented Interfaces:

```
android.content.ComponentCallbacks, android.content.ComponentCallbacks2,
android.content.DialogInterface.OnCancelListener,
android.content.DialogInterface.OnDismissListener,
android.view.View.OnCreateContextMenuListener, android.view.View.OnTouchListener
```

```
public class SMInAppContentImageFragment
extends android.app.DialogFragment
implements android.view.View.OnTouchListener
```

This class implements a fragment that will display In App Content containing an image. It can either be used as a standard fragment or as a full screen dialog fragment

Since:

1.4

Version:

2.1

Nested Class Summary

Nested classes/interfaces inherited from class android.app.Fragment

```
android.app.Fragment.InstantiationException, android.app.Fragment.SavedState
```

Field Summary

Fields inherited from class android.app.DialogFragment

```
STYLE_NO_FRAME, STYLE_NO_INPUT, STYLE_NO_TITLE, STYLE_NORMAL
```

Fields inherited from interface android.content.ComponentCallbacks2

```
TRIM_MEMORY_BACKGROUND, TRIM_MEMORY_COMPLETE, TRIM_MEMORY_MODERATE,
TRIM_MEMORY_RUNNING_CRITICAL, TRIM_MEMORY_RUNNING_LOW, TRIM_MEMORY_RUNNING_MODERATE,
TRIM_MEMORY_UI_HIDDEN
```

Constructor Summary

Constructors**Constructor and Description**

SMInAppContentImageFragment()

Method Summary**All Methods****Static Methods****Instance Methods****Concrete Methods**

Modifier and Type	Method and Description
java.lang.String	getContentCategory()
	This method returns the category given at the creation of the instance of SMInAppContentFragment
int	getContentCount()
	This method returns the number of contents in the fragment
SMContentType	getContentType()
	This method returns the type given at the creation of the instance of SMInAppContentFragment
boolean	hasContent()
	Tells if the fragment has content or not.
static SMInAppContentImageFragment newInstance (java.lang.String category)	Method used to create a new instance of SMInAppContentImageFragment
android.view.View	onCreateView (android.view.LayoutInflater inflater, android.view.ViewGroup container, android.os.Bundle savedInstanceState)
void	onSaveInstanceState (android.os.Bundle savedInstanceState)
boolean	onTouch (android.view.View view, android.view.MotionEvent motionEvent)
void	onViewCreated (android.view.View view, android.os.Bundle savedInstanceState)
void	refresh()
	This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.
void	show (android.app.FragmentManager fragmentManager, java.lang.String tag)
	Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager.
int	show (android.app.FragmentTransaction fragmentTransaction, java.lang.String tag)
	Display the fragment as a full screen dialog, adding the fragment using an existing transaction and then committing the transaction.

Methods inherited from class android.app.DialogFragment

```
dismiss, dismissAllowingStateLoss, dump, getDialog, getShowsDialog, getTheme,
isCancelable, onActivityCreated, onAttach, onCancel, onCreate, onCreateDialog,
onDestroyView, onDetach, onDismiss, onGetLayoutInflater, onStart, onStop, setCancelable,
setShowsDialog, setStyle
```

Methods inherited from class android.app.Fragment

```
equals, getActivity, getAllowEnterTransitionOverlap, getAllowReturnTransitionOverlap,
getArguments, getChildFragmentManager, getContext, getEnterTransition,
getExitTransition, getFragmentManager, getHost, getId, getLayoutInflater,
getLoaderManager, getParentFragment, getReenterTransition, getResources,
getRetainInstance, getReturnTransition, getSharedElementEnterTransition,
getSharedElementReturnTransition, getString, getString, getTag, getTargetFragment,
getTargetRequestCode, getText, getUserVisibleHint, getView, hashCode, instantiate,
instantiate, isAdded, isDetached, isHidden, isInLayout, isRemoving, isResumed,
isStateSaved, isVisible, onActivityResult, onAttach, onAttachFragment,
onConfigurationChanged, onContextItemSelected, onCreateAnimator, onCreateOptionsMenu,
onCreateOptionsMenu, onDestroy, onDestroyOptionsMenu, onHiddenChanged, onInflate,
onInflate, onLowMemory, onMultiWindowModeChanged, onMultiWindowModeChanged,
onOptionsItemSelected, onOptionsMenuClosed, onPause, onPictureInPictureModeChanged,
onPictureInPictureModeChanged, onPrepareOptionsMenu, onRequestPermissionsResult,
onResume, onTrimMemory, onViewStateRestored, postponeEnterTransition,
registerForContextMenu, requestPermissions, setAllowEnterTransitionOverlap,
setAllowReturnTransitionOverlap, setArguments, setEnterSharedElementCallback,
setEnterTransition, setExitSharedElementCallback, setExitTransition, setHasOptionsMenu,
setInitialSavedState, setMenuVisibility, setReenterTransition, setRetainInstance,
setReturnTransition, setSharedElementEnterTransition, setSharedElementReturnTransition,
setTargetFragment, setUserVisibleHint, shouldShowRequestPermissionRationale,
startActivity, startActivityForResult, startActivityForResultForResult,
startIntentSenderForResult, startPostponedEnterTransition, toString,
unregisterForContextMenu
```

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, wait, wait, wait
```

Constructor Detail

SMInAppContentImageFragment

```
public SMInAppContentImageFragment()
```

Method Detail

newInstance

```
public static SMInAppContentImageFragment newInstance(java.lang.String category)
```

Method used to create a new instance of SMInAppContentImageFragment

Parameters:

category - String specifying the category of the content

Returns:

the new instance of SMInAppContentImageFragment or null if one of the parameters is null.

Since:

1.4

onTouch

```
public boolean onTouch(android.view.View view,
                      android.view.MotionEvent motionEvent)
```

Specified by:

onTouch in interface android.view.View.OnTouchListener

onCreateView

```
public android.view.View onCreateView(android.view.LayoutInflater inflater,
                                      android.view.ViewGroup container,
                                      android.os.Bundle savedInstanceState)
```

Overrides:

onCreateView in class android.app.Fragment

onViewCreated

```
public void onViewCreated(android.view.View view,
                        android.os.Bundle savedInstanceState)
```

Overrides:

onViewCreated in class android.app.Fragment

onSaveInstanceState

```
public void onSaveInstanceState(android.os.Bundle savedInstanceState)
```

Overrides:

onSaveInstanceState in class android.app.DialogFragment

show

```
public void show(android.app.FragmentManager fragmentManager,
                java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager. This is a convenience for explicitly creating a transaction, adding the fragment to it with the given tag, and committing it. This does not add the transaction to the back stack. When the fragment is dismissed, a new transaction will be executed to remove it from the activity. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentManager - The FragmentManager this fragment will be added to.

tag - String to identify the fragment

Since:

1.4

show

```
public int show(android.app.FragmentTransaction fragmentTransaction,
               java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment using an existing transaction and then committing the transaction. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentTransaction - An existing transaction in which to add the fragment.

tag - String to identify the fragment

Returns:

the identifier of the committed transaction, -1 if there is no content.

Since:

1.4 WARNING: If you set `SMSettings.LoadCacheAsynchronously` to true, there might not be any content yet when this is executed. Prefer the method `show(FragmentManager, String)` which makes sure the content is retrieved before showing the dialog.

hasContent

```
public boolean hasContent()
```

Tells if the fragment has content or not. This is useful to know if the fragment can be displayed or not.

Returns:

true if there is content, false otherwise

Since:

1.4 WARNING: If you set `SMSettings.LoadCacheAsynchronously` to true, there might not be any content yet when this is executed.

getContentCategory

```
public java.lang.String getContentCategory()
```

This method returns the category given at the creation of the instance of SMInAppContentFragment

Returns:

a String representing the category

Since:

1.4

getContentType

```
public SMContentType getContentType()
```

This method returns the type given at the creation of the instance of SMInAppContentFragment

Returns:

the SMContentType

getContentCount

```
public int getContentCount()
```

This method returns the number of contents in the fragment

Returns:

an int corresponding to the number of contents in the fragment

Since:

1.4

refresh

```
public void refresh()
```

This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.

com.selligent.sdk

Class SMInAppContentUrlFragment

```
java.lang.Object
    android.app.Fragment
        android.app.DialogFragment
            com.selligent.sdk.SMInAppContentUrlFragment
```

All Implemented Interfaces:

```
android.content.ComponentCallbacks, android.content.ComponentCallbacks2,
android.content.DialogInterface.OnCancelListener,
android.content.DialogInterface.OnDismissListener,
android.view.View.OnCreateContextMenuListener
```

```
public class SMInAppContentUrlFragment
extends android.app.DialogFragment
```

This class implements a fragment that will display In App Content containing an url. It can either be used as a standard fragment or as a full screen dialog fragment

Since:

1.4

Version:

2.0

Nested Class Summary

Nested classes/interfaces inherited from class android.app.Fragment

```
android.app.Fragment.InstantiationException, android.app.Fragment.SavedState
```

Field Summary

Fields inherited from class android.app.DialogFragment

```
STYLE_NO_FRAME, STYLE_NO_INPUT, STYLE_NO_TITLE, STYLE_NORMAL
```

Fields inherited from interface android.content.ComponentCallbacks2

```
TRIM_MEMORY_BACKGROUND, TRIM_MEMORY_COMPLETE, TRIM_MEMORY_MODERATE,
TRIM_MEMORY_RUNNING_CRITICAL, TRIM_MEMORY_RUNNING_LOW, TRIM_MEMORY_RUNNING_MODERATE,
TRIM_MEMORY_UI_HIDDEN
```

Constructor Summary

Constructors

Constructor and Description

SMInAppContentUrlFragment()

Method Summary

All Methods

Static Methods

Instance Methods

Concrete Methods

Modifier and Type

Method and Description

java.lang.String

getContentCategory()

This method returns the category given at the creation of the instance of SMInAppContentFragment

int

getContentCount()

This method returns the number of contents in the fragment

SMContentType

getContentType()

This method returns the type given at the creation of the instance of SMInAppContentFragment

boolean

hasContent()

Tells if the fragment has content or not.

static SMInAppContentUrlFragment **newInstance**(java.lang.String category)

Method used to create a new instance of SMInAppContentImageFragment

android.view.View

onCreateView(android.view.LayoutInflater inflater,
android.view.ViewGroup container,
android.os.Bundle savedInstanceState)

void

onSaveInstanceState(android.os.Bundle savedInstanceState)

void

onViewCreated(android.view.View view,
android.os.Bundle savedInstanceState)

void

refresh()

This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.

void

show(android.app.FragmentManager fragmentManager,
java.lang.String tag)

Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager.

int

show(android.app.FragmentTransaction fragmentTransaction,
java.lang.String tag)

Display the fragment as a full screen dialog, adding the fragment using an existing transaction and then committing the transaction.

Methods inherited from class android.app.DialogFragment

dismiss, dismissAllowingStateLoss, dump, getDialog, getShowsDialog, getTheme, isCancelable, onActivityCreated, onAttach, onCancel, onCreate, onCreateDialog, onDestroyView, onDetach, onDismiss, onGetLayoutInflater, onStart, onStop, setCancelable, setShowsDialog, setStyle

Methods inherited from class android.app.Fragment

equals, getActivity, getAllowEnterTransitionOverlap, getAllowReturnTransitionOverlap, getArguments, getChildFragmentManager, getContext, getEnterTransition, getExitTransition, getFragmentManager, getHost, getId, getLayoutInflater, getLoaderManager, getParentFragment, getReenterTransition, getResources, getRetainInstance, getReturnTransition, getSharedElementEnterTransition, getSharedElementReturnTransition, getString, getString, getTag, getTargetFragment, getTargetRequestCode, getText, getUserVisibleHint, getView, hashCode, instantiate, instantiate, isAdded, isDetached, isHidden, isInLayout, isRemoving, isResumed, isStateSaved, isVisible, onActivityResult, onAttach, onAttachFragment, onConfigurationChanged, onContextItemSelected, onCreateAnimator, onCreateOptionsMenu, onCreateOptionsMenu, onDestroy, onDestroyOptionsMenu, onHiddenChanged, onInflate, onInflate, onInflate, onLowMemory, onMultiWindowModeChanged, onMultiWindowModeChanged, onOptionsItemSelected, onOptionsMenuClosed, onPause, onPictureInPictureModeChanged, onPictureInPictureModeChanged, onPrepareOptionsMenu, onRequestPermissionsResult, onResume, onTrimMemory, onViewStateRestored, postponeEnterTransition, registerForContextMenu, requestPermissions, setAllowEnterTransitionOverlap, setAllowReturnTransitionOverlap, setArguments, setEnterSharedElementCallback, setEnterTransition, setExitSharedElementCallback, setExitTransition, setHasOptionsMenu, setInitialSavedState, setMenuVisibility, setReenterTransition, setRetainInstance, setReturnTransition, setSharedElementEnterTransition, setSharedElementReturnTransition, setTargetFragment, setUserVisibleHint, shouldShowRequestPermissionRationale, startActivity, startActivity, startActivityForResult, startActivityForResult, startIntentSenderForResult, startPostponedEnterTransition, toString, unregisterForContextMenu

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

SMInAppContentUrlFragment

```
public SMInAppContentUrlFragment()
```

Method Detail

newInstance

```
public static SMInAppContentUrlFragment newInstance(java.lang.String category)
```

Method used to create a new instance of SMInAppContentImageFragment

Parameters:

category - String specifying the category of the content

Returns:

the new instance of SMInAppContentImageFragment or null if one of the parameters is null.

Since:

1.4

onCreateView

```
public android.view.View onCreateView(android.view.LayoutInflater inflater,  
                                     android.view.ViewGroup container,  
                                     android.os.Bundle savedInstanceState)
```

Overrides:

onCreateView in class android.app.Fragment

onViewCreated

```
public void onViewCreated(android.view.View view,  
                         android.os.Bundle savedInstanceState)
```

Overrides:

onViewCreated in class android.app.Fragment

onSaveInstanceState

```
public void onSaveInstanceState(android.os.Bundle savedInstanceState)
```

Overrides:

onSaveInstanceState in class android.app.DialogFragment

show

```
public void show(android.app.FragmentManager fragmentManager,  
                java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment to the given FragmentManager. This is a convenience for explicitly creating a transaction, adding the fragment to it with the given tag, and committing it. This does not add the transaction to the back stack. When the fragment is dismissed, a new transaction will be executed to remove it from the activity. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentManager - The FragmentManager this fragment will be added to.

tag - String to identify the fragment

Since:

1.4

show

```
public int show(android.app.FragmentTransaction fragmentTransaction,  
                java.lang.String tag)
```

Display the fragment as a full screen dialog, adding the fragment using an existing transaction and then committing the transaction. Does nothing if there is no content.

Overrides:

show in class android.app.DialogFragment

Parameters:

fragmentTransaction - An existing transaction in which to add the fragment.

tag - String to identify the fragment

Returns:

the identifier of the committed transaction, -1 if there is no content.

Since:

1.4 WARNING: If you set SMSettings.LoadCacheAsynchronously to true, there might not be any content yet when this is executed. Prefer the method show(FragmentManager, String) which makes sure the content is retrieved before showing the dialog.

hasContent

```
public boolean hasContent()
```

Tells if the fragment has content or not. This is useful to know if the fragment can be displayed or not.

Returns:

true if there is content, false otherwise

Since:

1.4 WARNING: If you set SMSettings.LoadCacheAsynchronously to true, there might not be any content yet when this is executed.

getContentCategory

```
public java.lang.String getContentCategory()
```

This method returns the category given at the creation of the instance of SMInAppContentFragment

Returns:

a String representing the category

Since:

1.4

getContentType

```
public SMContentType getContentType()
```

This method returns the type given at the creation of the instance of SMInAppContentFragment

Returns:

the SMContentType

getContentCount

```
public int getContentCount()
```

This method returns the number of contents in the fragment

Returns:

an int corresponding to the number of contents in the fragment

Since:

1.4

refresh

```
public void refresh()
```

This method will refresh the content by getting it from the cache again and then visually refresh the component if the fragment is visible.

com.selligent.sdk

Class SMInAppMessage

java.lang.Object
com.selligent.sdk.SMInAppMessage

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMInAppMessage
extends java.lang.Object
implements java.io.Externalizable
```

An In App message

Since:

1.3

Version:

2.1

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field and Description
java.lang.String	id
java.lang.String	title

Constructor Summary

Constructors

Constructor and Description

SMInAppMessage()

SMInAppMessage(java.lang.String id, java.lang.String title)

Method Summary

All Methods

Instance Methods

Concrete Methods

Modifier and Type	Method and Description
boolean	equals (java.lang.Object otherMessage) Compares this instance with the specified object and indicates if they are equal.
int	hashCode () Returns an integer hash code for this object.
void	readExternal (java.io.ObjectInput serializedObject) This method is called when deserializing the object.
void	writeExternal (java.io.ObjectOutput serializedObject) This method is called when serializing the object.

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

id

public java.lang.String id

title

public java.lang.String title

Constructor Detail

SMInAppMessage

public SMInAppMessage()

SMInAppMessage

public SMInAppMessage(java.lang.String id,
 java.lang.String title)

Method Detail

equals

```
public boolean equals(java.lang.Object otherMessage)
```

Compares this instance with the specified object and indicates if they are equal.

Overrides:

equals in class java.lang.Object

Parameters:

otherMessage - the object to compare this instance with.

Returns:

true if the specified object is equal to this Object; false otherwise.

hashCode

```
public int hashCode()
```

Returns an integer hash code for this object. By contract, any two objects for which `equals (Object)` returns true must return the same hash code value. This means that subclasses of Object usually override both methods or neither method.

Overrides:

hashCode in class java.lang.Object

Returns:

this object's hash code.

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Specified by:

`readExternal` in interface `java.io.Externalizable`

Parameters:

serializedObject - the `ObjectInput` object containing all the values of the `SMInAppMessage` object to recreate.

Throws:

`java.io.IOException`

`java.lang.ClassNotFoundException`

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the SMInAppMessage object

Throws:

java.io.IOException

com.selligent.sdk

Enum SMInAppRefreshType

```
java.lang.Object
  java.lang.Enum<SMInAppRefreshType>
    com.selligent.sdk.SMInAppRefreshType
```

All Implemented Interfaces:

java.io.Serializable, java.lang.Comparable<SMInAppRefreshType>

```
public enum SMInAppRefreshType
extends java.lang.Enum<SMInAppRefreshType>
```

Enum with the different values for the refresh of the In App messages and In Ap contents. Messages/contents will be retrieved when the application becomes active (if In App messages/contents are enabled) if the last fetch was older than the refresh type. Minutely is there for testing purposes ONLY. We do NOT recommend using it in production.

Since:

1.3

Version:

2.1

Enum Constant Summary

Enum Constants**Enum Constant and Description****Daily****Hourly****Minutely****None**

Method Summary

All Methods**Static Methods****Concrete Methods****Modifier and Type****Method and Description****static SMInAppRefreshType****valueOf**(java.lang.String name)

Returns the enum constant of this type with the specified name.

static SMInAppRefreshType[] values()

Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

```
compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf
```

Methods inherited from class java.lang.Object

```
getClass, notify, notifyAll, wait, wait, wait
```

Enum Constant Detail**None**

```
public static final SMInAppRefreshType None
```

Minutely

```
public static final SMInAppRefreshType Minutely
```

Hourly

```
public static final SMInAppRefreshType Hourly
```

Daily

```
public static final SMInAppRefreshType Daily
```

Method Detail**values**

```
public static SMInAppRefreshType[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMInAppRefreshType c : SMInAppRefreshType.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static SMInAppRefreshType valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

java.lang.IllegalArgumentException - if this enum type has no constant with the specified name

java.lang.NullPointerException - if the argument is null

com.selligent.sdk

Class SMLink

java.lang.Object
 com.selligent.sdk.SMNotificationButton
 com.selligent.sdk.SMLink

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

```
public class SMLink
extends SMNotificationButton
```

A link of an SMInAppContent.

Since:

1.4

Version:

2.1

See Also:

Serialized Form

Field Summary

Fields inherited from class com.selligent.sdk.SMNotificationButton

```
action, data, id, label, type, value
```

Constructor Summary

Constructors

Constructor and Description

```
SMLink()
```

Method Summary

Methods inherited from class com.selligent.sdk.SMNotificationButton

```
readExternal, writeExternal
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructor Detail

SMLink

```
public SMLink()
```

com.selligent.sdk

Class SMManager

```
java.lang.Object
    com.selligent.sdk.SMManager
```

```
public class SMManager
extends java.lang.Object
```

Singleton object used to interact with the Selligent Mobile SDK.

Since:

1.0

Version:

2.1

Field Summary

Fields

Modifier and Type	Field and Description
static java.lang.String	BROADCAST_DATA_BUTTON String representing a key to retrieve an object inside an intent Use this key to retrieve the object SMNotificationButton from the intent received from the broadcast BROADCAST_EVENT_BUTTON_CLICKED .
static java.lang.String	BROADCAST_DATA_GCM_TOKEN String representing a key to retrieve an object inside an intent Use this key to retrieve the GCM token from the intent received from the broadcast BROADCAST_EVENT_RECEIVED_GCM_TOKEN .
static java.lang.String	BROADCAST_DATA_IN_APP_CONTENTS String representing a key to retrieve an object inside an intent Use this key to retrieve a dictionary containing the number of contents for each category from the broadcast BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE .
static java.lang.String	BROADCAST_DATA_IN_APP_MESSAGES String representing a key to retrieve an object inside an intent Use this key to retrieve an array of SMAInAppMessage from the intent received from the broadcast BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE .
static java.lang.String	BROADCAST_EVENT_BUTTON_CLICKED String representing a broadcast name you can listen to.
static java.lang.String	BROADCAST_EVENT_RECEIVED_GCM_TOKEN String representing a broadcast name you can listen to.
static java.lang.String	BROADCAST_EVENT_RECEIVED_IN_APP_CONTENTS String representing a broadcast name you can listen to.
static java.lang.String	BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE String representing a broadcast name you can listen to.
static java.lang.String	BROADCAST_EVENT_RECEIVED_REMOTE_NOTIFICATION Deprecated. Since listening to broadcast in background is no longer possible under Android O, this broadcast is now deprecated (it is still sent though, so if you don't target Android O, you will still be able to listen to it).
static java.lang.String	BROADCAST_EVENT_WILL_DISMISS_NOTIFICATION String representing a broadcast name you can listen to.
static java.lang.String	BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION String representing a broadcast name you can listen to.
static boolean	DEBUG When true, different actions and informations will be logged by the SDK and visible in the logcat in Android Studio (tag "SDK").
static boolean	DISPLAY_ERROR_MESSAGE Deprecated. This value is of no use anymore

static boolean	IS_LOCATIONTRACKER_ACTIF
	Deprecated.
	This is not used
static float	MIN_DISTANCE_CHANGE_FOR_UPDATES
	Deprecated.
	This is not used
static long	MIN_TIME_BW_UPDATES
	Deprecated.
	This is not used
static java.lang.Class	NOTIFICATION_ACTIVITY
	The activity that will be called when opening a notification.
static java.lang.String	VERSION_LIB
	The version of the Selligent Mobile SDK library

Method Summary

All Methods	Static Methods	Instance Methods	Concrete Methods	Deprecated Methods			
Modifier and Type		Method and Description					
boolean	areInAppMessagesEnabled()						
	This method tells if the management of In App messages is enabled or not						
boolean	areNotificationEnabled()						
	This method tells if the reception of notifications is enabled or not						
void	checkAndDisplayMessage(android.content.Intent intent, android.content.Context context)						
	This method will check if there is a message to be displayed in the given intent and will display it.						
void	disableGeolocation()						
	Disables the geolocation functionality.						
void	disableInAppMessages()						
	This method disables the management of "in app" messages.						
void	disableNotifications()						
	This method disables the reception of push notifications from the server.						
void	displayLastReceivedRemotePushNotification(android.app.Activity activity)						
	Display the latest received remote notification This is mostly used in conjunction with RemoteMessageDisplayType set to None						
void	displayMessage(java.lang.String messageId, android.app.Activity activity)						
	Display the given message (remote or In App) whose id is given, like if clicking on the notification						
void	displayNotification(android.content.Context context, android.content.Intent intent)						
	This method is to be used only if you set SMSettings.DoNotListenToThePush to true.						
void	enableGeolocation()						
	Enables the geolocation functionality.						
void	enableInAppMessages (SMInAppRefreshType refreshType)						
	This method enables the management of "in app" messages.						
void	enableNotifications()						
	This method enables the reception of push notifications from the server.						
void	executeLinkAction(android.content.Context context, SMLink link, SMInAppContent content)						
	This method will execute the action attached to the given SMLink of the given SMInAppContent .						
java.lang.String	getGCCMToken()						

This methods returns the GCM token stored by the SDK after calling `registerDevice(Context)`.

`java.util.ArrayList<SMInAppContent>`

`getInAppContents(java.lang.String category, SMContentType type, int max)`
Gets the list of valid `SMInAppContent` for the given type and category.

`void`

`getInAppContents(java.lang.String category, SMContentType type, int max, com.selligent.sdk.SMInAppContentReturn callbackEvent)`
Gets the list of valid `SMInAppContent` for the given type and category.

`static SMManager`

`getInstance()`

`java.util.HashMap<java.lang.String,java.lang.String>`

`getLastRemotePushNotification()`

Get the id and the title of the latest received remote notification This is mostly used in conjunction with RemoteMessageDisplayType set to None

`android.graphics.Bitmap`

`getNotificationLargeIcon()`

Gets the icon set by setNotificationLargeIcon.

`int`

`getNotificationSmallIcon()`

This returns the resource id set by setNotificationSmallIcon.

`SMRemoteMessageDisplayType`

`getRemoteMessagesDisplayType()`

Gets the way remote messages are displayed when the app is in foreground.

`boolean`

`isGeolocationEnabled()`

Tells if the geolocation is enabled or not.

`void`

`registerDevice(android.content.Context context)`

Deprecated.

Use the json file given by the Firebase Console when activating Cloud Messaging on your project. The SDK will then automatically retrieve the token.

`void`

`reload(SMSettings settings, android.app.Activity activity)`

This method is used in the special case of the Selligent demo app Parana and should not be needed.

`void`

`sendDeviceInfo()`

Deprecated.

`void`

`sendDeviceInfo(com.selligent.sdk.SMDeviceInfos deviceInfos)`

This method will send a "SetInfo" event to the platform ONLY if the properties of the SMDeviceInfos object changed since the last call

`void`

`sendEvent(SMEvent event)`

Deprecated.

use `sendSMEvent(com.selligent.sdk.SMEvent)` instead

`void`

`sendSMEvent(SMEvent event)`

Use this method to send an event to the Selligent platform.

`void`

`setApplication(android.app.Application app)`

This gives to the SDK a pointer to the Application instance.

`void`

`setFirebaseToken(java.lang.String token)`

This method is to be used only if you set `SMSettings.DoNotFetchTheToken` to true.

`void`

`setInAppContentAsSeen(SMInAppContent inAppContent)`

Set the given `SMInAppContent` as seen.

`void`

`setNotificationCallback(SMNotificationCallback callback)`

Deprecated.

Since 1.3, a broadcast is performed at the click of a button (cf. `BROADCAST_EVENT_BUTTON_CLICKED`)

`void`

`setNotificationLargeIcon(int iconResource)`

This allows the SDK to use a specific icon for the notifications.

`void`

`setNotificationSmallIcon(int iconResource)`

This allows the SDK to use a specific icon for the notifications.

`void`

`start(SMSettings settings)`

Mandatory method used to setup the Selligent Mobile SDK.

```
void start(SMSMSettings settings, android.app.Application application)
Mandatory method used to setup the Selligent Mobile SDK.
```

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait
```

Field Detail

BROADCAST_EVENT_RECEIVED_REMOTE_NOTIFICATION

```
@Deprecated
public static final java.lang.String BROADCAST_EVENT_RECEIVED_REMOTE_NOTIFICATION
```

Deprecated. Since listening to broadcast in background is no longer possible under Android O, this broadcast is now deprecated (it is still sent though, so if you don't target Android O, you will still be able to listen to it).

String representing a broadcast name you can listen to. It is broadcast shortly after receiving a remote-notification Primary-application may use this notification to decide when to display any remote-notification This broadcast can be sent while the app is in background and, therefore, is sent using a normal Context.sendBroadcast(Intent) To listen to this broadcast, you also have to set the package name of your app as a category to your IntentFilter

Since:

1.3

See Also:

Context.sendBroadcast(Intent), IntentFilter, Constant Field Values

BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE

```
public static final java.lang.String BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE
```

String representing a broadcast name you can listen to. It is broadcasted shortly after receiving InApp messages Primary-application may use this notification to manage the received InApp messages This broadcast is sent locally using LocalBroadcastManager.sendBroadcast(Intent)

Since:

1.3

See Also:

LocalBroadcastManager.sendBroadcast(Intent), Constant Field Values

BROADCAST_EVENT_RECEIVED_IN_APP_CONTENTS

```
public static final java.lang.String BROADCAST_EVENT_RECEIVED_IN_APP_CONTENTS
```

String representing a broadcast name you can listen to. It is broadcasted shortly after receiving InApp contents Primary-application may use this notification to manage the received InApp contents This broadcast is sent locally using LocalBroadcastManager.sendBroadcast(Intent)

Since:

1.4

See Also:

LocalBroadcastManager.sendBroadcast(Intent), Constant Field Values

BROADCAST_EVENT_BUTTON_CLICKED

```
public static final java.lang.String BROADCAST_EVENT_BUTTON_CLICKED
```

String representing a broadcast name you can listen to. It is broadcasted when the user interacts with a remote-notification Usefull to retrieve user's actions on a received remote-notification. This broadcast is sent locally using LocalBroadcastManager.sendBroadcast(Intent)

Since:

1.3

See Also:

LocalBroadcastManager.sendBroadcast(Intent), Constant Field Values

BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION

```
public static final java.lang.String BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION
```

String representing a broadcast name you can listen to. It is broadcasted shortly before displaying a remote-notification Primary-application may use this broadcast to pause any ongoing work before the remote-notification is displayed. This broadcast is also triggered even if you disable `shouldDisplayRemoteNotification` (see `SMSettings`). This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `BROADCAST_EVENT_WILL_DISMISS_NOTIFICATION`, Constant Field Values

BROADCAST_EVENT_WILL_DISMISS_NOTIFICATION

```
public static final java.lang.String BROADCAST_EVENT_WILL_DISMISS_NOTIFICATION
```

String representing a broadcast name you can listen to. It is broadcasted shortly before dismissing the current remote-notification Primary-application may use this broadcast to resume any paused work. (see `BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION`) This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION`, Constant Field Values

BROADCAST_EVENT RECEIVED_GCM_TOKEN

```
public static final java.lang.String BROADCAST_EVENT_RECEIVED_GCM_TOKEN
```

String representing a broadcast name you can listen to. It is broadcasted after receiving the GCM token and only if it changed. Primary-application may use this broadcast to retrieve the GCM token. This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, Constant Field Values

BROADCAST_DATA_IN_APP_MESSAGES

```
public static final java.lang.String BROADCAST_DATA_IN_APP_MESSAGES
```

String representing a key to retrieve an object inside an intent Use this key to retrieve an array of `SMInAppMessage` from the intent received from the broadcast `BROADCAST_EVENT RECEIVED_IN_APP_MESSAGE`. This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `SMInAppMessage`, `BROADCAST_EVENT RECEIVED_IN_APP_MESSAGE`, Constant Field Values

BROADCAST_DATA_IN_APP_CONTENTS

```
public static final java.lang.String BROADCAST_DATA_IN_APP_CONTENTS
```

String representing a key to retrieve an object inside an intent Use this key to retrieve an dictionary containing the number of contents for each category from the broadcast `BROADCAST_EVENT RECEIVED_IN_APP_MESSAGE`. This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.4

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `BROADCAST_EVENT RECEIVED_IN_APP_CONTENTS`, Constant Field Values

BROADCAST_DATA_BUTTON

```
public static final java.lang.String BROADCAST_DATA_BUTTON
```

String representing a key to retrieve an object inside an intent Use this key to retrive the object `SMNotificationButton` from the intent received from the broadcast `BROADCAST_EVENT_BUTTON_CLICKED`. This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `SMNotificationButton`, `BROADCAST_EVENT_BUTTON_CLICKED`, Constant Field Values

BROADCAST_DATA_GCM_TOKEN

```
public static final java.lang.String BROADCAST_DATA_GCM_TOKEN
```

String representing a key to retrieve an object inside an intent Use this key to retrieve the GCM token from the intent received from the broadcast `BROADCAST_EVENT_RECEIVED_GCM_TOKEN`. This broadcast is sent locally using `LocalBroadcastManager.sendBroadcast(Intent)`

Since:

1.3

See Also:

`LocalBroadcastManager.sendBroadcast(Intent)`, `BROADCAST_EVENT_RECEIVED_GCM_TOKEN`, Constant Field Values

MIN_TIME_BW_UPDATES

@Deprecated

```
public static long MIN_TIME_BW_UPDATES
```

Deprecated. This is not used

MIN_DISTANCE_CHANGE_FOR_UPDATES

@Deprecated

```
public static float MIN_DISTANCE_CHANGE_FOR_UPDATES
```

Deprecated. This is not used

IS_LOCATIONTRACKER_ACTIF

@Deprecated

```
public static boolean IS_LOCATIONTRACKER_ACTIF
```

Deprecated. This is not used

DISPLAY_ERROR_MESSAGE

@Deprecated

```
public static boolean DISPLAY_ERROR_MESSAGE
```

Deprecated. This value is of no use anymore

DEBUG

```
public static boolean DEBUG
```

When true, different actions and informations will be logged by the SDK and visible in the logcat in Android Studio (tag "SDK"). This is for debug only and should never be set to true in a release. Default value is false.

NOTIFICATION_ACTIVITY

```
public static java.lang.Class NOTIFICATION_ACTIVITY
```

The activity that will be called when opening a notification. Default value is `SMNotificationActivity`

VERSION_LIB

```
public static final java.lang.String VERSION_LIB
```

The version of the Selligent Mobile SDK library

See Also:

[Constant Field Values](#)

Method Detail**getInstance**

```
public static SMManager getInstance()
```

Returns:

the SMManager instance

start

```
public void start(SMSettings settings)
```

Mandatory method used to setup the Selligent Mobile SDK. It can only be called once (usually in a class extending SMApplication). Any later call with different values would be ineffective. Use this version ONLY if you extend [SMApplication](#)

Parameters:

settings - an SMSettings object containing the Google application id, the web service URL, the Selligent client id and the Selligent private key.

See Also:

[SMSettings](#)

start

```
public void start(SMSettings settings,
                  android.app.Application application)
```

Mandatory method used to setup the Selligent Mobile SDK. It can only be called once (usually in a class extending SMApplication). Any later call with different values would be ineffective. You must use this version if you do not extend [SMApplication](#)

Parameters:

settings - an SMSettings object containing the Google application id, the web service URL, the Selligent client id and the Selligent private key.

application - the instance of the class extending Application

Since:

1.1

See Also:

[SMSettings](#)

reload

```
public void reload(SMSettings settings,
                  android.app.Activity activity)
```

This method is used in the special case of the Selligent demo app Parana and should not be needed. It allows to change the settings given at startup by the start method.

Parameters:

settings - an SMSettings object containing the Google application id, the web service URL, the Selligent client id and the Selligent private key.

activity - the current Activity

See Also:

[SMSettings](#)

setApplication

```
public void setApplication(android.app.Application app)
```

This gives to the SDK a pointer to the Application instance. You should only call this if you do not extend SMAplication.

Parameters:

app - the Application instance

See Also:

[SMAplication](#)

registerDevice

@Deprecated

```
public void registerDevice(android.content.Context context)
```

Deprecated. Use the json file given by the Firebase Console when activating Cloud Messaging on your project. The SDK will then automatically retrieve the token.

This method will check if the application just started and, if so, will send a first event to the Selligent Mobile Platform. It will also register the device to Google Cloud Messaging if it isn't already. If the application comes from the background, it doesn't do anything. You have to use this method on the onCreate event of your activities if you do not extend `SMB BaseActivity` New since 1.5: if you are using the new Firebase way to retrieve the token (using the json file), then you don't need to call this method. It will not do anything anyway if the GoogleApplicationId is empty.

Parameters:

context - the activity in which this method is called

Since:

1.1

getGCMToken

```
public java.lang.String getGCMToken()
```

This methods returns the GCM token stored by the SDK after calling `registerDevice (Context)`. As the registration is asynchronous, the token returned may be empty or not up-to-date if the registration process is not completed.

Returns:

the stored GCM token

Since:

1.3

See Also:

`registerDevice (Context)`

setFirebaseToken

```
public void setFirebaseToken(java.lang.String token)
```

This method is to be used only if you set `SMSettings.DoNotFetchTheToken` to true. It will store the token in the SDK cache and send it to the Selligent platform if needed (if the SDK doesn't have it already or if the token changed)

Parameters:

token - The string that you got from Firebase to enable push notifications.

Since:

2.1.0

checkAndDisplayMessage

```
public void checkAndDisplayMessage(android.content.Intent intent,
                                  android.content.Context context)
```

This method will check if there is a message to be displayed in the given intent and will display it. It has to be used in the onCreate (after `registerDevice (Context)`) and onNewIntent events if your activity does not extend `SMB BaseActivity`.

Parameters:

intent - the intent containing the message
 context - the activity in which this method is called

Since:

1.1

enableNotifications

```
public void enableNotifications()
```

This method enables the reception of push notifications from the server. It sends an "opt-in" message to the web service to allow it to send push notifications to the device.

disableNotifications

```
public void disableNotifications()
```

This method disables the reception of push notifications from the server. It sends an "opt-out" message to the web service to tell it to stop sending push notifications to the device. Any still received will be ignored by the SDK.

areNotificationEnabled

```
public boolean areNotificationEnabled()
```

This method tells if the reception of notifications is enabled or not

Returns:

true if enabled, false otherwise

setNotificationSmallIcon

```
public void setNotificationSmallIcon(int iconResource)
```

This allows the SDK to use a specific icon for the notifications. This small icon will be visible in the status bar at the top of the device.

Parameters:

iconResource - the resource id of the icon (R.id.your_icon)

getNotificationSmallIcon

```
public int getNotificationSmallIcon()
```

This returns the resource id set by setNotificationSmallIcon.

Returns:

the resource id.

See Also:

[setNotificationSmallIcon\(int\)](#)

setNotificationLargeIcon

```
public void setNotificationLargeIcon(int iconResource)
```

This allows the SDK to use a specific icon for the notifications. This large icon will be visible in the notification view.

Parameters:

iconResource - the resource id of the icon (R.id.your_icon)

getNotificationLargeIcon

```
public android.graphics.Bitmap getNotificationLargeIcon()
```

Gets the icon set by setNotificationLargeIcon.

Returns:

```
the Bitmap of the icon
```

See Also:

```
setNotificationLargeIcon(int)
```

setNotificationCallback

@Deprecated

```
public void setNotificationCallback(SMNotificationCallback callback)
```

Deprecated. Since 1.3, a broadcast is performed at the click of a button (cf. `BROADCAST_EVENT_BUTTON_CLICKED`)

Sets the callback object containing the code that will be executed whenever a button received in a push notification is clicked

Parameters:

```
callback - a SMNotificationCallback object
```

See Also:

```
SMNotificationCallback
```

displayLastReceivedRemotePushNotification

```
public void displayLastReceivedRemotePushNotification(android.app.Activity activity)
```

Display the latest received remote notification This is mostly used in conjunction with RemoteMessageDisplayType set to None

Parameters:

```
activity - the current activity
```

Since:

1.3

getLastRemotePushNotification

```
public java.util.HashMap<java.lang.String,java.lang.String> getLastRemotePushNotification()
```

Get the id and the title of the latest received remote notification This is mostly used in conjunction with RemoteMessageDisplayType set to None

Returns:

```
a HashMap containing the "id" and "title" of the last remote notification
```

Since:

1.3

getRemoteMessagesDisplayType

```
public SMRemoteMessageDisplayType getRemoteMessagesDisplayType()
```

Gets the way remote messages are displayed when the app is in foreground. If Automatic, no notification will be created, the message will be displayed right away. If Notification, a notification will be created and the message will be displayed only after clicking on it. If None, nothing will happen, the app will need to manage the display of the message (cf. `getLastRemotePushNotification()`, `displayLastReceivedRemotePushNotification(android.app.Activity)`)

Returns:

```
the SMRemoteMessageDisplayType
```

Since:

1.3

displayNotification

```
public void displayNotification(android.content.Context context,
                               android.content.Intent intent)
```

This method is to be used only if you set `SMSettings.DoNotListenToThePush` to true. It will create a notification based on the information present in the intent and will display it. If the app is in foreground and the setting `SMSettings.RemoteMessageDisplayType` is set to 'Automatic', the SDK will display the in-app message linked to the push right away without going through a notification.

Parameters:

context -
 intent - it contains all the push information. If you retrieve the push using the `FirebaseMessagingService` method `onMessageReceived`, simply call `toIntent()` on the `RemoteMessage` object received.

Since:

2.1.0

enableInAppMessages

```
public void enableInAppMessages (SMInAppRefreshType refreshType)
```

This method enables the management of "in app" messages.

Parameters:

refreshType - How often the SDK will fetch the new messages.

Since:

1.3

areInAppMessagesEnabled

```
public boolean areInAppMessagesEnabled()
```

This method tells if the management of In App messages is enabled or not

Returns:

true if enabled, false otherwise

Since:

1.3

disableInAppMessages

```
public void disableInAppMessages()
```

This method disables the management of "in app" messages.

Since:

1.3

displayMessage

```
public void displayMessage(java.lang.String messageId,
                           android.app.Activity activity)
```

Display the given message (remote or In App) whose id is given, like if clicking on the notification

Parameters:

messageId - the string id of the message to display

activity - the current activity

Since:

1.3

getInAppContents

```
public java.util.ArrayList<SMInAppContent> getInAppContents(java.lang.String category,
                                                               SMContentType type,
                                                               int max)
```

Gets the list of valid `SMInAppContent` for the given type and category. Use this method if you do not want to implement our Fragments.

Parameters:

category - The category of the `SMInAppContent`.

type - The `SMContentType` of the `SMInAppContent`.

max - The number of contents to get. -1 to get them all.

Returns:

An ArrayList of SMInAppContent.

Since:

1.4 Warning: if the cache is loaded asynchronously, there might not be any content yet when you execute this call. In order to be sure to retrieve them, call `getInAppContents(String, SMContentType, int, SMInAppContentReturn)`

getInAppContents

```
public void getInAppContents(java.lang.String category,
                           SMContentType type,
                           int max,
                           com.selligent.sdk.SMInAppContentReturn callbackEvent)
```

Gets the list of valid SMInAppContent for the given type and category. Use this method if you do not want to implement our Fragments.

Parameters:

category - The category of the SMInAppContent.

type - The SMContentType of the SMInAppContent.

max - The number of contents to get. -1 to get them all.

callbackEvent - The event that will be called when the contents are retrieved. It will be passed an ArrayList of SMInAppContent

Since:

2.1.0

setInAppContentAsSeen

```
public void setInAppContentAsSeen(SMInAppContent inAppContent)
```

Set the given SMInAppContent as seen. It will also send an event to the platform to inform it. Use this method if you do not want to implement our Fragments.

Parameters:

inAppContent - the SMInAppContent

Since:

1.4

executeLinkAction

```
public void executeLinkAction(android.content.Context context,
                           SMLink link,
                           SMInAppContent content)
```

This method will execute the action attached to the given SMLink of the given SMInAppContent. It will also send an event to the platform to inform the link was clicked. Use this method if you do not want to implement our Fragments.

Parameters:

context - the current Activity.

link - the SMLink containing the action to execute.

content - the corresponding SMInAppContent.

Since:

1.4

enableGeolocation

```
public void enableGeolocation()
```

Enables the geolocation functionality. It will be enabled until `disableGeolocation()` is called. It will keep going even if the app or the device is restarted. The goal is to provide users with an opt-in. WARNING: this method should only be called if "enableOnFirstRun" is set to "false" in the plotconfig.json file. **With the default configuration, you do not have to call it.**

Since:

1.7

disableGeolocation

```
public void disableGeolocation()
```

Disables the geolocation functionality. No geolocation related notification will be sent anymore to the user. It will be disabled until `enableGeolocation()` is called even if the app or the device is restarted. The goal is to provide users with an opt-out.

Since:

1.7

isGeolocationEnabled

```
public boolean isGeolocationEnabled()
```

Tells if the geolocation is enabled or not.

Since:

1.7

sendEvent

@Deprecated

```
public void sendEvent(SMEvent event)
```

Deprecated. use `sendSMEvent(com.selligent.sdk.SMEvent)` instead

Use this method to send an event to the Selligent platform.

Parameters:

`event` - an `SMEvent` object

See Also:

`SMEvent`, `SMEventUserLogin`, `SMEventUserLogout`, `SMEventUserRegister`, `SMEventUserUnregister`

sendSMEvent

```
public void sendSMEvent(SMEvent event)
```

Use this method to send an event to the Selligent platform. If you are sending a simple `SMEvent`, then we will check if the values are different from the last time you sent them. If they are not, the event won't be sent.

Parameters:

`event` - an `SMEvent` object

Since:

1.2

See Also:

`SMEvent`, `SMEventUserLogin`, `SMEventUserLogout`, `SMEventUserRegister`, `SMEventUserUnregister`

sendDeviceInfos

@Deprecated

```
public void sendDeviceInfos()
```

Deprecated.

This method is deprecated as of 1.6 and does not do anything anymore. Use `sendDeviceInfos(SMDeviceInfos)` instead

Since:

1.4.1

sendDeviceInfos

```
public void sendDeviceInfos(com.selligent.sdk.SMDeviceInfos deviceInfos)
```

This method will send a "SetInfo" event to the platform ONLY if the properties of the SMDeviceInfo object changed since the last call

Parameters:

deviceInfos - Wrapper over a few properties of the device.

com.selligent.sdk

Class SMNotificationButton

java.lang.Object
 com.selligent.sdk.SMNotificationButton

All Implemented Interfaces:

java.io.Externalizable, java.io.Serializable

Direct Known Subclasses:

SMLink

```
public class SMNotificationButton
extends java.lang.Object
implements java.io.Externalizable
```

Object containing all the data used to implement a button in a notification/message.

Since:

1.3

Version:

2.1

See Also:

[Serialized Form](#)

Field Summary

Fields

Modifier and Type	Field and Description
int	action
java.util.Hashtable<java.lang.String,java.lang.String>	data
java.lang.String	id
java.lang.String	label
int	type
java.lang.String	value

Constructor Summary

Constructors

Constructor and Description

```
SMNotificationButton()
```

Method Summary

All Methods	Instance Methods	Concrete Methods
Modifier and Type		Method and Description
void		readExternal (java.io.ObjectInput serializedObject) This method is called when deserializing the object.
void		writeExternal (java.io.ObjectOutput serializedObject) This method is called when serializing the object.

Methods inherited from class java.lang.Object

```
equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Field Detail

label

```
public java.lang.String label
```

id

```
public java.lang.String id
```

type

```
public int type
```

action

```
public int action
```

value

```
public java.lang.String value
```

data

```
public java.util.Hashtable<java.lang.String,java.lang.String> data
```

Constructor Detail

SMNotificationButton

```
public SMNotificationButton()
```

Method Detail

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Specified by:

readExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectInput object containing all the values of the SMNotificationButton object to recreate.

Throws:

java.io.IOException

java.lang.ClassNotFoundException

Since:

1.3

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Specified by:

writeExternal in interface java.io.Externalizable

Parameters:

serializedObject - the ObjectOutputStream object used to store the values of the

SMNotificationButton

SMNotificationButton object

Throws:

java.io.IOException

Since:

1.3

com.selligent.sdk

Interface SMNotificationCallback

Deprecated.

Since 1.3, a broadcast is performed at the click on a button (cf. `SMManager.BROADCAST_EVENT_BUTTON_CLICKED`)

```
@Deprecated  
public interface SMNotificationCallback
```

Interface used to allow code to be called when clicking on a button received from a push and displayed in an alert dialog, menu of a web view, etc. It will be called no matter the action the button is supposed to perform.

Since:

1.0

Version:

2.1

Method Summary

All Methods	Instance Methods	Abstract Methods	Deprecated Methods
Modifier and Type	Method and Description		
void	<code>onButtonClick(java.lang.String buttonId, int buttonAction, java.lang.String buttonValue)</code> Deprecated.		

Method Detail

onButtonClick

```
void onButtonClick(java.lang.String buttonId,  
                  int buttonAction,  
                  java.lang.String buttonValue)
```

Deprecated.

com.selligent.sdk

Enum SMRemoteMessageDisplayType

```
java.lang.Object
    java.lang.Enum<SMRemoteMessageDisplayType>
        com.selligent.sdk.SMRemoteMessageDisplayType
```

All Implemented Interfaces:

```
java.io.Serializable, java.lang.Comparable<SMRemoteMessageDisplayType>
```

```
public enum SMRemoteMessageDisplayType
extends java.lang.Enum<SMRemoteMessageDisplayType>
```

List the different possibilities to display a remote message received while the app is in foreground - Automatic: the message is automatically displayed - Notification: a notification is created, the user needs to click on it to display the message - None: nothing is done, the message is not displayed, it is up to the app to display it (cf.

```
SMManager.getLastRemotePushNotification(),
SMManager.displayLastReceivedRemotePushNotification(android.app.Activity))
```

Since:

1.3

Version:

2.1

Enum Constant Summary

Enum Constants**Enum Constant and Description****Automatic****None****Notification**

Method Summary

All Methods**Static Methods****Concrete Methods****Modifier and Type****Method and Description****static SMRemoteMessageDisplayType****valueOf (java.lang.String name)**

Returns the enum constant of this type with the specified name.

static SMRemoteMessageDisplayType []**values ()**

Returns an array containing the constants of this enum type, in

the order they are declared.

Methods inherited from class java.lang.Enum

compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Detail

Automatic

```
public static final SMRemoteMessageDisplayType Automatic
```

Notification

```
public static final SMRemoteMessageDisplayType Notification
```

None

```
public static final SMRemoteMessageDisplayType None
```

Method Detail

values

```
public static SMRemoteMessageDisplayType[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMRemoteMessageDisplayType c : SMRemoteMessageDisplayType.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

SMRemoteMessageDisplayType

```
public static SMRemoteMessageDisplayType valueOf(java.lang.String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

`java.lang.IllegalArgumentException` - if this enum type has no constant with the specified name

`java.lang.NullPointerException` - if the argument is null

com.selligent.sdk

Class SMSettings

java.lang.Object
 com.selligent.sdk.SMSettings

```
public class SMSettings
extends java.lang.Object
```

Configuration object passed to the 'start' method of SMManager.

Since:

1.0

Version:

2.1

See Also:

SMManager.start(SMSettings)

Field Summary

Fields

Modifier and Type	Field and Description
SMClearCache	ClearCacheIntervalValue This value tells how often the SDK's inAppMessagesCache mechanism should clear itself.
java.lang.String	ClientId The client id given by Selligent to contact the web services
boolean	ConfigureGeolocation This will tell the SDK to use the geolocation.
boolean	DoNotFetchTheToken If set to true, the SDK will not try to retrieve the token used for push notification from Firebase.
boolean	DoNotListenToThePush If set to true, the SDK will not listen for the push anymore.
java.lang.String	GoogleApplicationId Deprecated. You don't need to set this property as long as you use the JSON file given by Firebase
SMInAppRefreshType	InAppContentRefreshType This will tell how often the SDK must get the In App content.

SMInAppRefreshType	InAppMessageRefreshType
boolean	This is will tell how often the SDK must get the In App messages.
java.lang.String	LoadCacheAsynchronously
	This will make the SDK load the content of its cache asynchronously.
java.lang.String	PrivateKey
	The private key given by Selligent to contact the web services
SMRemoteMessageDisplayType	RemoteMessageDisplayType
	If set to Automatic, when the app is active, the remote push messages will automatically be displayed.
SMTHEMECategories	Theme
	Deprecated.
	since 1.4, this value is not used anymore
java.lang.String	WebServiceUrl
	The URL of the Selligent web services

Constructor Summary

Constructors

Constructor and Description

SMSettings ()

Method Summary

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

GoogleApplicationId

```
@Deprecated
public java.lang.String GoogleApplicationId
```

Deprecated. You don't need to set this property as long as you use the JSON file given by Firebase
The application id given by the Firebase Developer Console

WebServiceUrl

```
public java.lang.String WebServiceUrl
```

The URL of the Selligent web services

ClientId

```
public java.lang.String ClientId
```

The client id given by Selligent to contact the web services

PrivateKey

```
public java.lang.String PrivateKey
```

The private key given by Selligent to contact the web services

Theme

@Deprecated

```
public SMTHEMECategories Theme
```

Deprecated. since 1.4, this value is not used anymore

The category of theme used (Holo, Material, AppCompat, DeviceDefault or Theme). This will allow the SDK to create the alert dialogs with a correct layout. If set to DeviceDefault, the layout of the dialog will depend on the version of Android (Lollipop and above will have Material, others will have Holo).

Since:

1.2

ClearCacheIntervalValue

```
public SMClearCache ClearCacheIntervalValue
```

This value tells how often the SDK's inAppMessagesCache mechanism should clear itself. Internally, each notification-messages has a life span. Clearing the inAppMessagesCache stands for deleting notification messages with an expired life span. In other words, only old notification messages are deleted from the inAppMessagesCache. More recent ones are kept in memory until their life span expires and a new clearInAppMessageCache is called. By default, this value is set to Auto. Configuring this value depends how frequently the application will query specific notification messages. In other words, it depends how often you call the API `SMManager.displayMessage(String, Activity)`. In a nutshell: * If the application will never query `SMManager.displayMessage(String, Activity)`, we recommend keeping this value to default. * If the application uses the "In app messages" service, we recommend keeping this value to default. * On the other hand, if the application abuses `SMManager.displayMessage(String, Activity)`, we recommend selecting a value higher than the default one. As soon as IAM-service is enabled, the SDK will consider Week as being the default value. Except if you explicitly override the property. In 99% of the cases, you should not override this property as the SDK is smart enough to handle the inAppMessagesCache mechanism by itself.

Since:

1.3

InAppMessageRefreshType

```
public SMInAppRefreshType InAppMessageRefreshType
```

This is will tell how often the SDK must get the In App messages. Setting this property WILL enable the In App messages in the SDK, even if the value is set to "None". If you do not want to enable the In App messages, leave it to null. If you do not set a value, you can still do it later by calling `SMManager.enableInAppMessages(SMInAppRefreshType)`

Since:

1.3

InAppContentRefreshType

```
public SMInAppRefreshType InAppContentRefreshType
```

This is will tell how often the SDK must get the In App content. Setting this property WILL enable the In App content in the SDK, even if the value is set to "None". If you do not want to enable the In App content, leave it to null.

Since:

1.4

ConfigureGeolocation

```
public boolean ConfigureGeolocation
```

This is will tell the SDK to use the geolocation. Default is false. If you didn't set "enableOnFirstRun" to false in the plotconfig.json file, geolocation will enable right away, asking for the permission if needed, monitoring geofences and displaying notifications. Otherwise, you will need to call `SMManager.enableGeolocation()`. NB: In the plotconfig.json file, if "enableOnFirstRun" or "automaticallyAskLocationPermission" is set to false, you have to ask for the location permission yourself. The default value for these settings is true.

Since:

1.7

RemoteMessageDisplayType

```
public SMRemoteMessageDisplayType RemoteMessageDisplayType
```

If set to Automatic, when the app is active, the remote push messages will automatically be displayed. If set to Notification, the user will have to click on the notification to display them. If set to None, nothing will happen, the app has to manage the display (cf. `SMManager.getLastRemotePushNotification()`, `SMManager.displayLastReceivedRemotePushNotification(android.app.Activity)`) Default value is Automatic.

Since:

1.3

See Also:[SMManager](#)**LoadCacheAsynchronously**

```
public boolean LoadCacheAsynchronously
```

This will make the SDK load the content of its cache asynchronously. It improves performance at startup as reading the files will be done in a separate thread. This has an impact on the management of In-App contents, so if you are already using them and want to set this to true, you might have to review your code (cf. document "Using the SDK" for more information about this). If you don't already use the In-App contents, feel free to set this to true. Default value is false.

Since:

2.1.0

DoNotFetchTheToken

```
public boolean DoNotFetchTheToken
```

If set to true, the SDK will not try to retrieve the token used for push notification from Firebase. Instead, you will be responsible to retrieve it and give it to the SDK by calling the method

`SMManager.setFirebaseToken (java.lang.String)` every time the token changes. Use this if you already have your own way to retrieve the token and do not need the SDK to do it. Default value is false.

Since:

2.1.0

DoNotListenToThePush

```
public boolean DoNotListenToThePush
```

If set to true, the SDK will not listen for the push anymore. Instead, you will be responsible to listen and give it to the SDK by calling the method `SMManager.displayNotification (android.content.Context, android.content.Intent)` every time a push is received. Use this if you already have your own way to listen to the Firebase push and do not want the SDK to do it. Default value is false

Since:

2.1.0

Constructor Detail

SMSMSettings

```
public SMSMSettings()
```

com.selligent.sdk

Enum SMThemeCategories

java.lang.Object
 java.lang.Enum<SMThemeCategories>
 com.selligent.sdk.SMThemeCategories

All Implemented Interfaces:

java.io.Serializable, java.lang.Comparable<SMThemeCategories>

Deprecated.

@Deprecated
public enum **SMThemeCategories**
extends java.lang.Enum<SMThemeCategories>

Since:

1.2

Version:

2.1

Enum Constant Summary

Enum Constants

Enum Constant and Description

AppCompat

Deprecated.

DeviceDefault

Deprecated.

Holo

Deprecated.

Material

Deprecated.

Theme

Deprecated.

Method Summary

All Methods Static Methods Concrete Methods Deprecated Methods

Modifier and Type**Method and Description**

<code>static SMThemeCategories</code>	<code>valueOf(java.lang.String name)</code>
	Deprecated.
	Returns the enum constant of this type with the specified name.
<code>static SMThemeCategories[]</code>	<code>values()</code>
	Deprecated.
	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

`compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf`

Methods inherited from class java.lang.Object

`getClass, notify, notifyAll, wait, wait, wait`

Enum Constant Detail**Theme**

`public static final SMThemeCategories Theme`

Deprecated.

DeviceDefault

`public static final SMThemeCategories DeviceDefault`

Deprecated.

Holo

`public static final SMThemeCategories Holo`

Deprecated.

Material

`public static final SMThemeCategories Material`

Deprecated.

AppCompat

```
public static final SMThemeCategories AppCompat
```

Deprecated.

Method Detail

values

```
public static SMThemeCategories[] values()
```

Deprecated.

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (SMThemeCategories c : SMThemeCategories.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static SMThemeCategories valueOf(java.lang.String name)
```

Deprecated.

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

java.lang.IllegalArgumentException - if this enum type has no constant with the specified name

java.lang.NullPointerException - if the argument is null

Serialized Form

Package com.selligent.sdk

Class *com.selligent.sdk.SMEvent* extends *java.lang.Object* implements *Serializable*

serialVersionUID: 1L

Serialization Methods

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
           java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Throws:

java.io.IOException

java.lang.ClassNotFoundException

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Throws:

java.io.IOException

Class *com.selligent.sdk.SMEventUserLogin* extends *com.selligent.sdk.SMEventUser* implements *Serializable*

serialVersionUID: 1L

Serialization Methods

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
```

```
throws java.io.IOException,  
       java.lang.ClassNotFoundException
```

Throws:

```
java.io.IOException  
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)  
    throws java.io.IOException
```

Throws:

```
java.io.IOException
```

**Class *com.selligent.sdk.SMEventUserLogout* extends *com.selligent.sdk.SMEventUser*
implements Serializable****serialVersionUID:** 1L**Serialization Methods****readExternal**

```
public void readExternal(java.io.ObjectInput serializedObject)  
    throws java.io.IOException,  
           java.lang.ClassNotFoundException
```

Throws:

```
java.io.IOException  
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)  
    throws java.io.IOException
```

Throws:

```
java.io.IOException
```

Class *com.selligent.sdk.SMEventUserRegister* extends *com.selligent.sdk.SMEventUser*

implements Serializable**serialVersionUID:** 1L**Serialization Methods****readExternal**

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Throws:

```
java.io.IOException  
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

Throws:

```
java.io.IOException
```

**Class com.selligent.sdk.SMEventUserUnregister extends com.selligent.sdk.SMEventUser
implements Serializable****serialVersionUID:** 1L**Serialization Methods****readExternal**

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

Throws:

```
java.io.IOException  
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
```

```
throws java.io.IOException
```

Throws:

```
java.io.IOException
```

Class *com.selligent.sdk.SMInAppContent* extends *com.selligent.sdk.BaseMessage* implements *Serializable*

serialVersionUID: 1L

Serialization Methods

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
        java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

```
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

Class *com.selligent.sdk.SMInAppMessage* extends *java.lang.Object* implements *Serializable*

serialVersionUID: 3L

Serialization Methods

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
```

```
throws java.io.IOException,  
       java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Throws:

```
java.io.IOException  
  
java.lang.ClassNotFoundException
```

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)  
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

Class *com.sellgent.sdk.SMLink* extends *SMNotificationButton* implements *Serializable***serialVersionUID: 1L****Serialization Methods****readExternal**

```
public void readExternal(java.io.ObjectInput serializedObject)  
    throws java.io.IOException,  
           java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Throws:

```
java.io.IOException  
  
java.lang.ClassNotFoundException
```

Since:

1.3

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)  
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

Since:

1.3

Class *com.selligent.sdk.SMNotificationButton* extends *java.lang.Object* implements *Serializable*

serialVersionUID: 2L

Serialization Methods

readExternal

```
public void readExternal(java.io.ObjectInput serializedObject)
    throws java.io.IOException,
           java.lang.ClassNotFoundException
```

This method is called when deserializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

```
java.lang.ClassNotFoundException
```

Since:

1.3

writeExternal

```
public void writeExternal(java.io.ObjectOutput serializedObject)
    throws java.io.IOException
```

This method is called when serializing the object. It should not be called manually.

Throws:

```
java.io.IOException
```

Since:

1.3

Constant Field Values

Contents

com.selligent.*

com.selligent.*

Modifier and Type	Constant Field	Value
public static final java.lang.String	BROADCAST_DATA_BUTTON	"SMDaDataButton"
public static final java.lang.String	BROADCAST_DATA_GCM_TOKEN	"SMDaDataGCMToken"
public static final java.lang.String	BROADCAST_DATA_IN_APP_CONTENTS	"SMDaDataInAppContents"
public static final java.lang.String	BROADCAST_DATA_IN_APP_MESSAGES	"SMDaDataInAppMessages"
public static final java.lang.String	BROADCAST_EVENT_BUTTON_CLICKED	"SMEventButtonClicked"
public static final java.lang.String	BROADCAST_EVENT_RECEIVED_GCM_TOKEN	"SMReceivedGCMToken"
public static final java.lang.String	BROADCAST_EVENT_RECEIVED_IN_APP_CONTENTS	"SMReceivedInAppContent"
public static final java.lang.String	BROADCAST_EVENT_RECEIVED_IN_APP_MESSAGE	"SMReceivedInAppMessage"
public static final java.lang.String	BROADCAST_EVENT_RECEIVED_REMOTE_NOTIFICATION	"SMReceivedRemoteNotification"
public static final java.lang.String	BROADCAST_EVENT_WILL_DISMISS_NOTIFICATION	"SMEventWillDismissNotification"
public static final java.lang.String	BROADCAST_EVENT_WILL_DISPLAY_NOTIFICATION	"SMEventWillDisplayNotification"
public static final java.lang.String	VERSION_LIB	"2.1.1"