

# mcfeedback — Iteration 3: Flipped Flagging Signs

experiment-003.mjs · N = 10 seeds · Seeds: 42, 137, 271, 314, 500, 618, 777, 888, 999, 1234 · 1000 training episodes · Frozen-weight evaluation · Random chance = 50%

**Hypothesis:** inverting flagging signs may help the network learn the inversion task.

coActivationStrength ~~+1.0~~ → -1.0

mismatchStrength ~~-0.5~~ → +0.5

coSilenceStrength 0.5 (unchanged)


**Verdict: hypothesis rejected — no jump above chance.**

Full model is locked at 46.0% mean, nearly identical to the original 45.5%. 9 out of 10 seeds hit *exactly* 45%, and variance collapsed to ±3.2% (vs Baseline ±5.9%). Flipping the signs did not unlock learning — it reinforced the same fixed-output attractor. No condition is significantly different from Baseline (all  $p > 0.1$ ). The problem is not sign polarity; the flagging mechanism itself is suppressing specialisation.


Baseline      Ambient only      Dampening only      Full model

## 1 — ACCURACY DISTRIBUTION ACROSS SEEDS

---



## 2 — MEAN $\pm$ 1 STD



### 3 — PAIRED T-TESTS VS BASELINE


Comparison	Mean diff	t	p	Result
Ambient only vs Baseline	-1.5%	-0.3869	0.5223	ns
Dampening only vs Baseline	-2.0%	-1.3093	0.1645	ns
Full model vs Baseline	-1.5%	-0.6690	0.3840	ns

Two-tailed paired t-test, df=9. \*\* p<0.01 \* p<0.05 ns = not significant.

### 4 — RAW DATA (ALL SEEDS)

Seed	Baseline	Ambient	Dampening	Full
42	55%	35%	45%	45%
137	55%	45%	55%	45%
271	40%	45%	40%	45%
314	45%	35%	45%	45%
500	40%	55%	45%	45%
618	45%	35%	45%	45%
777	45%	45%	45%	55%
888	50%	65%	45%	45%
999	45%	55%	45%	45%
1234	55%	45%	45%	45%
<b>Mean</b>	<b>47.5%</b>	<b>46.0%</b>	<b>45.5%</b>	<b>46.0%</b>
Std	±5.9%	±9.9%	±3.7%	±3.2%

### 5 — PER-PATTERN ACCURACY (MEAN ACROSS SEEDS)



#### What the per-pattern data shows:

Full model (54/44/38/48%) is the *flattest* condition — closer to uniform than any other. This is consistent with the flags actively suppressing the weight differentiation needed to distinguish patterns. Baseline retains strong asymmetry (64/34/62/30%), showing the underlying reward signal does carry some information; the flags are erasing it.

#### Context vs previous runs:

Original multi-seed (positive flags): Full model mean = 45.5%, std =  $\pm 5.0\%$

This run (flipped flags): Full model mean = 46.0%, std =  $\pm 3.2\%$

The flip made no meaningful difference in mean accuracy, and further collapsed variance — the network is *more* deterministically stuck, not less. Next diagnostic: ablate flags entirely from Full model to confirm they are the culprit.

