




Date	Rev.	Description



P.C. MOUNTING



Schematic



Model No.	Switching Position	
T100	ON	OFF

SPECIFICATIONS:

CONTACT RATING : 5 AMPS @ 120 V AC or 28 V DC.
 2 AMPS @ 250 V AC or 0.4VA AMPS @20 V AC or DC.
 ELECTRICAL LIFE : 50,000 make-and-break cycles at full load.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
 100 mA, for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min.
 DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERATURE : -30 °C to 130 °C



MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
 ACTUATOR : Brass, chrome plated.
 BUSHING : Brass, nickel plated.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Brass, with silver or gold plated.
 or gold over silver.
 SWITCH SUPPORT : Brass, tin plated.


DCC. NO.
A4 DRAWING NO.

MATERIAL		GOldsun Electronics Co., Ltd.			
		JAMECO NO.	GOLDSUN NO. T100T1B4A2		
DRAWN: Ivan Wang		Description TOGGLE SWITCH, SPST, ON-OFF. PCB MOUNT, 5A/120V, 2 PIN			Rev. 1
VERIFY PEOPLE: Jenny		UNIT: mm	SCALE:	SHEET 1 OF 1	CAS No: ERN No:

Date	Rev.	Description



P.C. MOUNTING



Schematic



Model No.	Switching Position	
T100	ON	OFF

SPECIFICATIONS:

CONTACT RATING : 5 AMPS @ 120 V AC or 28 V DC.
2 AMPS @ 250 V AC or 0.4VA AMPS @20 V AC or DC.
ELECTRICAL LIFE : 50,000 make-and-break cycles at full load.
CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 V DC.
100 mA, for both silver and gold plated contacts.
INSULATION RESISTANCE : 1,000 MΩ min.
DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
OPERATING TEMPERATURE : -30 °C to 130 °C

MATERIALS:

CASE : Diallyl phthalate (DAP)(UL-94V-0).
ACTUATOR : Brass, chrome plated.
BUSHING : Brass, nickel plated.
HOUSING : Stainless steel.
TERMINAL/CONTACT : Brass, with silver or gold plated.
or gold over silver.
SWITCH SUPPORT : Brass, tin plated.

DCC. NO.
A4 DRAWING NO.

MATERIAL		GOLDSUN ELECTRONICS CO., LTD.		
		JAMECO NO.	GOLDSUN NO. T100T1B4A2	
DRAWN: Ivan Wang		Description TOGGLE SWITCH, SPST, ON-OFF. PCB MOUNT, 5A/120V, 2 PIN		Rev. 1
VERIFY PEOPLE: Jenny		UNIT: mm	SCALE:	CAS No: ERN No:
		SHEET 1 OF 1		