

DOWNHOLE WELL STATUS						3-1/2" SINGLE WATER INJECTOR						RIG : GW-303		WELL : SY-146								
RTKB :	315.71	WZL LS :	-	GL :	292.81	CASING , CEMENT & TUBING DATA																
THS :	296.11	WZL SS :	-	13-3/8" CHH :	294.11																	
TD :	8110'	TVD :	4369'	PBDT :	NIL																	
P/U WT :	39 klbs	S/O WT :	32 klbs	BRINE WT :	8.7 ppb																	
WELLHEAD DATA																						
DESCRIPTION	MAKER	SIZE & PRESSURE		TYPE		13-3/8"	68	L-80	BTC	31	205'	CEMENT			SACKS			RTNS	TOP JOBS			
				WEIGHT (LBS)	GRADE							CONN	JOINTS	DEPTH MD (FT)	L	T	STG			L	T	STG
9-5/8"	47	L-80	TSB																			
7"	29	L-80	TPCQ																			
7" TOL																						
3-1/2"	9.2	L-80	TSH BLUE	154	4797.62																	
13-3/8" X 4-1/16" X 5000 PSI	CIW			FLS																		
4-1/16" X 5000 PSI	CIW			FLS																		
10" X 4-1/2" VAM TOP X 5000 PSI	CIW			DCD																		
13-5/8" - 3000 PSI X 11" - 5000 PSI	CIW			DCD																		
13-5/8" X 9-5/8" VAM TOP BTM X ACME	BH																					
13-3/8" X 13-5/8" - 3000 PSI	BH																					

ITEM	DESCRIPTION	ID	OD	LENGTH	MD	
	ELEVATION			19.60	-1.50	
1	TUBING HANGER 10" X 4-1/2" (PN: 2235431-11-02 SN: 121719845003)	3.900	10.860	1.13	18.10	
2	4-1/2" 9.2PPF L-80 VAM TOP PIN X 3-1/2" 9.2PPF L-80 VAM TOP PIN X-OVER	2.992	4.535	2.48	19.23	
3	3.5" 9.2PPF L80 VAM TOP BOX X TSH BLUE PIN XOVER	2.992	3.920	4.83	21.71	
4	3-1/2" TUBING 9.20 LB/FTL-80 TSH BLUE BOX X PIN	2.969	3.940	152.58	26.54	
5	3-1/2" 9.2PPF L-80 TSH BLUE BOX X VAM TOP PIN XOVER	2.992	3.945	9.90	179.12	
6	3.5" 9.2PPF L80 VAM TOP FLOW COUPLING (PN: 104718028 SN: A07642-1A-ADN SN:41 SAP ID# 130010035746)	2.992	3.932	5.75	189.02	
7	NIPPLE,LNDG,3-1/2,2.281,CPX,L80,VTP (PN: 104455627 SN: A07708-1A-ADN SN:01 SAP ID# 130010037108) INJECTION VALVE: (PN: 104446787 / SN:C255-0655 / SAP ID: 130010037974) LOCK MANDREL: (PN:104632973 / SN:A07458-2A-ADN / SAP ID: 130010036730)	2.813	3.878	1.19	194.77	
8	3.5" 9.2PPF L80 VAM TOP FLOW COUPLING (PN: 104718028 SN: A07642-1A-ADN SN:33 SAP ID# 130010035746)	2.992	3.933	5.75	195.96	
9	3.5" 9.2PPF L80 VAM TOP BOX X TSH BLUE PIN XOVER	2.992	3.924	4.87	201.71	
10	3-1/2" TUBING 9.20 LB/FTL-80 TSH BLUE BOX X PIN	2.969	3.940	3751.38	206.58	
11	3-1/2" 9.2PPF L-80 TSH BLUE BOX X VAM TOP PIN XOVER	2.992	3.950	4.93	3957.96	
12	7 X 3-1/2 BLUEPACK MAX RH (26-32), 41XX (80), HNBR (90-90-90), 3-1/2 (9.2) VAM TOP, QCP-103667240, 2FT CTR LENGTH, APIMONOGRAMMED (PN: 104606301 SN: C24P-329 SAP ID# 130010037847)	@+/-47°	2.940	5.915	7.35	3962.89
13	3-1/2" 9.2PPF PUP JOINT L-80 VAM TOP BOX X PIN	2.992	3.930	10.29	3970.24	
14	3-1/2" 9.2PPF PUP JOINT L-80 VAM TOP BOX X PIN	2.992	3.920	10.30	3980.53	
15	NIPPLE,LNDG,3-1/2,2.75,CPXN,L80,VTP , 2.635 NOGO (PN: 104454817 SN: A07889-2A-ADN-SN-3 SAP ID# 130010037093)	@+/-48°	2.635	3.875	1.24	3990.83
16	3.5" 9.2PPF L80 VAM TOP BOX X TSH BLUE PIN XOVER	2.992	3.925	4.88	3992.07	
17	3-1/2" TUBING 9.20 LB/FTL-80 TSH BLUE BOX X PIN	2.969	3.940	793.50	3996.95	
18	3-1/2" 9.2PPF L80 TSH BLUE BOX X VAM TOP PIN XOVER	2.992	3.940	4.92	4790.45	
18	SELF INDEXING MULE SHOE,3-1/2,L80,VTP (PN: 104674548 SN: PRX-PO-23117469-042 SAP ID# 130010036327)	2.992	3.815	2.25	4795.37	
				EOT	4797.62	

PREVIOUS PACKER DEPTH: 3901'

7" TOL @3761' MD

9-5/8" SHOE @4315' MD

7" L. SHOE @ 5102' MD

2-3/4" CHANNEL
6881.4FT TO
6926.4FT MD

2-3/4" CHANNEL
6990 FT TO
7035 FT MD

6" H. HOLE, TD @ 8110' MD/
4375.5' TVD

DE:

3-1/2" SINGLE WATER INJECTOR

COMPLETION CODE WI307/L80SE20

NOTE : ALL ITEMS ARE CARBON STEEL MATERIAL

REVISION : FINAL

DATE : 10-Jul-25

COMPLETION ENGINEER: MUHAMMAD NAVEED

DRILLING SUPERVISOR : MUHAMMAD ALI RADWAN