

Data structures and algorithms  
(2018/19)  
Written exam 23. prosinca 2019

This written exam must be taken individually. Any and all literature may be used while taking this test. In your answers be precise, and: (i) answer the questions *as they were asked*; and (ii) answer *all* tasks – if you will be answering to all tasks you might get bonus points.

Time: 60 minutes.

We wish you a lot of success - veliko uspeha!

NALOGA	TOČK	OD TOČK	NALOGA	TOČK	OD TOČK
1			3		
2			4		

IME IN PRIIMEK: \_\_\_\_\_

ŠTUDENTSKA ŠTEVILKA: \_\_\_\_\_

DATUM: \_\_\_\_\_

PODPIS: \_\_\_\_\_

**1. naloga:** Basics. Let us define the function

```

int FooBar(c, n):
    int p= 2**n
    result= 1
    while (p > 0):
        result= result * c
        p= p-1
    return result

```


**QUESTIONS:**

- A) What is the time complexity of the function `FooBar` in terms of  $n$ ? Justify your answer.
- B) Can you speed up the function `FooBar`? If yes, how and what is the time complexity now, and if not, why not.
- C) Prove that

$$n \ln n = O(n^{3/2})$$

and

$$n \ln n = \Omega(n^{1/2}) .$$

**2. naloga:** Peter Puzzle found a small paper where a tree as in Figure 1 was drawn.

**Slika 1:** Search tree.

## QUESTIONS:

- A) (i.) Is the tree an AVL tree? Justify your answer. (ii.) Can you colour it so that it becomes a red-black tree? Justify your answer. (iii.) Augment the picture of a tree by adding to each vertex the information about the number of elements in the subtree of that vertex including the vertex itself.
- B) We define the function  $\text{RangeNum}(a, b)$ , which returns the number of elements in a tree that are contained in the interval  $[a, b]$ , including  $a$  and  $b$ .
- (i.) What does the function  $\text{RangeNum}(18, 45)$  return on the tree from Figure 1?

(ii.) The augmented tree has the following definition of a node:

```
node:
  int root
  int num
  subtree left, right
```

Using this definition write a (pseudo)code of the function  $\text{RangeNum}(a, b)$ .

- C) What is the time and space complexity of your function, if there are  $n$  elements in a tree and  $k$  of them lie in the interval  $[a, b]$ ? Justify your answer.

**3. naloga: Tries.**

## QUESTIONS:

- A) For a (PATRICIA) tree it holds that paths are compressed by height, that is, each node has always two successors, if the alphabet is  $\Sigma = \{0, 1\}$ . Show that a Patricia tree with  $n$  elements has precisely  $n - 1$  internal nodes.
- B) We have a Patricia tree, where we always add elements at leaves<sup>1</sup>. In such a tree insert the following elements and draw the corresponding tree after each insertion: 01010011, 0000101 and 10101.

HINT: When drawing do not forget that internal nodes have additional information. Which one?

- C) Suppose that we have now a ternary alphabet  $\Sigma = \{0, 1, X\}$  and  $n$  elements. What is the greatest possible height of a Patricia tree and what the smallest possible? Justify your answer.

---

<sup>1</sup>Indices of letters used in internal nodes do not necessary decrease from the root.

**4. naloga:** Graph algorithms and dynamic programming.

## QUESTIONS:

- A) Throughout our lectures, we have described different spanning trees. Draw a graph that has different minimum spanning tree and spanning tree of shortest paths from some vertex to all other vertices.
- B) Represent the drawn graph with the incidence matrix and the adjacency matrix.
- C) Shortest paths between a pair of vertices can be found by dynamic programming (Floyd-Warshall algorithm). It is defined by the following formula:

$$\delta_{i,j}^{(n)} = \begin{cases} w_{i,j} & \text{if } n = 0 \\ \min(\delta_{i,j}^{(n-1)}, \delta_{i,n}^{(n-1)} + \delta_{n,j}^{(n-1)}) & \text{otherwise} \end{cases},$$

where  $w_{i,j}$  is the cost of the edge  $(v_i, v_j)$  and  $\delta_{i,j}^{(m)}$  is the weight of a shortest path  $v_i \rightsquigarrow v_j$  such that for all intermediate vertices  $v_k$  on the path (excluding initial and terminal vertex) we have  $k \leq m$ . (i.) Write down an algorithm by using this recursive definition and use memoization. (ii.) What is the time and space complexity of your algorithm? Justify your answer.