Provide_Services

AirlineCode	AirportCode	AirlineName	Owner	FleetSize	Address	NoOfDestinations	HeadOfficeEmail	WebsiteURL	CommencementYear	AirportName	City	Country	EstablishedYear

FD1

FD2

After Normalising to 2NF

Provide_Services_Airline

| AirlineCode	AirlineName	Owner	FleetSize	Address	NoOfDestinations	HeadOfficeEmail	WebsiteURL	CommencementYear

FD1

The newly created **Provide_Services_Airline** does not have composite or multivalued attributes and is not consisted of nested relations.
Therefore the table **Provide_Services_Aitline** is in 1NF.
The table **Provide_Services_Airlines** is not consisted of partial dependencies.
Therefore the table **Provide_Services_Airlines** is in 2NF.

Provide_Services_Airport

| AirportCode	AirportName	City	Country	EstablishedYear

The newly created **Provide_Services_Airport** does not have composite or multivalued attributes and is not consisted of nested relations.
Therefore the table **Provide_Services_Aitport** is in 1NF.
The table **Provide_Services_Airport** is not consisted of partial dependencies.
Therefore the table **Provide_Services_Airport** is in 2NF.

Airline_Contact_No

AirlineCode	ContactNo

FD1

The table **Airline_Contact_No** has non primary key attributes.
It's already in 2NF

Aircrew_Contact_No

StaffID	ContactNo

FD1

The table **Aircrew_Contact_No** has non primary key attributes.
It's already in 2NF

Passenger_Contact_No

PassportNo	ContactNo

FD1

The table **Passenger_Contact_No** has non primary key attributes.
It's already in 2NF

Landing

FlightNo	AirportName

FD1

The table **Landing** has non primary key attributes.
It's already in 2NF

Take_Off

FlightNo	AirportName

FD1

The table **Tale_Off** has non primary key attributes.
It's already in 2NF