AI-Based Adaptive VR Meditation System

RL-Based Personalized Adaptive Virtual Environment Generation and Optimization Module

R26-DS-006

Project Proposal Report

Perera W.T.S.R – IT22231314

B.Sc. (Hons) Degree in Information Technology Specialized in Data Science

Department of Computer Science

Sri Lanka Institute of Information Technology Sri Lanka

March 2026

DECLARATION FORM

DECLARATION

I declare that this is my own work, and this proposal does not knowingly incorporate any material previously submitted for a degree or diploma at any other university or higher education institution, nor does it contain any material that has been previously published or written by another person apart from where proper acknowledgment is given in the text.

Name	Student ID	Signature
Perera W.T.S.R	IT22231314	

The above candidate is conducting research for their undergraduate Dissertation under my supervision.

Name	Date	Signature
Mr. Samadhi Rathnayake	19/03/2026	

ABSTRACT

Personalized adaptive relaxation environments are crucial for achieving successful stress reduction. Most existing VR applications for relaxation have pre-determined, static scenes and/or allow for user-selected types of scenes without considering the types of scenes that different users will find relaxing. There is no literature examining the gap in the marketplace for an adaptive VR application that utilizes an individual user's continuous physiological feedback to continuously adapt the combination of lighting, sound, weather, and type of scene to create the optimal experience for each user.

To address this gap, we have created a prototype of a VR relaxation system that uses real-time physiological data (i.e., heart rate and skin conductance) to determine each user's unique preferences and to modify the amount of lighting, sound, weather, and scene type in response to the individual user's physiological state in order to provide the optimal experience for each user by learning from each user's preferences based on repeated exposure.

The expected outcomes of this project are the development of a prototype system and the collection of empirical data supporting the proposition that the use of adaptive VR technology will provide a greater reduction in stress than the use of non-adaptive VR technology. Additionally, the project will contribute to the definition of the RL state-action-reward framework (pluralistic model of user preference), provide empirical evidence of the practical limitations of adaptive VR technology (e.g., sensor noise and difficulty in developing rewards), and support the achievement of the UN Sustainable Development Goal 3 (to ensure healthy lives and promote well-being for all). This project has the potential to be commercially viable in the growing VR/AR (augmented reality) wellness industry.

Keywords: Virtual Reality, Stress Relief, Personalized Adaptive Systems, Reinforcement Learning, Physiological Feedback

ACKNOWLEDGEMENT

I would like to express my sincere appreciation towards my supervisor Mr. Samadhi Rathnayake, co-supervisor Ms. Malithi Nawarathne, for providing me with guidance in the development of this research proposal. Furthermore, I would like to thank my teammates Praveen Perera, Sarindu Samarasekara, and Prathikesh Senthilkumaran, for the support provided on this project. This work has been supported by the Department of Computer Science at Sri Lanka Institute of Information Technology, and I would also like to acknowledge the support of my family and friends throughout this process.

TABLE OF CONTENT

DECLARATION FORM 2

ABSTRACT 3

ACKNOWLEDGEMENT 4

TABLE OF CONTENT 5

LIST OF TABLES 6

LIST OF FIGURES 7

LIST OF ABBREVIATIONS 8

LIST OF APPENDICES 9

1. INTRODUCTION 10

1.1 BACKGROUND AND CONTEXT 10

1.2 LITERATURE REVIEW - HANDLING PLURALISTIC AND DIVERGENT PREFERENCES IN RL-DRIVEN ADAPTIVE VR 11

1.3 RESEARCH GAP 12

2. OBJECTIVE 14

2.1 MAIN OBJECTIVE 14

2.2 SPECIFIC OBJECTIVES 14

3. METHODOLOGY 15

4. HIGH-LEVEL SYSTEM ARCHITECTURE 17

4.1 COMPONENT INTERACTIONS 17

4.2 DATA FLOW EXPLANATION 18

4.2.1 OVERVIEW 18

4.2.2 HIGH-LEVEL DATA FLOW 19

4.3 SCALABILITY AND SECURITY CONSIDERATIONS 20

4.3.1 SCALABILITY CONSIDERATIONS 20

4.3.2 SECURITY CONSIDERATIONS 20

5. USER REQUIREMENTS 22

5.1 STAKEHOLDER IDENTIFICATION 22

5.1.1 PRIMARY STAKEHOLDERS 22

5.1.2 SECONDARY STAKEHOLDERS 22

5.2 FUNCTIONAL REQUIREMENTS 22

5.3 NON- FUNCTIONAL REQUIREMENTS 23

6. COMMERCIALIZATION PLAN 25

7. BUDGET AND JUSTIFICATION 27
7.1 OVERVIEW 27
7.2 HARDWARE COSTS 27
7.3 SOFTWARE COSTS 27
7.5 HUMAN EFFORT COST 28
7.6 BUDGET SUMMARY 28
7.7 OVERALL BUDGET JUSTIFICATION 28
8. WORK BREAKDOWN STRUCTURE (WBS) 30
8.1 OVERVIEW 30
8.2 TASK BREAKDOWN 30
9. GANTT CHART 31
10. REFERENCES LIST 32
11. APPENDICES 33
APPENDIX A – SYSTEM ARCHITECTURE DIAGRAM 33
APPENDIX B – DATA FLOW DIAGRAM 33
APPENDIX C – ADAPTATION LOGIC AND REINFORCEMENT LEARNING MODEL 33
APPENDIX D – GENAI ASSET PROMPTS 33
APPENDIX E – KEY IMPLEMENTATION SNIPPETS 33
APPENDIX F – TEST CASES AND RESULT 34
APPENDIX G – GANTT CHART 34

LIST OF TABLES

Table 1: COMMERCIALIZATION PLAN 25
Table 2: HARDWARE COSTS TABLE 27
Table 3: SOFTWARE COSTS TABLE 27
Table 4: HUMAN EFFORT COSTS TABLE 28
Table 5: BUDGET SUMMARY TABLE 28

LIST OF FIGURES

Figure 1: HIGH-LEVEL SYSTEM ARCHITECTURE DIAGRAM 17
Figure 2: COMPONENT HIGH-LEVEL ARCHITECTURE DIAGRAM 17
Figure 3: COMPONENT HIGH-LEVEL DATA FLOW DIAGRAM 19
Figure 4: GANTT CHART 31

LIST OF ABBREVIATIONS

Abbreviation	Full Form
VR	Virtual Reality
AR	Augmented Reality
XR	Extended Reality
AI	Artificial Intelligence
ML	Machine Learning
RL	Reinforcement Learning
GenAI	Generative Artificial Intelligence
HRV	Heart Rate Variability
BPM	Beats Per Minute
UI	User Interface
UX	User Experience
SDK	Software Development Kit
API	Application Programming Interface
JSON	JavaScript Object Notation
FPS	Frames Per Second
GPU	Graphics Processing Unit
CPU	Central Processing Unit
LOD	Level of Detail
DFD	Data Flow Diagram
URP	Universal Render Pipeline (Unity)
XR Toolkit	Extended Reality Interaction Toolkit
OpenXR	Open Standard for VR/AR Runtime
APK	Android Package Kit
HTTP	Hypertext Transfer Protocol
HTTPS	Hypertext Transfer Protocol Secure

LIST OF APPENDICES

APPENDIX A – SYSTEM ARCHITECTURE DIAGRAM 33
APPENDIX B – DATA FLOW DIAGRAM 33
APPENDIX C – ADAPTATION LOGIC AND REINFORCEMENT LEARNING MODEL 33
APPENDIX D – GENAI ASSET PROMPTS 33
APPENDIX E – KEY IMPLEMENTATION SNIPPETS 33
APPENDIX F – TEST CASES AND RESULT 34
APPENDIX G – GANTT CHART 34

1. INTRODUCTION

1.1 BACKGROUND AND CONTEXT

The Therapeutic Potential of Virtual Reality Virtual reality (VR) utilizes computer-generated simulations and head-mounted displays to replace physical world sensory inputs, creating a profound sense of psychological immersion and physical presence. As technology has matured, its applications have expanded significantly beyond entertainment and training into clinical and therapeutic domains. Specifically, VR has demonstrated a unique capacity to safely and realistically simulate restorative environments, such as nature scenes that can effectively reduce cognitive fatigue, lower anxiety, and promote mental relaxation.

The Limitations of Static VR and Cybersickness Despite its therapeutic promise, the efficacy of VR relaxation interventions is frequently bottlenecked by the static nature of traditional applications. Historically, VR systems have relied on standardized, "one-size-fits-all" design paradigms. This static approach is fundamentally limited when applied to subjective states like relaxation, as individuals exhibit diverse learning styles, emotional triggers, and environmental preferences. Furthermore, prolonged exposure to immersive virtual environments often induces cybersickness, a condition characterized by nausea, dizziness, and visual fatigue. Cybersickness not only disrupts the user's sense of presence but also actively induces physiological stress, thereby negating the intended relaxation benefits of the experience. Because individual susceptibility to cybersickness and sensory conflict varies wildly, a static environment cannot maintain an optimal experience for all users.

Closing the Affective Loop with HR and HRV To overcome the limitations of static designs, current research is shifting toward adaptive VR systems capable of dynamically altering the virtual environment in real-time to suit the user's immediate state. Transitioning to adaptive VR requires continuous, objective measurements of the user's condition rather than relying solely on subjective post-exposure questionnaires. Multimodal bio signals, specifically Heart Rate (HR) and Heart Rate Variability (HRV), serve as vital, real-time indicators of a user's autonomic nervous system activity, effectively quantifying their current levels of cognitive load, stress, and emotional arousal. By utilizing continuous HR and HRV feedback, systems can establish an "affective loop", a closed-loop mechanism where the VR environment actively monitors and responds to physiological shifts to mitigate discomfort and enhance relaxation.

Reinforcement Learning and the Gap of Pluralistic Preferences Reinforcement Learning (RL) provides the necessary algorithmic framework to drive these adaptive environments, allowing intelligent agents to autonomously discover and execute optimal environmental modifications based on continuous physiological feedback. However, implementing RL for personalized relaxation reveals a critical research gap: **Handling Pluralistic and Divergent Preferences.**

Current Reinforcement Learning from Human Feedback (RLHF) techniques predominantly operate under a unimodal assumption, meaning they attempt to learn a single, universal reward model that averages out the preferences of all users. Because relaxation is a highly subjective

experience, user preferences are inherently pluralistic and divergent; an AI-generated environment configuration that relaxes one user may cause cognitive overload or cybersickness in another. Standard RL models fail to reconcile these conflicting values, resulting in mis specified reward models that generate homogeneous, suboptimal environments. Therefore, developing advanced RL frameworks capable of modeling latent, individualized contexts to optimize AI-generated VR parameters for diverse user preferences remains a vital challenge in maximizing true, personalized relaxation.

1.2 LITERATURE REVIEW - HANDLING PLURALISTIC AND DIVERGENT PREFERENCES IN RL-DRIVEN ADAPTIVE VR

The integration of Reinforcement Learning (RL) and Virtual Reality (VR) allows for the creation of dynamically adaptive environments that respond to user states in real-time[1]. However, individuals exhibit highly subjective and diverse responses to virtual stimuli, making personalization a critical challenge in maximizing user relaxation and comfort[2], [3]. To effectively "close the affective loop" and handle these pluralistic preferences, modern RL-driven VR systems increasingly rely on physiological bio signals, particularly Heart Rate (HR) and Heart Rate Variability (HRV), to objectively quantify user states and guide environmental adaptation[4], [5].

The Limitation of Unimodal Assumptions in Preference Modeling Traditional Reinforcement Learning from Human Feedback (RLHF) methodologies typically utilize the Bradley-Terry-Luce (BTL) model, which operates under a "unimodal" assumption[6]. This assumption posits that all human preferences can be derived from a single, shared utility function, effectively mode-averaging divergent preferences across a population[6]. When applied to relaxation in VR, this approach is fundamentally flawed because an environment that is calming to one user might be overstimulating to another[6]. Consequently, standard RLHF produces inaccurate reward models that ignore minority groups and fail to adequately personalize the VR experience for users with divergent needs[6].

Pluralistic Alignment through Variational Preference Learning (VPL) To handle pluralistic and divergent preferences, recent literature proposes moving towards latent-variable formulations such as Variational Preference Learning (VPL)[6]. VPL explicitly accounts for the inherent plurality of human values by inferring a user-specific hidden context from a small set of preference annotations[6]. By utilizing a variational encoder alongside a latent-conditional reward model, VPL accurately recovers true multi-modal preference distributions[6]. This enables the RL policy to steer and personalize the generated environment to the specific user, ensuring that the system can account for and serve the unique relaxation profiles of different individuals without requiring extensive new data[6].

Leveraging HR and HRV as Objective Reward Signals Capturing these divergent preferences during active VR sessions requires reliable physiological inputs. HR and HRV are essential bio signals that reflect the activity of the Autonomic Nervous System (ANS), providing objective, real-time indicators of a user's stress, cognitive load, emotional arousal,

and recovery[4], [5]. In adaptive VR systems, integrating HRV and HR allows the RL agent to continuously monitor the user's affective state and accurately assess whether the current environment is inducing relaxation or stress[5], [7]. For instance, machine learning classifiers like Support Vector Machines (SVM), K-Nearest Neighbors (KNN), and Random Forests (RF) have been successfully employed to predict multi-class emotional states utilizing HR signals during VR exposure[8]. Using these bio signals, the RL agent's reward function can be dynamically shaped to maximize positive emotional engagement and physiological relaxation[7].

Experience-Driven RL and Multi-Objective Balancing Experience-Driven Reinforcement Learning (EDRL) represents a promising framework that uses RL to autonomously search for and generate content tailored to specific affective patterns[2]. By utilizing HR and HRV data, EDRL agents can evaluate the affective impact of generated VR elements and adjust parameters to match a user's unique relaxation profile[2]. Furthermore, because prolonged VR exposure can induce cybersickness, which disrupts relaxation and manifests in autonomic changes detectable via HRV, adaptive RL systems must perform multi-objective optimization[7], [9]. RL models utilize real-time HRV data to dynamically balance the enhancement of immersion with the mitigation of sensory conflicts, altering the environment proactively to maintain user comfort[3], [9].

Conclusion Overcoming the limitations of static or unimodal VR environments requires a synergy between advanced RL techniques and robust physiological monitoring[1], [7]. By adopting latent-variable models like VPL to understand divergent preferences and utilizing HR and HRV to provide continuous, objective feedback, RL-driven adaptive VR can deliver truly personalized, restorative experiences that accommodate the individual differences of every user[6], [7].

1.3 RESEARCH GAP

1. Overcoming the Unimodal Assumption in Real-Time Physiological Adaptation While Heart Rate (HR) and Heart Rate Variability (HRV) offer objective, real-time metrics for assessing cognitive load and emotional states, current adaptive VR systems predominantly rely on fixed logic trees or rule-based adaptations derived from aggregate trends[1], [3]. These approaches fail to account for individual variability in physiological baselines and subjective relaxation triggers[3]. Consequently, Experience-Driven RL agents often struggle to reliably elicit targeted affective states across distinct, diverse user profiles (e.g., low-aroused beginners versus experts)[2]. A critical research gap lies in successfully integrating pluralistic, latent-variable models (such as Variational Preference Learning) with continuous HR/HRV feedback to dynamically generate individualized reward structures that do not rely on a "one-size-fits-all" baseline.

2. Mitigating the "Cold Start" Problem and Adaptation Latency When a novice user first interacts with an RL-driven VR environment, the agent faces an "initial cold start" problem, requiring a period of trial-and-error experimentation to establish a personalized policy[1].

Because the agent lacks prior knowledge of the individual's unique HR/HRV relaxation patterns, this exploratory phase risks applying incorrect environmental parameters that could induce stress or frustration rather than relaxation[1]. Furthermore, processing continuous, high-dimensional physiological data to drive generative AI environment changes introduces adaptation latency, the delay between a physiological trigger and the system's corresponding visual or auditory response[3], [7]. Minimizing this latency is essential, as delays can disrupt the "affective loop," break the user's sense of presence, and ultimately hinder the relaxation process.

3. Disentangling Bio signal Confounders in Multi-Objective Optimization Maximizing user relaxation in VR is inherently tied to user comfort, yet prolonged exposure or dynamic environmental changes can induce cybersickness, which significantly alters autonomic nervous system markers like HR and HRV. Research indicates that users constantly navigate a complex, dynamic interplay between curiosity-driven exploration and the onset of discomfort or cybersickness. A major algorithmic gap is the development of multi-objective reward functions that can accurately untangle shifts in HRV caused by genuine relaxation and engagement from the physiological stress signals of early onset cybersickness. Without this distinction, the RL agent may misinterpret the bio signals and alter the AI-generated environment in ways that inadvertently exacerbate sensory conflict.

4. Addressing Domain Bias and Contextual Data Sparsity Existing emotion and preference models utilized in VR are frequently trained on narrow datasets (e.g., single virtual environments), which restricts the agent's exposure to diverse contextual data and limits its ability to assess new content accurately[2]. Moreover, these underlying models often lack a complete representation of emotional diversity and relaxation preferences across different cultures[1]. This introduces a significant domain bias, meaning an RL agent optimized for one specific demographic may fail to generalize its environmental adaptations (e.g., lighting, acoustic frequencies, visual complexity) to users from differing sociocultural backgrounds[7]. Scaling these personalized RL frameworks to robustly handle cross-cultural pluralistic preferences without demographic bias remains heavily underexplored.

2. OBJECTIVE

2.1 MAIN OBJECTIVE

The goal is to create an RL-based virtual reality relaxation system which adapts virtual environment settings according to physiological data to assess its effectiveness in reducing stress compared to standard non-adaptive systems.

2.2 SPECIFIC OBJECTIVES

1. **Identify Effective VR Parameters:** Determine which modifiable VR parameters (e.g., scene type, lighting, ambient sound) plausibly influence relaxation and specify their ranges for adaptation.
2. **State Representation and Feedback Integration:** Develop a model that maps real-time physiological signals (HR, HRV) to a discrete or continuous stress/relaxation state used by the RL agent.
3. **RL Formulation:** Define the RL problem: states, actions (environment adjustments), and a reward function reflecting relaxation (e.g. decrease in physiological arousal). Choose appropriate algorithms (e.g. Q-learning, contextual bandit).
4. **Personalization Mechanism:** Implement the RL agent to learn user-specific environment-preference mappings over one or more sessions and enable policy updates as more data are collected.
5. **Evaluation:** Conduct a user study comparing the adaptive system against a static-VR baseline. Measure outcomes with physiological metrics (HR, HRV) and subjective stress/anxiety ratings.
6. **Comparison of Adaptation Strategies:** Investigate whether simpler methods (contextual bandits or rule-based control) perform comparably to full RL in this setting, given limited data.
7. **Assess Practicality:** Analyze system behavior and limitations, including effects of sensor noise, sample efficiency, and whether RL converges in reasonable time, to guide future research scope.

3. METHODOLOGY

We will follow an **iterative design-science approach**, combining system development with experimental evaluation. Our methodology includes:

- **System Design:** We will build a closed-loop VR relaxation system. Physiological signals (heart rate, HRV, EDA) will be fed into a signal-processing module that classifies stress level. An RL agent will then select VR environment actions to maximize a relaxation reward (e.g. reduction in stress indicators). We will implement this prototype in Unity (VR) and Python (RL logic).

- **RL Framework:** We formulate this as a sequential decision problem. *State:* the user's estimated stress level (discretized low/medium/high or continuous index) plus possibly context features (time of day, session count). *Action space:* adjustments to VR parameters, either as discrete choices (e.g. switch to a preset scene) or incremental changes (increase brightness, change sky). To keep learning tractable, we will limit the action set (e.g. 3–5 actions per parameter) as informed by pilot testing. *Reward:* we will define reward as the negative of the change in stress (e.g. reward = stress_before – stress_after, or negative physiological arousal). This encourages actions that lower stress. We will experiment with reward smoothing or penalties for abrupt changes. The RL update (e.g. Q-learning or contextual bandit) will occur after each action based on subsequent physiological feedback.

- **Algorithm Selection:** Due to the likely small data regime, we will start with a simple RL or bandit algorithm. A tabular Q-learning (with discretized states) or a contextual multi-armed bandit (one-step adaptation using context) may suffice. If preliminary trials suggest complexity, we may implement a small deep Q-network (DQN). However, we must remain realistic: heavy deep RL is unlikely to converge on a 10-month project with few participants. Thus, we explicitly plan to compare simpler models (contextual bandit, ε-greedy selection) as baselines and only use full RL if needed. We will justify whichever approach is chosen based on performance and feasibility.

- **Data Acquisition:** We will use off-the-shelf physiological sensors (e.g. commercial heart-rate strap) to stream HR and EDA. These are treated as external inputs – hardware construction is beyond scope. We will process signals in real time: bandpass filtering, beat detection, HRV (time-domain) computation over sliding windows, and skin conductance level for EDA. Noise and artifacts will be managed by robust filtering. Our stress estimator might be a threshold or simple regression calibrated in a short baseline session.

- **Environment Adaptation:** The VR environment will include several predefined scenes (e.g. forest, beach, mountain). We will define adjustable parameters for each (light intensity/color, background audio volume/type, weather effect toggles). The RL agent will output parameter changes which Unity will apply between adaptation steps (e.g. every 30 seconds). We will ensure changes are gradual to avoid jarring transitions.

- **Experiment and Evaluation:** We will recruit 8–12 participants for a within-subject study. Each participant will experience both the **adaptive VR** (RL agent active) and a **static VR** condition (random or fixed environment, no adaptation), in counterbalanced order. Each session (~10 min) will include a mild stress induction (e.g. mental arithmetic task) followed by VR relaxation. We will record physiological data and subjective stress/anxiety (e.g. using SUDS or STAI) before and after. Primary metrics: reduction in heart rate and skin conductance, change in HRV, and self-reported relaxation. We will statistically compare adaptive vs static (paired t-test or non-parametric test) to test for significant improvement.

- **Validation:** Beyond the main test, we will analyze the learned policies to understand what the agent did. For example, did it learn different strategies for different users? We will also conduct ablation: e.g. disable learning to see if just random adaptation has effect. Usability feedback will be collected through questionnaires on perceived relaxation and presence. Ethical approval will be obtained; data will be anonymized.

- **Risk Mitigation:** We acknowledge RL may not converge with few samples; if so, we will fall back on simpler heuristics or bandits. Reward mis-specification risk will be mitigated by testing multiple reward formulations (e.g. incorporating subjective feedback). Sensor noise risk is managed by filtering and possibly using median HR over seconds. If real-time adaptation is too slow, we will consider an offline learning approach across sessions.

Overall, the methodology balances ambition (introducing RL adaptation) with realism (using simpler algorithms and rigorous evaluation). We will critically assess whether RL yields tangible benefits over non-learning approaches.

4. HIGH-LEVEL SYSTEM ARCHITECTURE




Figure 1: HIGH-LEVEL SYSTEM ARCHITECTURE DIAGRAM




Figure 2: COMPONENT HIGH-LEVEL ARCHITECTURE DIAGRAM

4.1 COMPONENT INTERACTIONS

This component directly interacts with the stress classification component to receive classified stress information. Also, it directly interacts with the mobile application to receive user preferences. Furthermore, this component interacts with the context-aware adaptive sound module to further enhance the user experience.

4.2 DATA FLOW EXPLANATION

4.2.1 OVERVIEW

The proposed component operates as an adaptive VR environment generation and optimization pipeline, where multiple data sources are integrated to dynamically personalize user experience.

The system processes:

- Stress classifications from the stress prediction module
- User preferences from mobile application

These inputs are used to:

1. Generate an initial VR environment
2. Apply rule-based adaptations (baseline control)
3. Enable a Reinforcement Learning (RL) agent to progressively optimize the environment for user relaxation.

4.2.2 HIGH-LEVEL DATA FLOW




Figure 3: COMPONENT HIGH-LEVEL DATA FLOW DIAGRAM

4.3 SCALABILITY AND SECURITY CONSIDERATIONS

4.3.1 SCALABILITY CONSIDERATIONS

The proposed system is designed with a modular and lightweight architecture, enabling scalability across users, environments, and devices.

System Scalability

The component follows a decoupled pipeline (input → environment generation → adaptation), allowing individual modules (e.g., RL agent, scene generator) to be scaled independently.

The rule-based module ensures baseline functionality, reducing dependency on computationally expensive learning models during initial stages.

User Scalability

The system supports multiple users by maintaining separate user preference profiles and learned RL policies

Personalization is handled at the user level, enabling concurrent sessions without interference.

Content Scalability

New VR environments can be added by extending the asset library (textures, models, skyboxes) without modifying core logic.

The rule-based and RL modules operate on parameterized environments, making them reusable across different scenes.

Computational Scalability

- The system is optimized for mobile VR devices, using:
    - Pre-generated assets
    - Lightweight rule-based adaptation
- RL computation can be:
    - Performed locally (for small-scale use), or
    - Offloaded to cloud services for large-scale deployment

4.3.2 SECURITY CONSIDERATIONS

The system handles user-related and physiological data, requiring appropriate security and privacy measures.

Data Privacy

- User data (stress levels, preferences) should be treated as sensitive personal data.
- Store only minimal required data and avoid unnecessary data retention.

Data Transmission

- Any communication between modules (e.g., mobile app → VR system) should use secure protocols (HTTPS / encrypted channels).
- Prevent interception of physiological data streams.

Data Storage

If cloud storage is used:

- Apply access control mechanisms
- Use authentication and authorization (e.g., Firebase Auth)

Store user profiles in a secure, isolated manner

Model Security

Protect the RL model from:

- Unauthorized modification
- Malicious input manipulation

Validate all incoming inputs (stress values, preferences) to prevent abnormal behavior.

Device-Level Security

Ensure the VR application:

- Runs in a sandboxed environment
- Does not expose system-level vulnerabilities on mobile devices

5. USER REQUIREMENTS

5.1 STAKEHOLDER IDENTIFICATION

The proposed AI-based stress inference component involves several stakeholders who interact with or benefit from the system.

5.1.1 PRIMARY STAKEHOLDERS

1. End Users (Meditation App Users):

These are individuals who use the VR meditation system to monitor and manage their stress levels. They benefit from personalized stress detection and adaptive meditation guidance.

2. Mental Health Practitioners:

Psychologists, therapists, and wellness coaches who may use the system to monitor physiological indicators of stress and recommend appropriate interventions.

3. Researchers and Data Scientists:

Researchers working in affective computing, bioinformatics, and digital health who analyze physiological data and improve stress inference models.

5.1.2 SECONDARY STAKEHOLDERS

1. System Developers / Engineers:

Software developers responsible for implementing the HRV processing pipeline, machine learning models, and cloud infrastructure.

2. Healthcare Institutions and Wellness Platforms:

Organizations that may deploy the system for employee wellness programs or clinical support tools.

3. Device Manufacturers:

Companies who produce wearable sensors (ECG/PPG devices) that provide physiological data to the system.

5.2 FUNCTIONAL REQUIREMENTS

This component needs to execute specific functions according to its functional requirements.

1. The system shall receive processed physiological signals (HRV features derived from ECG or PPG data) from the data acquisition component.

2. The system shall perform HRV feature extraction including metrics such as RMSSD, SDNN, and LF/HF ratio.
3. The system should implement circadian rhythm modeling using Cosinor or similar mathematical rhythmometry techniques.
4. The system will create an ongoing physiological baseline which changes according to the biological rhythms of each user.
5. The system will calculate HRV residual values by measuring actual HRV against established circadian base values.
6. The system will feed HRV data together with time-based residual data to a machine learning classification system.
7. The system will identify 4 different stress levels which include Relaxed, Mild Stress Moderate Stress, High Stress.
8. The system will send the detected stress level to the VR meditation system which will use it to modify the meditation process.
9. The system will maintain an ongoing process of personalized baseline updates whenever new physiological measures are obtained.
10. The system will keep all processed physiological data and predictive results in secure storage within the cloud database so they can be analyzed later.

5.3 NON- FUNCTIONAL REQUIREMENTS

The system's non-functional requirements describe its essential system quality attributes.

1. **Security:**

The system will protect all physiological information by encrypting it during both data transfer and data storage processes. The system will protect user privacy by converting all personal identification information into non-identifiable formats. The system will use authentication methods together with access control systems to protect its resources.

2. **Performance:**

The system will conduct stress inference processes throughout the day while maintaining low system impact during its daily operations. The system will process physiological data streams with minimal latency. The system will provide continuous monitoring capability without creating major system performance demands.

3. **Scalability:**

The system will handle multiple users at the same time because it uses cloud infrastructure. The system architecture allows for simple attachment of new sensors plus additional data sources.

4. **Reliability:**

The system will function continuously with stable performance while it monitors physiological changes. The stress inference model will produce identical results for all users throughout various time intervals.

5. **Usability:**

The system will produce stress level outputs which users can easily understand. The system will function properly because it requires no technical knowledge from its users.

6. **Maintainability:**

The system architecture will permit fast implementation of updates for all machine learning models plus their corresponding algorithms. The system will enable modular system upgrades which will help organizations improve their future stress detection capabilities.

6. COMMERCIALIZATION PLAN

Table 1: COMMERCIALIZATION PLAN

Area	Commercialization Details
Project / Product Name	AI-Based Adaptive VR Meditation System
Commercial Product Concept	A personalized digital wellness platform that combines wearable physiological sensing, AI-driven stress inference, adaptive VR environment control, personalized therapeutic audio, and session validation to deliver more effective meditation and stress-reduction experiences.
Core Market Problem	Existing meditation apps and VR relaxation systems are mostly static, generic, and weakly validated. They do not reliably adapt to the user's real stress state, signal confidence, or changing relaxation preferences.
Overall Value Proposition	Provides a closed-loop therapeutic meditation experience that measures the user's physiology, infers stress in real time, adapts VR and audio intelligently, and validates session effectiveness afterward. This creates a more personalized, safe, and measurable meditation product than standard wellness apps.
Primary Target Customers	1. Individual consumers seeking stress relief and guided meditation 2. Corporate wellness programs 3. Mental health / digital therapeutics providers 4. Hospitals, therapy centers, and rehabilitation clinics 5. Universities and research labs studying stress, VR, and biofeedback
Secondary Target Customers	VR wellness studios, meditation coaches, health-tech startups, insurance-backed preventive wellness programs, and wearable-device ecosystem partners.
Delivery Model	Mobile app + VR headset experience + wearable sensor integration + cloud analytics/dashboard for personalization and reporting.
Business Model	B2C subscription for end users, B2B licensing for clinics and enterprises, and SDK / API licensing for third-party wellness or VR developers.
Revenue Streams	1. Monthly / annual premium subscription 2. Enterprise Wellness Licensing 3. Clinical platform licensing 4. White-label SDK/API licensing 5. Hardware bundle revenue with compatible wearable partners 6. Research / institutional deployment packages
Competitive Advantage	Unlike normal meditation apps, this system combines confidence-aware sensing (A), multi-level stress intelligence (B), RL-driven adaptive VR personalization (C), multilingual voice-based session validation (D), and adaptive therapeutic audio control (E) into one integrated product.
Go-to-Market Strategy	Start with a pilot MVP for universities, wellness centers, and small therapy clinics. Then expand into corporate wellness and consumer subscription markets once the adaptive models and usability are validated.
Pilot Deployment Strategy	Conduct pilot trials with student populations, office workers, and clinic users. Use these pilots to validate user relaxation, immersion, adaptation stability, and session outcome reporting.
Technology Commercialization Strategy	Commercialize the system in layers: first as a full product, then as independent modules that can be licensed separately depending on customer needs.
Component A – Commercial Role	Confidence-Aware RR Sensing Layer. This component can be commercialized as a wearable signal-quality engine / SDK for low-cost wrist-based physiological sensing. It adds value by improving RR reliability and sending confidence-scored cleaned RR streams to

	downstream models. This makes the full system safer and more usable with affordable hardware.
Component B – Commercial Role	Stress Intelligence Engine. This can be commercialized as a real-time physiological stress inference API for wellness apps, VR systems, and biofeedback tools. It converts cleaned RR signals into four-level stress classifications and probability scores.
Component C – Commercial Role	Adaptive VR Personalization Engine. This is the core immersive product layer and can be commercialized as a VR adaptation module / SDK for relaxation and mental wellness applications. It uses RL to personalize environment parameters according to stress level and user preferences.
Component D – Commercial Role	Session Validation and Outcome Analytics Layer. This component can be commercialized as a post-session effectiveness analysis module, especially for clinics, enterprises, and researchers who need measurable evidence of therapeutic benefit. Its multilingual voice-based validation and anomaly detection increases trust and accountability.
Component E – Commercial Role	Personalized Adaptive Therapeutic Audio Engine. This can be commercialized as a generative meditation audio controller / API that adapts sound using stress level and physiological confidence. It is valuable as a standalone audio personalization product or as part of the full VR meditation platform.
Integrated Product Offering	The strongest commercial form is the full-stack adaptive meditation platform, where all five components work together: sensing → stress inference → adaptive VR → adaptive audio → outcome validation.
Standalone Licensing Opportunities	A and B can be licensed to wearable or biofeedback platforms; C can be licensed to VR wellness apps; D can be licensed to clinics and researchers; E can be licensed to meditation, wellness, and immersive-audio platforms.
Customer Benefits	Higher personalization, better stress reduction potential, real-time adaptation, safer control through confidence awareness, measurable session outcomes, multilingual accessibility, and stronger trust than static meditation systems.
Key Partners	Wearable device manufacturers, VR hardware vendors, Unity/Unreal developers, wellness app companies, clinics, universities, corporate HR/wellness providers, and cloud AI infrastructure partners.
Commercial Feasibility	The project is commercially feasible because it is built on a combination of software intelligence + affordable hardware + subscription-ready wellness delivery, which is scalable beyond a research prototype.
Scalability	The product can scale through cloud-hosted analytics, modular APIs, cross-platform mobile integration, and support multiple industries such as wellness, education, therapy, and digital health.
Pricing Approach	Consumer tier: low monthly subscription. Clinical / enterprise tier: higher-seat or annual license pricing. SDK/API tier: usage-based or developer licensing model.
Market Entry Advantage	The system does not compete only as a meditation app; it can also be positioned as a digital therapeutic support system, adaptive relaxation platform, and research-grade biofeedback tool.
Future Expansion Opportunities	Add more languages, more sensors, therapist dashboards, longitudinal mental wellness tracking, personalized session recommendations, and integration with smartwatch ecosystems and telehealth platforms.

7. BUDGET AND JUSTIFICATION

7.1 OVERVIEW

The budget prioritizes affordability, accessibility, and functional adequacy, while leveraging free and open-source technologies wherever possible. It is designed to be feasible for undergraduate-level implementation.

The estimated total implementation cost ranges between LKR 35,000 – 85,000.

7.2 HARDWARE COSTS

Table 2: HARDWARE COSTS TABLE

Item	**Description**	**Estimated Cost (LKR)**
VR Headset	Samsung Gear VR (used) or equivalent mobile VR headset	10,000 – 25,000
Smartphone	Android device with gyroscope and VR support (already available)	0
Total		**10,000 – 25,000**

- A mobile VR headset (e.g., Gear VR) is selected instead of high-end devices (e.g., Meta Quest) to significantly reduce costs while maintaining sufficient immersion.
- The smartphone-based VR approach eliminates the need for expensive standalone VR hardware. An Android smartphone with sufficient performance and required support is already owned. Therefore, the cost for a smartphone is not included in the budget.

7.3 SOFTWARE COSTS

Table 3: SOFTWARE COSTS TABLE

Item	**Description**	**Cost (LKR)**
Unity Engine (Personal Edition)	VR development platform	0
GenAI Tools • Stable Diffusion (Local) • Skybox AI (Free tier) • Meshy/Sloyd (Free tier)	Asset generation (textures, skyboxes, 3D models)	0
Development Tools (VS Code, Python)	Programming and integration	0

Total		**0**

- The system leverages free-tier and open-sources tools, eliminating licensing costs
- Unity personal edition provides full VR development capabilities suitable for prototyping
- GenAI tools are used in offline/pre-generation mode, avoiding API costs

7.5 HUMAN EFFORT COST

Table 4: HUMAN EFFORT COSTS TABLE

Role	Estimated Hours	Rate (LKR/hr)	Cost (LKR)
Unity Developer	80 – 120	500	40,000 – 60,000
AI/ML Developer	40 – 60	500	20,000 – 30,000
Total			**60,000 – 90,000**

- These are theoretical costs only, meaning there is no cost involved for human effort as this component will be entirely developed by oneself. However, this section reflects the true development effort.

7.6 BUDGET SUMMARY

Table 5: BUDGET SUMMARY TABLE

Category	Cost (LKR)
Hardware	10,000 – 25,000
Software	0
Human Effort (Theoretical)	60,000 – 90,000
Total Actual Cost	**10,000 – 25,000**

7.7 OVERALL BUDGET JUSTIFICATION

The proposed budget reflects a strategic balance between cost and functionality:

- Low-cost hardware ensures accessibility and replicability in resource-constrained environments.
- Free software and GenAI tools significantly reduce development expenses without limiting system capability.
- The architecture avoids computationally expensive cloud processing, favoring efficient local execution.

- The budget aligns with the project's goal of delivering a functional, research-oriented prototype rather than a commercial product.

Furthermore, the system demonstrates that advanced technologies such as VR and AI-driven adaptation can be implemented within a constrained budget.

8. WORK BREAKDOWN STRUCTURE (WBS)

8.1 OVERVIEW

The component is divided into key functional modules to ensure structured development, parallel execution, and manageable workload distribution. The focus is on environment generation, VR integration, and adaptive optimization

8.2 TASK BREAKDOWN

1. Planning & Requirements

- Define system scope and architecture
- Identify input/output data flows
- Finalize tools and technologies

2. Prompt Processing Module

- Design prompt structure
- Implement prompt parsing
- Extract environment parameters

3. GenAI Asset Preparation

- Generate textures, skyboxes, and 3D models
- Optimize assets for mobile VR
- Organize asset library

4. Scene Assembly Engine

- Develop rule-based environment generation
- Implement terrain, object placement, and lighting
- Configure spatial audio

5. Unity VR Development

- Setup Unity project and XR tools
- Integrate scenes into VR environment
- Implement basic user interaction
- Optimize performance for mobile VR

6. Adaptive System Development

- Define stress input format
- Design rule-based adaptation module
- Implement RL-based optimization model
- Map stress → environment parameters

7. System Integration

- Connect all modules into a unified pipeline
- Ensure smooth data flow between components

8. Testing & Validation

- Functional testing of each module
- Performance testing on target device
- User testing and refinement

9. Deployment & Documentation

- Build and deploy VR application
- Prepare technical documentation and reports

9. GANTT CHART




Figure 4: GANTT CHART

10. REFERENCES LIST

[1] I. Kishor, U. Mamodiya, M. Almaayah, A. Alqutaish, R. Shehab, and T. H. H. Aldhyani, "Agentic AI-Enhanced Virtual Reality for Adaptive Immersive Learning Environments," *Mesopotamian J. Comput. Sci.*, vol. 2025, pp. 398–416, Oct. 2025, doi: 10.58496/MJCSC/2025/026.

[2] M. Barthet, D. Branco, R. Gallotta, A. Khalifa, and G. N. Yannakakis, "Closing the Affective Loop via Experience-Driven Reinforcement Learning Designers," Jul. 23, 2024, *arXiv*: arXiv:2408.06346. doi: 10.48550/arXiv.2408.06346.

[3] F. Aji Purnomo, F. Arifin, and H. D. Surjono, "Optimizing VR-UX: analysis and adaptive recommendations for enhancing immersion and reducing motion sickness," *Int. J. Adv. Appl. Sci.*, vol. 14, no. 4, p. 1181, Dec. 2025, doi: 10.11591/ijaas.v14.i4.pp1181-1191.

[4] L. Keating, "ADAPTIVE VR TRAINING WITH PHYSIOLOGICAL FEEDBACK".

[5] T. Li, Y. Zhu, H.-N. Liang, and Y. Wang, "Adapting to the User: A Systematic Review of Personalized Interaction in VR," Oct. 15, 2025, *arXiv*: arXiv:2510.13123. doi: 10.48550/arXiv.2510.13123.

[6] S. Poddar, Y. Wan, H. Ivison, A. Gupta, and N. Jaques, "Personalizing Reinforcement Learning from Human Feedback with Variational Preference Learning".

[7] C. Halkiopoulos and E. Gkintoni, "The Role of Machine Learning in AR/VR-Based Cognitive Therapies: A Systematic Review for Mental Health Disorders," *Electronics*, vol. 14, no. 6, p. 1110, Mar. 2025, doi: 10.3390/electronics14061110.

[8] B. Mohan, S. Mahalakshmi, S. K. Suman, Y. Monikarchana, S. P. Santhoshkumar, and P. Vigneshwaran, "Machine Learning Enhanced Stress Assessment and Learning Outcome Analysis using Skin Conductance in Virtual Reality Environments," in *2025 7th International Conference on Signal Processing, Computing and Control (ISPCC)*, SOLAN, India: IEEE, Mar. 2025, pp. 770–775. doi: 10.1109/ISPCC66872.2025.11039318.

[9] M. Fernández-Cañas *et al.*, "Cybersickness Evaluation in Immersive Virtual Environments: A Systematic Review with Implications for Neurological Rehabilitation," *J. Clin. Med.*, vol. 15, no. 1, p. 46, Dec. 2025, doi: 10.3390/jcm15010046.

11. APPENDICES

APPENDIX A – SYSTEM ARCHITECTURE DIAGRAM

This appendix includes the overall system architecture of the component, illustrating the interaction between the stress classification module, user preference input, environment generation pipeline, rule-based adaptation module, and the reinforcement learning agent.

APPENDIX B – DATA FLOW DIAGRAM

This appendix presents the data flow within the component, showing how stress classifications and user preferences are processed to generate and continuously adapt the VR environment.

APPENDIX C – ADAPTATION LOGIC AND REINFORCEMENT LEARNING MODEL

This appendix provides detailed descriptions of:

- The rule-based adaptation logic used during initial system operation
- The reinforcement learning framework, including:
    - State representation
    - Action space
    - Reward function
    - Policy update mechanism

APPENDIX D – GENAI ASSET PROMPTS

This appendix contains sample prompts used for generating VR assets, including:

- Skyboxes
- Textures
- Environmental objects

These prompts support reproducibility of the generated environments.

APPENDIX E – KEY IMPLEMENTATION SNIPPETS

This appendix includes selected code snippets from the implementation, particularly:

- Scene generation logic
- Environment parameter update scripts

- Adaptation mechanisms within the Unity environment

APPENDIX F – TEST CASES AND RESULT

This appendix presents sample test cases used to validate the system, including:

- Input conditions (stress levels and user preferences)
- Expected outcomes
- Observed results

APPENDIX G – GANTT CHART

This appendix includes the project timeline for the component, illustrating task distribution and development phases from March to December.