


SLT-BB-0415-ER-S0030RG-55-(0)

Lead screw driven linear axes with reduced installation height

3D View

To activate the interactive 3D view, you must trust this document (see hint on the top) in Adobe Acrobat and click on the question mark.



Zoom

Moves you toward or away from objects in the scene when you drag vertically. You can also zoom with the hand tool by holding down Shift as you drag.



Pan

Moves the model vertically and horizontally only. You can also pan with the hand tool: Ctrl-drag.



Rotate

Turns 3D objects around relative to the screen. How the objects move depends on the starting view, where you start dragging and the direction in which you drag.

3D PDF DATASHEET

Create Your Individual 3D PDF
Datasheet



 **eCATALOG**solutions

Learn How to Create Your
Mechanical Product Catalog



 **BIM** catalogs.net

Learn How to Create Your BIM
Product Catalog



 **PART**solutions

Reduce Your Costs in
Engineering and Purchasing




igus[®]

Engineering Plastic


SLT-BB-0415-ER-S0030RG-55-(0)

Lead screw driven linear axes with reduced installation height

2D derivation



ISO View



3D PDF DATASHEET

Create Your Individual 3D PDF Datasheet



Learn How to Create Your Mechanical Product Catalog



Learn How to Create Your BIM Product Catalog




Reduce Your Costs in Engineering and Purchasing




SLT-BB-04 15-ER-S0030RG-55-(0)

Lead screw driven linear axes with reduced installation height

Technical drawings





SLT-BB-0415-ER-S0030RG-55-(0)

Lead screw driven linear axes with reduced installation height

Technical Data

ARTNR (Part no.)	SLT-BB-0415-ER-S0030RG-55
INFO (Info PDF)	INFO
CNSMASSEXACT (Weight / kg)	0.466
HUB (Stroke length / mm)	55
SP (Carriage position / mm)	0
ASP (Direction lead screw)	Right (Standard)
T (lead screw)	Steel, trapezoidal thread TR12x3
MHUB (Maximum stroke length / mm)	600
ZGEW (Additional weight (per 100mm) / kg)	0.12
FA (Max. static load-bearing capacity axial / N)	200
FR (Max. static load-bearing capacity radial / N)	400
DR (max. rpm / 1/min.)	1000
GS (max. speed / m/min.)	3
A (Width / mm)	58
AL (Length / mm)	45
H (Height / mm)	30
E1 (Width / mm)	19
E2 (Width / mm)	25
E3 (Width / mm)	35
L (Length / mm)	89
L2 (Length / mm)	17
D2 (Diameter)	12
HA (Height / mm)	15
SG (Thread)	M3x13
TK (Length / mm)	8
TG (Thread)	M5x15
F (Height / mm)	2.8
LB (Length / mm)	6.5
LT (Diameter / mm)	22
D (Diameter / mm)	17
AS (Diameter / mm)	16

3D PDF DATASHEET

Create Your Individual 3D PDF
Datasheet



 **eCATALOG**solutions

Learn How to Create Your
Mechanical Product Catalog



 **BIM** catalogs.net

Learn How to Create Your BIM
Product Catalog



 **PART**solutions

Reduce Your Costs in
Engineering and Purchasing



SLT-BB-0415-ER-S0030RG-55-(0)

Lead screw driven linear axes with reduced installation height

Bill of Materials

N°	Description	Amount
1	SLT-BB-0415-ER-S0030RG-55-(0)	1