

Plantim Icons v4.1 — proposal report

New icons for loading states and placeholders, the specific cases the app currently works around, a set of plant-styled profile avatars, and a country-flag asset class in rectangular and circular shapes — authored in the v4 design language, gated mechanically, and delivered as a review package (interactive decision catalog + PDF catalog + this report). Additive only: no shipped id changes.

66	52	14	1584
PROPOSED IDS	SEMANTIC ICONS	FLAGS	GENERATED SVGS



proposalHash f08b08dd56234f83112dc3b9fa3a5fc99ec690dca322aa85b59067a17e6c905d
derived from v4 4.0.0 · v4Hash f12d51dd066e0493bb460f13ca0d9c957e58542320303fbce9aadf893972be4b

Summary

The v4 rework (237 icons) covers the app's existing icon surface. This proposal fills three gaps the app audit (reports/v4-app-icon-audit.md) exposed but v4 deliberately left out of scope:

- 1. **Loading states & placeholders** (9 ids) — the app ships `profile-placeholder.svg` as a raw asset, scales `plant.sprout` to 56 px as the plant-photo fallback and has no skeleton, pending or offline glyphs at all.
- 2. **Specific cases** (18 ids) — ids with no semantic equivalent in v2/v3/v4 that the clients fake with a neighbouring glyph (download via upload, room via navigation.home, add-photo via camera, add-event via action.add, humidity via the watering drop, light via the weather sun, ...).
- 3. **Plant avatars** (25 ids) — a default profile picture that belongs to a plant-care product. Today a user without a photo gets `account.user` (the Profile tab glyph) or a raw `profile-placeholder.svg`; neither is pickable and neither says anything about the person.
- 4. **Country flags** (14 ids) — a language/region picker needs them; the web client already carries `assets/flags/*.svg` outside the registry, so iOS and Android would each re-source them.

Everything is authored in the v4 DSL (same grid, strokes, grades, layer roles, color tokens) and passes the same gates, so an approved id promotes into v4 by moving its module — no redraw, no adapter change beyond regeneration. Flags use a dedicated, narrower DSL and renderer because they are not monochrome semantic icons (see §3).

Method

- **Grounding.** Every id cites the surface that needs it (audit §2 usage table, §3 gaps, §3c hardcoded assets). Ids that an existing semantic id already covers were *not* proposed (e.g. a generic image placeholder is `utility.image` at `ink.300`; a generic empty state is `utility.inbox`).
- **Authoring.** 6 hand-authored modules under `design-tokens/icons/v4.1-proposal/src/` using the v4 DSL (`icon / layer / P / C / R`): 24-grid, 2 px round strokes, named layers with hand-assigned roles, per-icon multicolor tokens, declared solid counters. 35 of 52 icons carry an authored micro grade; 33 have true-fill solids with declared counters, the rest use bold-mode solids (line-only geometry, the v4 P1 convention).
- **Gates.** `check-proposal-icons.mjs` runs the v4 structural checks (hash integrity, determinism via `--verify`, source hygiene, path-walked bounds and 3-decimal clamp, per-grade stroke discipline, 4 × 6 size-set completeness, a11y keys, token refs) plus proposal rules (ids must be new across v2/v3/v4; tiers P1/P2 only; every status/semantic label present in `en/de/tr`) and flag rules (clip + border present, no `currentColor` in color variants, canonical hex, micro survivors). `--raster` adds the v4 flood-fill counter check and outline ↔ solid silhouette IoU ≥ 0.90 for the 33 filled solids. Both pass on this build.
- **Human loop.** Contact sheets (`render-v4-sheets.mjs` proposal: four variants at 128 px, 16 → 72 ramp, solid + multicolor on dark, 16–24 on dark) inspected zoomed; two icons reworked after the first pass (`plant.light` rays converged into an arrowhead → now radiate from the corner; `care.misting` trigger lengthened), one skeleton solid re-proportioned to pass the silhouette gate.

1. Loading states & placeholders 9 ids

Skeleton and fallback glyphs for the moments before content exists: profile photo, plant photo, list rows, cards, charts, plus inline loading, pending and offline states. Today these are raw assets (`profile-placeholder.svg`), scaled-up tab icons (`plant.sprout` at 56 px as the plant-hero fallback) or nothing at all.

Design rule. Container + ghost content. Multicolor stays inside the ink ramp (`ink.300` container, `ink.500` content) so a placeholder recedes; duotone mutes the container. Solids are real tiles, so a placeholder can occupy exactly the footprint of the asset it stands in for.

24 PX · 16 PX	ID · WHY · WHERE
	<code>placeholder.avatar</code> P1 Ring + bust with the shoulders meeting the ring — the classic 'no photo' crop. Distinct from <code>account.user</code> (Profile tab) at every size; the solid keeps the space around the bust as its counter. web: <code>assets/profile-placeholder.svg</code> (raw asset, outside the registry) · ios: <code>ProfileView</code> falls back to <code>account.user</code> · member lists, comments, public profile
	<code>placeholder.card</code> P1 Media block + two lines: card skeleton for plant / garden grids and the social feed. Garden grid, Plants grid, SocialFeed cards

	<code>placeholder.chart</code> P2 Axes + ghost bars for chart loading/empty. <code>utility.bar.chart3</code> stays the 'chart' action glyph. web: <code>GrowthChart.vue</code> empty state (<code>utility.bar.chart3</code> h-7 today) · stats tiles
	<code>placeholder.list</code> P1 Avatar disc + two lines: a list-row skeleton (notifications, members, followers). <code>NotificationFeed</code>, <code>InviteMemberSheet</code>, garden members
	<code>placeholder.plant</code> P1 Photo tile + leaf. Replaces the scaled-up <code>plant.sprout</code> used as the plant-hero fallback; solid = filled tile with the leaf as counter. web: <code>PlantDetailsHero.vue:357</code> (<code>plant.sprout</code> h-14) · plant cards without a photo · <code>AddPlant</code> preview
	<code>placeholder.text</code> P1 Two full lines + one short — the canonical text skeleton. Bold solid gives fat bars for shimmer overlays. feed / notification / journal rows while loading · Today card summaries
	<code>status.loading.dots</code> P1 Bouncing-dots snapshot (middle dot raised) so it never collides with <code>utility.more.horizontal</code>; multicolor/duotone carry the trail. Reuses the existing <code>a11y.icons.status.loading</code> label. Chat: 'AI is typing' · inline saves, optimistic updates · static fallback where Lottie is unavailable status: Loading
	<code>status.offline</code> P1 Cloud + slash. The mobile client has no connectivity glyph; the status color lands on the slash. offline banner (iOS/PWA) · sync indicator in Settings status: Offline
	<code>status.pending</code> P1 Hourglass for waiting states that are not spinners: pending invites, queued sync, unverified email. <code>InviteMemberSheet</code>, garden co-owner invites · <code>VerifyEmail</code> · offline queue status: Pending

2. Specific cases the app works around 18 ids

Ids with no semantic equivalent in v2/v3/v4 that the clients currently fake with a neighbouring glyph: download (upload exists), sort, drag handle, QR, external link, language picker, add-photo, add-event, plant identification, humidity/light requirements, pet safety, misting/rotating care types, and room/indoor/outdoor placement (`navigation.home` doubles as "room" on both platforms).

Design rule. Same v4 DSL, gates and grades as the shipped set. Siblings reuse v4 geometry verbatim where a pair must match (`calendar.add` ← `calendar.date` frame; `utility.camera.plus` ← `utility.camera` body; `utility.download` ← `utility.upload` tray).

24 PX · 16 PX	ID · WHY · WHERE
	<code>calendar.add</code> P1 <code>calendar.date</code>'s hand-drawn frame + rings with a plus in the body; the plus survives the solid as a counter. web: <code>AddCareModal.vue</code>, <code>CalendarSidebar.vue</code> (action.add today) · ios: <code>AddCareModalView.swift</code>
	<code>care.misting</code> P2 Spray bottle + mist dots. Completes v3's <code>care.watering/fertilizing/pruning/repotting</code> with the one care type they lack. care calendar categories · care rhythm strip
	<code>care.rotating</code> P2 Pot + clockwise arrow: turn the plant toward the light (even growth). care calendar categories · care suggestions
	<code>location.indoor</code> P2 Window (frame + mullions) on a sill — distinct from <code>utility.grid2x2</code>. placement attribute on plants / gardens

	<code>location.outdoor</code> P2 Single round-crown tree on the ground; <code>utility.trees</code> is two pines. placement attribute on plants / gardens · balcony / garden gardens
	<code>location.room</code> P1 Door on a floor line; the knob survives the solid as a counter. Frees <code>navigation.home</code>, which currently means both 'Today' and 'room' (audit §3a-5). web/ios: RoomSelect, room chips · RoomScene / RoomColumn headers
	<code>plant.humidity</code> P1 Two drops — never confused with the single <code>plant.watering</code> drop (47 refs). plant detail environment row · weather widgets / LocationPostcard
	<code>plant.identify</code> P1 Viewfinder brackets + leaf: AI plant identification. Today the flow borrows <code>utility.sparkles</code> + <code>utility.camera</code>. AddPlant identify step · Chat plant-picker overlay
	<code>plant.light</code> P1 Leaf lit by three rays from the corner: light requirement. <code>weather.sun</code> (17 refs) currently doubles as theme toggle and <code>weather</code>. plant detail environment row · species select · room light hint
	<code>plant.pet.safe</code> P2 Paw in leaf green. Pet safety is the most-asked species attribute after light and water. species attributes · plant detail badges semantic: Pet safe
	<code>plant.pet.unsafe</code> P2 Same paw with a slash; <code>status.error</code> on the slash in multicolor. Semantic pair with <code>plant.pet.safe</code>. species attributes · plant detail warning badge semantic: Toxic to pets
	<code>utility.camera.plus</code> P1 The v4 camera body with a plus in the lens: 'add photo' as a distinct CTA. <code>utility.camera</code> (24 refs) currently means both 'photo' and 'add photo'. profile photo · plant photo · journal entry
	<code>utility.download</code> P1 Mirror of <code>utility.upload</code> (same tray, reversed arrow). The registry has <code>upload/upload.cloud</code> but no download. privacy: export my data · save plant photo · download care report / calendar
	<code>utility.drag.handle</code> P2 2×3 grip for reordering; <code>utility.move</code> (4-way arrows) means relocate, not reorder. reorder rooms, plants in a garden, care steps
	<code>utility.external.link</code> P1 Box + arrow leaving top-right — the universal 'opens elsewhere' affordance the policy pages lack. PrivacyPolicy, AccessibilityStatement links · species source links
	<code>utility.language</code> P1 Speech bubble + 'A': the language/region picker trigger. Pairs with the <code>flag.*</code> asset class; crossbar dropped at micro. Settings: language & region · onboarding locale step
	<code>utility.qr.code</code> P2 Three finder patterns + modules; <code>utility.scan.line</code> stays the scanning action. True-fill solid with the finder rings as counters. share garden / public profile via QR · scan plant label
	<code>utility.sort</code> P1 Paired up/down arrows for list ordering. <code>utility.chevrons.up.down</code> is the select affordance, not sort. Plants list, Calendar, Feed ordering toolbar

3. Plant avatars (profile logos) 25 ids

Twenty-five default profile avatars, each modelled on a real plant the Plantim audience recognises — monstera, saguaro, echeveria, fiddle-leaf fig, snake plant, lavender, ... A user without a photo picks one in Profile; the same glyph identifies them in comments, member lists and the social feed.

Design rule. One family: the placeholder.avatar ring as the crop, a closed plant silhouette inside it, interior detail strokes that drop at micro. The solid variant is a sticker (disc with the plant punched out), so every silhouette is a declared counter. Foliage stays on the leaf ramp, blooms on bloom/sun, wood on earth; the ring takes a pastel so the picker shows tinted discs. Built for 32–72 px; the 16 px reading is the silhouette alone.

24 PX · 16 PX	ID · WHY · WHERE
	avatar.aloe P1 five spiky leaves fanning from a low base Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Aloe
	avatar.bamboo P1 segmented stalk with a leaf on either side Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Bamboo
	avatar.bonsai P1 cloud canopy on a short trunk in a shallow tray Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Bonsai
	avatar.cactus P1 saguaro column with two arms Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Cactus
	avatar.calathea P1 oval leaf with paired stripes (prayer plant) Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Calathea
	avatar.clover P1 four heart leaflets on a stem Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Clover
	avatar.eucalyptus P1 stem with three pairs of round leaves Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Eucalyptus
	avatar.fern P1 one-sided frond with four leaflet lobes Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Fern
	avatar.ficus P1 fiddle-leaf fig — violin-shaped leaf on a stub stem Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Fiddle-leaf fig
	avatar.ivy P1 three-lobed leaf on a stem Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Ivy

	avatar.lavender P1 spike of florets on a stem with one leaf Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Lavender
	avatar.lotus P1 five petals fanning up from the water line Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Lotus
	avatar.monstera P1 lobed leaf with two slits and a midrib Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Monstera
	avatar.oak P1 lobed oak leaf with a midrib Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Oak
	avatar.orchid P1 five petals around a small lip Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Orchid
	avatar.palm P1 four fronds drooping from a slim trunk Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Palm
	avatar.pilea P1 Chinese money plant — coin leaf on a stalk Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Pilea
	avatar.pine P1 three-tier conifer with its trunk Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Pine
	avatar.pothos P1 heart leaf with a short curling stem Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Pothos
	avatar.rose P1 bud from above — round bloom with a spiral Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Rose
	avatar.sansevieria P1 three upright sword leaves with a pale centre stripe Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Snake plant
	avatar.sprout P1 the beginner avatar — two seed leaves on a stem in soil Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Sprout
	avatar.succulent P1 echeveria rosette — six pointed leaves around a heart Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Succulent

	avatar.sunflower P1 eight petals around a wide seed disc Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Sunflower
	avatar.tulip P1 cup bloom with three petal tips on a short stem Profile: avatar picker (no photo) · comments, member lists, social feed · public profile header semantic: Tulip

4. Country flags 14 ids

A locale/region picker needs flags; the web client already ships assets/flags/*.svg outside the registry. Proposed as a new asset class `flag.\*` — not semantic icons — in two shapes: rectangular (`color` / `mono`) and circular (`circle` / `circle.mono`), the latter cropped into the same Ø18.5 disc the avatars use so a flag sits in a locale chip or next to a profile picture without a shape clash.

Design rule. Starter set = the three shipped locales (de, en → gb/us, tr), the EU, nine likely-next European regions, and a neutral `flag.unknown`. Icon-size simplification is deliberate (no coats of arms, 7 stripes / 8 stars on US, single-layer saltire on GB): a 16 px flag reads by silhouette and color. Colors are never theme tokens; dark mode is handled by the 12 % hairline border, not by re-coloring. The circular shapes scale the flag to cover the disc height and crop the sides — the standard circle-flag treatment.

24 PX · 16 PX	ID · WHY · WHERE
	flag.at P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Austria
	flag.ch P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Switzerland
	flag.de P1 shipped locale (de) Settings: language & region · profile LocationPostcard · public profile semantic: Germany
	flag.es P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Spain
	flag.eu P1 region grouping / GDPR surfaces privacy & data region semantic: European Union
	flag.fr P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: France
	flag.gb P1 shipped locale (en) Settings: language & region · profile LocationPostcard · public profile semantic: United Kingdom
	flag.it P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Italy

	<code>flag.nl</code> P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Netherlands
	<code>flag.pl</code> P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Poland
	<code>flag.pt</code> P1 likely next region for a European plant-care audience Settings: language & region · LocationPostcard semantic: Portugal
	<code>flag.tr</code> P1 shipped locale (tr) Settings: language & region · profile LocationPostcard · public profile semantic: Türkiye
	<code>flag.unknown</code> P2 neutral fallback when no region is set (never an empty slot) Settings · public profile semantic: Region not set
	<code>flag.us</code> P1 shipped locale (en) Settings: language & region · profile LocationPostcard · public profile semantic: United States

Plant avatars are a picker, not a semantic vocabulary

- **Why they are here.** Everything else in the registry answers "what does this control do". An avatar answers "who is this", and the app has no answer today: a user without a photo gets the Profile tab glyph (`account.user`) or a raw asset, so every photo-less member looks identical.
- **One family, 25 plants.** Each avatar is the `placeholder.avatar` ring holding one closed plant silhouette, with interior detail (veins, stripes, slits) on a second layer. Real plants, chosen for silhouette contrast rather than taxonomy: a monstera, a saguaro, an echeveria rosette, a fiddle-leaf fig, a snake plant, a lavender spike, a bonsai, a lotus, and so on.
- **The solid is a sticker.** The disc fills and the plant is punched out of it, so an avatar can sit on any background. Every silhouette is a declared counter and the raster gate flood-fills to prove it; interior detail is authored as bars nested inside the cut-out, which flip back to filled under `fill-rule="evenodd"` — that is how a monstera keeps its slits and a calathea its stripes in the solid instead of going blank.
- **Color.** Foliage on the leaf ramp, blooms on bloom/sun, wood and soil on earth; the ring cycles a pastel so a picker shows tinted discs rather than 25 identical circles. Duotone mutes the ring and keeps the plant.
- **Size honesty.** They are built for 32–72 px (profile header, picker grid, comment rows). At 16/20 px the detail layer drops and an avatar reads as its silhouette only — the same grade rule as the rest of v4, but it matters more here because the set differentiates on interior detail.

Flags are an asset class, not semantic icons

- **Why not the v4 registry.** v4 guarantees four variants sharing one silhouette, `currentColor` strokes and theme tokens. A flag has none of those properties: its colors are fixed by vexillology, an "outline flag" is meaningless, and it must not re-theme in dark mode. Forcing flags through the v4 gates would either weaken the gates or produce wrong flags.
- **Two shapes × two treatments.** `color` — the canonical flag, clipped to a 20×14 rounded rect (rx 2) at (2,5) on the 24-grid, with a 12 % black hairline inset border so white edges (PL, AT, NL) keep a silhouette on light UI and saturated fields stay soft on dark UI. `mono` — frame + partition lines in `currentColor` for tinted lists, inactive states and monochrome contexts, at the v4 grade stroke (2.4 / 2 / 1.6). `circle` and `circle.mono` — the same flag and the same partitions cropped into the Ø18.5 disc the avatars use, so a flag sits in a locale chip or beside a profile picture without a shape clash. The circular shapes scale the flag to cover the disc height (×1.321) and crop the sides — the standard circle-flag treatment; inside the scaled group the mono stroke is divided by the scale so it still renders at the grade weight.
- **Sizes.** The same six sizes and three grades as v4; micro (16/20) drops layers flagged `micro: false` (US stars, GB saltire, PT shield) and grows the EU stars so the ring closes.

- **Simplification policy.** No coats of arms (ES), 7 stripes + 8 stars (US), single-layer saltire (GB), armillary sphere as three discs (PT). The goal is recognition at 16 px, not heraldic accuracy — the policy every icon-size flag set follows.
- **Colors.** Commonly published values, uppercase hex, authored per flag; never tokens. The structural gate rejects `currentColor` in a color variant and non-canonical hex anywhere.
- **Accessibility.** Every flag is semantic with a localized label key (`ally.icons.flag.<code>`) in `en/de/tr`, so a language picker announces "Deutschland", not "flag".
- **Scope.** 14 flags: the three shipped locales (`de`, `en` → `gb` + `us`, `tr`), the EU, nine likely-next European regions, and `flag.unknown` for "region not set". Adding a flag is one `flag()` call; the id space is ISO 3166-1 alpha-2.

Accessibility

- **Status icons** (`status.loading.dots`, `status.offline`, `status.pending`) require a label in every locale; `status.loading.dots` reuses `ally.icons.status.loading`, the other keys live in `locales.proposal.json` and merge into `locales/*.json` on promotion.
- **Semantic icons** (`avatar.aloe`, `avatar.bamboo`, `avatar.bonsai`, `avatar.cactus`, `avatar.calathea`, `avatar.clover`, `avatar.eucalyptus`, `avatar.fern`, `avatar.ficus`, `avatar.ivy`, `avatar.lavender`, `avatar.lotus`, `avatar.monstera`, `avatar.oak`, `avatar.orchid`, `avatar.palm`, `avatar.pilea`, `avatar.pine`, `avatar.pothos`, `avatar.rose`, `avatar.sansevieria`, `avatar.sprout`, `avatar.succulent`, `avatar.sunflower`, `avatar.tulip`, `plant.pet.safe`, `plant.pet.unsafe`) and all 14 flags carry localized labels the same way.
- Placeholders are decorative: the surrounding control owns the accessible name ("Loading profile..."), and the icon must never be the only signal — the v4 status-icon rule applies unchanged.
- Placeholder multicolor stays at `ink.300/ink.500`: it is meant to recede. Where a placeholder is the only content on screen, pair it with text.

Platform delivery (on promotion)

- **Web.** Semantic icons flow through the existing `@plantim/icons/v4` subpath (count-agnostic generator: no code change). Flags need a sibling subpath `@plantim/icons/flags` exporting `PlantimFlag` (props: `code`, `variant = color | mono`, `size`) plus tree-shakable per-flag modules; the generator is a ~1:1 copy of `generate-v4-package.mjs` over `registry.flags`.
- **iOS.** Semantic icons: `PlantimIconV4` regeneration. Flags: a `PlantimFlag` SwiftUI view rendering the color layers as `Paths` with fixed `Color(hex:)` values (no dynamic colors) and the mono variant through the existing stroke renderer.
- **Android.** Semantic icons: Vector Drawables + Compose ImageVectors via `generate-v4-android.mjs`. Flags: non-tintable drawables (fixed fills, values -night unchanged) and a tintable mono drawable.
- **Size budget.** 52 icons ≈ +62 KB of per-icon modules (tree-shaken); flags ≈ +11 KB. Both stay far below the package-size gate, but the number is worth re-checking with `icons:package:size` after promotion.

Promotion checklist

1. Review in `reports/plantim-icons-v4.1-proposal-catalog.html`; export the decision record (`.md/.json`).
2. For each **Approve**: move the icon's `icon()` into the matching `design-tokens/icons/v4/src/<category>.mjs` (or a new module), add its tier/verdict to `tiers.json`, merge its label keys into `locales/*.json`.
3. Flags: `land flags/src/flags.mjs` + `lib/flag-dsl.mjs` + `lib/flag-render.mjs` as a generator input alongside v4 (or as `design-tokens/icons/flags/`), add the `web/iOS/Android` flag generators described above.
4. Bump the registry to **4.1.0** (additive ids → minor, per governance), run `npm run icons:v4`, `icons:v4:raster`, `icons:v4:package`, `icons:v4:swift`, `icons:v4:android`, then `npm run icons:validate`.
5. Regenerate v4 catalog/report PDFs; add the CHANGELOG entry; delete the promoted modules from the proposal so it stays a delta.

Open decisions

- **Skeleton glyphs vs CSS skeletons.** Web already draws shimmer blocks in CSS; `placeholder.text/list/card` matter most on iOS/Android and in empty-state illustrations. Keep all six, or keep `avatar/plant/chart` and drop the three pure skeletons?
- **Flag scope.** Starter set of 14. If the picker is language-based rather than region-based, `flag.gb` vs `flag.us` for "English" is a product decision (many apps show neither and use `utility.language + text`).
- **Flag shape.** Both shapes ship; the app should pick one per surface and stay with it (circles beside avatars, rectangles in a settings list). Shipping both doubles the flag asset count — say so if you would rather keep only the circles.
- **Avatar count and defaults.** 25 avatars is a picker, not a set of semantic ids — which one is the default for a new account, and should the set be seeded per locale or per the user's first plant?

- **Avatar micro grade.** Interior detail (veins, stripes, slits) is dropped at 16/20 px by design, so at that size an avatar reads as its silhouette. If avatars must be identifiable in a 16 px list row, that is a redraw, not a tuning.
- **Tier of plant.pet.* and care.misting/rotating.** Proposed P2 (library) until the species attributes / care types exist in the data model; promote to P1 with authored micro grades when they ship.
- **Animation.** status.loading.dots is a static frame; a Lottie bounce (3 × 120 ms stagger) is a natural P0-style addition but out of scope for a P1 status icon under DESIGN.md §7.

Appendix — build evidence

ARTIFACT	PATH
authored geometry	design-tokens/icons/v4.1-proposal/src/*.mjs, flags/src/flags.mjs
compiled registry / manifest	registry.proposal.json (f08b08dd56234f83...), index.proposal.json
SVGs	svg/<variant>/<id>@<size>.svg — 1584 files (icons: outline/solid/duotone/multicolor; flags: color/mono/circle/circle.mono)
gates	npm run icons:proposal:check (structural) · npm run icons:proposal:raster
sheets	npm run icons:proposal:sheets → reports/v4-sheets/proposal/ (gitignored working artifacts)
review package	reports/plantim-icons-v4.1-proposal-catalog.html · ...-catalog.pdf · this report