

Humanoid robot G1_Humanoid Robot Functions_Humanoid Robot Price | Unitree Robotics

Source HTML: 机器人产品资料库_2026-06-21/02_Word补充资料/企业与产品资料/051_Unitree_G1_official_product_page.html

- RobotsRobot - Consumer/EducationAs2Go2Go1A1Robot - IndustryA2B2B1AlienGoRobotic ArmsZ1 / D1-TPerception4DLiDARComponentsComponentsAs2Compact Size Industrial CapabilityAs2-WPower Pioneer, Small Yet Exceptional

Robots

Robot - Consumer/Education

Robot - Industry

Robotic Arms

Perception

Components

- As2Compact Size Industrial Capability

As2

Compact Size Industrial Capability

- As2-WPower Pioneer, Small Yet Exceptional

As2-W

Power Pioneer, Small Yet Exceptional

- HumanHumanoid RobotH2R1G1H1 / H1-2Application PlanR1-A / R1-A-DG1-DG1-CompG1-BoxingDexterous HandDex2/5Dex1-1Dex5-1Dex3-1H2Destiny AwakeningH2 PlusIntegrated R&D and Manufacturing, Embarking on Full-Stack Development

Human

Humanoid Robot

Application Plan

Dexterous Hand

- H2Destiny Awakening

H2

Destiny Awakening

- H2 PlusIntegrated R&D and Manufacturing, Embarking on Full-Stack Development

H2 Plus

Integrated R&D and Manufacturing, Embarking on Full-Stack Development

- IndustryAdvanced Quadruped Inspection SolutionsUnitree quadruped robot launched a new power intelligent inspection solution, designed a series of solutions for dangerous, urgent and repetitive tasks, and provided efficient guarantee for power system construction, operation and maintenance and other work.Fire Rescue SolutionsOvercome Hazards, Protect the Ones Who March Against the Tide

Industry

Advanced Quadruped Inspection Solutions

Unitree quadruped robot launched a new power intelligent inspection solution, designed a series of solutions for dangerous, urgent and repetitive tasks, and provided efficient guarantee for power system construction, operation and maintenance and other work.

Fire Rescue Solutions

Overcome Hazards, Protect the Ones Who March Against the Tide

- Unifolm

- OS

- ServicesTerms & PoliciesDownload CenterResource CenterCustomer ServiceDocument Center

Services

- ExploreNewsAbout UnitreeContact Us

Explore

- DownloadUniStoreR1G1H1 / H1-2A2 / A2-WB2 / B2-WGo2As2

Download

Price from \$13.5K

Flexibility beyond ordinary people

Extra large joint movement angle space, 23~43 joint motors

Imitation & reinforcement learning driven

Robotics technology accelerated by AI is upgrading and evolving every day

Force control dexterous hand, manipulation of all things

Combined with force-position hybrid control, it is sensitive and reliable, and can simulate human hands to achieve precise operation of objects.

Robot world model, let ' s create it together

UnifoLM (Unified Robot Large Model), create a new era of intelligence together

More flexible and more comfortable!

Start the agent New era

Unitree G1 Parameter

- ModelG1G1 EDU

Model

G1

G1 EDU

- Height, Width and Thickness (Stand) 1320x450x200mm1320x450x200mm

Height, Width and Thickness (Stand)

1320x450x200mm

- Height, Width and Thickness (Fold) 690x450x300mm690x450x300mm

Height, Width and Thickness (Fold)

690x450x300mm

- Weight (With Battery)About 35kgAbout 35kg+

Weight (With Battery)

About 35kg

About 35kg+

- Total Degrees of Freedom (Joint Freedom) 2323 - 43

Total Degrees of Freedom (Joint Freedom)

23

23 - 43

- Single Leg Degrees of Freedom66

Single Leg Degrees of Freedom

- Waist Degrees of Freedom11+(Optional 2 additional waist degrees of freedom)

Waist Degrees of Freedom

1+(Optional 2 additional waist degrees of freedom)

- Single Arm Degrees of Freedom55

Single Arm Degrees of Freedom

- Single Hand Degrees of Freedom/7 (Optional Force control of three-fingered hand) +2(Optional 2 additional wrist degrees of freedom)*Three-fingered dexterous hand Dex3-1 Parameter: The thumb has 3 active degrees of freedom; the index finger has 2 active degrees of freedom; the middle finger has 2 active degrees of freedom.**Dex3-1 can optionally be installed with tactile sensor arrays

Single Hand Degrees of Freedom

7 (Optional Force control of three-fingered hand) +2(Optional 2 additional wrist degrees of freedom)

*Three-fingered dexterous hand Dex3-1 Parameter: The thumb has 3 active degrees of freedom; the index finger has 2 active degrees of freedom; the middle finger has 2 active degrees of freedom.

**Dex3-1 can optionally be installed with tactile sensor arrays

- Joint output bearingIndustrial grade crossed roller bearings (high precision, high load capacity)Industrial grade crossed roller bearings (high precision, high load capacity)

Joint output bearing

Industrial grade crossed roller bearings (high precision, high load capacity)

- Joint motorLow inertia high-speed internal rotor PMSM(permanent magnet synchronous motor,better response speed and heat dissipation)Low inertia high-speed internal rotor PMSM(permanent magnet synchronous motor,better response speed and heat dissipation)

Joint motor

Low inertia high-speed internal rotor PMSM(permanent magnet synchronous motor,better response speed and heat dissipation)

- Maximum Torque of Knee Joint 【1】 90N.m120N.m

Maximum Torque of Knee Joint 【1】

90N.m

120N.m

- Arm Maximum Load 【2】 About 2KgAbout 3Kg

Arm Maximum Load 【2】

About 2Kg

About 3Kg

- Calf + Thigh Length0.6M0.6M

Calf + Thigh Length

0.6M

- Arm SpanAbout 0.45MAbout 0.45M

Arm Span

About 0.45M

- Extra Large Joint Movement SpaceWaist joint : $Z \pm 155^\circ$ Knee joint : $0 \sim 165^\circ$ Hip joint : $P \pm 154^\circ$ 、 $R - 30 \sim +170^\circ$ 、 $Y \pm 158^\circ$ Waist joint : $Z \pm 155^\circ$ 、 $X \pm 30^\circ$ 、 $Y \pm 30^\circ$ Knee joint : $0 \sim 165^\circ$ Hip joint : $P \pm 154^\circ$ 、 $R - 30 \sim +170^\circ$ 、 $Y \pm 158^\circ$ Wrist joint : $P \pm 92.5^\circ$ 、 $Y \pm 92.5^\circ$

Extra Large Joint Movement Space

Waist joint : $Z \pm 155^\circ$

Knee joint : $0 \sim 165^\circ$

Hip joint : $P \pm 154^\circ$ 、 $R - 30 \sim +170^\circ$ 、 $Y \pm 158^\circ$

Waist joint : $Z \pm 155^\circ$ 、 $X \pm 30^\circ$ 、 $Y \pm 30^\circ$

Wrist joint : $P \pm 92.5^\circ$ 、 $Y \pm 92.5^\circ$

- Full Joint Hollow Electrical RoutingYESYES

Full Joint Hollow Electrical Routing

YES

- Joint EncoderDual encoderDual encoder

Joint Encoder

Dual encoder

- Cooling SystemLocal air coolingLocal air cooling

Cooling System

Local air cooling

- Power Supply13 string lithium battery13 string lithium battery

Power Supply

13 string lithium battery

- Basic Computing Power8-core high-performance CPU8-core high-performance CPU

Basic Computing Power

8-core high-performance CPU

- Sensing SensorDepth Camera+3D LiDARDepth Camera+3D LiDAR

Sensing Sensor

Depth Camera+3D LiDAR

- 4 Microphone ArrayYESYES

4 Microphone Array

- 5W SpeakerYESYES

5W Speaker

- WiFi 6 、 Bluetooth 5.2YESYES

WiFi 6 、 Bluetooth 5.2

- High Computing Power Module/Multiple brands and models availablesuch as Orin, etc.

High Computing Power Module

Multiple brands and models available

such as Orin, etc.

- Smart Battery (Quick Release)9000mAh9000mAh

Smart Battery (Quick Release)

9000mAh

- Charger 54V 5A 54V 5A

Charger

54V 5A

- Manual Controller YES YES

Manual Controller

- Battery Life About 2h About 2h

Battery Life

About 2h

- Upgraded Intelligent OTA YES YES

Upgraded Intelligent OTA

- Secondary Development 【3】 /YES

Secondary Development 【3】

- Warranty Period 【4】 8 months 18 months

Warranty Period 【4】

8 months

18 months

- Price (Tax and Shipping cost excluded) US \$13.5K Contact sales

Price (Tax and Shipping cost excluded)

US \$13.5K

Contact sales

[1]

The maximum torque of the joint motors of the whole machine is different. This is the maximum torque of the largest joint motor among them.

[2]

The maximum load of the arm varies greatly under different arm extension postures.

[3]

For more information, please read the secondary development manual.

[4]

For more detailed warranty terms, please read the product warranty brochure.

[5]

The above parameters may vary in different scenarios and configurations, please subject to actual situation.

[6]

The humanoid robot has a complex structure and extremely powerful power. Users are asked to keep a sufficient safe distance between the humanoid robot and people. Please use with caution

[7]

The product appearance is subject to change. Please refer to the final product.

[8]

Some sample functions on this page are still being developed and tested, and will be opened to users in the future.

[9]

Currently, the global humanoid robot industry is in the early stages of exploration. Individual users are strongly advised to thoroughly understand the limitations of humanoid robots before making a purchase.

This product is a civilian robot. We kindly request that all users refrain from making any dangerous modifications or using the robot in a hazardous manner.

Please visit Unitree Robotics Website for more related terms and policies, and comply with local laws and regulations.

- As2
- Go2Go2-W
- Go1A1
- B2B2-W
- A2A2-W
- B1AlienGo
- H2H1 / H1-2
- G1R1
- Dex2/5Dex1-1
- Dex5-1Dex3-1
- Z1
- D1-T
- 4D LiDAR L2
- 4D LiDAR L1
- Bionic Robot Joint Motor
- Brushless Digital ServoSV1-25
- A1 MotorGO-M8010-6
- Super Robot Waterproof Joints B1-16
- R1-D
- G1-D
- G1-CompIron Fist King
- Advanced Quadruped Inspection Solutions
- Fire Rescue Solutions
- Go2As2
- H1 / H1-2
- A2 / A2-W
- B2 / B2-W
- Open Source
- Document Center
- Download Center
- Security and Privacy
- News Center
- UniFolm

- UniStore
- UniPlatform
- About Unitree
- Contact Us
- Store/Cooperate
- Customer Service

Copyright © 2016 - 2025

YuShu TECHNOLOGY CO.,LTD All Rights Reserved