



# SCM1612

## Wi-Fi 6 and BLE 5 Low-Power SoC

### HTTP Client Development Guide

---

Revision 0.1  
Date 2024-09-23

#### Contact Information

Senscomm Semiconductor ([www.senscomm.com](http://www.senscomm.com))  
Room 303, International Building, West 2 Suzhou Avenue,  
SIP, Suzhou, China  
For sales or technical support, please send email to  
[info@senscomm.com](mailto:info@senscomm.com)

### Disclaimer and Notice

This document is provided on an “as-is” basis only. Senscomm reserves the right to make corrections, improvements and other changes to it or any specification contained herein without further notice.

All liability, including liability for infringement of any proprietary rights, relating to use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

All third party’s information in this document is provided as is with NO warranties to its authenticity and accuracy.

All trade names, trademarks and registered trademarks mentioned in this document are property of their respective owners and are hereby acknowledged.

© 2024 Senscomm Semiconductor Co.,Ltd. All Rights Reserved.

Senscomm Confidential

## Version History

---

Version	Date	Description
0.1	2024-9-23	Initial draft

Senscomm Confidential

# Table of Contents

---

Version History.....	3
1 Overview .....	5
2 Demo Configuration and Build .....	6
2.1 Set up Build Configuration .....	6
2.2 Set up Test HTTP Server .....	6
2.3 Set up Wi-Fi Parameters.....	6
2.4 Build wise-mcuboot.bin. ....	6
3 Using the HTTP Client.....	8
3.1 Basic HTTP Request.....	8
3.2 HTTP Authentication .....	9
3.3 HTTP Streaming.....	9
3.4 HTTP Native.....	10
3.5 HTTPS Requests .....	12
3.5.1 Obtaining a Root CA Certificate .....	12
3.5.2 Upload the Root CA Certificate File.....	13
3.5.3 Time Synchronization for HTTPS .....	14

# 1 Overview

---

This document serves as a guide for implementing applications that require running an HTTP client on the SCM1612 platform.

The SCM1612 SDK utilizes the [esp\\_http\\_client](#) module from [ESP-IDF](#):

- **API Location:** lib/net/esp\_http\_client
- **Demo Location:** api/examples/protocols/http\_client

Senscomm Confidential

## 2 Demo Configuration and Build

To run the HTTP client demo, follow these steps:

### 2.1 Set up Build Configuration

1. Select the HTTP client demo as a main application:  
\$ make scm1612s\_defconfig  
\$ make menuconfig
2. Navigate to the following options in the menuconfig interface:
  - `Applications -> Protocols Demo`
  - Select `Protocols Demo -> HTTP Client Demo`
  - `Libraries/middleware -> net -> ESP HTTP Client`
  - Select `Enable HTTP Basic Authentication`
  - Select `Enable HTTP Digest Authentication`
3. Exit and save the configuration.

### 2.2 Set up Test HTTP Server.

1. Navigate to `Applications -> Example Configuration` in the menuconfig interface.
2. Modify the test HTTP server settings as needed.

```
(httpbin.org) Example HTTP Endpoint  
[ ] Enable logging response buffer from HTTP event handler
```

### 2.3 Set up Wi-Fi Parameters

1. Open the menuconfig interface:  
\$ make menuconfig
2. Navigate to `Applications -> Common -> include WI-FI Configuration`
3. Enter the Wi-Fi parameters in `DEMO WI-FI Configuration`. Use the Help menu for each item if needed.
4. Exit and save the configuration.

### 2.4 Build wise-mcuboot.bin.

1. Build the project:  
\$ make

2. Refer to the `SDK\_Getting\_Started\_Guide` to download the generated image and run it on an SCM1612 EVK.

```
WISE 2018.02+ (Sep 23 2024 - 08:42:25 +0900)
$
$ I (3243) HTTP_CLIENT: WIFI CONNECTED
I (3244) SCM_API: AP SSID: Redmi_Test
I (3245) SCM_API: AP BSSID: 4c:c6:4c:8f:8d:20
I (3246) SCM_API: AP CH: 1
I (3247) SCM_API: AP RSSI: -25
I (3248) SCM_API: AP Country : CN
I (3248) SCM_API: Status: CONNECTED
I (3777) HTTP_CLIENT: WIFI GOT IP
```

Senscomm Confidential

## 3 Using the HTTP Client

The HTTP client API provides functions for making various types of HTTP requests and handling authentication, streaming, and HTTPS connections.

```
$ httpc
Usage: httpc rest <type : url or hostname>
or: httpc auth
or: httpc digest_auth <type : md5 or sha256>
or: httpc stream_read
or: httpc native_req
or: httpc secure <type : url or hostname or invalid>
$
```

### 3.1 Basic HTTP Request

The esp\_http\_client API allows performing GET, POST, PUT, PATCH, and DELETE requests. Once a connection is established, you can make multiple requests before closing it. This section focuses on the common use cases of testing REST APIs with URLs or hostnames.

- Testing with URLs

```
$ httpc rest url
$ I (3635574) HTTP_CLIENT: HTTP client Start
I (3636162) HTTP_CLIENT: HTTP GET Status = 200, content_length = 0x121
0x00225490: .... 7b0a 2020 .....{
0x002254a0: 2261 7267 7322 3a20 7b0a 2020 2020 2273 "args": { "s
0x002254b0: 636d 223a 2022 220a 2020 7d2c 200a 2020 cm": "" },
0x002254c0: 2268 6561 6465 7273 223a 207b 0a20 2020 "headers": {
0x002254d0: 2022 436f 6e74 656e 742d 4c65 6e67 7468 "Content-Length
0x002254e0: 223a 2022 3022 2c20 0a20 2020 2022 486f ": "0", "Ho
0x002254f0: 7374 223a 2022 6874 7470 6269 6e2e 6f72 st": "httpbin.or
0x00225500: 6722 2c20 0a20 2020 2022 5573 6572 2d41 g", "User-A
0x00225510: 6765 6e74 223a 2022 5343 4d20 4854 5450 gent": "SCM HTTP
0x00225520: 2043 6c69 656e 742f 312e 3022 2c20 0a20 Client/1.0",
0x00225530: 2020 2022 582d 416d 7a6e 2d54 7261 6365 "X-Amzn-Trace
0x00225540: 2d49 6422 3a20 2252 6f6f 743d 312d 3636 -Id": "Root=1-66
0x00225550: 6630 6239 6233 2d33 6665 6466 3134 6331 f0b9b3-3fedf14c1
0x00225560: 3938 6537 6534 6437 6564 3231 6135 3322 98e7e4d7ed21a53"
0x00225570: 0a20 207d 2c20 0a20 2022 6f72 6967 696e }, "origin
0x00225580: 223a 2022 3131 352e 3932 2e31 3138 2e35 ": "115.92.118.5
0x00225590: 3322 2c20 0a20 2022 7572 6c22 3a20 2268 3", "url": "h
0x002255a0: 7474 703a 2f2f 6874 7470 6269 6e2e 6f72 ttp://httpbin.or
0x002255b0: 672f 6765 743f 7363 6d22 0a7d 0a.. .... g/get?scm" } ...
I (3636725) HTTP_CLIENT: HTTP POST Status = 200, content_length = 0x1a5
I (3637176) HTTP_CLIENT: HTTP PUT Status = 200, content_length = 0x1a4
I (3637384) HTTP_CLIENT: HTTP PATCH Status = 200, content_length = 0x14d
I (3637592) HTTP_CLIENT: HTTP DELETE Status = 200, content_length = 0x14e
I (3637800) HTTP_CLIENT: HTTP HEAD Status = 200, content_length = 0x10c
I (3637802) HTTP_CLIENT: HTTP client done
```



- Testing with Hostnames

```
$ httpc rest hostname
$ I (3650035) HTTP_CLIENT: HTTP client Start
I (3650441) HTTP_CLIENT: HTTP GET Status = 200, content_length = 0x10c
I (3650887) HTTP_CLIENT: HTTP POST Status = 200, content_length = 0x1ba
I (3651374) HTTP_CLIENT: HTTP PUT Status = 200, content_length = 0x1b9
I (3651575) HTTP_CLIENT: HTTP PATCH Status = 200, content_length = 0x14d
I (3651777) HTTP_CLIENT: HTTP DELETE Status = 200, content_length = 0x14e
I (3651976) HTTP_CLIENT: HTTP HEAD Status = 200, content_length = 10c
I (3651977) HTTP_CLIENT: HTTP client done
```

## 3.2 HTTP Authentication

The HTTP client supports both Basic and Digest authentication. Digest authentication supports MD5 and SHA-256.

- Basic Authentication

```
$ httpc auth
$ I (4540966) HTTP_CLIENT: HTTP client Start
I (4541480) HTTP_CLIENT: HTTP Basic Auth Status = 200, content_length = 0x2f
I (4541482) HTTP_CLIENT: HTTP client done
```

- MD5 Authentication

```
$ httpc digest_auth md5
$ I (4644049) HTTP_CLIENT: HTTP client Start
I (4644784) HTTP_CLIENT: HTTP MD5 Digest Auth Status = 200, content_length = 0x2f
I (4644786) HTTP_CLIENT: HTTP client done
```

- SHA256 Authentication

```
$ httpc digest_auth sha256
$ I (4677430) HTTP_CLIENT: HTTP client Start
I (4678150) HTTP_CLIENT: HTTP SHA256 Digest Auth Status = 200, content_length = 0x2f
I (4678152) HTTP_CLIENT: HTTP client done
```

## 3.3 HTTP Streaming

- For applications that require active control over data exchange (e.g., real-time data streams), you can use HTTP streaming. The application flow differs from typical requests.

```
$ httpc stream_read
$ I (5632910) HTTP_CLIENT: HTTP client Start
I (5633320) HTTP_CLIENT: HTTP Stream reader Status = 200, content_length = 0x10e
0x0022eca0: 7b0a 2020 2261 7267 7322 3a20 7b7d 2c20 { "args": {},
0x0022ecb0: 0a20 2022 6865 6164 6572 7322 3a20 7b0a "headers": {
0x0022ecc0: 2020 2020 2243 6f6e 7465 6e74 2d4c 656e "Content-Len
0x0022ecd0: 6774 6822 3a20 2230 222c 200a 2020 2020 gth": "0",
0x0022ece0: 2248 6f73 7422 3a20 2268 7474 7062 696e "Host": "httpbin
0x0022ecf0: 2e6f 7267 222c 200a 2020 2020 2255 7365 .org", "Use
0x0022ed00: 722d 4167 656e 7422 3a20 2245 5350 3332 r-Agent": "ESP32
0x0022ed10: 2048 5454 5020 436c 6965 6e74 2f31 2e30 HTTP Client/1.0
0x0022ed20: 222c 200a 2020 2020 2258 2d41 6d7a 6e2d ", "X-Amzn-
0x0022ed30: 5472 6163 652d 4964 223a 2022 526f 6f74 Trace-Id": "Root
0x0022ed40: 3d31 2d36 3666 3063 3138 302d 3133 6262 =1-66f0c180-13bb
0x0022ed50: 3165 6633 3138 3231 6238 3137 3434 3231 1ef31821b8174421
0x0022ed60: 3966 3166 220a 2020 7d2c 200a 2020 226f 9f1f" }, "o
0x0022ed70: 7269 6769 6e22 3a20 2231 3135 2e39 322e rigin": "115.92.
0x0022ed80: 3131 382e 3533 222c 200a 2020 2275 726c 118.53", "url
0x0022ed90: 223a 2022 6874 7470 3a2f 2f68 7474 7062 ": "http://httpb
0x0022eda0: 696e 2e6f 7267 2f67 6574 220a 7d0a .... in.org/get" } ..
I (5633417) HTTP_CLIENT: HTTP client done
```

### 3.4 HTTP Native

The HTTP client provides low-level APIs for more fine-grained control over the HTTP connection.

```
$ httpc native_req
$ I (5883926) HTTP_CLIENT: HTTP client Start
I (5884533) HTTP_CLIENT: HTTP GET Status = 200, content_length = 0x10e
0x00225490: .... 7b0a 2020 .....{
0x002254a0: 2261 7267 7322 3a20 7b7d 2c20 0a20 2022 "args": {}, "
0x002254b0: 6865 6164 6572 7322 3a20 7b0a 2020 2020 headers": {
0x002254c0: 2243 6f6e 7465 6e74 2d4c 656e 6774 6822 "Content-Length"
0x002254d0: 3a20 2230 222c 200a 2020 2020 2248 6f73 : "0", "Hos
0x002254e0: 7422 3a20 2268 7474 7062 696e 2e6f 7267 t": "httpbin.org
0x002254f0: 222c 200a 2020 2020 2255 7365 722d 4167 ", "User-Ag
0x00225500: 656e 7422 3a20 2245 5350 3332 2048 5454 ent": "ESP32 HT
0x00225510: 5020 436c 6965 6e74 2f31 2e30 222c 200a P Client/1.0",
0x00225520: 2020 2020 2258 2d41 6d7a 6e2d 5472 6163 "X-Amzn-Trac
0x00225530: 652d 4964 223a 2022 526f 6f74 3d31 2d36 e-Id": "Root=1-6
0x00225540: 3666 3063 3237 622d 3266 3137 6632 3165 6f0c27b-2f17f21e
0x00225550: 3733 3563 3131 6630 3232 3563 3838 3365 735c11f0225c883e
0x00225560: 220a 2020 7d2c 200a 2020 226f 7269 6769 " }, "origi
0x00225570: 6e22 3a20 2231 3135 2e39 322e 3131 382e n": "115.92.118.
0x00225580: 3533 222c 200a 2020 2275 726c 223a 2022 53", "url": "
0x00225590: 6874 7470 3a2f 2f68 7474 7062 696e 2e6f http://httpbin.o
0x002255a0: 7267 2f67 6574 220a 7d0a .... rg/get" } .....
I (5885243) HTTP_CLIENT: HTTP POST Status = 200, content_length = 0x1a7
0x00225490: .... 7b0a 2020 .....{
0x002254a0: 2261 7267 7322 3a20 7b7d 2c20 0a20 2022 "args": {}, "
0x002254b0: 6461 7461 223a 2022 7b5c 2266 6965 6c64 data": "{w"field
0x002254c0: 315c 223a 5c22 7661 6c75 6531 5c22 7d22 1w":w"value1w"}"
0x002254d0: 2c20 0a20 2022 6669 6c65 7322 3a20 7b7d , "files": {}
0x002254e0: 2c20 0a20 2022 666f 726d 223a 207b 7d2c , "form": {},
0x002254f0: 200a 2020 2268 6561 6465 7273 223a 207b "headers": {
0x00225500: 0a20 2020 2022 436f 6e74 656e 742d 4c65 "Content-Le
0x00225510: 6e67 7468 223a 2022 3139 222c 200a 2020 ngth": "19",
0x00225520: 2020 2243 6f6e 7465 6e74 2d54 7970 6522 "Content-Type"
0x00225530: 3a20 2261 7070 6c69 6361 7469 6f6e 2f6a : "application/j
0x00225540: 736f 6e22 2c20 0a20 2020 2022 486f 7374 son", "Host
0x00225550: 223a 2022 6874 7470 6269 6e2e 6f72 6722 ": "httpbin.org"
0x00225560: 2c20 0a20 2020 2022 5573 6572 2d41 6765 , "User-Age
0x00225570: 6e74 223a 2022 4553 5033 3220 4854 5450 nt": "ESP32 HTTP
0x00225580: 2043 6c69 656e 742f 312e 3022 2c20 0a20 Client/1.0",
0x00225590: 2020 2022 582d 416d 7a6e 2d54 7261 6365 "X-Amzn-Trace
0x002255a0: 2d49 6422 3a20 2252 6f6f 743d 312d 3636 -Id": "Root=1-66
0x002255b0: 6630 6332 3763 2d30 3831 6639 3866 6636 f0c27c-081f98ff6
0x002255c0: 6263 3632 3537 3536 3331 3038 6431 3622 bc6257563108d16"
0x002255d0: 0a20 2020 2c20 0a20 2022 6a73 6f6e 223a }, "json":
0x002255e0: 207b 0a20 2020 2022 6669 656c 6431 223a { "field1":
0x002255f0: 2022 7661 6c75 6531 220a 2020 7d2c 200a "value1" },
0x00225600: 2020 226f 7269 6769 6e22 3a20 2231 3135 "origin": "115
0x00225610: 2e39 322e 3131 382e 3533 222c 200a 2020 .92.118.53",
0x00225620: 2275 726c 223a 2022 6874 7470 3a2f 2f68 "url": "http://h
0x00225630: 7474 7062 696e 2e6f 7267 2f70 6f73 7422 ttpbin.org/post"
0x00225640: 0a7d 0a.. .... } .....
I (5885413) HTTP_CLIENT: HTTP client done
```



## 3.5 HTTPS Requests

The HTTP client supports SSL connections using mbed TLS. For demonstration, [www.howsmyssl.com](http://www.howsmyssl.com) is a suitable test server.

### 3.5.1 Obtaining a Root CA Certificate

For HTTPS, a root CA certificate (PEM file) is required. This example demonstrates using openssl and save into the file `howsmysl_com_root_cert.pem`:

```
openssl s_client -showcerts -connect www.howsmyssl.com:443 < /dev/null
```

```
howsmysl_com_root_cert.pem x
-----BEGIN CERTIFICATE-----
MIIFBTCCAu2gAwIBAgIQS6hSk/eaL6JzBkuoBI110DANBgkqhkiG9w0BAQsFADBP
MQswCQYDVQQGEwJVUzEpMCcGA1UEChMgSW50ZXJuZXQgU2VjdXJpdHkgUmVzZWYy
Y2ggR3JvdXAxFtATBgNVBAMTDElTUkcgUm9vdCBYMTAeFw0yNDAzMTRwMDAwMDBa
Fw0yNzAzMTIyMzU5NTlaMDMxCzAJBgNVBAYTA1VTMRywFAYDVQQKEw1MZXQncyBF
bmNyeXB0MQwwCgYDVQQDEwNSMTAwggEiMA0GCSqGSIb3DQEBAQUAA4IBDwAwggEK
AoIBAQPdV+XmxFQs7bRH/sknWHZGUCiMHT6I3wWd1bUYKb3dtVq/+vbOo76vACFL
YlpaPAEvxVgD9on/jhFD68G14BQHlo9vH9fnuoE5CXVlt8KvGFs3Jijno/QHK20a
/6tYvJWuQP/py1fEtVt/eA0YYbwX51TGumRzW4Y0YCF7qZ1Nrx06rxQTO8IfM4
FpOUurDTazgGzRYSespSdcitdrLCnF2YRVxvYXvGLE48E1KGAdlX5jgc3421H5KR
mudKHMxFqHJV8LDmowfs/acbZp4/SitxhHFYyTr6717yW0QrPHTnj7JHwQdqzZq3
DZb3EoEmUVQK7GH29/Xi8orIlQ2NAGMBAAGjgfgwgfUwDgYDVR0PAAQH/BAQDAgGG
MB0GA1UdJQQWMBQGCCsGAQUFBwMCBggrBgEFBQcDATASBgNVHRMBAf8ECDAGAQH/
AgEAMB0GA1UdDgQWBBs7vMNHpeS8qcbDpHIMEI2iNeHI6DAfBgNVHSMEGDAwBR5
tFnme7b15AFzgAiIyBpY9umbbjAyBggrBgEFBQcBAQQmMCQwIgYIKwYBBQUHMAKG
Fmh0dHA6Ly94MS5pLmXlbnNyLm9yZy8wEwYDVR0gBAwwCjAIBgZngQwBAgEwJwYD
VR0fBCAwHjAcoBqgGIYWaHR0cDovL3gxLmMubGVuY3Iub3JnLzANBgkqhkiG9w0B
AQsFAAOCAgEAKrHnQTfreZ2B5s3iJeE6I0mQRJWjgVzPw139vaBw1bGWCIL0vIo
zwzn10ZdjCQiHcFCKtEjr59L9MhwTyAWsVrdAfYf+B9haxQnsHKNY67u4s5Lzzfd
u6PUzeetUK29v+PsPmI2cJkxp+iN3epi4hKu9ZzUPSwMqtCceb7qPVxEbpYxY1p9
1n5PJKB�BX9eb9LU6l8zSxPWV7bK3lG4XaMJgnT9x3ies7msFtpKK5bDtotij/10
GaKeA97pb5uwD9KgWvaFXMIet8jVTjLEvwRdvCn294GPDF08U8lAkIv7tghluaQh
1Qn1E4SEN4LOECj8dsIGJXpGUk3aU3KkJz9icKy+aUgA+2cP21uh6NcDIS3XyfaZ
QjmDQ993ChII8SXWupQZVBiIpcW04RqZk3lr7Bz5MUCwzDIA359e57SSq5CCkY0N
4B6Vulk7LktfwrDGNVI5BsC9qqsSwSKgRJeZ9wygIaehbHFHFhcBaMDKpiZlBHyZ
rsnn1FXCb5s8HKn5LsUgGvB24L7sGNZP2CX7dhHov+YhD+jozLW2p9W4959Bz2Ei
RmqDtmiXlnzqTpXbI+suyCsohKRg6Un0RC47+cpiVwHiXZAW+cn8eiNIjqbVgXLx
KPpdzvvtTn0PlC7SQZSYmdunr3Bf9b77AiC/ZidstK36dRILKz70A54=
-----END CERTIFICATE-----
```


### 3.5.2 Upload the Root CA Certificate File

For the demo, the `fs load` command is used to upload certificate files. Follow the steps below to upload a file into WISE for demo purposes:

Use the fs load command and specify the file name under which you want to save the uploaded file

```
$
$ fs load /root_ca.pem
load local file to /root_ca.pem
C
```

Choose the file you want to upload from YMODEM.



Use the `fs read` command along with the file name to read the content of the specific file.

```
$
$ fs read /root_ca.pem
read /root_ca.pem
size: 1801
-----BEGIN CERTIFICATE-----
MIIFBTCCAu2gAwIBAgIQS6hSk/eaL6JzBkuoBI110DANBgkqhkiG9w0BAQsFADBP
MQswCQYDVQQGEwJVUzEpMCcGALUEChMgSW50ZXJuZXQGU2VjdXJpdHkgUmVzZWYy
Y2ggR3JvdXAxFtATBgNVBAMTElTUKcgUm9vdCBYMTAeFw0yNDAzMTMwMDAwMDBa
Fw0yNzAzMTIyMzU5NTlaMDMxCzAJBgNVBAYTAlVTMRYYwFAYDVQQKEwlmZXQncyBF
bmNyeXB0MQwwCgYDVQQDEwNSMTAwggEiMA0GCSqGSIb3DQEBAQUAA4IBDwAwggEK
AoIBAQDPV+XmxFQS7bRH/sknWHZGUCiMHT6I3wWdlbUYKb3dtVq/+vbOo76vACFL
YlpaPAEvxVgD9on/jhFD68G14BQHlo9vH9fnuoE5CXVlt8KvGFs3Jijno/QHK20a
/6tYvJWuQP/pylfEtVt/eA0YYbwX5lTGU0mRzW4Y0YCF7qZlNrx06rxQTO8IfM4
FpOUurDTazgGzRYSespSdcitdrLCnF2YRVxvYXvGLE48ElKGAdlX5jgc3421H5KR
mudKHMxFqHJV8LDMowfs/acbZp4/SItxhHFYyTr6717yW0QrPHTnj7JHwQdqzZq3
DZb3EoEmUVQK7GH29/Xi8orIlQ2NAGMBAAGjgfgwgfUwDgYDVR0PAQH/BAQDAgGG
MB0GAlUdJQQWMBQGCCsGAQUFBwMCBggrBgEFBQcDATASBgNVHRMBAf8ECDAGAQH/
AgEAMBOGAlUdDgQWBBS7vMNHpeS8qcbDpHIMEI2iNeHI6DAfBgNVHSMEGDAwBR5
tFnme7bl5AFzgAiIyBpY9umbbjAyBggrBgEFBQcBAQQmMCQwIgYIKwYBBQUHMAKG
Fmh0dHA6Ly94MS5pLmxiLmNyLm9yZy8wEwYDVR0gBAwwCjAIBgZngQwBAgEwJwYD
VR0fBCAwHjAcoBqgGIYWAHR0cDovL3gxLmMubGVuY3Iub3JnLzANBgkqhkiG9w0B
AQsFAAOCAgEAKrHnQTfreZ2B5s3iJeE6IOmQRJWjgVzPwl39vaBwlbGwKCIL0vIo
zwznloZDjCQiHcFCKtEjr59L9MhwTyAWsVrdAfYf+B9haxQnsHKNY67u4s5Lzzfd
u6PUzeetUK29v+PsPmI2cJkxp+iN3epi4hKu9ZzUPSwMqtCceb7qPVxEbpYxYlp9
ln5PJKBLBX9eb9LU6l8zSxPWV7bK3lG4XaMJgnT9x3ies7msFtpKK5bDtotij/10
GaKeA97pb5uwD9KgWvaFXMIET8jVTjLEvwrDvCn294GPDF08U8lAkIv7tghluaQh
lQnlE4SEN4LOECj8dsIGJXpGuk3aU3KkZj9icKy+aUgA+2cP2luh6NcDIS3XyfaZ
QjmdQ993ChII8SXWupQZVBiIpcW04Rq2k3lr7Bz5MUCwzDIA359e57SSq5CCkY0N
4B6Vulk7LktfwrDGNVI5BsC9qgxSwSKgrJeZ9wygIaehbHFHFhcBaMDKpiZlBHyZ
rsnnlFXCb5s8HKn5LsUgGvB24L7sGNZP2CX7dhHov+YhD+jozLW2p9W4959Bz2Ei
RmqDtmiXLnzqTpXbI+suyCsohKRg6Un0RC47+cpiVwHiXZAW+cn8eiNIjqbVgXLx
KPpdzvvtTnOPlC7SQZSYmdunr3Bf9b77AiC/ZidstK36dRILKz7OA54=
-----END CERTIFICATE-----
```

### 3.5.3 Time Synchronization for HTTPS

For HTTPS authentication verification, the device's time must be synchronized. The SCM1612 SDK supports STNP for time synchronization.

- If the time is not synchronized



```
$ httpc secure url
$ I (6556543) HTTP_CLIENT: HTTP client Start
E (6557199) esp-tls-mbedtls: mbedtls_ssl_handshake returned -0x2700
I (6557200) esp-tls-mbedtls: Failed to verify peer certificate!
E (6557201) esp-tls: Failed to open new connection
E (6557201) transport_base: Failed to open a new connection
E (6557204) HTTP_CLIENT: Connection failed, sock < 0
E (6557208) HTTP_CLIENT: Error perform http request 0x 7002
E (6557214) HTTP_CLIENT: Last esp error code : 0x801a
E (6557219) HTTP_CLIENT: Last mbedtls failure: 0x2700
I (6557226) HTTP_CLIENT: HTTP client done
```

- Time synchronized

```
$ sntp setserver pool.ntp.org
host name [pool.ntp.org]
$ sntp init
$ sntp time
UTC Time : 2024-09-23 01:33:50
$
```

- After time synchronized, HTTPS request.  
httpc secure url /root\_ca.pem

```
$ httpc secure url /root_ca.pem
$ I (5023019) HTTP_CLIENT: HTTP client Start
I (5024824) HTTP_CLIENT: HTTPS Status = 200, content_length = 0x20f1
I (5024825) HTTP_CLIENT: HTTP client done
```

httpc secure hostname /root\_ca.pem

```
$ httpc secure hostname /root_ca.pem
$ I (5043473) HTTP_CLIENT: HTTP client Start
I (5045210) HTTP_CLIENT: HTTPS Status = 200, content_length = 0x20f1
I (5045211) HTTP_CLIENT: HTTP client done
```