


# 24V LINEAR LED LIGHT SOURCE

## MILES ECO

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE				
							2300	2700	3200	4100	5500
<b>030</b>	60	4.8	360	83	5.0m	100mm		●	●	●	
<b>060</b>	120	9.6	680	83	5.0m	50mm		●	●	●	
<b>095</b>	60	14.4	1080	83	5.0m	100mm		●	●	●	
<b>120</b>	240	19.2	1420	83	5.0m	25mm		●	●	●	



## MILES PRO-LP

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE				
							2300	2700	3000	4000	5500
<b>065</b>	71	6	650	83	8.5m	84mm	●	●	●	●	●
<b>085</b>	100	8.3	850	83	7.5m	60mm	●	●	●	●	●
<b>105</b>	200	9.5	1050	83	6.0m	30mm	●	●	●	●	●



## MILES PRO-HP

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE					
							2300	2700	3000	3500	4000	5500
100	40	10.6	1080	85	6.0m	150mm		●	●	●	●	
170	66	17.9	1800	85	5.0m	90mm		●	●	●	●	
190	40	19.3	1920	85	4.5m	150mm		●	●	●	●	●



## MILES PRO-PLUS

Single bin only, MacAdam colour consistency, LED pitch in 8mm

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE						
							2200	2500	2700	3000	3500	4000	5500
<b>107</b>	117	8	1043*	85	7.5m	60mm	●	●	●	●	●	●	●
<b>325</b>	117	26	3246*	85	3.5m	60mm	●	●	●	●	●	●	●

\* Lumen output based on 3000K, for other output information, please consult Senso or refer to separate LED specification document.



104

325

## MILES CONTROLLED WHITE

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE
							2000-4000
CT1	200	16	1477	85	3.24m	60mm	●



CT1

## MILES PRO-CRI95

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH	COLOUR TEMPERATURE				
							2300	2700	3000	4000	5500
<b>150</b>	66	17.9	1533	95	5.0m	90mm		●	●	●	



150

## MILES RGB

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH
<b>RGB</b>	60	14.4	670		5.0m	100mm



RGB

## MILES RGB+W

STYLE	LED/M	WATT/M	LUMENS/M	CRI	MAX. LENGTH	CUT LENGTH
<b>RGB+W</b>	266	22.25	1193		3.25m	90mm



RGB+W