

# PROFILE SABRE



The Sabre recessed mounting low profile is perfectly suited for installation in furniture and cabinets.

### Profile

Extruded aluminium construction Anodized finish Available in custom length  $L \le [8'] (2,44 \text{ m})$ Easy wiring: profiles sections connect directly to each other via connectors (or using a connectors equipped jumper wire if necessary) Caps included





# HOW TO ORDER SABRE?

### Please pick your profile e.g. 555-615-2.00 555 - 615 part no. LENGTH 555 profile **615** Sabre Please pick your lens: e.g. 555-502-2.00 555 part no. LENGTH MODEL LENS 555 profile 500 frosted 502 clear Please pick your LED 551 part no. e.g. 551-580-030-40-2.00 COLOUR TEMPERATURE LENGTH LED CRI STYLE 2700 K 90 **580** < 85 ECO 030 360 70 3200 K 680






## For your reference

### **LED Pixelation**

in profile with frosted lens



# 24V LINEAR LED LIGHT SOURCE

| STYLE | LED/M   | WATT/M    | LUMENS/M      | CRI  | MAX.   | MAX. CUT |      | COLO | OUR TEMPER | RATURE |      |
|-------|---------|-----------|---------------|------|--------|----------|------|------|------------|--------|------|
| STILL | LLD/IVI | WAI I/IVI | LOIVILINO/IVI | Citi | LENGTH | LENGTH   | 2300 | 2700 | 3200       | 4100   | 5500 |
| 030   | 60      | 4.8       | 360           | 83   | 5.0m   | 100mm    |      | •    | •          | •      |      |
| 060   | 120     | 9.6       | 680           | 83   | 5.0m   | 50mm     |      | •    | •          | •      |      |
| 095   | 60      | 14.4      | 1080          | 83   | 5.0m   | 100mm    |      | •    | •          | •      |      |



| STYLE | LED/M   | WATT/M     | LUMENS/M      | CRI  | MAX.   | CUT    |      | COLOUR TEMPERATURE |      |      |      |
|-------|---------|------------|---------------|------|--------|--------|------|--------------------|------|------|------|
| STILL | LLD/IVI | VVAI 1/IVI | LOIVILINO/IVI | CITI | LENGTH | LENGTH | 2300 | 2700               | 3000 | 4000 | 5500 |
| 065   | 71      | 6          | 650           | 83   | 8.5m   | 84mm   | •    | •                  | •    | •    | •    |
| 085   | 100     | 8.3        | 850           | 83   | 7.5m   | 60mm   | •    | •                  | •    | •    | •    |
| 105   | 200     | 9.5        | 1050          | 83   | 6.0m   | 30mm   | •    | •                  | •    | •    | •    |



| STYLE | LED/M   | WATT/M    | LUMENS/M     | CRI | MAX.   | CUT    | MAX. CUT |      | COLO | OUR TEMPER | RATURE |  |
|-------|---------|-----------|--------------|-----|--------|--------|----------|------|------|------------|--------|--|
| SITLE | LED/IVI | WAI I/IVI | LUIVIENS/IVI | Chi | LENGTH | LENGTH | 2300     | 2700 | 3000 | 4000       | 5500   |  |
| 100   | 40      | 10.6      | 1080         | 85  | 6.0m   | 150mm  |          | •    | 0    | •          |        |  |



| RGB   | 60    | 14.4   | 670      |     | 5.0m           | 100mm         |
|-------|-------|--------|----------|-----|----------------|---------------|
| STYLE | LED/M | WATT/M | LUMENS/M | CRI | MAX.<br>LENGTH | CUT<br>LENGTH |



RGB





# Terminal Cap Used to end a section of profile PVC construction Installed on one end of profile section End Cap With Connector Hole Allows the installation of connectors PVC construction Allows connections between sections of profiles that Lead Cable for Driver cannot be linked directly Comes preinstalled to the driver box Connector preinstalled: ready to plug to profiles 22mm Easily clipped in profile Comes precut to match profile length 13mm /0.5" 9mm clear 95% transparent /0.35



# Mounting Clip part number 555-615-20


- Steel construction
- Profile is mounted flush to surface
- Not visible once installed






frosted 65% transparent

| 902 Standard series | Туре |     | part number |
|---------------------|------|-----|-------------|
| non-dimmable        | 24V  | 10W | 902-24010   |
|                     | 24V  | 25W | 902-24025   |
|                     | 24V  | 60W | 902-24060   |
|                     | 24V  | 80W | 902-24080   |
|                     | 24V  | 96W | 902-24096   |





| part number | Туре |     | 908 series |
|-------------|------|-----|------------|
| 908-24040   | 40W  | 24V | dimmable   |
| 908-24060   | 60W  | 24V |            |
| 908-24100   | 96W  | 24V |            |

