

pendant light fixture

SPECIFICATIONS

HERA

GENERAL

- The hera is a timeless classic, with modern efficiency. This LED pendant radiates warmth, and provides even light distribution from the LED power source.

LED

- consistent colour, uniform beam
- LED lifetime of 50,000h
- infrared and UV free beam
- different CRI, colour T° and lumen output available

ELECTRICAL

- standard 120 V driver included, options available:
 - standard dimming driver (using ELV dimmers)
- power consumption:

10"/200mm	9W
12"/300mm	15W
16"/400mm	20W
20"/500mm	22W

CONSTRUCTION

- acrylic shade
- height adjustable aircraft cable suspension system
- aircraft cable and electric wire included: 2m [78"]



INSTALLATION

- canopy included, fits on standard junction box

WEIGHT

2.7 kg [6 lbs]

DIMENSION



Please specify:

- | | |
|------------------------|--|
| MODEL | <input type="checkbox"/> 710 – 10", 700lm |
| | <input type="checkbox"/> 712 – 12", 1000lm |
| | <input type="checkbox"/> 716 – 16", 1300lm |
| | <input type="checkbox"/> 720 – 20", 1500lm |
| COLOUR RENDERING INDEX | <input type="checkbox"/> 580 – 83+ |
| COLOUR TEMPERATURE | <input type="checkbox"/> 90 – 2700K |
| | <input type="checkbox"/> 70 – 3000K |
| | <input type="checkbox"/> 60 – 3500K |
| | <input type="checkbox"/> 40 – 4000K |
| CANOPY FINISH | <input type="checkbox"/> 01 – white |
| CABLE COLOUR | <input type="checkbox"/> 00 – clear |
| | <input type="checkbox"/> 33 – red |
| DRIVER | <input type="checkbox"/> STD – non-dimmable |
| | <input type="checkbox"/> DIM – dimmable |
| | <input type="checkbox"/> LCS – 0-10V control |
| VOLTAGE | <input type="checkbox"/> 120 – 120V |
| | <input type="checkbox"/> 277 – 277V |

QUANTITY	PROJECT
NOTE	

