

LETO 11s

LETO LED PURE | EFFICIENT | PERENNIAL

SENSO
SPEC SHEET

SURFACE MOUNT



Consult this chart to confirm the availability of the desired combination before specifying below.

Colour Rendering Index (CRI)	STD/V CRI 83+				ARTIST/V/B CRI 98+		
Luminous Flux (lm)	700	1000	1300	2000	700	1000	1300
Consumption (W)	6.5	9.5	14	23	9	13	19
Colour T°	2700 K	•	•	•	•	•	•
	3000 K	•	•	•	•	•	•
	3500 K	•	•	•	•	•	•
	4000 K	•	•	•	•	•	•
ELV dimming DIM	•	•	•	•	•	•	•
0-10 V dimming LCS/ELDO	•	•	•	•	•	•	•
STD	•	•	•	•	•	•	•

• = available

▲ = XTM Beauty

surface mount downlight fixture

SPECIFICATIONS

LETO 11s

LED

- consistent colour, uniform beam
- LED lifetime of 50,000h
- infrared and UV free beam
- different CRI, colour T° and lumen output available, please refer to the chart

ELECTRICAL

- standard 120 V driver included, options available:
 - standard dimming driver (using ELV dimmers)
 - 0-10V dimmable driver (down to ~1%)
 - ELDO driver (0-10V dimming, down to ~0.1%)

FINISH

- satin power coat finish

CONSTRUCTION

- aluminium construction



INSTALLATION

- fits on standard junction box

WEIGHT

3.2 kg [7 lbs]

DIMENSION



Please specify:

- MODEL** ☐ **696** – LETO 11s
- COLOUR RENDERING INDEX** ☐ **581** – 83+
☐ **781** – 98+
☐ **781B** – Beauty (2700K only)
☐ **881** – vibrant (3000K only)
☐ **981** – vibrant/artist (3000K only)
- BEAM ANGLE** ☐ **610** – 18°
☐ **611** – 30°
☐ **612** – 45°
☐ **613** – 60°
- COLOUR TEMPERATURE** ☐ **90** – 2700K
☐ **70** – 3000K
☐ **60** – 3500K
☐ **40** – 4000K
- FINISH** ☐ **01** – white
☐ **02** – black
☐ **08** – silver
☐ **XX** – custom
- LUMEN** ☐ **07** – 700
☐ **10** – 1000
☐ **13** – 1300
☐ **20** – 2000
- DRIVER** ☐ **STD** – not dimmable
☐ **DIM** – dimmable
☐ **LCS** – 0-10V control
☐ **ELDO-LCS*** – 0-10V control
☐ **ELDO-DALI*** – addressable control

*Remote driver only

QUANTITY	PROJECT
NOTE	



SENSO