


# LETO 20

LETO LED PURE | EFFICIENT | PERENNIAL

SENSO  
SPEC SHEET

SURFACE MOUNT



Consult this chart to confirm the availability of the desired combination before specifying below.

Colour Rendering Index (CRI)	STD/V CRI 83+				ARTIST/V/B CRI 98+		
Luminous Flux (lm)	700	1000	1300	2000	700	1000	1300
Consumption (W)	6.5	9.5	14	23	9	13	19
Colour T°	2700 K	•	•	•	•	•	•
	3000 K	•	•	•	•	•	•
	3500 K	•	•	•	•	•	•
	4000 K	•	•	•	•	•	•
ELV dimming DIM	•	•	•	•	•	•	•
0-10 V dimming LCS/ELDO STD	•	•	•	•	•	•	•

• = available

▲ = XTM Beauty

## surface mount square downlight fixture

### SPECIFICATIONS

LETO 20

#### LED

- consistent colour, uniform beam
- LED lifetime of 50,000h
- infrared and UV free beam
- different CRI, colour T° and lumen output available, please refer to the chart

#### ELECTRICAL

- standard 120 V driver included, options available:
  - standard dimming driver (using ELV dimmers)
  - 0-10V dimmable driver (down to ~1%)
  - ELDO driver (0-10V dimming, down to ~0.1%)

#### FINISH

- satin power coat finish

#### CONSTRUCTION

- aluminium construction



#### INSTALLATION

- fits on standard junction box

#### WEIGHT

3.2 kg [7 lbs]

#### DIMENSION



#### Please specify:

- MODEL** ☐ **699** – LETO 20
- COLOUR RENDERING INDEX** ☐ **581** – 83+  
☐ **781** – 98+  
☐ **781B** – Beauty (2700K only)  
☐ **881** – vibrant (3000K only)  
☐ **981** – vibrant/artist (3000K only)
- BEAM ANGLE** ☐ **610** – 18°  
☐ **611** – 30°  
☐ **612** – 45°  
☐ **613** – 60°
- COLOUR TEMPERATURE** ☐ **90** – 2700K  
☐ **70** – 3000K  
☐ **60** – 3500K  
☐ **40** – 4000K
- FINISH** ☐ **01** – white  
☐ **02** – black  
☐ **08** – silver  
☐ **XX** – custom
- LUMEN** ☐ **07** – 700  
☐ **10** – 1000  
☐ **13** – 1300  
☐ **20** – 2000
- DRIVER** ☐ **STD** – not dimmable  
☐ **DIM** – dimmable  
☐ **LCS** – 0-10V control  
☐ **ELDO-LCS\*** – 0-10V control  
☐ **ELDO-DALI\*** – addressable control

\*Remote driver only

QUANTITY	PROJECT
NOTE	



SENSO